

NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD
WETLAND RESTORATION

(Ac.)

CODE 657

DEFINITION

The return of a wetland and its functions to a close approximation of its original condition as it existed prior to disturbance on a former or degraded wetland site.

PURPOSE

To restore wetland function, value, habitat, diversity, and capacity to a close approximation of the pre-disturbance conditions by restoring:

- Conditions conducive to hydric soil maintenance.
- Wetland hydrology (dominant water source, hydroperiod, and hydrodynamics).
- Native hydrophytic vegetation (including the removal of undesired species, and/or seeding or planting of desired species).
- Original fish and wildlife habitats.

CONDITIONS WHERE PRACTICE APPLIES

This practice applies only to natural wetland sites with hydric soils which have been subject to the degradation of hydrology, vegetation, or soils.

This practice is applicable only where the natural hydrologic conditions can be approximated by actions such as modifying drainage, restoring stream/floodplain connectivity, removing diversions, dikes, and levees, and/or by using a natural or artificial water source to provide conditions similar to the original, natural conditions.

This practice does not apply to:

- The treatment of point and non-point sources of water pollution (Constructed

Wetland - 656);

- The rehabilitation of a degraded wetland, the reestablishment of a former wetland, or the modification of an existing wetland, where specific wetland functions are augmented beyond the original natural conditions; possibly at the expense of other functions. (Wetland Enhancement - 659);
- The creation of a wetland on a site location which was historically non-wetland (Wetland Creation - 658).
- The management of fish and wildlife habitat on wetlands restored under this standard. (Wetland Wildlife Management (644)

CRITERIA

General Criteria Applicable to All Purposes

The purpose, goals, and objectives of the restoration shall be clearly defined in the restoration plan, including soils, hydrology, vegetation, and fish and wildlife habitat criteria that are to be met and are appropriate for the site and the project objectives.

These planning steps shall be done with the use of the current Iowa NRCS functional assessment models. The objectives will be determined by an analysis of current and historic site functions. They will be based on those functions which can reasonably be supported by current site constraints. Data from historic and recent aerial photography and/or other remotely sensed data, soil maps, topographic maps, stream gage data, intact reference wetlands, and historical records shall be gathered to document historic conditions.

The current soils, hydrology and vegetative

Conservation practice standards are reviewed periodically and updated if needed. To obtain the current version of this standard, contact your Natural Resources Conservation Service [State Office](#) or visit the [Field Office Technical Guide](#).

NRCS, Iowa
July 2011

conditions existing on the site, the adjacent landscape, and the contributing watershed shall be documented in the planning process.

The nutrient and pesticide tolerance of the plant and animal species likely to occur shall be evaluated where known nutrient and pesticide contamination exists. Sites suspected of containing hazardous material shall be tested to identify appropriate remedial measures. If remedial measures are not possible or practicable, the practice shall not be planned.

Water rights, if applicable, shall be assured prior to restoration.

Upon completion, the site shall meet soil, hydrology, vegetation, and habitat conditions of the wetland that previously existed on the site to the extent practicable.

Where offsite hydrologic alterations or the presence of invasive species impact the site, the design shall compensate for these impacts to the extent practicable.

Invasive species, federal/state listed noxious plant species, and nuisance species (e.g., those whose presence or overpopulation jeopardize the practice) shall be controlled on the site as necessary to restore wetland functions. The establishment and/or use of non-native plant species shall be discouraged.

Establish vegetative buffers around the wetlands to reduce the movement of sediment and soluble and sediment-attached substances carried by runoff. Use Filter Strip (393) to determine the minimum width of the vegetative buffer.

Dikes and excavated areas shall be shaped in a manner that is compatible with the existing landscape. For excavated areas leave ground surface as irregular as possible.

Criteria for Hydric Soil Restoration

Restoration sites will be located on soils that are hydric.

If the hydric soil is covered by fill, sediment, spoil, or other depositional material, the material covering the hydric soil shall be removed to the extent practicable to restore the original soil functions.

Soil hydrodynamic and bio-geochemical properties such as permeability, porosity, pH, or soil organic carbon levels shall be restored to the extent needed to restore hydric soil functions.

Criteria for Hydrology Restoration

The hydroperiod, hydrodynamics, and dominant water source of the restored site shall approximate the conditions that existed before alteration. The restoration plan shall document the adequacy of available water sources based on groundwater investigation, stream gage data, water budgeting, or other appropriate means.

The work associated with the wetland shall not adversely affect adjacent properties or other water users, the capacity of drainage systems on other properties, and shall not back surface water onto an adjoining property or restrict the capacity of adjacent subsurface drainage systems unless agreed to by signed written letter, easement or permit.

Any existing surface or subsurface drainage systems that would affect or be affected by the wetland shall be located and measures taken to determine the extent of those systems. Existing drainage systems will be utilized, removed, or modified as needed to achieve the restoration and ensure drainage rights. Refer to NEH Part 650 (EFH) Chapter 13 and current Iowa NRCS guidance for information related to surface and subsurface drain plugging.

Water control structures shall only be used to recreate natural hydrologic patterns or to allow management and maintenance of the desired community and shall meet the requirements of Structure for Water Control (587).

Non-perforated conduits shall be used downstream of a water control structure for a minimum 50 feet and under any dike. The connections of the water control structure and non-perforated conduit will be watertight for the pressure developed at the maximum pool level.

Timing and level setting of water control structures, if needed, will be based on the actions needed to maintain a close approximation of the original, natural hydrologic conditions.

If base flow - which may include seepage, subsurface drainage or spring flow - exists, a trickle tube or water control structure shall be provided. Base flow is designed as the greater of 1) the quick return flow [see NEH, Part 650, Chapter 2] or 2) the capacity of the intercepted subsurface drainage system. A trickle tube shall have a minimum diameter of 4 inches.

The original natural water supply should be used to reestablish the site's hydrology to approximate the hydrologic conditions of the wetland type. If this is not possible, an alternate natural or artificial water supply can be used; however, these sources shall not be diverted from other wetland resources. If the alternate water source requires energy inputs, these shall be estimated and documented in the restoration plan.

To the extent practicable, reestablish macrotopography (excavations/fills causing an elevation change over 6 inches) and/or microtopography (excavations/fills causing an elevation change less than 6 inches). Use reference sites within the local area to determine desired topographic relief. The location, size, and geometry of earthen structures, if needed, shall match that of the original macrotopographic features to the extent practicable. Refer to NEH, Part 650, Chapter 13, and Biology Technical Note 24 for guidance.

Macrotopographic features, including ditch plugs installed in lieu of re-filling surface drainage ditches, shall meet the requirements of other practice standards to which they may apply due to purpose, size, water storage capacity, hazard class, or other parameters. If no other practice standard applies, they shall meet the requirements for Dike (356) unless there is no potential for damage to the feature or other areas on or off site due to erosion, breaching, or overtopping. Dikes with an effective height greater than 10 feet shall be designed using the criteria for Pond (378) or Grade Stabilization Structure (410).

Flow over the top of the ditch plug may be used in limited cases. All of the following conditions must be met for flow over the ditch plug to be allowed:

- Drainage area < 50 acres
- No trickle flow

- Fill height < 5 feet, and
- Stable grade downstream

In these cases, use a minimum top width of 30 feet, 3:1 upstream slopes, and 10:1 or flatter downstream slopes.

In addition to the Dike (356) criteria, dikes located on a floodplain where overtopping of the dike by flow from the floodway into the wetland is likely may have a vegetated spillway area on level natural ground, in excavation, or on compacted fill. Vegetated spillways shall be at least 100 feet wide and have a crest length of at least 25 feet.

Compacted fill spillways shall meet the following criteria:

- Height of spillway crest to downstream toe is 2 feet or less
- Design flow depth of 0.5 feet or less
- Inlet and outlet slopes shall be 5:1 or flatter
- Mulching of spillway is required

The dike for a distance of 50 feet on each side of the principal spillway or water control structure shall have an additional 1 foot of overfill added to the constructed height to protect the control structure from damage by the overflow water.

The vegetated spillway shall be located in a position that minimizes the likelihood for flood flows from the stream system to damage the dike, water control structure, and vegetated spillway.

Excavations from within the wetland shall remove sediment to approximate the original topography or establish a water level that will compensate for the sediment that remains.

Water control structures that may impede the movement of target aquatic species or species of concern shall meet the criteria in Fish Passage, Code 396. Preclude fish access to the wetland unless fish habitat is an objective.

Wetland restoration sites that exhibit soil oxidation and/or subsidence, resulting in a lower surface elevation compared to pre-disturbance, shall take into account the appropriate hydrologic regime needed to support the original wetland functions.

Criteria for Vegetative Restoration

Hydrophytic vegetation restoration shall be of species typical for the wetland type(s) being established and the varying hydrologic regimes and soil types within the wetland. Preference shall be given to native wetland plants with localized genetic material.

Where natural colonization of acceptable species can realistically be expected to occur within 5 years, sites may be left to revegetate naturally. If not, the appropriate species will be established by seeding or planting. To decide if natural revegetation is appropriate, refer to ECS 190-15, Wetland Restoration, Enhancement, Management, & Monitoring for natural regeneration decision keys.

Adequate substrate material and site preparation necessary for proper establishment of the selected plant species shall be included in the plan.

Where topsoil will be used as a seedbank, topsoil shall not be stockpiled prior to redistribution during the summer. For other periods, topsoil shall only be stockpiled in a manner that limits deterioration of viable plant parts and seeds. Refer to ECS 190-15, Wetland Restoration, Enhancement, Management & Monitoring, for guidance.

When natural revegetation is used, deep tillage or other methods shall be used to expose the buried seedbank or bring the buried seedbank to the surface. If a site has not become dominated by the targeted species within 5 years, active forms of revegetation will be required.

Where planting and/or seeding is necessary, the minimum number of native species to be established shall be based on a reference wetland with the type of vegetative communities and species planned on the restoration site:

- Where the dominant vegetation will be herbaceous community types, a subset of the original vegetative community shall be established within 5 years, or a suitable precursor to the original community will be established within 5 years that creates conditions suitable for the establishment of the native community. Species richness shall be addressed in the planning of

herbaceous communities. Seeding rates shall be based upon the percentage of pure live seed and labeled with a current seed tag from a registered seed laboratory identifying the germination rate, purity analysis, and other seed statistics.

- Where the dominant vegetation will be forest or woodland community types, vegetation establishment will include a mix of woody species (trees and/or shrubs) adequate to establish the reference wetland community.
- Ensure that the approved seeding mixture does not include weed species and invasive species (e.g.: reed canarygrass).

Refer to Conservation Cover (327), Tree/Shrub Establishment (612), Restoration and Management of Declining Habitats (643), Wetland Wildlife Habitat Management (644), and NEH, Part 650, Chapter 13, and applicable Iowa Job Sheets and Technical Notes for vegetation establishment guidance.

If uplands are planned as part of a wetland creation, then native species shall be used for these areas as well. Refer to Conservation Cover (327) for herbaceous restorations, or Tree/Shrub Establishment (612) and Upland Wildlife Habitat Management (645) if trees and/or shrubs are desired.

CONSIDERATIONS

Soil Considerations

Consider making changes to physical soil properties, including:

- Increasing or decreasing saturated hydraulic conductivity by mechanical compaction or tillage, as appropriate.
- Incorporating soil amendments.
- The effect of construction equipment on soil density, infiltration, and structure.

Consider changes in soil bio-geochemical properties, including:

- Increasing soil organic carbon by incorporating compost.
- Increasing or decreasing soil pH with lime, gypsum, or other compounds

Hydrology Considerations

Natural drawdown through evapotranspiration is a natural and often desirable process rather than regulating water levels with water control structures. Drawdown of permanent storage is often necessary or desirable to manage wetlands.

Consider the general hydrologic effects of the restoration, including:

- Impacts on downstream stream hydrographs, volumes of surface runoff, and groundwater resources due to changes of water use and movement created by the restoration.

Consider the impacts of water level management, including:

- Increased predation due to concentrating aquatic organisms, including herptivores, in small pool areas during draw downs
- Increased predation of amphibians due to high water levels that can sustain predators.
- Decreased ability of aquatic organisms to move within the wetland and from the wetland area to adjacent habitats, including fish and amphibians as water levels are decreased.
- Increases in water temperature on-site, and in off-site receiving waters.
- Changes in the quantity and direction of movement of subsurface flows due to increases or decreases in water depth.
- The effect changes in hydrologic regime have on soil bio-geochemical properties, including: oxidation/reduction; maintenance of organic soils; and salinity increase or decrease on site and on adjacent areas.

Vegetation Considerations

Consider:

- The relative effects of planting density on fish and wildlife habitat versus production rates in woody plantings.

- The potential for vegetative buffers to increase function by trapping sediment, cycling nutrients, and removing pesticides.
- The selection of vegetation for the protection of structural measures that is appropriate for wetland function.
- The potential for invasive or noxious plant species to establish on bare soils after construction and before the planned plant community is established.
- The use of prescribed burning to restore wetland and adjacent upland plant communities.
- The manipulation of water levels or topography to control unwanted vegetation.

Fish and Wildlife Habitat Considerations

Consider:

- The addition of coarse woody debris on sites to be restored to woody plant communities for an initial carbon source and fish and wildlife cover.
- The potential to restore habitat capable of supporting fish and wildlife with the ability to control disease vectors such as mosquitoes.
- The potential to establish fish and wildlife corridors to link the site to adjacent landscapes, streams, and water bodies and to increase the sites colonization by native flora.
- The need to provide barriers to passage for unwanted or predatory species.

PLANS AND SPECIFICATIONS

Plans and specifications for this practice shall be prepared for each site. Plans and specifications shall be recorded using approved specifications sheets, job sheets, or other documentation. The plans and specifications for structural features will include, at a minimum, a plan view, quantities, and sufficient profiles and cross-sections to define the location, line, and grade for stakeout and checkout. Plans and specifications shall

be reviewed and approved by staff with appropriate job approval authority.

The following list of Construction Specifications is intended as a guide to selecting the appropriate specifications for each specific project. The list includes most, but may not contain all, of the specifications that are needed for a specific project:

IA-1	Site Preparation
IA-5	Pollution Control
IA-6	Seeding and Mulching for Protective Cover
IA-9	Drainage Tile Investigation and Removal
IA-11	Removal of Water
IA-21	Excavation
IA-23	Earthfill
IA-26	Topsoiling
IA-27	Diversions
IA-45	Plastic (PVC, PE) Pipe
IA-46	Tile Drains for Land Drainage
IA-51	Corrugated Metal Pipe
IA-52	Steel Pipe Conduits
IA-61	Loose Rock Riprap
IA-95	Geotextile

OPERATION AND MAINTENANCE

A separate Operation and Maintenance (O&M) Plan will be prepared for sites that have structural features. The plan will include specific actions for the normal and repetitive operation of installed structural items, especially water control structures, if included in the project. Refer to Iowa Biology Technical Note 20 for guidance in timing and level setting of water control structures required for establishment of desired hydrologic conditions or for management of vegetation.

The plan will also include the maintenance actions necessary to assure that constructed items are maintained for the life of the project. It will include the inspection schedule, a list of items to inspect, a checklist of potential damages to look for, recommended repairs, and procedures for documentation.

Management and monitoring activities needed to ensure the continued success of the wetland functions may be included in the above plan, or in a separate Management and Monitoring Plan. In addition to the monitoring schedule, this plan may include the following:

- The timing and methods for the use of fertilizers, pesticides, prescribed burning, or mechanical treatments.
- Circumstances when the use of biological control of undesirable plant species and pests (e.g. using predator or parasitic species) is appropriate, and the approved methods.
- Actions which specifically address any expected problems from invasive or noxious species.
- The circumstances which require the removal of accumulated sediment.
- Conditions which indicate the need to use haying or grazing as a management tool, including timing and methods.
- The timing and level setting of water control structures for the establishment and maintenance of vegetation, soil, and wildlife functions.

REFERENCES:

Baber, M. J., D. L. Childers, K. J. Babbitt, and D. H. Anderson. 2002. Controls on fish distribution and abundance in temporary wetlands. *Can. J. Fish. Aquat. Sci.* **59**: 1441–1450.

Executive order 13112, Invasive Species, February 3, 1999. *Federal Register*: Vol.64, No.25. Feb. 8, 1999.
http://frwebgate.access.gpo.gov/cgi-bin/getdoc.cgi?dbname=1999_register&docid=99-3184-filed.pdf

Galatowitsch, Susan, et al, 1994. *Restoring Prairie Wetlands: an ecological approach*. Iowa State University Press, Ames, IA. 246 pp.

Hall, C.D. and F.J. Cuthbert. 2000. Impact of a controlled wetland drawdown on Blanding's Turtles in Minnesota. *Chelonian Conservation Biology*. Vol. 3, No. 4, pp. 643-649
Hurt, G.W. and V.W. Carlisle, 2001.

Delineating Hydric Soils, in *Wetland Soils – Genesis, Hydrology, Landscapes and Classification*. Edited by J.L. Richardson and M.J. Vepraskas. CRC Press, Boca Raton, FL pp. 183 – 206.

- Kilgore, K.J. and J.A. Baker. 1996. Patterns of larval fish abundance in a bottomland hardwood wetland. *Wetlands* 16: 288-295.
- King, A.J., P. Humphries and P.S. Lake. 2003. Fish recruitment on floodplains: the roles of patterns of flooding and life history characteristics. *Canadian Journal of Fisheries and Aquatic Sciences* 60:773-786.
- Kingsbury, Bruce & Joanne Gibson, 2002. *Habitat Management Guidelines for Amphibians and Reptiles of the Midwest*. Partners in Amphibian & Reptile Conservation, Ft Wayne IN, 57 pp.
- Kwak, T.J. 1988. Lateral movement and use of floodplain habitat by fishes of the Kankakee River, Illinois. *Am. Midland Naturalist* 120(2): 241-249.
- M.J. Vepraskas and S. W. Sprecher editors, 1997. *Aquic Conditions and Hydric Soils: The Problem Soils*. Soil Science Society of America Special Publication Number 50. SSSA, Inc. Madison, WI.
- Maschhoff, Justin T & James H. Dooley, 2001. *Functional Requirements and Design Parameters for Restocking Coarse Woody Features in Restored Wetlands*, USDA-NRCS. Hydric Soil Technical Note 13, Deliberations of the National Technical Committee for Hydric Soils (NTCHS). ftp://ftp-fc.sc.egov.usda.gov/NSSC/Hydric_Soils/note13.pdf
- ASAE Meeting Presentation, Paper No: 012059.
- Pearsons, T. N., H. Li, and G. Lamberti. 1992. Influence of habitat complexity on resistance to flooding and resilience of stream fish assemblages. *Trans. Amer. Fish. Soc.* 121: 427-436.
- USDA, NRCS, 2003. *ECS 190-15 Wetland Restoration, Enhancement, Management & Monitoring*. 425 pp. <ftp://ftp-fc.sc.egov.usda.gov/WLI/wre&m.pdf>
- USDA, NRCS. *Wetland Restoration, Enhancement, or Creation, Engineering Field Handbook Chapter 13, Part 650*. 121 pp. <ftp://ftp-fc.sc.egov.usda.gov/WLI/wre&m.pdf>
- USDA, NRCS. 2002. *Field Indicators of Hydric Soils in the U.S., Version 6.0*. G.W. Hurt, P.M. Whited and R.F. Pringle (eds.). USDA, NRCS in cooperation with the National Technical Committee for Hydric Soils, Fort Worth, TX. ftp://ftp-fc.sc.egov.usda.gov/NSSC/Hydric_Soils/FieldIndicators_v6_0.pdf
- USDA-NRCS. 2000. *Indiana Biology Technical Note 1*. <http://www.nrcs.usda.gov/Programs/WRP/pdfs/In-final.pdf>