Practice: 558 - Roof Runoff Structure
Scenario: #1 - Gutters and downspouts

## **Scenario Description:**

A roof runoff structure, consisting of gutter(s), downspout(s) and splashguards. Used to keep roof clean water runoff uncontaminated and provide a stable outlet to ground surface. Facilitates waste management and protects environment by minimizing clean water additions to waste systems and addresses water quality concerns.

Associated practices include Waste Storage Facility (313), Composting Facility (317), Heavy Use Area Protection (561), Watering Facility (614), Underground Outlet (620), Diversion (362), and any relevant irrigation practices.

## **Before Situation:**

Applicable where: (1) a roof runoff management facility is included in an overall plan for an overall plan for a waste management system; (2) roof runoff needs to be diverted away from structures or contaminated areas; (3) there is a need to collect, control, and transport runoff from roofs to a stable outlet.

### **After Situation:**

Gutters, downspouts and splashguards servicing the portion of the building roof that would otherwise drain into a waste management system or create erosion. Roof line of 180 ln.ft. serviced with gutter, downspouts, and appurtances.

Scenario Feature Measure: Linear Length of Roof to be Guttered

Scenario Unit: Linear Feet Scenario Typical Size: 180

Scenario Cost: \$947.01 Scenario Cost/Unit: \$5.26

<b>Cost Details (by category</b>		Price				
Component Name	ID	Component Description		(\$/unit)	Quantity	Cost
Equipment/Installation						
Geotextile, woven	42	Woven Geotextile Fabric. Includes materials, equipment and labor	Square Yard	\$2.06	6	\$12.36
Labor						
General Labor	231	Labor performed using basic tools such as power tool, shovels, and other tools that do not require extensive training. Ex. pipe layer, herder, concrete placement, materials spreader, flagger, etc.	Hour	\$18.70	4	\$74.80
Materials						
Downspout, Aluminum, Small	1700	Aluminum downspout (3" to 5") in width with hangers. Materials only.	Foot	\$2.81	60	\$168.60
Gutter, Aluminum, Small	1689	Aluminum gutter (4" to 6") in width with hangers. Materials only.	Foot	\$2.58	180	\$464.40
Aggregate, Gravel, Graded	46	Gravel, includes materials, equipment and labor to transport and place. Includes washed and unwashed gravel.	Cubic yard	\$39.09	1	\$39.09
Mobilization						
Aggregate, Shipping, Cubic Yard-mile	2360	Mobilization of aggregate material beyond 20 miles of loca delivery from quarry to construction site. Cubic Yard-mile (Cubic Yard * miles of haul).	Cubic Yard-Mile	\$0.34	50	\$17.00
Mobilization, small equipment	1138	Equipment <70 HP but can't be transported by a pick-up truck or with typical weights between 3,500 to 14,000 pounds.	Each	\$170.76	1	\$170.76

Practice: 558 - Roof Runoff Structure

Scenario: #6 - Drip pad

# Scenario Description:

A roof runoff structure, consisting of a pad filled with rock located at the drip line of a building. Used to provide a stable outlet to ground surface. Environmental/design considerations, for example – snow loads, or a building without proper structural support needed for gutters dictate the use of a trench drain. Facilitates waste management and protects the environment by minimizing clean water additions to waste systems and addresses water quality concerns.

Associated practices include Waste Storage Facility (313), Composting Facility (317), Heavy Use Area Protection (561), Underground Outlet (620), and Diversion (362).

### **Before Situation:**

Applicable where: (1) a roof runoff management facility is included in an overall plan for an overall plan for a waste management system; (2) roof runoff needs to be diverted away from structures or contaminated areas; (3) there is a need to collect, control, and transport runoff from roofs to a stable outlet.

#### **After Situation:**

A 6" deep by 2' wide by 200 long deep rock filled splash pad, servicing the portion of the building roof that creates erosion and addresses a water quality resource concern.

Scenario Feature Measure: Linear length of roof to be drained

Scenario Unit: Linear Foot Scenario Typical Size: 200

Scenario Cost: \$762.57 Scenario Cost/Unit: \$3.81

Cost Details (by category): Price **Component Name Component Description** Unit **Quantity Cost** (\$/unit) Equipment/Installation \$1.83 7.4 Excavation, Common Earth, 48 Bulk excavation and side casting of common earth with Cubic \$13.54 side cast, small equipment hydraulic excavator with less than 1 CY capacity. Includes vard equipment and labor. Labor General Labor \$37.40 231 Labor performed using basic tools such as power tool, Hour \$18.70 2 shovels, and other tools that do not require extensive training. Ex. pipe layer, herder, concrete placement, materials spreader, flagger, etc. Materials Cubic 7.4 Aggregate, Gravel, Graded 46 Gravel, includes materials, equipment and labor to \$39.09 \$289.27 transport and place. Includes washed and unwashed vard gravel. Mobilization 2360 Mobilization of aggregate material beyond 20 miles of local Cubic 740 Aggregate, Shipping, Cubic \$0.34 \$251.60 Yard-mile delivery from quarry to construction site. Cubic Yard-mile Yard-Mile (Cubic Yard \* miles of haul). 1138 Equipment <70 HP but can't be transported by a pick-up Mobilization, small equipment Each \$170.76 1 \$170.76 truck or with typical weights between 3,500 to 14,000 pounds.