

# CONSTRUCTION SPECIFICATION

## PA 560 – ACCESS ROAD

### 1. SCOPE

The work shall consist of construction of the Access Road at the location, and to the dimensions and grades, shown on the drawings and as staked in the field.

### 2. SITE PREPARATION

All trees, stumps, roots, brush, weeds, and other objectionable material shall be removed from the work area and disposed of as directed.

All unsuitable material shall be removed from the roadbed area prior to placing fill or surfacing materials.

The roadbed shall be graded to the required elevations. All areas which require filling will be scarified prior to placement of fill. All fill shall be compacted according to the specified method with the appropriate equipment or to the specified density.

### 3. SURFACING

Aggregate for the subbase shall be clean and free from deleterious substances.

Where geotextile is used, the geotextile shall meet, at a minimum, the requirements of PennDOT Publication 408 Section 735 for Class 4 Type A non-woven geotextile or as otherwise stated in Section 6.

Gradation shall be such that a stable base will be formed. Placement of the surface course shall be in accordance with sound highway construction practices.

### 4. SEEDING

All disturbed areas shall be revegetated as designated on the drawings.

### 5. EROSION CONTROL

Construction operations shall be carried out in such a manner that erosion and air and water pollution will be minimized. State and local laws concerning pollution abatement must be followed.

### 6. ADDITIONAL CONDITIONS WHICH APPLY TO THIS PROJECT ARE: