



Natural Resources Conservation Service

CONSERVATION PRACTICE STANDARD

POND

CODE 378

(no)

DEFINITION

A pond is a water impoundment made by constructing an embankment, by excavating a dugout, or by a combination of both.

In this standard, NRCS defines ponds constructed by the first method as embankment ponds, and those constructed by the second method as excavated ponds. Ponds constructed by both the excavation and the embankment methods are classified as embankment ponds if the depth of water impounded against the embankment at the auxiliary spillway elevation is 3 feet or more above the lowest original ground along the centerline of the embankment.

PURPOSE

This practice is used to accomplish one or more of the following purposes—

- A pond stores water for livestock, fish and wildlife, recreation, fire control, erosion control, flow detention, and other uses such as improving water quality

CONDITIONS WHERE PRACTICE APPLIES

This practice applies to all excavated ponds. It also applies to embankment ponds that meet all of the criteria for low-hazard dams as listed below:

- The failure of the dam will not result in loss of life, damage to homes, commercial or industrial buildings, main highways, or railroads, or in interruption of the use or service of public utilities.
- The product of the storage times the effective height of the dam is less than 3,000 acre-feet². Storage is the capacity of the reservoir in acre-feet below the elevation of the crest of the lowest auxiliary spillway or the elevation of the top of the dam if there is no open channel auxiliary spillway. The effective height of the dam is the difference in elevation, in feet, between the lowest open channel auxiliary spillway crest and the lowest point in the original cross section taken on the centerline of the dam. If there is no open channel auxiliary spillway, use the lowest point on the top of the dam instead of the lowest open channel auxiliary spillway crest.
- The effective height of the dam is 35 feet or less.

Dams exceeding the listed limitations exceed the scope of this documents and shall NOT be considered under this standard. If a dam exceeding the listed limitations is required for a conservation practice, the hazard classification shall be defined per the National Engineering Manual (NEM), Part 520, Subpart C – Dams, and will meet or exceed the requirements of Technical Release No. 60, “Earth Dams and Reservoirs.”

CRITERIA

General Criteria Applicable to All Purposes

Design a minimum sediment storage capacity equal to the design life of the structure, or provide for periodic cleanout. Protect the drainage area above the pond to prevent sedimentation from adversely affecting the design life.

Design measures necessary to prevent serious injury or loss of life in accordance with requirements of NRCS National Engineering Manual (NEM), Part 503, Safety.

Conservation practices shall be designed on an individual basis to meet site conditions and functional requirements. They shall be part of an approved and overall engineering plan. Design and implementation of subsidiary components and/or structures shall meet all applicable NRCS conservation practice standards. The criteria for the design of any components not specifically addressed in NRCS practice standards or design guides shall be consistent with sound engineering principles and/or manufacturer recommendations.

Seed or sod the exposed surfaces of earthen embankments, earth spillways, borrow areas, and other areas disturbed during construction in accordance with the criteria in NRCS Conservation Practice Standard (CPS) Code 342, Critical Area Planting. When necessary to provide surface protection where climatic conditions preclude the use of seed or sod, use the criteria in CPS Code 484, Mulching, to install inorganic cover material such as gravel.

Cultural resources

Evaluate the existence of cultural resources in the project area and any project impacts on such resources. Provide conservation and stabilization of archeological, historic, structural, and traditional cultural properties when appropriate.

Site conditions

Select or modify the site to allow runoff from the design storm to safely pass through (1) a natural or constructed auxiliary spillway, (2) a combination of a principal spillway and an auxiliary spillway, or (3) a principal spillway.

Select a site that has an adequate supply of water for the intended purpose via surface runoff, groundwater, or a supplemental water source. Water quality must be suitable for its intended use.

Reservoir

Provide adequate storage volume to meet user demands for all intended purposes. Account for sedimentation, season of use, evaporation loss, and seepage loss when computing the storage volume.

Laws and Regulations

All Federal, State, Tribal, and local laws, rules, regulations, and requirements shall be addressed in the planning and design of this practice. Laws and regulations of particular concern include those involving water rights, water quality, land use, pollution control, property easements, wetlands, and endangered species.

The owner is responsible for securing necessary permits and water rights, complying with all laws and regulations, and meeting legal requirements applicable to the installation, operation, and maintenance of this practice and associated measures.

Fencing

If the area is used for livestock, the structures, earthfill, vegetated spillways, and other areas should be fenced as necessary to protect the structure. Near urban areas, fencing may be necessary to control access and exclude traffic that may damage the structure or to prevent serious injury or death to trespassers. Fencing shall comply with the guidelines in NRCS CPS 382, Fence.

Criteria Applicable to Embankment Ponds

Geological investigations

Use pits, trenches, borings, reviews of existing data or other suitable means of investigation to characterize materials within the embankment foundation, auxiliary spillway, and borrow areas. Classify soil materials using the Unified Soil Classification System (ASTM D2487).

The embankment foundation shall be thoroughly investigated to the required depth to determine:

1. *Depth to competent impervious layer;*
2. *Ability of the foundation to withstand load; and*
3. *Seepage potential through the abutments and foundation.*

The auxiliary spillway shall be investigated to determine:

1. *The suitability of the material as a borrow source;*
2. *The potential for the spillway to erode; and*
3. *The difficulty of excavation.*

The borrow areas shall be defined by at least three pits, trenches, or borings. Quantities of borrow volumes shall be computed based upon the site investigation.

Borrow operation shall not be permitted closer than 50 feet from the upstream toe of the embankment except where the cutoff trench extends into firm impervious material for its entire length.

Foundation cutoff

Design a cutoff of relatively impervious material under the dam and up the abutments as required for preventing seepage. Locate the cutoff at, or upstream from, the centerline of the dam. Extend the cutoff deep enough to intercept flow and connect with a relatively impervious layer. Combine seepage control with the cutoff as needed. Use a cutoff bottom width adequate to accommodate the equipment used for excavation, backfill, and compaction operations. Design cutoff side slopes no steeper than one horizontal to one vertical.

Seepage control

Include seepage control if (1) foundation cutoff does not intercept pervious layers, (2) seepage could create undesired wet areas, (3) embankment stability requires seepage control, or (4) special problems require drainage for a stable dam. Control seepage by (1) foundation, abutment, or embankment filters and drains; (2) reservoir blanketing; or (3) a combination of these measures.

Top width

Table 1 provides the minimum top widths for dams of various total heights. Total height is the vertical distance between the settled top of the dam and the lowest elevation at the downstream toe.

Design a minimum width of 16 feet for one-way traffic and 26 feet for two-way traffic for the top of dams used as public roads. Design guardrails or other safety measures where necessary and follow the requirements of the responsible road authority. For dams less than 20 feet in total height, maintenance considerations or construction equipment limitations may require increased top widths from the minimum shown in table 1.

Table 1. Minimum top width for dams.

Total height of dam (feet)	Top width (feet)
Less than 10	6
10–14.9	8
15–19.9	10
20–24.9	12

Total height of dam (<i>feet</i>)	Top width (<i>feet</i>)
25–34.9	14
35 or more	15

Side slopes

Design each side slope with a ratio of two horizontal to one vertical or flatter. Design the sum of the upstream- and downstream-side slopes with a ratio of five horizontal to one vertical or flatter. As required, design benches or flatten side slopes to assure stability of all slopes for all loading conditions.

Slope protection

Design special measures such as berms, rock riprap, sand-gravel, soil cement, or special vegetation as needed to protect the slopes of the dam from erosion. Use NRCS Engineering Technical Release TR-210-56, A Guide for Design and Layout of Vegetative Wave Protection for Earth Dam Embankments, and TR-210-69, Riprap for Slope Protection against Wave Action, as applicable.

Freeboard

Design a minimum of 1.0 feet of freeboard between design high-water-flow elevation in the auxiliary spillway and the top of the settled embankment. Design a minimum 2.0 feet of elevation difference between the crest of the auxiliary spillway and the top of the settled embankment when the dam has more than a 20-acre drainage area or more than 20 feet in effective height. Design a minimum of 1.0 feet of freeboard above the peak elevation of the routed design hydrograph to the top of the settled embankment, when the pond has no auxiliary spillway.

Settlement

Increase the height of the dam by the amount needed to ensure that the settled top elevation of the dam equals or exceeds the design top elevation. Design a minimum of 5 percent of the total height of the dam associated with each dam cross section, except where detailed soil testing and laboratory analyses or experience in the area shows that a lesser amount is adequate.

Principal spillway and pipe conduit through the embankment

Design a pipe conduit with needed appurtenances through the dam, except where rock, concrete, or other types of lined spillways are used, or where a vegetated or earth spillway can safely handle the rate and duration of base flow.

Design a minimum of 0.5-foot difference between the crest elevation of the auxiliary spillway and the crest elevation of the principal spillway when the dam has a drainage area of 20 acres or less. Design a minimum of 1.0-foot difference when the dam has a drainage area of over 20 acres.

Provide an antivortex device for a pipe conduit designed for pressure flow. Design the inlet and outlet to function for the full range of flow and hydraulic head anticipated.

Design adequate pipe conduit capacity to discharge long-duration, continuous, or frequent flows without causing flow through the auxiliary spillway. Design a principal spillway pipe with a minimum inside diameter of 4 inches. Design pipe with a minimum inside diameter of 1-1/4 inches for water supply pipes or for pipes used for any other purpose.

Design pipe conduits using ductile iron, welded steel, corrugated steel, corrugated aluminum, reinforced concrete (pre-cast or site-cast), or plastic. Do not use cast iron or unreinforced concrete pipe if the dam is 20 feet or greater in total height.

Design and install pipe conduits to withstand all external and internal loads without yielding, buckling, or cracking. Design rigid pipe for a positive projecting condition. Design flexible pipe conduits in accordance with the requirements of NRCS National Engineering Handbook (NEH), Part 636, Chapter 52, Structural Design of Flexible Conduits.

Design connections of flexible pipe to rigid pipe or other structures to accommodate differential movements and stress concentrations. Design and install all pipe conduits to be watertight using couplings, gaskets, caulking, water stops, or welding. Design joints to remain watertight under all internal and external loading including pipe elongation due to foundation settlement.

Design a concrete cradle or bedding for pipe conduits if needed to reduce or limit structural loading on pipe and improve support of the pipe.

Where a pipe conduit is to be installed:

1. *No valve shall be installed when the conduit serves the single purpose of carrying flow from a trickle tube riser. For secondary discharge systems, control valves shall be installed on the upstream end unless otherwise approved by the State Conservation Engineer.*
2. *When a pipe conduit is to be encased with concrete, the trench shall be excavated to the neat lines and grades so that the bottom and two sides become suitable forms for the concrete.*
3. *The installation of trickle tubes are allowed provided the tube is buried in the embankment side slopes at a shallow depth of 1.0 feet to protect the pipe. Usually trickle tubes are installed to convey water to a trough for livestock use.*
4. *The pipe conduit shall have a minimum slope of 0.5 foot per 100 feet (after foundation settlement) to provide positive drainage.*

Design outlet structures, such as cantilever pipe outlet sections and impact basins, to dissipate energy as needed.

Corrosion protection

Provide protective coatings for all steel pipe and couplings in areas that have traditionally experienced pipe corrosion or in embankments with saturated soil resistivity less than 4,000 Ohm-cm or soil pH less than 5. Protective coatings may include asphalt, polymer over galvanizing, aluminized coating, or coal tar enamel.

Ultraviolet protection

Use ultraviolet-resistant materials for all plastic pipe or provide coating or shielding to protect plastic pipe exposed to direct sunlight.

Cathodic protection

Provide cathodic protection for coated welded steel and galvanized corrugated metal pipe where soil and resistivity studies indicate that the pipe needs a protective coating and where the need and importance of the structure warrant additional protection and longevity. If the original design and installation did not include cathodic protection, consider establishing electrical continuity in the form of joint-bridging straps on pipes that have protective coatings. Add cathodic protection later if monitoring indicates the need.

Filter diaphragms

When the effective height of the dam is 15 feet or greater and the effective storage of the dam is 50 acre-ft. or more, provide filter diaphragms to control seepage on all pipes extending through the embankment with inverts below the peak elevation of the routed design hydrograph. Design filter diaphragms or alternative measures as needed to control seepage on pipes extending through all other embankments or for pipes with inverts above the peak elevation of the routed design hydrograph.

Design the filter diaphragm in accordance with the requirements of NEH, Part 628, Chapter 45, Filter Diaphragms. Locate the filter diaphragm immediately downstream of the cutoff trench, but downstream of the centerline of the dam if the foundation cutoff is upstream of the centerline or if there is no cutoff trench.

To improve filter diaphragm performance, provide a drain outlet for the filter diaphragm at the downstream toe of the embankment. Protect the outlet from surface erosion and animal intrusion.

Ensure filter diaphragm functions both as a filter for adjacent base soils and as a drain for seepage that it intercepts. Materials for the filter diaphragm shall meet the requirements of NEH Part 628, Chapter 45, Filter Diaphragms, Section 628.4503(d), Filter and Drain Gradation.

When using anti-seep collars in lieu of a filter diaphragm, ensure a watertight connection to the pipe. Limit the maximum spacing of the anti-seep collars to 14 times the minimum projection of the collar measured perpendicular to the pipe, or 25 feet, whichever is less. Locate anti-seep collars no closer than 10 feet apart. Use a collar material that is compatible with the pipe material.

When using anti-seep collars, design the collars to increase the seepage path along the pipe within the fill by at least 15 percent. *Use of anti-seep collars shall require approval by the State Conservation Engineer.*

Trash guard

Install a trash guard at the riser inlet to prevent clogging of the conduit, unless the watershed does not contain trash or debris that could clog the conduit.

Pool Drain

Provide a pipe with a suitable valve to drain the pool area if needed for proper pond management or if required by State law. The designer may use the principal spillway conduit as a pond drain if it is located where it can perform this function.

Auxiliary spillways

A dam must have an open channel auxiliary spillway, unless the principal spillway is large enough to pass the peak discharge from the routed design hydrograph and the trash that comes to it without overtopping the dam. The minimum criteria for acceptable use of a closed conduit principal spillway without an auxiliary spillway consist of a conduit with a cross-sectional area of 3 feet² or more, an inlet that will not clog, and an elbow designed to facilitate the passage of trash.

Design the minimum capacity of a natural or constructed auxiliary spillway to pass the peak flow expected from a total design storm of the frequency and duration shown in table 2, less any reduction creditable to the conduit discharge and detention storage.

Design the auxiliary spillway to safely pass the peak flow through the auxiliary spillway, or route the storm runoff through the reservoir. Start the routing either with the water surface at the elevation of the crest of the principal spillway or at the water surface after 10 days' drawdown, whichever is higher. Compute the 10-day drawdown from the crest of the auxiliary spillway or from the elevation attained from impounding the entire design storm, whichever is lower. Design the auxiliary spillway to pass the design flow at a safe velocity to a point downstream where the flow will not endanger the dam.

A constructed auxiliary spillway consists of an inlet channel, a control section, and an exit channel. Design the auxiliary spillway with a trapezoidal cross section. Locate the auxiliary spillway in undisturbed or compacted earth or in-situ rock. Design for stable side slopes for the material in which the spillway is to be constructed. Design a minimum bottom width of 10 feet for dams having an effective height of 20 feet or more.

Design a level inlet channel upstream from the control section for the distance needed to protect and maintain the crest elevation of the spillway. If necessary, curve the inlet channel upstream of the level section to fit existing topography. Design the exit channel grade in accordance with NEH Part 628, Chapter 50, Earth Spillway Design, or with equivalent procedures.

Structural auxiliary spillways

When used for principal spillways or auxiliary spillways, design chute spillways or drop spillways according to the principles set forth in NEH, Part 650, Engineering Field Handbook; and NEH, Section 5, Hydraulics; Section 11, Drop Spillways; and Section 14, Chute Spillways. Design a structural spillway with the minimum capacity required to pass the peak flow expected from a total design storm of the frequency

and duration shown in table 2, less any reduction creditable to the conduit discharge and detention storage.

Criteria for Excavated Ponds

Geological Investigations

Pits, trenches, borings, review of existing data or other suitable means of investigation shall be conducted to characterize materials within the excavation. Soil materials shall be classified using the Unified Soil Classification System (ASTM D2497).

The area to be excavated for the pond shall be investigated, thoroughly and to the depth of at least 2 feet below the anticipated lowest expected grade, to determine:

1. *The difficulty of excavation; and*
2. *Seepage loss potential through the pond.*

Clay or plastic pond liners should be used on excavated ponds where seepage losses are considered excessive.

Runoff

Design a minimum of 1.0 feet of freeboard above the peak elevation of the routed design hydrograph. Design a pipe and auxiliary spillway that will meet the capacity requirements of table 2. Consider runoff flow patterns when locating the excavated pond and placing the spoil.

Side slopes

Design stable side slopes in the excavated area no steeper than one horizontal to one vertical.

Watering Ramp

When wildlife or livestock need access to stored water, use the criteria in NRCS CPS Code 614, Watering Facility, to design a watering ramp.

Inlet protection

Protect the side slopes from erosion where surface water enters the pond in a natural or excavated channel.

Excavated material

Place the material excavated from the pond so that its weight does not endanger the stability of the pond side slopes and so that the soil will not wash back into the pond by rainfall.

Dispose of excavated material in one of the following ways:

- Uniformly spread to a height that does not exceed 3 feet, with the top graded to a continuous slope away from the pond.
- Uniformly place or shape reasonably well, with side slopes assuming a natural angle of repose. Place excavated material at a distance equal to the depth of the pond, but not less than 12 feet from the edge of the pond.
- Shape to a designed form that blends visually with the landscape.
- Provide for low embankment construction and leveling of surrounding landscape.
- Haul material offsite.

Table 2. Minimum auxiliary spillway capacity

Minimum design storm ²				
Drainage area (acre)	Effective height of dam ¹ (feet)	Detention storage (acre-feet)	Frequency (years)	Minimum duration (hours)
20 or less	20 or less	< than 50	10	24

20 or less	> than 20	< than 50	25	24
> than 20	-	< than 50	25	24
All others	-	-	50	24

¹ Defined under "Conditions where Practice Applies."

² Select rain distribution based on climatological region.

Additional Criteria for Providing Livestock Water

The required storage shall be calculated using 1.5 times the sum of the following:

1. *The specified minimum gallons per animal per day as stated in NRCS CPS 614, Watering Facility, for the estimated number of days.*
2. *The net evaporation loss for the design days of storage.*
3. *Seepage loss based on the best available data.*

Additional Criteria for Fish and Wildlife

Design the reservoir for the maximum amount of water in excess of three feet in depth. Management of ponds for fish production shall be in accordance with NRCS CPS 399, Fish Pond Management.

Additional Criteria for Recreation

The volume of water should be sufficient to exceed evaporation and seepage losses and maintain a desirable water level. The water must be free of pollution, especially where it is to be used for swimming.

Additional Criteria for Fire Control

Fire control shall be incorporated into the structure design by incorporating an underground piping system which connects the reservoir to a dry hydrant. Minimum water storage, location of intake pipe, etc., shall meet the requirement of NRCS CPS 432, Dry Hydrant. The pump shall be of sufficient capacity and hoses shall be of sufficient length to reach the structures to be protected.

Improving Water Quality

Water quality problems include sediment, fertilizers, pesticides, litter, oils, and solvents. A reduction of peak flows to a receiving stream or water body will slow water flow and thereby carry less suspended solids. Ponds designed for water quality improvement of downstream water bodies shall be designed so that the first flush of a storm event will be retained within the pond and later storm water flow will be the first flows released through the principal spillway. In addition, the pond will be designed with a permanent pool deep enough to hold water all year and with shallow areas (littoral zones) with dense vegetation. These practices will increase sedimentation of suspended solids, reduce re-suspension of sediments by wave action, remove floating debris from storm water, and aid in mosquito control.

Safety

The earth embankment pond structures are potentially hazardous and precautions must be taken to prevent serious injury or loss of life. Protective guardrails, warning signs, fences, or lifesaving equipment shall be added as needed.

Excavations over 4 feet shall comply with OSHA safety requirements.

If the area is used for livestock, the structures, earthfill, vegetated spillways, and other areas should be fenced as necessary to protect the structure. Near urban areas, fencing may be necessary to control access and exclude traffic that may damage the structure or to prevent serious injury or death to trespassers.

CONSIDERATIONS

Visual resource design

Carefully consider the visual design of ponds in areas of high public visibility and those associated with recreation. The shape and form of ponds, excavated material, and plantings are to relate visually to their surroundings and to their function.

Shape the embankment to blend with the natural topography. Shape the edge of the pond so that it is generally curvilinear rather than rectangular. Shape excavated material so that the final form is smooth, flowing, and fitting to the adjacent landscape rather than angular geometric mounds. If feasible, add islands to provide visual interest and to attract wildlife.

Fish and wildlife

Locate and construct ponds to minimize the impacts to existing fish and wildlife habitat.

When feasible, retain structures such as trees in the upper reaches of the pond and stumps in the pool area. Shape upper reaches of the pond to provide shallow areas and wetland habitat.

If operations include stocking fish, use CPS Code 399, Fishpond Management.

Vegetation

Stockpile topsoil for placement on disturbed areas to facilitate revegetation.

Consider selecting and placing vegetation to improve fish habitat, wildlife habitat and species diversity.

Water quantity

Consider effects upon components of the water budget, especially—

- Effects on volumes and rates of runoff, infiltration, evaporation, transpiration, deep percolation, and groundwater recharge.
- Variability of effects caused by seasonal or climatic changes.
- Effects on downstream flows and impacts to environment such as wetlands, aquifers, and social and economic impacts to downstream uses or users.
- *The potential for irrigation water management.*

Water quality

Consider the effects of—

- Erosion and the movement of sediment, pathogens, and soluble and sediment-attached substances that runoff carries.
- Short-term and construction-related effects of this practice on the quality of downstream watercourses.
- Water-level control on the temperatures of downstream water to prevent undesired effects on aquatic and wildlife communities.
- Wetlands and water-related wildlife habitats.
- Water levels on soil nutrient processes such as plant nitrogen use or denitrification.
- Soil water level control on the salinity of soils, soil water, or downstream water.
- Potential for earth moving to uncover or redistribute toxic materials.
- Livestock grazing adjacent to the pond. Consider fencing to keep livestock activities out of direct contact with the pond and dam.
- *The structure's ability to trap sediment and sediment-attached substances carried by runoff.*
- *The proposed structure on the movement of dissolved substances to ground water.*

- *The movement of dissolved substances below the root zone or to ground water.*
- *The structure on the temperature of downstream water that could cause undesirable effects on aquatic and wildlife communities.*

PLANS AND SPECIFICATIONS

Prepare plans and specifications that describe the requirements for applying the practice according to this standard. *Use Arizona drawing templates to the extent possible. These may be supplemented by additional drawings or specification notes on the drawings to provide full installation instructions.* As a minimum, include the following items:

- *Project location map, including section, township and range, North arrow, cooperator/owner acknowledgement and certification signature blocks, engineering job class (cover sheet). Include statements that the owner/cooperator are responsible for all permits, rights-of-way, easements and the contact, coordination and location determination of any existing utilities or clearances (buried utility disclaimer)*
- *A plan view of the layout of the pond and appurtenant features. Reference to a known or established benchmark or reference point with the location, description and elevation clearly shown. Tie-in with existing or other planned practices. Field surveys and notes, soil investigations or geologic soil boring locations and soil classifications, earthwork or material estimates/quantities (foundation or subgrade preparation and requirements)*
- *System overview and layout (i.e., alignment, stationing, topographical features, and reference to existing or proposed features or facilities; details of seepage control; requirements for diverting water or de-watering the site; soil or waste disposal, location and extent of borrow source or spoil area; vegetative requirements, construction/installation criteria, OSHA safety requirements, etc.*
- *Typical profiles and cross sections of the principal spillway, auxiliary spillway, dam, and appurtenant features as needed*
- *Structural drawings adequate to describe the construction requirements*
- *Requirements for vegetative establishment and/or mulching, as needed*
- *Safety features*
- *Site-specific construction and material requirements*
- *Use Arizona Construction and Material Specifications for each item of work and material, as applicable and available. Supplemental specifications (NEH 642 or other) may need to be incorporated to provide full material and installation instructions.*

OPERATION AND MAINTENANCE

Prepare an operation and maintenance plan for the operator.

As a minimum, include the following items in the operation and maintenance plan:

- *Periodic inspections (and after heavy rains) of all structures, earthen embankments, spillways, and other significant appurtenances*
- *Prompt repair or replacement of damaged components*
- *Prompt removal of sediment when it reaches predetermined storage elevations*
- *Periodic removal of trees, brush, and undesirable species*
- *Periodic inspection of safety components and immediate repair if necessary*
- *Maintenance of vegetative protection and immediate seeding of bare areas as needed*

REFERENCES

American Society for Testing and Materials. Standard Practice for Classification of Soils for Engineering Purposes (Unified Soil Classification System), ASTM D2487. West Conshohocken, PA.

USDA NRCS. Conservation Practice Standard 521A. Pond Sealing or Lining, Flexible Membrane. Washington, DC; amended Phoenix, AZ.

USDA NRCS. Conservation Practice Standard 521B. Pond Sealing or Lining, Soil Dispersant Treatment. Washington, DC; amended Phoenix, AZ.

USDA NRCS. Conservation Practice Standard 521C. Pond Sealing or Lining, Bentonite Treatment. Washington, DC; amended Phoenix, AZ.

USDA NRCS. Conservation Practice Standard 521D. Pond Sealing or Lining, Compacted Clay Treatment. Washington, DC; amended Phoenix, AZ.

USDA NRCS. Engineering Technical Releases, TR-210-56, A Guide for Design and Layout of Vegetative Wave Protection for Earth Dam Embankments. .

USDA NRCS. Engineering Technical Releases, TR-210-60, Earth Dams and Reservoirs. Washington, DC.

USDA NRCS. Engineering Technical Releases, TR-210-69, Riprap for Slope Protection against Wave Action. Washington, DC

USDA NRCS. National Engineering Handbook (NEH), Part 628, Dams. Washington, DC.

USDA NRCS. NEH, Part 633, Soil Engineering. Washington, DC.

USDA NRCS. NEH, Part 636, Structural Engineering. Washington, DC.

USDA NRCS. NEH, Part 650, Engineering Field Handbook. Washington, DC.

USDA NRCS. National Engineering Manual. Washington, DC.