



Natural Resources Conservation Service

CONSERVATION PRACTICE STANDARD

POND

CODE 378

(no)

DEFINITION

A pond is a water impoundment made by constructing an embankment, by excavating a dugout, or by a combination of both.

In this standard, NRCS defines ponds constructed by the first method as embankment ponds, and those constructed by the second method as excavated ponds. Ponds constructed by both the excavation and the embankment methods are classified as embankment ponds if the depth of water impounded against the embankment at the auxiliary spillway elevation is 3 feet or more above the lowest original ground along the centerline of the embankment.

PURPOSE

This practice is used to accomplish the following purpose—

- A pond stores water for livestock, fish and wildlife, recreation, fire control, erosion control, flow detention, and other uses such as improving water quality

CONDITIONS WHERE PRACTICE APPLIES

This practice applies to all excavated ponds. It also applies to embankment ponds that meet all of the criteria for low-hazard dams as listed below:

- The failure of the dam will not result in loss of life, damage to homes, commercial or industrial buildings, main highways, or railroads, or in interruption of the use or service of public utilities.
- The product of the storage times the effective height of the dam is less than 3,000 acre- feet². Storage is the capacity of the reservoir in acre-feet below the elevation of the crest of the lowest auxiliary spillway or the elevation of the top of the dam if there is no open channel auxiliary spillway. The effective height of the dam is the difference in elevation, in feet, between the lowest open channel auxiliary spillway crest and the lowest point in the original cross section taken on the centerline of the dam. If there is no open channel auxiliary spillway, use the lowest point on the top of the dam instead of the lowest open channel auxiliary spillway crest.
- The effective height of the dam is 35 feet or less.

This practice applies where the water resource, topography, soils, and geology are suitable for construction and maintenance of a water supply sufficient for the intended purpose. National Engineering Manual, Part AL 501 requires the use of form AL-ENG-27 or AL-ENG-27A and an operations and maintenance (O&M) plan on all earth fill ponds.

CRITERIA

General Criteria Applicable to All Purposes

Design a minimum sediment storage capacity equal to the design life of the structure, or provide for periodic cleanout. Protect the drainage area above the pond to prevent sedimentation from adversely affecting the design life.

Design measures necessary to prevent serious injury or loss of life in accordance with requirements of NRCS National Engineering Manual (NEM), Part 503, Safety.

Ponds located in flood plain areas shall meet the same requirements for flood plain blockage as those identified in the section **Criteria for Ponds Constructed Primarily for Aquaculture**.

Seed or sod the exposed surfaces of earthen embankments, earth spillways, borrow areas, and other areas disturbed during construction in accordance with the criteria in NRCS Conservation Practice Standard (CPS) Code 342, Critical Area Planting.

Cultural resources

Evaluate the existence of cultural resources in the project area and any project impacts on such resources. Provide conservation and stabilization of archeological, historic, structural, and traditional cultural properties when appropriate.

Site conditions

Site conditions shall be such that runoff from the design storm (Table 5) can be safely passed through:

1. natural or constructed auxiliary spillway,
2. combination of a principal spillway and an auxiliary spillway,
3. principal spillway designed to pass the auxiliary spillway design storm flow with a minimum 10-ft. wide auxiliary spillway, or
4. principal spillway designed to pass the 10-yr., 24-hr. storm for levee type ponds with embankments that exclude outside runoff.

Drainage area

The drainage area above the pond must be protected against erosion to the extent that expected normal sedimentation will not shorten the planned effective life of the structure.

The drainage area shall be large enough so that surface runoff, together with groundwater flow will maintain an adequate supply of water in the pond unless the owner supplements by pumping. The area must be free of sources of pollution or contamination so that the water will be suitable for its intended purpose.

Reservoir area

Provide adequate storage volume to meet user demands for all intended purposes. The topography and soils of the site shall permit storage of water at a depth and volume that insures a dependable supply, considering beneficial use, sedimentation, season of use, and evaporation and seepage losses. The pond supported by surface runoff shall have soils impervious enough to prevent excessive seepage losses or shall be of a type that sealing is practicable.

Criteria Applicable to Embankment Ponds

Definitions

The designed height of the dam is defined as being the vertical distance between the lowest normal ground point along the centerline of the dam and the top of dam.

Prevailing wind in Alabama is generally NW to SE; however, localized conditions may be different.

Geological investigations

Use pits, trenches, borings, reviews of existing data, or other suitable means of investigation to characterize materials within the embankment foundation, auxiliary spillway, and borrow areas. Borings for the embankment are usually along the centerline and used to determine if an adequate cutoff can be constructed. Borings in the auxiliary spillway and borrow areas are used to determine the adequacy of material to be used in the cutoff and embankment. All soil borings will be recorded using the appropriate engineering forms. Soil materials shall be classified using the Unified Soil Classification System (ASTM D2487).

Foundation cutoff

Design a cutoff of relatively impervious material under the dam and up the abutments as required for preventing seepage. Locate the cutoff at, or upstream from, the centerline of the dam. Extend the cutoff deep enough to intercept flow and connect with a relatively impervious layer, and extend it up the abutments as required to intercept flow. The cutoff shall extend into a relatively impervious layers a minimum of 1 ft. Combine seepage control with the cutoff as needed. The cutoff trench shall have a minimum bottom width of 8 ft. and be adequate to accommodate the equipment used for excavation, backfill, and compaction operations. Side slopes shall not be steeper than one horizontal to one vertical.

Seepage control

Include seepage control if (1) foundation cutoff does not intercept pervious layers, (2) seepage could create undesired wet areas, (3) embankment stability requires seepage control, or (4) special problems require drainage for a stable dam. Control seepage by (1) foundation, abutment, or embankment filters and drains; (2) reservoir blanketing; or (3) a combination of these measures.

Top width

Table 1 provides the minimum top widths for dams of various total heights. Total height is the vertical distance between the settled top of the dam and the lowest elevation at the downstream toe. Guard rails or other safety measures shall be used in public road situations and shall meet the requirements of the Alabama Department of Transportation Specifications. For dams less than 20 feet in total height, maintenance considerations or construction equipment limitations may require increased top widths from the minimum shown in table 1.

Side slopes

Design the combined upstream and downstream side slopes of the settled embankments to be no less than that shown in Table 2 and the front slope shall not be steeper than two horizontal to one vertical. As required, design benches or flatten side slopes to assure stability of all slopes for all loading conditions.

Slope protection

Where needed to protect the face of the dam, design special wave protection measures such as berms, rock riprap, sand-gravel, soil cement or special water tolerant vegetation (maiden cane, switchgrass, sandbar willows, and rice cutgrass). Use NRCS Engineering Technical Release (TR) 210-56, A Guide for Design and Layout of Vegetative Wave Protection for Earth Dam Embankments, and TR-210-59, Riprap for Slope Protection against Wave Action, as applicable. When the location of the pond exposes the dam to prevailing winds, and fetch length is greater than 1320 ft., the upstream slope shall be protected from wave damage as a minimum by one of the following methods:

1. Place an 8-ft. wide berm approximately 1 ft. above the designed waterline.
2. Place a blanket of riprap 2 ft. thick at the designed waterline, the upper limit of this blanket being 2 ft. above and the lower limit being 1 ft. below the waterline.
3. Increase the width through the dam at the designed waterline at least 4 ft. by flattening the side slopes.
4. Plant water tolerant vegetation of the right character and height on properly constructed berms. When vegetation is recommended for wave erosion protection, the vegetation should be capable of enduring short durations of inundation without serious damage and should be sod formers or bunch-type plants.

Freeboard

Design a minimum of 1.0 feet of freeboard between design high-water-flow elevation in the auxiliary spillway and the top of the settled embankment. Design a minimum 2.0 feet of elevation difference between the crest of the auxiliary spillway and the top of the settled embankment when the dam has more than a 20-acre drainage area or more than 20 feet in effective height. Design a minimum of 1.0 feet of freeboard above the peak elevation of the routed design hydrograph to the top of the settled embankment, when the pond has no auxiliary spillway. For levee type embankment ponds that exclude outside drainage area and have a principal spillway designed to handle the 10-yr., 24-hr. direct rainfall, the minimum difference in elevation between the settled top of dam and the permanent water elevation shall be based on the prevailing wind fetch length (Table 5, Note 7). In no case shall the difference be less than 1 foot.

All minimum freeboards shall be increased according to the prevailing wind fetch length (Table 5, Note 7).

Settlement

Increase the height of the dam by the amount needed to ensure that the settled top elevation of the dam equals or exceeds the design top elevation. Design a minimum of 5 percent of the total height of the dam associated with each dam cross section, except where detailed soil testing and laboratory analyses or experience in the area shows that a lesser amount is adequate.

Compaction

Proper compaction of earth fill is critical for ensuring the stability and impermeability of the dam. The following procedures are the minimum requirements for fill placement and compaction:

- The maximum uncompacted layer thickness shall be 8 inches.
- For dams having an effective height less than 20 feet compaction shall be accomplished by traversing every point on each layer a minimum of 3 times with construction/earth moving equipment having lugged pneumatic tires.
- For dams having an effective height of 20 feet and greater compaction shall be accomplished by use of a "sheepfoot" or tamping type roller. Each layer shall be rolled a minimum of 6 times, or until the feet "walk out" of the layer.

Where strict control of earth fill placement is deemed necessary, soil moisture and density may be specified and tested in accordance with procedures in ASTM Standard D 698.

Principal spillway and pipe conduit through the embankment

Design a pipe conduit with needed appurtenances through the dam, except where rock, concrete, or other types of lined spillways are used, or where a vegetated or earth spillway can safely handle the rate and duration of base flow. Water level control pipe systems with short risers or a hood inlet in a box may be used in renovation of excavated or embankment ponds where installation of a pipe through the base of the dam is not practical. Siphon systems may be used in new ponds or in renovation of existing ponds. Design the inlet and outlet to function for the full range of flow and hydraulic head anticipated.

Storm storage

For Job Class I Ponds, the principal spillway crest elevation shall be no less than 0.5 ft. below the crest of the auxiliary spillway for dams having a drainage area of 20 acres or less, and no less than 1 ft. for all dams having a drainage area of more than 20 acres.

When design discharge of the principal spillway is considered in calculating peak outflow through the auxiliary spillway, the crest elevation of the inlet shall be such that the full flow will be generated in the conduit before there is discharge through the auxiliary spillway except where the pipe is enlarged because of drawdown requirements.

Pipe conduit size

Design adequate pipe conduit capacity to discharge long-duration, continuous, or frequent flows without causing flow through the auxiliary spillway. Design a principal spillway pipe with a minimum inside

diameter of 4 inches. If the pipe conduit diameter is 10 in. or greater, its design discharge may be considered when calculating the peak outflow rate through the auxiliary spillway.

Watershed runoff and peak rates will be determined using methods outlined in National Engineering Handbook (NEH), Part 650, Engineering Field Handbook, Chapter 2, Estimating Runoff and Peak Discharges., Pipe size will be determined according to procedures in NEH, Part 650, Chapter 11, Ponds and Reservoirs. Approved computer programs, such as WINPOND may be used to select the size of pipe conduit and riser.

Requirements of pipe conduits under or through the dam

Design and install pipe conduits to withstand all external and internal loads without yielding, buckling, or cracking. Design rigid pipe for a positive projecting condition. Design flexible pipe conduits in accordance with the requirements of NRCS National Engineering Handbook (NEH), Part 636, Chapter 52, Structural Design of Flexible Conduits. Flexible pipe strength shall not be less than that necessary to support the design load with a maximum of 5 percent deflection. The modulus of elasticity for PVC pipe shall be assumed as one-third of the amount designated by the compound cell classification to account for long-term reduction in modulus of elasticity. The inlets and outlets shall be structurally sound and made from materials compatible with those of the pipe. Design and install all pipe conduits to be watertight using couplings, gaskets, caulking, water stops, or welding. Design joints to remain watertight under all internal and external loading including pipe elongation due to foundation settlement. Total pipe length will include a minimum of 6 ft. added to extend beyond the downstream toe and 4 ft. added to extend beyond the upstream toe.

For dams 20 ft. or less in total height, acceptable pipe materials are ductile iron, welded steel, corrugated steel or aluminum, reinforced concrete, plastic, and pre-cast and site-cast reinforced concrete. Concrete pipe shall be laid in concrete bedding. Plastic pipe that will be exposed to direct sunlight should be protected by coating or shielding. Connections of plastic pipe to less flexible pipe or structures must be designed to avoid stress concentrations that could rupture the plastic.

For dams more than 20 ft. in total height, conduits shall be reinforced concrete pipe, cast-in-place reinforced concrete, corrugated steel or aluminum, or welded steel pipe. The maximum height of fill over any principal spillway, corrugated steel pipe or aluminum pipe will not exceed 25 feet. Refer to Tables 3 and 4 in this standard.

Supply lines to watering troughs and other appurtenances shall have a minimum inside diameter of 1.25 inches. A watering trough when needed will be used and placed below embankment and excavated ponds. Refer to **Filter diaphragms** and **Anti-seep collars** sections for seepage control requirements for supply lines.

Pool drain

Provide a pipe with a suitable valve to drain the pool area if needed for proper pond management or if required by State law. The designer may use the principal spillway conduit as a pond drain if it is located where it can perform this function.

Joint and appurtenances

The joints between sections of pipe shall be designed to remain watertight after joint elongation caused by foundation consolidation. Design a concrete cradle or bedding for pipe conduits if needed to reduce or limit structural loading on pipe and improve support of the pipe. Design outlet structures, such as cantilever pipe outlet sections and impact basins, to dissipate energy as needed.

Corrosion protection

Provide protective coatings for all steel pipe and couplings in areas that have traditionally experienced pipe corrosion or in embankments with saturated soil resistivity less than 4,000 Ohm-cm or soil pH less than 5. Protective coatings may include asphalt, polymer over galvanizing, aluminized coating, or coal tar enamel (see Tables 3 and 4).

Ultraviolet protection

Use ultraviolet-resistant materials for all plastic pipe or provide coating or shielding to protect plastic pipe exposed to direct sunlight (see Tables 3 and 4).

Cathodic protection

Provide cathodic protection for coated welded steel and galvanized corrugated metal pipe where soil and resistivity studies indicate that the pipe needs a protective coating and where the need and importance of the structure warrant additional protection and longevity. If the original design and installation did not include cathodic protection, consider establishing electrical continuity in the form of joint-bridging straps on pipes that have protective coatings. Add cathodic protection later if monitoring indicates the need.

Filter diaphragms

Provide filter diaphragms to control seepage on all pipes extending through the embankment with inverts below the peak elevation of the routed design hydrograph. Design filter diaphragms or alternative measures as needed to control seepage on pipes extending through all other embankments or for pipes with inverts above the peak elevation of the routed design hydrograph.

Design the filter diaphragm in accordance with the requirements of NEH, Part 628, Chapter 45, Filter Diaphragms. Locate the filter diaphragm immediately downstream of the cutoff trench, but downstream of the centerline of the dam if the foundation cutoff is upstream of the centerline or if there is no cutoff trench.

The drain is to consist of sand, meeting fine concrete aggregate requirements in ASTM C-33 (at least 15% passing the No. 40 sieve but no more than 10% passing the No. 100 sieve). If unusual soil conditions exist, a special design analysis shall be made.

The drain shall be a minimum of 2-ft. thick and extend vertically upward and horizontally at least three times the pipe diameter, and vertically downward at least 18-in. beneath the conduit invert.

The drain diaphragm shall be located immediately downstream of the cutoff trench, approximately parallel to the centerline of the dam.

The drain shall be outletted at the embankment downstream toe, preferably using a drain backfill envelope continuously along the pipe to where it exits the embankment. Protect the drain outlet erosion by use of a properly designed filter system and riprap.

Anti-seep collars

Anti-seep collars may be used only in the following situations:

1. the depth of the water impounded against the embankment is less than 3 feet, and/or
2. the geometry of the embankment and pipe structure make it impossible or impractical to install a diaphragm drain having the required dimensions.

When using anti-seep collars in lieu of a filter diaphragm, ensure a watertight connection to the pipe. Limit the maximum spacing of the anti-seep collars to 14 times the minimum projection of the collar measured perpendicular to the pipe, or 25 feet, whichever is less. Locate anti-seep collars no closer than 10 feet apart. Use a collar material that is compatible with the pipe material.

When using anti-seep collars, design the collars to increase the seepage path along the pipe within the fill by at least 15 percent.

Trash guards

An approved type of trashrack sleeve (minimum length 24 in.) or wildlife sleeve shall be installed at the riser inlet on all drainage area embankment ponds to prevent the conduit from clogging. Levee ponds with no outside drainage area will have a trashrack or be screened to prevent fish from escaping and prevent wild trash fish from entering the pond through the pipe. The minimum quality of material used shall be 16 gage and shall be protected by asphalt coating, galvanizing, or water durable paint. Trash guards of PVC

or polyethylene are acceptable if size and thickness are adequate. Barrels or plastic buckets are not acceptable. All hardware used for mounting shall be of equal or compatible material.

Anti-vortex

Provide an anti-vortex device for a pipe conduit designed for pressure flow.

Outlet protection

Barrel pipes 12 in. or larger and siphon pipes are to have outlet protection.

Siphon spillway

A siphon pipe spillway is a closed conduit system formed in the shape of an inverted "V", positioned so that the invert of the bend (CREST) of the upper passageway is at normal water surface elevation. The initial discharge of the siphon, as the reservoir level rises above normal, is similar to flow over a weir. Siphoning action begins after the air in the siphon pipe has been exhausted, usually at a depth over the crest equal to about 1/3 the pipe diameter. An air vent is provided to break the siphoning action when the reservoir water surface is drawn down to normal pool elevation. Because of the negative pressure that exists within the siphon when flowing full, the pipe joints must be air tight and the pipe must be sufficiently rigid to withstand the collapsing forces. Welded steel or plastic pipe with glued joints should be used. Pipe joints using rubber gasketed joints may not be sufficiently airtight to function properly in a siphon system.

The following minimum criteria shall apply to siphon spillway systems, in addition to other applicable criteria listed elsewhere in this standard: The total lift of the siphon will be limited to a maximum of 20 feet. A 2-in. diameter vent pipe will be used on siphon pipes up through 8-in. and a 4-in. diameter vent pipe will be used for siphons 10-in. through 16-in. diameters. Pipe used for siphons shall be smooth steel or smooth plastic pipe with a minimum wall thickness equivalent to Schedule 40 or SDR 26. The siphon will have an elbow on the downstream end or will be submerged during flow to completely seal the end of the pipe. If an elbow is used, it will have a 1/4-in. to 3/8-in. weep hole drilled in the bottom of the elbow to insure that water does not freeze in the pipe and possibly prevent the siphon from functioning. The pipe will be buried through the dam and the downstream section of the pipe will be buried or will have adequate anchors and restraints to prevent thrust forces and vibrations from breaking the pipe. The vent pipe will be protected by a perforated pipe sleeve to prevent floating debris from clogging the vent. The total area of the perforations in the vent pipe sleeve should equal at least four times the vent pipe area. The inlet to the siphon shall have a perforated section which will exclude trash, turtles, fish, etc. The perforated inlet section must have an open area equivalent to at least two times the cross sectional area of the siphon pipe. PVC siphon pipes are to be protected against UV light degradation.

Auxiliary spillways

A dam must have an open channel auxiliary spillway, unless the principal spillway is large enough to pass the peak discharge from the routed design hydrograph and the trash that comes to it without overtopping the dam. The minimum criteria for acceptable use of a closed conduit principal spillway without an auxiliary spillway consist of a conduit with a cross-sectional area of 3 feet² or more, an inlet that will not clog, and an elbow designed to facilitate the passage of trash.

Design the minimum capacity of a natural or constructed auxiliary spillway to pass the peak flow expected from a total design storm of the frequency and duration shown in table 5, less any reduction creditable to the conduit discharge and detention storage.

Design the auxiliary spillway to safely pass the peak flow through the auxiliary spillway, or route the storm runoff through the reservoir. Start the routing either with the water surface at the elevation of the crest of the principal spillway or at the water surface after 10 days' drawdown, whichever is higher. Compute the 10-day drawdown from the crest of the auxiliary spillway or from the elevation attained from impounding the entire design storm, whichever is lower. Design the auxiliary spillway to pass the design flow at a safe velocity to a point downstream where the flow will not endanger the dam.

Where spillways are constructed in earth, they shall be vegetated. Earthen portions of a spillway constructed in rock shall be vegetated. All embankment ponds will have a minimum 10-ft. wide spillway,

except levee-type embankment ponds which exclude outside drainage area. These type levee ponds are not required to have an auxiliary spillway if the principal spillway is designed to handle a 10-yr., 24-hr. rainfall.

Cross-Section

The spillway shall be excavated in undisturbed earth and have a trapezoidal cross section with side slopes not steeper than three horizontal to one vertical. The side slopes may be vertical when the spillway is excavated in rock.

If a rock auxiliary spillway is to be designed, the table for vegetated spillways excavated in erosion resistant soil found in NEH, Part 650, Chapter 11, is to be used.

Profile

A constructed auxiliary spillway consists of an inlet channel, a control section, and an exit channel.

Inlet Channel

The inlet channel is that portion upstream from the control section. Design the inlet channel with a uniform negative grade toward the pond with a minimum slope of 0.5 percent or enough grade to achieve adequate drainage. The alignment of the inlet channel may be curved to fit existing topography.

Control Section

The control section shall be constructed level at designed grade with a minimum length of 25 feet.

Exit Channel

The exit channel, that portion downstream from the control section, shall be straight in alignment for a distance of 50 ft., if possible, and its centerline shall be perpendicular to the control section. Design the exit channel grade in accordance with NEH Part 628, Chapter 50, Earth Spillway Design, or with equivalent procedures. The exit channel shall terminate at a point where the design flow may be discharged without erosion or damage to the earth embankment.

Structural auxiliary spillways

When used for principal spillways or auxiliary spillways, design chute spillways or drop spillways according to the principles set forth in NEH, Part 650, Engineering Field Handbook; and NEH, Section 5, Hydraulics; Section 11, Drop Spillways; and Section 14, Chute Spillways. Design a structural spillway with the minimum capacity required to pass the peak flow expected from a total design storm of the frequency and duration shown in table 2, less any reduction creditable to the conduit discharge and detention storage.

Reservoir area

Reservoir areas are to be cleared at least up to the elevation of the lowest ungated principal spillway inlet. Stumps must be cut as close to the ground as possible. Less clearing may be approved by the state conservation engineer on a case-by-case basis.

Criteria for Excavated Ponds

Runoff

Design a minimum of 1.0 feet of freeboard above the peak elevation of the routed design hydrograph. A pipe will be used when flow from springs or from seepage is anticipated to occur for about six months of the year. The pipe will be set a minimum of 6 in. below the crest of the auxiliary spillway. Flow patterns will be considered when locating the pond and placing the spoil.

Site investigation

Site suitability and design shall be based on adequate investigations and surveys as described in NEH, Part 650, Chapter 11.

Capacity

The storage capacity of excavated ponds shall be such that an adequate supply of water is available for all intended purposes when needed.

Depth

The depth of a pond shall be no less than that required to provide water for the intended purposes. Where site conditions will permit, a minimum depth of 6 ft. shall be provided over at least one-half of the bottom area.

Auxiliary spillway

Where excavated material is used to construct an embankment, an auxiliary spillway (minimum 10 ft. width) must be installed with a stage and freeboard (minimum 1 ft.) sufficient to insure safety of the dam. If there is two feet of water, or more, impounded against the embankment at the auxiliary spillway elevation, or if the drainage area exceeds 10 acres, the auxiliary spillway shall be designed as for an earthfill pond.

Side slopes

Side slopes of excavated ponds shall be no flatter than those needed to obtain slope stability and in no event shall they be steeper than 1 horizontal to 1 vertical. Where the pond is to be used for direct watering by livestock, at least one slope shall be 3:1 or flatter. If the pond is used for

watering swine, the water will be piped to a trough or a concrete watering ramp installed and the pond shall be fenced to provide protection to the side slopes.

Watering ramp

When wildlife or livestock need access to stored water, use the criteria in NRCS CPS Code 614, Watering Facility, to design a watering ramp.

Perimeter form

When the pond is used for recreation or is located in high public view, the perimeter or edge should be shaped to a curvilinear form.

Inlet protection

Where surface water enters the pond in a natural or excavated channel, the side slope of the pond shall be protected against erosion.

Excavated material

Place the material excavated from the pond so that its weight does not endanger the stability of the pond side slopes and so that the soil will not wash back into the pond by rainfall.

Dispose of excavated material in one of the following ways:

- Uniformly spread to a height that does not exceed 3 feet, with the top graded to a continuous slope away from the pond.
- Uniformly place or shape reasonably well, with side slopes assuming a natural angle of repose. Place excavated material at a distance equal to the depth of the pond, but not less than 12 feet from the edge of the pond.
- Shape to a designed form that blends visually with the landscape.
- Provide for low embankment construction and leveling of surrounding landscape.
- Haul material offsite.

Criteria for Ponds Constructed Primarily for Aquaculture

Levee type ponds which exclude outside runoff and embankment ponds constructed for fish production shall be designed using the preceding criteria with these added requirements:

- **Pipe.** A pipe will be required for management purposes. The drain pipe on cut and fill ponds should

be placed at the lowest constructed ground elevation.

- **Shallow water.** All shallow water edges, where feasible, shall be deepened to provide a minimum depth of 2.5 ft. and preferably 3 ft. of water on slope of 4:1 or steeper. This does not apply to crawfish ponds.
- **Location of levee ponds.** Levee ponds located in the flood plain are to be located so the main drainage of the floodplain shall pass as a minimum the runoff from the 25-yr., 24-hr. storm without significant flooding or damage to utilities and private or public property. It is recommended that 40 to 50 percent of the owner's floodplain area around the channel be left open. Unless flood prone maps are available in each county, designers will make valley and channel section surveys for use in rating and determining flood plain limits of the design storm.
- **Water supply.** Levee production and embankment production ponds with small drainage areas should have an adequate water supply available to replenish oxygen losses and for proper pond management. A good rule of thumb is 15 to 25 gallons per minute, per acre of surface area. In addition, provision must be made for emergency aeration during periods of low oxygen.
- **Water control structure.** The riser and deep water release can be designed and installed to control the water level and remove excess water from either the bottom or from different elevations in the pond. The drain pipe must be adequate to completely drain the pond and draw the water down within a three-day period to a seineable depth and be so located as to provide positive uniform drainage from the entire pond area including harvesting basin. A screen should be installed over the valve inlet or outlet pipe to prevent fish loss and to prevent wild trash fish from entering the pond. The riser and drain facilities when possible should be located in one corner of the embankment area to provide a more desirable seineable harvest area.
- **Spillway storage.** The principal spillway and storage must be designed for a minimum 5-yr, 24-hr. storm runoff to limit auxiliary spillway operation. A properly designed trashrack or sleeve with screens for the riser will prevent loss of fish from the pond and also prevent trash fish from entering the pond during storm periods. When completing the principal spillway design, check to see if it drains the pond down to the seineable depth within the three-day period as specified in Item 5.
- **Harvesting basin.** The pond area for commercial harvested ponds shall be developed with a smooth bottom shaped to drain to the pipe and be free of stumps, snags, and other obstructions. The harvesting basin for small operations shall be constructed, as a minimum, 1/5 the size of the pond and at least 18 in. deep and the bottom and sides shall be smooth and uniform and be free of stumps and snags. When a series of small ponds are constructed together, consideration should be given to developing the harvest basin and drainage facilities adjacent to each other to permit the harvest of fish from two ponds at the same loading locations.
- **Road system.** An adequate all-weather road system with ramps shall be planned and constructed to provide access to the pond or ponds to facilitate stocking, feeding, and harvesting operations. Gravel, sand, crushed stone, chert, or other similar material should be used on main segments to facilitate all-weather use. Culverts should be installed in low areas along the all-weather road to provide surface drainage. The road around the pond shall be constructed a minimum of 1 ft. above the permanent waterline elevation to accommodate feeding and harvesting of fish.
- **Top width and side slopes.** The top width of dikes, levees, and dams for ponds used as roads for feeding and harvesting purposes in commercial fish production shall be a minimum of 14 ft., except embankments used for electrical service which shall have a minimum top width of 16 ft. (Refer to Alabama NRCS Conservation Practice Standard, Aquaculture Ponds – Code 397). Side slopes (wet) shall be 3:1 or flatter to facilitate harvest and to minimize damage from wave action. In order to reduce costs on some ponds, the engineer may approve the use of a 2.5:1 slope on the wet side of the dam. Levees or dikes between ponds not used as roads may be designed for minimum top width as shown in Table 1. Where embankments join other embankments or abutments longer radius turns should be used to enable larger trucks to make appropriate turns easier.
- **Vegetation.** The vegetation plan and operation and maintenance plan will be as outlined in the Plans and Specifications section.

Criteria for Ponds Constructed Primarily as Shallow Water Impoundments for Wildlife.

Ponds constructed as shallow water impoundments for wildlife shall be designed using the preceding criteria for embankment and excavated ponds with these exceptions:

- Green tree reservoirs shall meet the functional requirements contained in Alabama NRCS Conservation Practice Standard, Wetland Wildlife Habitat Management, Code 644.
- Sites with 6 ft. or less effective height (as defined in this standard) and less than a 5:1 watershed to pond ratio can be designed utilizing Class III dike criteria contained in Alabama NRCS Conservation Practice Standard, Dike, Code 356.
- Where frequent flood flows can bypass on the floodplain and return to the drainage ways without causing erosion or other undesirable conditions, the principal spillway (or other water control structure) may be sized to meet the functional requirements of the impoundment rather than the requirements of Table 5. The requirements for the auxiliary spillway design storm shall remain the same. Where these conditions exist, the riser may be set at no less than 0.5 ft. below the crest of the auxiliary spillway or bypass elevation.
- Ponds located in flood plain areas shall meet the same requirements for flood plain blockage as those identified for aquacultural ponds.
- The area around the embankment shall be cleared so that the distance to the edge of the nearest tree canopy is not closer than 20 ft. to the toe of the embankment.

Criteria for the Renovation of Embankment and Excavated Ponds

Pond clean out shall consist of removal of accumulated silt, debris, bank sloughing, and other material from the reservoir. The purpose of excavated pond renovation is to restore the useful storage capacity and to reduce safety and disease hazards to livestock. Renovation of embankment ponds will be to restore the original storage capacity and water level control pipe and to repair the embankment and the earth spillway.

Renovated ponds used for livestock watering should be fenced and a concrete or riprap watering ramp installed in the pond or a trough installed downstream to maintain water quality and quantity.

Renovation applies to water impoundment reservoirs constructed with or without costsharing funds. It is limited to excavated and small embankment ponds which no longer serve the purpose for which they were originally designed due to damage from erosion, cattle traffic, and sedimentation.

Material Requirements

Pipe materials shall meet the requirements of the reference specification for the type of material used as shown in Table 6.

Corrugated steel pipe

Field coupling of pipe sections shall be accomplished by means of coupling bands and watertight gaskets or flange pipe couplings. The band couplers shall be at least 5 corrugations wide for annular corrugated pipe, or 9 in. for spiral corrugated pipe. Minimum gage shall be as shown in Table 4, Minimum Gages, Corrugated Metal Pipe. Protective coatings shall be used as outlined in the section on Joints and Appurtenances, Principal Spillway, and Embankment Pond Criteria.

Smooth steel pipe

Good quality, used, smooth- welded steel pipe suitably protected from rust and corrosion may be used.

Used pipe must have a remaining wall thickness at any pitted or rust spot equal to 75% of the equivalent wall thickness of new pipe.

Reinforced concrete pipe

New pipe shall be used, shall have flexible watertight joints with rubber gaskets, shall be cambered, and shall be able to withstand the external loadings specified.

Plastic pipe

New pipe shall be used and shall conform to requirements in Table 3. The conduits shall be transported, stored, installed, and protected according to manufacturer's recommendations. Smooth lined corrugated plastic tubing pipe conforming to AASHTO M252 or M294 may be used in pond installations provided it is properly bedded and connected with watertight couplings.

Inspection

NRCS personnel shall thoroughly inspect the material and fittings to determine if they meet the requirements of the specifications, test results, and certification from the manufacturer. Although the products may have met standard specifications when tested or at the time of delivery by the supplier, they may have become defective before installation. Inspection by NRCS personnel at the job site is essential to determine the adequacy of the product to be used.

Materials evaluated and found not to meet the requirements of the specifications or found not suitable for the use intended shall not be used. Documentation shall be by a statement made in the Engineering Field Notes on the inspection and acceptance or rejection of the materials.

Pipe Installation Requirements

Pipe conduits shall be installed in a manner that provides uniform support to the pipe and continuous contact between the pipe, soil foundation and backfill. Except where the pipe penetrates drainage zones, earth fill around the pipe shall be of the more plastic soil available on site. The ability of pipe to withstand vertical loads is dependent upon the density of the soil surrounding the sides of the pipe. Manual compaction of soil within the two-foot zone surrounding the pipe is required to ensure that adequate soil density is achieved and to prevent damage to the pipe by construction equipment. Guidance for bedding and backfilling around pipe conduits may be found in NEH Part 650, Chapter 17, and Technical Note ENG-AL-10. Installation shall be in accordance with the requirements of construction specification CS-EMB-378. Joining pipe sections will be performed in a manner to ensure a watertight connection and in compliance with the manufacturer's recommendations.

The pipe conduit should be cambered to prevent breaking or joint separation as the dam settles. That is, the pipe should be laid essentially level to the centerline of dam, then laid essentially straight to the exit end elevation. Then as, settlement occurs, the pipe grade will flatten and tighten the joints. The amount of camber provided should be equal to or greater than the anticipated settlement along the pipe. The amount of deflection provided at any joint should not exceed the manufacturer's recommendations. Uniform bedding should be used to avoid stress concentrations in the pipe as soil load is applied.

Regulations Governing the Impounding of Water

To comply with the rules and regulations of the State of Alabama and U.S. Army Corp of Engineers (COE) governing the impounding of water or damming of water courses in Alabama, the following shall apply:

1. The construction of ponds in Alabama may require a National Pollution Discharge Elimination System (NPDES) Permit from the Alabama Department of Environmental Management (ADEM) by the landowner or contractor prior to construction based on the amount of land disturbed and the purpose of the pond.
2. Federal laws designed to protect wetlands and other waters of the U.S. require a permit for construction of some ponds. According to the COE, a 404 Permit determination must be made for ponds that involve more than 0.1 acre of wetland or other waters of the U.S. unless exempted as part of an established farming operation or otherwise permitted under a nationwide permit.
3. Safety measures such as warning signs, rescue facilities, fencing, etc., will be included in the plans as appropriate to the location and anticipated use of the ponds.
4. Construction operations shall be carried out in such a manner that soil erosion, and air, water, and noise pollution will be minimized and held within legal limits as established by state regulations.

CONSIDERATIONS

Ponds are constructed to improve water quality and they create new surface and groundwater regimes. Generally, peak discharge will be reduced and in many instances reduced to zero during dry periods. There may be increased recharge to the groundwater since most ponds seep and the base flow may extend for a longer period of time.

Properly constructed ponds will trap nutrients, sediment, and pesticides. Therefore, chemical concentrations will normally be higher in the pond area and lower in the downstream channel section. Ponds constructed in pervious soils may cause more leachable substances to be carried into the groundwater. Plans should be made for each site based on site conditions and the desired water quantity and quality needed downstream. Surface water temperature of the pond will increase.

Siphon spillway inlets are placed above the pond bottom and will not completely drain the reservoir. Siphon spillways can be designed to discharge poorer quality water from near the pond bottom thereby improving the quality of water in the reservoir.

Consider the use of anti-seep collars for siphons when poor soils or other conditions unfavorable for fill placement around the pipe exist.

Consider the use of fencing and a heavy use area protected watering ramp for ponds used as a direct source of water for livestock.

Visual resource design

The landscape will be considered in planning earthfill ponds to improve the surroundings. Trees and shrubs should not be left within 15 ft. of the dam except at locations above the waterline. The landscape can be improved by leaving desirable trees on the slopes between the auxiliary spillway and the end of the dam. Ponds in areas of high public visibility and those associated with recreation are to receive careful visual design. The underlying criterion for all visual design is appropriateness. The shape and form of ponds, excavated material and plantings are to relate visually to their surroundings and to their function.

The embankment can be shaped to blend with the natural topography. The edge of the pond can be shaped so it is generally curvilinear rather than rectangular. Excavated material can be shaped so the final form is smooth, flowing, and fitting to the adjacent landscape rather than appearing as angular geometric mounds. Where feasible, islands or piers can be added for visual interest and wildlife value.

Outlet protection

Pipe outlet protection should be considered on a case-by-case basis for barrel pipes less than 12 in. diameter.

Cultural resources

Consider existence of cultural resources in the project area and any project impacts on such resources. Consider conservation and stabilization of archeological, historic, structural, and traditional cultural properties when appropriate.

Fish and wildlife

Locate and construct ponds to minimize the impacts to existing fish and wildlife habitat.

When feasible, retain structures such as trees in the upper reaches of the pond and stumps in the pool area. Shape upper reaches of the pond to provide shallow areas and wetland habitat.

If operations include stocking fish, use CPS Code 399, Fishpond Management.

Vegetation

Stockpile topsoil for placement on disturbed areas to facilitate revegetation.

Consider selecting and placing vegetation to improve fish habitat, wildlife habitat and species diversity.

Water quantity

Consider effects upon components of the water budget, especially:

- Effects on volumes and rates of runoff, infiltration, evaporation, transpiration, deep percolation, and ground water recharge.
- Variability of effects caused by seasonal or climatic changes.
- Effects on downstream flows and impacts to environment such as wetlands, aquifers, and; social and economic impacts to downstream uses or users.
- Potential for multiple purposes.

Water quality

Consider the effects of:

- Erosion and the movement of sediment, pathogens, and soluble and sediment-attached substances that runoff carries.
- Short-term and construction-related effects of this practice on the quality of downstream watercourses.
- Water-level control on the temperatures of downstream water to prevent undesired effects on aquatic and wildlife communities.
- Wetlands and water-related wildlife habitats.
- Water levels on soil nutrient processes such as plant nitrogen use or denitrification.
- Soil water level control on the salinity of soils, soil water, or downstream water.
- Potential for earth moving to uncover or redistribute toxic materials.
- Livestock grazing adjacent to the pond.
- Consider fencing to keep livestock activities out of direct contact with the pond and dam.

PLANS AND SPECIFICATIONS

Prepare plans and specifications that describe the requirements for applying the practice according to this standard. As a minimum, include the following items:

- A plan view of the layout of the pond and appurtenant features
- Typical profiles and cross sections of the principal spillway, auxiliary spillway, dam, and appurtenant features as needed
- Structural drawings adequate to describe the construction requirements
- Requirements for vegetative establishment and/or mulching, as needed
- Safety features
- Site-specific construction and material requirements

The site will be protected by perennial vegetation as shown in the Construction Specifications for this practice. A strip of adapted perennial vegetation, at least 50 ft. wide, will be established above all impounded areas that are not already protected by a good sod, woods, or other protective type vegetation. The vegetation plan will include the salvage of surface soil from the site and placement over critical areas. The area will be mulched after seeding.

OPERATION AND MAINTENANCE

Prepare an operation and maintenance plan for the operator.

As a minimum, include the following items in the operation and maintenance plan:

- Periodic inspections of all structures, earthen embankments, spillways, and other significant appurtenances
- Prompt repair or replacement of damaged components
- Prompt removal of sediment when it reaches predetermined storage elevations
- Periodic removal of trees, brush, and undesirable species
- Periodic inspection of safety components and immediate repair if necessary
- Maintenance of vegetative protection and immediate seeding of bare areas as needed

An operation and maintenance plan will be made for each structure site and given to the landuser along with the plans and specifications for construction.

When needed, fencing, and watering trough will be provided to protect the pond and vegetation from livestock.

All ponds must be adequately maintained if their purposes are to be realized through the expected life. Special considerations shall be given for maintenance needs during the planning, design, and construction of the pond.

Rills on the slopes of the dam and eroded areas in the earth spillway shall be filled with suitable material, compacted, reseeded, and fertilized as needed. Should the upstream face of the dam wash, due to wave action, protection such as riprap shall be installed. If seepage through or under the dam occurs, proper corrective measures shall be taken.

The vegetative cover of the dam and earth spillway shall be maintained by mowing and fertilizing or burning when needed. Trees can cause leaks and safety hazards and should not be permitted in the embankment or the auxiliary spillway.

Appurtenances such as trickle tubes, trashracks, outlet structure and valves shall be kept free of trash and replaced when needed. If vent pipes on siphon spillway systems are allowed to plug with trash or ice, the siphon action will not be broken and the pond could drain.

REFERENCES

American Society for Testing and Materials. Standard Practice for Classification of Soils for Engineering Purposes (Unified Soil Classification System), ASTM D2487. West Conshohocken, PA.

USDA NRCS. Engineering Technical Releases, TR-210-60, Earth Dams and Reservoirs. Washington, DC.

USDA NRCS. National Engineering Handbook (NEH), Part 628, Dams. Washington, DC.

USDA NRCS. NEH, Part 633, Soil Engineering. Washington, DC.

USDA NRCS. NEH, Part 636, Structural Engineering. Washington, DC.

USDA NRCS. NEH, Part 650, Engineering Field Handbook. Washington, DC.

USDA NRCS. National Engineering Manual. Washington, DC.