



**Natural Resources Conservation Service**  
**CONSERVATION PRACTICE STANDARD**  
**RESIDUE AND TILLAGE MANAGEMENT, REDUCED TILL**  
**CODE 345**

(ac)

**DEFINITION**

Managing the amount, orientation, and distribution of crop and other plant residue on the soil surface year-round while limiting soil-disturbing activities used to grow and harvest crops in systems where the field surface is tilled prior to planting.

**PURPOSE**

This practice is used to accomplish one or more of the following purposes—

- Reduce sheet, rill, and wind erosion and excessive sediment in surface waters (soil erosion)
- Reduce tillage-induced particulate emissions (air quality impact)
- Improve soil health and maintain or increase organic matter content (soil quality degradation)
- Reduce energy use (inefficient energy use)

**CONDITIONS WHERE PRACTICE APPLIES**

This practice applies to all cropland.

**CRITERIA**

**General Criteria Applicable to All Purposes**

This practice includes tillage methods commonly referred to as mulch tillage or conservation tillage where the entire soil surface may be disturbed by tillage operations such as chisel plowing, field cultivating, tandem disking, or vertical tillage. It also includes tillage/planting systems with few tillage operations (e.g., ridge till) but which do not meet the soil tillage intensity rating (STIR) criteria for conservation practice Residue and Tillage Management, No Till (Code 329).

Uniformly distribute residues over the entire field. Removing residue from the row area prior to or as part of the planting operation is acceptable.

Do not burn residues, except for a light-to-moderate burn of sugarcane residue after harvest (as described in the wind and water erosion operations database).

The STIR value shall include all soil disturbance field operations that are performed during the crop interval (i.e., from the time immediately following harvest or termination of one cash crop through harvest or termination of the next cash crop in the rotation, including fallow periods). The crop interval STIR value rating shall be no greater than 80, and no primary inversion tillage implements (e.g., moldboard plow) shall be used.

### **Additional Criteria to Reduce Sheet, Rill and Wind Erosion, and Excessive Sediment in Surface Waters**

Use the current approved water and wind erosion prediction technology to document/determine the field operations to achieve the amount of randomly distributed surface residue needed, time of year residue needs to be present in the field, and the planned field operations allowed to reduce erosion to the desired level. Calculations shall account for the effects of other practices in the management system.

In ridge-till systems, plan ridge height and ridge orientation to manage runoff and minimize erosion, with a maximum row grade not to exceed four percent.

### **Additional Criteria to Reduce Tillage-Induced Particulate Emissions**

Reduce or modify tillage operations that create dust, especially during critical air quality periods.

### **Additional Criteria to Improve Soil Health and Maintain or Increase Organic Matter Content**

Ensure the soil condition index (SCI) for the cropping system results in a rating of greater than zero.

### **Additional Criteria to Reduce Energy Use**

Reduce the total energy consumption associated with field operations by at least 25 percent compared to the benchmark condition. Use the current approved NRCS tool for determining energy use to document energy use reductions.

## **CONSIDERATIONS**

### **General Considerations**

Removal of crop residue, such as by baling or grazing, can have a negative impact on resources. These activities should not be performed without full evaluation of impacts on soil, water, animal, plant, and air resources.

Reduced till may be practiced continuously throughout the crop sequence, or may be managed as part of a residue management system that includes other tillage methods such as no till.

Production of adequate amounts of crop residue necessary for the proper functioning of this practice can be enhanced by selection of high residue-producing crops and crop varieties in the rotation, use of cover crops, and adjustment of plant populations and row spacing.

When providing technical assistance to organic producers, ensure residue and tillage management activities are consistent with the USDA Agricultural Marketing Service National Organic Program regulations.

### **Additional Considerations for Maintaining or Improving Soil Organic Matter Content and Soil Health**

Carbon loss is directly related to the volume of soil disturbed, intensity of the disturbance and soil moisture content and soil temperature at the time the disturbance occurs. The following guidelines can make this practice more effective:

- When deep soil disturbance is performed, such as by subsoiling or fertilizer injection, make sure the vertical slot created by these implements is closed at the surface.
- Planting with a single disk opener no-till drill will release less CO<sub>2</sub> and oxidize less organic matter than planting with a wide-point hoe/chisel opener seeder drill.
- Maximizing year-round coverage of the soil with living vegetation and/or crop residues builds organic matter and reduces soil temperature, thereby slowing organic matter oxidation.
- Use a diverse crop rotation by incorporating multiple crop types (cool-season grass, cool-season legume/forb, warm-season grass, warm-season legume/forb) into the crop rotation.
- Plant a cover crop after every cash crop in the rotation. Multispecies cover crop mixes provide

greater benefits than single-specie cover crops.

- Using undercutting tools rather than burying tools will enhance accumulation of organic material in the surface layer.
- Conducting any soil-disturbing field operation when soil moisture is optimal, neither excessive nor too dry, will help maintain soil tilth, and reduce the need for additional tillage in the future.

## PLANS AND SPECIFICATIONS

Specifications shall be prepared for each site and purpose and recorded in the PI implementation requirements document.

- Purpose for applying the practice.
- Planned crop(s).
- Amount of residue produced by each crop.
- All field operations or activities that affect—
  - Residue orientation.
  - Surface disturbance.
  - The field operations and amount of residue (pounds/acre or percent surface cover) required to accomplish the purpose, and the time of year it must be present.
- Planned STIR value, SCI value, and erosion rate.
- Benchmark and planned energy consumptions.

## OPERATION AND MAINTENANCE

Evaluate/measure the crop residue cover and orientation for each crop to ensure the planned amounts and orientation are being achieved. Adjust management as needed to either plan a new residue amount or orientation; or adjust the planting, tillage, or harvesting equipment.

If there are areas of heavy residue accumulation (because of movement by water or wind) in the field, spread the residue prior to planting so it does not interfere with planter operation.

## REFERENCES

Kuepper, George, 2001. Pursuing conservation tillage systems for organic crop production. ATTRA.

<http://attra.ncat.org/attra-pub/organicmatters/conservationtillage.html>.

Reicosky, D.C., M.J. Lindstrom, T.E. Schumacher, D.E. Lobb, and D.D. Malo. 2005. Tillage-induced CO<sub>2</sub> loss across an eroded landscape. *Soil Tillage Res.* 81:183-194.

Reicosky, D.C. 2004. Tillage-induced soil properties and chamber mixing effects on gas exchange. Proc. 16th Triennial Conf., Int. Soil Till. Org. (ISTRO).

Renard, K.G., G.R. Foster, G.A. Weesies, D.K. McCool, and D.C. Yoder, coordinators. 1997. Predicting soil erosion by water: A guide to conservation planning with the Revised Universal Soil Loss Equation (RUSLE). USDA, Agricultural Handbook 703.

USDA-ARS. Skidmore, E.L. and N.P. Woodruff. 1968. Wind erosion forces in the United States and their use in predicting soil loss. USDA, Agriculture Handbook 346.

USDA, NRCS. 2011. National Agronomy Manual. 190-V. 4th Ed.