

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
1	ASCALON SANDY LOAM, 0 TO 4 PERCENT SLOPES								
		ASCALON	85	> 72	None	Not limited	Very limited	Moderate	Low
10	BRUSSETT LOAM, 0 TO 4 PERCENT SLOPES								
		BRUSSETT	85	> 72	None	Not limited	Somewhat limited	Moderately slow	Medium
11	BRUSSETT LOAM, 4 TO 8 PERCENT SLOPES								
		BRUSSETT	80	> 72	None	Not limited	Somewhat limited	Moderately slow	High
12	CONI LOAM, 4 TO 15 PERCENT SLOPES								
		CONI	80	> 72	None	Very limited	Very limited	Slow	Very high
13	CUSHMAN LOAM, 0 TO 4 PERCENT SLOPES								
		CUSHMAN	80	> 72	None	Somewhat limited	Very limited	Slow	Medium
14	CUSHMAN-ASCALON COMPLEX, 4 TO 15 PERCENT SLOPES								
		CUSHMAN	55	> 72	None	Somewhat limited	Very limited	Slow	High
		ASCALON	30	> 72	None	Somewhat limited	Very limited	Moderate	Medium
15	CUSHMAN-HARGREAVE COMPLEX, 8 TO 15 PERCENT SLOPES								
		CUSHMAN	40	> 72	None	Somewhat limited	Very limited	Slow	High
		HARGREAVE	30	> 72	None	Somewhat limited	Very limited	Slow	High
16	CUSHMAN-KUTCH COMPLEX, 8 TO 25 PERCENT SLOPES								
		CUSHMAN	50	> 72	None	Somewhat limited	Very limited	Slow	High
		KUTCH	30	> 72	None	Very limited	Very limited	Slow	Very high
17	ELBETH SANDY LOAM, 4 TO 8 PERCENT SLOPES								
		ELBETH	80	> 72	None	Somewhat limited	Somewhat limited	Moderate	Medium
18	ELBETH-KETTLE COMPLEX, 8 TO 25 PERCENT SLOPES								
		ELBETH	50	> 72	None	Very limited	Very limited	Moderate	Medium
		KETTLE	25	> 72	None	Very limited	Very limited	Rapid	Very low
19	ELLCOTT LOAMY COARSE SAND, 0 TO 4 PERCENT SLOPES								
		ELLCOTT	90	> 72	Frequent	Very limited	Very limited	Rapid	Negligible
2	ASCALON SANDY LOAM, 4 TO 8 PERCENT SLOPES								
		ASCALON	80	> 72	None	Not limited	Very limited	Moderate	Medium
20	ENGLEWOOD CLAY LOAM, 0 TO 4 PERCENT SLOPES								
		ENGLEWOOD	90	> 72	None	Very limited	Somewhat limited	Slow	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
21	FLUVAQUENTS, NEARLY LEVEL*								
		FLUVAQUENTS	70	30-72	Frequent	Very limited	Very limited	Moderate	Low
22	HAPLUSTOLLS, MODERATELY COARSE, NEARLY LEVEL*								
		HAPLUSTOLLS	70	> 72	Occasional	Very limited	Very limited	Rapid	Negligible
23	HAPLUSTOLLS, LOAMY, NEARLY LEVEL*								
		HAPLUSTOLLS	75	24-72	Occasional	Very limited	Very limited	Moderately slow	Medium
24	HELDT CLAY LOAM, 0 TO 4 PERCENT SLOPES								
		HELDT	85	> 72	None	Very limited	Somewhat limited	Slow	High
25	HOLDERNESS LOAM, 0 TO 4 PERCENT SLOPES								
		HOLDERNESS	85	> 72	None	Very limited	Somewhat limited	Slow	High
26	HOLDERNESS LOAM, 4 TO 8 PERCENT SLOPES								
		HOLDERNESS	85	> 72	None	Very limited	Somewhat limited	Slow	Very high
27	KETTLE LOAMY SAND, 8 TO 15 PERCENT SLOPES								
		KETTLE	90	> 72	None	Somewhat limited	Very limited	Rapid	Very low
28	KETTLE-ROCK OUTCROP COMPLEX, 15 TO 65 PERCENT SLOPES								
		KETTLE	40	> 72	None	Very limited	Very limited	Rapid	Low
		ROCK OUTCROP	35	> 72	None	Very limited	Very limited	Very slow	Very high
29	KUTCH CLAY LOAM, 0 TO 4 PERCENT SLOPES								
		KUTCH	85	> 72	None	Somewhat limited	Very limited	Slow	High
3	BACA-WILEY LOAMS, 0 TO 4 PERCENT SLOPES								
		BACA	45	> 72	None	Not limited	Somewhat limited	Moderately slow	Medium
		WILEY	35	> 72	None	Not limited	Somewhat limited	Moderate	Low
30	KUTCH CLAY LOAM, 4 TO 8 PERCENT SLOPES								
		KUTCH	90	> 72	None	Somewhat limited	Very limited	Slow	Very high
31	KUTCH-LOUVIERS COMPLEX, 8 TO 25 PERCENT SLOPES								
		KUTCH	40	> 72	None	Very limited	Very limited	Slow	Very high
		LOUVIERS	30	> 72	None	Very limited	Very limited	Slow	Very high
32	NUNN CLAY LOAM, 0 TO 4 PERCENT SLOPES								
		NUNN	80	> 72	None	Very limited	Somewhat limited	Slow	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
33	NUNN CLAY LOAM, 4 TO 8 PERCENT SLOPES								
		NUNN	85	> 72	None	Very limited	Somewhat limited	Slow	Very high
34	PEYTON SANDY LOAM, 4 TO 8 PERCENT SLOPES								
		PEYTON	80	> 72	None	Not limited	Very limited	Moderate	Medium
35	PEYTON-ELBETH SANDY LOAMS, 8 TO 25 PERCENT SLOPES								
		PEYTON	50	> 72	None	Somewhat limited	Very limited	Moderate	Medium
		ELBETH	30	> 72	None	Very limited	Very limited	Moderate	Medium
36	PEYTON-PRING COMPLEX, 8 TO 25 PERCENT SLOPES								
		PEYTON	50	> 72	None	Somewhat limited	Very limited	Moderate	Medium
		PRING	35	> 72	None	Very limited	Very limited	Moderately rapid	Low
37	PRING COARSE SANDY LOAM, 4 TO 8 PERCENT SLOPES								
		PRING	90	> 72	None	Not limited	Very limited	Moderately rapid	Low
38	RENOHILL CLAY LOAM, 4 TO 8 PERCENT SLOPES								
		RENOHILL	80	> 72	None	Somewhat limited	Very limited	Slow	Very high
39	RENOHILL-LOUVIERS COMPLEX, 8 TO 25 PERCENT SLOPES								
		RENOHILL	40	> 72	None	Somewhat limited	Very limited	Slow	Very high
		LOUVIERS	30	> 72	None	Very limited	Very limited	Very slow	Very high
4	BLUERIM-PEYTON SANDY LOAMS, 8 TO 20 PERCENT SLOPES								
		BLUERIM	45	> 72	None	Somewhat limited	Very limited	Slow	High
		PEYTON	35	> 72	None	Somewhat limited	Very limited	Moderate	Medium
40	TORRIORTHENTS-ROCK OUTCROP COMPLEX, STEEP*								
		TORRIORTHENTS	50	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
41	TRUCKTON SANDY LOAM, 4 TO 8 PERCENT SLOPES								
		TRUCKTON	85	> 72	None	Not limited	Very limited	Moderately rapid	Low
42	TRUCKTON-RENOHILL COMPLEX, 8 TO 25 PERCENT SLOPES								
		TRUCKTON	45	> 72	None	Very limited	Very limited	Moderately rapid	Low
		RENOHILL	25	> 72	None	Somewhat limited	Very limited	Slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
43	WELD LOAM, 0 TO 4 PERCENT SLOPES								
		WELD	85	> 72	None	Somewhat limited	Somewhat limited	Slow	High
44	WELD LOAM, 4 TO 8 PERCENT SLOPES								
		WELD	80	> 72	None	Very limited	Somewhat limited	Slow	Very high
45	WILEY-BACA LOAMS, 4 TO 8 PERCENT SLOPES								
		WILEY	45	> 72	None	Not limited	Somewhat limited	Moderate	Medium
		BACA	35	> 72	None	Not limited	Somewhat limited	Moderately slow	High
5	BRESSER SANDY LOAM, 0 TO 4 PERCENT SLOPES								
		BRESSER	80	> 72	None	Not limited	Very limited	Moderate	Low
6	BRESSER SANDY LOAM, 4 TO 8 PERCENT SLOPES								
		BRESSER	85	> 72	None	Not limited	Very limited	Moderate	Medium
7	BRESSER-CUSHMAN COMPLEX, 4 TO 20 PERCENT SLOPES								
		BRESSER	40	> 72	None	Somewhat limited	Very limited	Moderate	Medium
		CUSHMAN	30	> 72	None	Somewhat limited	Very limited	Slow	High
8	BRESSER-STAPLETON SANDY LOAMS, 8 TO 25 PERCENT SLOPES								
		BRESSER	50	> 72	None	Somewhat limited	Very limited	Moderate	Medium
		STAPLETON	25	> 72	None	Very limited	Very limited	Rapid	Very low
9	BRESSER-TRUCKTON SANDY LOAMS, 8 TO 25 PERCENT SLOPES								
		BRESSER	45	> 72	None	Somewhat limited	Very limited	Moderate	Medium
		TRUCKTON	35	> 72	None	Very limited	Very limited	Moderately rapid	Low