

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
1	ALTVAN LOAM, 0 TO 3 PERCENT SLOPES								
		ALTVAN	85	> 72	None	Not limited	Very limited	Moderate	Low
10	BAINVILLE-KEITH COMPLEX, 2 TO 9 PERCENT SLOPES								
		BAINVILLE	50	> 72	None	Somewhat limited	Very limited	Slow	High
		KEITH	35	> 72	None	Not limited	Somewhat limited	Moderately slow	Medium
100	STONEHAM LOAM, 0 TO 1 PERCENT SLOPES								
		STONEHAM	90	> 72	None	Somewhat limited	Somewhat limited	Moderate	Low
101	STONEHAM LOAM, 1 TO 3 PERCENT SLOPES								
		STONEHAM	90	> 72	None	Somewhat limited	Somewhat limited	Moderate	Low
102	STONEHAM LOAM, 3 TO 5 PERCENT SLOPES								
		STONEHAM	85	> 72	None	Somewhat limited	Somewhat limited	Moderate	Low
103	STONEHAM LOAM, 5 TO 9 PERCENT SLOPES								
		STONEHAM	85	> 72	None	Somewhat limited	Very limited	Moderate	Medium
104	SUNSHINE STONY SANDY LOAM, 5 TO 15 PERCENT SLOPES								
		SUNSHINE	90	> 72	None	Very limited	Very limited	Slow	Very high
105	TABLE MOUNTAIN LOAM, 0 TO 1 PERCENT SLOPES								
		TABLE MOUNTAIN	85	> 72	None	Not limited	Somewhat limited	Moderate	Low
106	TASSEL SANDY LOAM, 3 TO 25 PERCENT SLOPES								
		TASSEL	90	> 72	None	Very limited	Very limited	Slow	Very high
107	THEDALUND LOAM, 0 TO 3 PERCENT SLOPES								
		THEDALUND	90	> 72	None	Somewhat limited	Very limited	Moderate	Low
108	THEDALUND LOAM, 3 TO 9 PERCENT SLOPES								
		THEDALUND	90	> 72	None	Somewhat limited	Very limited	Moderate	Medium
109	THIEL GRAVELLY SANDY LOAM, 5 TO 25 PERCENT SLOPES								
		THIEL	95	> 72	None	Very limited	Very limited	Moderate	Medium
11	BALLER-CARNERO COMPLEX, 9 TO 35 PERCENT SLOPES								
		BALLER	45	> 72	None	Very limited	Very limited	Slow	Very high
		CARNERO	35	> 72	None	Very limited	Very limited	Slow	Very high
110	TINE GRAVELLY SANDY LOAM, 0 TO 3 PERCENT SLOPES								
		TINE	95	> 72	None	Very limited	Very limited	Moderately rapid	Very low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
111	TINE COBBLY SANDY LOAM, 15 TO 40 PERCENT SLOPES								
		TINE	95	> 72	None	Very limited	Very limited	Moderately rapid	Medium
112	TRAG-MOEN COMPLEX, 5 TO 30 PERCENT SLOPES								
		TRAG	45	> 72	None	Not limited	Very limited	Moderate	Low
		MOEN	40	> 72	None	Very limited	Very limited	Slow	Very high
113	ULM CLAY LOAM, 0 TO 3 PERCENT SLOPES								
		ULM	90	> 72	None	Somewhat limited	Somewhat limited	Moderate	Low
114	ULM CLAY LOAM, 3 TO 5 PERCENT SLOPES								
		ULM	85	> 72	None	Somewhat limited	Somewhat limited	Moderate	Low
115	WELD SILT LOAM, 0 TO 3 PERCENT SLOPES								
		WELD	90	> 72	None	Not limited	Somewhat limited	Slow	High
116	WETMORE-BOYLE-MOEN COMPLEX, 5 TO 40 PERCENT SLOPES								
		WETMORE	35	> 72	None	Very limited	Very limited	Slow	Very high
		BOYLE	25	> 72	None	Very limited	Very limited	Moderate	High
		MOEN	25	> 72	None	Very limited	Very limited	Slow	High
117	WETMORE-BOYLE-ROCK OUTCROP COMPLEX, 5 TO 60 PERCENT SLOPES								
		WETMORE	35	> 72	None	Very limited	Very limited	Slow	Very high
		BOYLE	30	> 72	None	Very limited	Very limited	Moderate	High
		ROCK OUTCROP	25	> 72	None	Very limited	Very limited	Slow	Very high
118	WILEY SILT LOAM, 1 TO 3 PERCENT SLOPES								
		WILEY	90	> 72	None	Not limited	Somewhat limited	Moderate	Low
119	WILEY SILT LOAM, 3 TO 5 PERCENT SLOPES								
		WILEY	85	> 72	None	Not limited	Somewhat limited	Moderate	Low
12	BALLER-ROCK OUTCROP COMPLEX, 15 TO 45 PERCENT SLOPES								
		BALLER	50	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Slow	Very high
120	ASCALON LOAM, 0 TO 6 PERCENT SLOPES								
		ASCALON	85	> 72	None	Somewhat limited	Somewhat limited	Moderate	Low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
121	BOYLE-BOYLE, THIN SOLUM, GRAVELLY LOAMS, 3 TO 6 PERCENT SLOPES								
		BOYLE	55	> 72	None	Very limited	Very limited	Moderate	Medium
		BOYLE	40	> 72	None	Very limited	Very limited	Moderately slow	Medium
122	BOYLE-ROCK OUTCROP-CATHEDRAL COMPLEX, 5 TO 45 PERCENT SLOPES								
		BOYLE	40	> 72	None	Very limited	Very limited	Moderately slow	Medium
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Slow	Very high
		CATHEDRAL	20	> 72	None	Very limited	Very limited	Moderately slow	Medium
123	CATHEDRAL-BOYLE COMPLEX, 10 TO 30 PERCENT SLOPES								
		CATHEDRAL	50	> 72	None	Very limited	Very limited	Moderately slow	Medium
		BOYLE	35	> 72	None	Very limited	Very limited	Moderately slow	High
124	EVANSTON LOAM, 0 TO 6 PERCENT SLOPES								
		EVANSTON	90	> 72	None	Somewhat limited	Somewhat limited	Moderate	Low
125	EVANSTON-IPSON ASSOCIATION, 3 TO 20 PERCENT SLOPES								
		EVANSTON	60	> 72	None	Somewhat limited	Somewhat limited	Moderate	Medium
		IPSON	25	> 72	None	Somewhat limited	Very limited	Moderate	Medium
126	IPSON-EVANSTON COMPLEX, 6 TO 30 PERCENT SLOPES								
		IPSON	50	> 72	None	Very limited	Very limited	Moderate	High
		EVANSTON	40	> 72	None	Somewhat limited	Very limited	Moderate	Medium
127	IPSON-TRIMAD COMPLEX, 15 TO 45 PERCENT SLOPES								
		IPSON	50	> 72	None	Very limited	Very limited	Moderate	High
		TRIMAD	30	> 72	None	Very limited	Very limited	Moderate	High
128	MERDEN, COOL-KOVICH COMPLEX, 0 TO 3 PERCENT SLOPES								
		MERDEN	60	12-72	None	Very limited	Very limited	Slow	High
		KOVICH	35	12-72	None	Very limited	Very limited	Moderate	Low
129	POPOSHIA-TRIMAD COMPLEX, 3 TO 15 PERCENT SLOPES								
		POPOSHIA	50	> 72	None	Not limited	Somewhat limited	Moderate	Medium
		TRIMAD	40	> 72	None	Somewhat limited	Very limited	Moderate	Medium

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
13	BLACKWELL CLAY LOAM, 0 TO 5 PERCENT SLOPES								
		BLACKWELL	75	15-72	Occasional	Very limited	Very limited	Moderately slow	Medium
130	REDTHAYNE-TYZAK-ROCK OUTCROP COMPLEX, 15 TO 45 PERCENT SLOPES								
		REDTHAYNE	40	> 72	None	Very limited	Very limited	Moderate	High
		TYZAK	30	> 72	None	Very limited	Very limited	Moderately slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Moderately slow	Very high
131	TIESIDE, NORTH SLOPES-ROCK OUTCROP COMPLEX, 10 TO 45 PERCENT SLOPES								
		TIESIDE	70	> 72	None	Very limited	Very limited	Moderately slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Moderately slow	Very high
132	TRIMAD-BLAZON, THIN SOLUM-ROCK OUTCROP COMPLEX, 20 TO 45 PERCENT SLOPES								
		TRIMAD	45	> 72	None	Very limited	Very limited	Moderate	High
		BLAZON	30	> 72	None	Very limited	Very limited	Moderately slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Slow	Very high
133	TYZAK-TYZAK, THIN SOLUM-ROCK OUTCROP COMPLEX, 30 TO 50 PERCENT SLOPES								
		TYZAK	40	> 72	None	Very limited	Very limited	Moderately slow	Very high
		TYZAK	30	> 72	None	Very limited	Very limited	Moderately slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Slow	Very high
134	WEED LOAM, 0 TO 6 PERCENT SLOPES								
		WEED	90	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	Medium
136	WATER								
		WATER	95	> 72	Not Rated	Very limited	Very limited	NA	Not Rated
14	BOYLE GRAVELLY SANDY LOAM, 3 TO 9 PERCENT SLOPES								
		BOYLE	85	> 72	None	Very limited	Very limited	Moderate	Medium
15	BOYLE GRAVELLY SANDY LOAM, 9 TO 30 PERCENT SLOPES								
		BOYLE	80	> 72	None	Very limited	Very limited	Moderate	High
16	BOYLE-RATAKE GRAVELLY SANDY LOAMS, 1 TO 9 PERCENT SLOPES								
		BOYLE	50	> 72	None	Very limited	Very limited	Moderate	Low
		RATAKE	30	> 72	None	Very limited	Very limited	Slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
17	BOYLE-RATAKE GRAVELLY SANDY LOAMS, 9 TO 25 PERCENT SLOPES								
		BOYLE	40	> 72	None	Very limited	Very limited	Moderate	Medium
		RATAKE	35	> 72	None	Very limited	Very limited	Slow	Very high
18	BREECE COARSE SANDY LOAM, 0 TO 3 PERCENT SLOPES								
		BREECE	95	> 72	None	Not limited	Very limited	Moderately rapid	Very low
19	BREECE COARSE SANDY LOAM, 3 TO 9 PERCENT SLOPES								
		BREECE	95	> 72	None	Not limited	Very limited	Moderately rapid	Low
2	ALTVAN LOAM, 3 TO 9 PERCENT SLOPES								
		ALTVAN	80	> 72	None	Not limited	Very limited	Moderate	Medium
20	BREECE COARSE SANDY LOAM, 9 TO 30 PERCENT SLOPES								
		BREECE	90	> 72	None	Very limited	Very limited	Moderately rapid	Medium
21	CARNERO LOAM, 3 TO 9 PERCENT SLOPES								
		CARNERO	90	> 72	None	Very limited	Very limited	Slow	Very high
22	CARUSO CLAY LOAM, 0 TO 1 PERCENT SLOPE								
		CARUSO	85	36-72	Occasional	Very limited	Very limited	Slow	High
23	CLERGERN FINE SANDY LOAM, 2 TO 10 PERCENT SLOPES								
		CLERGERN	80	> 72	None	Not limited	Very limited	Moderately rapid	Low
24	CONNERTON-BARNUM COMPLEX, 0 TO 3 PERCENT SLOPES								
		CONNERTON	50	> 72	None	Not limited	Not limited	Moderately slow	Medium
		BARNUM	40	> 72	Occasional	Very limited	Very limited	Moderate	Low
25	CONNERTON-BARNUM COMPLEX, 3 TO 9 PERCENT SLOPES								
		CONNERTON	60	> 72	None	Not limited	Somewhat limited	Moderately slow	High
		BARNUM	25	> 72	Occasional	Very limited	Very limited	Moderate	Low
26	CUSHMAN FINE SANDY LOAM, 0 TO 3 PERCENT SLOPES								
		CUSHMAN	90	> 72	None	Somewhat limited	Very limited	Slow	Medium
27	CUSHMAN FINE SANDY LOAM, 3 TO 9 PERCENT SLOPES								
		CUSHMAN	90	> 72	None	Somewhat limited	Very limited	Slow	High
28	DRIGGS LOAM, 0 TO 3 PERCENT SLOPES								
		DRIGGS	95	> 72	None	Not limited	Very limited	Moderate	Low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
29	DRIGGS LOAM, 3 TO 25 PERCENT SLOPES								
		DRIGGS	95	> 72	None	Somewhat limited	Very limited	Moderate	Medium
3	ALTVAN-SATANTA LOAMS, 0 TO 3 PERCENT SLOPES								
		ALTVAN	45	> 72	None	Not limited	Very limited	Moderate	Low
		SATANTA	30	> 72	None	Not limited	Somewhat limited	Moderate	Low
30	ELBETH-MOEN LOAMS, 5 TO 30 PERCENT SLOPES								
		ELBETH	45	> 72	None	Somewhat limited	Very limited	Moderate	Medium
		MOEN	35	> 72	None	Very limited	Very limited	Slow	Very high
31	FARNUF LOAM, 2 TO 10 PERCENT SLOPES								
		FARNUF	95	> 72	None	Not limited	Somewhat limited	Moderate	Medium
32	FARNUF-BOYLE-ROCK OUTCROP COMPLEX, 10 TO 25 PERCENT SLOPES								
		FARNUF	40	> 72	None	Somewhat limited	Very limited	Moderate	Medium
		BOYLE	30	> 72	None	Very limited	Very limited	Moderate	Medium
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Slow	Very high
33	FLUVAQUENTS, NEARLY LEVEL								
		FLUVAQUENTS	90	27-72	Frequent	Very limited	Very limited	Moderately rapid	Very low
34	FORT COLLINS LOAM, 0 TO 1 PERCENT SLOPES								
		FORT COLLINS	85	> 72	None	Not limited	Somewhat limited	Moderate	Low
35	FORT COLLINS LOAM, 1 TO 3 PERCENT SLOPES								
		FORT COLLINS	85	> 72	None	Not limited	Somewhat limited	Moderate	Low
36	FORT COLLINS LOAM, 3 TO 5 PERCENT SLOPES								
		FORT COLLINS	90	> 72	None	Not limited	Somewhat limited	Moderate	Low
37	FORT COLLINS LOAM, 5 TO 9 PERCENT SLOPES								
		FORT COLLINS	85	> 72	None	Not limited	Very limited	Moderate	Medium
38	FOXCREEK LOAM, 0 TO 3 PERCENT SLOPES								
		FOXCREEK	85	21-72	Rare	Very limited	Very limited	Moderate	Low
39	GAPO CLAY LOAM, 0 TO 5 PERCENT SLOPES								
		GAPO	90	24-72	None	Very limited	Very limited	Slow	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
4	ALTVAN-SATANTA LOAMS, 3 TO 9 PERCENT SLOPES								
		ALTVAN	55	> 72	None	Not limited	Very limited	Moderate	Medium
		SATANTA	35	> 72	None	Not limited	Somewhat limited	Moderate	Medium
40	GARRETT LOAM, 0 TO 1 PERCENT SLOPES								
		GARRETT	85	> 72	None	Somewhat limited	Very limited	Moderate	Low
41	GARRETT LOAM, 1 TO 3 PERCENT SLOPES								
		GARRETT	85	> 72	None	Somewhat limited	Very limited	Moderate	Low
42	GRAVEL PITS								
		GRAVEL PITS	95	> 72	None	Not limited	Very limited	Rapid	Negligible
43	HAPLOBOROLLS-ROCK OUTCROP COMPLEX, STEEP								
		HAPLOBOROLLS	55	> 72	None	Very limited	Very limited	Slow	High
44	HAPLUSTOLLS, HILLY								
		HAPLUSTOLLS	95	> 72	None	Very limited	Very limited	Moderate	High
45	HAPLUSTOLLS-ROCK OUTCROP COMPLEX, STEEP								
		HAPLUSTOLLS	65	> 72	None	Very limited	Very limited	Moderate	Medium
		ROCK OUTCROP	25	> 72	None	Very limited	Very limited	Slow	Very high
46	HARLAN FINE SANDY LOAM, 1 TO 3 PERCENT SLOPES								
		HARLAN	80	> 72	None	Not limited	Somewhat limited	Moderate	Low
47	HARLAN FINE SANDY LOAM, 3 TO 9 PERCENT SLOPES								
		HARLAN	80	> 72	None	Not limited	Somewhat limited	Moderate	Medium
48	HELDT CLAY LOAM, 0 TO 3 PERCENT SLOPES								
		HELDT	90	> 72	None	Very limited	Not limited	Slow	High
49	HELDT CLAY LOAM, 3 TO 6 PERCENT SLOPES								
		HELDT	85	> 72	None	Very limited	Somewhat limited	Slow	Very high
5	AQUEPTS, LOAMY								
		AQUEPTS	80	12-72	Rare	Very limited	Very limited	Very rapid	Negligible
50	KEITH SILTY CLAY LOAM, 0 TO 3 PERCENT SLOPES								
		KEITH	85	> 72	None	Not limited	Somewhat limited	Moderately slow	Medium
51	KILDOR CLAY LOAM, 0 TO 6 PERCENT SLOPES								
		KILDOR	85	> 72	None	Very limited	Very limited	Slow	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
52	KILDOR-SHALE OUTCROP COMPLEX, 5 TO 30 PERCENT SLOPES								
		KILDOR	45	> 72	None	Very limited	Very limited	Slow	Very high
		SHALE OUTCROP	40	> 72	None	Very limited	Very limited	Slow	Very high
53	KIM LOAM, 1 TO 3 PERCENT SLOPES								
		KIM	90	> 72	None	Not limited	Somewhat limited	Moderate	Low
54	KIM LOAM, 3 TO 5 PERCENT SLOPES								
		KIM	90	> 72	None	Not limited	Somewhat limited	Moderate	Low
55	KIM LOAM, 5 TO 9 PERCENT SLOPES								
		KIM	85	> 72	None	Not limited	Very limited	Moderate	Medium
56	KIM-THEDALUND LOAMS, 3 TO 15 PERCENT SLOPES								
		KIM	45	> 72	None	Not limited	Somewhat limited	Moderate	Medium
		THEDALUND	35	> 72	None	Somewhat limited	Very limited	Moderate	Medium
57	KIRTLEY LOAM, 3 TO 9 PERCENT SLOPES								
		KIRTLEY	85	> 72	None	Somewhat limited	Very limited	Slow	High
58	KIRTLEY-PURNER COMPLEX, 5 TO 20 PERCENT SLOPES								
		KIRTLEY	45	> 72	None	Somewhat limited	Very limited	Slow	High
		PURNER	40	> 72	None	Very limited	Very limited	Slow	Very high
59	LAPORTE-ROCK OUTCROP COMPLEX, 3 TO 30 PERCENT SLOPES								
		LAPORTE	45	> 72	None	Very limited	Very limited	Moderate	Medium
		ROCK OUTCROP	35	> 72	None	Very limited	Very limited	Slow	Very high
6	AQUEPTS, PONDED								
		AQUEPTS	90	9-72	Frequent	Very limited	Very limited	Very rapid	Negligible
60	LARIM GRAVELLY SANDY LOAM, 5 TO 40 PERCENT SLOPES								
		LARIM	85	> 72	None	Very limited	Very limited	Moderate	High
61	LARIMER FINE SANDY LOAM, 1 TO 3 PERCENT SLOPES								
		LARIMER	85	> 72	None	Not limited	Very limited	Moderate	Low
62	LARIMER-STONEHAM COMPLEX, 3 TO 10 PERCENT SLOPES								
		LARIMER	35	> 72	None	Not limited	Very limited	Moderate	Medium
		STONEHAM	25	> 72	None	Not limited	Very limited	Moderate	Low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
63	LONGMONT CLAY, 0 TO 3 PERCENT SLOPES								
		LONGMONT	85	27-72	Occasional	Very limited	Very limited	Slow	High
64	LOVELAND CLAY LOAM, 0 TO 1 PERCENT SLOPES								
		LOVELAND	90	27-72	Occasional	Very limited	Very limited	Moderately slow	Medium
65	MIDWAY CLAY LOAM, 5 TO 25 PERCENT SLOPES								
		MIDWAY	90	> 72	None	Very limited	Very limited	Slow	Very high
66	MINNEQUA SILT LOAM, 3 TO 9 PERCENT SLOPES								
		MINNEQUA	85	> 72	None	Somewhat limited	Very limited	Moderate	Medium
67	MINNEQUA-LAPORTE COMPLEX, 3 TO 15 PERCENT SLOPES								
		MINNEQUA	55	> 72	None	Somewhat limited	Very limited	Moderate	Medium
		LAPORTE	30	> 72	None	Very limited	Very limited	Moderate	Medium
68	MIRACLE SANDY LOAM, 5 TO 25 PERCENT SLOPES								
		MIRACLE	90	> 72	None	Very limited	Very limited	Slow	High
69	NAZ SANDY LOAM, 1 TO 3 PERCENT SLOPES								
		NAZ	90	> 72	None	Not limited	Very limited	Moderately rapid	Very low
7	ASCALON SANDY LOAM, 0 TO 3 PERCENT SLOPES								
		ASCALON	90	> 72	None	Not limited	Very limited	Moderate	Low
70	NAZ SANDY LOAM, 3 TO 25 PERCENT SLOPES								
		NAZ	90	> 72	None	Somewhat limited	Very limited	Moderately rapid	Low
71	NELSON FINE SANDY LOAM, 3 TO 9 PERCENT SLOPES								
		NELSON	85	> 72	None	Somewhat limited	Very limited	Moderate	Low
72	NEWFORK SANDY LOAM, 0 TO 3 PERCENT SLOPE								
		NEWFORK	90	12-72	Occasional	Very limited	Very limited	Moderately rapid	Very low
73	NUNN CLAY LOAM, 0 TO 1 PERCENT SLOPE								
		NUNN	85	> 72	None	Very limited	Not limited	Slow	High
74	NUNN CLAY LOAM, 1 TO 3 PERCENT SLOPES								
		NUNN	85	> 72	None	Very limited	Not limited	Slow	High
75	NUNN CLAY LOAM, 3 TO 5 PERCENT SLOPES								
		NUNN	85	> 72	None	Very limited	Somewhat limited	Slow	High
76	NUNN CLAY LOAM, WET, 1 TO 3 PERCENT SLOPES								
		NUNN	90	30-72	Rare	Very limited	Very limited	Moderately slow	Medium

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
77	OTERO SANDY LOAM, 0 TO 3 PERCENT SLOPES								
		OTERO	85	> 72	None	Not limited	Very limited	Moderately rapid	Very low
78	OTERO SANDY LOAM, 3 TO 5 PERCENT SLOPES								
		OTERO	85	> 72	None	Not limited	Very limited	Moderately rapid	Very low
79	OTERO SANDY LOAM, 5 TO 9 PERCENT SLOPES								
		OTERO	80	> 72	None	Not limited	Very limited	Moderately rapid	Low
8	ASCALON SANDY LOAM, 3 TO 5 PERCENT SLOPES								
		ASCALON	90	> 72	None	Not limited	Very limited	Moderate	Low
80	OTERO-NELSON SANDY LOAMS, 3 TO 25 PERCENT SLOPES								
		OTERO	50	> 72	None	Somewhat limited	Very limited	Moderately rapid	Low
		NELSON	35	> 72	None	Very limited	Very limited	Moderate	Low
81	PAOLI FINE SANDY LOAM, 0 TO 1 PERCENT SLOPES								
		PAOLI	85	> 72	None	Not limited	Very limited	Moderately rapid	Very low
82	PENDERGRASS-ROCK OUTCROP COMPLEX, 15 TO 25 PERCENT SLOPES								
		PENDERGRASS	50	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	35	> 72	None	Very limited	Very limited	Slow	Very high
83	PINATA-ROCK OUTCROP COMPLEX, 15 TO 45 PERCENT SLOPES								
		PINATA	50	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	35	> 72	None	Very limited	Very limited	Slow	Very high
84	POUDRE FINE SANDY LOAM, 0 TO 1 PERCENT SLOPE								
		POUDRE	85	24-72	Occasional	Very limited	Very limited	Moderately rapid	Very low
85	PURNER FINE SANDY LOAM, 1 TO 9 PERCENT SLOPES								
		PURNER	85	> 72	None	Very limited	Very limited	Slow	Very high
86	PURNER-ROCK OUTCROP COMPLEX, 10 TO 50 PERCENT SLOPES								
		PURNER	55	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Slow	Very high
87	RATAKE-ROCK OUTCROP COMPLEX, 25 TO 55 PERCENT SLOPES								
		RATAKE	60	> 72	None	Very limited	Very limited	Moderate	High
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Moderately slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
88	REDFEATHER SANDY LOAM, 5 TO 50 PERCENT SLOPES								
		REDFEATHER	85	> 72	None	Very limited	Very limited	Slow	Very high
89	RENOHILL CLAY LOAM, 0 TO 3 PERCENT SLOPES								
		RENOHILL	85	> 72	None	Somewhat limited	Very limited	Slow	High
9	BAINVILLE-EPPING SILT LOAMS, 5 TO 20 PERCENT SLOPES								
		BAINVILLE	45	> 72	None	Somewhat limited	Very limited	Slow	High
		EPPING	35	> 72	None	Very limited	Very limited	Slow	Very high
90	RENOHILL CLAY LOAM, 3 TO 9 PERCENT SLOPES								
		RENOHILL	85	> 72	None	Somewhat limited	Very limited	Slow	Very high
91	RENOHILL-MIDWAY CLAY LOAMS, 3 TO 15 PERCENT SLOPES								
		RENOHILL	55	> 72	None	Very limited	Very limited	Slow	Very high
		MIDWAY	30	> 72	None	Very limited	Very limited	Slow	Very high
92	RIVERWASH								
		RIVERWASH	100	> 72	Frequent	Very limited	Very limited	Rapid	Negligible
93	ROCK OUTCROP								
		ROCK OUTCROP	100	> 72	None	Very limited	Very limited	Moderately slow	Very high
94	SATANTA LOAM, 0 TO 1 PERCENT SLOPES								
		SATANTA	85	> 72	None	Not limited	Somewhat limited	Moderate	Low
95	SATANTA LOAM, 1 TO 3 PERCENT SLOPES								
		SATANTA	85	> 72	None	Not limited	Somewhat limited	Moderate	Low
96	SATANTA LOAM, 3 TO 5 PERCENT SLOPES								
		SATANTA	80	> 72	None	Not limited	Somewhat limited	Moderate	Low
97	SATANTA LOAM, GULLIED, 3 TO 9 PERCENT SLOPES								
		SATANTA	90	> 72	None	Not limited	Somewhat limited	Moderate	Medium
98	SATANTA VARIANT CLAY LOAM, 0 TO 3 PERCENT SLOPES								
		SATANTA VARIANT	90	36-72	Occasional	Very limited	Very limited	Slow	High
99	SCHOFIELD-REDFEATHER-ROCK OUTCROP COMPLEX, 5 TO 25 PERCENT SLOPES								
		SCHOFIELD	40	> 72	None	Very limited	Very limited	Slow	High
		REDFEATHER	30	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Moderately slow	Very high