

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD**

IRRIGATION FIELD DITCH

(Ft.)

CODE 388

DEFINITION

A permanent irrigation ditch constructed to convey water from the source of supply to a field or fields in a farm distribution system.

PURPOSE

To prevent erosion or loss of water quality or damage to the land, to make possible proper irrigation water use, and to efficiently convey water to minimize conveyance losses.

CONDITIONS WHERE PRACTICE APPLIES

This standard applies to open channels and elevated ditches of 25 cubic feet per second (cfs) or less capacity formed in and with earth materials. It does not include canals and laterals or ditches constructed and removed during a season and ditches shaped or constructed for lining installations or irrigation canals or laterals that deliver water to a farm.

Field ditches shall be planned and located as integral parts of an irrigation water distribution system designed to facilitate the conservation use of soil and water resources.

Water quality supply and delivery for the area served shall be sufficient to make irrigation practical for the crops to be grown and the irrigation water application methods to be used.

Field ditches shall be constructed in earth material that contains enough fines to prevent excessive seepage losses and where shrinkage cracks will not endanger the ditch. The sealing effect of sediment carried in the irrigation water may be considered.

CRITERIA

General Criteria Applicable to All Purposes

Laws, rules, and regulations. This practice shall conform to all federal, state, and local laws, rules, and regulations. Laws, rules, and regulations of particular concern include those involving water rights, land use, pollution control, property easements, wetlands, preservation of cultural resources, and endangered species.

Capacity requirements. Field ditches shall have the capacity to deliver to the field a flow adequate to meet the following:

- The design peak consumptive use of the crops to be grown in the field with proper provisions made for the expected field irrigation efficiency
- The largest irrigation stream required for the irrigation methods planned for the field

The capacity shall be increased further to provide for the additional flow required to compensate for the ditch seepage loss and to safely carry surface runoff from adjacent lands that must be transported to wasteways or overflow points. For capacity design, Manning's equation roughness coefficient "n" value shall be selected according to the material in which the ditch is constructed, the alignment and hydraulic radius, and additional retardance because of weeds or moss.

Velocities. Field ditches shall be designed to develop velocities that are non-erosive for the soil materials through which they pass. Local information on the velocity limit for specific soils shall be used when available. When such information is not available, the maximum design velocity shall not exceed that shown in Figure 6-2 in Chapter 6 of Technical Release No. 25 and Table 14-3 in Chapter 14 of National

Engineering Handbook Part 650, Engineering Field Handbook.

Field ditches shall be designed with enough capacity to carry the required flows at the velocities that will be developed under the maximum probable retardance conditions.

For checking designs to see that velocities will not exceed permissible values, a Manning's "n" value no greater than 0.025 shall be used and applicable criteria in the Conservation Practice Standard 582, Open Channel, shall be followed.

Cross section. Freeboard in field ditches shall be not less than one-third of the maximum design depth of water. Side slopes shall be stable. The top width of banks as measured at the elevation providing the required freeboard shall be not less than 1 foot and shall equal or exceed the flow depth.

If a field ditch is to be constructed on an embankment, the side slopes of the embankment shall not be steeper than:

Height to Water Surface on Centerline of Fill	Steepest Allowable Side Slope of Fill
Less than 3 feet	1½:1
3-6 feet	2:1
More than 6 feet	2½:1

Water surface elevations. All field ditches shall be designed so that the water surface elevations at field takeout points are high enough to provide the required flow onto the field surface. If ditch checks or other control structures are to be used to provide the necessary head, the backwater effect must be considered in computing freeboard requirements. The required elevation of the water surface above the field surface will vary with the type of takeout structure or device used and the amount of water to be delivered through each. A minimum head of 4 inches shall be provided.

Related structures. Erosion- or water-control structures, culverts, diversions, or other related structures needed to supplement the field ditch shall be designed and installed to meet conservation practice standards for the particular structure and type of construction.

Vegetation. All excavated areas and side slopes of the embankment shall be seeded.

Seedbed preparation, seeding, fertilizing, and mulching shall comply with Conservation Practice Standard 342, Critical Area Planting.

CONSIDERATIONS

Water Quantity. Consider the following:

- Effects on the water budget, especially on volumes and rates of runoff, infiltration, evaporation, transpiration, and deep percolation.
- Potential for a change in plant growth and transpiration because of changes in the volume or level of soil water.
- Effects on downstream flows or aquifers that would affect other water uses or users.
- Effect on the water table of the field in providing suitable rooting depth for anticipated land uses.

Water Quality. Consider the following:

- Effects on erosion and the movement of sediment, and the soluble and sediment attached substances carried by runoff.
- Effects on the movement of dissolved substances to ground water.
- Short-term and construction-related effects on the quality of downstream water courses.
- Potential for uncovering or redistributing toxic material.
- Effects on wetlands or water-related wildlife habitats.
- Effects on the visual quality of water resources.
- Effects of water level control on salinity of soils, soil water, or downstream water.

PLANS AND SPECIFICATIONS

Plans and specifications for constructing irrigation field ditches shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purposes.

OPERATION AND MAINTENANCE

An operation and maintenance plan shall be developed and reviewed with the landowner or individual responsible for operation and maintenance. The plan shall adequately guide in the routine maintenance and operational needs of the irrigation field ditch. The plan shall also include guidance on periodic inspections and post-storm inspections to detect and minimize damage to the practice.