

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD**

IRRIGATION REGULATING RESERVOIR

(No.)

CODE 552

DEFINITION

A small storage reservoir constructed to regulate an irrigation water supply.

PURPOSE

Collect and store water for a relatively short period of time to:

- Improve irrigation water management by regulating fluctuating flows in streams, canals, or from pumping plants.
- Provide storage for tailwater recovery and reuse.
- Improve off-site water quality.

CONDITIONS WHERE PRACTICE APPLIES

This standard applies to reservoirs created by impoundment structures and excavated pits for short-term storage of diverted surface water, water from pumped or flowing wells, or water from an irrigation delivery system. This standard applies to structures designed primarily for flow control or those designed to store water for only a few hours or a few days.

This standard applies to sites meeting the following applicable conditions:

1. The existing available irrigation stream is of such size that regulation is necessary to accomplish the intended purposes (for example, low yield irrigation wells where collection facilities are needed for efficient irrigation application).
2. Water must be stored to be used between times of rotation delivery.

3. An adequate and dependable volume of good quality water is or can be made available by storage.
4. Topographic, geologic, and soil conditions are suitable for practical construction of a regulating reservoir having adequate storage capacity, and any pervious soils in the reservoir area can be sealed to ensure seepage losses are not excessive.
5. If surface runoff enters the reservoir, the contributing drainage area is or can be protected against erosion so that normal sedimentation does not materially shorten planned reservoir life.

This standard pertains to the planning and functional design of irrigation regulating reservoirs. It does not include detailed design criteria or construction specifications for individual regulating reservoirs or components of the regulating facility.

This standard also applies to regulating reservoirs constructed of concrete, steel, and other suitable materials used to collect water from two or more irrigation wells for use in irrigation systems.

CRITERIA

General Criteria Applicable to All Purposes

This practice shall conform to all federal, state, and local laws, rules, and regulations. Laws, rules, and regulations of particular concern include those involving water rights, land use, pollution control, property easements, wetlands, preservation of cultural resources, and endangered species.

Criteria for design of components not addressed in conservation practice standards shall be consistent with sound engineering principles.

Irrigation regulating reservoirs created by earthen pits or embankments shall be designed according to Conservation Practice Standard 378, Pond.

Regulating reservoirs constructed of materials other than earth shall be designed according to sound engineering principles for the material being used.

Pumping plants installed to serve irrigation regulating reservoirs shall be designed according to Conservation Practice Standard 533, Pumping Plant.

Where additional storage is required to provide for sediment deposition, storage facilities shall be sized accordingly. Allowable retention times shall be site-specific to the particular soil types.

Additional Criteria Applicable to Regulating Fluctuating Flows in Streams, Canals, or from Pumping Plants

Capacity. Irrigation regulating reservoirs shall have a usable capacity sufficient to permit the existing irrigation stream to be regulated so that irrigation water can be applied with a reasonably high efficiency. In computing capacity requirements, consideration shall be given to diverted inflow, surface runoff, precipitation, evaporation, and seepage (as applicable). Excessive seepage losses shall be prevented by the use of an adapted method of sealing or lining. Additional capacity shall be provided, as necessary, for sediment storage.

Capacity requirements for regulating reservoirs used as part of a system for collecting water from 2 or more wells shall be based on the discharge capacities of the contributing wells and on the operation frequency of the irrigation system.

Inlet protection. Reservoir embankment or excavated side slopes at inlets shall be protected from erosion by use of pipe inlets or other suitable structures. Inlet structure capacity shall be adequate to accommodate the design inflow rate.

Overflow protection. An overflow protection structure having a capacity equal to or greater

than the inlet stream shall be provided for an enclosed embankment. This structure may be designed and installed in combination with the outlet works.

Outlet works. Outlet works shall be provided for the controlled release of irrigation water. The outlet works may consist of a gated conduit through or over the embankment for gravity flow to the irrigated area or to a pumping plant. They may also consist of a pumping plant designed to lift water directly from the reservoir basin.

The capacity of the outlet works shall be adequate to provide the outflow rate needed to meet peak period irrigation system demands.

Additional Criteria Applicable to Storage for Tailwater Recovery and Reuse

Irrigation regulating reservoirs used in irrigation tailwater recovery and reuse systems are often referred to as tailwater pits or sumps.

Capacity. Capacity requirements for irrigation regulating reservoirs for tailwater recovery shall be based on irrigation system runoff volume and rate as well as required level of water control at the point tailwater is returned to the irrigation system. Excessive seepage losses shall be prevented by the use of an adapted method of sealing or lining.

For systems where tailwater is discharged into an irrigation pit or regulating reservoir or into a pipeline having facilities for regulating fluctuating flows (for example, a float valve), small pits or sumps with frequently cycling pumping plants may be used. For systems unable to regulate flows, tailwater sumps or pits shall be made large enough to provide the regulation needed to permit efficient use of the water.

When energy sources for tailwater pump back systems are subject to interruption, safe auxiliary bypass areas cannot be provided, or tailwater discharges violate local or state regulations, tailwater storage requirements shall (as a minimum) include a volume adequate to store the complete runoff from a single irrigation set.

Inlet protection. Sumps and pits shall be equipped with inlets designed to protect side slopes and collection facilities from erosion. A dike, ditch, or water control structure shall be provided (if required by state law) to limit the

entrance of rainfall runoff into the designed inlet. Sediment traps shall be installed as needed.

Refer to Conservation Practice Standard 447, Irrigation System, Tailwater Recovery, for other design requirements.

Additional Criteria Applicable to Improving Water Quality

Capacity. Where additional storage and/or flow regulation is required to provide adequate retention time for breakdown of chemicals in runoff waters, storage facilities shall be sized accordingly. Allowable retention times shall be site-specific to the particular chemical of concern.

Seepage from irrigation regulating reservoirs shall be controlled to the extent practical when the facility is expected to receive chemical-laden waters. Control may be in the form of natural soil liners, soil additives, commercial liners, or other approved methods.

Inlet protection. Reservoir embankment or excavated side slopes at inlets shall be protected from erosion by use of pipe inlets or other suitable structures. Inlet structure capacity shall be adequate to accommodate the design inflow rate.

CONSIDERATIONS

When planning this practice the following items should be considered, as applicable:

- Effects of erosion and the movement of sediment, pathogens, and the soluble and sediment-attached substances carried by runoff.
- Short-term and construction-related effects on quality of downstream watercourses.
- Potential of uncovering or redistributing toxic material.

Consideration should also be given to the effects on the following:

- The water budget, especially on volume and rate of runoff, infiltration, evaporation, transpiration, deep percolation, and ground water recharge.
- Downstream flows or aquifers that would affect other water uses or users.

- The movement of dissolved substances to ground water.
- Wetlands or water-related wildlife habitats.
- Cultural resources.

PLANS AND SPECIFICATIONS

Plans and specifications for irrigation regulating reservoirs shall be in keeping with this standard and shall describe the requirements for properly installing the practice to achieve its intended purpose.

OPERATION AND MAINTENANCE

An operation and maintenance plan specific to facilities installed shall be prepared for use by the landowner or operator. The plan shall be reviewed with the landowner or individual responsible for operation and maintenance.

The plan should provide specific instructions for operating and maintaining facilities to ensure they function properly. The plan shall include provisions to address the following, as a minimum:

- Periodic cleaning and re-grading of collection facilities to maintain proper flow lines and functionality.
- Periodic checks and removal of debris as necessary from inlet and outlet structures to assure proper operation.
- Periodic removal of sediment from traps and/or storage facilities to maintain design capacity and efficiency.
- Inspection or testing of all pipelines and pumping plant components and appurtenances, as applicable.
- Routine maintenance of all mechanical components in accordance with manufacturer recommendations.
- Periodic inspection and maintenance of embankments including control of erosion and undesirable vegetation.
- Periodic water quality analysis as necessary to evaluate nutrients, pesticides, and pathogens.