

NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD

**IRRIGATION WATER CONVEYANCE
DITCH AND CANAL LINING, PLAIN CONCRETE (FEET)**

CODE 428A

DEFINITION

A fixed lining of impervious material installed in an existing or newly constructed irrigation field ditch or irrigation canal or lateral.

drainage facilities are installed with or before the lining. These linings shall not be installed on sites susceptible to severe frost heave or on sites where experience has indicated that the sulfate salt concentration in the soil causes rapid deterioration of concrete.

PURPOSE

- Improve management of irrigation water
- Prevent waterlogging of land
- Maintain water quality
- Prevent erosion
- Reduce water loss

CRITERIA

This practice shall conform to all Federal, State, Tribal and local laws and regulations. Laws and regulations of particular concern include those involving water rights, land use, pollution control, property easements, wetlands, preservation of cultural resources, and endangered species.

General. Plain concrete linings installed under the practice standard shall be limited to ditches or canals with:

- a bottom width not greater than 6 feet,
- flow capacity equal to or less than 200 cubic feet per second, and
- design velocity equal to or less than 15 feet per second.

CONDITIONS WHERE PRACTICE APPLIES

Ditches and canals to be lined shall serve as integral parts of an irrigation water distribution or conveyance system designed to facilitate the conservation use of soil and water resources on a farm or group of farms.

Materials. On sites where sulfate concentrations exist, concrete linings may be used only if they are made using special sulfate-resistant cement in accordance with those shown in Table 1.

Water supplies and irrigation deliveries for the area served shall be sufficient to make irrigation practical for the crops to be grown and the irrigation water application methods to be used.

Fly ash can be used to replace up to 15 percent (%) of the cement, by weight when other pozzolans are not used.

Lined ditches and canals shall be located where they are not susceptible to damage from side drainage flooding, or they shall be protected from such damage.

Air-entrainment admixture is recommended to improve workability and reduce damage due to

Plain concrete linings shall be installed only in well-drained soils or on sites where subgrade

**NRCS, MT
March 2005**

Conservation practice standards are reviewed periodically and updated if needed. To obtain the current version of this standard contact the Natural Resources Conservation Service.

NOTE: This type of font (AaBbCcDdEe 123..) indicates NRCS National Standards.
This type of font (AaBbCcDdEe 123..) indicates Montana Supplement.

428A - 2

freeze-thaw cycles. In-place, air content shall be **in the range of 4 to 7%** of the volume of concrete.

Table 1. Cement Requirements for Concrete Exposed to Sulfates

Water-soluble sulfate (SO ₄) percent by weight	Sulfate (as SO ₄) in water parts per million	Cement type ASTM C150 or C595
SO ₄ ≥ 0	SO ₄ ≥ 0	Any
SO ₄ ≥ 0.10	SO ₄ ≥ 150	II, IP(MS), IS(MS), P(MS), I(PM)(MS), I(SM)(MS)
SO ₄ ≥ 0.2	SO ₄ ≥ 1500	V
SO ₄ > 2.00	SO ₄ ≥ 10000	V plus pozzolan*

- Pozzolan known or shown to improve sulfate resistance in concrete with Type V cement

All materials described and required in this Standard shall meet or exceed the minimum requirements stated in the Field Office Technical Guide (FOTG), Section IV–Practice Standards and Specifications for MT-428-A.

Capacity. A lined ditch or canal shall have enough capacity to meet its requirement as part of the planned irrigation water distribution or conveyance system without damage or overtopping. Design capacity shall be based on the following, whichever is greater:

1. The capacity shall be enough to deliver water needed for irrigation to meet design peak consumptive use of crops.
2. The capacity shall be enough to provide an adequate irrigation system for all methods of irrigation planned.

For design purposes, the capacity shall be considered to be equal to the capacity as computed by Manning's Formula, using a coefficient of roughness, "n", of not less than 0.015.

Velocity. To avoid unstable surge flows, restrict design velocities in excess of 1.7 times the critical velocity to straight reaches that discharge into ditch sections or structures designed to reduce the velocity to less than critical velocity. Maximum velocity in these straight reaches shall be 15 ft/s.

The velocity in ditch reaches from which water is to be delivered onto the field through gates, turnouts, siphon tubes or by similar means shall be less than supercritical and sufficiently low to

permit operation of the planned takeout structure or device.

Freeboard. The required freeboard varies according to the ditch or canal, velocity of water, horizontal and vertical alignment, the amount of storm or wastewater that may be intercepted, and the change in water surface elevation that may occur when any control structure is operating. **The minimum freeboard of lining above the design water surface for any lined ditch or canal shall be .25 ft. for ≤ 25 cfs, .4 ft. for >25 cfs.**

Minimum freeboard requirement is based on assumption that the finished channel bottom elevation will vary no more than 0.1 ft. from design elevations. If a construction deviation greater than 0.1 ft. is permitted, the minimum freeboard shall be increased.

Additional freeboard shall be provided if required by velocity, depth of flow, alignment, obstruction, curves, and other site conditions.

Water surface elevations. All lined ditches and canals shall be designed so that water surface elevations at field takeout points are high enough to provide the required flow onto the field surface. If ditch checks or other control structures are to be used to provide necessary head, backwater effect must be considered in computing freeboard requirements.

The required elevation of the water surface above the field surface varies with the type of takeout structure or device used and the amounts of water to be delivered. A minimum head of 4 in. shall be provided. Where head is greater than 6 in. **with** erosive soils, exit velocity from gates, turnouts or siphon tubes may **require** devices to reduce **excess energy head.**

Lining thickness. Thickness of canal linings must be established on the basis of engineering consideration on each job. Location, canal size, velocity, subgrade conditions, method of construction, operation, and climate shall be evaluated in establishing thickness to be used. Minimum thickness for plain concrete linings in rectangular sections shall be 3½ in. For trapezoidal or parabolic sections, **the minimum thickness of canal linings shall be 3 inches for all design velocities.**

Ditch or canal side slopes. Plain concrete linings are generally used in ditches and canals that have either a trapezoidal or parabolic cross section.

They may be used in rectangular sections if the sidewall height is not greater than 1½ ft. Side slopes for usual construction methods shall not be steeper than shown below:

Hand-placed, formed concrete:

Height of lining less than 1½ ftVertical

Hand-placed, screeded concrete:

Height of lining less than 2½ ft3/4H to 1V*

Height of lining more than 2½ ft1H to 1V

Slip form concrete:

Height of lining less than 3 ft1H to 1V

Height of lining more than 3 ft1¼H to 1V

*H – Horizontal, V – Vertical

Ditch or canal banks. Ditch and canal banks shall be constructed with earth to at least the top edge of the lining. In cut sections, other than in rock, a berm shall be constructed not less than 2 in. above the top of the lining. Banks and berms shall be wide enough to ensure stability of fills and to prevent excessive deposition in cut sections. **Ditches in either cut or fill shall have a minimum berm of 2 feet on each side measured from the outside edge of the concrete.**

If the bank or berm is to be used as a roadway, the minimum top width shall be adequate for the purpose. Minimum recommended roadway width for straight sections is 12 ft.

Outside bank slopes and slopes above the berm elevation in cut sections must be flat enough to insure stability. A minimum slope is 2H to 1V is recommended. Where vegetation will be maintained by mowing, the minimum slope shall be 3H to 1V.

Related structures. Plans for ditch or canal lining installations shall provide for adequate inlets, outlets, turnouts, checks, crossings, and other related structures needed for successful conservation irrigation.

Structures shall be constructed or installed in such a way that the capacity or the freeboard of

the ditch is not reduced and the effectiveness of the lining is not impaired.

All structures shall meet applicable NRCS Conservation Practice Standard requirements for the type of structure used.

Vegetation. Disturbed areas not otherwise covered or protected, shall be established to grass as soon as practicable after construction is completed on the liner and related structures. Vegetation specifications shall comply with the local Field Office Technical Guide (FOTG), Section IV– Practice Standards and Specifications.

CONSIDERATIONS

Effects of downstream flows or aquifers that would affect other water usages or users.

Potential changes in growth and transpiration of vegetation located next to the conveyance because of elimination of leakage from the system.

Effects on the movement of dissolved substances into the groundwater.

Effects on wetlands or water-related wildlife habitats.

Effects on the visual quality of water resources.

Flow rates between 100 and 200 cfs, may require special design considerations, which include reinforcement, greater concrete thickness and higher freeboard.

Consider the addition of fiber reinforcement to increase durability and reduce the potential for minor cracking.

PLANS AND SPECIFICATIONS

Plans and specifications for installing plain concrete irrigation ditch and canal linings shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purpose.

Plans and Specifications are to be developed for each installation, and approved by the individual having design approval authority for the project.

428A - 4

Included within the plans and/or specifications shall be a process to pre-wash or clean all construction equipment used for installation of this practice to control noxious weeds, or other undesired vegetation as required by the landowner.

Safety items for the location and notification of owners of utilities shall be included in the plans and specifications following the procedures outlined in National Engineering Manual (NEM), Part 503, Safety.

OPERATION AND MAINTENANCE

An Operation and Maintenance (O&M) plan shall be developed for plain concrete irrigation ditch and canal linings. The plan should document needed actions to ensure that practices perform adequately throughout their expected life.

O&M requirements shall be determined as part of the design. Any requirements should be documented as brief statements in the plans, the specifications, or the conservation plan narrative, or as a separate O&M plan. Typical O&M may include sediment/debris removal, patching of cracked concrete, and replacement of deteriorated linings.