

NATURAL RESOURCES CONSERVATION SERVICE
MONTANA CONSERVATION PRACTICE STANDARD

WASTEWATER TREATMENT STRIP (ACRE)

CODE 635

DEFINITION

A treatment component of an agricultural waste management system consisting of a strip or area of herbaceous vegetation.

PURPOSE

The purpose of this practice is to improve water quality by reducing loading of nutrients, organics, pathogens, and other contaminants associated with animal manure and other wastes, and wastewater by treating agricultural wastewater and runoff from livestock holding areas with:

- Rapid infiltration
 - Overland flow
- or
- The slow rate process

CONDITIONS WHERE PRACTICE APPLIES

This practice applies:

- Where a treatment strip is a component of a planned agricultural waste management system
- Where a treatment strip can be constructed, operated and maintained without polluting air or water resources
- To the treatment of contaminated runoff from such areas as feedlots, barnyards, and other livestock holding areas
- To the treatment of dilute wastewater such as milk house effluent and diluted silage leachate

CRITERIA

General Criteria Applicable To All Purposes

The installation and operation of the wastewater treatment strip shall comply with all federal, state, tribal, and local laws, rules, and regulations. **Montana state law protects both surface and ground water from polluted runoff and percolation. A wastewater treatment strip shall follow Montana Department of Environmental Quality, Department Circular DEQ Number 9. DEQ Circular Number 9 is the minimum design requirements if there are any conflicts with this standard.**

Laws and regulations of particular concern include those involving land use, pollution control, property easements, wetlands, preservation of natural resources, and endangered species.

Inflow to wastewater treatment strips shall be pretreated. **As a minimum, a wastewater treatment strip shall be pretreated by a solid/liquid separation facility such as a settling basin prior to release of liquids to the wastewater treatment strip. A minimum detention time of 30 minutes is required to settle organic solids.**

Further design guidance for a wastewater treatment strip shall follow the Montana Supplement(s) to the National Engineering Handbook, Part 651, Agricultural Waste Management Field Handbook, Chapter 10, Design Methods. Chapter 10 defines that the designer should start with a settling basin that is approximately 5 percent of the surface area of the feedlot.

Discharge to and through treatment strips shall be as sheet flow. Some means, such as a ditch, curb, or gated pipe, shall be provided to disperse concentrated flow and ensure sheet flow across the width (dimension perpendicular to flow length) of the

NRCS, MT
June 2006

Conservation practice standards are reviewed periodically and updated if needed. To obtain the current version of this standard contact the Natural Resources Conservation Service.

NOTE: This type of font (**AaBbCcDdEe 123..**) indicates NRCS National Standards.
This type of font (**AaBbCcDdEe 123..**) indicates Montana Supplement.

treatment strip. Land grading and structural components necessary to maintain sheet flow throughout the length (dimension parallel to the flow) of the treatment strip shall be provided as necessary.

Permanent herbaceous vegetation consisting of a single species or a mixture of grasses, legumes and/or other forbs adapted to the soil and climate shall be established in the treatment strip **according to the appropriate Natural Resources Conservation Service Practice Standards**. Vegetation shall be able to withstand anticipated wetting and/or submerged conditions.

Clean water shall be diverted from the treatment strip to the fullest extent possible unless needed to promote vegetation growth in the treatment strip.

Treatment strips shall be located outside of floodplains. However, if site restrictions require location within a floodplain, they shall be protected from inundation or damage from a 25-year flood event, or larger if required by law. **DEQ Circular Number 9 states any waste control structure located within the 100-year floodplain shall be flood proofed. The top elevation of the embankment is to be at least one foot above the 100-year flood.**

Designs shall be based on the latest edition of the Environmental Protection Agency Technology Transfer Process Design Manual for Land Treatment of Municipal Wastewater or other technically acceptable reference.

Additional Criteria for Rapid Infiltration Treatment

Rapid infiltration treatment refers to a specific remediation technique that utilizes the filtering capabilities of moderately and highly permeable soils. Treatment for this purpose shall consist of directing wastewater or contaminated runoff from a livestock holding area into a uniformly graded strip or area of herbaceous vegetation and allowing it to flow over and infiltrate **into** the treatment strip.

Contaminated runoff shall be pretreated by solid/liquid separation utilizing a facility such as a settling basin, prior to discharge of liquid to the treatment strip.

The treatment strip shall be a uniformly graded strip or wide bottomed trapezoidal channel **with zero side slope**.

The treatment strip design shall be based on the runoff volume from the 25-year, 24-hour storm event from the livestock holding facility. **DEQ Circular Number 9 states that large swine, poultry or veal CAFO's designed or built after April 14, 2003, shall be designed to a 100-year, 24-hour rainfall event.** It may be designed to infiltrate a portion or the entire volume of the design storm. This determination will be based on management objectives. The portion of the design volume not infiltrated shall be transferred to a storage facility unless discharge is permitted by applicable regulations.

The treatment strip's area requirements shall be based on the soil's capacity to infiltrate and retain runoff within the root zone and the vegetation's capability to utilize the nutrient loading. The soil's ability to infiltrate and retain runoff shall be based on **up to 75% of available** water holding capacity in the root zone, infiltration rate, permeability, and hydraulic conductivity. This determination shall be based on the most restrictive soil layer within the root zone regardless of its thickness. The anticipated nutrient loading shall not exceed the vegetation's agronomic nutrient requirement.

The infiltration strip design shall be such that the upper soil profile remains unsaturated except during storm events and returns to an unsaturated condition within two days following storm events. The water table shall be either naturally deep enough or artificially lowered so that the infiltrated runoff does not mingle with the native ground water. Infiltration strips shall not be planned where soil features such as cracking will result in preferential flow paths that transport untreated runoff from the surface to below the root zone.

Additional Criteria for Overland Flow Treatment

Overland flow treatment refers to a specific microbial remediation technique that has minimal infiltration of wastewater. Treatment by overland flow shall consist of the application of wastewater along the upper portion of a uniformly sloped strip of herbaceous-vegetation, allowing it to flow over the vegetated surface for aerobic treatment to a collection ditch.

The design hydraulic loading rate and application rate shall be selected based on consideration of the anticipated levels of pretreatment, quality of effluent, temperature, and other climatic conditions. A maximum hydraulic loading rate of 2.0 inches per day and an application rate of eight gallons per hour per foot of slope width shall be used unless higher rates can be justified by on-site studies.

The application period shall not exceed 12 hours per day and the application frequency not exceed 5 days per week unless longer application periods and frequencies can be justified based on local conditions.

The nutrients anticipated to infiltrate the treatment strip shall not exceed the vegetation's agronomic nutrient requirement.

Overland flow treatment shall be constructed on soils with low permeability. The design shall be based on the most restrictive soil layer within the root zone. The maximum allowable permeability shall be 0.2 inches per hour unless a natural or constructed barrier within the soil profile mitigates the potential of ground water contamination.

The minimum slope length for the applied wastewater shall be 100 feet.

The sloped areas to receive wastewater shall be uniformly graded to eliminate wastewater ponding and short-circuiting for the length of the flow. Slopes shall be equal to or greater than 2.0% but shall not exceed 8.0%.

If there is any wastewater discharged from the treatment strip **it** shall be transferred to a waste storage facility, a waste treatment lagoon, or other facility for further treatment and/or utilization unless discharge is permitted by regulations.

Additional Criteria for Treating Wastewater with The Slow Rate Process

The slow rate process refers to a specific remediation technique involving the application of wastewater to a vegetated surface for treatment as it flows down through the plant-soil matrix.

The design hydraulic loading shall be based on the more restrictive of two limiting conditions – the capacity of the soil profile to transmit water (soil permeability) or in the nitrogen concentration in the water percolating below the root zone. The percolate nitrate-nitrogen concentration leaving the root zone shall not exceed 10 mg/L. The anticipated nutrient loading shall not exceed the vegetation's agronomic nutrient requirement.

Storage shall be provided when the amount of available wastewater exceeds the design hydraulic loading rate or for strip non-operating periods.

Wastewater shall be applied to the treatment strip utilizing a method that will result in an even

application of the entire strip and a rate that does not exceed the infiltration rate of the soil.

CONSIDERATIONS

- More than one overland flow treatment strip should be considered to allow for resting, harvesting vegetation, maintenance, and to minimize the potential for overloading.
- **Treatment strip width should be adjusted to accommodate harvest and maintenance equipment.**
- Consider pre-treating overland flow influent with solid/liquid separation to reduce organic loading, odor generation, and maintenance requirements.
- Consider suspension of application to treatment strips when weather conditions are not favorable for aerobic activity or when soil temperatures are lower than 39° F. When soil temperatures are between 39° F and 50° F reduction of application rate and increased application period while maintaining the hydraulic loading rate constant should also be considered.

Permits: One or more of various State and/or Local permits will likely be required. Consult the web site: http://dnrc.mt.gov/permits/stream_permittting/guide.asp for a list of permits required for various types of construction activities in Montana.

PLANS AND SPECIFICATIONS

Plans and specifications shall be prepared in accordance with the criteria of this standard and shall describe the requirements for applying the practice to achieve its intended use. Plans should include information about the location, construction sequence, and vegetation establishment.

Specifications will include:

- Length, width, and slope of the treatment strips to accomplish the planned purpose (length refers to flow length down the slope of the treatment strip)
- Herbaceous species and seed selection, and seeding rates to accomplish the planned purpose

- Planting dates, care, and handling of the seed to ensure that planted materials have an acceptable rate of survival
- Statement that only viable, certified weed free, high quality, and regionally adapted seed will be used
- Site preparation sufficient to establish and grow selected species
- **Included within the plans and specifications shall be a process to pre-wash or clean all construction equipment used for installation of this practice to control noxious weeds, or undesired vegetation as required by the producer.**

OPERATION AND MAINTENANCE

An operation and maintenance plan shall be developed that is consistent with the purposes of the practice, its intended life, safety requirements, and the criteria for its design. The plan shall include the following as appropriate:

- Harvest treatment strip vegetation as appropriate to encourage dense growth, maintain an upright growth habit, and remove nutrients and other contaminants that are contained in the plant tissue
- Control undesired weed species, especially state-listed noxious weeds
- Inspect and repair treatment strips after storm events to fill in gullies, remove flow disrupting

sediment accumulation, re-seed disturbed areas, and take other measures to prevent concentrated flow

- Apply supplemental nutrients as needed to maintain the desired species composition and stand density of herbaceous vegetation
- Maintain or restore the treatment strip as necessary by periodically grading when deposition jeopardizes its function, and then reestablishing to herbaceous vegetation
- Routinely de-thatch and/or aerate treatment strips used for treating runoff from livestock holding areas in order to promote infiltration
- Conduct maintenance activities only when the treatment strip is dry and moisture content in the surface soil layer will not allow compaction
- Prevent grazing in treatment strips.

Treatment strips in arid or semiarid regions that potentially could be affected by high salinity and/or sodicity (sodium content) should be monitored for excessive salt and sodium buildup. If found to be excessive, an appropriate corrective action shall be taken.

Within the maintenance plan, a program shall be established to maintain vegetation cover while controlling noxious weeds or other undesired vegetation.