

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD
RHODE ISLAND**

**SURFACE DRAINAGE, FIELD DITCH
(Ft.)**

CODE 607

DEFINITION

A graded ditch for collecting excess water in a field.

PURPOSE

Collect or intercept:

- excess surface water, such as sheet flow from natural and graded land surfaces or channel flow from furrows, and carry it to an outlet;
- excess subsurface water and carry it to an outlet.

CONDITIONS WHERE PRACTICE APPLIES

Applicable sites are flat or nearly flat and:

1. Have soils that are slowly permeable (low permeability) or that are shallow over barriers such as rock or clay, which hold or prevent ready percolation of water to a deep stratum.
2. Have surface depressions or barriers that trap rainfall.
3. Have insufficient land slope for ready movement of runoff across the surface.
4. Receive excess runoff or seepage from uplands.
5. Require the removal of excess irrigation water.
6. Require control of the water table.
7. Have adequate outlets available for disposal of drainage water by gravity flow or pumping.

CRITERIA

General Criteria Applicable to All Purposes

Laws and Regulations. All Federal, state, and local laws, rules, and regulations, including local inland wetland agency regulations, governing the construction and use of this practice as well as setbacks from wells, surface water and property boundaries shall be followed. Planned work shall comply with all federal, state, and local laws and permit conditions and requirements. **The landowner shall obtain all necessary permits prior to construction or any land clearing activities.**

Drainage field ditches shall be planned as integral parts of a drainage system for the field served and shall collect and intercept water and carry it to an outlet with continuity and without ponding.

Investigations. An adequate investigation shall be made of all sites.

Location. Ditches shall be established, insofar as topography and property boundaries permit, in straight or nearly straight courses. Random alignment may be used to follow depressions and isolated wet areas of irregular or undulating topography. Excessive cuts and the creation of small irregular fields shall be avoided.

On extensive areas of uniform topography, collection or interception ditches shall be installed as required for effective drainage.

Design. The size, depth, side slopes, and cross section area shall:

1. Be adequate to provide the required drainage for the site.
2. Permit free entry of water from adjacent land surfaces without causing excessive erosion.
3. Provide effective disposal or reuse of excess irrigation water (if applicable).
4. Conduct flow without causing excessive erosion.
5. Provide stable side slopes based on soil characteristics.
6. Permit crossing by field equipment if feasible.
7. Permit construction and maintenance with available equipment.

CONSIDERATIONS

When planning this practice, the following items should be considered where applicable:

- Potential impacts on downstream flows or aquifers that would affect other water uses or users.
- Potential water quality impacts for soluble pollutants, sediments and sediment-attached pollutants.
- Potential for uncovering or redistributing toxic materials.
- Impacts on cultural resources
- Effects on wetlands or water-related wildlife habitats.
- Effects of water level control on soil water, downstream water temperature or salinity of soils.
- The need for riparian buffers, filter strips and fencing.
- Effects on water budget components, especially the relationships between runoff and infiltration.

PLANS AND SPECIFICATIONS

Plans and specifications shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purpose. Plans and specifications shall include construction plans, drawings, job sheets or other similar documents. These documents shall as a minimum, specify the requirements for installing the practice and include the kind, quantity and quality of materials to be used.

To the extent practical, specifications shall conform to NRCS National Engineering Handbook Parts 642 and 643 (Section 20).

AS BUILT DRAWINGS

As built drawings shall be prepared which show all pertinent elements and elevations as actually installed. A copy shall be provided to the owner / operator upon construction completion.

OPERATION AND MAINTENANCE

An Operation and Maintenance (O&M) plan shall be prepared for, reviewed and signed by the landowner or operator. The plan shall specify that the treated areas and associated practices are inspected annually and after significant storm events to identify repair and maintenance needs.

The O&M plan shall detail the level of repairs needed to maintain the effectiveness and useful life of the practice.

The plan shall adequately guide the landowner(s) in the routine maintenance and operational needs of the ditch(es). The plan shall also include guidance on periodic inspections and post-storm inspections to detect and minimize damage to the ditch(es).