

NATURAL RESOURCES CONSERVATION SERVICE
VIRGINIA CONSERVATION PRACTICE STANDARD

CLOSURE OF WASTE IMPOUNDMENTS
(No.)

CODE 360

DEFINITION

The closure of waste impoundments (treatment lagoons and liquid storage facilities), that are no longer used for their intended purpose, in an environmentally safe manner.

PURPOSE

- Protect the quality of surface water and groundwater resources.
- Eliminate a safety hazard for humans and livestock
- Safeguard the public health.

CONDITIONS WHERE PRACTICE APPLIES

This practice applies to agricultural waste impoundments that are no longer needed as a part of a waste management system and are to be permanently closed or converted.

Where these impoundments are to be converted to fresh water storage and the original impoundment was not constructed to NRCS standards, this practice will only apply where the investigation, as required in National Engineering Manual (NEM) 501.23, shows structural integrity.

CRITERIA

General Criteria Applicable to All Purposes

The closure shall comply with all Federal, State, and local laws, rules, and regulations including pollutant discharge elimination system requirements.

All structures used to convey waste to waste impoundments or to provide drainage from the impoundment area shall be removed and replaced with compacted earth material or otherwise rendered unable to convey waste.

Liquid and slurry wastes shall be agitated and pumped to the extent conventional pumping will allow. Clean water shall be added as necessary to facilitate the agitation and pumping. The wastewater shall be utilized in accordance with Virginia Conservation Practice Standard *Nutrient Management (Code 590)*. The sludge remaining on the bottom and sides of the waste treatment lagoon or waste storage facility may remain in place if it will not pose a threat to the environment. If leaving the sludge in place would pose a threat, it shall be removed to the fullest extent practical and utilized in accordance with Virginia Conservation Practice Standard *Waste Utilization (Code 633)*.

Land Reclamation. Impoundments with embankments may be breached so that they will no longer impound water. Backfill of the excavated part of the impoundment may also be necessary. Excavated impoundments may be backfilled so that these areas may be reclaimed for other uses. Waste impoundments that have water impounded against the embankment are considered embankment structures if the depth of water is three feet or more above natural ground.

Embankment Impoundments. Waste shall be removed from the site before the embankment is breached. The slopes and bottom of the breach shall be stable for the soil material involved, however the side slopes shall be no

steeper than three horizontal to one vertical (3:1).

Excavated Impoundments. The backfill height shall exceed the design finished grade by 5 percent to allow for settlement. The top one foot of the backfill shall be constructed of the most clayey material available and mounded to shed rainfall runoff. Incorporate available topsoil where feasible to aid establishment of vegetation.

Liner Removal. When the structure will be filled with soil, clay liners on the interior side slopes shall be removed using earth-moving equipment or destroyed using subsoiling equipment. Synthetic liners may be disposed in legal landfills or rolled/folded and placed in the bottom of the structure prior to filling. The synthetic liner shall be removed from the top of the embankment to the higher in elevation of three feet from the structure bottom or the ground water elevation at the time of closure.

Fill Placement. The storage facility shall be filled with uncontaminated soil material. The soil shall be placed in maximum 12 inch lifts with each layer being compacted using two passes of heavy equipment. Soil moisture content shall be maintained to ensure adequate compaction of the material.

Waste Storage Structures. Closed waste storage structures shall be demolished or disassembled or otherwise altered to such an extent that no water can be impounded. Disassembled materials such as pieces of metal shall be temporarily stored until their final disposition in such a manner that they do not pose a hazard to animals or humans.

Demolished materials shall be buried on-site or moved off-site to locations designated by state or local officials. If buried on-site, the materials are to be covered with soil to a settled depth of one foot, and the backfill be sufficiently mounded such that runoff will be diverted from the site after the backfill settles.

Conversion to Fresh Water Storage. The converted impoundment shall meet the requirements as set forth in the appropriate NRCS practice standard for the intended purpose.

Safety. When sludge is not removed from a waste impoundment that is being converted to

fresh water storage, the impoundment shall not be used for fish production, swimming, or livestock watering until water quality is adequate for these purposes. Precautions (fencing and warning signs) shall be used to ensure that the facility is not used for purposes incompatible with the current quality of water.

Personnel shall not enter an enclosed waste impoundment without breathing apparatus or taking other appropriate measures.

Protection. All disturbed areas shall be re-vegetated or other suitable measures used to control erosion and restore the esthetic value of the site. Sites not suitable for re-vegetation through normal cropping practices shall be vegetated using Virginia Conservation Practice Standard *Critical Area Planting (Code 342)*.

Measures shall be taken during construction to minimize site erosion and pollution of downstream water resources. This may include such items as silt fences, hay bale barriers, temporary vegetation, and mulching.

CONSIDERATIONS

Reduce pumping effort to empty waste impoundments where the surface is covered by a dense mat of floating vegetation by first applying herbicide to the vegetation and then burning the residue. Appropriate permits must be obtained before burning.

Alternative methods of sludge removal may be required where the impoundments contain large amounts of oyster shells, soil, or other debris.

Minimize the impact of odors associated with emptying and land applying wastewater and sludge from a waste impoundment by using an incorporation application method at a time when the humidity is low, when winds are calm, and when wind direction is away from populated areas.

Soil to fill excavated ponds should not come from important farmlands (prime, statewide, local, and/or unique).

Breeched embankments may detract from the overall esthetics of the operation. The embankments should be removed and the site returned to its original grade.

Keep sludge left in place covered with water to prevent its aerobic decomposition with the potential release of nutrients to surface and ground water.

Disassembled structural facilities may be suitable for assembly at another site. Care should be taken during closure to minimize damage to the pieces of the facility, particularly coatings that prevent corrosion of metal pieces.

When converting waste treatment lagoons or waste storage ponds to fresh water ponds, the effects on the water budget should be considered. A pond will reduce surface runoff, trap sediment, and reduce nutrients and pesticides leaving the land.

If a fresh water pond is created for livestock drinking water, a watering ramp or trough should be used to provide access to the water.

PLANS AND SPECIFICATIONS

Plans and specifications for closure of abandoned waste treatment lagoons and waste storage facilities shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purpose. The plans and specifications shall also be consistent with the requirements of that standard.

Record all required information in an engineer field book, on a plan sheet or design computation sheet, or in another appropriate location.

DESIGN DATA

1. Completed Environmental Evaluation and subsequent requirements.
2. Soils investigation.
3. Survey and plot data: profile, cross-sections, topography, as needed.
4. Design computations, including purpose of practice and references used.
 - a. Quantity of sludge and disposal method.
 - b. Liner removal plan, as needed.
 - c. Disposal plan for storage structures, as needed.

5. Plan view of site with existing and planned features, including dimensions, distances, etc.
6. Standard Cover Sheet (VA-SO-100A).
7. Materials and quantities needed. Identify borrow material and/or spoil area, as needed.
8. Vegetation and/or ground cover requirements.
9. Identification of needed Erosion & Sediment Control measures.
10. Supplemental practices required.
11. Virginia Conservation Practice Specifications (700 Series).
12. Operation and Maintenance Plan.

CHECK DATA

1. As-built survey.
2. As-built plans including dimensions, types and quantities of materials installed, and variations from design. Include justification for variations.
3. Locations of appurtenant practices.
4. Adequacy of vegetation and/or ground cover.
5. Complete as-built section of Cover Sheet.

OPERATION AND MAINTENANCE

The proper closure of a waste treatment lagoon or waste storage facility should require little or no operation and maintenance. However, if it is converted to another use, such as a fresh water facility, operation and maintenance shall be in accordance with the needs as set forth in the appropriate NRCS conservation practice standard for the intended purpose.

REFERENCES

1. USDA-Natural Resources Conservation Service. Virginia Electronic Field Office Technical Guide (eFOTG), Section IV. [On-line]. Available at:

<http://www/nrcs.usda.gov/technical/eFOTG>

2. USDA- Natural Resources Conservation Service. Virginia 700 Series Construction Specifications.

[On-line]. Available at:

<http://www/nrcs.usda.gov/technical/eFOTG>

"The U.S. Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, age, disability, and where applicable, sex, marital status, familial status, parental status, religion, sexual orientation, genetic information, political beliefs, reprisal, or because all or a part of an individual's income is derived from any public assistance program. (Not all prohibited bases apply to all programs.) Persons with disabilities who require alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA's TARGET Center at (202) 720-2600 (voice and TDD). To file a complaint of discrimination write to USDA, Director, Office of Civil Rights, 1400 Independence Avenue, S.W., Washington, D.C. 20250-9410 or call (800) 795-3272 (voice) or (202) 720-6382 (TDD). USDA is an equal opportunity provider and employer."