

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD**

POND SEALING OR LINING - FLEXIBLE MEMBRANE

(Each)

CODE 521A

DEFINITION

A manufactured hydraulic barrier consisting of a functionally continuous layer of synthetic or partially synthetic, flexible material.

PURPOSE

To restrict, impede, and control seepage of contaminants from water and waste impoundment structures for water conservation and environmental protection.

CONDITION WHERE PRACTICE APPLIES

On ponds and water storage structures that require treatment to control seepage rates within acceptable limits.

On earthen waste storage lagoons and other waste impoundment structures that require treatment to control seepage of contaminants from the storage structure.

CRITERIA

Design. Structures to be lined shall have been constructed to meet all applicable NRCS standards. All inlets, outlets, ramps, and other appurtenances may be installed before, during, or after the liner placement, but shall be done in a manner that does not damage or impair the proper operation of the liner.

Design and installation of the flexible membrane shall be in accordance with manufacturer recommendations. All flexible membrane installations shall be certified by the installer as meeting the material and installation requirements of the plans and specifications.

Manufacturer recommendations shall be followed with regard to protection from weather and exposure.

Minimum Criteria for Membranes

Type	Limiting Parameter	
	Wastewater	Clear Water
HDPE	40 mil	30 mil
LLDPE	40 mil	20 mil
EPDM	45 mil	
PP (Reinforced)	36 mil	24 mil
(Un-reinforced)	40 mil	20 mil
RPE	NR	24 mil

1 mil = 1/1000 of an inch

HDPE – High Density Polyethylene Geomembrane

LLDPE – Linear Low Density Polyethylene Geomembrane

EPDM – Synthetic Rubber Geomembrane

PP – Polypropylene Geomembrane

RPE – Reinforced Polyethylene Geomembrane

NR – Not Recommended

Subgrade Preparation. Subgrade preparation shall conform to manufacturer recommendations. Subgrade materials shall not contain sharp, angular stones or any objects that could damage the liner or adversely affect its function. **Unless otherwise specified by the manufacturer, the side slopes that will support the liner shall be no steeper than 2.5 horizontal to 1 vertical.**

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resources Conservation Service [State Office](#) or visit the [electronic Field Office Technical Guide](#).

Padding. A cushion or padding shall be placed beneath the liner if the subgrade particles contain sharp angular stones that could damage the liner or particles greater than $\frac{3}{8}$ -inch for geomembrane liners and $\frac{1}{2}$ -inch for geosynthetic clay liners. The padding or cushion may be an 8-ounce or greater non-woven geotextile or a soil meeting the particle size and shape requirements of the subgrade. **Padding shall also be used to help vent gases from underneath the liner, allow movement for expansion and contraction of the liner and to provide a conduit to help drain subsurface water away from the liner.**

Anchorage. Liners shall be anchored to prevent uplift due to wind or slippage down the side slope.

Safety. Design shall include appropriate safety features to minimize the hazards of the structure. Warning signs, fences, ladders, ropes, bars, rails, and other devices shall be provided, as appropriate, to ensure the safety of humans and livestock.

Vents. All liners shall be designed with vents to prevent the build up of gases under the liner. All vents shall be installed at the highest part of the liner as practical. When available, manufacturer's specifications for venting system shall be followed. The bottom shall have a minimum slope of two percent in order to vent gases.

Leak Detection. A leak detection system shall be installed on all earthen waste storage lagoons and other waste impoundments structures with flexible membrane type liners. The system shall have a minimum of one perforated drain installed at least one foot directly underneath the liner. This drain shall be directed to a manhole or other structure that is easily accessible. A valve shall be installed at the outlet of this structure so the flow can be turned off in the event a leak is detected. If a leak is detected, the contaminated water will have to be pumped out of the structure and properly disposed until the leak in the liner is found and repaired. The leak detection system maybe part of a designed drainage system.

CONSIDERATIONS

Venting of wastewater pond liners not covered with soil is recommended unless other site conditions exist to allow dissipation of gas pressure from beneath the liner. One such condition is the presence of granular foundation soils (SW, GW or GP). A minimum vent spacing of 50 feet is recommended.

If high water tables could adversely affect the proper functioning of the structure, interceptor or relief-type drainage systems should be considered to control uplift pressures.

PLANS AND SPECIFICATIONS

Plans and specifications shall be prepared for specific field sites in accordance with this standard and shall describe the requirements for applying the practice to achieve its intended uses.

As a minimum, the plans and specifications shall provide the following:

1. Layout of the containment structure, collection points, waste transfer locations or pipelines, and topography of the site
2. Required liner properties, cushion materials, and pipeline materials
3. Subgrade details, including tolerances on smoothness of the finished grade
4. Details of liner installation, seaming requirements, and requirements for attachments and appurtenances
5. Quality control testing
6. Fence and signage requirements.

OPERATION AND MAINTENANCE

A plan for operation and maintenance (O&M) of the liner and structure shall be prepared. The plan shall be consistent with the purposes of the type of liner chosen, intended life, safety requirements and design criteria. The plan shall contain requirements including but not limited to:

1. Design capacity and liquid level of the structure.
2. A description of the normal operation, safety concerns and maintenance requirements.
3. Repair procedures.
4. Periodic inspection of the following:
 - Visible portions of the liner for tears punctures, or other damage;
 - Liner interface with inlets, outlets, ramps, or other appurtenances for damage;
 - Liquid level in the structure;
 - Ballooning of the liner indicating presence of gas beneath the liner.
 - [The leak detection system.](#)

5. If leaks are detected:

- The valve in the leak detection system shall be turned off to prevent the effluent from leaving the system.
- The effluent from the leak detection system shall be pumped into the earthen waste storage lagoon or waste impoundment structure until the leak is repaired.
- The facility shall be pumped and cleaned out at the next scheduled opportunity and the liner repaired.

REFERENCES

Quality Assurance and Quality Control for Waste Containment Facilities, EPA/1600/R-93/182, September 1993.