

**NATURAL RESOURCES CONSERVATION SERVICE**  
**CONSERVATION PRACTICE STANDARD**  
**IRRIGATION SYSTEM, SPRINKLER**  
 (no. and acre)  
**CODE 442**

**DEFINITION**

A planned irrigation system in which all necessary facilities are installed for efficiently applying water by means of perforated pipes or nozzles operated under pressure.

**PURPOSE**

To efficiently and uniformly apply irrigation water to maintain adequate soil moisture for optimum plant growth without causing excessive water loss, erosion, or reduced water quality.

**CONDITIONS WHERE PRACTICE APPLIES**

Sprinkler irrigation plans shall be based on an evaluation of the site and the expected operating conditions. The soils and topography shall be suitable for irrigation for the proposed crops.

*Sufficient* good-quality water must be available for practical irrigation of the crops to be grown.

The sprinkler method of water application is suited to most crops, to most irrigable lands, and to most climatic conditions where irrigated agriculture is feasible.

**Scope**

This standard applies to the sprinkler irrigation system through which water is distributed by means of sprinklers or spray nozzles. It applies to all components of the

onfarm system except for special structures such as permanently installed mains and laterals (**Irrigation Pipeline**, Code 430). It does not include the practice **Irrigation System, Microirrigation** (Code 441).

**DESIGN CRITERIA**

**Depth of application.** The net depth of application shall be based on the available moisture capacity of the soil in the root zone of the crop irrigated or a lesser amount consistent with the land user's operation plan. The gross depth shall be determined by using field application efficiencies consistent with the conservation of water resources.

**Capacity Requirements.** In regularly irrigated areas, sprinkler irrigation systems shall have either (1) a design capacity adequate to meet the moisture demands of all crops to be irrigated in the design area or (2) enough capacity to meet the requirements of several selected irrigations during critical crop growth periods when less than full irrigation is planned. In computing capacity requirements, allowance must be made for reasonable water losses during application periods.

Systems for special-purpose irrigation shall have the capacity to apply a stated amount of water to the design area in a specified net operating period.

**Design application rate.** The design rate of application shall be within a range established by the minimum practical

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resources Conservation Service.

application rate under local climatic conditions and the maximum rate consistent with the intake rate of the soil and the conservation practices used on the land. If two or more sets of conditions are in the design area, the lowest maximum application rate for areas of significant size shall apply.

**Distribution patterns and spacing.** A combination of sprinkler spacing, nozzle sizes, and operating pressure that most nearly provides the design application rate and distribution shall be selected. The velocity of prevailing winds and other conditions must be considered.

If available from the manufacturers, uniformity coefficient data shall be used in selecting sprinkler spacing, nozzle sizes, and operating pressure. The uniformity coefficient shall be not less than as shown below:

70% for orchards

75% for deep-rooted (4 ft or more) field and forage crops

85% for high-value or shallow-rooted crops and for any crop where fertilizer or pesticides are applied through the system.

In the absence of such data, sprinkler performance tables provided by the manufacturers shall be used in selecting nozzle sizes, operating pressure, and wetted diameter for the required sprinkler discharge. The maximum spacing shall comply with the following criteria:

1. For low, intermediate, and moderate-pressure sprinklers, the spacing along lateral lines ( $S_1$ ) shall not exceed 50 percent of the wetted diameter, as given in the manufacturer's performance tables, when the sprinkler is operating under optimum pressure. The spacing of laterals along the main line ( $S_m$ ) shall not exceed 65 percent of this wetted

diameter. If winds that can affect the distribution pattern are likely, spacing ( $S_m$ ) shall be reduced to 60 percent for average velocities of 5 miles per hour, to 50 percent for average velocities of 10 miles per hour, and to 30 percent for average velocities greater than 10 miles per hour.

2. For high-pressure sprinklers and for the giant hydraulic type, the maximum distance (diagonal) between two sprinklers on adjacent lateral lines shall not exceed two-thirds of the wetted diameter under favorable operating conditions. If winds that can affect the distribution pattern are likely, the diagonal spacing shall be reduced to 50 percent of the wetted diameter for average velocities of 5 miles per hour and to 30 percent for average velocities greater than 10 miles per hour.
3. For perforated pipelines, the spacing recommendations of the manufactures for the design application rate, number and size of perforations, and operating pressure shall be followed.

**Lateral lines.** Lateral lines shall be so designed that the total pressure variation at the sprinkler heads, resulting from friction head and static head, does not exceed 20 percent of the design operating pressure of the sprinklers.

Except for under-tree operation, riser pipes used in lateral lines shall be long enough to prevent interference with the distribution pattern when the tallest crop is irrigated. Riser lengths shall not be less than shown below:

Sprinkler Discharge gal/ min	Riser Length inches
Less than 10	6
12 - 25	9
5 - 50	12
0 - 120	18
More than 120	36

**Mainlines.** The design of main lines, submains, and supply lines shall insure that the quantities of water required are conveyed to all lateral lines at the maximum required pressure.

If the pressure required for sprinkler system operation is provided by pumping, main line pipe sizes shall insure that there is an economical balance between the capitalized cost of the pipe and annual pumping costs.

*Permanently installed PVC, HDPE, or steel mainlines shall be designed according to the Hawaii Standard for **Irrigation Pipeline** (Code 430).*

**Pump and power unit.** The pump capacity and the power unit shall be adequate to operate the sprinkler system efficiently when maximum capacity is being pumped against maximum total dynamic head.

## **PLANNING CONSIDERATIONS FOR WATER QUANTITY AND QUALITY**

### **Water Quantity**

1. *Effects on the water budget, especially the volume and rate of runoff, infiltration, evaporation, transpiration, deep percolation, and ground water recharge.*
2. *Potential for changes in plant growth and transpiration because of changes in the volume of soil water.*
3. *Effects on downstream flows or aquifers that would affect other water uses or users.*
4. *The effect on the water table of the field in providing suitable rooting depth for anticipated land uses.*
5. *Potential ability to manage irrigation water through control of water in the root zone.*

### **Water Quality**

1. *Effects on erosion and the movement of sediment and soluble and sediment-attached substance carried by runoff.*
2. *Effects of nutrients and pesticides on surface and ground water quality.*
3. *Potential effects on the movement of dissolved substances below the root zone or to ground water.*
4. *Effects of soil water levels on such nutrient processes as nitrification and denitrification.*
5. *Effects of soil water levels in controlling the salinity of soils, soil water or downstream water quality.*
6. *Effects on the visual quality of water resources.*

## **PLANS AND SPECIFICATIONS**

Plans and specifications for constructing irrigation sprinkler systems shall be in keeping with this standard and shall describe the requirements for properly installing the practice to achieve its intended purpose.

*Construction plans for sprinkler irrigation systems should include the crops to be grown, sprinkler operating pressure, sprinkler discharge, sprinkler nozzle size, minimum wetted diameter, sprinkler spacing, number of sprinklers to operate at one time, number of laterals lines, lateral line spacing, lateral line size, lateral length, type of lateral line material, lateral pipe pressure rating, backflow prevention devices, and irrigation water management data.*

*Construction plans for permanently installed main lines (**Irrigation Pipeline**, Code 430) may be incorporated into the sprinkler system plans.*

## **OPERATION AND MAINTENANCE**

An operation and maintenance plan must be prepared for use by the owner or others responsible for operating the system. The plan should provide specific instructions for operating and maintaining the system to insure that it functions properly. It should

also provide for periodic inspections and prompt repair or replacement of damaged components.

*The Hawaii Operation and Maintenance Guide for Sprinklers will be included with the construction plans.*