

ADDISON COUNTY SEPTIC SYSTEM RATING CLASSES

1/2/97

MAP SYMBOL	MAP UNIT NAME	CLASS	FOOT NOTE
AdA	ADAMS LOAMY FINE SAND, 0 TO 5 PERCENT SLOPES	1	
AdB	ADAMS LOAMY FINE SAND, 5 TO 12 PERCENT SLOPES	1	
AdD	ADAMS LOAMY FINE SAND, 12 TO 30 PERCENT SLOPES	1	b
AdE	ADAMS LOAMY FINE SAND, 30 TO 50 PERCENT SLOPES	1	b
AmB	AMENIA STONY LOAM, 0 TO 8 PERCENT SLOPES	4	
AmC	AMENIA STONY LOAM, 8 TO 15 PERCENT SLOPES	4	
AsC	AMENIA EXTREMELY STONY LOAM, 0 TO 15 PERCENT SLOPES	4	
AsD	AMENIA EXTREMELY STONY LOAM, 15 TO 25 PERCENT SLOPES	4	c
BeA	BERKSHIRE AND MARLOW STONY LOAMS, 0 TO 3 PERCENT SLOPES	3	
BeB	BERKSHIRE AND MARLOW STONY LOAMS, 3 TO 12 PERCENT SLOPES	3	
BeC	BERKSHIRE AND MARLOW STONY LOAMS, 12 TO 25 PERCENT SLOPES	3	c
BsC	BERKSHIRE AND MARLOW EXTREMELY STONY LOAMS, 3 TO 20 PERCENT SLOPES	3	
BsE	BERKSHIRE AND MARLOW EXTREMELY STONY LOAMS, 20 TO 50 PERCENT SLOPES	6	
BuC	BUCKLAND EXTREMELY STONY LOAM, 3 TO 15 PERCENT SLOPES	4	
BuD	BUCKLAND EXTREMELY STONY LOAM, 15 TO 25 PERCENT SLOPES	4	c
CaB	CABOT STONY LOAM, 0 TO 8 PERCENT SLOPES	6	
CbC	CABOT EXTREMELY STONY LOAM, 0 TO 15 PERCENT SLOPES	6	
ClC	CALAIS AND GLOVER SOILS, 5 TO 20 PERCENT SLOPES	5	a
ClE	CALAIS AND GLOVER SOILS, 20 TO 50 PERCENT SLOPES	6	
Cn	CANANDAIGUA SILT LOAM	6	
Co	COBBLY ALLUVIAL LAND	7	
CtA	COLTON GRAVELLY SANDY LOAM, 0 TO 5 PERCENT SLOPES	1	
CtB	COLTON GRAVELLY SANDY LOAM, 5 TO 12 PERCENT SLOPES	1	
CtD	COLTON GRAVELLY SANDY LOAM, 12 TO 30 PERCENT SLOPES	1	b
CtE	COLTON GRAVELLY SANDY LOAM, 30 TO 50 PERCENT SLOPES	1	b
Cv	COVINGTON SILTY CLAY, FLOODED	6	
Cw	COVINGTON AND PANTON SILTY CLAYS	6	
DaA	DUANE FINE SANDY LOAM, 0 TO 5 PERCENT SLOPES	4	
DaB	DUANE FINE SANDY LOAM, 5 TO 12 PERCENT SLOPES	4	
DcB	DUTCHESS STONY LOAM, 3 TO 8 PERCENT SLOPES	2	
DcC	DUTCHESS STONY LOAM, 8 TO 15 PERCENT SLOPES	2	
DcD	DUTCHESS STONY LOAM, 15 TO 25 PERCENT SLOPES	2	b

FOOTNOTES - see text

- a - Areas with bedrock at less than 24 inches are not suitable.
- b - This map unit has a slope limitation requiring site modification.
- c - Areas with slope greater than 20 % are not suitable.

ADDISON COUNTY SEPTIC SYSTEM RATING CLASSES

1/2/97

MAP SYMBOL	MAP UNIT NAME	CLASS	FOOT NOTE
DsC	DUTCHESS EXTREMELY STONY LOAM, 3 TO 15 PERCENT SLOPES	2	
DsE	DUTCHESS EXTREMELY STONY LOAM, 15 TO 50 PERCENT SLOPES	2	b
ElB	ELMWOOD FINE SANDY LOAM, COARSE VARIANT, 0 TO 8 PERCENT SLOPES	4	
ElC	ELMWOOD FINE SANDY LOAM, COARSE VARIANT, 8 TO 15 PERCENT SLOPES	4	
FaC	FARMINGTON EXTREMELY ROCKY SILT LOAM, 5 TO 20 PERCENT SLOPES	6	
FaE	FARMINGTON EXTREMELY ROCKY SILT LOAM, 20 TO 50 PERCENT SLOPES	6	
FdB	FARMINGTON STONY SILT LOAM, MODERATELY DEEP VARIANT, 3 TO 8 PERCENT SLOPES	4	a
FdC	FARMINGTON STONY SILT LOAM, MODERATELY DEEP VARIANT, 8 TO 15 PERCENT SLOPES	4	a
FdD	FARMINGTON STONY SILT LOAM, MODERATELY DEEP VARIANT, 15 TO 25 PERCENT SLOPES	4	a, c
FdE	FARMINGTON STONY SILT LOAM, MODERATELY DEEP VARIANT, 25 TO 50 PERCENT SLOPES	6	
FnB	FARMINGTON-NELLIS ROCKY COMPLEX, 5 TO 12 PERCENT SLOPES	5	a
FnC	FARMINGTON-NELLIS ROCKY COMPLEX, 12 TO 20 PERCENT SLOPES	5	a
FnD	FARMINGTON-NELLIS ROCKY COMPLEX, 20 TO 30 PERCENT SLOPES	6	
Fw	FRESH WATER MARSH	7	
GP	GRAVEL PITS	7	
Hf	HADLEY VERY FINE SANDY LOAM	6	
Hh	HADLEY VERY FINE SANDY LOAM, FREQUENTLY FLOODED	6	
Le	LIMERICK SILT LOAM	6	
Lf	LIMERICK SILT LOAM, VERY WET	6	
Lh	LIVINGSTON CLAY	6	
Lk	LIVINGSTON CLAY, FLOODED	6	
LmB	LYMAN-BERKSHIRE ROCKY COMPLEX, 5 TO 12 PERCENT SLOPES	5	a
LmC	LYMAN-BERKSHIRE ROCKY COMPLEX, 12 TO 20 PERCENT SLOPES	5	a
LxC	LYMAN-BERKSHIRE VERY ROCKY COMPLEX, 5 TO 20 PERCENT SLOPES	5	a
LxE	LYMAN-BERKSHIRE VERY ROCKY COMPLEX, 20 TO 50 PERCENT SLOPES	6	
MP	MINES AND PITS	7	
MaA	MASSENA STONY SILT LOAM, 0 TO 3 PERCENT SLOPES	6	
MnB	MASSENA EXTREMELY STONY SILT LOAM, 0 TO 8 PERCENT SLOPES	6	
MrA	MELROSE FINE SANDY LOAM, 0 TO 3 PERCENT SLOPES	3	
MrB	MELROSE FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES	3	
MrC	MELROSE FINE SANDY LOAM, 8 TO 15 PERCENT SLOPES	3	
MrD	MELROSE FINE SANDY LOAM, 15 TO 25 PERCENT SLOPES	3	c

FOOTNOTES - see text

- a - Areas with bedrock at less than 24 inches are not suitable.
- b - This map unit has a slope limitation requiring site modification.
- c - Areas with slope greater than 20 % are not suitable.

ADDISON COUNTY SEPTIC SYSTEM RATING CLASSES

1/2/97

MAP SYMBOL	MAP UNIT NAME	CLASS	FOOT NOTE
MrE	MELROSE FINE SANDY LOAM, 25 TO 50 PERCENT SLOPES	6	
Mv	MUCK AND PEAT	7	
NaB	NASSAU-DUTCHESS ROCKY COMPLEX, 3 TO 8 PERCENT SLOPES	5	a
NaC	NASSAU-DUTCHESS ROCKY COMPLEX, 8 TO 15 PERCENT SLOPES	5	a
NaD	NASSAU-DUTCHESS ROCKY COMPLEX, 15 TO 25 PERCENT SLOPES	5	a, c
NdC	NASSAU EXTREMELY ROCKY SILT LOAM, 3 TO 25 PERCENT SLOPES	6	
NeB	NELLIS STONY LOAM, 3 TO 8 PERCENT SLOPES	3	
NeC	NELLIS STONY LOAM, 8 TO 15 PERCENT SLOPES	3	
NeD	NELLIS STONY LOAM, 15 TO 25 PERCENT SLOPES	3	c
NsC	NELLIS EXTREMELY STONY LOAM, 3 TO 15 PERCENT SLOPES	3	
NsD	NELLIS EXTREMELY STONY LOAM, 15 TO 50 PERCENT SLOPES	3	c
PeA	PERU STONY LOAM, 0 TO 5 PERCENT SLOPES	4	
PeB	PERU STONY LOAM, 5 TO 12 PERCENT SLOPES	4	
PeC	PERU STONY LOAM, 12 TO 20 PERCENT SLOPES	4	
PsC	PERU EXTREMELY STONY LOAM, 0 TO 20 PERCENT SLOPES	4	
PsD	PERU EXTREMELY STONY LOAM, 20 TO 50 PERCENT SLOPES	6	
Qu	QUARRY	7	
RL	RUBBLE LAND	7	
RaB	RAYNHAM SILT LOAM, 0 TO 6 PERCENT SLOPES	6	
RaC	RAYNHAM SILT LOAM, 6 TO 12 PERCENT SLOPES	6	
RaD	RAYNHAM SILT LOAM, 12 TO 25 PERCENT SLOPES	4	c
Rk	ROCK LAND	7	
SaB	SALMON VERY FINE SANDY LOAM, 2 TO 6 PERCENT SLOPES	2	
SaC	SALMON VERY FINE SANDY LOAM, 6 TO 12 PERCENT SLOPES	2	
SaE	SALMON VERY FINE SANDY LOAM, 12 TO 50 PERCENT SLOPES	2	b
StA	STETSON GRAVELLY FINE SANDY LOAM, 0 TO 5 PERCENT SLOPES	1	
StB	STETSON GRAVELLY FINE SANDY LOAM, 5 TO 12 PERCENT SLOPES	1	
StD	STETSON GRAVELLY FINE SANDY LOAM, 12 TO 30 PERCENT SLOPES	1	b
StE	STETSON GRAVELLY FINE SANDY LOAM, 30 TO 50 PERCENT SLOPES	1	b
Sw	SWANTON FINE SANDY LOAM	6	
VgB	VERGENNES CLAY, 2 TO 6 PERCENT SLOPES	4	
VgC	VERGENNES CLAY, 6 TO 12 PERCENT SLOPES	4	

FOOTNOTES - see text

- a - Areas with bedrock at less than 24 inches are not suitable.
- b - This map unit has a slope limitation requiring site modification.
- c - Areas with slope greater than 20 % are not suitable.

ADDISON COUNTY SEPTIC SYSTEM RATING CLASSES

1/2/97

MAP SYMBOL	MAP UNIT NAME	CLASS	FOOT NOTE
VgD	VERGENNES CLAY, 12 TO 25 PERCENT SLOPES	4	c
VgE	VERGENNES CLAY, 25 TO 50 PERCENT SLOPES	6	
VrB	VERGENNES ROCKY CLAY, MODERATELY SHALLOW VARIANT, 2 TO 6 PERCENT SLOPES	4	a
VrC	VERGENNES ROCKY CLAY, MODERATELY SHALLOW VARIANT, 6 TO 12 PERCENT SLOPES	4	a
VrD	VERGENNES ROCKY CLAY, MODERATELY SHALLOW VARIANT, 12 TO 25 PERCENT SLOPES	4	a, c
W	WATER, LESS THAN 40 ACRES	7	
Wa	WALPOLE SILT LOAM	6	
Wo	WINOOSKI VERY FINE SANDY LOAM	6	

FOOTNOTES - see text

- a - Areas with bedrock at less than 24 inches are not suitable.
- b - This map unit has a slope limitation requiring site modification.
- c - Areas with slope greater than 20 % are not suitable.