

Table of Contents Section II – Soil and Site Information

	Issue Date	Date of Last Review	Responsible Staff
<i>Use and Explanation of Soil Interpretations</i>			
<i>Explanation of Key Phrases Used in Soil Interpretations</i>			
Soils Legends	1/02	1/02	SOI
<i>* Acreage and Proportionate Extent of the Soils</i>			
Soil Descriptions - Nontechnical	1/02	1/93	SOI
<i>Use and Explanation of Nontechnical Descriptions</i>			
<i>*Nontechnical Soils Description Report</i>			
Soil Descriptions - Technical	1/02	1/02	SOI
<i>*Map Unit Description Report</i>			
Cropland Interpretations - Technical	1/02	1/02	SOI
<i>*Prime Farmland Report</i>			
<i>* Kansas Soil Rating for Plant Growth Index</i>			
<i>*Soil Properties for Conservation Planning</i>			
Rangeland, Grazed Forestland, Native Pastureland Interpretations	1/02	1/02	SOI
<i>*Rangeland Productivity Report</i>			
<i>*Range Site Descriptions</i>			
Forestland Interpretations	1/93	1/93	SOI
<i>Use and Explanation of Forestland Interpretations</i>			
<i>*Woodland Management and Productivity</i>			
Nonagricultural Interpretations	1/02	1/02	SOI
<i>*Building Site Development Report</i>			
<i>*Construction Materials Report</i>			
Recreation Interpretations	1/02	1/02	SOI
<i>*Recreational Interpretations</i>			
Wildlife Interpretations	1/02	1/02	SOI
<i>*Wildlife Interpretations Report</i>			
Pastureland and Hayland Interpretations	1/02	1/02	SOI
<i>*Yields Per Acre of Pasture and Hayland</i>			

	Issue Date	Date of Last Review	Responsible Staff
Mined Land Interpretations <i>Use and Explanation of Mined Land Interpretations</i>	1/93	1/93	SOI
Windbreak Interpretations <i>*Conservation Tree and Shrub Management Report</i>	1/02	1/02	SOI
Engineering Interpretations <i>*Engineering Index Properties</i> <i>*Physical Properties of the Soils</i> <i>*Chemical Properties of the Soils</i> <i>*Water Features</i> <i>*Soil Features</i> <i>*Water Management Report</i>	1/02	1/02	SOI
Waste Disposal Interpretations <i>*Sanitary Facilities Report</i> <i>*Agricultural Waste Management Report</i>	1/02	1/02	SOI
Water Quantity and Quality Interpretations <i>Use and Explanation of Water Quantity and Quality Interpretations</i> <i>*Appendix A – Soils Potential For Surface Loss and Leaching</i> <i>*Appendix B – Pesticide Selected Properties Database</i> <i>*Appendix C – Herbicide Selected Properties Database</i> <i>*Soil-Pesticide Interaction Screening Procedure Worksheet (Blank)</i> <i>*WIN-PST SPISP II Soil Sensitivity to Pesticide Loss Rating Report</i>	1/02	1/02	SOI
Hydric Soil Interpretations <i>Use and Explanation of Hydric Soil Interpretations</i> <i>*Hydric Soils List</i>	1/02	1/02	SOI
HEL Interpretations <i>Use and Explanation of Highly Erodible Land Interpretations</i> <i>*Highly Erodible Lands Report</i> <i>*LS and Supporting Data for 1990 Frozen HEL List</i> <i>*CRP 20 Soil Supporting Data for 1990 Frozen HEL List</i>	7/95	1/00	SOI

**County specific computer generated reports.*

ACREAGE AND PROPORTIONATE EXTENT OF THE SOILS

Riley County, Kansas: Published

Map symbol	Soil name	Acres	Percent
027CS	Crete Silt Loam, 1 To 3 Percent Slopes-----	151	*
027CX	Crete Silty Clay Loam, 3 To 8 Percent Slopes, Eroded-----	1,316	0.3
027HN	Hobbs Silt Loam, Channeled-----	304	*
027KS	Kipson-Sogn Silty Clay Loams, 5 To 20 Percent Slopes-----	888	0.2
061BE	Benfield-Florence Complex, 5 To 30 Percent Slopes-----	10,095	2.5
061CF	Clime-Sogn Silty Clay Loams, 5 To 20 Percent Slopes-----	4,456	1.1
061CR	Crete Silty Clay Loam, 0 To 1 Percent Slopes-----	97	*
061CS	Crete Silty Clay Loam, 1 To 4 Percent Slopes-----	3,457	0.9
061EU	Eudora Silt Loam, Occasionally Flooded-----	259	*
061HE	Haynie Silt Loam, Frequently Flooded-----	1	*
061KA	Kahola Silt Loam, Channeled-----	45	*
061KB	Kahola Silt Loam, Occasionally Flooded-----	471	0.1
061RE	Reading Silty Clay Loam, 0 To 2 Percent Slopes-----	49	*
061TO	Tully Silty Clay Loam, 3 To 8 Percent Slopes-----	90	*
117PA	Pawnee Clay Loam, 1 To 4 Percent Slopes-----	90	*
117PB	Pawnee Clay Loam, 4 To 8 Percent Slopes-----	48	*
149HS	Haynie-Sarpy Complex, Occasionally Flooded-----	5	*
149PS	Paxico Silt Loam, Frequently Flooded-----	1,337	0.3
149SF	Sarpy Sand, Frequently Flooded-----	7	*
197CM	Clime Silty Clay Loam, 3 To 7 Percent Slopes-----	50	*
197FL	Florence-Labette Complex, 3 To 15 Percent Slopes-----	731	0.2
197IB	Irwin Silty Clay Loam, 1 To 3 Percent Slopes-----	943	0.2
197ID	Irwin Silty Clay Loam, 3 To 7 Percent Slopes-----	221	*
197IV	Ivan Silt Loam, Occasionally Flooded-----	167	*
197IX	Ivan Silty Clay Loam, Channeled-----	148	*
197PN	Pawnee Clay Loam, 3 To 7 Percent Slopes-----	43	*
197WE	Wamego Silty Clay Loam, 3 To 7 Percent Slopes-----	2	*
201CS	Crete Silty Clay Loam, 1 To 3 Percent Slopes-----	4,433	1.1
201CX	Crete Silty Clay Loam, 3 To 7 Percent Slopes, Eroded-----	367	*
201KS	Kipson-Sogn Complex, 5 To 30 Percent Slopes-----	145	*
201LC	Lancaster Loam, 3 To 7 Percent Slopes-----	4	*
Ad	Ivan Silt Loam, Channeled-----	8,516	2.1
AED	Arents, Earthen Dam-----	58	*
BE	Benfield Silty Clay Loam, 3 To 7 Percent Slopes-----	205	*
Bf	Benfield-Florence Complex, 5 To 20 Percent Slopes-----	21,072	5.3
Bk	Wymore-Kennebec Complex, 0 To 17 Percent Slopes-----	9,308	2.3
BOP	Borrow Pits-----	440	0.1
Ca	Carr-Sarpy Complex, Occasionally Flooded-----	2,659	0.7
Ch	Chase Silty Clay Loam, Rarely Flooded-----	4,209	1.1
Cs	Clime-Sogn Complex, 5 To 20 Percent Slopes-----	72,934	18.3
CT	Crete Silty Clay Loam, 3 To 7 Percent Slopes-----	1,257	0.3
Dr	Dwight-Irwin Complex, 1 To 4 Percent Slopes-----	16,844	4.2
Dw	Dwight-Irwin Complex, 1 To 4 Percent Slopes, Eroded-----	13,417	3.4
Em	Elmont Silt Loam, 3 To 8 Percent Slopes-----	1,561	0.4
En	Elmont-Clime Complex, 5 To 15 Percent Slopes-----	520	0.1
Eu	Eudora Silt Loam, Rarely Flooded-----	4,866	1.2
Ga	Geary Silt Loam, 1 To 4 Percent Slopes-----	560	0.1
Ge	Geary Silt Loam, 4 To 8 Percent Slopes-----	2,682	0.7
Ha	Haynie Very Fine Sandy Loam, Occasionally Flooded-----	5,412	1.4
HO	Hobbs Silt Loam, Occasionally Flooded-----	597	0.1
Ic	Irwin Silty Clay Loam, 4 To 8 Percent Slopes-----	18,716	4.7
Id	Irwin Silty Clay Loam, 4 To 8 Percent Slopes, Eroded-----	28,212	7.1
Ie	Ivan Silty Clay Loam, 1 To 3 Percent Slopes-----	494	0.1
Iv	Ivan And Kennebec Silt Loams, Occasionally Flooded-----	12,568	3.2
Ka	Kahola Silt Loam, Rarely Flooded-----	1,058	0.3
Ke	Kenesaw Silt Loam, 2 To 6 Percent Slopes-----	142	*
Kf	Kenesaw Silt Loam, 6 To 10 Percent Slopes-----	173	*
KN	Kennebec Silt Loam, Occasionally Flooded-----	72	*
M-W	Miscellaneous Water-----	86	*
Ma	Mayberry Clay Loam, 2 To 6 Percent Slopes-----	1,159	0.3
Mb	Mayberry Clay Loam, 2 To 6 Percent Slopes, Eroded-----	1,213	0.3
Mu	Muir Silt Loam, Rarely Flooded-----	3,389	0.9
QUA	Quarries-----	237	*
Rd	Reading Silt Loam, 0 To 1 Percent Slopes, Rarely Flooded-----	12,001	3.0
Re	Reading Silt Loam, 1 To 3 Percent Slopes, Rarely Flooded-----	6,292	1.6
Sa	Sarpy Loamy Fine Sand, 0 To 4 Percent Slopes, Occasionally Flooded-----	2,171	0.5
Sm	Smolan Silt Loam, 1 To 4 Percent Slopes-----	3,567	0.9
Sn	Smolan Silt Loam, 4 To 8 Percent Slopes-----	2,541	0.6
So	Smolan Silty Clay Loam, 4 To 8 Percent Slopes, Eroded-----	1,727	0.4
St	Clime Silty Clay Loam, 20 To 40 Percent Slopes, Stony-----	17,666	4.4
Su	Sutphen Silty Clay, Occasionally Flooded-----	2,381	0.6
Ts	Tully Silty Clay Loam, 1 To 4 Percent Slopes-----	572	0.1
Tt	Tully Silty Clay Loam, 1 To 4 Percent Slopes, Eroded-----	1,249	0.3
Tu	Tully Silty Clay Loam, 4 To 8 Percent Slopes-----	6,865	1.7
Tv	Tully Silty Clay Loam, 4 To 8 Percent Slopes, Eroded-----	8,111	2.0
W	Water-----	7,932	2.0
Wm	Wymore Silty Clay Loam, 0 To 1 Percent Slopes-----	2,359	0.6
Wn	Wymore Silty Clay Loam, 1 To 4 Percent Slopes-----	12,696	3.2
Wo	Wymore Silty Clay Loam, 1 To 4 Percent Slopes, Eroded-----	40,721	10.2
Wr	Wymore Silty Clay Loam, 4 To 8 Percent Slopes-----	1,414	0.4
Ws	Wymore Silty Clay Loam, 4 To 8 Percent Slopes, Eroded-----	3,079	0.8
	Total-----	398,400	100.0

* Less than 0.1 percent.

NONTECHNICAL SOIL DESCRIPTIONS
Riley County, Kansas

Nontechnical soil descriptions describe soil properties or management considerations specific to a soil map unit or group of map units, shown in the NonTechnical Descriptions report. These descriptions are written in terminology that Non-technical users of soil survey information can understand. Nontechnical soil descriptions are a powerful tool for creating reports. These high quality, easy to read reports can be generated by conservation planners and other NRCS employees for distribution to land users. Soil map unit descriptions and National Soil Information System records are the basis for these descriptions.

027CS Crete Silt Loam, 1 To 3 Percent Slopes

Crete soil makes up 90 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping shoulder, backslope hillslope on upland. The runoff class is high. The parent material consists of silty and clayey loess. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 2e.

027CX Crete Silty Clay Loam, 3 To 8 Percent Slopes, Eroded

Crete soil makes up 83 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillside on upland. The runoff class is very high. The parent material consists of silty and clayey loess. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 4e.

027HN Hobbs Silt Loam, Channeled

Hobbs soil makes up 90 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on meander belt. The runoff class is low. The parent material consists of fine-silty alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is frequently flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Lowland (pe25-34) range site. It is in the nonirrigated land capability classification 5w.

027KS Kipson-Sogn Silty Clay Loams, 5 To 20 Percent Slopes

Kipson soil makes up 70 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep hillslope on upland. The runoff class is high. The parent material consists of loamy residuum weathered from limestone and shale. The soil is 7 to 20 inches deep to bedrock (paralithic). This soil is somewhat excessively drained. The slowest permeability is moderate. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 60 percent calcium carbonate. This soil is in the Limy Upland (pe25-34) range site. It is in the nonirrigated land capability classification 6e.

Sogn soil makes up 15 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep hillslope on upland. The runoff class is medium. The parent material consists of loamy residuum weathered from limestone and shale. The soil is 4 to 20 inches deep to bedrock (lithic). This soil is somewhat excessively drained. The slowest permeability is moderate. It has a very low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Shallow Limy (pe25-34) range site. It is in the nonirrigated land capability classification 6e.

061BE Benfield-Florence Complex, 5 To 30 Percent Slopes

Benfield soil makes up 42 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to steep backslope hillslope on upland. The runoff class is very high. The parent material consists of clayey pedisidiment derived from limestone and shale over clayey residuum weathered from calcareous shale. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 6e.

Florence soil makes up 28 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep backslope hillslope on upland. The runoff class is high. The parent material consists of gravelly residuum weathered from cherty limestone. The soil is 40 to 60 inches deep to bedrock (lithic). This soil is well drained. The slowest permeability is moderately slow. It has a low available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 6e.

NONTECHNICAL SOIL DESCRIPTIONS--Continued
Riley County, Kansas

061CF Clime-Sogn Silty Clay Loams, 5 To 20 Percent Slopes

Clime soil makes up 60 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey residuum weathered from shale, calcareous. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 35 percent calcium carbonate. This soil is in the Limy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 6e.

Sogn soil makes up 20 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately steep hillslope, upland. The runoff class is medium. The parent material consists of loamy residuum weathered from limestone, unspecified. The soil is 4 to 20 inches deep to bedrock (lithic). This soil is somewhat excessively drained. The slowest permeability is moderate. It has a very low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Shallow Limy (pe30-36) range site. It is in the nonirrigated land capability classification 6s.

061CR Crete Silty Clay Loam, 0 To 1 Percent Slopes

Crete soil makes up 90 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level shoulder, summit ridge on upland. The runoff class is medium. The parent material consists of loess. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 2s.

061CS Crete Silty Clay Loam, 1 To 4 Percent Slopes

Crete soil makes up 90 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping shoulder, backslope hillslope on upland. The runoff class is high. The parent material consists of loess. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 2e.

061EU Eudora Silt Loam, Occasionally Flooded

Eudora soil makes up 85 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on river valley. The runoff class is low. The parent material consists of loamy alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a low shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 2w.

061HE Haynie Silt Loam, Frequently Flooded

Haynie soil makes up 55 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on river valley. The runoff class is low. The parent material consists of coarse-silty alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a low shrink swell potential. This soil is frequently flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 30 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 5w.

061KA Kahola Silt Loam, Channeled

Kahola soil makes up 75 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on meander belt. The runoff class is low. The parent material consists of silty alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is frequently flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 5w.

061KB Kahola Silt Loam, Occasionally Flooded

Kahola soil makes up 75 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is low. The parent material consists of silty alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 2w.

NONTECHNICAL SOIL DESCRIPTIONS--Continued
Riley County, Kansas

061RE Reading Silty Clay Loam, 0 To 2 Percent Slopes

Reading soil makes up 85 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is low. The parent material consists of silty alluvium. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is rarely flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 1.

061TO Tully Silty Clay Loam, 3 To 8 Percent Slopes

Tully soil makes up 85 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping footslope hillslope on upland. The runoff class is very high. The parent material consists of clayey colluvium. This soil is well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 3e.

117PA Pawnee Clay Loam, 1 To 4 Percent Slopes

Pawnee soil makes up 88 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping hillslope on upland. The runoff class is medium. The parent material consists of clayey drift. This soil is moderately well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 2e.

117PB Pawnee Clay Loam, 4 To 8 Percent Slopes

Pawnee soil makes up 88 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping hillslope on upland. The runoff class is very high. The parent material consists of clayey drift. This soil is moderately well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

149HS Haynie-Sarpy Complex, Occasionally Flooded

Haynie soil makes up 60 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level flood-plain step on river valley. The runoff class is low. The parent material consists of coarse-silty alluvium. This soil is moderately well drained. The slowest permeability is moderate. It has a very high available water capacity and a low shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 30 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 3w.

Sarpy soil makes up 25 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on river valley. The runoff class is negligible. The parent material consists of sandy alluvium. This soil is excessively drained. The slowest permeability is rapid. It has a low available water capacity and a low shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Sandy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 3w.

149PS Paxico Silt Loam, Frequently Flooded

Paxico soil makes up 90 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level flood plain on river valley. The runoff class is low. The parent material consists of loamy alluvium over sandy alluvium. This soil is somewhat poorly drained. The slowest permeability is moderate. It has a high available water capacity and a low shrink swell potential. This soil is very rare flooded and is not ponded. The top of the seasonal high water table is at 27 inches. The soil contains a maximum amount of 15 percent calcium carbonate. It is in the nonirrigated land capability classification 5w.

149SF Sarpy Sand, Frequently Flooded

Sarpy soil makes up 90 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on river valley. The runoff class is negligible. The parent material consists of sandy alluvium. This soil is excessively drained. The slowest permeability is rapid. It has a low available water capacity and a low shrink swell potential. This soil is frequently flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Sandy Lowland (pe30-37) range site. It is in the nonirrigated land capability classification 4s.

NONTECHNICAL SOIL DESCRIPTIONS--Continued
Riley County, Kansas

197CM Clime Silty Clay Loam, 3 To 7 Percent Slopes

Clime soil makes up 85 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping backslope hillslope on upland. The runoff class is high. The parent material consists of silty and clayey residuum weathered from calcareous shale. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Limy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 4e.

197FL Florence-Labette Complex, 3 To 15 Percent Slopes

Florence soil makes up 40 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep backslope hillslope on upland. The runoff class is high. The parent material consists of clayey residuum weathered from cherty limestone. The soil is 40 to 60 inches deep to bedrock (lithic). This soil is well drained. The slowest permeability is moderately slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 6e.

Labette soil makes up 30 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping shoulder ridge on upland. The runoff class is high. The parent material consists of silty and clayey residuum weathered from limestone and shale. The soil is 20 to 40 inches deep to bedrock (lithic). This soil is well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 6e.

197IB Irwin Silty Clay Loam, 1 To 3 Percent Slopes

Irwin soil makes up 80 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a gently sloping shoulder hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey residuum weathered from clayey shale. This soil is moderately well drained. The slowest permeability is very slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Clay Upland (pe30-36) range site. It is in the nonirrigated land capability classification 3e.

197ID Irwin Silty Clay Loam, 3 To 7 Percent Slopes

Irwin soil makes up 85 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping backslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey alluvium over clayey residuum weathered from limestone and shale. This soil is moderately well drained. The slowest permeability is very slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 3 percent calcium carbonate. This soil contains a very slightly saline horizon, it has a horizon that is slightly sodic. This soil is in the Clay Upland (pe30-36) range site. It is in the nonirrigated land capability classification 4e.

197IV Ivan Silt Loam, Occasionally Flooded

Ivan soil makes up 90 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is low. The parent material consists of calcareous fine-silty alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 10 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 2w.

197IX Ivan Silty Clay Loam, Channeled

Ivan soil makes up 80 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is low. The parent material consists of calcareous fine-silty alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is frequently flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 10 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 5w.

197PN Pawnee Clay Loam, 3 To 7 Percent Slopes

Pawnee soil makes up 85 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping backslope hillslope on upland. The runoff class is high. The parent material consists of clayey drift. This soil is moderately well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

NONTECHNICAL SOIL DESCRIPTIONS--Continued
Riley County, Kansas

197WE Wamego Silty Clay Loam, 3 To 7 Percent Slopes

Wamego soil makes up 90 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping backslope hillslope on upland. The runoff class is high. The parent material consists of sandy and silty residuum weathered from shale, unspecified. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 4e.

201CS Crete Silty Clay Loam, 1 To 3 Percent Slopes

Crete soil makes up 95 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping hillslope on upland. The runoff class is high. The parent material consists of silty and clayey loess. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe26-30) range site. It is in the nonirrigated land capability classification 2e.

201CX Crete Silty Clay Loam, 3 To 7 Percent Slopes, Eroded

Crete, eroded, soil makes up 90 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping hillslope on upland. The runoff class is high. The parent material consists of silty and clayey loess. This soil is moderately well drained. The slowest permeability is impermeable. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe26-30) range site. It is in the nonirrigated land capability classification 4e.

201KS Kipson-Sogn Complex, 5 To 30 Percent Slopes

Kipson soil makes up 70 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to steep backslope hillslope on upland. The runoff class is medium. The parent material consists of loamy residuum weathered from limestone and shale. The soil is 7 to 20 inches deep to bedrock (paralithic). This soil is somewhat excessively drained. The slowest permeability is moderate. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 60 percent calcium carbonate. This soil is in the Limy Upland (pe26-30) range site. It is in the nonirrigated land capability classification 6e.

Sogn soil makes up 15 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep shoulder hillslope on upland. The runoff class is medium. The parent material consists of loamy residuum weathered from limestone. The soil is 4 to 20 inches deep to bedrock (lithic). This soil is somewhat excessively drained. The slowest permeability is moderate. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 8 percent calcium carbonate. This soil is in the Shallow Limy (pe26-30) range site. It is in the nonirrigated land capability classification 6e.

201LC Lancaster Loam, 3 To 7 Percent Slopes

Lancaster soil makes up 85 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping hillslope on upland. The runoff class is medium. The parent material consists of loamy residuum weathered from sandstone and shale. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is moderate. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe26-30) range site. It is in the nonirrigated land capability classification 4e.

Ad Ivan Silt Loam, Channeled

Ivan soil makes up 99 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on alluvial plain. The runoff class is low. The parent material consists of loamy alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is frequently flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Loamy Lowland (pe25-34) range site. It is in the nonirrigated land capability classification 5w.

BE Benfield Silty Clay Loam, 3 To 7 Percent Slopes

Benfield soil makes up 89 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping hillslope on upland. The runoff class is high. The parent material consists of silty loess over clayey residuum. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe25-34) range site. It is in the nonirrigated land capability classification 4e.

NONTECHNICAL SOIL DESCRIPTIONS--Continued
Riley County, Kansas

Bf Benfield-Florence Complex, 5 To 20 Percent Slopes

Benfield soil makes up 45 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep hillslope on upland. The runoff class is very high. The parent material consists of clayey residuum weathered from limestone and shale. The soil is 22 to 39 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 6e.

Florence soil makes up 30 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep hillslope on upland. The runoff class is high. The parent material consists of clayey residuum weathered from cherty limestone. The soil is 24 to 39 inches deep to bedrock (lithic). This soil is well drained. The slowest permeability is moderately slow. It has a very low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 6e.

Bk Wymore-Kennebec Complex, 0 To 17 Percent Slopes

Wymore soil makes up 60 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a strongly sloping to moderately steep footslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey loess over clayey pedisidiment. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 6e.

Kennebec soil makes up 45 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level flood plain on alluvial plain. The runoff class is low. The parent material consists of fine-silty alluvium. This soil is moderately well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is occasionally flooded and is not ponded. The top of the seasonal high water table is at 48 inches. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 1.

Ca Carr-Sarpy Complex, Occasionally Flooded

Carr soil makes up 45 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level flood plain on river valley. The runoff class is negligible. The parent material consists of loamy alluvium. This soil is well drained. The slowest permeability is moderately rapid. It has a high available water capacity and a low shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 10 percent calcium carbonate. This soil is in the Sandy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 3w.

Sarpy soil makes up 40 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level flood plain on river valley. The runoff class is negligible. The parent material consists of sandy alluvium. This soil is excessively drained. The slowest permeability is rapid. It has a low available water capacity and a low shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Sands (pe30-36) range site. It is in the nonirrigated land capability classification 3w.

Ch Chase Silty Clay Loam, Rarely Flooded

Chase soil makes up 84 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level terrace on river valley. The runoff class is high. The parent material consists of silty and clayey alluvium. This soil is somewhat poorly drained. The slowest permeability is slow. It has a moderate available water capacity and a very high shrink swell potential. This soil is rarely flooded and is not ponded. The top of the seasonal high water table is at 36 inches. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 2w.

Cs Clime-Sogn Complex, 5 To 20 Percent Slopes

Clime soil makes up 50 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey residuum weathered from shale, calcareous. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 10 percent calcium carbonate. This soil is in the Limy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 6e.

Sogn soil makes up 30 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping hillslope on upland. The runoff class is medium. The parent material consists of loamy residuum weathered from limestone, unspecified. The soil is 4 to 20 inches deep to bedrock (lithic). This soil is somewhat excessively drained. The slowest permeability is moderate. It has a very low available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Shallow Limy (pe30-36) range site. It is in the nonirrigated land capability classification 6e.

NONTECHNICAL SOIL DESCRIPTIONS--Continued
Riley County, Kansas

CT Crete Silty Clay Loam, 3 To 7 Percent Slopes

Crete soil makes up 83 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping backslope hillside on upland. The runoff class is high. The parent material consists of silty and clayey loess. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 3e.

Dr Dwight-Irwin Complex, 1 To 4 Percent Slopes

Dwight soil makes up 45 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping summit depression on ridge on upland. The runoff class is very high. The parent material consists of silty and clayey residuum weathered from limestone, cherty. The soil is 40 to 60 inches deep to bedrock (lithic). This soil is moderately well drained. The slowest permeability is very slow. It has a low available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil contains a slightly saline horizon. This soil is in the Clay Pan (pe25-34) range site. It is in the nonirrigated land capability classification 4e.

Irwin soil makes up 40 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping ridge on upland. The runoff class is very high. The parent material consists of clayey pediment derived from limestone and shale. The soil is 40 to 60 inches deep to bedrock (paralithic). This soil is moderately well drained. The slowest permeability is very slow. It has a moderate available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 4e.

Dw Dwight-Irwin Complex, 1 To 4 Percent Slopes, Eroded

Dwight soil makes up 45 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping summit depression on divide on upland. The runoff class is very high. The parent material consists of silty and clayey residuum weathered from limestone, cherty. The soil is 40 to 60 inches deep to bedrock (lithic). This soil is moderately well drained. The slowest permeability is very slow. It has a low available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil contains a slightly saline horizon. This soil is in the Clay Pan (pe25-34) range site. It is in the nonirrigated land capability classification 4e.

Irwin soil makes up 40 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping summit divide on upland. The runoff class is very high. The parent material consists of clayey pediment derived from limestone and shale. The soil is 40 to 60 inches deep to bedrock (paralithic). This soil is moderately well drained. The slowest permeability is very slow. It has a moderate available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 4e.

Em Elmont Silt Loam, 3 To 8 Percent Slopes

Elmont soil makes up 74 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillside on upland. The runoff class is high. The parent material consists of silty and clayey residuum weathered from shale-siltstone. The soil is 40 to 60 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is moderately slow. It has a moderate available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 3e.

En Elmont-Clime Complex, 5 To 15 Percent Slopes

Elmont soil makes up 35 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillside on upland. The runoff class is high. The parent material consists of silty and clayey residuum weathered from shale-siltstone. The soil is 40 to 60 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is moderately slow. It has a moderate available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 6e.

Clime soil makes up 30 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to moderately steep backslope hillside on upland. The runoff class is high. The parent material consists of silty and clayey residuum weathered from shale, calcareous. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 20 percent calcium carbonate. This soil is in the Limy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 6e.

NONTECHNICAL SOIL DESCRIPTIONS--Continued
Riley County, Kansas

Eu Eudora Silt Loam, Rarely Flooded

Eudora soil makes up 88 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on river valley. The runoff class is low. The parent material consists of loamy alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a low shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 2w.

Ga Geary Silt Loam, 1 To 4 Percent Slopes

Geary soil makes up 90 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping backslope hillside on upland. The runoff class is low. The parent material consists of silty loess. This soil is well drained. The slowest permeability is moderate. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 2e.

Ge Geary Silt Loam, 4 To 8 Percent Slopes

Geary soil makes up 90 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillside on upland. The runoff class is medium. The parent material consists of silty loess. This soil is well drained. The slowest permeability is moderate. It has a high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 3e.

Ha Haynie Very Fine Sandy Loam, Occasionally Flooded

Haynie soil makes up 90 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level flood plain on river valley. The runoff class is negligible. The parent material consists of loamy alluvium. This soil is moderately well drained. The slowest permeability is moderately slow. It has a high available water capacity and a low shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 25 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 1.

HO Hobbs Silt Loam, Occasionally Flooded

Hobbs soil makes up 89 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on alluvial plain. The runoff class is low. The parent material consists of fine-silty alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Lowland (pe25-34) range site. It is in the nonirrigated land capability classification 2w.

Ic Irwin Silty Clay Loam, 4 To 8 Percent Slopes

Irwin soil makes up 85 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping hillslope on upland. The runoff class is very high. The parent material consists of clayey pediment derived from shale. The soil is 40 to 60 inches deep to bedrock (paralithic). This soil is moderately well drained. The slowest permeability is very slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 4e.

Id Irwin Silty Clay Loam, 4 To 8 Percent Slopes, Eroded

Irwin, eroded, soil makes up 85 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping hillslope on upland. The runoff class is very high. The parent material consists of clayey pediment derived from shale. The soil is 40 to 60 inches deep to bedrock (paralithic). This soil is moderately well drained. The slowest permeability is very slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 4e.

Ie Ivan Silty Clay Loam, 1 To 3 Percent Slopes

Ivan soil makes up 88 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a gently sloping flood plain on valley. The runoff class is low. The parent material consists of calcareous fine-silty colluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 10 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 2e.

NONTECHNICAL SOIL DESCRIPTIONS--Continued
Riley County, Kansas

Iv Ivan And Kennebec Silt Loams, Occasionally Flooded

Ivan soil makes up 45 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level flood plain on valley. The runoff class is negligible. The parent material consists of calcareous fine-silty alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 10 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 2w.

Kennebec soil makes up 45 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level flood plain on valley. The runoff class is low. The parent material consists of fine-silty alluvium. This soil is moderately well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is occasionally flooded and is not ponded. The top of the seasonal high water table is at 48 inches. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 1.

Ka Kahola Silt Loam, Rarely Flooded

Kahola soil makes up 85 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level flood plain on river valley. The runoff class is negligible. The parent material consists of fine-silty alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is rarely flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 15 percent calcium carbonate. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 1.

Ke Kenesaw Silt Loam, 2 To 6 Percent Slopes

Kenesaw soil makes up 90 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping hillslope on upland. The runoff class is low. The parent material consists of coarse-silty loess. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a low shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 3e.

Kf Kenesaw Silt Loam, 6 To 10 Percent Slopes

Kenesaw soil makes up 85 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping hillslope on upland. The runoff class is medium. The parent material consists of coarse-silty loess. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a low shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 4e.

KN Kennebec Silt Loam, Occasionally Flooded

Kennebec soil makes up 95 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on valley. The runoff class is low. The parent material consists of fine-silty alluvium. This soil is moderately well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is occasionally flooded and is not ponded. The top of the seasonal high water table is at 42 inches. This soil is in the Loamy Lowland (pe35-42) range site. It is in the nonirrigated land capability classification 2w.

Ma Mayberry Clay Loam, 2 To 6 Percent Slopes

Mayberry soil makes up 95 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping backslope hillslope on upland. The runoff class is high. The parent material consists of till, unspecified. This soil is moderately well drained. The slowest permeability is slow. It has a moderate available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe30-37) range site. It is in the nonirrigated land capability classification 3e.

Mb Mayberry Clay Loam, 2 To 6 Percent Slopes, Eroded

Mayberry soil makes up 95 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping upland on hillslope. The runoff class is high. The parent material consists of clayey till. This soil is moderately well drained. The slowest permeability is slow. It has a moderate available water capacity and a very high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 12 inches. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Clay Upland (pe30-36) range site. It is in the nonirrigated land capability classification 3e.

NONTECHNICAL SOIL DESCRIPTIONS--Continued
Riley County, Kansas

Mu Muir Silt Loam, Rarely Flooded

Muir soil makes up 84 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level to gently sloping flood plain on alluvial plain. The runoff class is low. The parent material consists of silty alluvium. This soil is well drained. The slowest permeability is moderate. It has a very high available water capacity and a moderate shrink swell potential. This soil is rarely flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 2 percent calcium carbonate. This soil is in the Loamy Terrace (pe25-34) range site. It is in the nonirrigated land capability classification 1.

Rd Reading Silt Loam, 0 To 1 Percent Slopes, Rarely Flooded

Reading soil makes up 90 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level terrace on river valley. The runoff class is low. The parent material consists of fine-silty alluvium. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is rarely flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 1.

Re Reading Silt Loam, 1 To 3 Percent Slopes, Rarely Flooded

Reading soil makes up 90 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a gently sloping alluvial fan on river valley. The runoff class is medium. The parent material consists of fine-silty alluvium. This soil is well drained. The slowest permeability is moderately slow. It has a high available water capacity and a moderate shrink swell potential. This soil is rarely flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Lowland (pe30-36) range site. It is in the nonirrigated land capability classification 2e.

Sa Sarpy Loamy Fine Sand, 0 To 4 Percent Slopes, Occasionally Flooded

Sarpy soil makes up 98 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level to moderately sloping flood plain on river valley. The runoff class is negligible. The parent material consists of sandy alluvium. This soil is excessively drained. The slowest permeability is rapid. It has a low available water capacity and a low shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Sands (pe30-36) range site. It is in the nonirrigated land capability classification 4s.

Sm Smolan Silt Loam, 1 To 4 Percent Slopes

Smolan soil makes up 90 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping hillslope on upland. The runoff class is high. The parent material consists of silty and clayey loess. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 2e.

Sn Smolan Silt Loam, 4 To 8 Percent Slopes

Smolan soil makes up 75 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey loess. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 3e.

So Smolan Silty Clay Loam, 4 To 8 Percent Slopes, Eroded

Smolan, eroded, soil makes up 80 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey loess. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Clay Upland (pe30-36) range site. It is in the nonirrigated land capability classification 4e.

St Clime Silty Clay Loam, 20 To 40 Percent Slopes, Stony

Clime soil makes up 75 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a steep to steep backslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey residuum weathered from shale, calcareous. The soil is 20 to 40 inches deep to bedrock (paralithic). This soil is well drained. The slowest permeability is slow. It has a low available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 35 percent calcium carbonate. This soil is in the Limy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 7e.

NONTECHNICAL SOIL DESCRIPTIONS--Continued
Riley County, Kansas

Su Sutphen Silty Clay, Occasionally Flooded

Sutphen soil makes up 100 percent of the map unit. This map unit is in the Bluestem Hills Major Land Resource Area. This soil occurs on a nearly level flood plain on river valley. The runoff class is very high. The parent material consists of clayey alluvium. This soil is somewhat poorly drained. The slowest permeability is very slow. It has a moderate available water capacity and a high shrink swell potential. This soil is occasionally flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 3 percent calcium carbonate. This soil is in the Clay Lowland (pe26-30) range site. It is in the nonirrigated land capability classification 3w.

Ts Tully Silty Clay Loam, 1 To 4 Percent Slopes

Tully soil makes up 85 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping footslope hillslope on upland. The runoff class is high. The parent material consists of clayey colluvium. This soil is well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. The soil contains a maximum amount of 5 percent calcium carbonate. This soil is in the Loamy Upland (pe30-36) range site. It is in the nonirrigated land capability classification 2e.

Tt Tully Silty Clay Loam, 1 To 4 Percent Slopes, Eroded

Tully, eroded, soil makes up 85 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping footslope hillslope on upland. The runoff class is high. The parent material consists of clayey colluvium. This soil is well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 3e.

Tu Tully Silty Clay Loam, 4 To 8 Percent Slopes

Tully soil makes up 85 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping footslope hillslope on upland. The runoff class is very high. The parent material consists of clayey colluvium. This soil is well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Loamy Upland (pe25-34) range site. It is in the nonirrigated land capability classification 3e.

Tv Tully Silty Clay Loam, 4 To 8 Percent Slopes, Eroded

Tully, eroded, soil makes up 85 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping footslope hillslope on upland. The runoff class is very high. The parent material consists of clayey colluvium. This soil is well drained. The slowest permeability is slow. It has a moderate available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The seasonal high water table is at a depth of more than 6 feet. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 4e.

Wm Wymore Silty Clay Loam, 0 To 1 Percent Slopes

Wymore soil makes up 100 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a nearly level summit hillslope on upland. The runoff class is medium. The parent material consists of silty and clayey loess over clayey pedisidement. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. This soil is in the Loamy Upland (pe25-34) range site. It is in the nonirrigated land capability classification 2s.

Wn Wymore Silty Clay Loam, 1 To 4 Percent Slopes

Wymore soil makes up 90 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping backslope, shoulder hillslope on upland. The runoff class is high. The parent material consists of silty and clayey loess over clayey pedisidement. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. This soil is in the Loamy Upland (pe25-34) range site. It is in the nonirrigated land capability classification 2e.

Wo Wymore Silty Clay Loam, 1 To 4 Percent Slopes, Eroded

Wymore, eroded, soil makes up 90 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a gently sloping to moderately sloping backslope hillslope on upland. The runoff class is high. The parent material consists of silty and clayey loess over clayey pedisidement. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 3e.

NONTECHNICAL SOIL DESCRIPTIONS--Continued
Riley County, Kansas

Wr Wymore Silty Clay Loam, 4 To 8 Percent Slopes

Wymore soil makes up 90 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey loess over clayey pedisidiment. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. This soil is in the Loamy Upland (pe25-34) range site. It is in the nonirrigated land capability classification 3e.

Ws Wymore Silty Clay Loam, 4 To 8 Percent Slopes, Eroded

Wymore, eroded, soil makes up 90 percent of the map unit. This map unit is in the Central Loess Plains Major Land Resource Area. This soil occurs on a moderately sloping to strongly sloping backslope hillslope on upland. The runoff class is very high. The parent material consists of silty and clayey loess over clayey pedisidiment. This soil is moderately well drained. The slowest permeability is slow. It has a high available water capacity and a high shrink swell potential. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. This soil is in the Clay Upland (pe25-34) range site. It is in the nonirrigated land capability classification 4e.

027CS—Crete silt loam, 1 to 3 percent slopes

Map Unit Composition

Crete: 90 percent
Minor components: 10 percent

Component Descriptions

Crete

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Shoulder, backslope
Parent material: Silty and clayey loess
Slope: 1 to 3 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 10.1 inches)
Shrink-swell potential: Very high (About 9.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 2e

Typical Profile:

Ap—0 to 6 inches; silty clay loam
BA—6 to 11 inches; silty clay loam
Bt—11 to 27 inches; silty clay
Btk—27 to 40 inches; silty clay loam
BC—40 to 60 inches; silty clay loam

Minor Components

Geary

Composition: About 2 percent
Landform: hillslope on upland
Slope: 2 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Benfield

Composition: About 2 percent
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Hobbs

Composition: About 2 percent
Slope: 0 to 3 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe25-34)

Lancaster

Composition: About 2 percent
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe26-30)

Holder

Composition: About 2 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

027CX—Crete silty clay loam, 3 to 8 percent slopes, eroded

Map Unit Composition

Crete: 83 percent
Minor components: 17 percent

Component Descriptions

Crete

MLRA: 75 - Central Loess Plains
Landform: Hillside on upland
Hillslope position: Backslope
Parent material: Silty and clayey loess
Slope: 3 to 8 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 9.8 inches)
Shrink-swell potential: Very high (About 9.2 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 7 inches; silty clay loam
Bt—7 to 31 inches; silty clay
C—31 to 60 inches; silty clay loam

Minor Components

Geary

Composition: About 5 percent
Landform: hillslope on upland
Slope: 2 to 7 percent

Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Holder

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Benfield

Composition: About 3 percent
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches
to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Hobbs

Composition: About 2 percent
Slope: 0 to 3 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe25-34)

Lancaster

Composition: About 2 percent
Slope: 5 to 12 percent
Depth to restrictive feature: 20 to 40 inches
to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe26-30)

**027HN—Hobbs silt loam,
channeled****Map Unit Composition**

Hobbs: 90 percent
Minor components: 10 percent

Component Descriptions**Hobbs**

MLRA: 75 - Central Loess Plains
Landform: Flood plain on meander belt
Parent material: Fine-silty alluvium
Slope: 0 to 2 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60
in/hr)
Available water capacity: High (About 11.9
inches)
Shrink-swell potential: Moderate (About 3.3
LEP)
Flooding hazard: Frequent
Ponding hazard: None

Depth to seasonal water saturation: More than 6
feet

Runoff class: Low

Ecological site: Loamy Lowland (pe25-34)

Land capability (nonirrigated): 5w

Typical Profile:

A—0 to 8 inches; silt loam
C1—8 to 24 inches; silt loam
C2—24 to 44 inches; silt loam
C3—44 to 60 inches; silt loam

Minor Components**Unnamed Hydric Soil (ponding)**

Composition: About 2 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 2 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Crete

Composition: About 2 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Geary

Composition: About 2 percent
Landform: hillslope on upland
Slope: 2 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Muir

Composition: About 2 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Terrace (pe25-34)

**027KS—Kipson-Sogn silty clay
loams, 5 to 20 percent slopes****Map Unit Composition**

Kipson: 70 percent
Sogn: 15 percent
Minor components: 15 percent

Component Descriptions**Kipson**

MLRA: 75 - Central Loess Plains

Landform: Hillslope on upland
Parent material: Loamy residuum weathered from limestone and shale
Slope: 5 to 20 percent
Depth to restrictive feature: 7 to 20 inches to bedrock (paralithic)
Drainage class: Somewhat excessively drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Low (About 3.3 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Limy Upland (pe25-34)
Land capability (nonirrigated): 6e

Typical Profile:

A—0 to 8 inches; silty clay loam
 AC—8 to 18 inches; silty clay loam
 Cr—18 to 22 inches; weathered bedrock

Sogn

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Parent material: Loamy residuum weathered from limestone and shale
Slope: 5 to 20 percent
Depth to restrictive feature: 4 to 20 inches to bedrock (lithic)
Drainage class: Somewhat excessively drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very low (About 2.4 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Shallow Limy (pe25-34)
Land capability (nonirrigated): 6e

Typical Profile:

A—0 to 12 inches; silty clay loam
 R—12 to 16 inches; unweathered bedrock

Minor Components**Tully**

Composition: About 5 percent
Slope: 2 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Benfield

Composition: About 5 percent
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Geary

Composition: About 2 percent
Landform: hillslope on upland
Slope: 2 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Unnamed Hydric Soil (saturation)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Rock outcrop

Composition: About 1 percent

Crete

Composition: About 1 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

061BE—Benfield-Florence complex, 5 to 30 percent slopes**Map Unit Composition**

Benfield: 42 percent
 Florence: 28 percent
 Minor components: 30 percent

Component Descriptions**Benfield**

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Clayey pediment derived from limestone and shale over clayey residuum
 weathered from calcareous shale
Slope: 5 to 30 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Low (About 5.7 inches)

Shrink-swell potential: High (About 8.9 LEP)
Flooding hazard: None
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 6e

Typical Profile:

A1—0 to 5 inches; silty clay loam
 A2—5 to 10 inches; silty clay loam
 Bt1—10 to 19 inches; gravelly silty clay
 Bt2—19 to 34 inches; silty clay
 2Btk—34 to 38 inches; silty clay
 2Cr—38 to 56 inches; weathered bedrock

Florence

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Gravelly residuum weathered from cherty limestone
Slope: 5 to 15 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (lithic)
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: Low (About 4.6 inches)
Shrink-swell potential: Very high (About 9.2 LEP)
Flooding hazard: None
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 6e

Typical Profile:

A1—0 to 5 inches; gravelly silt loam
 A2—5 to 14 inches; very gravelly silty clay
 Bt—14 to 48 inches; very cobbly clay
 Btk—48 to 56 inches; extremely cobbly silty clay
 R—56 to 60 inches; unweathered bedrock

Minor Components**Clime**

Composition: About 10 percent
Landform: hillslope on upland
Slope: 20 to 40 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

Konza

Composition: About 10 percent
Landform: ridge on upland
Slope: 1 to 3 percent
Drainage class: Moderately well drained
Ecological site: Clay Pan (pe30-36)

Labette

Composition: About 3 percent
Slope: 0 to 4 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (lithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Irwin

Composition: About 2 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-36)

Tully

Composition: About 2 percent
Landform: hillslope on upland
Slope: 8 to 15 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Kahola

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Ivan

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Rock outcrop

Composition: About 1 percent

061CF—Clime-Sogn silty clay loams, 5 to 20 percent slopes**Map Unit Composition**

Clime: 60 percent
 Sogn: 20 percent
 Minor components: 20 percent

Component Descriptions**Clime**

MLRA: 76 - Bluestem Hills

Landform: Hillslope on upland
Parent material: Silty and clayey residuum weathered from shale, calcareous
Slope: 5 to 20 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Low (About 5.2 inches)
Shrink-swell potential: High (About 8.4 LEP)
Flooding hazard: None
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Limy Upland (pe30-36)
Land capability (nonirrigated): 6e

Typical Profile:

A—0 to 12 inches; silty clay loam
 Bw—12 to 26 inches; silty clay
 C—26 to 30 inches; silty clay
 Cr—30 to 34 inches; weathered bedrock

Sogn

MLRA: 76 - Bluestem Hills
Landform: Hillslope, upland
Parent material: Loamy residuum weathered from limestone, unspecified
Slope: 1 to 20 percent
Depth to restrictive feature: 4 to 20 inches to bedrock (lithic)
Drainage class: Somewhat excessively drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very low (About 2.0 inches)
Shrink-swell potential: Moderate (About 4.9 LEP)
Flooding hazard: None
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Shallow Limy (pe30-36)
Land capability (nonirrigated): 6s

Typical Profile:

A—0 to 9 inches; silty clay loam
 R—9 to 13 inches; unweathered bedrock

Minor Components**Tully**

Composition: About 12 percent
Landform: hillslope on upland
Slope: 8 to 15 percent
Drainage class: Well drained

Ecological site: Loamy Upland (pe30-36)

Tuttle

Composition: About 2 percent
Landform: hillslope on upland
Slope: 20 to 40 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Somewhat excessively drained

Irwin

Composition: About 2 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-36)

Ivan

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Konza

Composition: About 1 percent
Landform: ridge on upland
Slope: 1 to 3 percent
Drainage class: Moderately well drained
Ecological site: Clay Pan (pe30-36)

Kahola

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Unnamed Hydric Soil (saturation)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

061CR—Crete silty clay loam, 0 to 1 percent slopes**Map Unit Composition**

Crete: 90 percent
 Minor components: 10 percent

Component Descriptions**Crete**

MLRA: 75 - Central Loess Plains
Landform: Ridge on upland
Hillslope position: Shoulder, summit

Parent material: Loess
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 10.3 inches)
Shrink-swell potential: Very high (About 9.5 LEP)
Flooding hazard: None
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 2s

Typical Profile:

Ap—0 to 6 inches; silty clay loam
 BA—6 to 14 inches; silty clay loam
 Bt—14 to 30 inches; silty clay
 Btk—30 to 42 inches; silty clay loam
 BC—42 to 60 inches; silty clay loam

Minor Components**Holder**

Composition: About 5 percent
Landform: hillslope on upland
Slope: 1 to 3 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Hastings

Composition: About 5 percent
Landform: divide on upland
Slope: 1 to 3 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe26-30)

061CS—Crete silty clay loam, 1 to 4 percent slopes**Map Unit Composition**

Crete: 90 percent
 Minor components: 10 percent

Component Descriptions**Crete**

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Shoulder, backslope
Parent material: Loess
Slope: 1 to 4 percent
Drainage class: Moderately well drained

Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 10.1 inches)
Shrink-swell potential: Very high (About 9.5 LEP)
Flooding hazard: None
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 2e

Typical Profile:

Ap—0 to 6 inches; silty clay loam
 BA—6 to 11 inches; silty clay loam
 Bt—11 to 27 inches; silty clay
 Btk—27 to 40 inches; silty clay loam
 BC—40 to 60 inches; silty clay loam

Minor Components**Holder**

Composition: About 4 percent
Landform: hillslope on upland
Slope: 1 to 3 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Hastings

Composition: About 4 percent
Landform: divide on upland
Slope: 1 to 3 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe26-30)

Clime

Composition: About 2 percent
Slope: 1 to 4 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

061EU—Eudora silt loam, occasionally flooded**Map Unit Composition**

Eudora: 85 percent
 Minor components: 15 percent

Component Descriptions**Eudora**

MLRA: 75 - Central Loess Plains

Landform: Flood plain on river valley
Parent material: Loamy alluvium
Slope: 0 to 2 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.1 inches)
Shrink-swell potential: Low (About 2.4 LEP)
Flooding hazard: Occasional
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 2w

Typical Profile:

Ap—0 to 7 inches; silt loam
 A1—7 to 14 inches; silt loam
 A2—14 to 19 inches; silt loam
 C1—19 to 26 inches; silt loam
 C2—26 to 60 inches; very fine sandy loam

Minor Components**Mccook**

Composition: About 10 percent
Slope: 0 to 1 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe25-34)

Sarpy

Composition: About 3 percent
Slope: 0 to 4 percent
Drainage class: Excessively drained
Ecological site: Sandy Lowland (pe30-36)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

061HE—Haynie silt loam, frequently flooded**Map Unit Composition**

Haynie: 55 percent
 Minor components: 45 percent

Component Descriptions**Haynie**

MLRA: 75 - Central Loess Plains
Landform: Flood plain on river valley
Parent material: Coarse-silty alluvium
Slope: 0 to 2 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.4 inches)
Shrink-swell potential: Low (About 2.6 LEP)
Flooding hazard: Frequent
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 5w

Typical Profile:

A—0 to 10 inches; silt loam
 C—10 to 60 inches; very fine sandy loam

Minor Components**Unnamed Stratified Soils (fine-Silty)**

Composition: About 33 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained

Unnamed Stratified Soils (fine)

Composition: About 9 percent
Slope: 0 to 2 percent
Drainage class: Moderately well drained

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Unnamed Stratified Soils (sandy)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Excessively drained

**061KA—Kahola silt loam,
channeled**

Slope: 0 to 2 percent
Drainage class: Poorly drained

Map Unit Composition

Kahola: 75 percent
Minor components: 25 percent

Component Descriptions**Kahola**

MLRA: 75 - Central Loess Plains
Landform: Flood plain on meander belt
Parent material: Silty alluvium
Slope: 0 to 2 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.9 inches)
Shrink-swell potential: Moderate (About 4.0 LEP)
Flooding hazard: Frequent
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 5w

Typical Profile:

A1—0 to 24 inches; silt loam
A2—24 to 36 inches; silt loam
AC—36 to 44 inches; silt loam
C—44 to 60 inches; silt loam

Minor Components**Tully**

Composition: About 13 percent
Landform: hillslope on upland
Slope: 3 to 8 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Ivan

Composition: About 10 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 1 percent

**061KB—Kahola silt loam,
occasionally flooded****Map Unit Composition**

Kahola: 75 percent
Minor components: 25 percent

Component Descriptions**Kahola**

MLRA: 75 - Central Loess Plains
Landform: Flood plain on valley
Parent material: Silty alluvium
Slope: 0 to 2 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.9 inches)
Shrink-swell potential: Moderate (About 4.0 LEP)
Flooding hazard: Occasional
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 2w

Typical Profile:

A1—0 to 24 inches; silt loam
A2—24 to 36 inches; silt loam
AC—36 to 44 inches; silt loam
C—44 to 60 inches; silt loam

Minor Components**Ivan**

Composition: About 10 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Tully

Composition: About 8 percent
Landform: hillslope on upland
Slope: 3 to 8 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Reading

Composition: About 5 percent

Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Unnamed Hydric Soil (ponding)
Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)
Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

061RE—Reading silty clay loam, 0 to 2 percent slopes

Map Unit Composition

Reading: 85 percent
 Minor components: 15 percent

Component Descriptions

Reading

MLRA: 75 - Central Loess Plains
Landform: Flood plain on valley
Parent material: Silty alluvium
Slope: 0 to 2 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 11.7 inches)
Shrink-swell potential: Moderate (About 5.1 LEP)
Flooding hazard: Rare
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 1

Typical Profile:

Ap—0 to 8 inches; silty clay loam
 A—8 to 20 inches; silty clay loam
 Bt1—20 to 52 inches; silty clay loam
 Bt2—52 to 60 inches; silty clay loam

Minor Components

Tully

Composition: About 10 percent
Landform: hillslope on upland
Slope: 1 to 4 percent

Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Kahola

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

061TO—Tully silty clay loam, 3 to 8 percent slopes

Map Unit Composition

Tully: 85 percent
 Minor components: 15 percent

Component Descriptions

Tully

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Footslope
Parent material: Clayey colluvium
Slope: 3 to 8 percent
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 9.1 inches)
Shrink-swell potential: High (About 8.0 LEP)
Flooding hazard: None
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 3e

Typical Profile:

A—0 to 12 inches; silty clay loam
 BA—12 to 21 inches; silty clay loam
 Bt1—21 to 31 inches; silty clay
 Bt2—31 to 40 inches; silty clay
 Bt3—40 to 52 inches; silty clay
 BC—52 to 60 inches; silty clay

Minor Components

Kahola

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Reading

Composition: About 3 percent

Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Benfield

Composition: About 2 percent
Landform: hillslope on upland
Slope: 5 to 15 percent
Depth to restrictive feature: 20 to 40 inches
to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Florence

Composition: About 2 percent
Landform: hillslope on upland
Slope: 5 to 15 percent
Depth to restrictive feature: 40 to 60 inches
to bedrock (lithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Clime

Composition: About 2 percent
Slope: 3 to 8 percent
Depth to restrictive feature: 20 to 40 inches
to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

Ivan

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

117PA—Pawnee clay loam, 1 to 4 percent slopes**Map Unit Composition**

Pawnee: 88 percent
 Minor components: 12 percent

Component Descriptions**Pawnee**

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Parent material: Clayey drift
Slope: 1 to 4 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 8.1 inches)
Shrink-swell potential: High (About 7.5 LEP)

Flooding hazard: None
Depth to seasonal water saturation: About 12 to 36 inches
Runoff class: Medium
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 2e

Typical Profile:

H1—0 to 13 inches; clay loam
 H2—13 to 36 inches; clay
 H3—36 to 60 inches; clay loam

Minor Components**Wymore**

Composition: About 3 percent
Landform: hillslope on upland
Slope: 1 to 4 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Shelby

Composition: About 3 percent
Slope: 10 to 14 percent
Drainage class: Moderately well drained

Morrill

Composition: About 3 percent
Slope: 4 to 8 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Kipson

Composition: About 3 percent
Slope: 5 to 25 percent
Depth to restrictive feature: 7 to 20 inches to bedrock (paralithic)
Drainage class: Somewhat excessively drained
Ecological site: Limy Upland (pe30-36)

117PB—Pawnee clay loam, 4 to 8 percent slopes**Map Unit Composition**

Pawnee: 88 percent
 Minor components: 12 percent

Component Descriptions**Pawnee**

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Parent material: Clayey drift
Slope: 4 to 8 percent
Drainage class: Moderately well drained

Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 8.1 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 12 to 36 inches
Runoff class: Very high
Ecological site: Loamy Upland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

H1—0 to 13 inches; clay loam
 H2—13 to 36 inches; clay
 H3—36 to 60 inches; clay loam

Minor Components**Wymore**

Composition: About 3 percent
Landform: hillslope on upland
Slope: 1 to 4 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

Shelby

Composition: About 3 percent
Slope: 10 to 14 percent
Drainage class: Moderately well drained

Morrill

Composition: About 3 percent
Slope: 4 to 8 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Kipson

Composition: About 3 percent
Slope: 5 to 25 percent
Depth to restrictive feature: 7 to 20 inches to bedrock (paralithic)
Drainage class: Somewhat excessively drained
Ecological site: Limy Upland (pe30-36)

149HS—Haynie-Sarpy complex, occasionally flooded**Map Unit Composition**

Haynie: 60 percent
 Sarpy: 25 percent
 Minor components: 15 percent

Component Descriptions**Haynie**

MLRA: 76 - Bluestem Hills
Landform: Flood-plain step on river valley
Parent material: Coarse-silty alluvium
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.4 inches)
Shrink-swell potential: Low (About 1.5 LEP)
Flooding hazard: Occasional
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe30-37)
Land capability (nonirrigated): 3w

Typical Profile:

H1—0 to 9 inches; very fine sandy loam
 H2—9 to 60 inches; silt loam

Sarpy

MLRA: 76 - Bluestem Hills
Landform: Flood plain on river valley
Parent material: Sandy alluvium
Slope: 0 to 3 percent
Drainage class: Excessively drained
Slowest permeability: Rapid (About 5.95 in/hr)
Available water capacity: Low (About 4.1 inches)
Shrink-swell potential: Low (About 1.5 LEP)
Flooding hazard: Occasional
Depth to seasonal water saturation: More than 6 feet
Runoff class: Negligible
Ecological site: Sandy Lowland (pe30-37)
Land capability (nonirrigated): 3w

Typical Profile:

H1—0 to 6 inches; fine sand
 H2—6 to 60 inches; sand

Minor Components**Eudora**

Composition: About 7 percent
Slope: 0 to 1 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Kimo

Composition: About 7 percent
Slope: 0 to 1 percent
Drainage class: Somewhat poorly drained
Ecological site: Clay Lowland (pe30-37)

Unnamed Hydric Soil

Composition: About 1 percent
Drainage class: Poorly drained

**149PS—Paxico silt loam,
frequently flooded****Map Unit Composition**

Paxico: 90 percent
 Minor components: 10 percent

Component Descriptions**Paxico**

MLRA: 76 - Bluestem Hills
Landform: Flood plain on river valley
Parent material: Loamy alluvium over sandy alluvium
Slope: 0 to 1 percent
Drainage class: Somewhat poorly drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: High (About 10.4 inches)
Shrink-swell potential: Low (About 1.5 LEP)
Flooding hazard: Very Rare
Depth to seasonal water saturation: About 18 to 36 inches
Runoff class: Low
Land capability (nonirrigated): 5w

Typical Profile:

H1—0 to 42 inches; silt loam
 H2—42 to 60 inches; loamy fine sand

Minor Components**Haynie**

Composition: About 5 percent
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Sarpy

Composition: About 5 percent
Slope: 0 to 3 percent
Drainage class: Excessively drained
Ecological site: Sandy Lowland (pe30-37)

149SF—Sarpy sand, frequently flooded**Map Unit Composition**

Sarpy: 90 percent
 Minor components: 10 percent

Component Descriptions**Sarpy**

MLRA: 76 - Bluestem Hills
Landform: Flood plain on river valley
Parent material: Sandy alluvium
Slope: 0 to 2 percent
Drainage class: Excessively drained
Slowest permeability: Rapid (About 5.95 in/hr)
Available water capacity: Low (About 4.1 inches)
Shrink-swell potential: Low (About 1.5 LEP)
Flooding hazard: Frequent
Depth to seasonal water saturation: More than 6 feet
Runoff class: Negligible
Ecological site: Sandy Lowland (pe30-37)
Land capability (nonirrigated): 4s

Typical Profile:

H1—0 to 6 inches; sand
 H2—6 to 60 inches; sand

Minor Components**Eudora**

Composition: About 4 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Haynie

Composition: About 3 percent
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-37)

Kimo

Composition: About 3 percent
Slope: 0 to 1 percent
Drainage class: Somewhat poorly drained
Ecological site: Clay Lowland (pe30-37)

197CM—Clime silty clay loam, 3 to 7 percent slopes

Map Unit Composition

Clime: 85 percent
Minor components: 15 percent

Component Descriptions

Clime

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Silty and clayey residuum weathered from calcareous shale
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Low (About 4.7 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Limy Upland (pe30-36)
Land capability (nonirrigated): 4e

Typical Profile:

H1—0 to 5 inches; silty clay loam
H2—5 to 18 inches; silty clay
H3—18 to 32 inches; silty clay
Cr—32 to 36 inches; weathered bedrock

Minor Components

Sogn

Composition: About 5 percent
Landform: hillslope on upland
Slope: 5 to 20 percent
Depth to restrictive feature: 4 to 20 inches to bedrock (lithic)
Drainage class: Somewhat excessively drained
Ecological site: Shallow Limy (pe30-36)

Wamego

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Martin

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe35-42)

197FL—Florence-Labette complex, 3 to 15 percent slopes

Map Unit Composition

Florence: 40 percent
Labette: 30 percent
Minor components: 30 percent

Component Descriptions

Florence

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Clayey residuum weathered from cherty limestone
Slope: 3 to 15 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (lithic)
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: Low (About 5.3 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 6e

Typical Profile:

H1—0 to 14 inches; gravelly silt loam
H2—14 to 18 inches; gravelly silty clay loam
H3—18 to 56 inches; very gravelly clay
R—56 to 60 inches; unweathered bedrock

Labette

MLRA: 76 - Bluestem Hills
Landform: Ridge on upland
Hillslope position: Shoulder
Parent material: Silty and clayey residuum weathered from limestone and shale
Slope: 3 to 5 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (lithic)

Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 6.1 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 6e

Typical Profile:

H1—0 to 7 inches; silt loam
 H2—7 to 35 inches; silty clay
 R—35 to 39 inches; unweathered bedrock

Minor Components**Clime**

Composition: About 10 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

Martin

Composition: About 10 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe35-42)

Sogn

Composition: About 5 percent
Landform: hillslope on upland
Slope: 5 to 20 percent
Depth to restrictive feature: 4 to 20 inches to bedrock (lithic)
Drainage class: Somewhat excessively drained
Ecological site: Shallow Limy (pe30-36)

Irwin

Composition: About 5 percent
Landform: hillslope on upland
Slope: 1 to 3 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-36)

1971B—Irwin silty clay loam, 1 to 3 percent slopes**Map Unit Composition**

Irwin: 80 percent
 Minor components: 20 percent

Component Descriptions**Irwin**

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Hillslope position: Shoulder
Parent material: Silty and clayey residuum weathered from clayey shale
Slope: 1 to 3 percent
Drainage class: Moderately well drained
Slowest permeability: Very slow (About 0.00 in/hr)
Available water capacity: Moderate (About 8.6 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Upland (pe30-36)
Land capability (nonirrigated): 3e

Typical Profile:

H1—0 to 12 inches; silty clay loam
 H2—12 to 42 inches; clay, silty clay
 H3—42 to 60 inches; clay

Minor Components**Ladysmith**

Composition: About 10 percent
Landform: divide on upland
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Ecological site: Clay Upland (pe30-36)

Dwight

Composition: About 10 percent
Slope: 1 to 3 percent
Drainage class: Moderately well drained
Ecological site: Clay Pan (pe35-42)

1971D—Irwin silty clay loam, 3 to 7 percent slopes

Map Unit Composition

Irwin: 85 percent
Minor components: 15 percent

Component Descriptions

Irwin

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Silty and clayey alluvium over clayey residuum weathered from limestone and shale
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Slowest permeability: Very slow (About 0.00 in/hr)
Available water capacity: Moderate (About 8.7 inches)
Shrink-swell potential: High (About 8.9 LEP)
Flooding hazard: None
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Upland (pe30-36)
Land capability (nonirrigated): 4e

Typical Profile:

A—0 to 6 inches; silty clay loam
BA—6 to 13 inches; silty clay loam
Bt1—13 to 30 inches; silty clay
Btk—30 to 41 inches; silty clay
2Bt2—41 to 72 inches; silty clay

Minor Components

Konza

Composition: About 10 percent
Landform: ridge on upland
Slope: 1 to 3 percent
Drainage class: Moderately well drained
Ecological site: Clay Pan (pe30-36)

Florence

Composition: About 2 percent
Landform: hillslope on upland
Slope: 5 to 10 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (lithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Clime

Composition: About 2 percent
Slope: 3 to 8 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

Unnamed Hydric Soil (saturation)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

1971V—Ivan silt loam, occasionally flooded

Map Unit Composition

Ivan: 90 percent
Minor components: 10 percent

Component Descriptions

Ivan

MLRA: 76 - Bluestem Hills
Landform: Flood plain on valley
Parent material: Calcareous fine-silty alluvium
Slope: 0 to 2 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 13.1 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: Occasional
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 2w

Typical Profile:

H1—0 to 36 inches; silt loam
H2—36 to 60 inches; silt loam

Minor Components

Chase

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Somewhat poorly drained
Ecological site: Loamy Lowland (pe35-42)

Reading

Composition: About 4 percent
Slope: 0 to 1 percent
Drainage class: Moderately well drained

Ecological site: Loamy Lowland (pe30-36)

Unnamed Hydric Soil (saturation)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

**197IX—Ivan silty clay loam,
channeled**

Map Unit Composition

Ivan: 80 percent
 Minor components: 20 percent

Component Descriptions

Ivan

MLRA: 76 - Bluestem Hills
Landform: Flood plain on valley
Parent material: Calcareous fine-silty alluvium
Slope: 0 to 2 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.8 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: Frequent
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 5w

Typical Profile:

H1—0 to 40 inches; silty clay loam
 H2—40 to 60 inches; silt loam

Minor Components

Martin

Composition: About 10 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe30-36)

Reading

Composition: About 10 percent
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-36)

Unnamed Hydric Soil

Slope: 0 to 2 percent
Drainage class: Poorly drained

**197PN—Pawnee clay loam, 3 to 7
percent slopes**

Map Unit Composition

Pawnee: 85 percent
 Minor components: 15 percent

Component Descriptions

Pawnee

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Clayey drift
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 8.3 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 9 to 14 inches
Runoff class: High
Ecological site: Clay Upland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

H1—0 to 14 inches; clay loam
 H2—14 to 34 inches; clay
 H3—34 to 72 inches; sandy clay loam

Minor Components

Oska

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 6 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (lithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe35-42)

Morrill

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-37)

Martin

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe35-42)

Slope: 6 to 12 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe30-37)

**197WE—Wamego silty clay loam,
3 to 7 percent slopes****Map Unit Composition**

Wamego: 90 percent
 Minor components: 10 percent

Component Descriptions**Wamego**

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Sandy and silty residuum weathered from shale, unspecified
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Low (About 4.6 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Clay Upland (pe30-37)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 9 inches; silty clay loam
 Bt—9 to 20 inches; silty clay loam
 BC—20 to 25 inches; silty clay loam
 Cr—25 to 36 inches; weathered bedrock

Minor Components**Olmitz**

Composition: About 5 percent
Landform: fan terrace on upland
Slope: 2 to 5 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe30-37)

Pawnee

Composition: About 5 percent
Landform: hillslope on upland

**201CS—Crete silty clay loam, 1 to
3 percent slopes****Map Unit Composition**

Crete: 95 percent
 Minor components: 5 percent

Component Descriptions**Crete**

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Parent material: Silty and clayey loess
Slope: 1 to 3 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 10.0 inches)
Shrink-swell potential: Very high (About 9.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Clay Upland (pe26-30)
Land capability (nonirrigated): 2e

Typical Profile:

Ap—0 to 6 inches; silty clay loam
 BA—6 to 9 inches; silty clay loam
 Bt—9 to 32 inches; silty clay
 Btk—32 to 40 inches; silty clay loam
 BC—40 to 60 inches; silty clay loam

Minor Components**Hobbs**

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe26-30)

201CX—Crete silty clay loam, 3 to 7 percent slopes, eroded

Map Unit Composition

Crete: 90 percent
Minor components: 10 percent

Component Descriptions

Crete

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Parent material: Silty and clayey loess
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Slowest permeability: Impermeable (About 0.00 in/hr)
Available water capacity: High (About 10.9 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Clay Upland (pe26-30)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 5 inches; silty clay loam
Bt—5 to 30 inches; silty clay
BC—30 to 60 inches; silt loam

Minor Components

Hobbs

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe26-30)

Longford

Composition: About 5 percent
Slope: 3 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe26-30)

201KS—Kipson-Sogn complex, 5 to 30 percent slopes

Map Unit Composition

Kipson: 70 percent
Sogn: 15 percent

Minor components: 15 percent

Component Descriptions

Kipson

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Loamy residuum weathered from limestone and shale
Slope: 5 to 30 percent
Depth to restrictive feature: 7 to 20 inches to bedrock (paralithic)
Drainage class: Somewhat excessively drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Low (About 3.4 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Limy Upland (pe26-30)
Land capability (nonirrigated): 6e

Typical Profile:

H1—0 to 12 inches; silty clay loam
H2—12 to 18 inches; silty clay loam
Cr—18 to 22 inches; weathered bedrock

Sogn

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Shoulder
Parent material: Loamy residuum weathered from limestone
Slope: 5 to 15 percent
Depth to restrictive feature: 4 to 20 inches to bedrock (lithic)
Drainage class: Somewhat excessively drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Low (About 3.1 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Shallow Limy (pe26-30)
Land capability (nonirrigated): 6e

Typical Profile:

H1—0 to 8 inches; silt loam
H2—8 to 16 inches; channery silt loam
H3—16 to 20 inches; unweathered bedrock

Minor Components

Crete

Composition: About 5 percent
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe26-30)

Tully

Composition: About 5 percent
Landform: hillslope on upland
Slope: 5 to 12 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe26-30)

Rock outcrop

Composition: About 3 percent
Slope: 15 to 45 percent

Unnamed Hydric Soil

Composition: About 1 percent
Drainage class: Poorly drained

Unnamed Hydric Soils

Composition: About 1 percent
Drainage class: Poorly drained

201LC—Lancaster loam, 3 to 7 percent slopes

Map Unit Composition

Lancaster: 85 percent
 Minor components: 15 percent

Component Descriptions

Lancaster

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Parent material: Loamy residuum weathered from sandstone and shale
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Low (About 5.2 inches)
Shrink-swell potential: Moderate (About 4.1 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium

Ecological site: Loamy Upland (pe26-30)
Land capability (nonirrigated): 4e

Typical Profile:

A—0 to 9 inches; loam
 Bt—9 to 24 inches; clay loam
 BC—24 to 29 inches; sandy clay loam
 Cr—29 to 29 inches; weathered bedrock

Minor Components

Crete

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Wells

Composition: About 5 percent
Slope: 3 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Longford

Composition: About 3 percent
Slope: 3 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe26-30)

Hedville

Composition: About 1 percent
Landform: hillslope on upland
Slope: 5 to 30 percent
Depth to restrictive feature: 4 to 20 inches to bedrock (lithic)
Drainage class: Somewhat excessively drained
Ecological site: Shallow Sandstone (pe26-30)

Edalgo

Composition: About 1 percent
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Clay Upland (pe26-30)

Ad—Ivan silt loam, channeled

Map Unit Composition

Ivan: 99 percent
 Minor components: 1 percent

Component Descriptions

Ivan

MLRA: 75 - Central Loess Plains

Landform: Flood plain on alluvial plain

Parent material: Loamy alluvium

Slope: 0 to 3 percent

Drainage class: Well drained

Slowest permeability: Moderate (About 0.60 in/hr)

Available water capacity: Very high (About 12.3 inches)

Shrink-swell potential: Moderate (About 4.5 LEP)

Flooding hazard: Frequent

Depth to seasonal water saturation: More than 6 feet

Runoff class: Low

Ecological site: Loamy Lowland (pe25-34)

Land capability (nonirrigated): 5w

Typical Profile:

A1—0 to 7 inches; silt loam

A2—7 to 26 inches; silty clay loam

AC—26 to 39 inches; silty clay loam

C—39 to 64 inches; silty clay loam

Minor Components

Unnamed Hydric Soil (ponding)

Composition: About 1 percent

Slope: 0 to 2 percent

Drainage class: Poorly drained

Drainage class: Well drained

Slowest permeability: Slow (About 0.06 in/hr)

Available water capacity: Low (About 5.8 inches)

Shrink-swell potential: High (About 7.5 LEP)

Flooding hazard: None

Depth to seasonal water saturation: More than 6 feet

Runoff class: High

Ecological site: Loamy Upland (pe25-34)

Land capability (nonirrigated): 4e

Typical Profile:

A—0 to 10 inches; silty clay loam

Bt—10 to 32 inches; silty clay

2Cr—32 to 36 inches; weathered bedrock

Minor Components

Crete

Composition: About 5 percent

Landform: hillslope on upland

Slope: 3 to 7 percent

Drainage class: Moderately well drained

Ecological site: Clay Upland (pe25-34)

Kipson

Composition: About 5 percent

Slope: 5 to 20 percent

Depth to restrictive feature: 7 to 20 inches to bedrock (paralithic)

Drainage class: Somewhat excessively drained

Ecological site: Limy Upland (pe25-34)

Rock outcrop

Composition: About 1 percent

AED—Arents, Earthen Dam

BE—Benfield silty clay loam, 3 to 7 percent slopes

Map Unit Composition

Benfield: 89 percent

Minor components: 11 percent

Component Descriptions

Benfield

MLRA: 76 - Bluestem Hills

Landform: Hillslope on upland

Parent material: Silty loess over clayey residuum

Slope: 3 to 7 percent

Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)

Bf—Benfield-Florence complex, 5 to 20 percent slopes

Map Unit Composition

Benfield: 45 percent

Florence: 30 percent

Minor components: 25 percent

Component Descriptions

Benfield

MLRA: 76 - Bluestem Hills

Landform: Hillslope on upland

Parent material: Clayey residuum weathered from limestone and shale

Slope: 5 to 20 percent

Depth to restrictive feature: 22 to 39 inches to bedrock (paralithic)

Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 6.0 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 6e

Typical Profile:

H1—0 to 6 inches; silty clay loam
 H2—6 to 30 inches; silty clay
 H3—30 to 35 inches; silty clay loam
 Cr—35 to 39 inches; weathered bedrock

Florence

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Parent material: Clayey residuum weathered from cherty limestone
Slope: 5 to 15 percent
Depth to restrictive feature: 24 to 39 inches to bedrock (lithic)
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: Very low (About 2.8 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 6e

Typical Profile:

H1—0 to 5 inches; gravelly silt loam
 H2—5 to 10 inches; very gravelly silty clay loam
 H3—10 to 14 inches; very gravelly silty clay loam
 H4—14 to 30 inches; gravelly clay
 R—30 to 34 inches; unweathered bedrock

Minor Components**Clime**

Composition: About 10 percent
Slope: 5 to 20 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

Sogn

Composition: About 5 percent
Slope: 5 to 8 percent
Depth to restrictive feature: 4 to 20 inches to bedrock (lithic)
Drainage class: Somewhat excessively drained
Ecological site: Shallow Limy (pe30-36)

Dwight

Composition: About 4 percent
Slope: 1 to 3 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (lithic)
Drainage class: Moderately well drained
Ecological site: Clay Pan (pe25-34)

Irwin

Composition: About 3 percent
Slope: 1 to 4 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Tully

Composition: About 3 percent
Landform: hillslope on upland
Slope: 4 to 8 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

**Bk—Wymore-Kennebec complex,
0 to 17 percent slopes****Map Unit Composition**

Wymore: 60 percent
 Kennebec: 45 percent
 Minor components: 5 percent

Component Descriptions**Wymore**

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Footslope
Parent material: Silty and clayey loess over clayey pedisidiment
Slope: 11 to 17 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 10.4 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None

Depth to seasonal water saturation: About 12 to 36 inches

Runoff class: Very high

Ecological site: Clay Upland (pe25-34)

Land capability (nonirrigated): 6e

Typical Profile:

H1—0 to 13 inches; silty clay loam

H2—13 to 33 inches; silty clay

H3—33 to 64 inches; silty clay loam

Kennebec

MLRA: 75 - Central Loess Plains

Landform: Flood plain on alluvial plain

Parent material: Fine-silty alluvium

Slope: 0 to 1 percent

Drainage class: Moderately well drained

Slowest permeability: Moderate (About 0.60 in/hr)

Available water capacity: Very high (About 12.8 inches)

Shrink-swell potential: Moderate (About 4.5 LEP)

Flooding hazard: Occasional

Depth to seasonal water saturation: About 36 to 60 inches

Runoff class: Low

Ecological site: Loamy Lowland (pe30-36)

Land capability (nonirrigated): 1

Typical Profile:

H1—0 to 18 inches; silt loam

H2—18 to 60 inches; silty clay loam

Minor Components

Ivan

Composition: About 3 percent

Slope: 0 to 2 percent

Drainage class: Well drained

Ecological site: Loamy Lowland (pe30-36)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent

Slope: 0 to 2 percent

Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 1 percent

Slope: 0 to 2 percent

Drainage class: Poorly drained

BOP—Borrow Pits

General Considerations: An open excavation from which soil and underlying material have been removed usually for construction purposes.

Ca—Carr-Sarpy complex, occasionally flooded

Map Unit Composition

Carr: 45 percent

Sarpy: 40 percent

Minor components: 15 percent

Component Descriptions

Carr

MLRA: 76 - Bluestem Hills

Landform: Flood plain on river valley

Parent material: Loamy alluvium

Slope: 0 to 1 percent

Drainage class: Well drained

Slowest permeability: Moderately rapid (About 2.00 in/hr)

Available water capacity: High (About 9.9 inches)

Shrink-swell potential: Low (About 0.5 LEP)

Flooding hazard: Occasional

Depth to seasonal water saturation: More than 6 feet

Runoff class: Negligible

Ecological site: Sandy Lowland (pe30-36)

Land capability (nonirrigated): 3w

Typical Profile:

A1—0 to 9 inches; fine sandy loam

A2—9 to 17 inches; fine sandy loam

AC—17 to 28 inches; fine sandy loam

C—28 to 60 inches; very fine sandy loam

Sarpy

MLRA: 76 - Bluestem Hills

Landform: Flood plain on river valley

Parent material: Sandy alluvium

Slope: 0 to 1 percent

Drainage class: Excessively drained

Slowest permeability: Rapid (About 5.95 in/hr)

Available water capacity: Low (About 4.3 inches)

Shrink-swell potential: Low (About 0.0 LEP)

Flooding hazard: Occasional

Depth to seasonal water saturation: More than 6 feet

Runoff class: Negligible

Ecological site: Sands (pe30-36)

Land capability (nonirrigated): 3w

Typical Profile:

A—0 to 5 inches; loamy fine sand

C—5 to 60 inches; fine sand

Minor Components**Haynie**

Composition: About 13 percent
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-36)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Ch—Chase silty clay loam, rarely flooded**Map Unit Composition**

Chase: 84 percent
 Minor components: 15 percent

Component Descriptions**Chase**

MLRA: 76 - Bluestem Hills
Landform: Terrace on river valley
Parent material: Silty and clayey alluvium
Slope: 0 to 1 percent
Drainage class: Somewhat poorly drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 8.2 inches)
Shrink-swell potential: Very high (About 9.2 LEP)
Flooding hazard: Rare
Depth to seasonal water saturation: About 24 to 48 inches
Runoff class: High
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 2w

Typical Profile:

Ap—0 to 7 inches; silty clay loam
 AB—7 to 13 inches; silty clay loam
 Bt—13 to 40 inches; silty clay
 BC—40 to 50 inches; silty clay
 C—50 to 60 inches; silty clay

Minor Components**Reading**

Composition: About 10 percent
Slope: 0 to 1 percent
Drainage class: Well drained

Ecological site: Loamy Lowland (pe30-36)

Sutphen

Composition: About 4 percent
Slope: 0 to 1 percent
Drainage class: Somewhat poorly drained
Ecological site: Clay Lowland (pe26-30)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Cs—Clime-Sogn complex, 5 to 20 percent slopes**Map Unit Composition**

Clime: 50 percent
 Sogn: 30 percent
 Minor components: 20 percent

Component Descriptions**Clime**

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Parent material: Silty and clayey residuum weathered from shale, calcareous
Slope: 5 to 20 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Low (About 5.3 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Limy Upland (pe30-36)
Land capability (nonirrigated): 6e

Typical Profile:

H1—0 to 12 inches; silty clay loam
 H2—12 to 30 inches; silty clay
 Cr—30 to 34 inches; weathered bedrock

Sogn

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Parent material: Loamy residuum weathered from limestone, unspecified

Slope: 5 to 8 percent
Depth to restrictive feature: 4 to 20 inches to bedrock (lithic)
Drainage class: Somewhat excessively drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very low (About 1.8 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Shallow Limy (pe30-36)
Land capability (nonirrigated): 6e

Typical Profile:
 H1—0 to 9 inches; silty clay loam
 R—9 to 13 inches; unweathered bedrock

Minor Components

Unnamed Soil

Composition: About 10 percent
Slope: 5 to 20 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

Rock outcrop

Composition: About 5 percent

Irwin

Composition: About 3 percent
Slope: 4 to 8 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Unnamed Hydric Soils

Composition: About 1 percent
Drainage class: Poorly drained

Unnamed Hydric Soil

Composition: About 1 percent
Drainage class: Poorly drained

CT—Crete silty clay loam, 3 to 7 percent slopes

Map Unit Composition

Crete: 83 percent
 Minor components: 17 percent

Component Descriptions

Crete

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Silty and clayey loess
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 10.1 inches)
Shrink-swell potential: Very high (About 9.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 7 inches; silty clay loam
 BA—7 to 11 inches; silty clay loam
 Bt—11 to 30 inches; silty clay
 BCk—30 to 40 inches; silty clay loam
 C—40 to 60 inches; silty clay loam

Minor Components

Geary

Composition: About 5 percent
Landform: hillslope on upland
Slope: 2 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Holder

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Benfield

Composition: About 3 percent
Slope: 3 to 7 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Hobbs

Composition: About 2 percent
Slope: 0 to 3 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe25-34)

Lancaster

Composition: About 2 percent
Slope: 5 to 12 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe26-30)

Dr—Dwight-Irwin complex, 1 to 4 percent slopes**Map Unit Composition**

Dwight: 45 percent
 Irwin: 40 percent
 Minor components: 15 percent

Component Descriptions**Dwight**

MLRA: 75 - Central Loess Plains
Landform: Depression on ridge on upland
Hillslope position: Summit
Parent material: Silty and clayey residuum weathered from limestone, cherty
Slope: 1 to 3 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (lithic)
Drainage class: Moderately well drained
Slowest permeability: Very slow (About 0.00 in/hr)
Available water capacity: Low (About 5.6 inches)
Shrink-swell potential: Very high (About 9.9 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Pan (pe25-34)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 4 inches; silt loam
 Bt—4 to 17 inches; silty clay
 BC—17 to 43 inches; silty clay
 R—43 to 43 inches; unweathered bedrock

Irwin

MLRA: 75 - Central Loess Plains
Landform: Ridge on upland
Parent material: Clayey pedisidiment derived from limestone and shale
Slope: 1 to 4 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Slowest permeability: Very slow (About 0.00 in/hr)
Available water capacity: Moderate (About 7.0 inches)
Shrink-swell potential: Very high (About 9.9 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 7 inches; silty clay loam
 AB—7 to 11 inches; silty clay loam
 Bt—11 to 35 inches; silty clay
 BC—35 to 50 inches; silty clay
 C—50 to 55 inches; silty clay
 Cr—55 to 55 inches; unweathered bedrock

Minor Components**Clime**

Composition: About 5 percent
Slope: 3 to 6 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

Rock outcrop

Composition: About 5 percent

Wymore

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 6 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe25-34)

Dw—Dwight-Irwin complex, 1 to 4 percent slopes, eroded

Map Unit Composition

Dwight: 45 percent
Irwin: 40 percent
Minor components: 15 percent

Component Descriptions

Dwight

MLRA: 75 - Central Loess Plains
Landform: Depression on divide on upland
Hillslope position: Summit
Parent material: Silty and clayey residuum weathered from limestone, cherty
Slope: 1 to 3 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (lithic)
Drainage class: Moderately well drained
Slowest permeability: Very slow (About 0.00 in/hr)
Available water capacity: Low (About 5.6 inches)
Shrink-swell potential: Very high (About 9.9 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Pan (pe25-34)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 4 inches; silt loam
Bt—4 to 17 inches; silty clay
BC—17 to 43 inches; silty clay
R—43 to 43 inches; unweathered bedrock

Irwin

MLRA: 75 - Central Loess Plains
Landform: Divide on upland
Hillslope position: Summit
Parent material: Clayey pedisidiment derived from limestone and shale
Slope: 1 to 4 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Slowest permeability: Very slow (About 0.00 in/hr)
Available water capacity: Moderate (About 6.6 inches)
Shrink-swell potential: Very high (About 9.9 LEP)

Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 4e

Typical Profile:

Ap—0 to 8 inches; silty clay loam
Bt—8 to 35 inches; silty clay
BC—35 to 50 inches; silty clay
C—50 to 55 inches; silty clay
Cr—55 to 55 inches; unweathered bedrock

Minor Components

Clime

Composition: About 5 percent
Slope: 3 to 6 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

Rock outcrop

Composition: About 5 percent

Wymore

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 6 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe25-34)

Em—Elmont silt loam, 3 to 8 percent slopes

Map Unit Composition

Elmont: 74 percent
Minor components: 26 percent

Component Descriptions

Elmont

MLRA: 76 - Bluestem Hills
Landform: Hillside on upland
Hillslope position: Backslope
Parent material: Silty and clayey residuum weathered from shale-siltstone
Slope: 3 to 8 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)

Available water capacity: Moderate (About 8.4 inches)
Shrink-swell potential: Moderate (About 5.4 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 3e

Typical Profile:

A—0 to 10 inches; silt loam
 BA—10 to 18 inches; silty clay loam
 Bt—18 to 28 inches; silty clay loam
 BC—28 to 33 inches; silty clay loam
 C—33 to 44 inches; clay loam
 R—44 to 44 inches; weathered bedrock

Minor Components

Unnamed Soil (moderately Deep)

Composition: About 25 percent
Slope: 3 to 8 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Rock outcrop

Composition: About 1 percent

En—Elmont-Clime complex, 5 to 15 percent slopes

Map Unit Composition

Elmont: 35 percent
 Clime: 30 percent
 Minor components: 35 percent

Component Descriptions

Elmont

MLRA: 76 - Bluestem Hills
Landform: Hillside on upland
Hillslope position: Backslope
Parent material: Silty and clayey residuum weathered from shale-siltstone
Slope: 5 to 12 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)

Available water capacity: Moderate (About 8.4 inches)
Shrink-swell potential: Moderate (About 5.4 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 6e

Typical Profile:

A—0 to 10 inches; silt loam
 BA—10 to 18 inches; silty clay loam
 Bt—18 to 28 inches; silty clay loam
 BC—28 to 33 inches; silty clay loam
 C—33 to 44 inches; clay loam
 R—44 to 44 inches; weathered bedrock

Clime

MLRA: 76 - Bluestem Hills
Landform: Hillside on upland
Hillslope position: Backslope
Parent material: Silty and clayey residuum weathered from shale, calcareous
Slope: 5 to 15 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Low (About 5.9 inches)
Shrink-swell potential: High (About 6.6 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Limy Upland (pe30-36)
Land capability (nonirrigated): 6e

Typical Profile:

A1—0 to 8 inches; silty clay loam
 A2—8 to 12 inches; silty clay loam
 Bw—12 to 20 inches; silty clay loam
 C—20 to 30 inches; silty clay loam
 Cr—30 to 30 inches; weathered bedrock

Minor Components

Unnamed Soil (moderately Deep)

Composition: About 20 percent
Slope: 5 to 12 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Irwin

Composition: About 10 percent
Slope: 4 to 8 percent

Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Sogn

Composition: About 5 percent
Slope: 5 to 8 percent
Depth to restrictive feature: 4 to 20 inches to bedrock (lithic)
Drainage class: Somewhat excessively drained
Ecological site: Shallow Limy (pe30-36)

Eu—Eudora silt loam, rarely flooded**Map Unit Composition**

Eudora: 88 percent
 Minor components: 12 percent

Component Descriptions**Eudora**

MLRA: 76 - Bluestem Hills
Landform: Flood plain on river valley
Parent material: Loamy alluvium
Slope: 0 to 2 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.1 inches)
Shrink-swell potential: Low (About 2.4 LEP)
Flooding hazard: Occasional
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 2w

Typical Profile:

Ap—0 to 7 inches; silt loam
 A1—7 to 14 inches; silt loam
 A2—14 to 19 inches; silt loam
 C1—19 to 26 inches; silt loam
 C2—26 to 60 inches; very fine sandy loam

Minor Components**Muir**

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Terrace (pe25-34)

Haynie

Composition: About 5 percent
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-36)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Ga—Geary silt loam, 1 to 4 percent slopes**Map Unit Composition**

Geary: 90 percent
 Minor components: 10 percent

Component Descriptions**Geary**

MLRA: 76 - Bluestem Hills
Landform: Hillside on upland
Hillslope position: Backslope
Parent material: Silty loess
Slope: 1 to 4 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: High (About 11.7 inches)
Shrink-swell potential: Moderate (About 5.4 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 2e

Typical Profile:

A—0 to 8 inches; silt loam
 BA—8 to 13 inches; silty clay loam
 Bt—13 to 29 inches; silty clay loam
 BC—29 to 42 inches; silty clay loam
 C—42 to 60 inches; silty clay loam

Minor Components**Smolan**

Composition: About 10 percent
Slope: 1 to 4 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe30-36)

Ecological site: Loamy Upland (pe30-36)

Ge—Geary silt loam, 4 to 8 percent slopes**Map Unit Composition**

Geary: 90 percent
 Minor components: 10 percent

Component Descriptions**Geary**

MLRA: 76 - Bluestem Hills
Landform: Hillside on upland
Hillslope position: Backslope
Parent material: Silty loess
Slope: 4 to 8 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: High (About 11.7 inches)
Shrink-swell potential: Moderate (About 5.4 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 3e

Typical Profile:

A—0 to 8 inches; silt loam
 BA—8 to 13 inches; silty clay loam
 Bt—13 to 29 inches; silty clay loam
 BC—29 to 42 inches; silty clay loam
 C—42 to 60 inches; silty clay loam

Minor Components**Kenesaw**

Composition: About 5 percent
Slope: 2 to 6 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Smolan

Composition: About 5 percent
Slope: 1 to 4 percent
Drainage class: Moderately well drained

Ha—Haynie very fine sandy loam, occasionally flooded**Map Unit Composition**

Haynie: 90 percent
 Minor components: 10 percent

Component Descriptions**Haynie**

MLRA: 76 - Bluestem Hills
Landform: Flood plain on river valley
Parent material: Loamy alluvium
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 11.1 inches)
Shrink-swell potential: Low (About 0.9 LEP)
Flooding hazard: Occasional
Depth to seasonal water saturation: More than 6 feet
Runoff class: Negligible
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 1

Typical Profile:

Ap—0 to 10 inches; very fine sandy loam
 C—10 to 20 inches; very fine sandy loam
 Ab—20 to 30 inches; very fine sandy loam
 ACb—30 to 41 inches; very fine sandy loam
 2C—41 to 60 inches; silty clay loam

Minor Components**Carr**

Composition: About 5 percent
Slope: 0 to 1 percent
Drainage class: Well drained
Ecological site: Sandy Lowland (pe30-36)

Eudora

Composition: About 4 percent
Slope: 0 to 1 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

HO—Hobbs silt loam, occasionally flooded**Map Unit Composition**

Hobbs: 89 percent
 Minor components: 11 percent

Component Descriptions**Hobbs**

MLRA: 75 - Central Loess Plains
Landform: Flood plain on alluvial plain
Parent material: Fine-silty alluvium
Slope: 0 to 3 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: High (About 12.0 inches)
Shrink-swell potential: Moderate (About 3.3 LEP)
Flooding hazard: Occasional
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe25-34)
Land capability (nonirrigated): 2w

Typical Profile:

A—0 to 8 inches; silt loam
 C1—8 to 16 inches; silt loam
 C2—16 to 40 inches; silt loam
 C3—40 to 60 inches; silt loam

Minor Components**Sutphen**

Composition: About 5 percent
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Ecological site: Clay Lowland (pe30-36)

Crete

Composition: About 2 percent
Landform: hillslope on upland
Slope: 3 to 7 percent
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Geary

Composition: About 2 percent
Landform: hillslope on upland
Slope: 2 to 7 percent
Drainage class: Well drained

Ecological site: Loamy Upland (pe25-34)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Ic—Irwin silty clay loam, 4 to 8 percent slopes**Map Unit Composition**

Irwin: 85 percent
 Minor components: 15 percent

Component Descriptions**Irwin**

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Parent material: Clayey pedisegment derived from shale
Slope: 4 to 8 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Slowest permeability: Very slow (About 0.00 in/hr)
Available water capacity: Moderate (About 8.0 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 4e

Typical Profile:

H1—0 to 11 inches; silty clay loam
 H2—11 to 55 inches; silty clay
 Cr—55 to 59 inches; unweathered bedrock

Minor Components**Clime**

Composition: About 5 percent
Slope: 3 to 6 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained

Ecological site: Limy Upland (pe30-36)

Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

Rock outcrop

Composition: About 5 percent

Rock outcrop

Composition: About 5 percent

Wymore

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 6 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe25-34)

Wymore

Phase: Eroded
Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 6 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe25-34)

Id—Irwin silty clay loam, 4 to 8 percent slopes, eroded

Ie—Ivan silty clay loam, 1 to 3 percent slopes

Map Unit Composition

Irwin: 85 percent
Minor components: 15 percent

Map Unit Composition

Ivan: 88 percent
Minor components: 12 percent

Component Descriptions

Irwin

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Parent material: Clayey pedisegment derived from shale
Slope: 4 to 8 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Slowest permeability: Very slow (About 0.00 in/hr)
Available water capacity: Moderate (About 8.0 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 4e

Typical Profile:

H1—0 to 11 inches; silty clay loam
H2—11 to 55 inches; silty clay
Cr—55 to 59 inches; unweathered bedrock

Minor Components

Clime

Phase: Eroded
Composition: About 5 percent
Slope: 3 to 6 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)

Component Descriptions

Ivan

MLRA: 76 - Bluestem Hills
Landform: Flood plain on valley
Parent material: Calcareous fine-silty colluvium
Slope: 1 to 3 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.5 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 2e

Typical Profile:

H1—0 to 7 inches; silty clay loam
H2—7 to 64 inches; silty clay loam

Minor Components

Reading

Composition: About 10 percent
Slope: 0 to 1 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent

Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 1 percent

Slope: 0 to 2 percent

Drainage class: Poorly drained

**Iv—Ivan and Kennebec silt loams,
occasionally flooded**

Map Unit Composition

Ivan: 45 percent

Kennebec: 45 percent

Minor components: 10 percent

Component Descriptions

Ivan

MLRA: 76 - Bluestem Hills

Landform: Flood plain on valley

Parent material: Calcareous fine-silty alluvium

Slope: 0 to 1 percent

Drainage class: Well drained

Slowest permeability: Moderate (About 0.60 in/hr)

Available water capacity: Very high (About 12.5 inches)

Shrink-swell potential: Moderate (About 4.5 LEP)

Flooding hazard: Occasional

Depth to seasonal water saturation: More than 6 feet

Runoff class: Negligible

Ecological site: Loamy Lowland (pe30-36)

Land capability (nonirrigated): 2w

Typical Profile:

H1—0 to 7 inches; silt loam

H2—7 to 64 inches; silty clay loam

Kennebec

MLRA: 76 - Bluestem Hills

Landform: Flood plain on valley

Parent material: Fine-silty alluvium

Slope: 0 to 1 percent

Drainage class: Moderately well drained

Slowest permeability: Moderate (About 0.60 in/hr)

Available water capacity: Very high (About 12.8 inches)

Shrink-swell potential: Moderate (About 4.5 LEP)

Flooding hazard: Occasional

Depth to seasonal water saturation: About 36 to 60 inches

Runoff class: Low

Ecological site: Loamy Lowland (pe30-36)

Land capability (nonirrigated): 1

Typical Profile:

H1—0 to 18 inches; silt loam

H2—18 to 60 inches; silty clay loam

Minor Components

Reading

Composition: About 4 percent

Slope: 0 to 1 percent

Drainage class: Well drained

Ecological site: Loamy Lowland (pe30-36)

Muir

Composition: About 4 percent

Slope: 0 to 2 percent

Drainage class: Well drained

Ecological site: Loamy Terrace (pe25-34)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent

Slope: 0 to 2 percent

Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 1 percent

Slope: 0 to 2 percent

Drainage class: Poorly drained

**Ka—Kahola silt loam, rarely
flooded**

Map Unit Composition

Kahola: 85 percent

Minor components: 15 percent

Component Descriptions

Kahola

MLRA: 76 - Bluestem Hills

Landform: Flood plain on river valley

Parent material: Fine-silty alluvium

Slope: 0 to 1 percent

Drainage class: Well drained

Slowest permeability: Moderate (About 0.60 in/hr)

Available water capacity: Very high (About 12.2 inches)

Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: Rare
Depth to seasonal water saturation: More than 6 feet
Runoff class: Negligible
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 1

Typical Profile:
 H1—0 to 13 inches; silt loam
 H2—13 to 60 inches; silty clay loam

Minor Components

Eudora

Composition: About 7 percent
Slope: 0 to 1 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-37)

Haynie

Composition: About 6 percent
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Ecological site: Loamy Lowland (pe30-36)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Ke—Kenesaw silt loam, 2 to 6 percent slopes

Map Unit Composition

Kenesaw: 90 percent
 Minor components: 10 percent

Component Descriptions

Kenesaw

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Parent material: Coarse-silty loess
Slope: 2 to 6 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.0 inches)

Shrink-swell potential: Low (About 1.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 3e

Typical Profile:
 H1—0 to 12 inches; silt loam
 H2—12 to 36 inches; silt loam
 H3—36 to 60 inches; silt loam

Minor Components

Geary

Composition: About 10 percent
Slope: 4 to 8 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Kf—Kenesaw silt loam, 6 to 10 percent slopes

Map Unit Composition

Kenesaw: 85 percent
 Minor components: 15 percent

Component Descriptions

Kenesaw

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Parent material: Coarse-silty loess
Slope: 6 to 10 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.0 inches)
Shrink-swell potential: Low (About 1.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 4e

Typical Profile:
 H1—0 to 12 inches; silt loam
 H2—12 to 36 inches; silt loam
 H3—36 to 60 inches; silt loam

Minor Components**Geary**

Composition: About 15 percent
Slope: 4 to 8 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

KN—Kennebec silt loam, occasionally flooded**Map Unit Composition**

Kennebec: 95 percent
 Minor components: 5 percent

Component Descriptions**Kennebec**

MLRA: 75 - Central Loess Plains
Landform: Flood plain on valley
Parent material: Fine-silty alluvium
Slope: 0 to 2 percent
Drainage class: Moderately well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 13.4 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: Occasional
Depth to seasonal water saturation: About 40 to 44 inches
Runoff class: Low
Ecological site: Loamy Lowland (pe35-42)
Land capability (nonirrigated): 2w

Typical Profile:

H1—0 to 48 inches; silt loam
 H2—48 to 60 inches; silt loam

Minor Components**Wabash**

Composition: About 4 percent
Slope: 0 to 1 percent
Drainage class: Poorly drained
Ecological site: Clay Lowland (pe30-37)

Unnamed Hydric Soil

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

M-W—Miscellaneous Water**Ma—Mayberry clay loam, 2 to 6 percent slopes****Map Unit Composition**

Mayberry: 95 percent
 Minor components: 5 percent

Component Descriptions**Mayberry**

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Till, unspecified
Slope: 2 to 6 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 7.0 inches)
Shrink-swell potential: Very high (About 9.2 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 9 to 14 inches
Runoff class: High
Ecological site: Clay Upland (pe30-37)
Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 7 inches; clay loam
 AB—7 to 13 inches; clay loam
 Bt—13 to 43 inches; clay
 BC—43 to 57 inches; clay
 C—57 to 64 inches; clay loam

Minor Components**Irwin**

Composition: About 5 percent
Slope: 4 to 8 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Mb—Mayberry clay loam, 2 to 6 percent slopes, eroded

Map Unit Composition

Mayberry: 95 percent
Minor components: 5 percent

Component Descriptions

Mayberry

MLRA: 76 - Bluestem Hills
Landform: Upland on hillslope
Parent material: Clayey till
Slope: 2 to 6 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 6.8 inches)
Shrink-swell potential: Very high (About 9.2 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 6 to 18 inches
Runoff class: High
Ecological site: Clay Upland (pe30-36)
Land capability (nonirrigated): 3e

Typical Profile:

Ap—0 to 7 inches; clay loam
Bt—7 to 37 inches; clay
BC—37 to 51 inches; clay
C—51 to 64 inches; clay loam

Minor Components

Irwin

Phase: Eroded
Composition: About 5 percent
Slope: 4 to 8 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Mu—Muir silt loam, rarely flooded

Map Unit Composition

Muir: 84 percent
Minor components: 16 percent

Component Descriptions

Muir

MLRA: 76 - Bluestem Hills
Landform: Flood plain on alluvial plain
Parent material: Silty alluvium
Slope: 0 to 2 percent
Drainage class: Well drained
Slowest permeability: Moderate (About 0.60 in/hr)
Available water capacity: Very high (About 12.4 inches)
Shrink-swell potential: Moderate (About 3.0 LEP)
Flooding hazard: Rare
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Terrace (pe25-34)
Land capability (nonirrigated): 1

Typical Profile:

Ap—0 to 7 inches; silt loam
A—7 to 18 inches; silt loam
Bw1—18 to 24 inches; silt loam
Bw2—24 to 42 inches; silt loam
C—42 to 60 inches; silt loam

Minor Components

Sutphen

Composition: About 5 percent
Slope: 0 to 1 percent
Drainage class: Somewhat poorly drained
Ecological site: Clay Lowland (pe30-36)

Eudora

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Reading

Composition: About 5 percent
Slope: 0 to 1 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

QUA—Quarries

Rd—Reading silt loam, 0 to 1 percent slopes, rarely flooded**Map Unit Composition**

Reading: 90 percent
 Minor components: 10 percent

Component Descriptions**Reading**

MLRA: 76 - Bluestem Hills
Landform: Terrace on river valley
Parent material: Fine-silty alluvium
Slope: 0 to 1 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 11.5 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: Rare
Depth to seasonal water saturation: More than 6 feet
Runoff class: Low
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 1

Typical Profile:

H1—0 to 11 inches; silt loam
 H2—11 to 52 inches; silty clay loam
 H3—52 to 60 inches; silty clay loam

Minor Components**Muir**

Composition: About 5 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Terrace (pe25-34)

Chase

Composition: About 5 percent
Slope: 0 to 1 percent
Drainage class: Somewhat poorly drained
Ecological site: Loamy Lowland (pe30-36)

Re—Reading silt loam, 1 to 3 percent slopes, rarely flooded**Map Unit Composition**

Reading: 90 percent
 Minor components: 10 percent

Component Descriptions**Reading**

MLRA: 76 - Bluestem Hills
Landform: Alluvial fan on river valley
Parent material: Fine-silty alluvium
Slope: 1 to 3 percent
Drainage class: Well drained
Slowest permeability: Moderately slow (About 0.20 in/hr)
Available water capacity: High (About 11.5 inches)
Shrink-swell potential: Moderate (About 4.5 LEP)
Flooding hazard: Rare
Depth to seasonal water saturation: More than 6 feet
Runoff class: Medium
Ecological site: Loamy Lowland (pe30-36)
Land capability (nonirrigated): 2e

Typical Profile:

H1—0 to 11 inches; silt loam
 H2—11 to 52 inches; silty clay loam
 H3—52 to 60 inches; silty clay loam

Minor Components**Tully**

Composition: About 10 percent
Landform: hillslope on upland
Slope: 4 to 8 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe25-34)

Sa—Sarpy loamy fine sand, 0 to 4 percent slopes, occasionally flooded**Map Unit Composition**

Sarpy: 98 percent
 Minor components: 2 percent

Component Descriptions

Sarpy

MLRA: 76 - Bluestem Hills
Landform: Flood plain on river valley
Parent material: Sandy alluvium
Slope: 0 to 5 percent
Drainage class: Excessively drained
Slowest permeability: Rapid (About 5.95 in/hr)
Available water capacity: Low (About 4.1 inches)
Shrink-swell potential: Low (About 1.5 LEP)
Flooding hazard: Occasional
Depth to seasonal water saturation: More than 6 feet
Runoff class: Negligible
Ecological site: Sands (pe30-36)
Land capability (nonirrigated): 4s

Typical Profile:

H1—0 to 5 inches; loamy fine sand
 H2—5 to 60 inches; fine sand

Minor Components

Unnamed Hydric Soil (ponding)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Unnamed Hydric Soil (saturation)

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Poorly drained

Sm—Smolan silt loam, 1 to 4 percent slopes

Map Unit Composition

Smolan: 90 percent
 Minor components: 10 percent

Component Descriptions

Smolan

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Parent material: Silty and clayey loess
Slope: 1 to 4 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 10.5 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None

Depth to seasonal water saturation: More than 6 feet

Runoff class: High

Ecological site: Loamy Upland (pe30-36)

Land capability (nonirrigated): 2e

Typical Profile:

H1—0 to 8 inches; silt loam
 H2—8 to 17 inches; silty clay loam
 H3—17 to 51 inches; silty clay loam
 H4—51 to 60 inches; silty clay loam

Minor Components

Wymore

Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 6 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe25-34)

Geary

Composition: About 5 percent
Slope: 4 to 8 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Sn—Smolan silt loam, 4 to 8 percent slopes

Map Unit Composition

Smolan: 75 percent
 Minor components: 25 percent

Component Descriptions

Smolan

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Parent material: Silty and clayey loess
Slope: 4 to 8 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 10.5 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 3e

Typical Profile:

H1—0 to 8 inches; silt loam

H2—8 to 17 inches; silty clay loam
 H3—17 to 51 inches; silty clay loam
 H4—51 to 60 inches; silty clay loam

Minor Components

Geary

Composition: About 20 percent
Slope: 4 to 8 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Rock outcrop

Composition: About 5 percent

So—Smolan silty clay loam, 4 to 8 percent slopes, eroded

Map Unit Composition

Smolan: 80 percent
 Minor components: 20 percent

Component Descriptions

Smolan

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Parent material: Silty and clayey loess
Slope: 4 to 8 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 9.7 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Upland (pe30-36)
Land capability (nonirrigated): 4e

Typical Profile:

H1—0 to 7 inches; silty clay loam
 H2—7 to 51 inches; silty clay loam
 H3—51 to 60 inches; silty clay loam

Minor Components

Geary

Phase: Eroded
Composition: About 20 percent
Slope: 4 to 8 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

St—Clime silty clay loam, 20 to 40 percent slopes, stony

Map Unit Composition

Clime: 75 percent
 Minor components: 25 percent

Component Descriptions

Clime

MLRA: 76 - Bluestem Hills
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Silty and clayey residuum weathered from shale, calcareous
Slope: 20 to 40 percent
Surface fragments: About 0 to 3 percent angular (shape or size unspecified)
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Low (About 5.3 inches)
Shrink-swell potential: High (About 8.4 LEP)
Flooding hazard: None
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Limy Upland (pe30-36)
Land capability (nonirrigated): 7e

Typical Profile:

A1—0 to 2 inches; silty clay loam
 A2—2 to 9 inches; silty clay
 Bw—9 to 27 inches; silty clay
 C—27 to 33 inches; silty clay
 Cr—33 to 37 inches; weathered bedrock

Minor Components

Tuttle

Composition: About 10 percent
Landform: hillslope on upland
Slope: 20 to 40 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Somewhat excessively drained

Tully

Composition: About 8 percent
Landform: hillslope on upland
Slope: 8 to 15 percent
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Rock outcrop

Composition: About 4 percent
Slope: 30 to 50 percent

Ivan

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Kahola

Composition: About 1 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Sogn

Composition: About 1 percent
Slope: 1 to 20 percent
Depth to restrictive feature: 4 to 20 inches to bedrock (lithic)
Drainage class: Somewhat excessively drained
Ecological site: Shallow Limy (pe30-36)

Su—Sutphen silty clay, occasionally flooded**Map Unit Composition**

Sutphen: 100 percent

Component Descriptions**Sutphen**

MLRA: 76 - Bluestem Hills
Landform: Flood plain on river valley
Parent material: Clayey alluvium
Slope: 0 to 1 percent
Drainage class: Somewhat poorly drained
Slowest permeability: Very slow (About 0.00 in/hr)
Available water capacity: Moderate (About 7.7 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: Occasional
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Lowland (pe26-30)
Land capability (nonirrigated): 3w

Typical Profile:

H1—0 to 8 inches; silty clay
H2—8 to 32 inches; silty clay
H3—32 to 60 inches; silty clay loam

Minor Components**Unnamed Hydric Soils****Unnamed Hydric Soil****Ts—Tully silty clay loam, 1 to 4 percent slopes****Map Unit Composition**

Tully: 85 percent
Minor components: 15 percent

Component Descriptions**Tully**

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Footslope
Parent material: Clayey colluvium
Slope: 1 to 4 percent
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 9.1 inches)
Shrink-swell potential: High (About 8.0 LEP)
Flooding hazard: None
Ponding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Loamy Upland (pe30-36)
Land capability (nonirrigated): 2e

Typical Profile:

A—0 to 12 inches; silty clay loam
BA—12 to 21 inches; silty clay loam
Bt1—21 to 31 inches; silty clay
Bt2—31 to 40 inches; silty clay
Bt3—40 to 52 inches; silty clay
BC—52 to 60 inches; silty clay

Minor Components**Kahola**

Composition: About 6 percent
Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Reading

Composition: About 5 percent

Slope: 0 to 2 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Florence

Composition: About 2 percent
Landform: hillslope on upland
Slope: 5 to 8 percent
Depth to restrictive feature: 40 to 60 inches
to bedrock (lithic)
Drainage class: Well drained
Ecological site: Loamy Upland (pe30-36)

Clime

Composition: About 2 percent
Slope: 1 to 4 percent
Depth to restrictive feature: 20 to 40 inches
to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

Tt—Tully silty clay loam, 1 to 4 percent slopes, eroded**Map Unit Composition**

Tully: 85 percent
 Minor components: 15 percent

Component Descriptions**Tully**

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Footslope
Parent material: Clayey colluvium
Slope: 1 to 4 percent
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 8.1 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: High
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 3e

Typical Profile:

H1—0 to 7 inches; silty clay loam
 H2—7 to 51 inches; silty clay
 H3—51 to 60 inches; silty clay

Minor Components**Irwin**

Phase: Eroded
Composition: About 5 percent
Slope: 1 to 4 percent
Depth to restrictive feature: 40 to 60 inches
to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Wymore

Phase: Eroded
Composition: About 5 percent
Landform: hillslope on upland
Slope: 3 to 6 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe25-34)

Reading

Composition: About 5 percent
Slope: 0 to 1 percent
Drainage class: Well drained
Ecological site: Loamy Lowland (pe30-36)

Tu—Tully silty clay loam, 4 to 8 percent slopes**Map Unit Composition**

Tully: 85 percent
 Minor components: 15 percent

Component Descriptions**Tully**

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Footslope
Parent material: Clayey colluvium
Slope: 4 to 8 percent
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 8.3 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Loamy Upland (pe25-34)
Land capability (nonirrigated): 3e

Typical Profile:

H1—0 to 10 inches; silty clay loam
 H2—10 to 51 inches; silty clay

H3—51 to 60 inches; silty clay

Minor Components

Irwin

Composition: About 8 percent
Slope: 1 to 4 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Wymore

Composition: About 6 percent
Landform: hillslope on upland
Slope: 3 to 6 percent
Drainage class: Moderately well drained
Ecological site: Loamy Upland (pe25-34)

Unnamed Hydric Soil

Composition: About 1 percent
Drainage class: Poorly drained

Tv—Tully silty clay loam, 4 to 8 percent slopes, eroded

Map Unit Composition

Tully: 85 percent
 Minor components: 15 percent

Component Descriptions

Tully

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Footslope
Parent material: Clayey colluvium
Slope: 4 to 8 percent
Drainage class: Well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: Moderate (About 8.1 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: More than 6 feet
Runoff class: Very high
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 4e

Typical Profile:

H1—0 to 7 inches; silty clay loam
 H2—7 to 51 inches; silty clay
 H3—51 to 60 inches; silty clay

Minor Components

Clime

Composition: About 5 percent
Slope: 3 to 6 percent
Depth to restrictive feature: 20 to 40 inches to bedrock (paralithic)
Drainage class: Well drained
Ecological site: Limy Upland (pe30-36)

Rock outcrop

Composition: About 5 percent

Irwin

Phase: Eroded
Composition: About 5 percent
Slope: 4 to 8 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

W—Water

Wm—Wymore silty clay loam, 0 to 1 percent slopes

Map Unit Composition

Wymore: 100 percent

Component Descriptions

Wymore

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Summit
Parent material: Silty and clayey loess over clayey pedisediment
Slope: 0 to 1 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 10.4 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 12 to 36 inches
Runoff class: Medium
Ecological site: Loamy Upland (pe25-34)
Land capability (nonirrigated): 2s

Typical Profile:

H1—0 to 13 inches; silty clay loam
 H2—13 to 33 inches; silty clay
 H3—33 to 64 inches; silty clay loam

Wn—Wymore silty clay loam, 1 to 4 percent slopes

Map Unit Composition

Wymore: 90 percent
 Minor components: 10 percent

Component Descriptions

Wymore

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Backslope, shoulder
Parent material: Silty and clayey loess over clayey pedisodiment
Slope: 1 to 4 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 10.4 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 12 to 36 inches
Runoff class: High
Ecological site: Loamy Upland (pe25-34)
Land capability (nonirrigated): 2e

Typical Profile:

H1—0 to 13 inches; silty clay loam
 H2—13 to 33 inches; silty clay
 H3—33 to 64 inches; silty clay loam

Minor Components

Rock outcrop

Composition: About 5 percent

Irwin

Composition: About 5 percent
Slope: 4 to 8 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Wo—Wymore silty clay loam, 1 to 4 percent slopes, eroded

Map Unit Composition

Wymore: 90 percent
 Minor components: 10 percent

Component Descriptions

Wymore

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Silty and clayey loess over clayey pedisodiment
Slope: 1 to 4 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 9.9 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 12 to 36 inches
Runoff class: High
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 3e

Typical Profile:

H1—0 to 7 inches; silty clay loam
 H2—7 to 33 inches; silty clay
 H3—33 to 64 inches; silty clay loam

Minor Components

Rock outcrop

Composition: About 5 percent

Irwin

Phase: Eroded
Composition: About 5 percent
Slope: 4 to 8 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Wr—Wymore silty clay loam, 4 to 8 percent slopes**Map Unit Composition**

Wymore: 90 percent
 Minor components: 10 percent

Component Descriptions**Wymore**

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Silty and clayey loess over clayey pedisement
Slope: 4 to 8 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 10.4 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 12 to 36 inches
Runoff class: Very high
Ecological site: Loamy Upland (pe25-34)
Land capability (nonirrigated): 3e

Typical Profile:

H1—0 to 13 inches; silty clay loam
 H2—13 to 33 inches; silty clay
 H3—33 to 64 inches; silty clay loam

Minor Components**Rock outcrop**

Composition: About 5 percent

Irwin

Composition: About 5 percent
Slope: 4 to 8 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Ws—Wymore silty clay loam, 4 to 8 percent slopes, eroded**Map Unit Composition**

Wymore: 90 percent
 Minor components: 10 percent

Component Descriptions**Wymore**

MLRA: 75 - Central Loess Plains
Landform: Hillslope on upland
Hillslope position: Backslope
Parent material: Silty and clayey loess over clayey pedisement
Slope: 4 to 8 percent
Drainage class: Moderately well drained
Slowest permeability: Slow (About 0.06 in/hr)
Available water capacity: High (About 9.9 inches)
Shrink-swell potential: High (About 7.5 LEP)
Flooding hazard: None
Depth to seasonal water saturation: About 12 to 36 inches
Runoff class: Very high
Ecological site: Clay Upland (pe25-34)
Land capability (nonirrigated): 4e

Typical Profile:

H1—0 to 7 inches; silty clay loam
 H2—7 to 33 inches; silty clay
 H3—33 to 60 inches; silty clay loam

Minor Components**Irwin**

Phase: Eroded
Composition: About 5 percent
Slope: 4 to 8 percent
Depth to restrictive feature: 40 to 60 inches to bedrock (paralithic)
Drainage class: Moderately well drained
Ecological site: Clay Upland (pe25-34)

Rock outcrop

Composition: About 5 percent

Prime farmland is one of several kinds of important farmland defined by the U.S. Department of Agriculture. It is of major importance in meeting the Nation's short- and long-range needs for food and fiber. Because the supply of high-quality farmland is limited, the U.S. Department of Agriculture recognizes that responsible levels of government, as well as individuals, should encourage and facilitate the wise use of our Nation's prime farmland.

Prime farmland, as defined by the U.S. Department of Agriculture, is land that has the best combination of physical and chemical characteristics for producing food, feed, forage, fiber, and oilseed crops and is available for these uses. It could be cultivated land, pastureland, forestland, or other land, but it is not urban or built-up land or water areas. The soil qualities, growing season, and moisture supply are those needed for the soil to economically produce sustained high yields of crops when proper management, including water management, and acceptable farming methods are applied. In general, prime farmland has an adequate and dependable supply of moisture from precipitation or irrigation, a favorable temperature and growing season, acceptable acidity or alkalinity, an acceptable salt and sodium content, and few or no rocks. It is permeable to water and air. It is not excessively erodible or saturated with water for long periods, and it either is not frequently flooded during the growing season or is protected from flooding. Slope ranges mainly from 0 to 6 percent. More detailed information about the criteria for prime farmland is available at the local office of the Natural Resources Conservation Service.

A recent trend in land use in some parts of the survey area has been the loss of some prime farmland to industrial and urban uses. The loss of prime farmland to other uses puts pressure on marginal lands, which generally are more erodible, droughty, and less productive and cannot be easily cultivated.

The map units in the survey area that are considered prime farmland are listed in the following table. This list does not constitute a recommendation for a particular land use. On some soils included in the list, measures that overcome a hazard or limitation, such as flooding, wetness, and droughtiness, are needed. Onsite evaluation is needed to determine whether or not the hazard or limitation has been overcome by corrective measures. The extent of each listed map unit is shown in the "Acres and Proportionate Extent of Soils" table. The location is shown on the detailed soil maps. The soil qualities that affect use and management are described in other tables in this document."

Map symbol	Mapunit name	Farmland Classification
027CS	Crete silt loam, 1 to 3 percent slopes	All areas are prime farmland
061CR	Crete silty clay loam, 0 to 1 percent slopes	All areas are prime farmland
061CS	Crete silty clay loam, 1 to 4 percent slopes	All areas are prime farmland
061EU	Eudora silt loam, occasionally flooded	All areas are prime farmland
061KB	Kahola silt loam, occasionally flooded	All areas are prime farmland
061RE	Reading silty clay loam, 0 to 2 percent slopes	All areas are prime farmland
117PA	Pawnee clay loam, 1 to 4 percent slopes	All areas are prime farmland
197IB	Irwin silty clay loam, 1 to 3 percent slopes	All areas are prime farmland
197IV	Ivan silt loam, occasionally flooded	All areas are prime farmland
201CS	Crete silty clay loam, 1 to 3 percent slopes	All areas are prime farmland
201LC	Lancaster loam, 3 to 7 percent slopes	All areas are prime farmland
Ch	Chase silty clay loam, rarely flooded	All areas are prime farmland
CT	Crete silty clay loam, 3 to 7 percent slopes	All areas are prime farmland
Em	Elmont silt loam, 3 to 8 percent slopes	All areas are prime farmland
Eu	Eudora silt loam, rarely flooded	All areas are prime farmland
Ga	Geary silt loam, 1 to 4 percent slopes	All areas are prime farmland
Ge	Geary silt loam, 4 to 8 percent slopes	All areas are prime farmland
Ha	Haynie very fine sandy loam, occasionally flooded	All areas are prime farmland
HO	Hobbs silt loam, occasionally flooded	All areas are prime farmland
Ie	Ivan silty clay loam, 1 to 3 percent slopes	All areas are prime farmland
Iv	Ivan and kennebec silt loams, occasionally flooded	All areas are prime farmland
Ka	Kahola silt loam, rarely flooded	All areas are prime farmland
Ke	Kenesaw silt loam, 2 to 6 percent slopes	All areas are prime farmland
KN	Kennebec silt loam, occasionally flooded	All areas are prime farmland
Mu	Muir silt loam, rarely flooded	All areas are prime farmland
Rd	Reading silt loam, 0 to 1 percent slopes, rarely flooded	All areas are prime farmland
Re	Reading silt loam, 1 to 3 percent slopes, rarely flooded	All areas are prime farmland
Sm	Smolan silt loam, 1 to 4 percent slopes	All areas are prime farmland
Su	Sutphen silty clay, occasionally flooded	All areas are prime farmland
Ts	Tully silty clay loam, 1 to 4 percent slopes	All areas are prime farmland
Tt	Tully silty clay loam, 1 to 4 percent slopes, eroded	All areas are prime farmland
Wm	Wymore silty clay loam, 0 to 1 percent slopes	All areas are prime farmland
Wn	Wymore silty clay loam, 1 to 4 percent slopes	All areas are prime farmland
Wo	Wymore silty clay loam, 1 to 4 percent slopes, eroded	All areas are prime farmland

SOIL RATING FOR PLANT GROWTH, modified 1998
Riley County, Kansas

The "Soil Rating for Plant Growth, modified 1998" (SRPG) is a relative rating of the capacity of a soil to produce a specific plant under a defined management system. The index is determined from yield data on a few benchmark soils and is used to calculate yields, the net returns from crops, land assessment values, and taxes and to perform risk analysis when land management decisions are made. Specific information on plants and yields can be obtained from the local office of the Natural Resources Conservation Service or the Cooperative Extension Service.

Map symbol	Soil name	Crop Index
027CS	Crete Silt Loam, 1 To 3 Percent Slopes-----	69
027CX	Crete Silty Clay Loam, 3 To 8 Percent Slopes, Eroded-----	65
027HN	Hobbs Silt Loam, Channeled-----	56
027KS	Kipson-Sogn Silty Clay Loams, 5 To 20 Percent Slopes-----	14
061BE	Benfield-Florence Complex, 5 To 30 Percent Slopes-----	36
061CF	Clime-Sogn Silty Clay Loams, 5 To 20 Percent Slopes-----	25
061CR	Crete Silty Clay Loam, 0 To 1 Percent Slopes-----	73
061CS	Crete Silty Clay Loam, 1 To 4 Percent Slopes-----	69
061EU	Eudora Silt Loam, Occasionally Flooded-----	70
061HE	Haynie Silt Loam, Frequently Flooded-----	45
061KA	Kahola Silt Loam, Channeled-----	59
061KB	Kahola Silt Loam, Occasionally Flooded-----	74
061RE	Reading Silty Clay Loam, 0 To 2 Percent Slopes-----	79
061TO	Tully Silty Clay Loam, 3 To 8 Percent Slopes-----	67
117PA	Pawnee Clay Loam, 1 To 4 Percent Slopes-----	60
117PB	Pawnee Clay Loam, 4 To 8 Percent Slopes-----	58
149HS	Haynie-Sarpy Complex, Occasionally Flooded-----	44
149PS	Paxico Silt Loam, Frequently Flooded-----	40
149SF	Sarpy Sand, Frequently Flooded-----	21
197CM	Clime Silty Clay Loam, 3 To 7 Percent Slopes-----	35
197FL	Florence-Labette Complex, 3 To 15 Percent Slopes-----	50
197IB	Irwin Silty Clay Loam, 1 To 3 Percent Slopes-----	67
197ID	Irwin Silty Clay Loam, 3 To 7 Percent Slopes-----	52
197IV	Ivan Silt Loam, Occasionally Flooded-----	63
197IX	Ivan Silty Clay Loam, Channeled-----	55
197PN	Pawnee Clay Loam, 3 To 7 Percent Slopes-----	69
197WE	Wamego Silty Clay Loam, 3 To 7 Percent Slopes-----	37
201CS	Crete Silty Clay Loam, 1 To 3 Percent Slopes-----	69
201CX	Crete Silty Clay Loam, 3 To 7 Percent Slopes, Eroded-----	72
201KS	Kipson-Sogn Complex, 5 To 30 Percent Slopes-----	13
201LC	Lancaster Loam, 3 To 7 Percent Slopes-----	47
AED	Arents, Earthen Dam-----	0
Ad	Ivan Silt Loam, Channeled-----	47
BE	Benfield Silty Clay Loam, 3 To 7 Percent Slopes-----	44
BOP	Borrow Pits-----	0
Bf	Benfield-Florence Complex, 5 To 20 Percent Slopes-----	38
Bk	Wymore-Kennebec Complex, 0 To 17 Percent Slopes-----	67
CT	Crete Silty Clay Loam, 3 To 7 Percent Slopes-----	66
Ca	Carr-Sarpy Complex, Occasionally Flooded-----	39
Ch	Chase Silty Clay Loam, Rarely Flooded-----	63
Cs	Clime-Sogn Complex, 5 To 20 Percent Slopes-----	21
Dr	Dwight-Irwin Complex, 1 To 4 Percent Slopes-----	55
Dw	Dwight-Irwin Complex, 1 To 4 Percent Slopes, Eroded-----	54
Em	Elmont Silt Loam, 3 To 8 Percent Slopes-----	70
En	Elmont-Clime Complex, 5 To 15 Percent Slopes-----	55
Eu	Eudora Silt Loam, Rarely Flooded-----	71
Ga	Geary Silt Loam, 1 To 4 Percent Slopes-----	78
Ge	Geary Silt Loam, 4 To 8 Percent Slopes-----	75
HO	Hobbs Silt Loam, Occasionally Flooded-----	71
Ha	Haynie Very Fine Sandy Loam, Occasionally Flooded-----	50
Ic	Irwin Silty Clay Loam, 4 To 8 Percent Slopes-----	61
Id	Irwin Silty Clay Loam, 4 To 8 Percent Slopes, Eroded-----	61
Ie	Ivan Silty Clay Loam, 1 To 3 Percent Slopes-----	61
Iv	Ivan And Kennebec Silt Loams, Occasionally Flooded-----	70
KN	Kennebec Silt Loam, Occasionally Flooded-----	80
Ka	Kahola Silt Loam, Rarely Flooded-----	62
Ke	Kenesaw Silt Loam, 2 To 6 Percent Slopes-----	75
Kf	Kenesaw Silt Loam, 6 To 10 Percent Slopes-----	71
M-W	Miscellaneous Water-----	0
Ma	Mayberry Clay Loam, 2 To 6 Percent Slopes-----	55
Mb	Mayberry Clay Loam, 2 To 6 Percent Slopes, Eroded-----	53
Mu	Muir Silt Loam, Rarely Flooded-----	75
QUA	Quarries-----	0
Rd	Reading Silt Loam, 0 To 1 Percent Slopes, Rarely Flooded-----	81
Re	Reading Silt Loam, 1 To 3 Percent Slopes, Rarely Flooded-----	81
Sa	Sarpy Loamy Fine Sand, 0 To 4 Percent Slopes, Occasionally Flooded-----	23
Sm	Smolan Silt Loam, 1 To 4 Percent Slopes-----	78
Sn	Smolan Silt Loam, 4 To 8 Percent Slopes-----	72
So	Smolan Silty Clay Loam, 4 To 8 Percent Slopes, Eroded-----	72
St	Clime Silty Clay Loam, 20 To 40 Percent Slopes, Stony-----	8
Su	Sutphen Silty Clay, Occasionally Flooded-----	48
Ts	Tully Silty Clay Loam, 1 To 4 Percent Slopes-----	71
Tt	Tully Silty Clay Loam, 1 To 4 Percent Slopes, Eroded-----	69
Tu	Tully Silty Clay Loam, 4 To 8 Percent Slopes-----	66
Tv	Tully Silty Clay Loam, 4 To 8 Percent Slopes, Eroded-----	61
W	Water-----	0
Wm	Wymore Silty Clay Loam, 0 To 1 Percent Slopes-----	78
Wn	Wymore Silty Clay Loam, 1 To 4 Percent Slopes-----	72
Wo	Wymore Silty Clay Loam, 1 To 4 Percent Slopes, Eroded-----	70
Wr	Wymore Silty Clay Loam, 4 To 8 Percent Slopes-----	69
Ws	Wymore Silty Clay Loam, 4 To 8 Percent Slopes, Eroded-----	67

The "Soil Rating for Plant Growth, modified 1998" (SRPG) is a relative rating of the capacity of a soil to produce a specific plant under a defined management system. The index is determined from yield data on a few benchmark soils and is used to calculate yields, the net returns from crops, land assessment values, and taxes and to perform risk analysis when land management decisions are made. Specific information on plants and yields can be obtained from the local office of the Natural Resources Conservation Service or the Cooperative Extension Service.

Map symbol	Soil name	Crop Index

Riley County, Kansas: Published
 Field Office Thunderbook: Soils Properties for Conservation Planning

(Entries under "Erosion factors--T" apply to the entire profile. Entries under "K", "Kf", "Wind Erodibility Group" and "Wind Erodibility Index" apply only to the surface layer)

Map symbol and soil name	Percent	Irr Cap Class	Nonirr Cap Class	Prime Farmland	Hydro-logic Group	Range site name	Windbreak suitability group	Erosion factors			Wind erodibility group	Wind erodibility index
								K	Kf	T		
027CS:CRETE-----	90	N/A	2e	All areas are prime farmland	C	Clay Upland (pe25-34)	7	.37	.37	5	6	48
027CX:CRETE-----	83	N/A	4e	Not prime farmland	C	Clay Upland (pe25-34)	8	.37	.37	5	7	38
027HN:HOBBS-----	90	N/A	5w	Not prime farmland	B	Loamy Lowland (pe25-34)	7	.32	.32	5	6	48
027KS:KIPSON----	70	N/A	6e	Not prime farmland	D	Limy Upland (pe25-34)	5	.32	.49	2	4L	86
027KS:SOGN-----	15	N/A	6e	Not prime farmland	D	Shallow Limy (pe25-34)	5	.32	.49	1	4L	86
061BE:BENFIELD--	42	N/A	6e	Not prime farmland	C	Loamy Upland (pe30-36)	8	.37	.37	3	7	38
061BE:FLORENCE--	28	N/A	6e	Not prime farmland	C	Loamy Upland (pe30-36)	9	.15	.24	3	8	0
061CF:CLIME-----	60	N/A	6e	Not prime farmland	C	Limy Upland (pe30-36)	4	.24	.32	3	4	86
061CF:SOGN-----	20	N/A	6s	Not prime farmland	D	Shallow Limy (pe30-36)	5	.24	.32	1	4L	86
061CR:CRETE-----	90	N/A	2s	All areas are prime farmland	C	Clay Upland (pe25-34)	8	.37	.37	5	7	38
061CS:CRETE-----	90	N/A	2e	All areas are prime farmland	C	Clay Upland (pe25-34)	8	.37	.37	5	7	38
061EU:EUDORA----	85	N/A	2w	All areas are prime farmland	B	Loamy Lowland (pe30-36)	6	.32	.32	5	5	56
061HE:HAYNIE----	55	N/A	5w	Not prime farmland	B	Loamy Lowland (pe30-36)	5	.32	.32	5	4L	86
061KA:KAHOLA----	75	N/A	5w	Not prime farmland	B	Loamy Lowland (pe30-36)	7	.32	.32	5	6	48
061KB:KAHOLA----	75	N/A	2w	All areas are prime farmland	B	Loamy Lowland (pe30-36)	7	.32	.32	5	6	48
061RE:READING---	85	N/A	1	All areas are prime farmland	B	Loamy Lowland (pe30-36)	8	.32	.32	5	7	38
061TO:TULLY-----	85	N/A	3e	Not prime farmland	C	Loamy Upland (pe30-36)	8	.37	.37	5	7	38
117PA:PAWNEE----	88	N/A	2e	All areas are prime farmland	D	Loamy Upland (pe30-37)	7	.37	.37	5	6	48

Riley County, Kansas: Published
 Field Office Thunderbook: Soils Properties for Conservation Planning--Continued

Map symbol and soil name	Percent	Irr Cap Class	Nonirr Cap Class	Prime Farmland	Hydro-logic Group	Range site name	Windbreak suitability group	Erosion factors			Wind erodi-bility group	Wind erodi-bility index
								K	Kf	T		
117PB:PAWNEE----	88	N/A	3e	Not prime farmland	D	Loamy Upland (pe30-37)	7	.37	.37	5	6	48
149HS:HAYNIE----	60	N/A	3w	Not prime farmland	B	Loamy Lowland (pe30-37)	3	.37	.37	5	3	86
149HS:SARPY-----	25	N/A	3w	Not prime farmland	A	Sandy Lowland (pe30-37)	1	.15	.15	5	1	250
149PS:PAXICO----	90	N/A	5w	Not prime farmland	B	Unspecified	5	.37	.37	5	4L	86
149SF:SARPY-----	90	N/A	4s	Not prime farmland	A	Sandy Lowland (pe30-37)	1	.15	.15	5	1	220
197CM:CLIME-----	85	N/A	4e	Not prime farmland	C	Limy Upland (pe30-36)	4	.32	.32	3	4	86
197FL:FLORENCE--	40	N/A	6e	Not prime farmland	C	Loamy Upland (pe30-36)	9	.24	.64	3	8	0
197FL:LABETTE---	30	N/A	6e	Not prime farmland	C	Loamy Upland (pe30-36)	7	.32	.32	2	6	48
197IB:IRWIN-----	80	N/A	3e	All areas are prime farmland	D	Clay Upland (pe30-36)	8	.32	.32	5	7	38
197ID:IRWIN-----	85	N/A	4e	Not prime farmland	D	Clay Upland (pe30-36)	8	.37	.37	5	7	38
197IV:IVAN-----	90	N/A	2w	All areas are prime farmland	B	Loamy Lowland (pe30-36)	5	.32	.32	5	4L	86
197IX:IVAN-----	80	N/A	5w	Not prime farmland	B	Loamy Lowland (pe30-36)	5	.32	.32	5	4L	86
197PN:PAWNEE----	85	N/A	3e	Not prime farmland	D	Clay Upland (pe30-37)	7	.37	.37	5	6	48
197WE:WAMEGO----	90	N/A	4e	Not prime farmland	C	Clay Upland (pe30-37)	8	.32	.32	3	7	38
201CS:CRETE-----	95	N/A	2e	All areas are prime farmland	C	Clay Upland (pe26-30)	8	.37	.37	5	7	38
201CX:CRETE-----	90	N/A	4e	Not prime farmland	C	Clay Upland (pe26-30)	8	.37	.37	5	7	38
201KS:KIPSON----	70	N/A	6e	Not prime farmland	D	Limy Upland (pe26-30)	5	.32	.49	2	4L	86
201KS:SOGN-----	15	N/A	6e	Not prime farmland	D	Shallow Limy (pe26-30)	5	.32	.37	1	4L	86
201LC:LANCASTER-	85	N/A	4e	All areas are prime farmland	B	Loamy Upland (pe26-30)	7	.24	.28	3	6	48
AED:ARENTS, EARTHEN DAM----	100	N/A	8	Not prime farmland		Unspecified		---	---	-	---	---

Riley County, Kansas: Published
 Field Office Thunderbook: Soils Properties for Conservation Planning--Continued

Map symbol and soil name	Percent	Irr Cap Class	Nonirr Cap Class	Prime Farmland	Hydro-logic Group	Range site name	Windbreak suitability group	Erosion factors			Wind erodi-bility group	Wind erodi-bility index
								K	Kf	T		
Ad:IVAN-----	99	N/A	5w	Not prime farmland	B	Loamy Lowland (pe25-34)	5	.32	.32	5	4L	86
BE:BENFIELD----	89	N/A	4e	Not prime farmland	C	Loamy Upland (pe25-34)	8	.37	.43	3	7	38
BOP:BORROW PITS-	100	N/A	N/A	Not prime farmland		Unspecified		---	---	-	---	---
Bf:BENFIELD----	45	N/A	6e	Not prime farmland	C	Loamy Upland (pe30-36)	8	.37	.43	3	7	38
Bf:FLORENCE-----	30	N/A	6e	Not prime farmland	C	Loamy Upland (pe30-36)	9	.24	.64	3	8	0
Bk:WYMORE-----	60	N/A	6e	Not prime farmland	D	Clay Upland (pe25-34)	8	.37	.37	5	7	38
Bk:KENNEBEC----	45	N/A	1	Not prime farmland	B	Loamy Lowland (pe30-36)	7	.32	.32	5	6	48
CT:CRETE-----	83	N/A	3e	All areas are prime farmland	C	Clay Upland (pe25-34)	8	.37	.37	5	7	38
Ca:CARR-----	45	N/A	3w	Not prime farmland	B	Sandy Lowland (pe30-36)	3	.24	.24	4	3	86
Ca:SARPY-----	40	N/A	3w	Not prime farmland	A	Sands (pe30-36)	2	.17	.17	5	2	134
Ch:CHASE-----	84	N/A	2w	All areas are prime farmland	C	Loamy Lowland (pe30-36)	8	.37	.37	5	7	38
Cs:CLIME-----	50	N/A	6e	Not prime farmland	C	Limy Upland (pe30-36)	4	.32	.32	3	4	86
Cs:SOGN-----	30	N/A	6e	Not prime farmland	D	Shallow Limy (pe30-36)	5	.32	.32	1	4L	86
Dr:DWIGHT-----	45	N/A	4e	Not prime farmland	D	Clay Pan (pe25-34)	7	.43	.43	2	6	48
Dr:IRWIN-----	40	N/A	4e	Not prime farmland	D	Clay Upland (pe25-34)	8	.37	.37	4	7	38
Dw:DWIGHT-----	45	N/A	4e	Not prime farmland	D	Clay Pan (pe25-34)	7	.43	.43	2	6	48
Dw:IRWIN-----	40	N/A	4e	Not prime farmland	D	Clay Upland (pe25-34)	8	.37	.37	4	7	38
Em:ELMONT-----	74	N/A	3e	All areas are prime farmland	B	Loamy Upland (pe30-36)	7	.32	.32	5	6	48
En:ELMONT-----	35	N/A	6e	Not prime farmland	B	Loamy Upland (pe30-36)	7	.32	.32	5	6	48
En:CLIME-----	30	N/A	6e	Not prime farmland	C	Limy Upland (pe30-36)	4	.32	.32	3	4	86

Riley County, Kansas: Published
 Field Office Thunderbook: Soils Properties for Conservation Planning--Continued

Map symbol and soil name	Percent	Irr Cap Class	Nonirr Cap Class	Prime Farmland	Hydro-logic Group	Range site name	Windbreak suitability group	Erosion factors			Wind erodi-bility group	Wind erodi-bility index
								K	Kf	T		
Eu:EUDORA-----	88	N/A	2w	All areas are prime farmland	B	Loamy Lowland (pe30-36)	6	.32	.32	5	5	56
Ga:GEARY-----	90	N/A	2e	All areas are prime farmland	B	Loamy Upland (pe30-36)	7	.32	.32	5	6	48
Ge:GEARY-----	100	N/A	3e	All areas are prime farmland	B	Loamy Upland (pe30-36)	7	.32	.32	5	6	48
HO:HOBBS-----	89	N/A	2w	All areas are prime farmland	B	Loamy Lowland (pe25-34)	7	.32	.32	5	6	48
Ha:HAYNIE-----	90	N/A	1	All areas are prime farmland	B	Loamy Lowland (pe30-36)	3	.37	.37	5	3	86
Ic:IRWIN-----	85	N/A	4e	Not prime farmland	D	Clay Upland (pe25-34)	8	.37	.37	4	7	38
Id:IRWIN-----	85	N/A	4e	Not prime farmland	D	Clay Upland (pe25-34)	8	.37	.37	4	7	38
Ie:IVAN-----	88	N/A	2e	All areas are prime farmland	B	Loamy Lowland (pe30-36)	5	.32	.32	5	4L	86
Iv:IVAN-----	45	N/A	2w	All areas are prime farmland	B	Loamy Lowland (pe30-36)	5	.32	.32	5	4L	86
Iv:KENNEBEC-----	45	N/A	1	All areas are prime farmland	B	Loamy Lowland (pe30-36)	7	.32	.32	5	6	48
KN:KENNEBEC-----	95	N/A	2w	All areas are prime farmland	B	Loamy Lowland (pe35-42)	7	.28	.28	5	6	48
Ka:KAHOLA-----	85	N/A	1	All areas are prime farmland	B	Loamy Lowland (pe30-36)	7	.32	.32	5	6	48
Ke:KENESAW-----	90	N/A	3e	All areas are prime farmland	B	Loamy Upland (pe30-36)	7	.32	.32	5	6	48
Kf:KENESAW-----	85	N/A	4e	Not prime farmland	B	Loamy Upland (pe30-36)	7	.32	.32	5	6	48
M- W:MISCELLANEOUS WATER-----	100	N/A	N/A	Not prime farmland		Unspecified		---	---	-	---	---
Ma:MAYBERRY-----	95	N/A	3e	Not prime farmland	D	Clay Upland (pe30-37)	7	.37	.37	5	6	48
Mb:MAYBERRY-----	95	N/A	3e	Not prime farmland	D	Clay Upland (pe30-36)	7	.37	.37	5	6	48
Mu:MUIR-----	84	N/A	1	All areas are prime farmland	B	Loamy Terrace (pe25-34)	7	.32	.32	5	6	48

Riley County, Kansas: Published
 Field Office Thunderbook: Soils Properties for Conservation Planning--Continued

Map symbol and soil name	Percent	Irr Cap Class	Nonirr Cap Class	Prime Farmland	Hydro-logic Group	Range site name	Windbreak suitability group	Erosion factors			Wind erodi-bility group	Wind erodi-bility index
								K	Kf	T		
QUA:QUARRIES----	100	N/A	N/A	Not prime farmland		Unspecified		---	---	-	---	---
Rd:READING-----	90	N/A	1	All areas are prime farmland	B	Loamy Lowland (pe30-36)	7	.32	.32	5	6	48
Re:READING-----	90	N/A	2e	All areas are prime farmland	B	Loamy Lowland (pe30-36)	7	.32	.32	5	6	48
Sa:SARPY-----	98	N/A	4s	Not prime farmland	A	Sands (pe30-36)	2	.17	.17	5	2	134
Sm:SMOLAN-----	90	N/A	2e	All areas are prime farmland	C	Loamy Upland (pe30-36)	7	.37	.37	5	6	48
Sn:SMOLAN-----	75	N/A	3e	Not prime farmland	C	Loamy Upland (pe30-36)	7	.37	.37	5	6	48
So:SMOLAN-----	80	N/A	4e	Not prime farmland	C	Clay Upland (pe30-36)	8	.37	.37	5	7	38
St:CLIME-----	75	N/A	7e	Not prime farmland	C	Limy Upland (pe30-36)	9	.24	.32	3	8	0
Su:SUTPHEN-----	100	N/A	3w	All areas are prime farmland	D	Clay Lowland (pe26-30)	4	.28	.28	5	4	86
Ts:TULLY-----	85	N/A	2e	All areas are prime farmland	C	Loamy Upland (pe30-36)	8	.37	.37	5	7	38
Tt:TULLY-----	85	N/A	3e	All areas are prime farmland	C	Clay Upland (pe25-34)	8	.37	.37	5	7	38
Tu:TULLY-----	85	N/A	3e	Not prime farmland	C	Loamy Upland (pe25-34)	8	.37	.37	5	7	38
Tv:TULLY-----	85	N/A	4e	Not prime farmland	C	Clay Upland (pe25-34)	8	.37	.37	5	7	38
W:WATER-----	100	N/A	N/A			Unspecified		---	---	-	---	---
Wm:WYMORE-----	100	N/A	2s	All areas are prime farmland	D	Loamy Upland (pe25-34)	8	.37	.37	5	7	38
Wn:WYMORE-----	90	N/A	2e	All areas are prime farmland	D	Loamy Upland (pe25-34)	8	.37	.37	5	7	38
Wo:WYMORE-----	90	N/A	3e	All areas are prime farmland	D	Clay Upland (pe25-34)	8	.37	.37	5	7	38
Wr:WYMORE-----	90	N/A	3e	Not prime farmland	D	Loamy Upland (pe25-34)	8	.37	.37	5	7	38
Ws:WYMORE-----	90	N/A	4e	Not prime farmland	D	Clay Upland (pe25-34)	8	.37	.37	5	7	38

RANGELAND PRODUCTIVITY
Riley County, Kansas

Use and Explanation of Rangeland, Grazed Forest Land, Native Pastureland Interpretations

Information in this subsection can be used to plan the use and management of soils for rangeland, grazed forest land, and native pasture. Different kinds of soils vary in their capacity to produce native grasses and other plants suitable for grazing. Information in this subsection provides groupings of similar soils and estimates of potential forage production, which can be used to determine livestock stocking rates.

Rangeland. Range is land on which the native vegetation (climax or natural potential plant community) is predominantly grasses, grasslike plants, forbs, and shrubs suitable for grazing and browsing. Range includes natural grasslands, savannas, many wetlands, some deserts, tundra, and certain shrub and forb communities. Rangeland receives no regular or frequent cultural treatment. The composition and production of the plant community are determined by soil, climate, topography, overstory canopy, and grazing management.

Grazed Forest Land. Includes land on which the understory includes, as an integral part of the forest plant community, plants that can be grazed without significantly impairing other forest values.

Native Pasture. Includes land on which the native vegetation (climax or natural potential plant community) is forest but which is used and managed primarily for production of native plants for forage. Native pasture includes cut-over forest land and forest land cleared and now managed for native or naturalized forage plants.

Rangeland

In areas that have similar climate and topography, differences in the kind and amount of vegetation produced on rangeland are closely related to the kind of soil. Effective management based on the relationship between the soils and vegetation and water.

The Rangeland, Grazed Forest land, Native Pastureland Interpretations shows, for each soil that supports rangeland vegetation, the ecological site and the potential annual production of vegetation in favorable, normal, unfavorable years. An explanation of the column headings in this table follows.

An ecological site is the product of all the environmental factors responsible for its development. It has characteristic soils that have developed over time throughout the soil development process; a characteristic hydrology, particularly infiltration and runoff, that has developed over time; and a characteristic plant community (kind and amount of vegetation). The hydrology of a site is influenced by development of the soil and plant community. The vegetation, soils, and hydrology are all interrelated. Each is influenced by the others and influences the development of the others. The plant community on an ecological site is typified by an association of species that differs from that of other ecological sites in the kind and/or proportion of species or in total production. Descriptions of ecological sites are provided in the Field Office Technical Guide, which is available in local offices of the Natural Resources Conservation Service.

Total dry-weight production is the amount of vegetation that can be expected to grow annually on well managed rangeland that is supporting the potential natural plant community. It includes all vegetation, whether or not it is palatable to grazing animals. It includes the current year's growth of leaves, twigs, and fruits of woody plants. It does not include the increase in stem diameter of trees and shrubs. It is expressed in pounds per acre of air-dry vegetation for favorable, average, and unfavorable years. In a favorable year, the amount and distribution of precipitation and the temperatures make growing conditions substantially better than average. In a normal year, growing conditions are about average. In an unfavorable year, growing conditions are well below average, generally because of low available soil moisture. Yields are adjusted to a common percent of air-dry moisture content.

Range management requires a knowledge of the kinds of soil and of the potential natural plant community. It also requires an evaluation of the present range similarity index and rangeland trend. Range similarity index is determined by comparing the present plant community with the potential natural plant community on a particular rangeland ecological site. The more closely the existing community resembles the potential community, the higher the range similarity index. Rangeland trend is defined as the direction of change in an existing plant community relative to the potential natural plant community. Further information about the range similarity index and rangeland trend is available in chapter 4 of the National Range and Pasture Handbook, which is available in local offices of the Natural Resources Conservation Service. The objective in range management is to control grazing so that the plants growing on a site are about the same in kind and amount as the potential natural plant community for that site. Such management generally results in the optimum production of vegetation, control of undesirable brush species, conservation of water, and control of erosion. Sometimes, however, an area with a range similarity index somewhat below the potential meets grazing needs, provides wildlife habitat, and protects soil and water resources.

RANGELAND PRODUCTIVITY--Continued
Riley County, Kansas

(Only the soils that support rangeland vegetation suitable for grazing are rated.) Refer to range site description to determine the percentage allowable of grasses, forbs, and shrubs for the range ecological site.

Map symbol and soil name	Ecological site	Total dry-weight production		
		Favorable year	Average year	Unfavorable year
		Lb/acre	Lb/acre	Lb/acre
027CS: Crete-----	Clay Upland (pe25-34)	4,500	4,100	3,000
027CX: Crete-----	Clay Upland (pe25-34)	4,500	4,100	3,000
027HN: Hobbs-----	Loamy Lowland (pe25-34)	4,700	4,200	4,000
027KS: Kipson-----	Limy Upland (pe25-34)	4,500	3,500	2,000
027KS: Sogn-----	Shallow Limy (pe25-34)	3,500	2,500	1,500
061BE: Benfield-----	Loamy Upland (pe30-36)	6,000	4,500	3,000
061BE: Florence-----	Loamy Upland (pe30-36)	5,500	4,500	3,500
061CF: Clime-----	Limy Upland (pe30-36)	5,000	3,500	2,500
061CF: Sogn-----	Shallow Limy (pe30-36)	3,500	2,500	1,500
061CR: Crete-----	Clay Upland (pe25-34)	4,500	4,100	3,700
061CS: Crete-----	Clay Upland (pe25-34)	4,500	4,100	3,700
061EU: Eudora-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
061HE: Haynie-----	Loamy Lowland (pe30-36)	5,300	4,900	4,500
061KA: Kahola-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
061KB: Kahola-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
061RE: Reading-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
061TO: Tully-----	Loamy Upland (pe30-36)	6,000	5,000	3,500
117PA: Pawnee-----	Loamy Upland (pe30-37)	3,700	3,200	2,700
117PB: Pawnee-----	Loamy Upland (pe30-37)	3,700	3,200	2,700
149HS: Haynie-----	Loamy Lowland (pe30-37)	5,300	4,900	4,500
149HS: Sarpy-----	Sandy Lowland (pe30-37)	3,800	3,500	3,000
149PS: Paxico-----	---	---	---	---
149SF: Sarpy-----	Sandy Lowland (pe30-37)	3,800	3,500	3,000
197CM: Clime-----	Limy Upland (pe30-36)	5,000	3,500	2,500
197FL: Florence-----	Loamy Upland (pe30-36)	5,500	4,500	3,500
197FL: Labette-----	Loamy Upland (pe30-36)	5,500	4,500	3,500
197IB: Irwin-----	Clay Upland (pe30-36)	5,000	3,500	2,000
197ID: Irwin-----	Clay Upland (pe30-36)	5,000	3,500	2,000
197IV: Ivan-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
197IX: Ivan-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
197PN: Pawnee-----	Clay Upland (pe30-37)	3,700	3,200	2,700
197WE: Wamego-----	Clay Upland (pe30-37)	6,500	4,500	3,500
201CS: Crete-----	Clay Upland (pe26-30)	4,500	4,100	3,700
201CX: Crete, eroded-----	Clay Upland (pe26-30)	4,500	4,100	3,700
201KS: Kipson-----	Limy Upland (pe26-30)	4,500	3,500	2,000
201KS: Sogn-----	Shallow Limy (pe26-30)	3,500	2,500	1,500
201LC: Lancaster-----	Loamy Upland (pe26-30)	5,000	3,500	2,000
Ad: Ivan-----	Loamy Lowland (pe25-34)	10,000	8,000	6,000
AED: Arents, Earthen Dam-----	---	---	---	---
BE: Benfield-----	Loamy Upland (pe25-34)	5,500	4,000	3,000
Bf: Benfield-----	Loamy Upland (pe30-36)	6,000	4,500	3,000
Bf: Florence-----	Loamy Upland (pe30-36)	5,500	4,500	3,500
Bk: Wymore-----	Clay Upland (pe25-34)	4,100	3,600	3,200
Bk: Kennebec-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
BOP: Borrow Pits-----	---	---	---	---
Ca: Carr-----	Sandy Lowland (pe30-36)	6,500	5,500	4,500
Ca: Sarpy-----	Sands (pe30-36)	3,800	3,500	3,000

RANGELAND PRODUCTIVITY--Continued
Riley County, Kansas

(Only the soils that support rangeland vegetation suitable for grazing are rated.) Refer to range site description to determine the percentage allowable of grasses, forbs, and shrubs for the range ecological site.

Map symbol and soil name	Ecological site	Total dry-weight production		
		Favorable year	Average year	Unfavorable year
		Lb/acre	Lb/acre	Lb/acre
Ch: Chase-----	Loamy Lowland (pe30-36)	10,000	8,500	6,000
Cs: Clime----- Sogn-----	Limy Upland (pe30-36) Shallow Limy (pe30-36)	5,000 3,500	3,500 2,500	2,500 1,500
CT: Crete-----	Clay Upland (pe25-34)	4,500	4,100	3,700
Dr: Dwight----- Irwin-----	Clay Pan (pe25-34) Clay Upland (pe25-34)	4,000 5,000	3,000 3,500	2,000 2,000
Dw: Dwight----- Irwin-----	Clay Pan (pe25-34) Clay Upland (pe25-34)	4,000 5,000	3,000 3,500	2,000 2,000
Em: Elmont-----	Loamy Upland (pe30-36)	7,000	5,500	4,000
En: Elmont----- Clime-----	Loamy Upland (pe30-36) Limy Upland (pe30-36)	7,000 5,000	5,500 3,500	4,000 2,500
Eu: Eudora-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
Ga: Geary-----	Loamy Upland (pe30-36)	6,000	4,000	3,000
Ge: Geary-----	Loamy Upland (pe30-36)	6,000	4,000	3,000
Ha: Haynie-----	Loamy Lowland (pe30-36)	5,300	4,900	4,500
HO: Hobbs-----	Loamy Lowland (pe25-34)	4,700	4,200	4,000
Ic: Irwin-----	Clay Upland (pe25-34)	5,000	3,500	2,000
Id: Irwin, eroded-----	Clay Upland (pe25-34)	5,000	3,500	2,000
Ie: Ivan-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
Iv: Ivan----- Kennebec-----	Loamy Lowland (pe30-36) Loamy Lowland (pe30-36)	10,000 10,000	8,000 8,000	6,000 6,000
Ka: Kahola-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
Ke: Kenesaw-----	Loamy Upland (pe30-36)	4,500	4,200	3,800
Kf: Kenesaw-----	Loamy Upland (pe30-36)	4,500	4,200	3,800
KN: Kennebec-----	Loamy Lowland (pe35-42)	10,000	8,000	6,000
M-W: Miscellaneous Water-----	---	---	---	---
Ma: Mayberry-----	Clay Upland (pe30-37)	6,500	4,500	3,500
Mb: Mayberry-----	Clay Upland (pe30-36)	3,700	3,200	2,700
Mu: Muir-----	Loamy Terrace (pe25-34)	7,500	5,500	4,000
QUA: Quarries-----	---	---	---	---
Rd: Reading-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
Re: Reading-----	Loamy Lowland (pe30-36)	10,000	8,000	6,000
Sa: Sarpy-----	Sands (pe30-36)	3,800	3,500	3,000
Sm: Smolan-----	Loamy Upland (pe30-36)	5,500	4,000	3,000
Sn: Smolan-----	Loamy Upland (pe30-36)	5,500	4,000	3,000
So: Smolan, eroded-----	Clay Upland (pe30-36)	5,500	4,000	3,000
St: Clime-----	Limy Upland (pe30-36)	5,000	3,500	2,500
Su: Sutphen-----	Clay Lowland (pe26-30)	7,500	5,500	3,500
Ts: Tully-----	Loamy Upland (pe30-36)	6,000	5,000	3,500
Tt: Tully, eroded-----	Clay Upland (pe25-34)	6,000	5,000	3,500
Tu: Tully-----	Loamy Upland (pe25-34)	6,000	5,000	3,500
Tv: Tully, eroded-----	Clay Upland (pe25-34)	6,000	5,000	3,500
W: Water-----	---	---	---	---
Wm: Wymore-----	Loamy Upland (pe25-34)	4,100	3,600	3,200
Wn: Wymore-----	Loamy Upland (pe25-34)	4,100	3,600	3,200

RANGELAND PRODUCTIVITY--Continued
 Riley County, Kansas

(Only the soils that support rangeland vegetation suitable for grazing are rated.) Refer to range site description to determine the percentage allowable of grasses, forbs, and shrubs for the range ecological site.

Map symbol and soil name	Ecological site	Total dry-weight production		
		Favorable year	Average year	Unfavorable year
		Lb/acre	Lb/acre	Lb/acre
Wo: Wymore, eroded-----	Clay Upland (pe25-34)	4,100	3,600	3,200
Wr: Wymore-----	Loamy Upland (pe25-34)	4,100	3,600	3,200
Ws: Wymore, eroded-----	Clay Upland (pe25-34)	4,100	3,600	3,200

BUILDING SITE DEVELOPMENT
Riley County, Kansas

Building Site Development

Soil properties influence the development of building sites, including the selection of the site, the design of the structure, construction, performance after construction, and maintenance. The following tables show the degree and kind of soil limitations that affect dwellings with and without basements, small commercial buildings, local roads and streets, shallow excavations, and lawns and landscaping.

The ratings in the tables are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect building site development. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Dwellings are single-family houses of three stories or less. For dwellings without basements, the foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of 2 feet or at the depth of maximum frost penetration, whichever is deeper. For dwellings with basements, the foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of about 7 feet. The ratings for dwellings are based on the soil properties that affect the capacity of the soil to support a load without movement and on the properties that affect excavation and construction costs. The properties that affect the load-supporting capacity include depth to a water table, ponding, flooding, subsidence, linear extensibility (shrink-swell potential), and compressibility. Compressibility is inferred from the Unified classification. The properties that affect the ease and amount of excavation include depth to a water table, ponding, flooding, slope, depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, and the amount and size of rock fragments.

Small commercial buildings are structures that are less than three stories high and do not have basements. The foundation is assumed to consist of spread footings of reinforced concrete built on undisturbed soil at a depth of 2 feet or at the depth of maximum frost penetration, whichever is deeper. The ratings are based on the soil properties that affect the capacity of the soil to support a load without movement and on the properties that affect excavation and construction costs. The properties that affect the load-supporting capacity include depth to a water table, ponding, flooding, subsidence, linear extensibility (shrink-swell potential), and compressibility (which is inferred from the Unified classification). The properties that affect the ease and amount of excavation include flooding, depth to a water table, ponding, slope, depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, and the amount and size of rock fragments.

Local roads and streets have an all-weather surface and carry automobile and light truck traffic all year. They have a subgrade of cut or fill soil material; a base of gravel, crushed rock, or soil material stabilized by lime or cement; and a surface of flexible material (asphalt), rigid material (concrete), or gravel with a binder. The ratings are based on the soil properties that affect the ease of excavation and grading and the traffic-supporting capacity. The properties that affect the ease of excavation and grading are depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, depth to a water table, ponding, flooding, the amount of large stones, and slope. The properties that affect the traffic-supporting capacity are soil strength (as inferred from the AASHTO group index number), subsidence, linear extensibility (shrink-swell potential), the potential for frost action, depth to a water table, and ponding.

Shallow excavations are trenches or holes dug to a maximum depth of 5 or 6 feet for graves, utility lines, open ditches, or other purposes. The ratings are based on the soil properties that influence the ease of digging and the resistance to sloughing. Depth to bedrock or a cemented pan, hardness of bedrock or a cemented pan, the amount of large stones, and dense layers influence the ease of digging, filling, and compacting. Depth to the seasonal high water table, flooding, and ponding may restrict the period when excavations can be made. Slope influences the ease of using machinery. Soil texture, depth to the water table, and linear extensibility (shrink-swell potential) influence the resistance to sloughing.

Lawns and landscaping require soils on which turf and ornamental trees and shrubs can be established and maintained. Irrigation is not considered in the ratings. The ratings are based on the soil properties that affect plant growth and trafficability after vegetation is established. The properties that affect plant growth are reaction; depth to a water table; ponding; depth to bedrock or a cemented pan; the available water capacity in the upper 40 inches; the content of salts, sodium, or calcium carbonate; and sulfidic materials. The properties that affect trafficability are flooding, depth to a water table, ponding, slope, stoniness, and the amount of sand, clay, or organic matter in the surface layer.

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
027CS: Crete-----	90	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
027CX: Crete-----	83	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.48
027HN: Hobbs-----	90	Very limited Flooding Shrink-swell	1.00 0.02	Very limited Flooding Shrink-swell	1.00 0.02	Very limited Flooding Shrink-swell	1.00 0.02
027KS: Kipson-----	70	Somewhat limited Depth to soft bedrock Slope Shrink-swell	1.00 0.84 0.50	Very limited Depth to soft bedrock Slope Shrink-swell	1.00 0.84 0.50	Very limited Depth to soft bedrock Slope Shrink-swell	1.00 1.00 0.50
Sogn-----	15	Very limited Depth to hard bedrock Slope Shrink-swell	1.00 0.84 0.50	Very limited Depth to hard bedrock Slope Shrink-swell	1.00 0.84 0.50	Very limited Depth to hard bedrock Slope Shrink-swell	1.00 1.00 0.50
061BE: Benfield-----	42	Very limited Shrink-swell Slope	1.00 1.00	Very limited Shrink-swell Slope Depth to soft bedrock	1.00 1.00 0.01	Very limited Shrink-swell Slope	1.00 1.00
Florence-----	28	Very limited Shrink-swell Slope	1.00 0.16	Very limited Shrink-swell Slope Depth to hard bedrock	1.00 0.16 0.05	Very limited Shrink-swell Slope	1.00 1.00
061CF: Clime-----	60	Very limited Shrink-swell Slope	1.00 0.84	Very limited Shrink-swell Slope Depth to soft bedrock	1.00 0.84 0.46	Very limited Shrink-swell Slope	1.00 1.00
Sogn-----	20	Very limited Depth to hard bedrock Shrink-swell	1.00 0.73	Very limited Depth to hard bedrock Shrink-swell	1.00 0.73	Very limited Depth to hard bedrock Shrink-swell Slope	1.00 0.73 0.12
061CR: Crete-----	90	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
061CS: Crete-----	90	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
061EU: Eudora-----	85	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
061HE: Haynie-----	55	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
061KA: Kahola-----	75	Very limited Flooding Shrink-swell	1.00 0.00	Very limited Flooding Shrink-swell	1.00 0.22	Very limited Flooding Shrink-swell	1.00 0.00
061KB: Kahola-----	75	Very limited Flooding Shrink-swell	1.00 0.00	Very limited Flooding Shrink-swell	1.00 0.22	Very limited Flooding Shrink-swell	1.00 0.00
061RE: Reading-----	85	Very limited Flooding Shrink-swell	1.00 0.82	Very limited Flooding Shrink-swell	1.00 0.82	Very limited Flooding Shrink-swell	1.00 0.82
061TO: Tully-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.48
117PA: Pawnee-----	88	Very limited Shrink-swell Depth to saturated zone	1.00 0.39	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Shrink-swell Depth to saturated zone	1.00 0.39

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
117PB: Pawnee-----	88	Very limited Shrink-swell Depth to saturated zone	1.00 0.39	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Shrink-swell Slope Depth to saturated zone	1.00 0.48 0.39
149HS: Haynie-----	60	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
Sarpy-----	25	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
149PS: Pawnee-----	90	Very limited Flooding Depth to saturated zone	1.00 0.07	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 0.07
149SF: Sarpy-----	90	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
197CM: Clime-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell Depth to soft bedrock	1.00 0.29	Very limited Shrink-swell Slope	1.00 0.12
197FL: Florence-----	40	Very limited Shrink-swell Slope	1.00 0.04	Very limited Shrink-swell Depth to hard bedrock Slope	1.00 0.05 0.04	Very limited Shrink-swell Slope	1.00 1.00
Labette-----	30	Very limited Shrink-swell Depth to hard bedrock	1.00 0.10	Very limited Shrink-swell Depth to hard bedrock	1.00 1.00	Very limited Shrink-swell Depth to hard bedrock Slope	1.00 0.10 0.00
197IB: Irwin-----	80	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
197ID: Irwin-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.12
197IV: Ivan-----	90	Very limited Flooding Shrink-swell	1.00 0.00	Very limited Flooding	1.00	Very limited Flooding Shrink-swell	1.00 0.00
197IX: Ivan-----	80	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50
197PN: Pawnee-----	85	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.12
197WE: Wamego-----	90	Somewhat limited Shrink-swell	0.50	Somewhat limited Depth to soft bedrock Shrink-swell	0.84 0.50	Somewhat limited Shrink-swell Slope	0.50 0.12
201CS: Crete-----	95	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
201CX: Crete, eroded-----	90	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.12

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
201KS: Kipson-----	70	Very limited Depth to soft bedrock Slope Shrink-swell	1.00 1.00 0.50	Very limited Depth to soft bedrock Slope Shrink-swell	1.00 1.00 0.50	Very limited Depth to soft bedrock Slope Shrink-swell	1.00 1.00 0.50
Sogn-----	15	Very limited Depth to hard bedrock Shrink-swell Slope	1.00 0.50 0.16	Very limited Depth to hard bedrock Shrink-swell Slope	1.00 0.50 0.16	Very limited Depth to hard bedrock Slope Shrink-swell	1.00 1.00 0.50
201LC: Lancaster-----	85	Somewhat limited Shrink-swell	0.27	Somewhat limited Depth to soft bedrock Shrink-swell	0.54 0.27	Somewhat limited Shrink-swell Slope	0.27 0.12
Ad: Ivan-----	99	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
BE: Benfield-----	89	Very limited Shrink-swell	1.00	Very limited Shrink-swell Depth to soft bedrock	1.00 0.29	Very limited Shrink-swell Slope	1.00 0.12
Bf: Benfield-----	45	Very limited Shrink-swell Slope	1.00 0.84	Very limited Shrink-swell Slope Depth to soft bedrock	1.00 0.84 0.10	Very limited Shrink-swell Slope	1.00 1.00
Florence-----	30	Very limited Shrink-swell Depth to hard bedrock Slope	1.00 0.46 0.16	Very limited Shrink-swell Depth to hard bedrock Slope	1.00 1.00 0.16	Very limited Shrink-swell Slope Depth to hard bedrock	1.00 1.00 0.46
Bk: Wymore-----	60	Very limited Shrink-swell Slope Depth to saturated zone	1.00 0.96 0.39	Very limited Shrink-swell Depth to saturated zone Slope	1.00 1.00 0.96	Very limited Slope Shrink-swell Depth to saturated zone	1.00 1.00 0.39
Kennebec-----	45	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 0.61 0.50	Very limited Flooding Shrink-swell	1.00 0.50
BOP: Borrow Pits-----	100	Not rated		Not rated		Not rated	
Ca: Carr-----	45	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
Sarpy-----	40	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
Ch: Chase-----	84	Very limited Flooding Shrink-swell	1.00 1.00	Very limited Flooding Shrink-swell Depth to saturated zone	1.00 1.00 0.95	Very limited Flooding Shrink-swell	1.00 1.00
Cs: Clime-----	50	Somewhat limited Slope Shrink-swell	0.84 0.50	Somewhat limited Slope Shrink-swell Depth to soft bedrock	0.84 0.50 0.46	Very limited Slope Shrink-swell	1.00 0.50
Sogn-----	30	Very limited Depth to hard bedrock Shrink-swell	1.00 0.50	Very limited Depth to hard bedrock Shrink-swell	1.00 0.50	Very limited Depth to hard bedrock Slope Shrink-swell	1.00 0.86 0.50

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
CT: Crete-----	83	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.12
Dr: Dwight-----	45	Very limited Shrink-swell	1.00	Very limited Shrink-swell Depth to hard bedrock	1.00 0.42	Very limited Shrink-swell	1.00
Irwin-----	40	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
Dw: Dwight-----	45	Very limited Shrink-swell	1.00	Very limited Shrink-swell Depth to hard bedrock	1.00 0.42	Very limited Shrink-swell	1.00
Irwin-----	40	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
Em: Elmont-----	74	Somewhat limited Shrink-swell	0.92	Somewhat limited Shrink-swell	0.73	Somewhat limited Shrink-swell Slope	0.92 0.48
En: Elmont-----	35	Somewhat limited Shrink-swell Slope	0.92 0.04	Somewhat limited Shrink-swell Slope	0.73 0.04	Very limited Slope Shrink-swell	1.00 0.92
Clime-----	30	Very limited Shrink-swell Slope	1.00 0.16	Very limited Shrink-swell Depth to soft bedrock Slope	1.00 0.42 0.16	Very limited Shrink-swell Slope	1.00 1.00
Eu: Eudora-----	88	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
Ga: Geary-----	90	Somewhat limited Shrink-swell	0.92	Somewhat limited Shrink-swell	0.38	Somewhat limited Shrink-swell	0.92
Ge: Geary-----	100	Somewhat limited Shrink-swell	0.92	Somewhat limited Shrink-swell	0.38	Somewhat limited Shrink-swell Slope	0.92 0.48
Ha: Haynie-----	90	Very limited Flooding	1.00	Very limited Flooding Shrink-swell	1.00 0.62	Very limited Flooding	1.00
HO: Hobbs-----	89	Very limited Flooding Shrink-swell	1.00 0.02	Very limited Flooding Shrink-swell	1.00 0.02	Very limited Flooding Shrink-swell	1.00 0.02
Ic: Irwin-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.48
Id: Irwin, eroded-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.48
Ie: Ivan-----	88	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50	Somewhat limited Shrink-swell	0.50
Iv: Ivan-----	45	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50
Kennebec-----	45	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 0.61 0.50	Very limited Flooding Shrink-swell	1.00 0.50
Ka: Kahola-----	85	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50
Ke: Kenesaw-----	90	Not limited		Not limited		Somewhat limited Slope	0.00

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Kf: Kenesaw-----	85	Somewhat limited Slope	0.00	Somewhat limited Slope	0.00	Very limited Slope	1.00
KN: Kennebec-----	95	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Depth to saturated zone Shrink-swell	1.00 0.82 0.50	Very limited Flooding Shrink-swell	1.00 0.50
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Mayberry-----	95	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Depth to saturated zone Shrink-swell Slope	1.00 1.00 0.00
Mb: Mayberry-----	95	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Depth to saturated zone Shrink-swell	1.00 1.00	Very limited Shrink-swell Depth to saturated zone Slope	1.00 1.00 0.00
Mu: Muir-----	84	Very limited Flooding Shrink-swell	1.00 0.00	Very limited Flooding	1.00	Very limited Flooding Shrink-swell	1.00 0.00
QUA: Quarries-----	100	Not rated		Not rated		Not rated	
Rd: Reading-----	90	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50
Re: Reading-----	90	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50	Very limited Flooding Shrink-swell	1.00 0.50
Sa: Sarpy-----	98	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
Sm: Smolan-----	90	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
Sn: Smolan-----	75	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.48
So: Smolan, eroded-----	80	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.48
St: Clime-----	75	Very limited Slope Shrink-swell	1.00 1.00	Very limited Slope Shrink-swell Depth to soft bedrock	1.00 1.00 0.20	Very limited Slope Shrink-swell	1.00 1.00
Su: Sutphen-----	100	Very limited Flooding Shrink-swell	1.00 1.00	Very limited Flooding Shrink-swell	1.00 1.00	Very limited Flooding Shrink-swell	1.00 1.00
Ts: Tully-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
Tt: Tully, eroded-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00
Tu: Tully-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.48
Tv: Tully, eroded-----	85	Very limited Shrink-swell	1.00	Very limited Shrink-swell	1.00	Very limited Shrink-swell Slope	1.00 0.48

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Dwellings without basements		Dwellings with basements		Small commercial buildings	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
W: Water-----	100	Not rated		Not rated		Not rated	
Wm: Wymore-----	100	Very limited Shrink-swell Depth to saturated zone	1.00 0.39	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Shrink-swell Depth to saturated zone	1.00 0.39
Wn: Wymore-----	90	Very limited Shrink-swell Depth to saturated zone	1.00 0.39	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Shrink-swell Depth to saturated zone	1.00 0.39
Wo: Wymore, eroded-----	90	Very limited Shrink-swell Depth to saturated zone	1.00 0.39	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Shrink-swell Depth to saturated zone	1.00 0.39
Wr: Wymore-----	90	Very limited Shrink-swell Depth to saturated zone	1.00 0.39	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Shrink-swell Slope Depth to saturated zone	1.00 0.48 0.39
Ws: Wymore, eroded-----	90	Very limited Shrink-swell Depth to saturated zone	1.00 0.39	Very limited Shrink-swell Depth to saturated zone	1.00 1.00	Very limited Shrink-swell Slope Depth to saturated zone	1.00 0.48 0.39

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
027CS: Crete-----	90	Very limited Shrink-swell Low strength Frost action	1.00 1.00 0.50	Somewhat limited Too clayey Cutbanks cave	0.12 0.10	Not limited	
027CX: Crete-----	83	Very limited Shrink-swell Low strength Frost action	1.00 1.00 0.50	Somewhat limited Too clayey Cutbanks cave	0.12 0.10	Not limited	
027HN: Hobbs-----	90	Very limited Flooding Low strength Frost action Shrink-swell	1.00 1.00 0.50 0.02	Somewhat limited Flooding Cutbanks cave	0.80 0.10	Very limited Flooding	1.00
027KS: Kipson-----	70	Somewhat limited Depth to soft bedrock Slope Shrink-swell Frost action	1.00 0.84 0.50 0.50	Very limited Depth to soft bedrock Slope Cutbanks cave	1.00 0.84 0.10	Very limited Depth to bedrock Carbonate content Slope Content of large stones Droughty	1.00 1.00 0.84 0.20
Sogn-----	15	Very limited Depth to hard bedrock Slope Shrink-swell Frost action	1.00 0.84 0.50 0.50	Very limited Depth to hard bedrock Slope Cutbanks cave	1.00 0.84 0.10	Very limited Depth to bedrock Droughty Slope Content of large stones	1.00 0.92 0.84 0.00
061BE: Benfield-----	42	Very limited Low strength Shrink-swell Slope	1.00 1.00 1.00	Very limited Slope Too clayey Cutbanks cave Depth to soft bedrock	1.00 0.50 0.10 0.01	Very limited Slope Depth to bedrock	1.00 0.01
Florence-----	28	Very limited Shrink-swell Low strength Slope	1.00 1.00 0.16	Very limited Too clayey Slope Cutbanks cave Depth to hard bedrock	1.00 0.16 0.10 0.05	Somewhat limited Gravel content Droughty Slope Content of large stones	0.54 0.22 0.16 0.00
061CF: Clime-----	60	Very limited Low strength Shrink-swell Slope	1.00 1.00 0.84	Somewhat limited Slope Depth to soft bedrock Too clayey Cutbanks cave	0.84 0.46 0.28 0.10	Somewhat limited Slope Depth to bedrock	0.84 0.46
Sogn-----	20	Very limited Depth to hard bedrock Low strength Shrink-swell Frost action	1.00 1.00 0.73 0.50	Very limited Depth to hard bedrock Cutbanks cave	1.00 0.10	Very limited Depth to bedrock Droughty Content of large stones	1.00 1.00 0.00
061CR: Crete-----	90	Very limited Shrink-swell Low strength	1.00 1.00	Somewhat limited Too clayey Cutbanks cave	0.12 0.10	Not limited	
061CS: Crete-----	90	Very limited Shrink-swell Low strength	1.00 1.00	Somewhat limited Too clayey Cutbanks cave	0.12 0.10	Not limited	
061EU: Eudora-----	85	Very limited Frost action Flooding	1.00 1.00	Somewhat limited Flooding Cutbanks cave	0.60 0.10	Somewhat limited Flooding	0.60
061HE: Haynie-----	55	Very limited Frost action Flooding Low strength	1.00 1.00 0.22	Somewhat limited Flooding Cutbanks cave	0.80 0.10	Very limited Flooding	1.00

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
061KA: Kahola-----	75	Very limited Flooding Low strength Frost action Shrink-swell	1.00 1.00 0.50 0.00	Somewhat limited Flooding Cutbanks cave	0.80 0.10	Very limited Flooding	1.00
061KB: Kahola-----	75	Very limited Flooding Low strength Frost action Shrink-swell	1.00 1.00 0.50 0.00	Somewhat limited Flooding Cutbanks cave	0.60 0.10	Somewhat limited Flooding	0.60
061RE: Reading-----	85	Very limited Low strength Shrink-swell Frost action Flooding	1.00 0.82 0.50 0.40	Somewhat limited Cutbanks cave	0.10	Not limited	
061TO: Tully-----	85	Very limited Shrink-swell Low strength	1.00 1.00	Somewhat limited Too clayey Cutbanks cave	0.24 0.10	Not limited	
117PA: Pawnee-----	88	Very limited Frost action Shrink-swell Depth to saturated zone	1.00 1.00 0.19	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.12 0.10	Somewhat limited Depth to saturated zone	0.19
117PB: Pawnee-----	88	Very limited Frost action Shrink-swell Depth to saturated zone	1.00 1.00 0.19	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.12 0.10	Somewhat limited Depth to saturated zone	0.19
149HS: Haynie-----	60	Very limited Frost action Flooding Low strength	1.00 1.00 1.00	Somewhat limited Flooding Cutbanks cave	0.60 0.10	Somewhat limited Flooding	0.60
Sarpy-----	25	Very limited Flooding	1.00	Very limited Cutbanks cave Flooding	1.00 0.60	Somewhat limited Droughty Flooding	0.69 0.60
149PS: Paxico-----	90	Very limited Frost action Flooding Depth to saturated zone	1.00 1.00 0.03	Very limited Cutbanks cave Depth to saturated zone Flooding	1.00 1.00 0.80	Very limited Flooding Depth to saturated zone	1.00 0.03
149SF: Sarpy-----	90	Very limited Flooding	1.00	Very limited Cutbanks cave Flooding	1.00 0.80	Very limited Flooding Droughty Too sandy	1.00 0.69 0.50
197CM: Clime-----	85	Very limited Shrink-swell Frost action	1.00 0.50	Somewhat limited Too clayey Depth to soft bedrock Cutbanks cave	0.32 0.29 0.10	Somewhat limited Depth to bedrock	0.29
197FL: Florence-----	40	Very limited Shrink-swell Frost action Slope	1.00 0.50 0.04	Very limited Cutbanks cave Too clayey Depth to hard bedrock Slope	1.00 1.00 0.05 0.04	Very limited Gravel content Slope Content of large stones	1.00 0.04 0.00
Labette-----	30	Very limited Shrink-swell Frost action Depth to hard bedrock	1.00 0.50 0.10	Very limited Depth to hard bedrock Too clayey Cutbanks cave	1.00 0.12 0.10	Somewhat limited Depth to bedrock	0.10

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
197IB: Irwin-----	80	Very limited Shrink-swell Frost action	1.00 0.50	Somewhat limited Too clayey Cutbanks cave	0.50 0.10	Not limited	
197ID: Irwin-----	85	Very limited Shrink-swell Low strength Frost action	1.00 1.00 0.50	Somewhat limited Too clayey Cutbanks cave	0.50 0.10	Not limited	
197IV: Ivan-----	90	Very limited Flooding Frost action Shrink-swell	1.00 0.50 0.00	Somewhat limited Flooding Cutbanks cave	0.60 0.10	Somewhat limited Flooding	0.60
197IX: Ivan-----	80	Very limited Flooding Shrink-swell Frost action	1.00 0.50 0.50	Somewhat limited Flooding Cutbanks cave	0.80 0.10	Very limited Flooding	1.00
197PN: Pawnee-----	85	Very limited Frost action Shrink-swell Depth to saturated zone	1.00 1.00 1.00	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.12 0.10	Very limited Depth to saturated zone	1.00
197WE: Wamego-----	90	Very limited Low strength Shrink-swell Frost action	1.00 0.50 0.50	Somewhat limited Depth to soft bedrock Cutbanks cave	0.84 0.10	Somewhat limited Depth to bedrock	0.84
201CS: Crete-----	95	Very limited Shrink-swell Low strength Frost action	1.00 1.00 0.50	Somewhat limited Too clayey Cutbanks cave	0.12 0.10	Not limited	
201CX: Crete, eroded-----	90	Very limited Shrink-swell Frost action	1.00 0.50	Somewhat limited Too clayey Cutbanks cave	0.12 0.10	Not limited	
201KS: Kipson-----	70	Very limited Depth to soft bedrock Slope Shrink-swell Frost action	1.00 1.00 0.50 0.50	Very limited Depth to soft bedrock Slope Cutbanks cave	1.00 1.00 0.10	Very limited Depth to bedrock Slope Carbonate content Content of large stones Droughty	1.00 1.00 0.20 0.18
Sogn-----	15	Very limited Depth to hard bedrock Shrink-swell Frost action Slope	1.00 0.50 0.50 0.16	Very limited Depth to hard bedrock Slope Cutbanks cave	1.00 0.16 0.10	Very limited Depth to bedrock Droughty Slope Content of large stones	1.00 0.35 0.16 0.00
201LC: Lancaster-----	85	Very limited Low strength Frost action Shrink-swell	1.00 0.50 0.27	Somewhat limited Depth to soft bedrock Cutbanks cave	0.54 0.10	Somewhat limited Depth to bedrock	0.54
Ad: Ivan-----	99	Very limited Flooding Low strength Shrink-swell Frost action	1.00 1.00 0.50 0.50	Somewhat limited Flooding Cutbanks cave	0.80 0.10	Very limited Flooding	1.00
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
BE: Benfield-----	89	Very limited Shrink-swell	1.00	Somewhat limited Depth to soft bedrock	0.29	Somewhat limited Depth to bedrock	0.29
		Low strength	1.00	Cutbanks cave	0.10	Content of large stones	0.03
		Frost action	0.50	Too clayey	0.04		
Bf: Benfield-----	45	Very limited Shrink-swell	1.00	Somewhat limited Slope	0.84	Somewhat limited Slope	0.84
		Slope	0.84	Cutbanks cave	0.10	Depth to bedrock	0.10
		Frost action	0.50	Depth to soft bedrock	0.10	Content of large stones	0.03
				Too clayey	0.04		
Florence-----	30	Very limited Shrink-swell	1.00	Very limited Depth to hard bedrock	1.00	Very limited Gravel content	1.00
		Frost action	0.50	Cutbanks cave	1.00	Droughty	0.66
		Depth to hard bedrock	0.46	Too clayey	1.00	Depth to bedrock	0.46
		Slope	0.16	Slope	0.16	Slope	0.16
						Content of large stones	0.00
Bk: Wymore-----	60	Very limited Frost action	1.00	Very limited Depth to saturated zone	1.00	Somewhat limited Slope	0.96
		Shrink-swell	1.00	Slope	0.96	Depth to saturated zone	0.19
		Slope	0.96	Too clayey	0.32		
		Depth to saturated zone	0.19	Cutbanks cave	0.10		
Kennebec-----	45	Very limited Frost action	1.00	Somewhat limited Depth to saturated zone	0.61	Somewhat limited Flooding	0.60
		Flooding	1.00	Flooding	0.60		
		Low strength	1.00	Cutbanks cave	0.10		
		Shrink-swell	0.50				
BOP: Borrow Pits-----	100	Not rated		Not rated		Not rated	
Ca: Carr-----	45	Very limited Flooding	1.00	Somewhat limited Flooding	0.60	Somewhat limited Flooding	0.60
				Cutbanks cave	0.10		
Sarpy-----	40	Very limited Flooding	1.00	Very limited Cutbanks cave	1.00	Somewhat limited Flooding	0.60
				Flooding	0.60	Droughty	0.51
Ch: Chase-----	84	Very limited Shrink-swell	1.00	Somewhat limited Depth to saturated zone	0.95	Not limited	
		Frost action	1.00	Too clayey	0.12		
		Flooding	0.40	Cutbanks cave	0.10		
Cs: Clime-----	50	Somewhat limited Slope	0.84	Somewhat limited Slope	0.84	Somewhat limited Slope	0.84
		Shrink-swell	0.50	Depth to soft bedrock	0.46	Depth to bedrock	0.46
		Frost action	0.50	Too clayey	0.32		
				Cutbanks cave	0.10		
Sogn-----	30	Very limited Depth to hard bedrock	1.00	Very limited Depth to hard bedrock	1.00	Very limited Depth to bedrock	1.00
		Shrink-swell	0.50	Cutbanks cave	0.10	Droughty	1.00
		Frost action	0.50			Content of large stones	0.00
CT: Crete-----	83	Very limited Shrink-swell	1.00	Somewhat limited Too clayey	0.12	Not limited	
		Low strength	1.00	Cutbanks cave	0.10		
		Frost action	0.50				

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Dr: Dwight-----	45	Very limited Shrink-swell	1.00	Somewhat limited Depth to hard bedrock	0.42	Not limited	
		Frost action	0.50	Too clayey Cutbanks cave	0.32 0.10		
Irwin-----	40	Very limited Shrink-swell	1.00	Somewhat limited Too clayey	0.32	Not limited	
		Frost action	0.50	Cutbanks cave	0.10		
Dw: Dwight-----	45	Very limited Shrink-swell	1.00	Somewhat limited Depth to hard bedrock	0.42	Not limited	
		Frost action	0.50	Too clayey Cutbanks cave	0.32 0.10		
Irwin-----	40	Very limited Shrink-swell	1.00	Somewhat limited Too clayey	0.32	Not limited	
		Frost action	0.50	Cutbanks cave	0.10		
Em: Elmont-----	74	Very limited Frost action	1.00	Somewhat limited Cutbanks cave	0.10	Not limited	
		Shrink-swell	0.92				
En: Elmont-----	35	Very limited Frost action	1.00	Somewhat limited Cutbanks cave	0.10	Somewhat limited Slope	0.04
		Shrink-swell	0.92	Slope	0.04		
		Slope	0.04				
Clime-----	30	Very limited Shrink-swell	1.00	Somewhat limited Depth to soft bedrock	0.42	Somewhat limited Depth to bedrock	0.42
		Frost action	0.50	Slope	0.16	Slope	0.16
		Slope	0.16	Cutbanks cave	0.10		
Eu: Eudora-----	88	Very limited Frost action	1.00	Somewhat limited Flooding	0.60	Somewhat limited Flooding	0.60
		Flooding	1.00	Cutbanks cave	0.10		
Ga: Geary-----	90	Very limited Frost action	1.00	Somewhat limited Cutbanks cave	0.10	Not limited	
		Low strength	1.00				
		Shrink-swell	0.92				
Ge: Geary-----	100	Very limited Frost action	1.00	Somewhat limited Cutbanks cave	0.10	Not limited	
		Low strength	1.00				
		Shrink-swell	0.92				
Ha: Haynie-----	90	Very limited Frost action	1.00	Somewhat limited Flooding	0.60	Somewhat limited Flooding	0.60
		Flooding	1.00	Cutbanks cave	0.10		
HO: Hobbs-----	89	Very limited Flooding	1.00	Somewhat limited Flooding	0.60	Somewhat limited Flooding	0.60
		Low strength	1.00	Cutbanks cave	0.10		
		Frost action	0.50				
		Shrink-swell	0.02				
Ic: Irwin-----	85	Very limited Shrink-swell	1.00	Somewhat limited Too clayey	0.32	Not limited	
		Frost action	0.50	Cutbanks cave	0.10		
Id: Irwin, eroded-----	85	Very limited Shrink-swell	1.00	Somewhat limited Too clayey	0.32	Not limited	
		Frost action	0.50	Cutbanks cave	0.10		
Ie: Ivan-----	88	Somewhat limited Shrink-swell	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
		Frost action	0.50				

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Iv: Ivan-----	45	Very limited Flooding Shrink-swell Frost action	1.00 0.50 0.50	Somewhat limited Flooding Cutbanks cave	0.60 0.10	Somewhat limited Flooding	0.60
Kennebec-----	45	Very limited Frost action Flooding Low strength Shrink-swell	1.00 1.00 1.00 0.50	Somewhat limited Depth to saturated zone Flooding Cutbanks cave	0.61 0.60 0.10	Somewhat limited Flooding	0.60
Ka: Kahola-----	85	Somewhat limited Shrink-swell Frost action Flooding	0.50 0.50 0.40	Somewhat limited Cutbanks cave	0.10	Not limited	
Ke: Kenesaw-----	90	Somewhat limited Frost action	0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
Kf: Kenesaw-----	85	Somewhat limited Frost action Slope	0.50 0.00	Somewhat limited Cutbanks cave Slope	0.10 0.00	Somewhat limited Slope	0.00
KN: Kennebec-----	95	Very limited Frost action Flooding Low strength Shrink-swell	1.00 1.00 1.00 0.50	Somewhat limited Depth to saturated zone Flooding Cutbanks cave	0.82 0.60 0.10	Somewhat limited Flooding	0.60
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Mayberry-----	95	Very limited Shrink-swell Frost action Low strength Depth to saturated zone	1.00 1.00 1.00 1.00	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.12 0.10	Very limited Depth to saturated zone	1.00
Mb: Mayberry-----	95	Very limited Shrink-swell Frost action Low strength Depth to saturated zone	1.00 1.00 1.00 1.00	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.12 0.10	Very limited Depth to saturated zone	1.00
Mu: Muir-----	84	Very limited Low strength Frost action Flooding Shrink-swell	1.00 0.50 0.40 0.00	Somewhat limited Cutbanks cave	0.10	Not limited	
QUA: Quarries-----	100	Not rated		Not rated		Not rated	
Rd: Reading-----	90	Very limited Frost action Shrink-swell Flooding	1.00 0.50 0.40	Somewhat limited Cutbanks cave	0.10	Not limited	
Re: Reading-----	90	Very limited Frost action Shrink-swell Flooding	1.00 0.50 0.40	Somewhat limited Cutbanks cave	0.10	Not limited	
Sa: Sarpy-----	98	Very limited Flooding	1.00	Very limited Cutbanks cave Flooding	1.00 0.60	Somewhat limited Droughty Flooding	0.69 0.60
Sm: Smolan-----	90	Very limited Shrink-swell Frost action	1.00 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	

BUILDING SITE DEVELOPMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Local roads and streets		Shallow excavations		Lawns and landscaping	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Sn: Smolan-----	75	Very limited Shrink-swell Frost action	1.00 0.50	Somewhat limited Cutbanks cave	0.10	Not limited	
So: Smolan, eroded-----	80	Very limited Shrink-swell Frost action	1.00 0.50	Somewhat limited Cutbanks cave Too clayey	0.10 0.04	Not limited	
St: Clime-----	75	Very limited Slope Low strength Shrink-swell	1.00 1.00 1.00	Very limited Slope Too clayey Depth to soft bedrock Cutbanks cave	1.00 0.28 0.20 0.10	Very limited Slope Depth to bedrock Content of large stones	1.00 0.20 0.03
Su: Sutphen-----	100	Very limited Flooding Shrink-swell	1.00 1.00	Somewhat limited Flooding Too clayey Cutbanks cave	0.60 0.28 0.10	Very limited Too clayey Flooding	1.00 0.60
Ts: Tully-----	85	Very limited Shrink-swell Low strength	1.00 1.00	Somewhat limited Too clayey Cutbanks cave	0.24 0.10	Not limited	
Tt: Tully, eroded-----	85	Very limited Shrink-swell Frost action	1.00 0.50	Somewhat limited Too clayey Cutbanks cave	0.12 0.10	Not limited	
Tu: Tully-----	85	Very limited Shrink-swell Frost action	1.00 0.50	Somewhat limited Too clayey Cutbanks cave	0.12 0.10	Not limited	
Tv: Tully, eroded-----	85	Very limited Shrink-swell Frost action	1.00 0.50	Somewhat limited Too clayey Cutbanks cave	0.12 0.10	Not limited	
W: Water-----	100	Not rated		Not rated		Not rated	
Wm: Wymore-----	100	Very limited Frost action Shrink-swell Depth to saturated zone	1.00 1.00 0.19	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.32 0.10	Somewhat limited Depth to saturated zone	0.19
Wn: Wymore-----	90	Very limited Frost action Shrink-swell Depth to saturated zone	1.00 1.00 0.19	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.32 0.10	Somewhat limited Depth to saturated zone	0.19
Wo: Wymore, eroded-----	90	Very limited Frost action Shrink-swell Depth to saturated zone	1.00 1.00 0.19	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.32 0.10	Somewhat limited Depth to saturated zone	0.19
Wr: Wymore-----	90	Very limited Frost action Shrink-swell Depth to saturated zone	1.00 1.00 0.19	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.32 0.10	Somewhat limited Depth to saturated zone	0.19
Ws: Wymore, eroded-----	90	Very limited Frost action Shrink-swell Depth to saturated zone	1.00 1.00 0.19	Very limited Depth to saturated zone Too clayey Cutbanks cave	1.00 0.32 0.10	Somewhat limited Depth to saturated zone	0.19

CONSTRUCTION MATERIALS
Riley County, Kansas

Construction Materials

The following tables give information about the soils as potential sources of gravel, sand, topsoil, reclamation material, and roadfill. Normal compaction, minor processing, and other standard construction practices are assumed.

The soils are rated good, fair, or poor as potential sources of topsoil, reclamation material, and roadfill. The features that limit the soils as sources of these materials are specified in the tables. The numerical ratings given after the specified features indicate the degree to which the features limit the soils as sources of topsoil, reclamation material, or roadfill. The lower the number, the greater the limitation.

The soils are rated as a probable or improbable source of sand and gravel. A rating of probable means that the source material is likely to be in or below the soil. The numerical ratings in these columns indicate the degree of probability. The number 0.00 indicates that the soil is an improbable source. A number between 0.00 and 1.00 indicates the degree to which the soil is a probable source of sand or gravel.

Sand and gravel are natural aggregates suitable for commercial use with a minimum of processing. They are used in many kinds of construction. Specifications for each use vary widely. In these tables, only the probability of finding material in suitable quantity is evaluated. The suitability of the material for specific purposes is not evaluated, nor are factors that affect excavation of the material. The properties used to evaluate the soil as a source of sand or gravel are gradation of grain sizes (as indicated by the Unified classification of the soil), the thickness of suitable material, and the content of rock fragments. If the lowest layer of the soil contains sand or gravel, the soil is rated as a probable source regardless of thickness. The assumption is that the sand or gravel layer below the depth of observation exceeds the minimum thickness.

Topsoil is used to cover an area so that vegetation can be established and maintained. The upper 40 inches of a soil is evaluated for use as topsoil. Also evaluated is the reclamation potential of the borrow area. The ratings are based on the soil properties that affect plant growth; the ease of excavating, loading, and spreading the material; and reclamation of the borrow area. Toxic substances, soil reaction, and the properties that are inferred from soil texture, such as available water capacity and fertility, affect plant growth. The ease of excavating, loading, and spreading is affected by rock fragments, slope, depth to a water table, soil texture, and thickness of suitable material. Reclamation of the borrow area is affected by slope, depth to a water table, rock fragments, depth to bedrock or a cemented pan, and toxic material.

The surface layer of most soils is generally preferred for topsoil because of its organic matter content. Organic matter greatly increases the absorption and retention of moisture and nutrients for plant growth.

Reclamation material is used in areas that have been drastically disturbed by surface mining or similar activities. When these areas are reclaimed, layers of soil material or unconsolidated geological material, or both, are replaced in a vertical sequence. The reconstructed soil favors plant growth. The ratings in the table do not apply to quarries and other mined areas that require an offsite source of reconstruction material. The ratings are based on the soil properties that affect erosion and stability of the surface and the productive potential of the reconstructed soil. These properties include the content of sodium, salts, and calcium carbonate; reaction; available water capacity; erodibility; texture; content of rock fragments; and content of organic matter and other features that affect fertility.

Roadfill is soil material that is excavated in one place and used in road embankments in another place. In this table, the soils are rated as a source of roadfill for low embankments, generally less than 6 feet high and less exacting in design than higher embankments.

The ratings are for the whole soil, from the surface to a depth of about 5 feet. It is assumed that soil layers will be mixed when the soil material is excavated and spread.

The ratings are based on the amount of suitable material and on soil properties that affect the ease of excavation and the performance of the material after it is in place. The thickness of the suitable material is a major consideration. The ease of excavation is affected by large stones, depth to a water table, and slope. How well the soil performs in place after it has been compacted and drained is determined by its strength (as inferred from the AASHTO classification of the soil) and linear extensibility (shrink-swell potential).

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
027CS: Crete-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
027CX: Crete-----	83	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
027HN: Hobbs-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
027KS: Kipson-----	70	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Sogn-----	15	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
061BE: Benfield-----	42	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Florence-----	28	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
061CF: Clime-----	60	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Sogn-----	20	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
061CR: Crete-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
061CS: Crete-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
061EU: Eudora-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Fair Thickest layer Bottom layer	0.00 0.07
061HE: Haynie-----	55	Poor Bottom layer Thickest layer	0.00 0.00	Fair Thickest layer Bottom layer	0.00 0.04
061KA: Kahola-----	75	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
061KB: Kahola-----	75	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
061RE: Reading-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
061TO: Tully-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
117PA: Pawnee-----	88	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
117PB: Pawnee-----	88	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
149HS: Haynie-----	60	Poor Bottom layer Thickest layer	0.00 0.00	Fair Bottom layer Thickest layer	0.00 0.03
Sarpy-----	25	Poor Bottom layer Thickest layer	0.00 0.00	Fair Bottom layer Thickest layer	0.50 0.50
149PS: Paxico-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Fair Thickest layer Bottom layer	0.00 0.22
149SF: Sarpy-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Fair Bottom layer Thickest layer	0.50 0.50
197CM: Clime-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
197FL: Florence-----	40	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Labette-----	30	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
197IB: Irwin-----	80	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
197ID: Irwin-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
197IV: Ivan-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
197IX: Ivan-----	80	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
197PN: Pawnee-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
197WE: Wamego-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
201CS: Crete-----	95	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
201CX: Crete, eroded-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
201KS: Kipson-----	70	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Sogn-----	15	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
201LC: Lancaster-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ad: Ivan-----	99	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
AED: Arents, Earthen Dam-	100	Not rated		Not rated	
BE: Benfield-----	89	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Bf: Benfield-----	45	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Florence-----	30	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Bk: Wymore-----	60	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Kennebec-----	45	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
BOP: Borrow Pits-----	100	Not rated		Not rated	
Ca: Carr-----	45	Poor Bottom layer Thickest layer	0.00 0.00	Fair Thickest layer Bottom layer	0.08 0.08
Sarpy-----	40	Poor Bottom layer Thickest layer	0.00 0.00	Good Thickest layer	0.22
Ch: Chase-----	84	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Cs: Clime-----	50	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
Sogn-----	30	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
CT: Crete-----	83	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
Dr: Dwight-----	45	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
Irwin-----	40	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
Dw: Dwight-----	45	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
Irwin-----	40	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
Em: Elmont-----	74	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
En: Elmont-----	35	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
Clime-----	30	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
Eu: Eudora-----	88	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Fair Thickest layer Bottom layer	0.00 0.07 0.00
Ga: Geary-----	90	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
Ge: Geary-----	100	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
Ha: Haynie-----	90	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Fair Bottom layer Thickest layer	0.00 0.00 0.07
HO: Hobbs-----	89	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
Ic: Irwin-----	85	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00
Id: Irwin, eroded-----	85	Poor Bottom layer Thickest layer	0.00 0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00 0.00

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
Ie: Ivan-----	88	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Iv: Ivan-----	45	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Kennebec-----	45	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ka: Kahola-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ke: Kenesaw-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Kf: Kenesaw-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
KN: Kennebec-----	95	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
M-W: Miscellaneous Water-	100	Not rated		Not rated	
Ma: Mayberry-----	95	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Mb: Mayberry-----	95	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Mu: Muir-----	84	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
QUA: Quarries-----	100	Not rated		Not rated	
Rd: Reading-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Re: Reading-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Sa: Sarpy-----	98	Poor Bottom layer Thickest layer	0.00 0.00	Fair Thickest layer Bottom layer	0.36 0.43
Sm: Smolan-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of gravel		Potential source of sand	
		Rating class	Value	Rating class	Value
Sn: Smolan-----	75	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
So: Smolan, eroded-----	80	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
St: Clime-----	75	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Su: Sutphen-----	100	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ts: Tully-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Tt: Tully, eroded-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Tu: Tully-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Tv: Tully, eroded-----	85	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
W: Water-----	100	Not rated		Not rated	
Wm: Wymore-----	100	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Wn: Wymore-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Wo: Wymore, eroded-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Wr: Wymore-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00
Ws: Wymore, eroded-----	90	Poor Bottom layer Thickest layer	0.00 0.00	Poor Bottom layer Thickest layer	0.00 0.00

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
027CS: Crete-----	90	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.50 0.84 0.99	Poor Low strength Shrink-swell	0.00 0.14	Poor Too Clayey	0.00
027CX: Crete-----	83	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.12 0.84 0.99	Poor Low strength Shrink-swell	0.00 0.16	Poor Too Clayey	0.00
027HN: Hobbs-----	90	Fair Low content of organic matter	0.88	Poor Low strength Shrink-swell	0.00 0.99	Good	
027KS: Kipson-----	70	Poor Depth to bedrock Carbonate content Droughty Low content of organic matter Too clayey	0.00 0.00 0.03 0.88 0.92	Poor Depth to bedrock Shrink-swell	0.00 0.87	Poor Depth to bedrock Carbonate content Slope Too Clayey Rock fragments	0.00 0.00 0.16 0.66 0.68
Sogn-----	15	Poor Droughty Depth to bedrock Low content of organic matter Too clayey	0.00 0.00 0.88 0.98	Poor Depth to bedrock Shrink-swell	0.00 0.97	Poor Depth to bedrock Slope Too Clayey	0.00 0.16 0.70
061BE: Benfield-----	42	Poor Too clayey Droughty Depth to bedrock No water erosion limitation	0.00 0.99 0.01 0.99	Poor Depth to bedrock Low strength Shrink-swell Slope	0.00 0.00 0.01 0.82	Poor Too Clayey Slope Rock fragments Depth to bedrock	0.00 0.00 0.50 0.99
Florence-----	28	Poor Too clayey Droughty Cobble content	0.00 0.63 0.79	Poor Shrink-swell Low strength Cobble content Depth to bedrock	0.00 0.00 0.55 0.95	Poor Too Clayey Hard to reclaim Rock fragments Slope	0.00 0.00 0.00 0.84
061CF: Clime-----	60	Poor Too clayey Depth to bedrock Low content of organic matter Droughty Carbonate content	0.00 0.54 0.88 0.89 0.92	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.06	Poor Too Clayey Slope Depth to bedrock Carbonate content	0.00 0.16 0.54 0.92
Sogn-----	20	Poor Droughty Depth to bedrock Too clayey	0.00 0.00 0.98	Poor Depth to bedrock Low strength	0.00 0.00	Poor Depth to bedrock Too Clayey	0.00 0.93
061CR: Crete-----	90	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.12 0.84 0.99	Poor Low strength Shrink-swell	0.00 0.14	Poor Too Clayey	0.00

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
061CS: Crete-----	90	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.50 0.84 0.99	Poor Low strength Shrink-swell	0.00 0.14	Poor Too Clayey	0.00
061EU: Eudora-----	85	Fair Low content of organic matter	0.02	Good		Good	
061HE: Haynie-----	55	Fair Low content of organic matter Water erosion Carbonate content	0.50 0.90 0.97	Fair Low strength	0.78	Fair Carbonate content	0.97
061KA: Kahola-----	75	Good		Poor Low strength Shrink-swell	0.00 0.98	Good	
061KB: Kahola-----	75	Good		Poor Low strength Shrink-swell	0.00 0.98	Good	
061RE: Reading-----	85	Fair Too clayey Too acid	0.92 0.95	Poor Low strength Shrink-swell	0.00 0.80	Fair Too Clayey	0.84
061TO: Tully-----	85	Fair Too clayey No water erosion limitation	0.82 0.99	Poor Low strength Shrink-swell	0.00 0.20	Fair Too Clayey	0.82
117PA: Pawnee-----	88	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.08 0.99	Fair Shrink-swell Depth to saturated zone	0.16 0.53	Poor Too Clayey Depth to saturated zone	0.00 0.53
117PB: Pawnee-----	88	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.08 0.99	Fair Shrink-swell Depth to saturated zone	0.16 0.53	Poor Too Clayey Depth to saturated zone	0.00 0.53
149HS: Haynie-----	60	Fair Low content of organic matter Carbonate content No water erosion limitation	0.08 0.97 0.99	Poor Low strength	0.00	Fair Carbonate content	0.97
Sarpy-----	25	Poor Too sandy Wind erosion Low content of organic matter Droughty	0.00 0.00 0.08 0.35	Good		Poor Too sandy	0.00
149PS: Paxico-----	90	Fair No water erosion limitation	0.99	Fair Depth to saturated zone	0.76	Fair Depth to saturated zone	0.76

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
149SF: Sarpy-----	90	Poor Too sandy Wind erosion Low content of organic matter Droughty	0.00 0.00 0.08 0.35	Good		Poor Too sandy	0.00
197CM: Clime-----	85	Poor Too clayey Droughty Depth to bedrock	0.00 0.68 0.71	Poor Depth to bedrock Shrink-swell	0.00 0.12	Poor Too Clayey Depth to bedrock	0.00 0.71
197FL: Florence-----	40	Poor Too clayey Droughty	0.00 0.93	Fair Shrink-swell Depth to bedrock Cobble content	0.18 0.95 0.99	Poor Too Clayey Rock fragments Hard to reclaim Slope	0.00 0.00 0.00 0.96
Labette-----	30	Poor Too clayey Depth to bedrock Too acid No water erosion limitation	0.00 0.90 0.95 0.99	Poor Depth to bedrock Shrink-swell	0.00 0.12	Poor Rock fragments Too Clayey Depth to bedrock	0.00 0.00 0.90
197IB: Irwin-----	80	Poor Too clayey	0.00	Fair Shrink-swell	0.15	Poor Too Clayey	0.00
197ID: Irwin-----	85	Poor Too clayey Low content of organic matter Sodium content No water erosion limitation	0.00 0.50 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.03	Poor Too Clayey Sodium content	0.00 0.98
197IV: Ivan-----	90	Good		Fair Shrink-swell	0.97	Good	
197IX: Ivan-----	80	Fair Too clayey	0.98	Fair Shrink-swell	0.87	Fair Too Clayey	0.98
197PN: Pawnee-----	85	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.08 0.99	Poor Depth to saturated zone Shrink-swell	0.00 0.17	Poor Too Clayey Depth to saturated zone	0.00 0.00
197WE: Wamego-----	90	Fair Too clayey Depth to bedrock Droughty Water erosion Too acid	0.05 0.16 0.59 0.90 0.95	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.87	Fair Too Clayey Depth to bedrock	0.04 0.16
201CS: Crete-----	95	Poor Too clayey Too acid No water erosion limitation	0.00 0.84 0.99	Poor Low strength Shrink-swell	0.00 0.09	Poor Too Clayey	0.00

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
201CX: Crete, eroded-----	90	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.08 0.84 0.99	Fair Shrink-swell	0.12	Poor Too Clayey	0.00
201KS: Kipson-----	70	Poor Depth to bedrock Carbonate content Droughty	0.00 0.00 0.04	Poor Depth to bedrock Slope Shrink-swell	0.00 0.82 0.87	Poor Depth to bedrock Slope Rock fragments	0.00 0.00 0.68
Sogn-----	15	Poor Depth to bedrock Droughty	0.00 0.01	Poor Depth to bedrock Shrink-swell	0.00 0.87	Poor Depth to bedrock Rock fragments Slope	0.00 0.00 0.84
201LC: Lancaster-----	85	Fair Depth to bedrock Droughty Too acid	0.46 0.89 0.95	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.94	Fair Depth to bedrock	0.46
Ad: Ivan-----	99	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Low strength Shrink-swell	0.00 0.87	Good	
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
BE: Benfield-----	89	Poor Too clayey Depth to bedrock No water erosion limitation Droughty	0.00 0.71 0.99 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.12	Poor Too Clayey Rock fragments Depth to bedrock	0.00 0.28 0.71
Bf: Benfield-----	45	Poor Too clayey Depth to bedrock No water erosion limitation	0.00 0.90 0.99	Poor Depth to bedrock Shrink-swell	0.00 0.12	Poor Too Clayey Slope Rock fragments Depth to bedrock	0.00 0.16 0.28 0.90
Florence-----	30	Poor Too clayey Droughty Low content of organic matter Depth to bedrock	0.00 0.00 0.18 0.54	Poor Depth to bedrock Shrink-swell No cobble limitation	0.00 0.26 0.99	Poor Too Clayey Rock fragments Depth to bedrock Slope	0.00 0.00 0.54 0.84
Bk: Wymore-----	60	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.50 0.95 0.99	Fair Shrink-swell Depth to saturated zone	0.16 0.53	Poor Too Clayey Slope Depth to saturated zone	0.00 0.04 0.53
Kennebec-----	45	Fair Water erosion	0.90	Poor Low strength Shrink-swell	0.00 0.87	Good	
BOP: Borrow Pits-----	100	Not rated		Not rated		Not rated	

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ca: Carr-----	45	Fair Low content of organic matter	0.02	Good		Good	
Sarpy-----	40	Poor Too sandy Wind erosion Low content of organic matter Droughty	0.00 0.00 0.02 0.48	Good		Poor Too sandy	0.00
Ch: Chase-----	84	Poor Too clayey No water erosion limitation	0.00 0.99	Fair Shrink-swell	0.01	Poor Too Clayey	0.00
Cs: Clime-----	50	Poor Too clayey Low content of organic matter Depth to bedrock Droughty	0.00 0.50 0.54 0.92	Poor Depth to bedrock Shrink-swell	0.00 0.87	Poor Too Clayey Slope Depth to bedrock	0.00 0.16 0.54
Sogn-----	30	Poor Droughty Depth to bedrock Too clayey	0.00 0.00 0.98	Poor Depth to bedrock	0.00	Poor Depth to bedrock Too Clayey	0.00 0.93
CT: Crete-----	83	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.12 0.84 0.99	Poor Low strength Shrink-swell	0.00 0.12	Poor Too Clayey	0.00
Dr: Dwight-----	45	Poor Too clayey Low content of organic matter Water erosion Droughty	0.00 0.50 0.90 0.98	Poor Shrink-swell Depth to bedrock	0.00 0.58	Poor Too Clayey	0.00
Irwin-----	40	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.88 0.99	Poor Shrink-swell Depth to bedrock	0.00 0.58	Poor Too Clayey	0.00
Dw: Dwight-----	45	Poor Too clayey Low content of organic matter Water erosion Droughty	0.00 0.50 0.90 0.98	Poor Shrink-swell Depth to bedrock	0.00 0.58	Poor Too Clayey	0.00
Irwin-----	40	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.88 0.99	Poor Shrink-swell Depth to bedrock	0.00 0.58	Poor Too Clayey	0.00
Em: Elmont-----	74	Fair Low content of organic matter Too clayey Water erosion Too acid	0.12 0.82 0.90 0.97	Fair Depth to bedrock Shrink-swell	0.58 0.80	Fair Too Clayey	0.82

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
En: Elmont-----	35	Fair Low content of organic matter Too clayey Water erosion Too acid	0.12 0.82 0.90 0.97	Fair Depth to bedrock Shrink-swell	0.58 0.80	Fair Too Clayey Slope	0.82 0.96
Clime-----	30	Fair Too clayey Low content of organic matter Depth to bedrock	0.02 0.12 0.58	Poor Depth to bedrock Shrink-swell	0.00 0.34	Fair Too Clayey Depth to bedrock Slope	0.01 0.58 0.84
Eu: Eudora-----	88	Fair Low content of organic matter	0.02	Good		Good	
Ga: Geary-----	90	Fair Low content of organic matter Too clayey Water erosion Too acid	0.12 0.82 0.90 0.95	Poor Low strength Shrink-swell	0.00 0.85	Fair Too Clayey	0.59
Ge: Geary-----	100	Fair Low content of organic matter Too clayey Water erosion Too acid	0.12 0.82 0.90 0.95	Poor Low strength Shrink-swell	0.00 0.85	Fair Too Clayey	0.59
Ha: Haynie-----	90	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Low strength	0.00	Good	
HO: Hobbs-----	89	Fair Low content of organic matter	0.88	Poor Low strength Shrink-swell	0.00 0.99	Good	
IC: Irwin-----	85	Poor Too clayey No water erosion limitation	0.00 0.99	Fair Shrink-swell Depth to bedrock	0.14 0.92	Poor Too Clayey	0.00
Id: Irwin, eroded-----	85	Poor Too clayey No water erosion limitation	0.00 0.99	Fair Shrink-swell Depth to bedrock	0.14 0.92	Poor Too Clayey	0.00
Ie: Ivan-----	88	Fair Too clayey	0.92	Fair Shrink-swell	0.87	Fair Too Clayey	0.80
Iv: Ivan-----	45	Fair Too clayey	0.92	Fair Shrink-swell	0.87	Fair Too Clayey	0.80
Kennebec-----	45	Fair Water erosion	0.90	Poor Low strength Shrink-swell	0.00 0.87	Good	
Ka: Kahola-----	85	Good		Fair Shrink-swell	0.87	Good	
Ke: Kenesaw-----	90	Fair Water erosion Low content of organic matter	0.90 0.92	Good		Good	

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Kf: Kenesaw-----	85	Fair Water erosion Low content of organic matter	0.90 0.92	Good		Good	
KN: Kennebec-----	95	Good		Poor Low strength Shrink-swell	0.00 0.87	Good	
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Mayberry-----	95	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.88 0.95 0.99	Poor Low strength Depth to saturated zone Shrink-swell	0.00 0.00 0.01	Poor Too Clayey Depth to saturated zone	0.00 0.00
Mb: Mayberry-----	95	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.88 0.95 0.99	Poor Low strength Depth to saturated zone Shrink-swell	0.00 0.00 0.01	Poor Too Clayey Depth to saturated zone	0.00 0.00
Mu: Muir-----	84	Good		Poor Low strength	0.00	Good	
QUA: Quarries-----	100	Not rated		Not rated		Not rated	
Rd: Reading-----	90	Fair Water erosion Too acid Too clayey	0.90 0.95 0.98	Fair Shrink-swell	0.88	Fair Too Clayey	0.89
Re: Reading-----	90	Fair Water erosion Too acid Too clayey	0.90 0.95 0.98	Fair Shrink-swell	0.89	Fair Too Clayey	0.89
Sa: Sarpy-----	98	Poor Wind erosion Too sandy Low content of organic matter Droughty	0.00 0.01 0.08 0.35	Good		Fair Too sandy	0.01
Sm: Smolan-----	90	Fair Too clayey No water erosion limitation	0.02 0.99	Fair Shrink-swell	0.32	Fair Too Clayey	0.02
Sn: Smolan-----	75	Fair Too clayey No water erosion limitation	0.02 0.99	Fair Shrink-swell	0.32	Fair Too Clayey	0.02
So: Smolan, eroded-----	80	Poor Too clayey No water erosion limitation	0.00 0.99	Fair Shrink-swell	0.22	Poor Too Clayey	0.00

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
St: Clime-----	75	Poor Too clayey Depth to bedrock Low content of organic matter Droughty Carbonate content	0.00 0.79 0.88 0.90 0.92	Poor Depth to bedrock Low strength Slope Shrink-swell	0.00 0.00 0.00 0.04	Poor Slope Too Clayey Depth to bedrock Carbonate content	0.00 0.00 0.79 0.92
Su: Sutphen-----	100	Poor Too clayey	0.00	Fair Shrink-swell	0.12	Poor Too Clayey	0.00
Ts: Tully-----	85	Fair Too clayey No water erosion limitation	0.82 0.99	Poor Low strength Shrink-swell	0.00 0.20	Fair Too Clayey	0.82
Tt: Tully, eroded-----	85	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.82 0.99	Fair Shrink-swell	0.12	Poor Too Clayey Rock fragments	0.00 0.88
Tu: Tully-----	85	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.82 0.99	Fair Shrink-swell	0.12	Poor Too Clayey Rock fragments	0.00 0.88
Tv: Tully, eroded-----	85	Poor Too clayey Low content of organic matter No water erosion limitation	0.00 0.82 0.99	Fair Shrink-swell	0.12	Poor Too Clayey Rock fragments	0.00 0.88
W: Water-----	100	Not rated		Not rated		Not rated	
Wm: Wymore-----	100	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.50 0.95 0.99	Fair Shrink-swell Depth to saturated zone	0.16 0.53	Poor Too Clayey Depth to saturated zone	0.00 0.53
Wn: Wymore-----	90	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.50 0.95 0.99	Fair Shrink-swell Depth to saturated zone	0.16 0.53	Poor Too Clayey Depth to saturated zone	0.00 0.53
Wo: Wymore, eroded-----	90	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.50 0.95 0.99	Fair Shrink-swell Depth to saturated zone	0.12 0.53	Poor Too Clayey Depth to saturated zone	0.00 0.53

CONSTRUCTION MATERIALS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 0.99. The smaller the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Wr: Wymore-----	90	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.50 0.95 0.99	Fair Shrink-swell Depth to saturated zone	0.16 0.53	Poor Too Clayey Depth to saturated zone	0.00 0.53
Ws: Wymore, eroded-----	90	Poor Too clayey Low content of organic matter Too acid No water erosion limitation	0.00 0.50 0.95 0.99	Fair Shrink-swell Depth to saturated zone	0.12 0.53	Poor Too Clayey Depth to saturated zone	0.00 0.53

RECREATIONAL INTERPRETATIONS
Riley County, Kansas

Recreation

The soils of the survey area are rated in the following tables according to limitations that affect their suitability for recreation. The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the recreational uses. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

The ratings in the tables are based on restrictive soil features, such as wetness, slope, and texture of the surface layer. Susceptibility to flooding is considered. Not considered in the ratings, but important in evaluating a site, are the location and accessibility of the area, the size and shape of the area and its scenic quality, vegetation, access to water, potential water impoundment sites, and access to public sewer lines. The capacity of the soil to absorb septic tank effluent and the ability of the soil to support vegetation also are important. Soils that are subject to flooding are limited for recreational uses by the duration and intensity of flooding and the season when flooding occurs. In planning recreational facilities, onsite assessment of the height, duration, intensity, and frequency of flooding is essential.

The information in this table can be supplemented by other information in this survey, for example, interpretations for building site development, construction materials, sanitary facilities, and water management.

Camp areas require site preparation, such as shaping and leveling the tent and parking areas, stabilizing roads and intensively used areas, and installing sanitary facilities and utility lines. Camp areas are subject to heavy foot traffic and some vehicular traffic. The ratings are based on the soil properties that affect the ease of developing camp areas and the performance of the areas after development. Slope, stoniness, and depth to bedrock or a cemented pan are the main concerns affecting the development of camp areas.

The soil properties that affect the performance of the areas after development are those that influence trafficability and promote the growth of vegetation, especially in heavily used areas. For good trafficability, the surface of camp areas should absorb rainfall readily, remain firm under heavy foot traffic, and not be dusty when dry. The soil properties that influence trafficability are texture of the surface layer, depth to a water table, ponding, flooding, permeability, and large stones. The soil properties that affect the growth of plants are depth to bedrock or a cemented pan, permeability, and toxic substances in the soil.

Picnic areas are subject to heavy foot traffic. Most vehicular traffic is confined to access roads and parking areas. The ratings are based on the soil properties that affect the ease of developing picnic areas and that influence trafficability and the growth of vegetation after development. Slope and stoniness are the main concerns affecting the development of picnic areas. For good trafficability, the surface of picnic areas should absorb rainfall readily, remain firm under heavy foot traffic, and not be dusty when dry. The soil properties that influence trafficability are texture of the surface layer, depth to a water table, ponding, flooding, permeability, and large stones. The soil properties that affect the growth of plants are depth to bedrock or a cemented pan, permeability, and toxic substances in the soil.

Playgrounds require soils that are nearly level, are free of stones, and can withstand intensive foot traffic. The ratings are based on the soil properties that affect the ease of developing playgrounds and that influence trafficability and the growth of vegetation after development. Slope and stoniness are the main concerns affecting the development of playgrounds. For good trafficability, the surface of the playgrounds should absorb rainfall readily, remain firm under heavy foot traffic, and not be dusty when dry. The soil properties that influence trafficability are texture of the surface layer, depth to a water table, ponding, flooding, permeability, and large stones. The soil properties that affect the growth of plants are depth to bedrock or a cemented pan, permeability, and toxic substances in the soil.

Paths and trails for hiking and horseback riding should require little or no slope modification through cutting and filling. The ratings are based on the soil properties that affect trafficability and erodibility. These properties are stoniness, depth to a water table, ponding, flooding, slope, and texture of the surface layer.

Golf fairways are subject to heavy foot traffic and some light vehicular traffic. Cutting or filling may be required. Irrigation is not considered in the ratings. The ratings are based on the soil properties that affect plant growth and trafficability after vegetation is established. The properties that affect plant growth are reaction; depth to a water table; ponding; depth to bedrock or a cemented pan; the available water capacity in the upper 40 inches; the content of salts, sodium, or calcium carbonate; and sulfidic materials. The properties that affect trafficability are flooding, depth to a water table, ponding, slope, stoniness, and the amount of sand, clay, or organic matter in the surface layer. The suitability of the soil for traps, tees, roughs, and greens is not considered in the ratings.

RECREATIONAL INTERPRETATIONS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
027CS: Crete-----	90	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability Slope	0.39 0.00
027CX: Crete-----	83	Somewhat limited Restricted permeability	0.41	Somewhat limited Restricted permeability	0.41	Very limited Slope Restricted permeability	1.00 0.41
027HN: Hobbs-----	90	Very limited Flooding	1.00	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
027KS: Kipson-----	70	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Slope Content of large stones Gravel content	1.00 1.00 0.20 0.08
Sogn-----	15	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Slope Content of large stones	1.00 1.00 0.00
061BE: Benfield-----	42	Very limited Slope Restricted permeability	1.00 0.39	Very limited Slope Restricted permeability	1.00 0.39	Very limited Slope Restricted permeability Depth to bedrock	1.00 0.39 0.01
Florence-----	28	Somewhat limited Gravel content Slope	0.54 0.16	Somewhat limited Gravel content Slope	0.54 0.16	Very limited Slope Gravel content Content of large stones	1.00 1.00 0.00
061CF: Clime-----	60	Somewhat limited Slope Restricted permeability	0.84 0.39	Somewhat limited Slope Restricted permeability	0.84 0.39	Very limited Slope Depth to bedrock Restricted permeability	1.00 0.46 0.39
Sogn-----	20	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Slope Content of large stones	1.00 0.87 0.00
061CR: Crete-----	90	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39
061CS: Crete-----	90	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability Slope	0.39 0.13
061EU: Eudora-----	85	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
061HE: Haynie-----	55	Very limited Flooding	1.00	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
061KA: Kahola-----	75	Very limited Flooding	1.00	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
061KB: Kahola-----	75	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
061RE: Reading-----	85	Very limited Flooding Restricted permeability	1.00 0.15	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability	0.15
061TO: Tully-----	85	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Very limited Slope Restricted permeability	1.00 0.39

RECREATIONAL INTERPRETATIONS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
117PA: Pawnee-----	88	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.39	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.19	Somewhat limited Restricted permeability Depth to saturated zone Slope	0.94 0.39 0.13
117PB: Pawnee-----	88	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.39	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.19	Very limited Slope Restricted permeability Depth to saturated zone	1.00 0.94 0.39
149HS: Haynie-----	60	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
Sarpy-----	25	Very limited Flooding Too sandy	1.00 0.88	Somewhat limited Too sandy	0.88	Somewhat limited Too sandy Flooding Slope	0.88 0.60 0.00
149PS: Paxico-----	90	Very limited Flooding Depth to saturated zone	1.00 0.07	Somewhat limited Flooding Depth to saturated zone	0.40 0.03	Very limited Flooding Depth to saturated zone	1.00 0.07
149SF: Sarpy-----	90	Very limited Flooding Too sandy	1.00 0.88	Somewhat limited Too sandy Flooding	0.88 0.40	Very limited Flooding Too sandy	1.00 0.88
197CM: Clime-----	85	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Somewhat limited Slope Restricted permeability Depth to bedrock	0.87 0.39 0.29
197FL: Florence-----	40	Very limited Gravel content Slope	1.00 0.04	Very limited Gravel content Slope	1.00 0.04	Very limited Gravel content Slope Content of large stones	1.00 1.00 0.00
Labette-----	30	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Somewhat limited Slope Restricted permeability Depth to bedrock	0.50 0.39 0.10
197IB: Irwin-----	80	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability Slope	0.45 0.00
197ID: Irwin-----	85	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability	0.45	Somewhat limited Slope Restricted permeability	0.87 0.45
197IV: Ivan-----	90	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
197IX: Ivan-----	80	Very limited Flooding	1.00	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
197PN: Pawnee-----	85	Very limited Depth to saturated zone Restricted permeability	1.00 0.94	Very limited Depth to saturated zone Restricted permeability	1.00 0.94	Very limited Depth to saturated zone Restricted permeability Slope	1.00 0.94 0.87
197WE: Wamego-----	90	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability Slope Depth to bedrock	0.94 0.87 0.84
201CS: Crete-----	95	Somewhat limited		Somewhat limited		Somewhat limited	

RECREATIONAL INTERPRETATIONS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
201CX: Crete, eroded-----	90	Restricted permeability	0.39	Restricted permeability	0.39	Restricted permeability Slope	0.39 0.00
		Somewhat limited Restricted permeability	0.05	Somewhat limited Restricted permeability	0.05	Somewhat limited Slope Restricted permeability	0.87 0.05
201KS: Kipson-----	70	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to bedrock Slope Content of large stones Gravel content	1.00 1.00 0.20 0.08
		Very limited Depth to bedrock Slope	1.00 0.16	Very limited Depth to bedrock Slope	1.00 0.16	Very limited Depth to bedrock Slope Content of large stones	1.00 1.00 0.00
Sogn-----	15	Very limited Depth to bedrock Slope	1.00 0.16	Very limited Depth to bedrock Slope	1.00 0.16	Very limited Depth to bedrock Slope Content of large stones	1.00 1.00 0.00
201LC: Lancaster-----	85	Not limited		Not limited		Somewhat limited Slope Depth to bedrock	0.87 0.54
Ad: Ivan-----	99	Very limited Flooding	1.00	Somewhat limited Flooding	0.40	Very limited Flooding Slope	1.00 0.00
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
BE: Benfield-----	89	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Somewhat limited Slope Restricted permeability Depth to bedrock Content of large stones	0.87 0.39 0.29 0.03
		Somewhat limited Slope Restricted permeability	0.84 0.39	Somewhat limited Slope Restricted permeability	0.84 0.39	Very limited Slope Restricted permeability Depth to bedrock Content of large stones	1.00 0.39 0.10 0.03
Bf: Benfield-----	45	Somewhat limited Slope Restricted permeability	0.84 0.39	Somewhat limited Slope Restricted permeability	0.84 0.39	Very limited Slope Restricted permeability Depth to bedrock Content of large stones	1.00 0.39 0.10 0.03
Florence-----	30	Very limited Gravel content Slope	1.00 0.16	Very limited Gravel content Slope	1.00 0.16	Very limited Gravel content Slope Depth to bedrock Content of large stones	1.00 1.00 0.46 0.00
Bk: Wymore-----	60	Somewhat limited Slope Restricted permeability Depth to saturated zone	0.96 0.94 0.39	Somewhat limited Slope Restricted permeability Depth to saturated zone	0.96 0.94 0.19	Very limited Slope Restricted permeability Depth to saturated zone	1.00 0.94 0.39
		Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
BOP: Borrow Pits-----	100	Not rated		Not rated		Not rated	
Ca: Carr-----	45	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
Sarpy-----	40	Very limited Flooding Too sandy	1.00 0.49	Somewhat limited Too sandy	0.49	Somewhat limited Flooding Too sandy	0.60 0.49
Ch: Chase-----	84	Very limited Flooding	1.00	Somewhat limited Restricted permeability	0.94	Somewhat limited Restricted permeability	0.94
		Restricted permeability	0.94				

RECREATIONAL INTERPRETATIONS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Cs: Clime-----	50	Somewhat limited Slope Restricted permeability	0.84 0.39	Somewhat limited Slope Restricted permeability	0.84 0.39	Very limited Slope Depth to bedrock Restricted permeability	1.00 0.46 0.39
Sogn-----	30	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Slope Content of large stones	1.00 1.00 0.00
CT: Crete-----	83	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Somewhat limited Slope Restricted permeability	0.87 0.39
Dr: Dwight-----	45	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability Slope	0.45 0.00
Irwin-----	40	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability Slope	0.45 0.13
Dw: Dwight-----	45	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability Slope	0.45 0.00
Irwin-----	40	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability Slope	0.45 0.13
Em: Elmont-----	74	Somewhat limited Restricted permeability	0.15	Somewhat limited Restricted permeability	0.15	Very limited Slope Restricted permeability	1.00 0.15
En: Elmont-----	35	Somewhat limited Restricted permeability Slope	0.15 0.04	Somewhat limited Restricted permeability Slope	0.15 0.04	Very limited Slope Restricted permeability	1.00 0.15
Clime-----	30	Somewhat limited Restricted permeability Slope	0.39 0.16	Somewhat limited Restricted permeability Slope	0.39 0.16	Very limited Slope Depth to bedrock Restricted permeability	1.00 0.42 0.39
Eu: Eudora-----	88	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
Ga: Geary-----	90	Not limited		Not limited		Somewhat limited Slope	0.13
Ge: Geary-----	100	Not limited		Not limited		Very limited Slope	1.00
Ha: Haynie-----	90	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
HO: Hobbs-----	89	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
Ic: Irwin-----	85	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability	0.45	Very limited Slope Restricted permeability	1.00 0.45
Id: Irwin, eroded-----	85	Somewhat limited Restricted permeability	0.45	Somewhat limited Restricted permeability	0.45	Very limited Slope Restricted permeability	1.00 0.45

RECREATIONAL INTERPRETATIONS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ie: Ivan-----	88	Not limited		Not limited		Somewhat limited Slope	0.00
Iv: Ivan-----	45	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
Kennebec-----	45	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
Ka: Kahola-----	85	Very limited Flooding	1.00	Not limited		Not limited	
Ke: Kenesaw-----	90	Not limited		Not limited		Somewhat limited Slope	0.50
Kf: Kenesaw-----	85	Somewhat limited Slope	0.00	Somewhat limited Slope	0.00	Very limited Slope	1.00
KN: Kennebec-----	95	Very limited Flooding	1.00	Not limited		Somewhat limited Flooding	0.60
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Mayberry-----	95	Very limited Depth to saturated zone Restricted permeability	1.00 0.94	Very limited Depth to saturated zone Restricted permeability	1.00 0.94	Very limited Depth to saturated zone Restricted permeability Slope	1.00 0.94 0.50
Mb: Mayberry-----	95	Very limited Depth to saturated zone Restricted permeability	1.00 0.94	Very limited Depth to saturated zone Restricted permeability	1.00 0.94	Very limited Depth to saturated zone Restricted permeability Slope	1.00 0.94 0.50
Mu: Muir-----	84	Very limited Flooding	1.00	Not limited		Not limited	
QUA: Quarries-----	100	Not rated		Not rated		Not rated	
Rd: Reading-----	90	Very limited Flooding	1.00	Not limited		Not limited	
Re: Reading-----	90	Very limited Flooding	1.00	Not limited		Somewhat limited Slope	0.00
Sa: Sarpy-----	98	Very limited Flooding Too sandy	1.00 0.76	Somewhat limited Too sandy	0.76	Somewhat limited Too sandy Flooding Slope	0.76 0.60 0.00
Sm: Smolan-----	90	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability Slope	0.39 0.13
Sn: Smolan-----	75	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Very limited Slope Restricted permeability	1.00 0.39
So: Smolan, eroded-----	80	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Very limited Slope Restricted permeability	1.00 0.39
St: Clime-----	75	Very limited Slope Restricted permeability Too Stony	1.00 0.39 0.00	Very limited Slope Restricted permeability Too Stony	1.00 0.39 0.00	Very limited Slope Restricted permeability Depth to bedrock Content of large stones Gravel content	1.00 0.39 0.20 0.03 0.00

RECREATIONAL INTERPRETATIONS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Camp areas		Picnic areas		Playgrounds	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Su: Sutphen-----	100	Very limited Flooding Too clayey Restricted permeability	1.00 0.50 0.45	Somewhat limited Too clayey Restricted permeability	0.50 0.45	Somewhat limited Flooding Too clayey Restricted permeability	0.60 0.50 0.45
Ts: Tully-----	85	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability Slope	0.39 0.13
Tt: Tully, eroded-----	85	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability Slope Gravel content	0.39 0.13 0.06
Tu: Tully-----	85	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Very limited Slope Restricted permeability Gravel content	1.00 0.39 0.06
Tv: Tully, eroded-----	85	Somewhat limited Restricted permeability	0.39	Somewhat limited Restricted permeability	0.39	Very limited Slope Restricted permeability Gravel content	1.00 0.39 0.06
W: Water-----	100	Not rated		Not rated		Not rated	
Wm: Wymore-----	100	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.39	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.19	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.39
Wn: Wymore-----	90	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.39	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.19	Somewhat limited Restricted permeability Depth to saturated zone Slope	0.94 0.39 0.13
Wo: Wymore, eroded-----	90	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.39	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.19	Somewhat limited Restricted permeability Depth to saturated zone Slope	0.94 0.39 0.13
Wr: Wymore-----	90	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.39	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.19	Very limited Slope Restricted permeability Depth to saturated zone	1.00 0.94 0.39
Ws: Wymore, eroded-----	90	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.39	Somewhat limited Restricted permeability Depth to saturated zone	0.94 0.19	Very limited Slope Restricted permeability Depth to saturated zone	1.00 0.94 0.39

RECREATIONAL INTERPRETATIONS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Paths and trails		Golf fairways	
		Rating class and limiting features	Value	Rating class and limiting features	Value
027CS: Crete-----	90	Not limited		Not limited	
027CX: Crete-----	83	Not limited		Not limited	
027HN: Hobbs-----	90	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
027KS: Kipson-----	70	Not limited		Very limited Depth to bedrock Carbonate content Slope Content of large stones Droughty	1.00 1.00 0.84 0.20 0.20
Sogn-----	15	Not limited		Very limited Depth to bedrock Droughty Slope Content of large stones	1.00 0.92 0.84 0.00
061BE: Benfield-----	42	Somewhat limited Slope	0.18	Very limited Slope Depth to bedrock	1.00 0.01
Florence-----	28	Not limited		Somewhat limited Gravel content Droughty Slope Content of large stones	0.54 0.22 0.16 0.00
061CF: Clime-----	60	Not limited		Somewhat limited Slope Depth to bedrock	0.84 0.46
Sogn-----	20	Not limited		Very limited Depth to bedrock Droughty Content of large stones	1.00 1.00 0.00
061CR: Crete-----	90	Not limited		Not limited	
061CS: Crete-----	90	Not limited		Not limited	
061EU: Eudora-----	85	Not limited		Somewhat limited Flooding	0.60
061HE: Haynie-----	55	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
061KA: Kahola-----	75	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
061KB: Kahola-----	75	Not limited		Somewhat limited Flooding	0.60
061RE: Reading-----	85	Not limited		Not limited	
061TO: Tully-----	85	Not limited		Not limited	
117PA: Pawnee-----	88	Not limited		Somewhat limited Depth to saturated zone	0.19
117PB: Pawnee-----	88	Not limited		Somewhat limited Depth to saturated zone	0.19
149HS: Haynie-----	60	Not limited		Somewhat limited Flooding	0.60
Sarpy-----	25	Somewhat limited Too sandy	0.88	Somewhat limited Droughty Flooding	0.69 0.60
149PS: Paxico-----	90	Somewhat limited Flooding	0.40	Very limited Flooding Depth to saturated zone	1.00 0.03
149SF: Sarpy-----	90	Somewhat limited		Very limited	

RECREATIONAL INTERPRETATIONS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Paths and trails		Golf fairways	
		Rating class and limiting features	Value	Rating class and limiting features	Value
		Too sandy	0.88	Flooding	1.00
		Flooding	0.40	Droughty	0.69
				Too sandy	0.50
197CM: Clime-----	85	Not limited		Somewhat limited Depth to bedrock	0.29
197FL: Florence-----	40	Not limited		Very limited Gravel content	1.00
				Slope	0.04
				Content of large stones	0.00
Labette-----	30	Not limited		Somewhat limited Depth to bedrock	0.10
197IB: Irwin-----	80	Not limited		Not limited	
197ID: Irwin-----	85	Not limited		Not limited	
197IV: Ivan-----	90	Not limited		Somewhat limited Flooding	0.60
197IX: Ivan-----	80	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
197PN: Pawnee-----	85	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
197WE: Wamego-----	90	Not limited		Somewhat limited Depth to bedrock	0.84
201CS: Crete-----	95	Not limited		Not limited	
201CX: Crete, eroded-----	90	Not limited		Not limited	
201KS: Kipson-----	70	Somewhat limited Slope	0.18	Very limited Depth to bedrock	1.00
				Slope	1.00
				Carbonate content	1.00
				Content of large stones	0.20
				Droughty	0.18
Sogn-----	15	Not limited		Very limited Depth to bedrock	1.00
				Droughty	0.35
				Slope	0.16
				Content of large stones	0.00
201LC: Lancaster-----	85	Not limited		Somewhat limited Depth to bedrock	0.54
Ad: Ivan-----	99	Somewhat limited Flooding	0.40	Very limited Flooding	1.00
AED: Arents, Earthen Dam-	100	Not rated		Not rated	
BE: Benfield-----	89	Not limited		Somewhat limited Depth to bedrock	0.29
				Content of large stones	0.03
Bf: Benfield-----	45	Not limited		Somewhat limited Slope	0.84
				Depth to bedrock	0.10
				Content of large stones	0.03
Florence-----	30	Not limited		Very limited Gravel content	1.00
				Droughty	0.66
				Depth to bedrock	0.46
				Slope	0.16
				Content of large stones	0.00
Bk: Wymore-----	60	Not limited		Somewhat limited Slope	0.96

RECREATIONAL INTERPRETATIONS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Paths and trails		Golf fairways	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Kennebec-----	45	Not limited		Depth to saturated zone	0.19
BOP:				Somewhat limited Flooding	0.60
Borrow Pits-----	100	Not rated		Not rated	
Ca:					
Carr-----	45	Not limited		Somewhat limited Flooding	0.60
Sarpy-----	40	Somewhat limited Too sandy	0.49	Somewhat limited Flooding Droughty	0.60 0.51
Ch:					
Chase-----	84	Not limited		Not limited	
Cs:					
Clime-----	50	Not limited		Somewhat limited Slope	0.84
				Depth to bedrock	0.46
Sogn-----	30	Not limited		Very limited Depth to bedrock Droughty	1.00 1.00
				Content of large stones	0.00
CT:					
Crete-----	83	Not limited		Not limited	
Dr:					
Dwight-----	45	Not limited		Not limited	
Irwin-----	40	Not limited		Not limited	
Dw:					
Dwight-----	45	Not limited		Not limited	
Irwin-----	40	Not limited		Not limited	
Em:					
Elmont-----	74	Not limited		Not limited	
En:					
Elmont-----	35	Not limited		Somewhat limited Slope	0.04
				Somewhat limited Depth to bedrock Slope	0.42 0.16
Clime-----	30	Not limited			
Eu:					
Eudora-----	88	Not limited		Somewhat limited Flooding	0.60
Ga:					
Geary-----	90	Not limited		Not limited	
Ge:					
Geary-----	100	Not limited		Not limited	
Ha:					
Haynie-----	90	Not limited		Somewhat limited Flooding	0.60
HO:					
Hobbs-----	89	Not limited		Somewhat limited Flooding	0.60
Ic:					
Irwin-----	85	Not limited		Not limited	
Id:					
Irwin, eroded-----	85	Not limited		Not limited	
Ie:					
Ivan-----	88	Not limited		Not limited	
Iv:					
Ivan-----	45	Not limited		Somewhat limited Flooding	0.60
				Somewhat limited Flooding	0.60
Kennebec-----	45	Not limited			
Ka:					
Kahola-----	85	Not limited		Not limited	
Ke:					
Kenesaw-----	90	Not limited		Not limited	
Kf:					
Kenesaw-----	85	Not limited		Somewhat limited Slope	0.00
KN:					
Kennebec-----	95	Not limited		Somewhat limited Flooding	0.60
M-W:					
Miscellaneous Water-	100	Not rated		Not rated	
Ma:					
Mayberry-----	95	Very limited		Very limited	

RECREATIONAL INTERPRETATIONS--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Paths and trails		Golf fairways	
		Rating class and limiting features	Value	Rating class and limiting features	Value
		Depth to saturated zone	1.00	Depth to saturated zone	1.00
Mb: Mayberry-----	95	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
Mu: Muir-----	84	Not limited		Not limited	
QUA: Quarries-----	100	Not rated		Not rated	
Rd: Reading-----	90	Not limited		Not limited	
Re: Reading-----	90	Not limited		Not limited	
Sa: Sarpy-----	98	Somewhat limited Too sandy	0.76	Somewhat limited Droughty Flooding	0.69 0.60
Sm: Smolan-----	90	Not limited		Not limited	
Sn: Smolan-----	75	Not limited		Not limited	
So: Smolan, eroded----	80	Not limited		Not limited	
St: Clime-----	75	Very limited Slope Too Stony	1.00 0.00	Very limited Slope Depth to bedrock Content of large stones	1.00 0.20 0.03
Su: Sutphen-----	100	Somewhat limited Too clayey	0.50	Very limited Too clayey Flooding	1.00 0.60
Ts: Tully-----	85	Not limited		Not limited	
Tt: Tully, eroded-----	85	Not limited		Not limited	
Tu: Tully-----	85	Not limited		Not limited	
Tv: Tully, eroded-----	85	Not limited		Not limited	
W: Water-----	100	Not rated		Not rated	
Wm: Wymore-----	100	Not limited		Somewhat limited Depth to saturated zone	0.19
Wn: Wymore-----	90	Not limited		Somewhat limited Depth to saturated zone	0.19
Wo: Wymore, eroded----	90	Not limited		Somewhat limited Depth to saturated zone	0.19
Wr: Wymore-----	90	Not limited		Somewhat limited Depth to saturated zone	0.19
Ws: Wymore, eroded----	90	Not limited		Somewhat limited Depth to saturated zone	0.19

WILDLIFE INTERPRETATIONS
Riley County, Kansas

Use and Explanation of Wildlife Interpretations

Soils directly affect the kind and amount of vegetation that is available to wildlife as food and cover. They also affect the development of water impoundments. The kind and abundance of wildlife that populate an area depend largely on the amount and distribution of food, cover, water, and living space. If any one of these elements is missing, inadequate, or inaccessible, wildlife will be scarce or will not inhabit the area. If the soils have the potential, wildlife habitat can be created or improved by planting appropriate vegetation, properly managing the existing plant cover, and fostering the natural establishment of desirable plants.

In the Wildlife Interpretations table, the soils in the survey area are rated according to their potential for providing habitat for various kinds of wildlife. This information can be used in planning parks, wildlife refuges, nature study areas, and other developments for wildlife; in selecting soils that are suitable for establishing, improving, or maintaining specific elements of wildlife habitat; and in determining the intensity of management needed for each element of the habitat.

Suitability Ratings

The potential of the soil is rated good, fair, poor, or very poor.

Good - means that the element of wildlife habitat or the kind of habitat is easily created, improved, or maintained. Few or no limitations affect management, and satisfactory results can be expected if the soil is used for the designated purpose.

Fair - means that the element of wildlife habitat or kind of habitat can be created, improved, or maintained in most places. Moderately intensive management is required for satisfactory results.

Poor - means that limitations are severe for the designated element or kind of wildlife habitat. Habitat can be created, improved, or maintained in most places, but management is difficult and requires intensive effort.

Very Poor - means that limitations are very severe for the designated element or kind of wildlife habitat. Habitat is difficult to create, improve, or maintain in most places, and management is difficult and requires intensive effort.

Description of Wildlife Habitat Elements

Openland habitat consists of croplands, pastures, meadows, and areas that are overgrown with grasses, herbs, shrubs, and vines. These areas produce grain and seed crops, grasses and legumes, and wild herbaceous plants. The kind of wildlife attracted to these areas include bobwhite quail, pheasant, meadowlark, field sparrow, killdeer, cottontail rabbit, red fox, and coyote.

Woodland habitat consists of hardwood or conifers, or a mixture of these and associated grasses, legumes and wild herbaceous plants. Examples of wildlife attracted to this habitat are wild turkey, thrushes, woodpeckers, owl, tree squirrels, raccoon, and deer.

Wetland habitat consists of water-tolerant plants in open, marshy or swampy, shallow water areas. Examples of wildlife attracted to this habitat are ducks, geese, herons, bitterns, rails, kingfishers, shorebirds, muskrat, mink, and beaver.

The elements of wildlife habitat are described in the following paragraphs.

Grain and seed crops are domestic grains and seed-producing herbaceous plants. Soil properties and features that affect the growth of grain and seed crops are depth of the root zone, texture of the surface layer, available water capacity, wetness, slope, surface stoniness, and flooding. Soil temperature and soil moisture also are considerations. Examples of grain and seed crops are corn, wheat, oats, and barley.

Grasses and legumes are domestic perennial grasses and herbaceous legumes. Soil properties and features that affect the growth of grasses and legumes are depth of the root zone, texture of the surface layer, available water capacity, wetness, surface stoniness, flooding, and slope. Soil temperature and soil moisture also are considerations. Examples of grasses and legumes are fescue, lovegrass, bromegrass, clover, and alfalfa.

Wild herbaceous plants are native or naturally established grasses and forbs, including weeds. Soil properties and features that affect the growth of these plants are depth of the root zone, texture of the surface layer, available water capacity, wetness, surface stoniness, and flooding. Soil temperature and soil moisture also are considerations. Examples of wild herbaceous plants are bluestem, goldenrod, beggarweed, wheatgrass, and grama.

Hardwood trees and woody understory produce nuts or other fruit, buds, catkins, twigs, bark, and foliage. Soil properties and features that affect the growth of hardwood trees and shrubs are depth of the root zone, available water capacity, and wetness. Examples of these plants are oak, poplar, cherry, sweetgum, apple, hawthorn, dogwood, hickory, blackberry, and blueberry. Examples of fruit-producing shrubs that are suitable for planting on soils rated good are Russian-olive, autumn-olive, and crabapple.

Coniferous plants furnish browse and seeds. Soil properties and features that affect the growth of coniferous trees, shrubs, and ground cover are depth of the root zone, available water capacity, and wetness. Examples of coniferous plants are pine, spruce, fir, cedar, and juniper.

Shrubs are bushy woody plants that produce fruit, buds, twigs, bark, and foliage. Soil properties and features that affect the growth of shrubs are depth of the root zone, available water capacity, salinity, and soil moisture. Examples of shrubs are fragrant sumac, chokecherry, American plum, sand plum, and garden currant.

Wetland plants are annual and perennial wild herbaceous plants that grow on moist or wet sites. Submerged or floating aquatic plants are excluded. Soil properties and features affecting wetland plants are texture of the surface layer, wetness, reaction, salinity, slope, and surface stoniness. Examples of wetland plants are smartweed, wild millet, saltgrass, cordgrass, rushes, sedges, and cattails.

Shallow water areas have an average depth of less than 5 feet. Some are naturally wet areas. Others are created by dams, levees, or other water-control structures. Soil properties and features affecting shallow water areas are depth to bedrock, wetness, surface stoniness, slope, and permeability. Examples of shallow water areas are marshes, waterfowl feeding areas, and ponds.

The habitat for various kinds of wildlife is described in the following paragraphs.

Habitat for openland wildlife consists of cropland, pasture, meadows, and areas that are overgrown with grasses, herbs, shrubs, and vines. These areas produce grain and seed crops, grasses and legumes, and wild herbaceous plants. Wildlife attracted to these areas include bobwhite quail, pheasant, meadowlark, field sparrow, cottontail, red fox and coyote.

Habitat for woodland wildlife consists of areas of deciduous and/or coniferous plants and associated grasses, legumes, and wild herbaceous plants. Wildlife attracted to these areas include wild turkey, thrushes, woodpeckers, squirrels, gray fox, raccoon, and deer.

Habitat for wetland wildlife consists of open, marshy or swampy shallow water areas. Some of the wildlife attracted to such areas are ducks, geese, herons, shore birds, muskrat, mink, and beaver.

Habitat for rangeland wildlife consists of areas of shrubs and wild herbaceous plants. Wildlife attracted to rangeland include antelope, deer, cottontail rabbit, prairie chicken, meadowlark, quail, and pheasant.

WILDLIFE INTERPRETATIONS
Riley County, Kansas

Map symbol and soil name	Potential for habitat elements								Potential as habitat for--			
	Grain and seed crops	Grasses and legumes	Wild herba- ceous plants	Hard- wood trees	Conif- erous plants	Shrubs	Wetland plants	Shallow water areas	Open- land wild- life	Wood- land wild- life	Wetland wild- life	Range- land wild- life
027CS: CRETE-----	Good	Good	Good	Fair	Fair	Fair	Very poor	Very poor	Good	Fair	Very poor	Good
027CX: CRETE-----	Fair	Good	Good	Fair	Fair	Fair	Very poor	Very poor	Fair	Fair	Very poor	Good
027HN: HOBBS-----	Poor	Fair	Fair	Fair	Fair	Fair	Very poor	Very poor	Fair	Fair	Very poor	Fair
027KS: KIPSON-----	Poor	Fair	Fair	---	---	Poor	Very poor	Very poor	Fair	---	Very poor	Poor
SOGN-----	Very poor	Very poor	Poor	---	---	Poor	Very poor	Very poor	Very poor	---	Very poor	Poor
061BE: BENFIELD-----	Poor	Fair	Fair	---	---	Fair	Very poor	Very poor	Fair	---	Very poor	Fair
FLORENCE-----	Poor	Good	Fair	---	---	Fair	Poor	Very poor	Fair	---	Very poor	Fair
061CF: CLIME-----	Fair	Fair	Good	---	---	Fair	Very poor	Very poor	Fair	---	Very poor	Fair
SOGN-----	Very poor	Very poor	Poor	---	---	Poor	Very poor	Very poor	Very poor	---	Very poor	Poor
061CR: CRETE-----	Good	Good	Good	Fair	Fair	Fair	Very poor	Very poor	Good	Fair	Very poor	Good
061CS: CRETE-----	Good	Good	Good	Fair	Fair	Fair	Very poor	Very poor	Good	Fair	Very poor	Good
061EU: EUDORA-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	Good
061HE: HAYNIE-----	Fair	Fair	Fair	Fair	Poor	---	Poor	Poor	Fair	Fair	Poor	---
061KA: KAHOLA-----	Poor	Fair	Fair	Good	Good	Good	Poor	Fair	Fair	Good	Poor	Good
061KB: KAHOLA-----	Good	Good	Good	Good	Good	Good	Poor	Fair	Good	Good	Poor	Good
061RE: READING-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	---
061TO: TULLY-----	Fair	Good	Good	---	---	Fair	Poor	Poor	Fair	---	Poor	Fair
117PA: PAWNEE-----	Fair	Good	Good	---	Fair	Fair	Very poor	Poor	Good	---	Poor	Fair
117PB: PAWNEE-----	Fair	Good	Good	---	Fair	Fair	Very poor	Poor	Good	---	Poor	Fair
149HS: HAYNIE-----	Good	Good	Good	Good	Good	---	Poor	Poor	Good	Good	Poor	---
SARPY-----	Poor	Poor	Fair	Poor	Poor	---	Very poor	Very poor	Poor	Poor	Very poor	---
149PS: PAXICO-----	Poor	Fair	Fair	Good	Good	---	Good	Good	Fair	Good	Fair	---
149SF: SARPY-----	Poor	Poor	Fair	Poor	Poor	---	Very poor	Very poor	Poor	Poor	Very poor	---
197CM: CLIME-----	Fair	Fair	Good	Fair	Fair	Fair	Very poor	Very poor	Fair	Fair	Very poor	Fair

WILDLIFE INTERPRETATIONS--Continued
Riley County, Kansas

Map symbol and soil name	Potential for habitat elements								Potential as habitat for--			
	Grain and seed crops	Grasses and legumes	Wild herba- ceous plants	Hard- wood trees	Conif- erous plants	Shrubs	Wetland plants	Shallow water areas	Open- land wild- life	Wood- land wild- life	Wetland wild- life	Range- land wild- life
197FL: FLORENCE-----	Poor	Good	Fair	---	---	Fair	Poor	Very poor	Fair	---	Very poor	Fair
LABETTE-----	Fair	Good	Fair	---	---	Fair	Poor	Poor	Fair	---	Poor	Fair
197IB: IRWIN-----	Good	Good	Good	---	---	Fair	Poor	Poor	Good	---	Poor	Fair
197ID: IRWIN-----	Fair	Good	Good	Good	Good	Fair	Poor	Poor	Fair	Good	Poor	Fair
197IV: IVAN-----	Good	Good	Good	Good	Good	Good	Poor	Fair	Good	Good	Poor	Good
197IX: IVAN-----	Poor	Fair	Fair	Good	Good	Good	Poor	Fair	Fair	Good	Poor	Good
197PN: PAWNEE-----	Fair	Good	Good	---	Fair	Fair	Very poor	Poor	Good	---	Poor	Fair
197WE: WAMEGO-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Good	Good	Very poor	Good
201CS: CRETE-----	Good	Good	Good	Fair	Fair	Fair	Very poor	Very poor	Good	Fair	Very poor	Good
201CX: CRETE-----	Fair	Good	Good	Fair	Fair	Fair	Very poor	Very poor	Fair	Fair	Very poor	Good
201KS: KIPSON-----	Poor	Fair	Fair	---	---	Poor	Very poor	Very poor	Fair	---	Very poor	Poor
SOGN-----	Very poor	Very poor	Poor	---	---	Poor	Very poor	Very poor	Very poor	---	Very poor	Poor
201LC: LANCASTER-----	Fair	Good	Fair	---	---	Fair	Very poor	Very poor	Fair	---	Very poor	Fair
Ad: IVAN-----	Poor	Fair	Fair	Good	Good	Good	Poor	Fair	Fair	Good	Poor	Good
AED: ARENTS, EARTHEN DAM-----	---	---	---	---	---	---	---	---	---	---	---	---
BE: BENFIELD-----	Fair	Good	Fair	---	---	Fair	Very poor	Very poor	Fair	---	Very poor	Fair
Bf: BENFIELD-----	Poor	Fair	Fair	---	---	Fair	Very poor	Very poor	Fair	---	Very poor	Fair
FLORENCE-----	Poor	Good	Fair	---	---	Fair	Poor	Very poor	Fair	---	Very poor	Fair
Bk: WYMORE-----	Poor	Good	Fair	Fair	Fair	Fair	Very poor	---	---	---	---	---
KENNEBEC-----	Good	Good	Good	Good	Good	---	Poor	Poor	Good	Good	Poor	---
BOP: BORROW PITS-----	---	---	---	---	---	---	---	---	---	---	---	---
Ca: CARR-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	---
SARPY-----	Poor	Poor	Fair	Poor	Poor	---	Very poor	Very poor	Poor	Poor	Very poor	---
Ch: CHASE-----	Good	Good	Good	Good	Good	Good	Good	Fair	Good	Good	Fair	---
Cs: CLIME-----	Fair	Fair	Good	---	---	Fair	Very poor	Very poor	Fair	---	Very poor	Fair

WILDLIFE INTERPRETATIONS--Continued
Riley County, Kansas

Map symbol and soil name	Potential for habitat elements								Potential as habitat for--			
	Grain and seed crops	Grasses and legumes	Wild herba- ceous plants	Hard- wood trees	Conif- erous plants	Shrubs	Wetland plants	Shallow water areas	Open- land wild- life	Wood- land wild- life	Wetland wild- life	Range- land wild- life
SOGN-----	Very poor	Very poor	Poor	---	---	Poor	Very poor	Very poor	Very poor	---	Very poor	Poor
CT: CRETE-----	Fair	Good	Good	Fair	Fair	Fair	Very poor	Very poor	Fair	Fair	Very poor	Good
Dr: DWIGHT-----	Fair	Fair	Fair	---	---	Fair	Poor	Fair	Fair	---	Poor	Fair
IRWIN-----	Good	Good	Good	---	---	Fair	Poor	Poor	Good	---	Poor	Fair
Dw: DWIGHT-----	Fair	Fair	Fair	---	---	Fair	Poor	Fair	Fair	---	Poor	Fair
IRWIN-----	Good	Good	Good	---	---	Fair	Poor	Poor	Good	---	Poor	Fair
Em: ELMONT-----	Fair	Good	Good	Fair	Fair	Good	Poor	Very poor	Good	Fair	Very poor	Good
En: ELMONT-----	Fair	Good	Good	Fair	Fair	Good	Poor	Very poor	Good	Fair	Very poor	Good
CLIME-----	Fair	Fair	Good	---	---	Fair	Very poor	Very poor	Fair	---	Very poor	Fair
Eu: EUDORA-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	Good
Ga: GEARY-----	Good	Good	Good	Fair	Fair	Fair	Poor	Poor	Good	Fair	Poor	Good
Ge: GEARY-----	Fair	Good	Good	Fair	Fair	Fair	Very poor	Very poor	Good	Fair	Very poor	Good
Ha: HAYNIE-----	Good	Good	Good	Good	Good	---	Poor	Poor	Good	Good	Poor	---
HO: HOBBS-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	Good
Ic: IRWIN-----	Fair	Good	Good	---	---	Fair	Poor	Poor	Fair	---	Poor	Fair
Id: IRWIN-----	Fair	Good	Good	---	---	Fair	Poor	Poor	Fair	---	Poor	Fair
Ie: IVAN-----	Good	Good	Good	Good	Good	Good	Poor	Fair	Good	Good	Poor	Good
Iv: IVAN-----	Good	Good	Good	Good	Good	Good	Poor	Fair	Good	Good	Poor	Good
KENNEBEC-----	Good	Good	Good	Good	Good	---	Poor	Poor	Good	Good	Poor	---
Ka: KAHOLA-----	Good	Good	Good	Good	Good	Good	Poor	Fair	Good	Good	Poor	---
Ke: KENESAW-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Fair	Good	Very poor	Good
Kf: KENESAW-----	Fair	Good	Good	Good	Good	Good	Very poor	Very poor	Fair	Good	Very poor	Good
KN: KENNEBEC-----	Good	Good	Good	Good	Good	---	Poor	Poor	Good	Good	Poor	---
M-W: MISCELLANEOUS WATER-----	---	---	---	---	---	---	---	---	---	---	---	---
Ma: MAYBERRY-----	Fair	Good	Good	Fair	Fair	Good	Very poor	Very poor	Good	Fair	Very poor	Good
Mb: MAYBERRY-----	Fair	Good	Fair	---	Fair	Fair	Very poor	Very poor	Fair	---	Very poor	Fair

WILDLIFE INTERPRETATIONS--Continued
Riley County, Kansas

Map symbol and soil name	Potential for habitat elements								Potential as habitat for--			
	Grain and seed crops	Grasses and legumes	Wild herba- ceous plants	Hard- wood trees	Conif- erous plants	Shrubs	Wetland plants	Shallow water areas	Open- land wild- life	Wood- land wild- life	Wetland wild- life	Range- land wild- life
Mu: MUIR-----	Good	Good	Good	Good	Good	Good	Poor	Very poor	Good	Good	Very poor	Good
QUA: QUARRIES-----	---	---	---	---	---	---	---	---	---	---	---	---
Rd: READING-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	---
Re: READING-----	Good	Good	Good	Good	Good	Good	Poor	Poor	Good	Good	Poor	---
Sa: SARPY-----	Poor	Poor	Fair	Poor	Poor	---	Very poor	Very poor	Poor	Poor	Very poor	---
Sm: SMOLAN-----	Good	Good	Fair	---	---	Fair	Poor	Fair	Good	---	Poor	Fair
Sn: SMOLAN-----	Fair	Good	Fair	---	---	Fair	Very poor	Very poor	Fair	---	Very poor	Fair
So: SMOLAN-----	Fair	Good	Fair	---	---	Fair	Very poor	Very poor	Fair	---	Very poor	Fair
St: CLIME-----	Poor	Fair	Fair	---	---	Poor	---	Poor	Fair	---	Very poor	Fair
Su: SUTPHEN-----	Fair	Fair	Fair	Fair	Fair	Fair	Poor	Good	Fair	Fair	Fair	---
Ts: TULLY-----	Good	Good	Good	---	---	Fair	Poor	Poor	Good	---	Poor	Fair
Tt: TULLY-----	Good	Good	Good	---	---	Fair	Poor	Poor	Good	---	Poor	Fair
Tu: TULLY-----	Fair	Good	Good	---	---	Fair	Poor	Poor	Fair	---	Poor	Fair
Tv: TULLY-----	Fair	Good	Good	---	---	Fair	Poor	Poor	Fair	---	Poor	Fair
W: WATER-----	---	---	---	---	---	---	---	---	---	---	---	---
Wm: WYMORE-----	Good	Good	Fair	Good	Good	Fair	Poor	Very poor	Good	Good	Very poor	Fair
Wn: WYMORE-----	Fair	Good	Fair	Good	Good	Fair	Very poor	Very poor	Fair	Good	Very poor	Fair
Wo: WYMORE-----	Fair	Good	Fair	Good	Good	Fair	Very poor	Very poor	Fair	Good	Very poor	Fair
Wr: WYMORE-----	Fair	Good	Fair	Good	Good	Fair	Very poor	Very poor	Fair	Good	Very poor	Fair
Ws: WYMORE-----	Fair	Good	Fair	Good	Good	Fair	Very poor	Very poor	Fair	Good	Very poor	Fair

YIELDS PER ACRE OF PASTURE AND HAYLAND
Riley County, Kansas

Use and Explanation of Pastureland and Hayland Interpretations

This subsection provides information concerning the suitability of soils for the production of pasture and hayland. This subsection may contain pasture and hayland suitability groupings, land capability and yield estimates, yield estimates for individual grasses or legumes, or other information pertaining to the production of forage.

Pasture and Hayland Suitability Groupings

Soils are placed in pasture and hayland groups according to their suitability for the production of forage. The soils in each group are enough alike to be suited to the same grasses or legumes, to have similar limitations and hazards, to require similar management, and to have similar productivity and other responses to management. Thus, the pasture and hayland suitability group is a convenient way of grouping the soils for their management. If used, these groupings are identified and described in other reports in the subsection.

Yield Estimates

The average yields per acre that can be expected of the principal pasture or hayland crops, under a high level of management, are presented in this subsection. In any given year, yields may be higher or lower than those indicated in the tables because of variations in rainfall or other climatic factors. The yields are based mainly on the experience and records of farmers, conservationists, and extension agents. Available yield data from nearby counties and results of field trials and demonstrations are also considered.

Under good management, proper grazing is essential for the production of high quality forage, stand survival, and erosion control. Proper grazing helps plants maintain sufficient and generally vigorous top growth during the growing season. Brush control is essential in many areas, and weed control generally is needed. Rotation grazing and renovation are also important management practices.

The Pasture and Hayland table show yield estimates in tons per acre and animal unit months for pasture and hayland groups. An animal unit month is the amount of forage required by one animal unit (AU) for 30 days. One animal unit (AU) is one (1000 pound) mature cow and a calf up to weaning age (usually six months of age) or their equivalent. The Natural Resources Conservation Service uses 900 pounds of air dry forage as the amount needed to meet this requirement. To maintain a healthy and vigorous plant community, the degree of use should never be greater than 50 percent. Therefore only 25 percent of the total biomass grown is considered consumed by the grazing animal. Animal Unit Months can be converted to air dry pounds per acre production by multiplying the AUM by 30 days, then by 30 pounds per day, and then by four. This figure is the amount of total forage production.

Planners of management systems for individual fields or farms should consider the detailed information given in the description of each soil in the Nontechnical Description section. Specific information on plants and yields can be obtained from the local office of the Natural Resources Conservation Service or the Cooperative Extension Service.

(Yields in the "N" columns are for nonirrigated soils; those in the "I" columns are for irrigated soils. Yields are those that can be expected under a high level of nonirrigated and irrigated management by component. Absence of a yield indicates that the soil is not suited to the crop or the crop generally is not grown on the soil)
Animal-unit-month: The amount of forage or feed required to feed one animal unit (one cow, one horse, one mule, five sheep, or five goats) for 30 days.

Map symbol and soil name	Land capability		Alfalfa hay		Smooth brome grass	
	N	I	N	I	N	I
			Tons	Tons	AUM	AUM
027CS: Crete-----	2e	---	---	---	---	---
027CX: Crete-----	4e	---	---	---	---	---
027HN: Hobbs-----	5w	---	---	---	---	---
027KS: Kipson-----	6e	---	---	---	---	---
Sogn-----	6e	---	---	---	---	---
061BE: Benfield-----	6e	---	---	---	---	---
Florence-----	6e	---	---	---	---	---
061CF: Clime-----	6e	---	---	---	---	---
Sogn-----	6s	---	---	---	---	---
061CR: Crete-----	2s	---	---	---	---	---
061CS: Crete-----	2e	---	---	---	---	---
061EU: Eudora-----	2w	---	---	---	---	---
061HE: Haynie-----	5w	---	---	---	---	---
061KA: Kahola-----	5w	---	---	---	---	---
061KB: Kahola-----	2w	---	---	---	---	---
061RE: Reading-----	1	---	---	---	---	---
061TO: Tully-----	3e	---	---	---	---	---
117PA: Pawnee-----	2e	---	---	---	---	---
117PB: Pawnee-----	3e	---	---	---	---	---
149HS: Haynie-----	3w	---	---	---	---	---
Sarpy-----	3w	---	---	---	---	---
149PS: Paxico-----	5w	---	---	---	---	---
149SF: Sarpy-----	4s	---	---	---	---	---
197CM: Clime-----	4e	---	3.50	---	3.10	---
197FL: Florence-----	6e	---	---	---	---	---
Labette-----	6e	---	---	---	---	---
197IB: Irwin-----	3e	---	---	---	---	---
197ID: Irwin-----	4e	---	---	---	---	---

(Yields in the "N" columns are for nonirrigated soils; those in the "I" columns are for irrigated soils. Yields are those that can be expected under a high level of nonirrigated and irrigated management by component. Absence of a yield indicates that the soil is not suited to the crop or the crop generally is not grown on the soil)
Animal-unit-month: The amount of forage or feed required to feed one animal unit (one cow, one horse, one mule, five sheep, or five goats) for 30 days.

Map symbol and soil name	Land capability		Alfalfa hay		Smooth brome grass	
	N	I	N	I	N	I
			Tons	Tons	AUM	AUM
197IV: Ivan-----	2w	---	---	---	---	---
197IX: Ivan-----	5w	---	5.60	---	5.00	---
197PN: Pawnee-----	3e	---	3.50	4.80	---	---
197WE: Wamego-----	4e	---	3.90	---	5.00	---
201CS: Crete-----	2e	---	---	---	---	---
201CX: Crete, eroded-----	4e	---	---	---	---	---
201KS: Kipson-----	6e	---	---	---	---	---
Sogn-----	6e	---	---	---	---	---
201LC: Lancaster-----	4e	---	---	---	---	---
Ad: Ivan-----	5w	---	---	---	---	---
AED: Arents, Earthen Dam-----	8	---	---	---	---	---
BE: Benfield-----	4e	---	---	---	---	---
Bf: Benfield-----	6e	---	---	---	---	---
Florence-----	6e	---	---	---	---	---
Bk: Wymore-----	6e	---	---	---	---	---
Kennebec-----	1	---	---	---	---	---
BOP: Borrow Pits-----	---	---	---	---	---	---
Ca: Carr-----	3w	---	---	---	---	---
Sarpy-----	3w	---	---	---	---	---
Ch: Chase-----	2w	---	---	---	---	---
Cs: Clime-----	6e	---	---	---	---	---
Sogn-----	6e	---	---	---	---	---
CT: Crete-----	3e	---	---	---	---	---
Dr: Dwight-----	4e	---	---	---	---	---
Irwin-----	4e	---	---	---	---	---
Dw: Dwight-----	4e	---	---	---	---	---
Irwin-----	4e	---	---	---	---	---
Em: Elmont-----	3e	---	---	---	---	---
En: Elmont-----	6e	---	---	---	---	---

(Yields in the "N" columns are for nonirrigated soils; those in the "I" columns are for irrigated soils. Yields are those that can be expected under a high level of nonirrigated and irrigated management by component. Absence of a yield indicates that the soil is not suited to the crop or the crop generally is not grown on the soil)
Animal-unit-month: The amount of forage or feed required to feed one animal unit (one cow, one horse, one mule, five sheep, or five goats) for 30 days.

Map symbol and soil name	Land capability		Alfalfa hay		Smooth bromegrass	
	N	I	N	I	N	I
			Tons	Tons	AUM	AUM
Clime-----	6e	---	---	---	---	---
Eu: Eudora-----	2w	---	---	---	---	---
Ga: Geary-----	2e	---	---	---	---	---
Ge: Geary-----	3e	---	---	---	---	---
Ha: Haynie-----	1	---	---	---	---	---
HO: Hobbs-----	2w	---	---	---	---	---
Ic: Irwin-----	4e	---	---	---	---	---
Id: Irwin, eroded-----	4e	---	---	---	---	---
Ie: Ivan-----	2e	---	---	---	---	---
Iv: Ivan-----	2w	---	---	---	---	---
Kennebec-----	1	---	---	---	---	---
Ka: Kahola-----	1	---	---	---	---	---
Ke: Kenesaw-----	3e	---	---	---	---	---
Kf: Kenesaw-----	4e	---	---	---	---	---
KN: Kennebec-----	2w	---	---	---	7.10	---
M-W: Miscellaneous Water-----	---	---	---	---	---	---
Ma: Mayberry-----	3e	---	4.50	---	4.30	---
Mb: Mayberry-----	3e	---	---	---	---	---
Mu: Muir-----	1	---	---	---	---	---
QUA: Quarries-----	---	---	---	---	---	---
Rd: Reading-----	1	---	---	---	---	---
Re: Reading-----	2e	---	---	---	---	---
Sa: Sarpy-----	4s	---	---	---	---	---
Sm: Smolan-----	2e	---	---	---	---	---
Sn: Smolan-----	3e	---	---	---	---	---
So: Smolan, eroded-----	4e	---	---	---	---	---
St: Clime-----	7e	---	---	---	---	---

(Yields in the "N" columns are for nonirrigated soils; those in the "I" columns are for irrigated soils. Yields are those that can be expected under a high level of nonirrigated and irrigated management by component. Absence of a yield indicates that the soil is not suited to the crop or the crop generally is not grown on the soil)
Animal-unit-month: The amount of forage or feed required to feed one animal unit (one cow, one horse, one mule, five sheep, or five goats) for 30 days.

Map symbol and soil name	Land capability		Alfalfa hay		Smooth bromegrass	
	N	I	N	I	N	I
			Tons	Tons	AUM	AUM
Su: Sutphen-----	3w	---	---	---	---	---
Ts: Tully-----	2e	---	---	---	---	---
Tt: Tully, eroded-----	3e	---	---	---	---	---
Tu: Tully-----	3e	---	---	---	---	---
Tv: Tully, eroded-----	4e	---	---	---	---	---
W: Water-----	---	---	---	---	---	---
Wm: Wymore-----	2s	---	---	---	---	---
Wn: Wymore-----	2e	---	---	---	---	---
Wo: Wymore, eroded-----	3e	---	---	---	---	---
Wr: Wymore-----	3e	---	---	---	---	---
Ws: Wymore, eroded-----	4e	---	---	---	---	---

CONSERVATION TREE AND SHRUB MANAGEMENT
Riley County, Kansas

A Conservation Tree/Shrub Suitability Group (CTSG), formerly Windbreak Suitability Group, is a physiographic unit or area having similar climatic and edaphic characteristics that control the selection and height growth of trees and shrubs.

In this table, the Conservation Tree and Shrub Grouping is expressed as a group index number. The group index for Conservation Tree and Shrub groups (CTSG) are a guide for species best suited for different kinds of soil and for prediction height, growth, and effectiveness. The groupings can be used when selection woody plants for windbreaks, wildlife plantings riparian buffers, reforestation, other environmental plantings, recreation, landscaping, wetland restoration or enhancement and critical area plantings. CTSG's are developed to assure satisfactory species selection and adaptation to specific conditions of soil, climate and physiography. CTSG's are a guide for selection species best suited for different kinds of soil and prediction height growth and effectiveness.

All soil series mapped in the state have been placed in 10 groups of similar soil characteristics. Groups 1, 2, 3, 4, 6, and 9 are further divided into subgroups. In addition, all groups provide information by Major Land Resource Areas.

Each tree or shrub species has certain climatic and physiographic limits. Within these parameters a tree or shrub may be well or poorly suited because of soil characteristics. Each tree or shrub also has definable potentials of height growth depending on the factors just mentioned. Accurate definitions of potential heights are necessary for proper windbreak planning and design.

Windbreaks protect livestock, buildings, roads and yards from wind and snow. They also protect fruit trees and gardens, and they furnish habitat for wildlife. Several rows of low-growing and high-growing broadleaf and coniferous trees and shrubs provide the most protection.

Field windbreaks are narrow plantings made at right angles to the prevailing wind and at specific intervals across the field. The interval depends on the erodibility of the soil. Field windbreaks protect cropland and crops from wind, help to keep snow on the fields, and provide food and cover for wildlife.

Environmental plantings help to beautify and screen houses and other buildings and to abate noise. The plants, mostly evergreen shrubs and trees, are closely spaced. To ensure plant survival, a healthy planting stock of suitable species should be planted properly on a well prepared site and maintained in good condition.

Windbreaks are often planted on land that did not grow trees originally. Knowledge of how trees perform on such land can be gained only by observing and recording their performance where trees have been planted and survived. The problem is compounded by the fact that many favorite windbreak species are not indigenous to the areas in which they are planted.

The Kansas Field Office Technical Guide Notice KS-230, Conservation Tree and Shrub Plantings Suitability Groups shows the adapted species listing for each group index number. Showing the height that locally grown trees and shrubs are expected to reach in 20 years on various soils. The estimates are based on measurements and observation of established plantings that have been given adequate care. This information should be used to determine the placement of a windbreak, the area protected and the arrangement of species.

A number of attributes are included in the CTSG species tables for each group number found in this section of the Field Office Technical Guide. These attributes were rated subjectively and assigned a relative value to further assist those unfamiliar with individual species characteristics or desirability for the intended use. Definitions and explanations can be found. Additional information on planning windbreaks and screens and planting and caring for trees and shrubs can be obtained from the local office of the Natural Resources Conservation Service or of the Cooperative Extension Service or from a commercial nursery. See part 537 of the National Forestry Manual for additional information.

In the Tree and Shrub Management table interpretive ratings are given for various aspects of forest and conservation tree and shrub management. Some rating class terms indicate the degree to which the soils are suited to a specified forest management practice. Well suited indicates that the soil has features that are favorable for the specified practice and has no limitations. Good performance can be expected, and little or no maintenance is needed. Moderately well suited indicates that the soil has features that are moderately favorable for the specified practice. One or more soil properties are less than desirable and fair performance can be expected. Some maintenance is needed. Poorly suited indicates that the soil has one or more properties that are unfavorable for the specified practice. Overcoming the unfavorable properties requires special design, extra maintenance, and costly alteration. Unsited indicates that the expected performance of the soil is unacceptable for the specified practice or that extreme measures are needed to overcome the undesirable soil properties.

The paragraphs that follow indicate the soil properties considered in rating the soils for forest and conservation tree and shrub management practices. More detailed information about the criteria used in the ratings is available in the "National Forestry Manual," which is available in local offices of the Natural Resources Conservation Service or on the Internet. Also, in the Kansas Field Office Technical Guide Notice KS-230, Conservation Tree and Shrub Plantings Suitability Groups.

Ratings in the columns suitability for hand planting and suitability for mechanical planting are based on slope, depth to a restrictive layer, content of sand, plasticity index, rock fragments on or below the surface, depth to a water table, and ponding. The soils are described as well suited, moderately well suited, poorly suited, or unsited to these methods of planting. It is assumed that necessary site preparation is completed before seedlings are planted.

Ratings in the column suitability for mechanical site preparation (surface) are based on slope, depth to a restrictive layer, plasticity index, rock fragments on or below the surface, depth to a water table, and ponding. The soils are described as well suited, poorly suited, or unsited to this management activity. The part of the soil from the surface to a depth of about 1-foot is considered in the ratings.

Ratings in the column suitability for mechanical site preparation (deep) are based on slope, depth to a restrictive layer, rock fragments on or below the surface, depth to a water table, and ponding. The soils are described as well suited, poorly suited, or unsited to this management activity. The part of the soil from the surface to a depth of about 3 feet is considered in the ratings.

Ratings in the column potential for seedling mortality are based on flooding, ponding, depth to a water table, content of lime, reaction, salinity, available water capacity, soil moisture regime, soil temperature regime, aspect, and slope. The soils are described as having a low, moderate, or high potential for seedling mortality. See the National Forestry Manual, Subpart B for criteria used in rating management concerns. Specific information on plants and yields can be obtained from the local office of the Natural Resources Conservation Service or the Cooperative Extension Service.

CONSERVATION TREE AND SHRUB MANAGEMENT
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. Pines and spruces are prone to disease problems. See text for further explanation of ratings in this table.)

Map symbol and soil name	Wind break Group	Suitability for hand planting	Suitability for mechanical planting	Suitability for mechanical site preparation (surface)	Suitability for mechanical site preparation (deep)	Potential for seedling mortality
		Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features
027CS: Crete-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
027CX: Crete-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
027HN: Hobbs-----	1	Well suited	Well suited	Well suited	Well suited	Low
027KS: Kipson-----	10	Well suited	Moderately suited Slope Rock fragments	Well suited	Well suited	High Lime Soil reaction
Sogn-----	10	Well suited	Moderately suited Slope	Well suited	Well suited	Low
061BE: Benfield-----	4C	Moderately suited Stickiness	Poorly suited Slope Stickiness Rock fragments	Poorly suited Slope	Poorly suited Slope	Low
Florence-----	6D	Poorly suited Stickiness Rock fragments	Poorly suited Rock fragments Stickiness Slope	Poorly suited Rock fragments Stickiness	Well suited	Low
061CF: Clime-----	8	Moderately suited Stickiness	Moderately suited Slope Stickiness Rock fragments	Poorly suited Stickiness	Well suited	Moderate Lime
Sogn-----	10	Unsuited Restrictive layer	Moderately suited Slope Restrictive layer	Poorly suited Restrictive layer	Well suited	Low
061CR: Crete-----	4C	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Low
061CS: Crete-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
061EU: Eudora-----	1	Well suited	Well suited	Well suited	Well suited	Low
061HE: Haynie-----	1K	Well suited	Well suited	Well suited	Well suited	Moderate Lime
061KA: Kahola-----	1	Well suited	Well suited	Well suited	Well suited	Low
061KB: Kahola-----	1	Well suited	Well suited	Well suited	Well suited	Low
061RE: Reading-----	1	Well suited	Well suited	Well suited	Well suited	Low
061TO: Tully-----	3	Moderately suited Stickiness	Moderately suited Slope Stickiness	Well suited	Well suited	Low
117PA: Pawnee-----	4C	Well suited	Well suited	Well suited	Well suited	Low
117PB: Pawnee-----	4C	Well suited	Moderately suited Slope	Well suited	Well suited	Low
149HS: Haynie-----	1K	Well suited	Well suited	Well suited	Well suited	Moderate Lime
Sarpy-----	1K	Moderately suited Sandiness	Moderately suited Sandiness	Well suited	Well suited	Low
149PS: Paxico-----	10	Well suited	Well suited	Well suited	Well suited	High

CONSERVATION TREE AND SHRUB MANAGEMENT
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. Pines and spruces are prone to disease problems. See text for further explanation of ratings in this table.)

Map symbol and soil name	Wind break Group	Suitability for hand planting	Suitability for mechanical planting	Suitability for mechanical site preparation (surface)	Suitability for mechanical site preparation (deep)	Potential for seedling mortality
		Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features
149SF: Sarpy-----	1	Moderately suited Sandiness	Moderately suited Sandiness	Well suited	Well suited	Wetness High Wetness
197CM: Clime-----	8	Moderately suited Stickiness	Moderately suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
197FL: Florence-----	6D	Moderately suited Stickiness	Moderately suited Rock fragments Stickiness Slope	Well suited	Well suited	Low
Labette-----	4C	Moderately suited Stickiness	Moderately suited Stickiness Rock fragments	Well suited	Poorly suited Restrictive layer	Low
197IB: Irwin-----	4C	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Low
197ID: Irwin-----	4C	Well suited	Moderately suited Slope	Well suited	Well suited	Low
197IV: Ivan-----	1K	Well suited	Well suited	Well suited	Well suited	Moderate Soil reaction
197IX: Ivan-----	1K	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Moderate Soil reaction
197PN: Pawnee-----	4C	Well suited	Moderately suited Slope	Well suited	Well suited	High Wetness
197WE: Wamego-----	4	Moderately suited Stickiness	Moderately suited Stickiness Slope	Well suited	Well suited	Low
201CS: Crete-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
201CX: Crete, eroded-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
201KS: Kipson-----	10	Well suited	Poorly suited Slope Rock fragments	Poorly suited Slope	Poorly suited Slope	High Lime Soil reaction
Sogn-----	10	Well suited	Moderately suited Slope Rock fragments	Well suited	Unsuited Restrictive layer	Low
201LC: Lancaster-----	6D	Well suited	Moderately suited Slope	Well suited	Well suited	Low
Ad: Ivan-----	1K	Well suited	Well suited	Well suited	Well suited	Moderate Soil reaction
AED: Arents, Earthen Dam-----		Not rated	Not rated	Not rated	Not rated	Not rated
BE: Benfield-----	4C	Moderately suited Stickiness	Moderately suited Stickiness Slope	Well suited	Well suited	Low

CONSERVATION TREE AND SHRUB MANAGEMENT
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. Pines and spruces are prone to disease problems. See text for further explanation of ratings in this table.)

Map symbol and soil name	Wind break Group	Suitability for hand planting	Suitability for mechanical planting	Suitability for mechanical site preparation (surface)	Suitability for mechanical site preparation (deep)	Potential for seedling mortality
		Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features
Bf: Benfield-----	4C	Moderately suited Stickiness	Rock fragments Moderately suited Slope Stickiness Rock fragments	Well suited	Well suited	Low
Florence-----	6D	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Restrictive layer	Low
Bk: Wymore-----	4C	Well suited	Rock fragments Slope Moderately suited Slope	Well suited	Well suited	Low
Kennebec-----	1	Well suited	Well suited	Well suited	Well suited	Low
BOP: Borrow Pits-----		Not rated	Not rated	Not rated	Not rated	Not rated
Ca: Carr-----	1K	Well suited	Well suited	Well suited	Well suited	Moderate Soil reaction Low
Sarpy-----	1K	Well suited	Well suited	Well suited	Well suited	
Ch: Chase-----	1	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Low
Cs: Clime-----	8	Moderately suited Stickiness	Moderately suited Slope Stickiness	Poorly suited Stickiness	Well suited	Low
Sogn-----	10	Unsuited Restrictive layer	Unsuited Restrictive layer Slope	Unsuited Restrictive layer	Unsuited Restrictive layer	Low
CT: Crete-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
Dr: Dwight-----	9C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Irwin-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Dw: Dwight-----	9C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Irwin-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Em: Elmont-----	3	Well suited	Moderately suited Slope	Well suited	Well suited	Low
En: Elmont-----	3	Well suited	Moderately suited Slope	Well suited	Well suited	Low
Clime-----	8	Moderately suited Stickiness	Moderately suited Slope Stickiness	Well suited	Well suited	Low
Eu: Eudora-----	1	Well suited	Well suited	Well suited	Well suited	Low
Ga: Geary-----	3	Well suited	Well suited	Well suited	Well suited	Low
Ge: Geary-----	3	Well suited	Moderately suited Slope	Well suited	Well suited	Low
Ha: Haynie-----	1K	Well suited	Well suited	Well suited	Well suited	Low
HO: Hobbs-----	1	Well suited	Well suited	Well suited	Well suited	Low
Ic: Irwin-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low

CONSERVATION TREE AND SHRUB MANAGEMENT
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. Pines and spruces are prone to disease problems. See text for further explanation of ratings in this table.)

Map symbol and soil name	Wind break Group	Suitability for hand planting	Suitability for mechanical planting	Suitability for mechanical site preparation (surface)	Suitability for mechanical site preparation (deep)	Potential for seedling mortality
		Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features
Id: Irwin, eroded-----	4C	Poorly suited Stickiness	Slope Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Ie: Ivan-----	1K	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Moderate Soil reaction
Iv: Ivan-----	1K	Well suited	Well suited	Well suited	Well suited	Moderate Soil reaction
Ka: Kennebec-----	1	Well suited	Well suited	Well suited	Well suited	Low
Ke: Kahola-----	1	Well suited	Well suited	Well suited	Well suited	Low
KF: Kenesaw-----	3	Well suited	Well suited	Well suited	Well suited	Low
KN: Kenesaw-----	3	Well suited	Moderately suited Slope	Well suited	Well suited	Low
M-W: Miscellaneous Water-		Not rated	Not rated	Not rated	Not rated	Not rated
Ma: Mayberry-----	4C	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	High Wetness
Mb: Mayberry-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	High Wetness
Mu: Muir-----	1	Well suited	Well suited	Well suited	Well suited	Low
QUA: Quarries-----		Not rated	Not rated	Not rated	Not rated	Not rated
Rd: Reading-----	1	Well suited	Well suited	Well suited	Well suited	Low
Re: Reading-----	1	Well suited	Well suited	Well suited	Well suited	Low
Sa: Sarpy-----	1K	Well suited	Well suited	Well suited	Well suited	Low
Sm: Smolan-----	4C	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Low
Sn: Smolan-----	4C	Moderately suited Stickiness	Moderately suited Slope Stickiness	Well suited	Well suited	Low
So: Smolan, eroded-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
St: Clime-----	8	Moderately suited Stickiness	Unsuited Slope Stickiness Rock fragments	Poorly suited Slope Rock fragments Stickiness	Poorly suited Slope	Moderate Lime
Su: Sutphen-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Ts: Tully-----	3	Moderately suited Stickiness	Moderately suited Stickiness	Well suited	Well suited	Low
Tt: Tully, eroded-----	4C	Moderately suited Stickiness	Moderately suited Stickiness	Poorly suited Stickiness	Well suited	Low
Tu: Tully-----	3	Moderately suited Stickiness	Moderately suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low

CONSERVATION TREE AND SHRUB MANAGEMENT
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. Pines and spruces are prone to disease problems. See text for further explanation of ratings in this table.)

Map symbol and soil name	Wind break Group	Suitability for hand planting	Suitability for mechanical planting	Suitability for mechanical site preparation (surface)	Suitability for mechanical site preparation (deep)	Potential for seedling mortality
		Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features	Rating class and limiting features
Tv: Tully, eroded-----	4C	Moderately suited Stickiness	Moderately suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low
W: Water-----		Not rated	Not rated	Not rated	Not rated	Not rated
Wm: Wymore-----	4C	Well suited	Well suited	Well suited	Well suited	Low
Wn: Wymore-----	4C	Well suited	Well suited	Well suited	Well suited	Low
Wo: Wymore, eroded-----	4C	Poorly suited Stickiness	Poorly suited Stickiness	Poorly suited Stickiness	Well suited	Low
Wr: Wymore-----	4C	Well suited	Moderately suited Slope	Well suited	Well suited	Low
Ws: Wymore, eroded-----	4C	Poorly suited Stickiness	Poorly suited Stickiness Slope	Poorly suited Stickiness	Well suited	Low

ENGINEERING INDEX PROPERTIES
Riley County, Kansas

Engineering Index Properties table gives the engineering classifications and the range of index properties for the layers of each soil in the survey area. Depth to the upper and lower boundaries of each layer is indicated. Texture is given in the standard terms used by the U.S. Department of Agriculture. These terms are defined according to percentages of sand, silt, and clay in the fraction of the soil that is less than 2 millimeters in diameter. Loam, for example, is soil that is 7 to 27 percent clay, 28 to 50 percent silt, and less than 52 percent sand. If the content of particles coarser than sand is 15 percent or more, an appropriate modifier is added, for example, gravelly. Textural terms are defined in the Glossary.

Classification of the soils is determined according to the Unified soil classification system (ASTM, 1998) and the system adopted by the American Association of State Highway and Transportation Officials (AASHTO, 1998). The Unified system classifies soils according to properties that affect their use as construction material. Soils are classified according to particle-size distribution of the fraction less than 3 inches in diameter and according to plasticity index, liquid limit, and organic matter content. Sandy and gravelly soils are identified as GW, GP, GM, GC, SW, SP, SM, and SC; silty and clayey soils as ML, CL, OL, MH, CH, and OH; and highly organic soils as PT. Soils exhibiting engineering properties of two groups can have a dual classification, for example, CL-ML.

The AASHTO system classifies soils according to those properties that affect roadway construction and maintenance. In this system, the fraction of a mineral soil that is less than 3 inches in diameter is classified in one of seven groups from A-1 through A-7 on the basis of particle-size distribution, liquid limit, and plasticity index. Soils in group A-1 are coarse grained and low in content of fines (silt and clay). At the other extreme, soils in group A-7 are fine grained. Highly organic soils are classified in group A-8 on the basis of visual inspection. If laboratory data are available, the A-1, A-2, and A-7 groups are further classified as A-1-a, A-1-b, A-2-4, A-2-5, A-2-6, A-2-7, A-7-5, or A-7-6. As an additional refinement, the suitability of a soil as subgrade material can be indicated by a group index number. Group index numbers range from 0 for the best subgrade material to 20 or higher for the poorest. The AASHTO classification for soils tested, with group index numbers in parentheses, is given in Engineering Index Properties table.

Rock fragments larger than 10 inches in diameter and 3 to 10 inches in diameter are indicated as a percentage of the total soil on a dry-weight basis. The percentages are estimates determined mainly by converting volume percentage in the field to weight percentage. Percentage (of soil particles) passing designated sieves is the percentage of the soil fraction less than 3 inches in diameter based on an oven-dry weight. The sieves, numbers 4, 10, 40, and 200 (USA Standard Series), have openings of 4.76, 2.00, 0.420, and 0.074 millimeters, respectively. Estimates are based on laboratory tests of soils sampled in the survey area and in nearby areas and on estimates made in the field.

Liquid limit and plasticity index (Atterberg limits) indicate the plasticity characteristics of a soil. The estimates are based on test data from the survey area or from nearby areas and on field examination. The estimates of particle-size distribution, liquid limit, and plasticity index are generally rounded to the nearest 5 percent. Thus, if the ranges of gradation and Atterberg limits extend a marginal amount (1 or 2 percentage points) across classification boundaries, the classification in the marginal zone is generally omitted in the table.

ENGINEERING INDEX PROPERTIES--Continued
Riley County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth In	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit Pct	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
					Pct	Pct						
027CS: Crete-----	0-6	Silty clay loam	CL	A-7-6	0	0	100	100	97-100	88-99	36-45	20-30
	6-11	Silty clay loam	CL	A-7-6	0	0	100	100	97-100	96-99	38-45	22-30
	11-27	Silty clay	CH	A-7-6	0	0	100	100	97-100	96-99	48-60	30-40
	27-40	Silty clay loam			0	0	100	100	97-100	96-99	42-52	27-37
	40-60	Silty clay loam			0	0	100	100	97-100	88-99	40-50	22-33
027CX: Crete-----	0-7	Silty clay loam	CL	A-6, A-7	0	0	100	100	95-100	85-95	38-45	22-30
	7-31	Silty clay	CH	A-7	0	0	100	100	95-100	85-95	48-60	30-40
	31-60	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	70-95	40-50	22-33
027HN: Hobbs-----	0-8	Silt loam	CL, ML	A-6, A-4	0	0	100	100	95-100	85-100	26-36	8-16
	8-24	Silt loam	CL, ML	A-6, A-4	0	0	100	100	95-100	85-100	26-36	8-16
	24-44	Silt loam	CL, ML	A-6, A-4	0	0	100	100	95-100	80-100	26-39	8-18
	44-60	Silt loam	CL, ML	A-6, A-4	0	0	100	100	95-100	80-100	26-39	8-18
027KS: Kipson-----	0-8	Silty clay loam	CL	A-6, A-7	0	0-25	80-100	70-100	65-100	60-95	35-45	15-22
	8-18	Silty clay loam	CL	A-6, A-7-6	0	0-25	80-100	75-100	70-100	50-95	25-45	10-22
	18-22	Weathered bedrock			---	---	---	---	---	---	---	---
Sogn-----	0-12	Silty clay loam	CH, CL, MH, ML	A-6, A-7	0	0-10	85-100	85-100	85-100	70-100	25-55	10-25
	12-16	Unweathered bedrock			---	---	---	---	---	---	---	---
061BE: Benfield-----	0-5	Silty clay loam	CL	A-7-6	0	0-5	93-100	91-100	86-100	77-95	36-44	16-22
	5-10	Silty clay loam	CH	A-7-6	0	0-5	80-100	76-100	72-100	65-95	44-53	22-29
	10-19	Gravelly silty clay	CH	A-7-6	0	0-5	60-80	50-74	45-74	45-70	44-57	22-32
	19-34	Silty clay	CH	A-7-6	0	0-5	80-92	76-90	72-90	68-86	44-62	22-36
	34-38	Silty clay	CH	A-7-6	0	0	100	100	95-100	90-95	48-66	25-39
	38-56	Weathered bedrock			---	---	---	---	---	---	---	---
Florence-----	0-5	Gravelly silt loam	CL, GC	A-7-6	0	0-10	58-92	48-90	43-90	34-81	40-51	20-29
	5-14	Very gravelly silty clay	GC, CH	A-7-6	0	0-40	30-80	11-75	10-75	8-70	51-71	29-45
	14-48	Very cobbly clay	CH, GC	A-7	0	25-50	42-68	26-61	23-61	20-58	66-96	41-65
	48-56	Extremely cobbly silty clay	CH, GC	A-2-7	0	50-90	20-88	3-85	3-85	3-81	66-96	41-65
	56-60	Unweathered bedrock			---	---	---	---	---	---	---	---
061CF: Clime-----	0-12	Silty clay loam	CL	A-7-6	0	0-5	86-100	82-100	78-100	70-95	41-48	20-25
	12-26	Silty clay	CH, CL	A-7-6	0	0-5	86-100	82-100	78-100	70-95	44-57	22-32
	26-30	Silty clay	CH, CL	A-7-6	0	0	86-100	82-100	78-100	70-95	44-57	22-32
	30-34	Weathered bedrock			---	---	---	---	---	---	---	---
Sogn-----	0-9	Silty clay loam	CL	A-6, A-7-6	0	0-10	85-100	82-100	78-100	70-95	36-44	16-22
	9-13	Unweathered bedrock			---	---	---	---	---	---	---	---
061CR: Crete-----	0-6	Silty clay loam	CL	A-7-6	0	0	100	100	97-100	88-99	36-45	20-30
	6-14	Silty clay loam	CL	A-7-6	0	0	100	100	97-100	96-99	38-45	22-30
	14-30	Silty clay	CH	A-7-6	0	0	100	100	97-100	96-99	48-60	30-40
	30-42	Silty clay loam	CL, CH	A-7-6	0	0	100	100	97-100	96-99	42-52	27-37
	42-60	Silty clay loam	CL, CH	A-7-6	0	0	100	100	97-100	88-99	40-50	22-33
061CS: Crete-----	0-6	Silty clay loam	CL	A-7-6	0	0	100	100	97-100	88-99	36-45	20-30
	6-11	Silty clay loam	CL	A-7-6	0	0	100	100	97-100	96-99	38-45	22-30
	11-27	Silty clay	CH	A-7-6	0	0	100	100	97-100	96-99	48-60	30-40
	27-40	Silty clay loam			0	0	100	100	97-100	96-99	42-52	27-37
	40-60	Silty clay loam			0	0	100	100	97-100	88-99	40-50	22-33
061EU: Eudora-----	0-7	Silt loam	CL, CL-ML, ML	A-4	0	0	100	100	90-100	70-90	17-30	1-11
	7-14	Silt loam	CL, ML	A-4	0	0	100	100	90-100	70-90	17-30	1-11
	14-19	Silt loam	CL	A-4	0	0	100	100	90-100	70-90	17-28	1-10
	19-26	Silt loam	CL, CL-ML, ML	A-4	0	0	100	100	85-100	50-90	17-28	1-10
	26-60	Very fine sandy loam	CL	A-4	0	0	100	100	85-100	50-90	17-28	1-10
061HE: Haynie-----	0-10	Silt loam	CL	A-6, A-4	0	0	100	100	85-100	70-100	26-35	8-15
	10-60	Very fine sandy loam	CL, CL-ML	A-4	0	0	100	100	85-100	85-100	21-28	4-10
061KA: Kahola-----	0-24	Silt loam	CL	A-6	0	0	94-100	91-100	82-100	64-90	28-36	10-16
	24-36	Silt loam	CL	A-6	0	0	94-100	91-100	82-100	64-90	28-36	10-16
	36-44	Silt loam	CL	A-6, A-7	0	0	94-100	91-100	82-100	64-90	28-44	10-22
	44-60	Silt loam	CL	A-6, A-7	0	0	94-100	91-100	82-100	64-90	28-44	10-22
061KB: Kahola-----	0-24	Silt loam	CL	A-6	0	0	94-100	91-100	82-100	64-90	28-36	10-16
	24-36	Silt loam	CL	A-6	0	0	94-100	91-100	82-100	64-90	28-36	10-16
	36-44	Silt loam	CL	A-6, A-7	0	0	94-100	91-100	82-100	64-90	28-44	10-22
	44-60	Silt loam	CL	A-6, A-7	0	0	94-100	91-100	82-100	64-90	28-44	10-22

ENGINEERING INDEX PROPERTIES--Continued
Riley County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plasticity index
			Unified	AASHTO	>10	3-10	4	10	40	200		
					inches	inches						
					Pct	Pct					Pct	
061RE: Reading-----	0-8	Silty clay loam	CL	A-6	0	0	100	100	95-100	85-95	36-39	16-18
	8-20	Silty clay loam	CL	A-6	0	0	100	100	95-100	85-95	36-39	16-18
	20-52	Silty clay loam	CL	A-6, A-7	0	0	100	100	95-100	85-95	39-44	18-22
	52-60	Silty clay loam	CL	A-7, A-6	0	0	100	100	95-100	85-95	39-48	18-25
061TO: Tully-----	0-12	Silty clay loam	CL	A-6, A-7-6	0	0	93-100	91-100	86-100	77-95	37-46	17-24
	12-21	Silty clay loam	CL	A-6, A-7-6	0	0	93-100	91-100	86-100	77-95	39-48	18-25
	21-31	Silty clay	CH, CL	A-7-6	0	0	93-100	91-100	86-100	82-95	48-62	25-36
	31-40	Silty clay	CH, CL	A-7-6	0	0	93-100	91-100	86-100	82-95	48-62	25-36
	40-52	Silty clay	CH, CL	A-7-6	0	0	93-100	91-100	86-100	82-95	48-62	25-36
	52-60	Silty clay	CH, CL	A-7-6	0	0	93-100	91-100	86-100	77-95	44-53	22-29
117PA: Pawnee-----	0-13	Clay loam	CL	A-6	0	0	95-100	95-100	85-100	70-90	30-40	10-20
	13-36	Clay	CH	A-7	0	0	95-100	95-100	85-100	70-85	50-70	25-45
	36-60	Clay loam	CL, CH	A-6, A-7	0	0	95-100	95-100	80-100	70-90	35-55	20-40
117PB: Pawnee-----	0-13	Clay loam	CL	A-6	0	0	95-100	95-100	85-100	70-90	30-40	10-20
	13-36	Clay	CH	A-7	0	0	95-100	95-100	85-100	70-85	50-70	25-45
	36-60	Clay loam	CH, CL	A-6, A-7	0	0	95-100	95-100	80-100	70-90	35-55	20-40
149HS: Haynie-----	0-9	Very fine sandy loam	CL-ML, ML	A-4	0	0	100	100	85-100	70-100	15-25	NP-5
	9-60	Silt loam	CL, CL-ML	A-4, A-6	0	0	100	100	85-100	85-100	25-35	5-15
Sarpy-----	0-6	Fine sand	SM, SP, SP-SM	A-2-4, A-3	0	0	100	100	60-80	2-15	---	NP
	6-60	Sand	SM, SP, SP-SM	A-2-4, A-3	0	0	100	100	60-80	2-35	---	NP
149PS: Paxico-----	0-42	Silt loam	CL, CL-ML, ML	A-4	0	0	100	100	85-100	75-90	15-30	NP-10
	42-60	Loamy fine sand	CL-ML, ML, SC-SM, SM	A-2, A-4	0	0	100	95-100	70-90	25-55	15-25	NP-5
149SF: Sarpy-----	0-6	Sand	SM, SP, SP-SM	A-2-4, A-3	0	0	100	100	60-80	2-15	---	NP
	6-60	Sand	SM, SP, SP-SM	A-2-4, A-3	0	0	100	100	60-80	2-35	---	NP
197CM: Clime-----	0-5	Silty clay loam	CL	A-7-6	0	0-5	90-100	90-100	85-100	80-95	40-50	20-25
	5-18	Silty clay	MH, CH, CL	A-7	0	0	95-100	95-100	95-100	85-95	45-65	20-40
	18-32	Silty clay	MH, CH, CL	A-7	0	0	95-100	95-100	95-100	85-95	45-60	20-30
	32-36	Weathered bedrock			---	---	---	---	---	---	---	---
197FL: Florence-----	0-14	Gravelly silt loam	CL, GC, SC	A-2-7, A-7, A-7-6	0	0-10	30-90	20-75	20-75	20-70	40-50	20-30
	14-18	Gravelly silty clay loam	CL, GC, SC	A-2-7, A-7, A-7-6	0	5-20	30-75	20-70	15-70	15-65	40-50	20-30
	18-56	Very gravelly clay	CH, GC, SC	A-2-7, A-7	0	10-40	30-90	20-75	20-75	15-70	65-75	40-50
	56-60	Unweathered bedrock			---	---	---	---	---	---	---	---
Labette-----	0-7	Silt loam	CL	A-6	0	0	85-100	85-100	85-100	65-90	30-40	10-15
	7-35	Silty clay	MH, CH, CL, GC, SC	A-7-6	0	0-20	55-80	50-75	50-75	45-70	45-60	20-35
	35-39	Unweathered bedrock			---	---	---	---	---	---	---	---
197IB: Irwin-----	0-12	Silty clay loam	CL	A-6, A-7-6	0	0	100	95-100	90-100	80-95	35-45	15-20
	12-42	Silty clay, clay	MH, CH	A-7-6	0	0	100	95-100	95-100	85-95	50-60	25-30
	42-60	Clay	MH, CH, CL	A-7-6	0	0	100	100	95-100	80-95	40-60	20-30
197ID: Irwin-----	0-6	Silty clay loam	CL	A-7-6	0	0	93-100	91-100	86-100	77-95	37-44	17-22
	6-13	Silty clay loam	CL	A-7-6	0	0	93-100	91-100	86-100	77-95	37-44	17-22
	13-30	Silty clay	CH	A-7-6	0	0	93-100	91-100	82-100	68-95	48-66	25-39
	30-41	Silty clay	CH	A-7-6	0	0	93-100	91-100	82-100	68-95	48-66	25-39
	41-72	Silty clay	CH	A-7-6	0	0	93-100	91-100	86-100	77-95	44-62	22-36
197IV: Ivan-----	0-36	Silt loam	CL	A-4, A-6	0	0	95-100	95-100	90-100	70-100	25-40	7-20
	36-60	Silt loam	CL	A-4, A-6, A-7	0	0	95-100	95-100	90-100	65-100	25-45	7-25
197IX: Ivan-----	0-40	Silty clay loam	CL	A-6, A-7	0	0	95-100	95-100	90-100	70-100	35-45	15-25
	40-60	Silt loam	CL	A-4, A-6, A-7	0	0	95-100	95-100	90-100	65-100	25-45	7-25
197PN: Pawnee-----	0-14	Clay loam	CL	A-6	0	0	95-100	95-100	85-100	70-90	30-40	10-20
	14-34	Clay	CH	A-7	0	0	95-100	95-100	85-100	70-85	50-70	25-45
	34-72	Sandy clay loam	CH, CL	A-6, A-7	0	0	95-100	95-100	80-100	70-90	35-55	20-40
197WE: Wamego-----	0-9	Silty clay loam	CL	A-6	0	0	100	100	95-100	85-95	35-40	15-20
	9-20	Silty clay loam	CL	A-7	0	0	100	85-100	80-100	75-95	45-50	20-25
	20-25	Silty clay loam	CL	A-7	0	0	100	85-100	80-100	75-95	45-50	20-25
	25-36	Weathered bedrock			---	---	---	---	---	---	---	---
201CS: Crete-----	0-6	Silty clay loam	CL	A-7-6	0	0	100	100	97-100	88-99	36-45	20-30
	6-9	Silty clay loam	CL	A-7-6	0	0	100	100	97-100	96-99	38-45	22-30
	9-32	Silty clay	CH	A-7-6	0	0	100	100	97-100	96-99	48-60	30-40
	32-40	Silty clay loam			0	0	100	100	97-100	96-99	42-52	27-37
	40-60	Silty clay loam			0	0	100	100	97-100	88-99	40-50	22-33

ENGINEERING INDEX PROPERTIES--Continued
Riley County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plasticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
					Pct	Pct						
201CX: Crete, eroded--	0-5 5-30 30-60	Silty clay loam Silty clay Silt loam	CL CH CH, CL	A-6, A-7 A-7 A-6, A-7	0 0 0	0 0 0	100 100 100	100 100 100	100 100 100	90-100 90-100 95-100	35-50 50-65 30-55	15-30 25-40 10-35
201KS: Kipson-----	0-12 12-18 18-22	Silty clay loam Silty clay loam Weathered bedrock	CL CL	A-4, A-6, A-7 A-4, A-6	0 0	0-25 0-25	80-100 80-100	70-100 75-100	65-100 70-100	60-95 50-95	35-45 25-45	15-22 10-22
Sogn-----	0-8 8-16 16-20	Silt loam Channery silt loam Unweathered bedrock	CL CL, GC, SC	A-6 A-6, A-7	0 0	0-10 0-15	90-100 60-95	85-100 50-85	75-100 45-85	60-90 36-80	28-36 30-45	10-15 10-20
201LC: Lancaster-----	0-9 9-24 24-29 >29	Loam Clay loam Sandy clay loam Weathered bedrock	CL, CL-ML CL CL, CL-ML	A-4, A-6 A-6, A-7-6 A-6, A-4	0 0 0	0-5 0 0-5	88-100 94-100 88-100	84-100 91-100 84-100	71-95 82-100 67-90	50-75 64-80 29-55	23-35 28-44 23-39	5-15 10-22 5-18
Ad: Ivan-----	0-7 7-26 26-39 39-64	Silt loam Silty clay loam Silty clay loam Silty clay loam	CL CL CL CL	A-6 A-6, A-7 A-6, A-7 A-6, A-7	0 0 0 0	0 0 0 0	95-100 95-100 95-100 95-100	95-100 95-100 95-100 95-100	90-100 90-100 80-100 80-100	70-90 70-95 60-95 60-95	28-35 28-45 28-45 28-45	10-15 10-25 10-25 10-25
AED: Arents, Earthen Dam-----	---	---	---	---	---	---	---	---	---	---	---	---
BE: Benfield-----	0-10 10-32 32-36	Silty clay loam Silty clay Weathered bedrock	CL CH, CL	A-6, A-7 A-7-6	0 0	0-15 0-15	85-100 60-100	85-100 55-100	85-100 50-100	75-95 50-95	35-45 45-60	15-20 20-30
Bf: Benfield-----	0-6 6-30 30-35 35-39	Silty clay loam Silty clay Silty clay loam Weathered bedrock	CL CH, CL CH, CL	A-6, A-7 A-7-6 A-7-6	0 0 0	0-15 0-15 0-5	85-100 60-100 60-100	85-100 55-100 55-100	85-100 50-100 50-100	75-95 50-95 50-95	35-45 45-60 45-60	15-20 20-30 20-30
Florence-----	0-5 5-10 10-14 14-30 30-34	Gravelly silt loam Very gravelly silty clay loam Very gravelly silty clay loam Gravelly clay Unweathered bedrock	CL, GC, SC CL, GC, SC GC, SC CH, GC, SC	A-2-7, A-7, A-7-6 A-2-7, A-7, A-7-6 A-2-7, A-7 A-2-7, A-7	0 0 0 0	0-10 5-20 10-20 10-40	30-90 30-75 30-70 30-90	20-75 20-70 20-50 20-75	20-75 15-70 20-50 20-75	20-70 15-65 15-40 15-70	40-50 40-50 50-70 65-75	20-30 20-30 30-45 40-50
Bk: Wymore-----	0-13 13-33 33-64	Silty clay loam Silty clay Silty clay loam	CH, CL, MH, ML CH CH, CL	A-6, A-7 A-7 A-6, A-7	0 0 0	0 0 0	100 100 100	100 100 100	95-100 95-100 95-100	95-100 95-100 85-100	35-55 55-70 35-55	11-25 30-42 20-35
Kennebec-----	0-18 18-60	Silt loam Silty clay loam	CL CL, CL-ML	A-6, A-7 A-4, A-6	0 0	0 0	100 100	100 100	95-100 95-100	90-100 90-100	25-45 25-40	10-20 5-15
BOP: Borrow Pits----	---	---	---	---	---	---	---	---	---	---	---	---
Ca: Carr-----	0-9 9-17 17-28	Fine sandy loam Fine sandy loam Fine sandy loam	SC, SM SC, SM CL, ML, SC, SM	A-4 A-4 A-2-4, A-4	0 0 0	0 0 0	100 100 100	95-100 95-100 95-100	65-85 65-85 60-85	40-55 40-55 30-55	10-25 10-25 10-25	2-8 2-8 2-8
Sarpy-----	28-60 0-5 5-60	Very fine sandy loam Loamy fine sand Fine sand	CL, ML, SC, SM SM SM, SP, SP-SM	A-2-4, A-4 A-2-4 A-3, A-2-4	0 0 0	0 0 0	100 100 100	95-100 100 100	60-95 75-100 50-100	30-65 10-55 4-55	10-25 4-10 4-10	2-8 NP-3 NP-3
Ch: Chase-----	0-7 7-13 13-40 40-50 50-60	Silty clay loam Silty clay loam Silty clay Silty clay Silty clay	CL CL, CH CH CH, CL CH, CL	A-7 A-7 A-7 A-7 A-7	0 0 0 0 0	0 0 0 0 0	100 100 100 100 100	100 100 100 100 100	95-100 95-100 90-100 95-100 95-100	85-95 85-95 75-95 85-95 85-95	45-50 45-55 55-70 50-65 45-60	25-30 25-32 30-45 25-40 25-35
Cs: Clime-----	0-12 12-30 30-34	Silty clay loam Silty clay Weathered bedrock	CL CH, CL	A-7-6 A-7	0 0	0-5 0	90-100 95-100	90-100 95-100	85-100 95-100	80-95 85-95	40-50 45-65	20-25 20-40
Sogn-----	0-9 9-13	Silty clay loam Unweathered bedrock	CH, CL, MH, ML	A-6, A-7	0	0-10	85-100	85-100	85-100	70-100	25-55	10-25

ENGINEERING INDEX PROPERTIES--Continued
Riley County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plasticity index
			Unified	AASHTO	>10	3-10	4	10	40	200		
					inches	inches						
	In				Pct	Pct					Pct	
CT: Crete-----	0-7	Silty clay loam	CL	A-7-6	0	0	100	100	97-100	88-99	36-45	20-30
	7-11	Silty clay loam	CL	A-7-6	0	0	100	100	97-100	96-99	38-45	22-30
	11-30	Silty clay	CH	A-7-6	0	0	100	100	97-100	96-99	48-60	30-40
	30-40	Silty clay loam	CH, CL	A-7-6	0	0	100	100	97-100	96-99	42-52	27-37
	40-60	Silty clay loam	CL, CH	A-7-6	0	0	100	100	97-100	88-99	40-50	22-33
Dr: Dwight-----	0-4	Silt loam	CL	A-7, A-6	0	0	100	100	90-100	70-90	35-45	15-25
	4-17	Silty clay	CH	A-7	0	0	100	100	90-100	75-95	60-75	35-50
	17-43	Silty clay	CH	A-7	0	0	100	100	90-100	75-95	50-65	28-40
	>43	Unweathered bedrock			---	---	---	---	---	---	---	---
Irwin-----	0-7	Silty clay loam	CL	A-7	0	0	100	95-100	90-100	85-95	45-50	25-30
	7-11	Silty clay loam	CL, CH	A-7	0	0	100	95-100	90-100	85-95	45-55	25-32
	11-35	Silty clay	CH	A-7	0	0	100	95-100	85-100	80-95	55-70	30-45
	35-50	Silty clay	CH	A-7	0	0	100	95-100	85-100	80-95	55-70	30-45
	50-55	Silty clay	CH	A-7	0	0	100	95-100	85-100	80-95	50-70	28-45
	>55	Unweathered bedrock			---	---	---	---	---	---	---	---
Dw: Dwight-----	0-4	Silt loam	CL	A-7, A-6	0	0	100	100	90-100	70-90	35-45	15-25
	4-17	Silty clay	CH	A-7	0	0	100	100	90-100	75-95	60-75	35-50
	17-43	Silty clay	CH	A-7	0	0	100	100	90-100	75-95	50-65	28-40
	>43	Unweathered bedrock			---	---	---	---	---	---	---	---
Irwin-----	0-8	Silty clay loam	CL, CH	A-7	0	0	100	95-100	90-100	85-95	45-55	25-32
	8-35	Silty clay	CH	A-7	0	0	100	95-100	85-100	80-95	55-70	30-45
	35-50	Silty clay	CH	A-7	0	0	100	95-100	85-100	80-95	55-70	30-45
	50-55	Silty clay	CH	A-7	0	0	100	95-100	85-100	80-95	50-70	28-45
	>55	Unweathered bedrock			---	---	---	---	---	---	---	---
Em: Elmont-----	0-10	Silt loam	CL	A-6	0	0	100	100	90-100	70-90	28-35	10-15
	10-18	Silty clay loam	CL	A-6	0	0	100	100	90-100	70-95	35-40	15-20
	18-28	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	70-95	35-45	15-25
	28-33	Silty clay loam	CL	A-6, A-7	0	0	95-100	90-100	80-100	65-95	35-50	15-25
	33-44	Clay loam	CL	A-6, A-7	0	0	95-100	90-100	80-100	65-95	35-50	15-25
	>44	Weathered bedrock			---	---	---	---	---	---	---	---
En: Elmont-----	0-10	Silt loam	CL	A-6	0	0	100	100	90-100	70-90	28-35	10-15
	10-18	Silty clay loam	CL	A-6	0	0	100	100	90-100	70-95	35-40	15-20
	18-28	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	70-95	35-45	15-25
	28-33	Silty clay loam	CL	A-6, A-7	0	0	95-100	90-100	80-100	65-95	35-50	15-25
	33-44	Clay loam	CL	A-6, A-7	0	0	95-100	90-100	80-100	65-95	35-50	15-25
	>44	Weathered bedrock			---	---	---	---	---	---	---	---
Clime-----	0-8	Silty clay loam	CL	A-7	0	0-5	90-100	90-100	85-100	80-95	40-45	20-25
	8-12	Silty clay loam	CL	A-7	0	0-5	90-100	90-100	85-100	80-95	40-45	20-25
	12-20	Silty clay loam	CH, CL	A-7	0	1-5	95-100	95-100	90-100	85-95	45-55	20-30
	20-30	Silty clay loam	CH, CL	A-7	0	1-5	95-100	95-100	85-100	75-95	45-65	20-35
	>30	Weathered bedrock			---	---	---	---	---	---	---	---
Eu: Eudora-----	0-7	Silt loam	CL, CL-ML, ML	A-4	0	0	100	100	90-100	70-90	17-30	1-11
	7-14	Silt loam	CL, ML	A-4	0	0	100	100	90-100	70-90	17-30	1-11
	14-19	Silt loam	CL	A-4	0	0	100	100	90-100	70-90	17-28	1-10
	19-26	Silt loam	CL, CL-ML, ML	A-4	0	0	100	100	85-100	50-90	17-28	1-10
	26-60	Very fine sandy loam	CL	A-4	0	0	100	100	85-100	50-90	17-28	1-10
Ga: Geary-----	0-8	Silt loam	CL	A-6, A-4	0	0	100	100	90-100	70-90	25-35	8-15
	8-13	Silty clay loam	CL	A-6	0	0	100	100	90-100	70-95	35-40	15-20
	13-29	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	70-95	35-45	15-25
	29-42	Silty clay loam	CL	A-6	0	0	100	100	85-100	65-95	35-40	15-20
	42-60	Silty clay loam	CL	A-6	0	0	100	100	85-100	65-95	30-40	10-20
Ge: Geary-----	0-8	Silt loam	CL	A-6, A-4	0	0	100	100	90-100	70-90	25-35	8-15
	8-13	Silty clay loam	CL	A-6	0	0	100	100	90-100	70-95	35-40	15-20
	13-29	Silty clay loam	CL	A-6, A-7	0	0	100	100	90-100	70-95	35-45	15-25
	29-42	Silty clay loam	CL	A-6	0	0	100	100	85-100	65-95	35-40	15-20
	42-60	Silty clay loam	CL	A-6	0	0	100	100	85-100	65-95	30-40	10-20
Ha: Haynie-----	0-10	Very fine sandy loam	CL, CL-ML	A-4	0	0	100	100	85-95	50-75	15-30	3-10
	10-20	Very fine sandy loam	CL, CL-ML	A-4	0	0	100	100	85-95	50-75	15-30	3-10
	20-30	Very fine sandy loam	CL, CL-ML	A-4	0	0	100	100	85-95	50-75	15-30	2-10
	30-41	Very fine sandy loam	CL, CL-ML	A-4	0	0	100	100	85-95	50-75	15-30	2-10
	41-60	Silty clay loam	CL	A-6, A-7	---	---	100	100	90-100	70-95	30-45	10-25
HO: Hobbs-----	0-8	Silt loam	CL, ML	A-6, A-4	0	0	100	100	95-100	85-100	26-36	8-16
	8-16	Silt loam	CL, ML	A-6, A-4	0	0	100	100	95-100	85-100	26-36	8-16
	16-40	Silt loam	CL, ML	A-6, A-4	0	0	100	100	95-100	80-100	26-39	8-18
	40-60	Silt loam	ML, CL	A-6, A-4	0	0	100	100	95-100	80-100	26-39	8-18

ENGINEERING INDEX PROPERTIES--Continued
Riley County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth In	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit Pct	Plas- ticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
					Pct	Pct						
Ic: Irwin-----	0-11 11-55 55-59	Silty clay loam Silty clay Unweathered bedrock	CL, ML CH	A-6, A-7-6 A-7-6	0 0 ---	0 0 ---	100 100 ---	95-100 95-100 ---	90-100 95-100 ---	80-95 85-95 ---	35-50 50-65 ---	10-25 30-45 ---
Id: Irwin, eroded--	0-11 11-55 55-59	Silty clay loam Silty clay Unweathered bedrock	CL, ML CH	A-6, A-7-6 A-7-6	0 0 ---	0 0 ---	100 100 ---	95-100 95-100 ---	90-100 95-100 ---	80-95 85-95 ---	35-50 50-65 ---	10-25 30-45 ---
Ie: Ivan-----	0-7 7-64	Silty clay loam Silty clay loam	CL CL	A-6, A-7 A-4, A-6, A-7	0 0	0 0	95-100 95-100	95-100 95-100	90-100 90-100	70-100 65-100	35-45 25-45	15-25 7-25
Iv: Ivan-----	0-7 7-64	Silt loam Silty clay loam	CL CL	A-4, A-6 A-4, A-6, A-7	0 0	0 0	95-100 95-100	95-100 95-100	90-100 90-100	70-100 65-100	25-40 25-45	7-20 7-25
Kennebec-----	0-18 18-60	Silt loam Silty clay loam	CL CL, CL-ML	A-6, A-7 A-4, A-6	0 0	0 0	100 100	100 100	95-100 95-100	90-100 90-100	25-45 25-40	10-20 5-15
Ka: Kahola-----	0-13 13-60	Silt loam Silty clay loam	CL CL	A-4, A-6, A-7 A-7, A-4, A-6	0 0	0 0	100 100	100 100	95-100 95-100	85-100 75-100	30-45 30-45	8-20 8-20
Ke: Kenesaw-----	0-12 12-36 36-60	Silt loam Silt loam Silt loam	CL, CL-ML, ML CL, CL-ML, ML CL, CL-ML, ML	A-4, A-6 A-4, A-6 A-4, A-6	0 0 0	0 0 0	100 100 100	100 100 100	95-100 90-100 95-100	85-100 85-100 80-100	20-35 18-35 20-35	2-12 2-13 2-12
Kf: Kenesaw-----	0-12 12-36 36-60	Silt loam Silt loam Silt loam	CL, CL-ML, ML CL, CL-ML, ML CL, CL-ML, ML	A-4, A-6 A-4, A-6 A-4, A-6	0 0 0	0 0 0	100 100 100	100 100 100	95-100 90-100 95-100	85-100 85-100 80-100	20-35 18-35 20-35	2-12 2-13 2-12
KN: Kennebec-----	0-48 48-60	Silt loam Silt loam	CL CL, CL-ML	A-6, A-7 A-4, A-6	0 0	0 0	100 100	100 100	95-100 95-100	90-100 90-100	25-45 25-40	10-20 5-15
M-W: Miscellaneous Water-----	---	---	---	---	---	---	---	---	---	---	---	---
Ma: Mayberry-----	0-7 7-13 13-43 43-57 57-64	Clay loam Clay loam Clay Clay Clay loam	CL CL, CH CH CH CH, CL	A-7 A-7 A-7 A-7 A-7	0 0 0 0 0	0 0 0 0 0	100 100 100 95-100 95-100	95-100 95-100 90-100 95-100 95-100	82-100 85-100 75-100 85-100 85-100	60-80 65-80 45-95 65-95 65-95	40-50 45-55 55-65 50-60 45-60	20-30 25-35 30-40 25-35 25-35
Mb: Mayberry-----	0-7 7-37 37-51 51-64	Clay loam Clay Clay Clay loam	CL, CH CH CH CH, CL	A-7 A-7 A-7 A-7	0 0 0 0	0 0 0 0	100 100 95-100 95-100	95-100 90-100 95-100 95-100	85-100 75-100 85-100 85-100	65-80 45-95 65-95 65-95	45-55 55-65 50-60 45-60	25-32 30-40 25-35 25-35
Mu: Muir-----	0-7 7-18 18-24 24-42 42-60	Silt loam Silt loam Silt loam Silt loam Silt loam	CL CL CL CL CL	A-6 A-6 A-6, A-7-6 A-6, A-7-6 A-6, A-7-6	0 0 0 0 0	0 0 0 0 0	100 100 100 100 100	100 100 100 100 100	90-100 90-100 90-100 90-100 90-100	70-90 70-90 70-90 70-90 70-90	28-36 28-36 28-44 28-44 28-44	10-16 10-16 10-22 10-22 10-22
QUA: Quarries-----	---	---	---	---	---	---	---	---	---	---	---	---
Rd: Reading-----	0-11 11-52 52-60	Silt loam Silty clay loam Silty clay loam	CL CL CL	A-6 A-6, A-7 A-6, A-7	0 0 0	0 0 0	100 100 100	100 100 100	90-100 95-100 95-100	80-90 85-95 80-95	30-35 35-45 40-50	10-15 15-20 20-30
Re: Reading-----	0-11 11-52 52-60	Silt loam Silty clay loam Silty clay loam	CL CL CL	A-6 A-6, A-7 A-6, A-7	0 0 0	0 0 0	100 100 100	100 100 100	90-100 95-100 95-100	80-90 85-95 80-95	30-35 35-45 40-50	10-15 15-20 20-30
Sa: Sarpy-----	0-5 5-60	Loamy fine sand Fine sand	SM SM, SP, SP-SM	A-2-4 A-2-4, A-3	0 0	0 0	100 100	100 100	60-80 60-80	15-35 2-35	---	NP NP
Sm: Smolan-----	0-8 8-17 17-51 51-60	Silt loam Silty clay loam Silty clay loam Silty clay loam	CL CL CH CL	A-6, A-7 A-6, A-7 A-7 A-7	0 0 0 ---	0 0 0 0	100 100 100 100	100 100 100 100	95-100 95-100 95-100 95-100	85-100 85-100 90-100 90-100	35-42 35-50 50-65 42-50	15-22 15-28 28-40 22-28
Sn: Smolan-----	0-8 8-17 17-51 51-60	Silt loam Silty clay loam Silty clay loam Silty clay loam	CL CL CH CL	A-6, A-7 A-6, A-7 A-7 A-7	0 0 0 ---	0 0 0 0	100 100 100 100	100 100 100 100	95-100 95-100 95-100 95-100	85-100 85-100 90-100 90-100	35-42 35-50 50-65 42-50	15-22 15-28 28-40 22-28
So: Smolan, eroded--	0-7 7-51 51-60	Silty clay loam Silty clay loam Silty clay loam	CL CH CL	A-7 A-7 A-7	0 0 ---	0 0 0	100 100 100	100 100 100	95-100 95-100 95-100	85-100 90-100 90-100	42-50 50-65 42-50	22-28 28-40 22-28
St: Clime-----	0-2 2-9 9-27 27-33 33-37	Silty clay loam Silty clay Silty clay Silty clay Weathered bedrock	CL CH, CL CH, CL CH, CL	A-7-6 A-7-6 A-7-6 A-7-6	0-5 0 0 0 ---	0-12 0-12 0 0 ---	84-100 84-100 92-100 100 ---	79-100 79-100 90-100 100 ---	75-100 75-100 86-100 95-100 ---	67-95 67-95 77-95 77-95 ---	40-48 40-57 44-57 44-57 ---	19-25 19-32 22-32 22-32 ---

ENGINEERING INDEX PROPERTIES--Continued
Riley County, Kansas

(Absence of an entry indicates that the data were not estimated.)

Map symbol and soil name	Depth	USDA texture	Classification		Fragments		Percentage passing sieve number--				Liquid limit	Plasticity index
			Unified	AASHTO	>10 inches	3-10 inches	4	10	40	200		
					Pct	Pct						
Su: Sutphen-----	In											
	0-8	Silty clay	CH	A-7	0	0	100	100	95-100	90-95	55-70	35-45
	8-32	Silty clay	CH	A-7	0	0	100	100	95-100	90-100	55-70	35-45
	32-60	Silty clay loam	CH	A-7	0	0	100	100	95-100	90-100	50-70	30-45
Ts: Tully-----												
	0-12	Silty clay loam	CL	A-6, A-7-6	0	0	93-100	91-100	86-100	77-95	37-46	17-24
	12-21	Silty clay loam	CL	A-6, A-7-6	0	0	93-100	91-100	86-100	77-95	39-48	18-25
	21-31	Silty clay	CH, CL	A-7-6	0	0	93-100	91-100	86-100	82-95	48-62	25-36
	31-40	Silty clay	CH, CL	A-7-6	0	0	93-100	91-100	86-100	82-95	48-62	25-36
	40-52	Silty clay	CH, CL	A-7-6	0	0	93-100	91-100	86-100	82-95	48-62	25-36
	52-60	Silty clay	CH, CL	A-7-6	0	0	93-100	91-100	86-100	77-95	44-53	22-29
Tt: Tully, eroded--												
	0-7	Silty clay loam	CH, CL, MH, ML	A-6, A-7	0	0	100	75-100	75-100	70-95	35-55	10-25
	7-51	Silty clay	CH, CL	A-7	0	0	90-100	70-100	65-100	55-95	40-65	20-40
	51-60	Silty clay	CH, CL, SC	A-7	0	0	90-100	50-100	45-100	35-100	40-65	20-40
Tu: Tully-----												
	0-10	Silty clay loam	CH, CL, MH, ML	A-6, A-7	0	0	100	75-100	75-100	70-95	35-55	10-25
	10-51	Silty clay	CH, CL	A-7	0	0	90-100	70-100	65-100	55-95	40-65	20-40
	51-60	Silty clay	CH, CL, SC	A-7	0	0	90-100	50-100	45-100	35-100	40-65	20-40
Tv: Tully, eroded--												
	0-7	Silty clay loam	CH, CL, MH, ML	A-6, A-7	0	0	100	75-100	75-100	70-95	35-55	10-25
	7-51	Silty clay	CH, CL	A-7	0	0	90-100	70-100	65-100	55-95	40-65	20-40
	51-60	Silty clay	CH, CL, SC	A-7	0	0	90-100	50-100	45-100	35-100	40-65	20-40
W: Water-----	---	---	---	---	---	---	---	---	---	---	---	---
Wm: Wymore-----												
	0-13	Silty clay loam	CH, CL, MH, ML	A-6, A-7	0	0	100	100	95-100	95-100	35-55	11-25
	13-33	Silty clay	CH	A-7	0	0	100	100	95-100	95-100	55-70	30-42
	33-64	Silty clay loam	CH, CL	A-6, A-7	0	0	100	100	95-100	85-100	35-55	20-35
Wn: Wymore-----												
	0-13	Silty clay loam	CH, CL, MH, ML	A-6, A-7	0	0	100	100	95-100	95-100	35-55	11-25
	13-33	Silty clay	CH	A-7	0	0	100	100	95-100	95-100	55-70	30-42
	33-64	Silty clay loam	CH, CL	A-6, A-7	0	0	100	100	95-100	85-100	35-55	20-35
Wo: Wymore, eroded-												
	0-7	Silty clay loam	CH, CL, MH, ML	A-6, A-7	0	0	100	100	95-100	95-100	35-55	11-25
	7-33	Silty clay	CH	A-7	0	0	100	100	95-100	95-100	55-70	30-42
	33-64	Silty clay loam	CH, CL	A-7, A-6	0	0	100	100	95-100	85-100	35-55	20-35
Wr: Wymore-----												
	0-13	Silty clay loam	CH, CL, MH, ML	A-6, A-7	0	0	100	100	95-100	95-100	35-55	11-25
	13-33	Silty clay	CH	A-7	0	0	100	100	95-100	95-100	55-70	30-42
	33-64	Silty clay loam	CH, CL	A-6, A-7	0	0	100	100	95-100	85-100	35-55	20-35
Ws: Wymore, eroded-												
	0-7	Silty clay loam	CH, CL, MH, ML	A-6, A-7	0	0	100	100	95-100	95-100	35-55	11-25
	7-33	Silty clay	CH	A-7	0	0	100	100	95-100	95-100	55-70	30-42
	33-60	Silty clay loam	CH, CL	A-6, A-7	0	0	100	100	95-100	85-100	35-55	20-35

Physical Properties table shows estimates of some physical characteristics and features that affect soil behavior. These estimates are given for the layers of each soil in the survey area. The estimates are based on field observations and on test data for these and similar soils.

Depth to the upper and lower boundaries of each layer is indicated.

Particle size is the effective diameter of a soil particle as measured by sedimentation, sieving, or micrometric methods. Particle sizes are expressed as classes with specific effective diameter class limits. The broad classes are sand, silt, and clay, ranging from the larger to the smaller.

Sand as a soil separate consists of mineral soil particles that are 0.05 millimeter to 2 millimeters in diameter. In this table, the estimated sand content of each soil layer is given as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter.

Silt as a soil separate consists of mineral soil particles that are 0.002 to 0.05 millimeter in diameter. In this table, the estimated silt content of each soil layer is given as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter.

Clay as a soil separate consists of mineral soil particles that are less than 0.002 millimeter in diameter. In this table, the estimated clay content of each soil layer is given as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter.

The content of sand, silt, and clay affects the physical behavior of a soil. Particle size is important for engineering and agronomic interpretations, for determination of soil hydrologic qualities, and for soil classification.

The amount and kind of clay affect the fertility and physical condition of the soil and the ability of the soil to adsorb cations and to retain moisture. They influence shrink-swell potential, permeability, plasticity, the ease of soil dispersion, and other soil properties. The amount and kind of clay in a soil also affect tillage and earth moving operations.

Moist bulk density is the weight of soil (oven-dry) per unit volume. Volume is measured when the soil is at field moisture capacity, that is, the moisture content at 1/3- or 1/10-bar (33kPa or 10kPa) moisture tension. Weight is determined after the soil is dried at 105 degrees C. In the table, the estimated moist bulk density of each soil horizon is expressed in grams per cubic centimeter of soil material that is less than 2 millimeters in diameter. Bulk density data are used to compute shrink-swell potential, available water capacity, total pore space, and other soil properties. The moist bulk density of a soil indicates the pore space available for water and roots. Depending on soil texture, a bulk density of more than 1.4 can restrict water storage and root penetration. Moist bulk density is influenced by texture, kind of clay, content of organic matter, and soil structure.

Permeability (K_{sat}) refers to the ability of a soil to transmit water or air. The term "permeability," as used in soil surveys, indicates saturated hydraulic conductivity (K_{sat}). The estimates in the table indicate the rate of water movement, in inches per hour, when the soil is saturated. They are based on soil characteristics observed in the field, particularly structure, porosity, and texture. Permeability is considered in the design of soil drainage systems and septic tank absorption fields.

Available water capacity refers to the quantity of water that the soil is capable of storing for use by plants. The capacity for water storage is given in inches of water per inch of soil for each soil layer. The capacity varies, depending on soil properties that affect retention of water. The most important properties are the content of organic matter, soil texture, bulk density, and soil structure. Available water capacity is an important factor in the choice of plants or crops to be grown and in the design and management of irrigation systems. Available water capacity is not an estimate of the quantity of water actually available to plants at any given time.

Linear extensibility refers to the change in length of an unconfined clod as moisture content is decreased from a moist to a dry state. It is an expression of the volume change between the water content of the clod at 1/3- or 1/10-bar tension (33kPa or 10kPa tension) and oven dryness. The volume change is reported in the table as percent change for the whole soil. Volume change is influenced by the amount and type of clay minerals in the soil.

Linear extensibility is used to determine the shrink-swell potential of soils. The shrink-swell potential is low if the soil has a linear extensibility of less than 3 percent; moderate if 3 to 6 percent; high if 6 to 9 percent; and very high if more than 9 percent. If the linear extensibility is more than 3, shrinking and swelling can cause damage to buildings, roads, and other structures and to plant roots. Special design commonly is needed.

Organic matter is the plant and animal residue in the soil at various stages of decomposition. In Physical Properties table, the estimated content of organic matter is expressed as a percentage, by weight, of the soil material that is less than 2 millimeters in diameter. The content of organic matter in a soil can be maintained by returning crop residue to the soil. Organic matter has a positive effect on available water capacity, water infiltration, soil organism activity, and tilth. It is a source of nitrogen and other nutrients for crops and soil organisms.

Erosion factors are shown in the Physical Properties table as the K factor (K_w and K_f) and the T factor. Erosion factor K indicates the susceptibility of a soil to sheet and rill erosion by water. Factor K is one of six factors used in the Universal Soil Loss Equation (USLE) and the Revised Universal Soil Loss Equation (RUSLE) to predict the average annual rate of soil loss by sheet and rill erosion in tons per acre per year. The estimates are based primarily on percentage of silt, sand, and organic matter and on soil structure and permeability. Values of K range from 0.02 to 0.69. Other factors being equal, the higher the value, the more susceptible the soil is to sheet and rill erosion by water.

Erosion factor K_w indicates the erodibility of the whole soil. The estimates are modified by the presence of rock fragments.

Erosion factor K_f indicates the erodibility of the fine-earth fraction, or the material less than 2 millimeters in size.

Erosion factor T is an estimate of the maximum average annual rate of soil erosion by wind or water that can occur without affecting crop productivity over a sustained period. The rate is in tons per acre per year.

Wind erodibility groups are made up of soils that have similar properties affecting their susceptibility to

wind erosion in cultivated areas. The soils assigned to group 1 are the most susceptible to wind erosion, and those assigned to group 8 are the least susceptible. The groups are as follows:

1. Coarse sands, sands, fine sands, and very fine sands.
2. Loamy coarse sands, loamy sands, loamy fine sands, loamy very fine sands, ash material, and sapric soil material.
3. Coarse sandy loams, sandy loams, fine sandy loams, and very fine sandy loams.
- 4L. Calcareous loams, silt loams, clay loams, and silty clay loams.
4. Clays, silty clays, noncalcareous clay loams, and silty clay loams that are more than 35 percent clay.
5. Noncalcareous loams and silt loams that are less than 20 percent clay and sandy clay loams, sandy clays, and hemic soil material.
6. Noncalcareous loams and silt loams that are more than 20 percent clay and noncalcareous clay loams that are less than 35 percent clay.
7. Silts, noncalcareous silty clay loams that are less than 35 percent clay, and fibric soil material.
8. Soils that are not subject to wind erosion because of coarse fragments on the surface or because of surface wetness.

Wind erodibility index is a numerical value indicating the susceptibility of soil to wind erosion, or the tons per acre per year that can be expected to be lost to wind erosion. There is a close correlation between wind erosion and the texture of the surface layer, the size and durability of surface clods, rock fragments, organic matter, and a calcareous reaction. Soil moisture and frozen soil layers also influence wind erosion.

Explanation of Wind Erodibility Groups

Soil erodibility by wind is directly related to the percentage of dry non-erodible surface soil aggregates larger than 0.84 mm in diameter. From this percentage, the wind erodibility index (I-factor) is determined. The I-factor is an expression of the stability of these soil aggregates against breakdown by tillage and abrasion from wind erosion. Soils are placed in Wind Erodibility Groups (WEG) having similar percentages of dry soil aggregates larger than 0.84 mm as shown in the following table.

WEG	Properties of Soil Surface Layer	Dry Soil Aggregates >0.84mm Percent	Wind Erodibility Index T/Ac/Yr (I)
1	Very fine sand, fine sand, sand, or coarse sand	1	310 1/
		2	250
		3	220
		5	180
		7	160
		10	134
		25	86
2	Loamy very fine sand, loamy fine sand, loamy sand, loamy coarse sand, organic soil materials.	10	134
3	Very fine sandy loam, fine sandy loam, sandy loam, or coarse sandy loam.	25	86
4	Clay, silty clay, non-calcareous clay loam, or silty clay loam with >35 percent clay content.	25	86
4L	Calcareous 2/ loam, silt loam, clay loam, or silty clay loam.	25	86
5	Non-calcareous loam and silt loam with <20 percent clay content, or sandy clay loam, sandy clay, and hemic 3/ organic soil materials.	40	56
6	Non-calcareous loam and silt loam with >20 percent clay content, or non-calcareous clay loam with <35 percent clay content.	45	48
7	Silt, non-calcareous silty clay loam with >35 percent clay content and fibric 3/ organic soil material.	50	38
8	Soils not suitable for cultivation due to coarse fragments or wetness; wind erosion is not a problem.	--	0

1/ The "I" values for WEG 1 vary from 160 for coarse sands to 310 for very fine sands. Use an "I" of 220 as an average figure. For coarser sand that has gravel, use a lower figure. For a soil that has no gravel and very fine sand, use a higher figure. (Modification for coarse fragments is preparation.)

2/ Calcareous is a strongly or violently effervescent reaction to cold dilute (1N) HCL.

3/ See Soil Taxonomy for definition.

PHYSICAL PROPERTIES OF THE SOILS--Continued
 Riley County, Kansas: Published

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permeability (Ksat)	Available water capacity	Linear extensibility	Organic matter	Erosion factors			Wind erodibility group	Wind erodibility index
										K	Kf	T		
	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
027CS: Crete-----	0-6	7	66	24-35	1.20-1.40	0.20-0.60	0.21-0.23	3.9-7.0	2.0-4.0	.37	.37	5	6	48
	6-11	9	60	27-35	1.20-1.40	0.20-0.60	0.21-0.23	5.0-7.0	1.0-3.0	.37	.37			
	11-27	3	52	35-55	1.10-1.30	0.06-0.20	0.12-0.20	7.0-12.0	0.5-2.0	---	---			
	27-40	3	59	30-45	1.10-1.30	0.06-0.20	0.12-0.20	5.0-9.0	0.5-2.0	---	---			
	40-60	4	60	25-40	1.10-1.30	0.20-0.60	0.12-0.20	4.1-8.0	0.2-0.8	---	---			
027CX: Crete-----	0-7	20	49	27-35	1.20-1.40	0.20-0.60	0.21-0.23	4.6-6.7	1.0-3.0	.37	.37	5	7	38
	7-31	7	48	35-55	1.10-1.30	0.06-0.20	0.11-0.20	6.7-11.7	0.5-1.0	.37	.37			
	31-60	20	48	25-40	1.20-1.40	0.20-2.00	0.18-0.22	4.1-7.7	0.1-0.5	.37	.37			
027HN: Hobbs-----	0-8	11	68	15-27	1.20-1.40	0.60-2.00	0.21-0.24	1.6-4.1	2.0-4.0	.32	.32	5	6	48
	8-24	11	68	15-27	1.20-1.40	0.60-2.00	0.00-0.20	1.6-4.1	0.5-1.0	.32	.32			
	24-44	10	68	15-30	1.20-1.40	0.60-2.00	0.18-0.22	1.6-4.7	0.5-1.0	---	---			
	44-60	10	68	15-30	1.20-1.40	0.60-2.00	0.18-0.22	1.6-4.7	0.5-1.0	---	---			
027KS: Kipson-----	0-8	1-20	50-70	27-35	1.30-1.40	0.60-2.00	0.17-0.20	3.0-5.9	1.0-3.0	.32	.49	2	4L	86
	8-18	1-20	40-65	18-35	1.35-1.50	0.60-2.00	0.15-0.20	3.0-5.9	0.5-1.0	.32	.43			
	18-22	---	---	---	---	---	---	---	---	---	---			
Sogn-----	0-12	1-20	50-70	27-35	1.15-1.20	0.60-2.00	0.17-0.22	3.0-5.9	0.5-1.0	.32	.49	1	4L	86
	12-16	---	---	---	---	---	---	---	---	---	---			
061BE: Benfield----	0-5	8	61	27-35	1.30-1.50	0.20-0.60	0.21-0.24	4.1-5.8	2.0-6.0	.37	.37	3	7	38
	5-10	7	54	35-45	1.35-1.50	0.06-0.20	0.11-0.20	5.8-7.9	1.0-2.0	.24	.37			
	10-19	7	48	35-50	1.35-1.50	0.06-0.20	0.11-0.20	5.8-8.9	1.0-2.0	---	---			
	19-34	5	45	35-55	1.35-1.50	0.06-0.20	0.08-0.16	5.8-10.0	0.5-1.5	---	---			
	34-38	5	45	40-60	1.35-1.50	0.06-0.20	0.08-0.16	6.8-11.0	0.0-1.0	---	---			
	38-56	---	---	---	---	---	---	---	---	---	---			
Florence----	0-5	12	61	24-35	1.25-1.35	0.60-2.00	0.05-0.20	3.9-6.7	4.0-8.0	.15	.24	3	8	0
	5-14	7	48	35-55	1.35-1.55	0.20-0.60	0.03-0.11	6.7-11.7	2.0-6.0	.15	.24			
	14-48	10	20-45	50-80	1.35-1.55	0.20-0.60	0.03-0.12	6.0-11.0	0.8-3.0	---	---			
	48-56	10	20-45	50-80	1.35-1.55	0.20-0.60	0.03-0.12	6.0-11.0	0.5-1.0	---	---			
	56-60	---	---	---	---	---	---	---	---	---	---			
061CF: Clime-----	0-12	8	56	32-40	1.00-1.45	0.20-0.60	0.21-0.23	5.1-6.8	2.0-4.0	.24	.32	3	4	86
	12-26	6	47	35-50	1.00-1.50	0.06-0.20	0.12-0.18	5.8-8.9	0.5-1.0	.24	.28			
	26-30	8	50	35-50	1.00-1.50	0.06-0.20	0.10-0.14	5.8-8.9	0.0-0.5	---	---			
	30-34	---	---	---	---	---	---	---	---	---	---			
Sogn-----	0-9	20	49	27-35	1.35-1.45	0.60-2.00	0.21-0.23	4.1-5.8	1.0-3.0	.24	.32	1	4L	86
	9-13	---	---	---	---	---	---	---	---	---	---			
061CR: Crete-----	0-6	7	63	24-35	1.20-1.40	0.20-0.60	0.21-0.23	3.9-7.0	2.0-4.0	.37	.37	5	7	38
	6-14	9	60	27-35	1.20-1.40	0.20-0.60	0.21-0.23	5.0-7.0	1.0-3.0	.37	.37			
	14-30	3	52	35-55	1.10-1.30	0.06-0.20	0.12-0.20	7.0-12.0	0.5-2.0	---	---			
	30-42	3	59	30-45	1.10-1.30	0.06-0.20	0.12-0.20	5.0-9.0	0.2-0.8	---	---			
	42-60	4	60	25-40	1.10-1.30	0.20-0.60	0.12-0.20	4.1-8.0	0.0-0.5	---	---			
061CS: Crete-----	0-6	7	63	24-35	1.20-1.40	0.20-0.60	0.21-0.23	3.9-7.0	2.0-4.0	.37	.37	5	7	38
	6-11	9	60	27-35	1.20-1.40	0.20-0.60	0.21-0.23	5.0-7.0	1.0-3.0	.37	.37			
	11-27	3	52	35-55	1.10-1.30	0.06-0.20	0.12-0.20	7.0-12.0	0.5-2.0	---	---			
	27-40	3	59	30-45	1.10-1.30	0.06-0.20	0.12-0.20	5.0-9.0	0.5-2.0	---	---			
	40-60	4	60	25-40	1.10-1.30	0.20-0.60	0.12-0.20	4.1-8.0	0.2-0.8	---	---			
061EU: Eudora-----	0-7	12	69	10-20	1.00-1.50	0.60-2.00	0.20-0.24	0.5-2.6	1.0-3.0	.32	.32	5	5	56
	7-14	14	73	10-20	1.20-1.50	0.60-2.00	0.20-0.24	0.5-2.6	1.0-3.0	.32	.32			
	14-19	21	69	5-18	1.20-1.50	0.60-2.00	0.20-0.22	0.0-2.2	0.0-2.0	---	---			
	19-26	22	70	5-18	1.30-1.50	2.00-6.00	0.14-0.22	0.0-2.2	0.0-1.0	---	---			
	26-60	63	29	5-18	1.30-1.50	2.00-6.00	0.14-0.22	0.0-2.2	0.0-0.5	---	---			
061HE: Haynie-----	0-10	11	69	15-25	1.20-1.35	0.60-2.00	0.18-0.23	1.6-3.7	1.0-3.0	.32	.32	5	4L	86
	10-60	30-65	26	10-18	1.20-1.35	0.60-2.00	0.18-0.23	0.5-2.2	0.0-1.0	.43	.43			
061KA: Kahola-----	0-24	10	68	18-27	1.35-1.40	0.60-2.00	0.21-0.24	2.2-4.1	2.0-4.0	.32	.32	5	6	48
	24-36	10	68	18-27	1.35-1.40	0.60-2.00	0.21-0.24	2.2-4.1	1.0-4.0	.32	.32			
	36-44	9	64	18-35	1.35-1.40	0.60-2.00	0.17-0.22	2.2-5.8	0.5-2.0	---	---			
	44-60	9	64	18-35	1.35-1.40	0.60-2.00	0.17-0.22	2.2-5.8	0.5-1.5	---	---			
061KB: Kahola-----	0-24	10	68	18-27	1.35-1.40	0.60-2.00	0.21-0.24	2.2-4.1	2.0-4.0	.32	.32	5	6	48
	24-36	10	68	18-27	1.35-1.40	0.60-2.00	0.21-0.24	2.2-4.1	1.0-4.0	.32	.32			
	36-44	9	64	18-35	1.35-1.40	0.60-2.00	0.17-0.22	2.2-5.8	0.5-2.0	---	---			
	44-60	9	64	18-35	1.35-1.40	0.60-2.00	0.17-0.22	2.2-5.8	0.5-1.5	---	---			
061RE: Reading-----	0-8	7	64	27-30	1.35-1.40	0.20-0.60	0.21-0.23	3.0-4.7	2.0-4.0	.32	.32	5	7	38
	8-20	7	64	27-30	1.35-1.40	0.20-0.60	0.21-0.23	3.0-4.7	2.0-4.0	.32	.32			
	20-52	7	61	30-35	1.40-1.50	0.20-0.60	0.18-0.20	4.7-5.8	0.5-3.0	---	---			
	52-60	8	56	30-40	1.40-1.50	0.20-0.60	0.13-0.20	4.7-6.8	0.5-1.0	---	---			
061TO: Tully-----	0-12	10	57	28-38	1.35-1.45	0.20-0.60	0.21-0.23	4.3-6.4	3.0-6.0	.37	.37	5	7	38
	12-21	10	55	30-40	1.35-1.45	0.20-0.60	0.18-0.20	4.7-6.8	2.0-4.0	.37	.37			
	21-31	8	49	40-55	1.40-1.50	0.06-0.20	0.10-0.15	6.8-10.0	1.0-3.0	---	---			
	31-40	6	48	40-55	1.40-1.50	0.06-0.20	0.10-0.15	6.8-10.0	0.8-2.0	---	---			
	40-52	7	48	40-55	1.40-1.50	0.06-0.20	0.10-0.15	6.8-10.0	0.5-1.0	---	---			
	52-60	8	52	35-45	1.40-1.50	0.06-0.20	0.07-0.12	5.8-7.0	0.2-1.0	---	---			

PHYSICAL PROPERTIES OF THE SOILS--Continued
Riley County, Kansas: Published

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permeability (Ksat)	Available water capacity	Linear extensibility	Organic matter	Erosion factors			Wind erodibility group	Wind erodibility index
										K	Kf	T		
	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
117PA: Pawnee-----	0-13 13-36 36-60	20-45 15-40 20-55	20-50 15-40 20-50	30-38 40-50 25-35	1.40-1.50 1.50-1.70 1.40-1.50	0.20-0.60 0.06-0.20 0.06-0.20	0.17-0.19 0.09-0.11 0.14-0.16	3.0-5.9 6.0-8.9 6.0-8.9	2.0-4.0 0.5-1.5 0.1-0.5	.37 .37 .37	.37 .37 .37	5	6	48
117PB: Pawnee-----	0-13 13-36 36-60	20-45 15-40 20-50	20-50 15-40 20-50	30-38 40-50 25-35	1.40-1.50 1.50-1.70 1.40-1.50	0.20-0.60 0.06-0.20 0.06-0.20	0.17-0.19 0.09-0.11 0.14-0.16	3.0-5.9 6.0-8.9 6.0-8.9	2.0-4.0 0.5-1.5 0.1-0.5	.37 .37 .37	.37 .37 .37	5	6	48
149HS: Haynie-----	0-9 9-60	10-60 10-50	30-60 40-75	5-18 5-18	1.20-1.35 1.20-1.35	0.60-2.00 0.60-2.00	0.18-0.23 0.18-0.23	0.0-2.9 0.0-2.9	1.0-1.5 0.1-0.3	.37 .37	.37 .37	5	3	86
Sarpy-----	0-6 6-60	70-95 70-95	1-20 1-20	2-5 2-5	1.20-1.50 1.20-1.50	5.95-19.98 5.95-19.98	0.05-0.09 0.05-0.09	0.0-2.9 0.0-2.9	0.1-1.0 0.1-0.5	.15 .15	.15 .15	5	1	250
149PS: Paxico-----	0-42 42-60	1-20 55-90	50-80 5-30	5-18 2-15	1.20-1.50 1.40-1.60	0.60-2.00 2.00-6.00	0.15-0.23 0.10-0.17	0.0-2.9 0.0-2.9	1.0-3.0 0.2-1.5	.37 .17	.37 .17	5	4L	86
149SF: Sarpy-----	0-6 6-60	70-95 70-95	1-20 1-20	2-5 2-5	1.20-1.50 1.20-1.50	5.95-19.98 5.95-19.98	0.05-0.09 0.05-0.09	0.0-2.9 0.0-2.9	0.1-1.0 0.1-0.5	.15 .15	.15 .15	5	1	220
197CM: Clime-----	0-5 5-18 18-32 32-36	5-15 5-15 5-15	40-60 30-50 30-50	32-40 35-60 35-50	1.35-1.45 1.35-1.50 1.40-1.50	0.20-0.60 0.06-0.20 0.06-0.20	0.21-0.23 0.12-0.18 0.10-0.14	3.0-5.9 6.0-8.9 6.0-8.9	2.0-4.0 1.0-3.0 0.5-1.5	.32 .28 .32	.32 .28 .32	3	4	86
197FL: Florence-----	0-14 14-18 18-56 56-60	1-20 1-15 1-15	50-75 50-65 50-80	24-35 24-40 50-80	1.25-1.35 1.35-1.45 1.35-1.55	0.60-2.00 0.60-2.00 0.20-0.60	0.05-0.20 0.03-0.20 0.03-0.12	3.0-5.9 6.0-8.9 6.0-8.9	4.0-8.0 2.0-6.0 0.7-2.0	.24 .24 .24	.64 .64 .64	3	8	0
Labette-----	0-7 7-35 35-39	1-15 1-10	50-70 40-60	18-27 35-55	1.30-1.40 1.40-1.50	0.60-2.00 0.06-0.20	0.22-0.24 0.12-0.19	0.0-2.9 6.0-8.9	2.0-4.0 1.0-2.0	.32 .37	.32 .55	2	6	48
197IB: Irwin-----	0-12 12-42 42-60	3-10 2-10 2-8	40-65 35-50 35-55	28-35 40-60 35-55	1.35-1.45 1.40-1.50 1.40-1.50	0.20-0.60 0.00-0.06 0.06-0.20	0.21-0.23 0.10-0.13 0.09-0.19	3.0-5.9 6.0-8.9 6.0-8.9	2.0-4.0 1.0-3.0 0.5-2.0	.32 .28 .32	.32 .28 .32	5	7	38
197ID: Irwin-----	0-6 6-13 13-30 30-41 41-72	10 10 5 5 7	58 58 35-45 35-45 48	28-35 28-35 40-60 40-60 35-50	1.35-1.45 1.35-1.45 1.40-1.50 1.40-1.50 1.40-1.50	0.20-0.60 0.20-0.60 0.00-0.06 0.00-0.06 0.06-0.20	0.21-0.23 0.21-0.23 0.10-0.13 0.10-0.13 0.09-0.19	4.3-5.8 4.3-5.8 6.8-11.0 6.8-11.0 5.8-10.0	2.0-4.0 1.5-3.0 0.8-2.0 0.2-1.0 0.2-0.8	.37 .37 --- --- ---	.37 .37 --- --- ---	5	7	38
197IV: Ivan-----	0-36 36-60	1-10 1-10	50-75 45-75	16-27 18-35	1.30-1.45 1.35-1.55	0.60-2.00 0.60-2.00	0.22-0.24 0.19-0.22	1.5-4.5 3.0-5.9	2.0-4.0 1.0-2.0	.32 .32	.32 .32	5	4L	86
197IX: Ivan-----	0-40 40-60	1-10 1-10	50-75 45-75	28-35 18-35	1.30-1.45 1.35-1.55	0.60-2.00 0.60-2.00	0.21-0.23 0.19-0.22	3.0-5.9 3.0-5.9	2.0-4.0 1.0-2.0	.32 .32	.32 .32	5	4L	86
197PN: Pawnee-----	0-14 14-34 34-72	20-45 20-40 20-55	20-50 40-50 20-40	30-38 40-50 25-35	1.40-1.50 1.50-1.70 1.40-1.50	0.20-0.60 0.06-0.20 0.06-0.20	0.17-0.19 0.09-0.11 0.14-0.16	3.0-5.9 6.0-8.9 6.0-8.9	2.0-4.0 0.5-1.5 0.1-0.5	.37 .37 .37	.37 .37 .37	5	6	48
197WE: Wamego-----	0-9 9-20 20-25 25-36	2-10 2-22 2-22	55-70 50-65 50-65	27-32 35-42 35-42	1.30-1.40 1.50-1.70 1.50-1.70	0.60-2.00 0.06-0.20 0.06-0.20	0.21-0.23 0.12-0.20 0.12-0.20	0.0-2.9 3.0-5.9 3.0-5.9	2.0-4.0 1.0-2.0 0.5-1.0	.32 .43 .43	.32 .43 .43	3	7	38
201CS: Crete-----	0-6 6-9 9-32 32-40 40-60	7 9 3 3 4	66 60 52 59 60	24-35 27-35 35-55 30-45 25-40	1.20-1.40 1.20-1.40 1.10-1.30 1.10-1.30 1.10-1.30	0.20-0.60 0.20-0.60 0.06-0.20 0.06-0.20 0.20-0.60	0.21-0.23 0.21-0.23 0.12-0.20 0.12-0.20 0.12-0.20	3.9-7.0 5.0-7.0 7.0-12.0 5.0-9.0 4.1-8.0	2.0-4.0 1.0-3.0 0.5-2.0 0.5-2.0 0.2-0.8	.37 .37 --- --- ---	.37 .37 --- --- ---	5	7	38
201CX: Crete, eroded	0-5 5-30 30-60	1-20 1-20 1-20	50-70 40-60 50-75	27-35 35-55 23-40	1.20-1.40 1.10-1.30 1.20-1.40	0.20-0.60 0.00-0.60 0.20-2.00	0.21-0.23 0.12-0.20 0.18-0.22	6.0-8.9 6.0-8.9 6.0-8.9	1.5-3.5 1.0-3.0 0.1-0.3	.37 .37 .37	.37 .37 .37	5	7	38
201KS: Kipson-----	0-12 12-18 18-22	1-20 1-20	50-70 40-65	27-35 18-35	1.30-1.40 1.35-1.50	0.60-2.00 0.60-2.00	0.17-0.20 0.15-0.20	3.0-5.9 3.0-5.9	1.0-3.0 0.5-1.0	.32 .43	.49 .43	2	4L	86
Sogn-----	0-8 8-16 16-20	1-20 1-20	50-75 45-70	18-27 18-35	1.15-1.20 1.15-1.20	0.60-2.00 0.60-2.00	0.19-0.24 0.14-0.19	3.0-5.9 3.0-5.9	2.0-4.0 1.0-3.0	.32 .24	.37 .43	1	4L	86
201LC: Lancaster----	0-9 9-24 24-29 >29	43 34 57	38 36 18	12-26 18-35 12-30	1.35-1.45 1.35-1.50 1.40-1.55	0.60-2.00 0.60-2.00 0.60-2.00	0.17-0.22 0.15-0.19 0.15-0.19	0.9-3.9 2.2-5.8 0.9-4.7	1.0-4.0 1.0-2.0 0.5-1.0	.24 .24 ---	.28 .28 ---	3	6	48
Ad: Ivan-----	0-7 7-26 26-39 39-64	9 7 7 7	66 64 64 64	18-27 18-35 18-35 18-35	1.30-1.45 1.30-1.45 1.35-1.55 1.35-1.55	0.60-2.00 0.60-2.00 0.60-2.00 0.60-2.00	0.22-0.24 0.22-0.24 0.17-0.22 0.17-0.22	2.2-4.1 2.2-5.8 2.2-5.8 2.2-5.8	2.0-4.0 1.0-3.0 0.1-1.0 0.1-1.0	.32 .32 .43 .43	.32 .32 .43 .43	5	4L	86

PHYSICAL PROPERTIES OF THE SOILS--Continued
Riley County, Kansas: Published

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permeability (Ksat)	Available water capacity	Linear extensibility	Organic matter	Erosion factors			Wind erodibility group	Wind erodibility index
										K	Kf	T		
	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
AED: Arents, Earthen Dam-														
BE: Benfield-----	0-10 10-32 32-36	1-10 1-10	50-65 35-60	27-35 35-50	1.30-1.40 1.35-1.45	0.20-0.60 0.06-0.20	0.21-0.24 0.11-0.20	3.0-5.9 6.0-8.9	1.0-4.0 1.0-2.0	.37 .37	.43 .55	3	7	38
Bf: Benfield-----	0-6 6-30 30-35 35-39	1-10 1-10 1-10	50-65 35-60 35-50	27-35 35-50 35-50	1.30-1.40 1.35-1.45 1.35-1.45	0.20-0.60 0.06-0.20 0.06-0.20	0.21-0.24 0.11-0.20 0.11-0.20	3.0-5.9 6.0-8.9 6.0-8.9	1.0-4.0 1.0-2.0 0.1-0.3	.37 .37 .49	.43 .55 .49	3	7	38
Florence-----	0-5 5-10 10-14 14-30 30-34	1-20 1-20 1-20 1-30	50-70 50-65 40-60 20-50	24-35 24-35 35-55 50-80	1.25-1.35 1.35-1.45 1.35-1.55 1.35-1.55	0.60-2.00 0.60-2.00 0.20-0.60 0.20-0.60	0.05-0.20 0.03-0.20 0.03-0.11 0.03-0.12	3.0-5.9 3.0-5.9 3.0-5.9 6.0-8.9	2.0-4.0 1.0-3.0 0.5-1.5 0.1-0.5	.24 .64 .24 .64	.64 .64 .64 .64	3	8	0
Bk: Wymore-----	0-13 13-33 33-64	1-10 1-10 1-10	50-75 40-60 50-70	30-40 42-55 27-40	1.15-1.20 1.10-1.20 1.15-1.25	0.20-0.60 0.06-0.20 0.20-0.60	0.21-0.23 0.11-0.14 0.18-0.20	3.0-5.9 6.0-8.9 6.0-8.9	2.0-4.0 0.8-2.0 0.2-0.8	.37 .37 .37	.37 .37 .37	5	7	38
Kennebec-----	0-18 18-60	1-10 1-10	50-75 45-70	22-27 24-32	1.15-1.35 1.35-1.40	0.60-2.00 0.60-2.00	0.22-0.24 0.20-0.22	3.0-5.9 3.0-5.9	2.0-6.0 0.5-1.5	.32 .43	.32 .43	5	6	48
BOP: Borrow Pits--	---													
Ca: Carr-----	0-9 9-17 17-28 28-60	64 64 64 64	26 26 26 26	5-15 5-15 5-15 5-15	1.50-1.75 1.50-1.75 1.50-1.75 1.50-1.75	2.00-6.00 2.00-6.00 2.00-6.00 2.00-6.00	0.16-0.18 0.15-0.17 0.15-0.17 0.11-0.19	0.0-1.6 0.0-1.6 0.0-1.6 0.0-1.6	0.5-2.0 0.5-1.5 0.0-0.5 0.0-0.5	.24 .24 .24 .24	.24 .24 .24 .24	4	3	86
Sarpy-----	0-5 5-60	80 96	17 1	2-5 2-5	1.20-1.50 1.20-1.50	5.95-19.98 5.95-19.98	0.10-0.12 0.05-0.11	0.0-0.0 0.0-0.0	0.1-1.0 0.0-0.2	.17 .17	.17 .17	5	2	134
Ch: Chase-----	0-7 7-13 13-40 40-50 50-60	20 17 7 8 8	49 48 48 52 52	28-35 30-38 38-55 35-50 28-45	1.30-1.45 1.30-1.45 1.35-1.45 1.35-1.45 1.35-1.45	0.20-0.60 0.20-0.60 0.06-0.20 0.06-0.20 0.06-0.20	0.21-0.23 0.21-0.23 0.09-0.20 0.10-0.20 0.10-0.20	4.9-6.7 5.4-7.4 7.4-11.7 6.7-10.4 4.9-9.2	2.0-4.0 1.0-3.0 0.5-1.5 0.1-1.0 0.1-1.0	.37 .37 .28 .28 .28	.37 .37 .28 .28 .28	5	7	38
Cs: Clime-----	0-12 12-30 30-34	1-15 1-15	40-70 30-50	32-40 35-60	1.35-1.45 1.35-1.50	0.20-0.60 0.06-0.20	0.21-0.23 0.12-0.18	3.0-5.9 3.0-5.9	2.0-4.0 0.3-0.7	.32 .28	.32 .28	3	4	86
Sogn-----	0-9 9-13	1-15	50-70	27-35	1.15-1.20	0.60-2.00	0.17-0.22	3.0-5.9	1.0-3.0	.32	.32	1	4L	86
CT: Crete-----	0-7 7-11 11-30 30-40 40-60	7 9 3 3 4	63 60 52 59 60	24-35 27-35 35-55 30-45 25-40	1.20-1.40 1.20-1.40 1.10-1.30 1.10-1.30 1.10-1.30	0.20-0.60 0.20-0.60 0.06-0.20 0.06-0.20 0.20-0.60	0.21-0.23 0.21-0.23 0.12-0.20 0.12-0.20 0.12-0.20	3.9-7.0 5.0-7.0 7.0-12.0 5.0-9.0 4.1-8.0	2.0-4.0 1.0-3.0 0.5-2.0 0.2-0.8 0.0-0.5	.37 .37 --- --- ---	.37 .37 --- --- ---	5	7	38
Dr: Dwight-----	0-4 4-17 17-43 >43	25 5 8	52 47 50	18-27 45-60 35-50	1.20-1.35 1.30-1.40 1.30-1.40	0.60-2.00 0.00-0.06 0.00-0.06	0.22-0.24 0.10-0.14 0.09-0.20	2.4-4.6 9.2-13.0 6.7-10.4	2.0-4.0 0.5-1.5 0.1-0.8	.43 .32 .32	.43 .32 .32	2	6	48
Irwin-----	0-7 7-11 11-35 35-50 50-55 >55	20 17 5 7 8	49 48 47 49 50	28-35 30-38 40-55 40-55 35-55	1.35-1.45 1.35-1.45 1.40-1.50 1.40-1.50 1.40-1.50	0.20-0.60 0.20-0.60 0.00-0.06 0.00-0.06 0.00-0.06	0.21-0.23 0.21-0.23 0.09-0.13 0.08-0.12 0.08-0.18	4.9-6.7 5.4-7.4 7.9-11.7 7.9-11.7 6.7-11.7	2.0-4.0 1.0-3.0 0.2-1.5 0.1-1.0 0.1-0.5	.37 .37 .37 .37 .37	.37 .37 .37 .37 .37	4	7	38
Dw: Dwight-----	0-4 4-17 17-43 >43	25 5 8	52 47 50	18-27 45-60 35-50	1.20-1.35 1.30-1.40 1.30-1.40	0.60-2.00 0.00-0.06 0.00-0.06	0.22-0.24 0.10-0.14 0.09-0.20	2.4-4.6 9.2-13.0 6.7-10.4	2.0-4.0 0.5-1.5 0.1-0.8	.43 .32 .32	.43 .32 .32	2	6	48
Irwin-----	0-8 8-35 35-50 50-55 >55	17 5 7 8	48 47 49 50	28-38 40-55 40-55 35-55	1.35-1.45 1.40-1.50 1.40-1.50 1.40-1.50	0.20-0.60 0.00-0.06 0.00-0.06 0.00-0.06	0.21-0.23 0.09-0.13 0.08-0.12 0.08-0.18	4.9-7.4 7.9-11.7 7.9-11.7 6.7-11.7	1.0-3.0 0.2-1.5 0.1-1.0 0.1-0.5	.37 .37 .37 .37	.37 .37 .37 .37	4	7	38
Em: Elmont-----	0-10 10-18 18-28 28-33 33-44 >44	10 7 7 7 27	68 65 60 62 42	18-27 24-30 28-35 28-42 28-42	1.30-1.40 1.30-1.40 1.30-1.45 1.40-1.55 1.40-1.55	0.60-2.00 0.60-2.00 0.20-0.60 0.20-0.60 0.20-0.60	0.22-0.24 0.18-0.22 0.15-0.20 0.11-0.20 0.10-0.20	2.2-4.1 3.5-4.7 4.3-5.8 4.3-7.2 4.3-7.2	2.0-4.0 1.0-3.0 0.5-1.5 0.1-0.8 0.1-0.8	.32 .32 .43 .43 .43	.32 .32 .43 .43 .43	5	6	48

PHYSICAL PROPERTIES OF THE SOILS--Continued
Riley County, Kansas: Published

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permeability (Ksat)	Available water capacity	Linear extensibility	Organic matter	Erosion factors			Wind erodibility group	Wind erodibility index
										K	Kf	T		
	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
En:														
Elmont-----	0-10	10	68	18-27	1.30-1.40	0.60-2.00	0.22-0.24	2.2-4.1	2.0-4.0	.32	.32	5	6	48
	10-18	7	65	24-30	1.30-1.40	0.60-2.00	0.18-0.22	3.5-4.7	1.0-3.0	.32	.32			
	18-28	7	60	28-35	1.30-1.45	0.20-0.60	0.15-0.20	4.3-5.8	0.5-1.5	.43	.43			
	28-33	7	62	28-42	1.40-1.55	0.20-0.60	0.11-0.20	4.3-7.2	0.1-0.8	.43	.43			
	33-44	27	42	28-42	1.40-1.55	0.20-0.60	0.10-0.20	4.3-7.2	0.1-0.8	.43	.43			
	>44													
Clime-----	0-8	20	48	30-38	1.35-1.45	0.20-0.60	0.21-0.23	4.7-6.4	2.0-4.0	.32	.32	3	4	86
	8-12	17	48	32-38	1.35-1.45	0.20-0.60	0.21-0.23	5.1-6.4	1.0-3.0	.32	.32			
	12-20	7	54	35-45	1.35-1.50	0.06-0.20	0.12-0.20	5.8-7.9	0.5-1.5	.28	.28			
	20-30	7	54	35-55	1.35-1.50	0.06-0.20	0.09-0.20	5.8-9.9	0.1-0.8	.28	.28			
	>30													
Eu:														
Eudora-----	0-7	12	69	10-20	1.00-1.50	0.60-2.00	0.20-0.24	0.5-2.6	1.0-3.0	.32	.32	5	5	56
	7-14	14	73	10-20	1.20-1.50	0.60-2.00	0.20-0.24	0.5-2.6	1.0-3.0	.32	.32			
	14-19	21	69	5-18	1.20-1.50	0.60-2.00	0.20-0.22	0.0-2.2	0.0-2.0	---	---			
	19-26	22	70	5-18	1.30-1.50	2.00-6.00	0.14-0.22	0.0-2.2	0.0-1.0	---	---			
	26-60	63	29	5-18	1.30-1.50	2.00-6.00	0.14-0.22	0.0-2.2	0.0-0.5	---	---			
Ga:														
Geary-----	0-8	10	68	15-27	1.30-1.40	0.60-2.00	0.22-0.24	1.6-4.1	1.0-4.0	.32	.32	5	6	48
	8-13	7	65	24-30	1.30-1.40	0.60-2.00	0.21-0.24	3.5-4.7	1.0-3.0	.32	.32			
	13-29	7	60	28-35	1.35-1.50	0.60-2.00	0.15-0.20	4.3-5.8	0.5-1.5	.43	.43			
	29-42	7	65	24-32	1.30-1.40	0.60-2.00	0.14-0.22	3.5-5.1	0.1-0.8	.43	.43			
	42-60	7	65	20-32	1.30-1.40	0.60-2.00	0.14-0.22	2.6-5.1	0.1-0.8	.43	.43			
Ge:														
Geary-----	0-8	10	68	15-27	1.30-1.40	0.60-2.00	0.22-0.24	1.6-4.1	1.0-4.0	.32	.32	5	6	48
	8-13	7	65	24-30	1.30-1.40	0.60-2.00	0.21-0.24	3.5-4.7	1.0-3.0	.32	.32			
	13-29	7	60	28-35	1.35-1.50	0.60-2.00	0.15-0.20	4.3-5.8	0.5-1.5	.43	.43			
	29-42	7	65	24-32	1.30-1.40	0.60-2.00	0.14-0.22	3.5-5.1	0.1-0.8	.43	.43			
	42-60	7	65	20-32	1.30-1.40	0.60-2.00	0.14-0.22	2.6-5.1	0.1-0.8	.43	.43			
Ha:														
Haynie-----	0-10	61	27	8-18	1.20-1.35	0.60-2.00	0.20-0.23	0.1-2.2	1.0-3.0	.37	.37	5	3	86
	10-20	61	27	8-18	1.20-1.35	0.60-2.00	0.17-0.21	0.1-2.2	0.1-1.0	.43	.43			
	20-30	62	28	5-15	1.20-1.35	0.60-2.00	0.17-0.21	0.0-1.6	0.1-1.0	.43	.43			
	30-41	62	28	5-15	1.20-1.35	0.60-2.00	0.17-0.21	0.0-1.6	0.1-1.0	.43	.43			
	41-60	7	63	20-35	1.20-1.40	0.20-0.60	0.18-0.22	2.6-5.8	0.1-1.0	.43	.43			
HO:														
Hobbs-----	0-8	11	68	15-27	1.20-1.40	0.60-2.00	0.21-0.24	1.6-4.1	2.0-4.0	.32	.32	5	6	48
	8-16	11	68	15-27	1.20-1.40	0.60-2.00	0.00-0.20	1.6-4.1	0.5-1.0	.32	.32			
	16-40	10	68	15-30	1.20-1.40	0.60-2.00	0.18-0.22	1.6-4.7	0.5-1.0	---	---			
	40-60	10	68	15-30	1.20-1.40	0.60-2.00	0.18-0.22	1.6-4.7	0.5-1.0	---	---			
Ic:														
Irwin-----	0-11	3-10	40-65	28-35	1.35-1.45	0.20-0.60	0.18-0.23	3.0-5.9	2.0-4.0	.37	.37	4	7	38
	11-55	2-8	35-55	40-55	1.40-1.50	0.00-0.06	0.10-0.15	6.0-8.9	0.5-2.0	.37	.37			
	55-59													
Id:														
Irwin, eroded	0-11	3-10	40-65	28-35	1.35-1.45	0.20-0.60	0.18-0.23	3.0-5.9	2.0-4.0	.37	.37	4	7	38
	11-55	2-8	35-55	40-55	1.40-1.50	0.00-0.06	0.10-0.15	6.0-8.9	0.5-2.0	.37	.37			
	55-59													
Ie:														
Ivan-----	0-7	1-10	50-75	28-35	1.30-1.45	0.60-2.00	0.21-0.23	3.0-5.9	2.0-4.0	.32	.32	5	4L	86
	7-64	1-10	45-75	20-35	1.35-1.55	0.60-2.00	0.19-0.22	3.0-5.9	1.0-2.0	.32	.32			
Iv:														
Ivan-----	0-7	1-10	50-75	16-27	1.30-1.45	0.60-2.00	0.22-0.24	1.5-4.5	2.0-4.0	.32	.32	5	4L	86
	7-64	1-10	45-75	20-35	1.35-1.55	0.60-2.00	0.19-0.22	3.0-5.9	1.0-2.0	.32	.32			
Kennebec-----	0-18	1-10	50-75	22-27	1.25-1.35	0.60-2.00	0.22-0.24	3.0-5.9	2.0-6.0	.32	.32	5	6	48
	18-60	1-10	45-70	24-32	1.35-1.40	0.60-2.00	0.20-0.22	3.0-5.9	0.5-1.5	.43	.43			
Ka:														
Kahola-----	0-13	1-10	50-75	18-27	1.35-1.40	0.60-2.00	0.21-0.24	3.0-5.9	2.0-4.0	.32	.32	5	6	48
	13-60	1-15	45-70	18-35	1.35-1.40	0.60-2.00	0.17-0.22	3.0-5.9	1.0-3.0	.32	.32			
Ke:														
Kenesaw-----	0-12	1-20	50-75	12-20	1.20-1.40	0.60-2.00	0.20-0.24	0.0-2.9	1.0-3.0	.32	.32	5	6	48
	12-36	1-55	40-70	10-18	1.20-1.30	0.60-2.00	0.17-0.22	0.0-2.9	0.5-1.2	.43	.43			
	36-60	1-55	40-70	8-18	1.30-1.40	0.60-2.00	0.17-0.22	0.0-2.9	0.1-0.3	.43	.43			
Kf:														
Kenesaw-----	0-12	1-20	50-75	12-20	1.20-1.40	0.60-2.00	0.20-0.24	0.0-2.9	1.0-3.0	.32	.32	5	6	48
	12-36	1-55	40-70	10-18	1.20-1.30	0.60-2.00	0.17-0.22	0.0-2.9	0.5-1.2	.43	.43			
	36-60	1-55	40-70	8-18	1.30-1.40	0.60-2.00	0.17-0.22	0.0-2.9	0.1-0.3	.43	.43			
KN:														
Kennebec-----	0-48	1-10	50-75	22-27	1.25-1.35	0.60-2.00	0.22-0.24	3.0-5.9	2.0-6.0	.28	.28	5	6	48
	48-60	1-10	50-75	24-28	1.35-1.40	0.60-2.00	0.20-0.22	3.0-5.9	0.5-2.0	.43	.43			
M-W:														
Miscellaneous Water	---													
Ma:														
Mayberry-----	0-7	15-40	25-45	25-35	1.40-1.50	0.20-0.60	0.17-0.22	4.1-6.7	2.0-4.0	.37	.37	5	6	48
	7-13	15-40	25-45	30-38	1.40-1.50	0.20-0.60	0.17-0.19	5.4-7.4	1.0-2.0	.37	.37			
	13-43	20-50	10-35	40-50	1.50-1.65	0.06-0.20	0.09-0.11	7.9-10.4	0.5-1.5	.32	.32			
	43-57	35-55	10-45	35-45	1.40-1.50	0.06-0.20	0.08-0.16	6.7-9.2	0.1-1.0	.32	.32			
	57-64	35-55	10-45	28-42	1.40-1.50	0.06-0.20	0.08-0.16	4.9-8.4	0.1-0.5	.37	.37			

PHYSICAL PROPERTIES OF THE SOILS--Continued
Riley County, Kansas: Published

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permeability (Ksat)	Available water capacity	Linear extensibility	Organic matter	Erosion factors			Wind erodibility group	Wind erodibility index
										K	Kf	T		
	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
Mb: Mayberry-----	0-7	15-40	25-45	30-38	1.40-1.50	0.20-0.60	0.17-0.19	5.4-7.4	1.0-3.0	.37	.37	5	6	48
	7-37	20-50	10-35	40-50	1.50-1.65	0.06-0.20	0.09-0.11	7.9-10.4	0.5-1.5	.32	.32			
	37-51	35-55	10-45	35-45	1.40-1.50	0.06-0.20	0.08-0.16	6.7-9.2	0.1-1.0	.32	.32			
	51-64	35-55	10-45	28-42	1.40-1.50	0.06-0.20	0.08-0.16	4.9-8.4	0.1-0.5	.37	.37			
Mu: Muir-----	0-7	10	68	18-27	1.30-1.45	0.60-2.00	0.22-0.24	2.2-4.1	2.0-4.0	.32	.32	5	6	48
	7-18	10	68	18-27	1.30-1.45	0.60-2.00	0.22-0.24	2.2-4.1	2.0-4.0	.32	.32			
	18-24	9	64	18-35	1.30-1.50	0.60-2.00	0.18-0.22	2.2-5.8	1.0-3.0	---	---			
	24-42	9	64	18-35	1.30-1.50	0.60-2.00	0.18-0.22	2.2-5.8	1.0-3.0	---	---			
	42-60	9	64	18-35	1.30-1.50	0.60-2.00	0.18-0.22	2.2-5.8	0.0-0.5	---	---			
QUA: Quarries-----	---	---	---	---	---	---	---	---	---	---	---	-	---	---
Rd: Reading-----	0-11	1-10	50-75	18-27	1.35-1.40	0.60-2.00	0.22-0.24	1.5-4.5	2.0-4.0	.32	.32	5	6	48
	11-52	1-10	50-70	27-35	1.40-1.50	0.20-2.00	0.18-0.20	3.0-5.9	0.5-3.0	.43	.43			
	52-60	1-25	40-70	30-42	1.40-1.50	0.20-2.00	0.13-0.20	3.0-5.9	0.5-1.0	.43	.43			
Re: Reading-----	0-11	1-10	50-75	18-27	1.35-1.40	0.60-2.00	0.22-0.24	0.0-2.9	2.0-4.0	.32	.32	5	6	48
	11-52	1-10	50-70	27-35	1.40-1.50	0.20-2.00	0.18-0.20	3.0-5.9	0.5-3.0	.43	.43			
	52-60	1-25	40-70	30-42	1.40-1.50	0.20-2.00	0.13-0.20	3.0-5.9	0.5-1.0	.43	.43			
Sa: Sarpy-----	0-5	70-95	1-20	2-5	1.20-1.50	5.95-19.98	0.05-0.09	0.0-2.9	0.1-1.0	.17	.17	5	2	134
	5-60	70-95	1-20	2-5	1.20-1.50	5.95-19.98	0.05-0.09	0.0-2.9	0.1-0.5	.15	.15			
Sm: Smolan-----	0-8	5-15	50-70	18-27	1.30-1.40	0.60-2.00	0.22-0.24	1.5-4.5	2.0-4.0	.37	.37	5	6	48
	8-17	5-15	50-70	18-35	1.30-1.40	0.20-0.60	0.21-0.24	3.0-5.9	1.0-3.0	.37	.37			
	17-51	5-15	40-60	35-50	1.30-1.45	0.06-0.20	0.12-0.18	6.0-8.9	0.5-2.0	.37	.37			
	51-60	5-15	40-60	27-35	1.30-1.40	0.20-0.60	0.18-0.20	3.0-5.9	0.1-0.5	.37	.37			
Sn: Smolan-----	0-8	5-15	50-70	18-27	1.30-1.40	0.60-2.00	0.22-0.24	0.0-2.9	2.0-4.0	.37	.37	5	6	48
	8-17	5-15	50-70	18-35	1.30-1.40	0.20-0.60	0.21-0.24	3.0-5.9	1.0-3.0	.37	.37			
	17-51	5-15	40-60	35-50	1.30-1.45	0.06-0.20	0.12-0.18	6.0-8.9	0.5-2.0	.37	.37			
	51-60	5-15	40-60	27-35	1.30-1.40	0.20-0.60	0.18-0.20	3.0-5.9	0.1-0.5	.37	.37			
So: Smolan, eroded-----	0-7	5-15	50-70	27-35	1.30-1.40	0.20-0.60	0.21-0.23	3.0-5.9	1.5-3.5	.37	.37	5	7	38
	7-51	5-15	40-60	35-50	1.30-1.45	0.06-0.20	0.12-0.18	6.0-8.9	1.0-3.0	.37	.37			
	51-60	5-15	40-65	27-35	1.30-1.40	0.20-0.60	0.18-0.20	3.0-5.9	0.1-0.5	.37	.37			
St: Clime-----	0-2	8	56	32-40	1.00-1.45	0.20-0.60	0.21-0.23	5.1-6.8	2.0-4.0	.24	.32	3	8	0
	2-9	7	52	32-50	1.30-1.45	0.06-0.60	0.12-0.23	5.1-8.9	0.5-2.0	.17	.28			
	9-27	6	47	35-50	1.30-1.50	0.06-0.20	0.09-0.20	5.8-8.9	0.5-1.0	---	---			
	27-33	8	50	35-50	1.30-1.50	0.06-0.20	0.08-0.20	5.8-8.9	0.0-0.5	---	---			
	33-37	---	---	---	---	---	---	---	---	---	---			
Su: Sutphen-----	0-8	6	47	40-55	1.35-1.45	0.00-0.06	0.12-0.14	6.0-8.9	2.0-4.0	.28	.28	5	4	86
	8-32	6	47	40-55	1.35-1.45	0.00-0.06	0.10-0.14	6.0-8.9	1.0-3.0	.28	.28			
	32-60	7	48	35-55	1.35-1.45	0.06-0.20	0.10-0.18	6.0-8.9	1.0-2.0	.28	.28			
Ts: Tully-----	0-12	10	57	28-38	1.35-1.45	0.20-0.60	0.21-0.23	4.3-6.4	3.0-6.0	.37	.37	5	7	38
	12-21	10	55	30-40	1.35-1.45	0.20-0.60	0.18-0.20	4.7-6.8	2.0-4.0	.37	.37			
	21-31	8	49	40-55	1.40-1.50	0.06-0.20	0.10-0.15	6.8-10.0	1.0-3.0	---	---			
	31-40	6	48	40-55	1.40-1.50	0.06-0.20	0.10-0.15	6.8-10.0	0.8-2.0	---	---			
	40-52	7	48	40-55	1.40-1.50	0.06-0.20	0.10-0.15	6.8-10.0	0.5-1.0	---	---			
	52-60	8	52	35-45	1.40-1.50	0.06-0.20	0.07-0.12	5.8-7.0	0.2-1.0	---	---			
Tt: Tully, eroded	0-7	1-10	50-70	28-38	1.35-1.45	0.20-2.00	0.18-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	7-51	1-10	35-60	35-55	1.40-1.50	0.06-0.20	0.10-0.15	6.0-8.9	0.3-1.5	.37	.43			
	51-60	1-10	35-60	35-55	1.40-1.50	0.06-0.20	0.07-0.15	6.0-8.9	0.1-0.3	.37	.43			
Tu: Tully-----	0-10	1-10	50-70	28-38	1.35-1.45	0.20-2.00	0.18-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	10-51	1-10	35-60	35-55	1.40-1.50	0.06-0.20	0.10-0.15	6.0-8.9	0.3-1.5	.37	.43			
	51-60	1-10	35-60	35-55	1.40-1.50	0.06-0.20	0.07-0.15	6.0-8.9	0.1-0.3	.37	.43			
Tv: Tully, eroded	0-7	1-10	50-70	28-38	1.35-1.45	0.20-2.00	0.18-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	7-51	1-10	35-60	35-55	1.40-1.50	0.06-0.20	0.10-0.15	6.0-8.9	0.3-1.5	.37	.43			
	51-60	1-10	35-60	35-55	1.40-1.50	0.06-0.20	0.07-0.15	6.0-8.9	0.1-0.3	.37	.43			
W: Water-----	---	---	---	---	---	---	---	---	---	---	---	-	---	---
Wm: Wymore-----	0-13	1-10	50-75	30-40	1.15-1.20	0.20-0.60	0.21-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	13-33	1-10	40-60	42-55	1.10-1.20	0.06-0.20	0.11-0.14	6.0-8.9	0.8-2.0	.37	.37			
	33-64	1-10	50-70	27-40	1.15-1.25	0.20-0.60	0.18-0.20	6.0-8.9	0.2-0.8	.37	.37			
Wn: Wymore-----	0-13	1-10	50-70	30-40	1.15-1.20	0.20-0.60	0.21-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	13-33	1-10	40-60	42-55	1.10-1.20	0.06-0.20	0.11-0.14	6.0-8.9	0.8-2.0	.37	.37			
	33-64	1-10	50-70	27-40	1.15-1.25	0.20-0.60	0.18-0.20	6.0-8.9	0.2-0.8	.37	.37			
Wo: Wymore, eroded-----	0-7	1-10	50-75	30-40	1.15-1.20	0.20-0.60	0.21-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	7-33	1-10	40-60	42-55	1.10-1.20	0.06-0.20	0.11-0.14	6.0-8.9	0.8-2.0	.37	.37			
	33-64	1-10	50-70	27-40	1.15-1.25	0.20-0.60	0.18-0.20	6.0-8.9	0.2-0.8	.37	.37			

(Single entries under "Sand and Silt" are a representative percentage are calculated using an algorithm. Entries under "Erosion factors--T" apply to the entire profile. Entries under "Wind erodibility group" and "Wind erodibility index" apply only to the surface layer)

Map symbol and soil name	Depth	Sand	Silt	Clay	Moist bulk density	Permeability (Ksat)	Available water capacity	Linear extensibility	Organic matter	Erosion factors			Wind erodibility group	Wind erodibility index
										K	Kf	T		
	In	Pct	Pct	Pct	g/cc	in/hr	In/in	Pct	Pct					
Wr: Wymore-----	0-13	1-10	50-75	30-40	1.15-1.20	0.20-0.60	0.21-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	13-33	1-10	40-60	42-55	1.10-1.20	0.06-0.20	0.11-0.14	6.0-8.9	0.8-2.0	.37	.37			
	33-64	1-10	50-70	27-40	1.15-1.25	0.20-0.60	0.18-0.20	6.0-8.9	0.2-0.8	.37	.37			
Ws: Wymore, eroded-----	0-7	1-10	50-75	30-40	1.15-1.20	0.20-0.60	0.21-0.23	3.0-5.9	2.0-4.0	.37	.37	5	7	38
	7-33	1-10	40-60	42-55	1.10-1.20	0.06-0.20	0.11-0.14	6.0-8.9	0.8-2.0	.37	.37			
	33-60	1-10	50-70	27-40	1.15-1.25	0.20-0.60	0.18-0.20	6.0-8.9	0.2-0.8	.37	.37			

CHEMICAL PROPERTIES OF THE SOILS
Riley County, Kansas

The Chemical Properties table shows estimates of some characteristics and features that affect soil behavior. These estimates are given for the major layers of each soil in the survey area. The estimates are based on field observations and on test data for these and similar soils. Depth to the upper and lower boundaries of each layer is indicated.

Cation-exchange capacity is the total amount of extractable bases that can be held by the soil, expressed in terms of milliequivalents per 100 grams of soil at neutrality (pH 7.0) or at some other stated pH value. Soils having a low cation-exchange capacity hold fewer cations and may require more frequent applications of fertilizer than soils having a high cation-exchange capacity. Soils having a high cation-exchange capacity can retain cations. The ability to retain cations helps to prevent the pollution of ground water.

Soil reaction is a measure of acidity or alkalinity and is expressed as a range in pH values. The range in pH of each major horizon is based on many field tests. For many soils, values have been verified by laboratory analyses. Soil reaction is important in selecting crops and other plants, in evaluating soil amendments for fertility and stabilization, and in determining the risk of corrosion.

Calcium carbonate equivalent is the percent of carbonates, by weight, in the fraction of the soil less than 2 millimeters in size. The availability of plant nutrients is influenced by the amount of carbonates in the soil. Incorporating nitrogen fertilizer into calcareous soils helps to prevent nitrite accumulation and ammonium-N volatilization.

Gypsum is expressed as a percent, by weight, of hydrated calcium sulfates in the fraction of the soil less than 20 millimeters in size. Gypsum is partially soluble in water and can be dissolved and removed by water. Soils that have a high content of gypsum may collapse if the gypsum is removed by percolating water.

Salinity is a measure of soluble salts in the soil at saturation. It is expressed as the electrical conductivity of the saturation extract, in millimhos per centimeter at 25 degrees C. Estimates are based on field and laboratory measurements at representative sites of nonirrigated soils. The salinity of irrigated soils is affected by the quality of the irrigation water and by the frequency of water application. Hence, the salinity of soils in individual fields can differ greatly from the value given in the table. Salinity affects the suitability of a soil for crop production, the stability of soil if used as construction material, and the potential of the soil to corrode metal and concrete.

Sodium adsorption ratio (SAR) is a measure of the amount of sodium (Na) relative to calcium (Ca) and magnesium (Mg) in the water extract from saturated soil paste. It is the ratio of the Na concentration divided by the square root of one-half of the Ca + Mg concentration. Soils that have SAR values of 13 or more may be characterized by an increased dispersion of organic matter and clay particles, reduced permeability and aeration, and a general degradation of soil structure.

CHEMICAL PROPERTIES OF THE SOILS--Continued
Riley County, Kansas

Map symbol and soil name	Depth	Cation- exchange capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm	
027CS: Crete-----	0-6	20-29	5.6-6.0	0	0	0	0
	6-11	22-29	5.6-6.0	0	0	0	0
	11-27	29-44	6.1-7.3	0	0	0	0
	27-40	25-36	6.1-7.3	0-5	0	0	0
	40-60	20-33	6.1-7.3	0-5	0	0	0
027CX: Crete-----	0-7	18-34	5.6-6.0	0	0	0	0
	7-31	22-46	6.1-7.3	0	0	0	0
	31-60	15-33	7.4-8.4	0-5	0	0	0
027HN: Hobbs-----	0-8	12-19	6.1-7.8	0	0	0	0
	8-24	12-19	6.1-7.8	0	0	0	0
	24-44	12-21	6.1-7.8	0-5	0	0	0
	44-60	12-21	6.1-7.8	0-5	0	0	0
027KS: Kipson-----	0-8	11-23	7.4-8.4	10-20	0	0	0
	8-18	7.0-22	7.9-9.0	30-60	0	0	0
	18-22	---	---	---	---	---	---
Sogn-----	0-12	11-22	6.1-8.4	0	0	0	0
	12-16	---	---	---	---	---	---
061BE: Benfield-----	0-5	19-24	6.1-7.8	0	0	0	0
	5-10	24-30	6.6-8.4	0	0	0	0
	10-19	28-33	7.4-8.4	0	0	0	0
	19-34	28-36	7.4-8.4	0	0	0	0
	34-38	27-38	7.9-8.4	1-5	0	0	0
	38-56	---	---	---	---	---	---
Florence-----	0-5	20-28	5.6-7.3	0	0	0	0
	5-14	28-43	5.6-7.3	0	0	0	0
	14-48	43-62	6.1-7.8	0	0	0	0
	48-56	43-62	6.1-7.8	0-5	0	0	0
	56-60	---	---	---	---	---	---
061CF: Clime-----	0-12	22-27	6.6-8.4	1-15	0	0	0
	12-26	24-33	7.4-8.4	5-35	0	0	0
	26-30	24-33	7.4-8.4	10-35	0	0	0
	30-34	---	---	---	---	---	---
Sogn-----	0-9	19-24	6.1-8.4	0-5	0	0	0
	9-13	---	---	---	---	---	---
061CR: Crete-----	0-6	20-29	5.6-6.0	0	0	0	0
	6-14	22-29	5.6-6.0	0	0	0	0
	14-30	29-44	6.1-7.3	0	0	0	0
	30-42	25-36	6.1-7.3	0-5	0	0	0
	42-60	20-33	6.1-7.3	0-5	0	0	0
061CS: Crete-----	0-6	20-29	5.6-6.0	0	0	0	0
	6-11	22-29	5.6-6.0	0	0	0	0
	11-27	29-44	6.1-7.3	0	0	0	0
	27-40	25-36	6.1-7.3	0-5	0	0	0
	40-60	20-33	6.1-7.3	0-5	0	0	0
061EU: Eudora-----	0-7	8.9-15	5.1-7.8	0	0	0	0
	7-14	8.9-15	5.1-7.8	0	0	0	0
	14-19	9.0-14	5.1-7.8	0	0	0	0
	19-26	2.0-14	5.1-8.5	0-5	0	0	0
	26-60	2.0-14	5.1-8.5	0-5	0	0	0
061HE: Haynie-----	0-10	12-18	6.6-8.4	0-25	0	0	0
	10-60	8.9-14	7.4-8.4	5-30	0	0	0
061KA: Kahola-----	0-24	14-19	6.1-7.8	0	0	0	0
	24-36	14-19	6.1-7.8	0-3	0	0	0
	36-44	14-24	7.4-8.4	1-5	0	0	0
	44-60	14-24	7.4-8.4	1-5	0	0	0
061KB: Kahola-----	0-24	14-19	6.1-7.8	0	0	0	0
	24-36	14-19	6.1-7.8	0-3	0	0	0
	36-44	14-24	7.4-8.4	1-5	0	0	0
	44-60	14-24	7.4-8.4	1-5	0	0	0

CHEMICAL PROPERTIES OF THE SOILS--Continued
Riley County, Kansas

Map symbol and soil name	Depth	Cation- exchange capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm	
061RE: Reading-----	0-8	15-21	5.6-6.5	0	0	0	0
	8-20	15-21	5.6-6.5	0	0	0	0
	20-52	19-24	5.6-6.5	0	0	0	0
	52-60	19-27	6.1-7.8	0	0	0	0
061TO: Tully-----	0-12	20-26	5.6-7.3	0	0	0	0
	12-21	19-27	5.6-7.3	0	0	0	0
	21-31	27-36	5.6-8.4	0-5	0	0	0
	31-40	27-36	5.6-8.4	0-5	0	0	0
	40-52	27-36	5.6-8.4	0-5	0	0	0
	52-60	22-30	6.6-8.4	0-5	0	0	0
117PA: Pawnee-----	0-13	13-25	5.6-7.3	0	0	0	0
	13-36	16-30	6.1-8.4	0	0	0	0
	36-60	10-21	7.4-8.4	0-5	0	0	0
117PB: Pawnee-----	0-13	13-25	5.6-7.3	0	0	0	0
	13-36	16-30	6.1-8.4	0	0	0	0
	36-60	10-21	7.4-8.4	0-5	0	0	0
149HS: Haynie-----	0-9	6.0-14	6.6-8.4	0-25	0	0	0
	9-60	6.0-11	7.4-8.4	5-30	0	0	0
Sarpy-----	0-6	0.0-4.0	6.6-8.4	0	0	0	0
	6-60	0.0-3.0	6.6-8.4	0	0	0	0
149PS: Paxico-----	0-42	2.0-13	6.6-8.4	1-10	0	0	0
	42-60	0.0-9.0	7.4-8.4	5-15	0	0	0
149SF: Sarpy-----	0-6	0.0-4.0	6.6-8.4	0	0	0	0
	6-60	1.0-3.0	7.4-8.4	0	0	0	0
197CM: Clime-----	0-5	13-27	6.6-8.4	5-10	0	0	0
	5-18	14-39	7.4-8.4	5-10	0	0	0
	18-32	14-32	7.4-8.4	10-15	0	0	0
	32-36	---	---	---	---	---	---
197FL: Florence-----	0-14	10-24	5.6-7.3	0	0	0	0
	14-18	10-24	5.6-7.3	0	0	0	0
	18-56	20-49	6.1-7.8	0	0	0	0
	56-60	---	---	---	---	---	---
Labette-----	0-7	8.0-19	5.6-6.5	0	0	0	0
	7-35	14-34	5.6-8.4	0	0	0	0
	35-39	---	---	---	---	---	---
197IB: Irwin-----	0-12	12-24	5.6-7.3	0	0	0	0
	12-42	16-38	5.6-8.4	0	0	0	0
	42-60	14-34	6.6-8.4	0	0	0	0
197ID: Irwin-----	0-6	20-24	5.6-7.3	0	0	0.0-2.0	0-2
	6-13	20-24	5.6-7.3	0	0	0.0-2.0	0-2
	13-30	27-38	5.6-8.4	0-3	0	2.0-4.0	2-8
	30-41	27-38	5.6-8.4	0-3	0	2.0-4.0	2-8
	41-72	28-36	6.6-8.4	0-3	0	2.0-4.0	2-8
197IV: Ivan-----	0-36	7.0-19	7.4-8.4	1-5	0	0	0
	36-60	7.0-21	7.9-8.4	5-10	0	0	0
197IX: Ivan-----	0-40	12-24	7.4-8.4	1-5	0	0	0
	40-60	7.0-21	7.9-8.4	5-10	0	0	0
197PN: Pawnee-----	0-14	13-25	5.6-7.3	0	0	0	0
	14-34	16-30	6.1-8.4	0	0	0	0
	34-72	10-21	7.4-8.4	0-5	0	0	0
197WE: Wamego-----	0-9	15-30	5.6-6.5	0	0	0	0
	9-20	15-30	5.6-7.3	0	0	0	0
	20-25	15-30	5.6-7.3	0	0	0	0
	25-36	---	---	---	---	---	---

CHEMICAL PROPERTIES OF THE SOILS--Continued
Riley County, Kansas

Map symbol and soil name	Depth	Cation- exchange capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm	
201CS:							
Crete-----	0-6	20-29	5.6-6.0	0	0	0	0
	6-9	22-29	5.6-6.0	0	0	0	0
	9-32	29-44	6.1-7.3	0	0	0	0
	32-40	25-36	6.1-7.3	0-5	0	0	0
	40-60	20-33	6.1-7.3	0-5	0	0	0
201CX:							
Crete, eroded---	0-5	11-24	5.6-6.0	0	0	0	0
	5-30	14-33	6.1-7.3	0	0	0	0
	30-60	10-24	7.4-8.4	0-5	0	0	0
201KS:							
Kipson-----	0-12	11-23	7.4-8.4	10-20	0	0	0
	12-18	7.0-22	7.9-9.0	30-60	0	0	0
	18-22	---	---	---	---	---	---
Sogn-----	0-8	8.0-19	6.1-8.4	0-5	0	0	0
	8-16	7.0-23	6.1-8.4	0-8	0	0	0
	16-20	---	---	---	---	---	---
201LC:							
Lancaster-----	0-9	10-18	5.6-6.5	0	0	0	0
	9-24	14-24	5.6-7.3	0	0	0	0
	24-29	10-21	6.1-7.3	0	0	0	0
	>29	---	---	---	---	---	---
Ad:							
Ivan-----	0-7	11-24	7.4-8.4	0-5	0	0	0
	7-26	9.0-27	7.4-8.4	1-10	0	0	0
	26-39	7.0-23	7.9-8.4	5-15	0	0	0
	39-64	7.0-23	7.9-8.4	5-15	0	0	0
AED:							
Arents, Earthen Dam-----	---	---	---	---	---	---	---
BE:							
Benfield-----	0-10	11-24	6.1-7.8	0	0	0	0
	10-32	14-31	6.6-8.4	0	0	0	0
	32-36	---	---	---	---	---	---
Bf:							
Benfield-----	0-6	11-24	6.1-7.8	0	0	0	0
	6-30	14-31	6.6-8.4	0	0	0	0
	30-35	14-31	7.4-8.4	0	0	0	0
	35-39	---	---	---	---	---	---
Florence-----	0-5	10-24	5.6-7.3	0	0	0	0
	5-10	10-24	5.6-7.3	0	0	0	0
	10-14	14-35	5.6-7.3	0	0	0	0
	14-30	20-49	6.1-7.8	0	0	0	0
	30-34	---	---	---	---	---	---
Bk:							
Wymore-----	0-13	12-27	5.6-6.5	0	0	0	0
	13-33	16-33	5.6-7.3	0	0	0	0
	33-64	10-24	6.6-7.3	0	0	0	0
Kennebec-----	0-18	10-20	5.6-7.3	0	0	0	0
	18-60	10-18	6.1-7.3	0	0	0	0
BOP:							
Borrow Pits----	---	---	---	---	---	---	---
Ca:							
Carr-----	0-9	3.0-13	7.4-8.4	0-5	0	0	0
	9-17	3.0-12	7.4-8.4	0-5	0	0	0
	17-28	2.0-10	7.4-8.4	2-10	0	0	0
	28-60	2.0-10	7.4-8.4	2-10	0	0	0
Sarpy-----	0-5	0.0-4.0	6.6-8.4	0-5	---	0	0
	5-60	0.0-3.0	6.6-8.4	0-5	---	0	0
Ch:							
Chase-----	0-7	21-36	5.6-7.3	0	0	0	0
	7-13	20-36	5.6-7.3	0	0	0	0
	13-40	23-47	5.6-7.8	0	0	0	0
	40-50	21-42	6.1-8.4	0-5	0	0	0
	50-60	17-38	6.1-8.4	0-5	0	0	0
Cs:							
Clime-----	0-12	13-27	6.6-8.4	5-10	0	0	0
	12-30	14-39	7.4-8.4	5-10	0	0	0
	30-34	---	---	---	---	---	---
Sogn-----	0-9	11-23	6.1-8.4	0	0	0	0
	9-13	---	---	---	---	---	---

CHEMICAL PROPERTIES OF THE SOILS--Continued
Riley County, Kansas

Map symbol and soil name	Depth	Cation- exchange capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm	
CT:							
Crete-----	0-7	20-29	5.6-6.0	0	0	0	0
	7-11	22-29	5.6-6.0	0	0	0	0
	11-30	29-44	6.1-7.3	0	0	0	0
	30-40	25-36	6.1-7.3	0-5	0	0	0
	40-60	20-33	6.1-7.3	0-5	0	0	0
Dr:							
Dwight-----	0-4	15-30	5.6-7.3	0	---	0.0-2.0	---
	4-17	28-50	6.1-8.4	0-5	---	0.0-4.0	---
	17-43	21-42	6.6-8.4	0-5	---	0.0-8.0	---
	>43	---	---	---	---	---	---
Irwin-----	0-7	21-36	5.6-7.3	0	---	0	0
	7-11	20-36	5.6-7.3	0	---	0	0
	11-35	24-47	5.6-8.4	0	---	0	0
	35-50	24-46	5.6-8.4	0-5	---	0	0
	50-55	21-45	5.6-8.4	0-5	---	0	0
	>55	---	---	---	---	---	---
Dw:							
Dwight-----	0-4	15-30	5.6-7.3	0	---	0.0-2.0	---
	4-17	28-50	6.1-8.4	0-5	---	0.0-4.0	---
	17-43	21-42	6.6-8.4	0-5	---	0.0-8.0	---
	>43	---	---	---	---	---	---
Irwin-----	0-8	19-36	5.6-7.3	0	---	0	0
	8-35	24-47	5.6-8.4	0	---	0	0
	35-50	24-46	5.6-8.4	0-5	---	0	0
	50-55	21-45	5.6-8.4	0-5	---	0	0
	>55	---	---	---	---	---	---
Em:							
Elmont-----	0-10	11-24	5.1-7.3	0	---	0	0
	10-18	12-24	5.1-7.3	0	---	0	0
	18-28	12-24	5.1-7.3	0	---	0	0
	28-33	11-26	5.1-7.3	0	---	0	0
	33-44	11-26	5.1-7.3	0	---	0	0
	>44	---	---	---	---	---	---
En:							
Elmont-----	0-10	11-24	5.1-7.3	0	---	0	0
	10-18	12-24	5.1-7.3	0	---	0	0
	18-28	12-24	5.1-7.3	0	---	0	0
	28-33	11-26	5.1-7.3	0	---	0	0
	33-44	11-26	5.1-7.3	0	---	0	0
	>44	---	---	---	---	---	---
Clime-----	0-8	16-30	6.6-8.4	5-10	---	0	0
	8-12	15-28	6.6-8.4	5-15	---	0	0
	12-20	15-30	7.4-8.4	5-20	---	0	0
	20-30	14-34	7.4-8.4	5-20	---	0	0
	>30	---	---	---	---	---	---
Eu:							
Eudora-----	0-7	8.9-15	5.1-7.8	0	0	0	0
	7-14	8.9-15	5.1-7.8	0	0	0	0
	14-19	9.0-14	5.1-7.8	0	0	0	0
	19-26	2.0-14	5.1-8.5	0-5	0	0	0
	26-60	2.0-14	5.1-8.5	0-5	0	0	0
Ga:							
Geary-----	0-8	8.0-23	5.6-6.5	0	0	0	0
	8-13	12-24	5.6-6.5	0	0	0	0
	13-29	12-24	5.6-7.8	0	0	0	0
	29-42	10-20	6.1-8.4	0	0	0	0
	42-60	8.0-20	6.1-8.4	0	0	0	0
Ge:							
Geary-----	0-8	8.0-23	5.6-6.5	0	0	0	0
	8-13	12-24	5.6-6.5	0	0	0	0
	13-29	12-24	5.6-7.8	0	0	0	0
	29-42	10-20	6.1-8.4	0	0	0	0
	42-60	8.0-20	6.1-8.4	0	0	0	0
Ha:							
Haynie-----	0-10	4.0-17	6.6-8.4	1-15	0	0	0
	10-20	3.0-13	7.4-8.4	5-25	0	0	0
	20-30	2.0-11	7.4-8.4	5-25	0	0	0
	30-41	2.0-11	7.4-8.4	5-25	0	0	0
	41-60	8.0-23	7.4-8.4	5-25	0	0	0

CHEMICAL PROPERTIES OF THE SOILS--Continued
Riley County, Kansas

Map symbol and soil name	Depth	Cation- exchange capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm	
HO:							
Hobbs-----	0-8	12-19	6.1-7.8	0	0	0	0
	8-16	12-19	6.1-7.8	0	0	0	0
	16-40	12-21	6.1-7.8	0-5	0	0	0
	40-60	12-21	6.1-7.8	0-5	0	0	0
Ic:							
Irwin-----	0-11	12-24	5.6-7.3	0	0	0	0
	11-55	16-33	5.6-8.4	0	0	0	0
	55-59	---	---	---	---	---	---
Id:							
Irwin, eroded---	0-11	12-24	5.6-7.3	0	0	0	0
	11-55	16-33	5.6-8.4	0	0	0	0
	55-59	---	---	---	---	---	---
Ie:							
Ivan-----	0-7	12-24	7.4-8.4	1-5	0	0	0
	7-64	7.0-21	7.9-8.4	5-10	0	0	0
Iv:							
Ivan-----	0-7	7.0-19	7.4-8.4	1-5	0	0	0
	7-64	7.0-21	7.9-8.4	5-10	0	0	0
Kennebec-----	0-18	10-20	5.6-7.3	0	0	0	0
	18-60	10-18	6.1-7.3	0	0	0	0
Ka:							
Kahola-----	0-13	8.0-19	6.1-8.4	0	0	0	0
	13-60	7.0-21	7.4-8.4	5-15	0	0	0
Ke:							
Kenesaw-----	0-12	5.0-14	6.1-7.3	0	0	0	0
	12-36	4.0-11	6.6-8.4	0	0	0	0
	36-60	3.0-11	7.4-8.4	0	0	0	0
Kf:							
Kenesaw-----	0-12	5.0-14	6.1-7.3	0	0	0	0
	12-36	4.0-11	6.6-8.4	0	0	0	0
	36-60	3.0-11	7.4-8.4	0	0	0	0
KN:							
Kennebec-----	0-48	10-20	5.6-7.3	0	0	0	0
	48-60	10-18	6.1-7.3	0	0	0	0
M-W:							
Miscellaneous	---	---	---	---	---	---	---
Water-----							
Ma:							
Mayberry-----	0-7	19-36	5.6-6.5	0	0	0	0
	7-13	20-34	5.6-6.5	0	0	0	0
	13-43	25-44	5.6-7.8	0	0	0	0
	43-57	21-38	6.1-8.4	0-5	0	0	0
	57-64	17-34	6.1-8.4	0-5	0	0	0
Mb:							
Mayberry-----	0-7	20-36	5.6-6.5	0	0	0	0
	7-37	25-44	5.6-7.8	0	0	0	0
	37-51	21-38	6.1-8.4	0-5	0	0	0
	51-64	17-34	6.1-8.4	0-5	0	0	0
Mu:							
Muir-----	0-7	12-19	5.6-7.3	0	0	0	0
	7-18	12-19	5.6-7.3	0	0	0	0
	18-24	12-24	6.1-7.3	0	0	0	0
	24-42	12-24	6.1-7.3	0-2	0	0	0
	42-60	12-24	6.1-8.4	0-2	0	0	0
QUA:							
Quarries-----	---	---	---	---	---	---	---
Rd:							
Reading-----	0-11	8.0-19	5.6-6.5	0	0	0	0
	11-52	11-23	5.6-6.5	0	0	0	0
	52-60	12-26	6.1-8.4	0	0	0	0
Re:							
Reading-----	0-11	8.0-19	5.6-6.5	0	0	0	0
	11-52	11-23	5.6-6.5	0	0	0	0
	52-60	12-26	6.1-8.4	0	0	0	0
Sa:							
Sarpy-----	0-5	0.0-4.0	6.6-8.4	0	0	0	0
	5-60	0.0-3.0	6.6-8.4	0	0	0	0

CHEMICAL PROPERTIES OF THE SOILS--Continued
Riley County, Kansas

Map symbol and soil name	Depth	Cation- exchange capacity	Soil reaction	Calcium carbonate	Gypsum	Salinity	Sodium adsorption ratio
	In	meq/100g	pH	Pct	Pct	mmhos/cm	
Sm:							
Smolan-----	0-8	8.0-19	5.6-7.3	0	0	0	0
	8-17	7.0-21	5.6-7.3	0	0	0	0
	17-51	14-30	5.6-7.8	0	0	0	0
	51-60	10-21	6.6-7.8	0	0	0	0
Sn:							
Smolan-----	0-8	8.0-19	5.6-7.3	0	0	0	0
	8-17	7.0-21	5.6-7.3	0	0	0	0
	17-51	14-30	5.6-7.8	0	0	0	0
	51-60	10-21	6.6-7.8	0	0	0	0
So:							
Smolan, eroded--	0-7	11-24	5.6-7.3	0	0	0	0
	7-51	14-30	5.6-7.8	0	0	0	0
	51-60	10-21	6.6-7.8	0	0	0	0
St:							
Clime-----	0-2	22-27	6.6-8.4	1-15	0	0	0
	2-9	22-33	6.6-8.4	5-15	0	0	0
	9-27	24-33	7.4-8.4	10-35	0	0	0
	27-33	24-33	7.4-8.4	10-35	0	0	0
	33-37	---	---	---	---	---	---
Su:							
Sutphen-----	0-8	16-36	6.1-8.4	---	---	---	---
	8-32	16-35	6.6-8.4	---	---	---	---
	32-60	14-34	7.4-8.4	1-3	---	---	---
Ts:							
Tully-----	0-12	20-26	5.6-7.3	0	0	0	0
	12-21	19-27	5.6-7.3	0	0	0	0
	21-31	27-36	5.6-8.4	0-5	0	0	0
	31-40	27-36	5.6-8.4	0-5	0	0	0
	40-52	27-36	5.6-8.4	0-5	0	0	0
	52-60	22-30	6.6-8.4	0-5	0	0	0
Tt:							
Tully, eroded---	0-7	12-25	5.6-7.3	0	0	0	0
	7-51	14-33	5.6-7.8	0	0	0	0
	51-60	14-33	6.6-8.4	0	0	0	0
Tu:							
Tully-----	0-10	12-25	5.6-7.3	0	0	0	0
	10-51	14-33	5.6-7.8	0	0	0	0
	51-60	14-33	6.6-8.4	0	0	0	0
Tv:							
Tully, eroded---	0-7	12-25	5.6-7.3	0	0	0	0
	7-51	14-33	5.6-7.8	0	0	0	0
	51-60	14-33	6.6-8.4	0	0	0	0
W:							
Water-----	---	---	---	---	---	---	---
Wm:							
Wymore-----	0-13	12-27	5.6-6.5	0	0	0	0
	13-33	16-33	5.6-7.3	0	0	0	0
	33-64	10-24	6.6-7.3	0	0	0	0
Wn:							
Wymore-----	0-13	12-27	5.6-6.5	0	0	0	0
	13-33	16-33	5.6-7.3	0	0	0	0
	33-64	10-24	6.6-7.3	0	0	0	0
Wo:							
Wymore, eroded--	0-7	12-27	5.6-6.5	0	0	0	0
	7-33	16-33	5.6-7.3	0	0	0	0
	33-64	10-24	6.6-7.3	0	0	0	0
Wr:							
Wymore-----	0-13	12-27	5.6-6.5	0	0	0	0
	13-33	16-33	5.6-7.3	0	0	0	0
	33-64	10-24	6.6-7.3	0	0	0	0
Ws:							
Wymore, eroded--	0-7	12-27	5.6-6.5	0	0	0	0
	7-33	16-33	5.6-7.3	0	0	0	0
	33-60	10-24	6.6-7.3	0	0	0	0

WATER FEATURES
Riley County, Kansas

The Water Features table gives estimates of various water features. The estimates are used in land use planning that involves engineering considerations. Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The four hydrologic soil groups are:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

The months in the table indicate the portion of the year in which the feature is most likely to be a concern.

Water table refers to a saturated zone in the soil. The Water Features table indicates, by month, depth to the top (upper limit) and base (lower limit) of the saturated zone in most years. Estimates of the upper and lower limits are based mainly on observations of the water table at selected sites and on evidence of a saturated zone, namely grayish colors or mottles (redoximorphic features) in the soil. A saturated zone that lasts for less than a month is not considered a water table. Ponding is standing water in a closed depression. Unless a drainage system is installed, the water is removed only by percolation, transpiration, or evaporation. The Water Features table indicates surface water depth and the duration and frequency of ponding. Duration is expressed as very brief if less than 2 days, brief if 2 to 7 days, long if 7 to 30 days, and very long if more than 30 days. Frequency is expressed as none, rare, occasional, and frequent. None means that ponding is not probable; rare that it is unlikely but possible under unusual weather conditions (the chance of ponding is nearly 0 percent to 5 percent in any year); occasional that it occurs, on the average, once or less in 2 years (the chance of ponding is 5 to 50 percent in any year); and frequent that it occurs, on the average, more than once in 2 years (the chance of ponding is more than 50 percent in any year).

Flooding, the temporary inundation of an area, is caused by overflowing streams, by runoff from adjacent slopes, or by tides. Water standing for short periods after rainfall or snowmelt is not considered flooding, and water standing in swamps and marshes is considered ponding rather than flooding.

Duration and frequency are estimated. Duration is expressed as extremely brief if 0.1 hour to 4 hours, very brief if 4 hours to 2 days, brief if 2 to 7 days, long if 7 to 30 days, and very long if more than 30 days. Frequency is expressed as none, very rare, rare, occasional, frequent, and very frequent. None means that flooding is not probable; very rare that it is very unlikely but possible under extremely unusual weather conditions (the chance of flooding is less than 1 percent in any year); rare that it is unlikely but possible under unusual weather conditions (the chance of flooding is 1 to 5 percent in any year); occasional that it occurs infrequently under normal weather conditions (the chance of flooding is 5 to 50 percent in any year); frequent that it is likely to occur often under normal weather conditions (the chance of flooding is more than 50 percent in any year but is less than 50 percent in all months in any year); and very frequent that it is likely to occur very often under normal weather conditions (the chance of flooding is more than 50 percent in all months of any year).

The information is based on evidence in the soil profile, namely thin strata of gravel, sand, silt, or clay deposited by floodwater; irregular decrease in organic matter content with increasing depth; and little or no horizon development.

Also considered are local information about the extent and levels of flooding and the relation of each soil on the landscape to historic floods. Information on the extent of flooding based on soil data is less specific than that provided by detailed engineering surveys that delineate flood-prone areas at specific flood frequency levels.

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro- logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
			Ft	Ft	Ft				
027CS: Crete-----	C		---	---	---	---	---	---	---
027CX: Crete-----	C		---	---	---	---	---	---	---
027HN: Hobbs-----	B	April	---	---	---	---	None	Brief	Frequent
		May	---	---	---	---	None	Brief	Frequent
		June	---	---	---	---	None	Brief	Frequent
		July	---	---	---	---	None	Brief	Frequent
		August	---	---	---	---	None	Brief	Frequent
		September	---	---	---	---	None	Brief	Frequent
		October	---	---	---	---	None	Brief	Frequent
027KS: Kipson-----	D		---	---	---	---	---	---	---
Sogn-----	D		---	---	---	---	---	---	---
061BE: Benfield-----	C		---	---	---	---	---	---	---
Florence-----	C		---	---	---	---	---	---	---
061CF: Clime-----	C		---	---	---	---	---	---	---
Sogn-----	D		---	---	---	---	---	---	---
061CR: Crete-----	C		---	---	---	---	---	---	---
061CS: Crete-----	C		---	---	---	---	---	---	---
061EU: Eudora-----	B	April	---	---	---	---	None	Very brief	Occasional
		May	---	---	---	---	None	Very brief	Occasional
		June	---	---	---	---	None	Very brief	Occasional
		July	---	---	---	---	None	Very brief	Occasional
		August	---	---	---	---	None	Very brief	Occasional
		September	---	---	---	---	None	Very brief	Occasional
		October	---	---	---	---	None	Very brief	Occasional
061HE: Haynie-----	B	April	---	---	---	---	None	Very brief	Frequent
		May	---	---	---	---	None	Very brief	Frequent
		June	---	---	---	---	None	Very brief	Frequent
		July	---	---	---	---	None	Very brief	Frequent
		August	---	---	---	---	None	Very brief	Frequent
		September	---	---	---	---	None	Very brief	Frequent
		October	---	---	---	---	None	Very brief	Frequent
061KA: Kahola-----	B	January	---	---	---	---	None	---	Rare
		February	---	---	---	---	None	---	Rare
		March	---	---	---	---	None	---	Rare
		April	---	---	---	---	None	Very brief	Frequent
		May	---	---	---	---	None	Very brief	Frequent
		June	---	---	---	---	None	Very brief	Frequent
		July	---	---	---	---	None	Very brief	Frequent
		August	---	---	---	---	None	Very brief	Frequent
		September	---	---	---	---	None	Very brief	Frequent
		October	---	---	---	---	None	Very brief	Frequent
		November	---	---	---	---	None	---	Rare
		December	---	---	---	---	None	---	Rare
061KB: Kahola-----	B	January	---	---	---	---	None	---	Rare
		February	---	---	---	---	None	---	Rare
		March	---	---	---	---	None	---	Rare
		April	---	---	---	---	None	Very brief	Occasional
		May	---	---	---	---	None	Very brief	Occasional
		June	---	---	---	---	None	Very brief	Occasional
		July	---	---	---	---	None	Very brief	Occasional
		August	---	---	---	---	None	Very brief	Occasional
		September	---	---	---	---	None	Very brief	Occasional
		October	---	---	---	---	None	Very brief	Occasional
		November	---	---	---	---	None	---	Rare
		December	---	---	---	---	None	---	Rare
061RE:									

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro-logic group	Month	Soil Saturation		Ponding			Flooding		
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency	
			Ft	Ft	Ft					
Reading-----	B	March	---	---	---	---	None	---	Rare	
		April	---	---	---	---	None	---	Rare	
		May	---	---	---	---	None	---	Rare	
		June	---	---	---	---	None	---	Rare	
		July	---	---	---	---	None	---	Rare	
		August	---	---	---	---	None	---	Rare	
		September	---	---	---	---	None	---	Rare	
		October	---	---	---	---	None	---	Rare	
		November	---	---	---	---	None	---	Rare	
					---	---	---	---	---	---
					---	---	---	---	---	---
061TO: Tully-----	C		---	---	---	---	---	---		
117PA: Pawnee-----	D		---	---	---	---	---	---		
117PB: Pawnee-----	D	March	1.0-3.0	4.0-6.0	---	---	---	---	None	
		April	1.0-3.0	4.0-6.0	---	---	---	---	None	
		May	1.0-3.0	4.0-6.0	---	---	---	---	None	
149HS: Haynie-----	B	March	1.0-3.0	4.0-6.0	---	---	---	---	None	
		April	1.0-3.0	4.0-6.0	---	---	---	---	None	
		May	1.0-3.0	4.0-6.0	---	---	---	---	None	
Sarpy-----	A	January	---	---	---	---	---	---	Rare	
		February	---	---	---	---	---	---	Rare	
		March	---	---	---	---	---	Brief	Occasional	
		April	---	---	---	---	---	Brief	Occasional	
		May	---	---	---	---	---	Brief	Occasional	
		June	---	---	---	---	---	Brief	Occasional	
		July	---	---	---	---	---	Brief	Occasional	
		August	---	---	---	---	---	Brief	Occasional	
		September	---	---	---	---	---	Brief	Occasional	
		October	---	---	---	---	---	Brief	Occasional	
		November	---	---	---	---	---	---	Rare	
		December	---	---	---	---	---	---	Rare	
149PS: Paxico-----	B	January	1.5-3.0	>6.0	---	---	---	Brief	Very rare	
		February	1.5-3.0	>6.0	---	---	---	Brief	Very rare	
		March	1.5-3.0	>6.0	---	---	---	Brief	Rare	
		April	1.5-3.0	>6.0	---	---	---	Long	Frequent	
		May	1.5-3.0	>6.0	---	---	---	Long	Frequent	
		June	---	---	---	---	---	Long	Frequent	
		July	---	---	---	---	---	Long	Frequent	
		August	---	---	---	---	---	Long	Frequent	
		September	---	---	---	---	---	Long	Frequent	
		October	---	---	---	---	---	Long	Frequent	
		November	1.5-3.0	>6.0	---	---	---	Brief	Rare	
		December	1.5-3.0	>6.0	---	---	---	Brief	Very rare	
149SF: Sarpy-----	A	January	---	---	---	---	---	---	Rare	
		February	---	---	---	---	---	---	Rare	
		March	---	---	---	---	---	Long	Frequent	
		April	---	---	---	---	---	Long	Frequent	
		May	---	---	---	---	---	Long	Frequent	
		June	---	---	---	---	---	---	Rare	
		July	---	---	---	---	---	---	Rare	
		August	---	---	---	---	---	---	Rare	
		September	---	---	---	---	---	---	Rare	
		October	---	---	---	---	---	---	Rare	
		November	---	---	---	---	---	---	Rare	
		December	---	---	---	---	---	---	Rare	
197CM: Clime-----	C		---	---	---	---	---	---		
197FL: Florence-----	C		---	---	---	---	---	---		

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro-logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
Labette-----	C		Ft ---	Ft ---	Ft ---	---	---	---	---
197IB: Irwin-----	D		---	---	---	---	---	---	---
197ID: Irwin-----	D		---	---	---	---	---	---	---
197IV: Ivan-----	B	January	---	---	---	---	---	---	Rare
		February	---	---	---	---	---	---	Rare
		March	---	---	---	---	Very brief	Occasional	Occasional
		April	---	---	---	---	Very brief	Occasional	Occasional
		May	---	---	---	---	Very brief	Occasional	Occasional
		June	---	---	---	---	Very brief	Occasional	Occasional
		July	---	---	---	---	Very brief	Occasional	Occasional
		August	---	---	---	---	Very brief	Occasional	Occasional
		September	---	---	---	---	Very brief	Occasional	Occasional
		October	---	---	---	---	Very brief	Occasional	Occasional
		November	---	---	---	---	---	---	Rare
		December	---	---	---	---	---	---	Rare
197IX: Ivan-----	B	January	---	---	---	---	---	---	Rare
		February	---	---	---	---	---	---	Rare
		March	---	---	---	---	Very brief	Frequent	Frequent
		April	---	---	---	---	Very brief	Frequent	Frequent
		May	---	---	---	---	Very brief	Frequent	Frequent
		June	---	---	---	---	Very brief	Frequent	Frequent
		July	---	---	---	---	Very brief	Frequent	Frequent
		August	---	---	---	---	Very brief	Frequent	Frequent
		September	---	---	---	---	Very brief	Frequent	Frequent
		October	---	---	---	---	Very brief	Frequent	Frequent
		November	---	---	---	---	---	---	Rare
		December	---	---	---	---	---	---	Rare
197PN: Pawnee-----	D	February	0.8-1.2	2.8-3.2	---	---	---	---	None
		March	0.8-1.2	2.8-3.2	---	---	---	---	None
		April	0.8-1.2	2.8-3.2	---	---	---	---	None
197WE: Wamego-----	C		---	---	---	---	---	---	---
201CS: Crete-----	C		---	---	---	---	---	---	---
201CX: Crete, eroded-----	C		---	---	---	---	---	---	---
201KS: Kipson-----	D		---	---	---	---	---	---	---
Sogn-----	D		---	---	---	---	---	---	---
201LC: Lancaster-----	B		---	---	---	---	---	---	---
Ad: Ivan-----	B	April	---	---	---	---	---	Very brief	Frequent
		May	---	---	---	---	---	Very brief	Frequent
		June	---	---	---	---	---	Very brief	Frequent
		July	---	---	---	---	---	Very brief	Frequent
		August	---	---	---	---	---	Very brief	Frequent
		September	---	---	---	---	---	Very brief	Frequent
		October	---	---	---	---	---	Very brief	Frequent
BE: Benfield-----	C		---	---	---	---	---	---	---
Bf: Benfield-----	C		---	---	---	---	---	---	---
Florence-----	C		---	---	---	---	---	---	---
Bk: Wymore-----	D	March	1.0-3.0	1.5-3.0	---	---	---	---	None
		April	1.0-3.0	1.5-3.0	---	---	---	---	None

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro-logic group	Month	Soil Saturation		Ponding			Flooding		
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency	
Kennebec-----	B	January	3.0-5.0	>6.0	---	---	---	---	Rare	
		February	3.0-5.0	>6.0	---	---	---	---	Rare	
		March	3.0-5.0	>6.0	---	---	---	Very brief	Occasional	
		April	3.0-5.0	>6.0	---	---	---	Very brief	Occasional	
		May	3.0-5.0	>6.0	---	---	---	Very brief	Occasional	
		June	3.0-5.0	>6.0	---	---	---	Very brief	Occasional	
		July	3.0-5.0	>6.0	---	---	---	Very brief	Occasional	
		August	---	---	---	---	---	Very brief	Occasional	
		September	---	---	---	---	---	Very brief	Occasional	
		October	---	---	---	---	---	Very brief	Occasional	
		November	3.0-5.0	>6.0	---	---	---	---	Rare	
		December	3.0-5.0	>6.0	---	---	---	---	Rare	
BOP: Borrow Pits-----	---		---	---	---	---	---	---		
Ca: Carr-----	B	April	---	---	---	---	---	Brief	Occasional	
		May	---	---	---	---	---	Brief	Occasional	
		June	---	---	---	---	---	Brief	Occasional	
		July	---	---	---	---	---	Brief	Occasional	
		August	---	---	---	---	---	Brief	Occasional	
		September	---	---	---	---	---	Brief	Occasional	
		October	---	---	---	---	---	Brief	Occasional	
Sarpy-----	A	April	---	---	---	---	---	Brief	Occasional	
		May	---	---	---	---	---	Brief	Occasional	
		June	---	---	---	---	---	Brief	Occasional	
		July	---	---	---	---	---	Brief	Occasional	
		August	---	---	---	---	---	Brief	Occasional	
		September	---	---	---	---	---	Brief	Occasional	
		October	---	---	---	---	---	Brief	Occasional	
Ch: Chase-----	C	February	2.0-4.0	>6.0	---	---	---	---	None	
		March	2.0-4.0	>6.0	---	---	---	---	None	
		April	2.0-4.0	>6.0	---	---	---	Brief	Rare	
		May	2.0-4.0	>6.0	---	---	---	Brief	Rare	
		June	---	---	---	---	---	Brief	Rare	
		July	---	---	---	---	---	Brief	Rare	
		August	---	---	---	---	---	Brief	Rare	
		September	---	---	---	---	---	Brief	Rare	
		October	---	---	---	---	---	Brief	Rare	
Cs: Clime-----	C		---	---	---	---	---	---	---	
Sogn-----	D		---	---	---	---	---	---	---	
CT: Crete-----	C		---	---	---	---	---	---	---	
Dr: Dwight-----	D		---	---	---	---	---	---	---	
Irwin-----	D		---	---	---	---	---	---	---	
Dw: Dwight-----	D		---	---	---	---	---	---	---	
Irwin-----	D		---	---	---	---	---	---	---	
Em: Elmont-----	B		---	---	---	---	---	---	---	
En: Elmont-----	B		---	---	---	---	---	---	---	
Clime-----	C		---	---	---	---	---	---	---	
Eu: Eudora-----	B	April	---	---	---	---	---	None	Very brief	Occasional
		May	---	---	---	---	---	None	Very brief	Occasional
		June	---	---	---	---	---	None	Very brief	Occasional
		July	---	---	---	---	---	None	Very brief	Occasional
		August	---	---	---	---	---	None	Very brief	Occasional
		September	---	---	---	---	---	None	Very brief	Occasional
		October	---	---	---	---	---	None	Very brief	Occasional
Ga: Geary-----	B		---	---	---	---	---	---	---	
Ge: Geary-----	B		---	---	---	---	---	---	---	

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro-logic group	Month	Soil Saturation		Ponding			Flooding		
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency	
Ha: Haynie-----	B	April	---	---	---	---	---	---	---	
		May	---	---	---	---	---	Brief	Occasional	
		June	---	---	---	---	---	Brief	Occasional	
		July	---	---	---	---	---	Brief	Occasional	
		August	---	---	---	---	---	Brief	Occasional	
		September	---	---	---	---	---	Brief	Occasional	
		October	---	---	---	---	---	Brief	Occasional	
HO: Hobbs-----	B	April	---	---	---	---	---	None	Brief	Occasional
		May	---	---	---	---	---	None	Brief	Occasional
		June	---	---	---	---	---	None	Brief	Occasional
		July	---	---	---	---	---	None	Brief	Occasional
		August	---	---	---	---	---	None	Brief	Occasional
		September	---	---	---	---	---	None	Brief	Occasional
		October	---	---	---	---	---	None	Brief	Occasional
Ic: Irwin-----	D		---	---	---	---	---	---	---	
Id: Irwin, eroded-----	D		---	---	---	---	---	---	---	
Ie: Ivan-----	B		---	---	---	---	---	---	---	
Iv: Ivan-----	B	January	---	---	---	---	---	---	Rare	
		February	---	---	---	---	---	---	Rare	
		March	---	---	---	---	---	Very brief	Occasional	
		April	---	---	---	---	---	Very brief	Occasional	
		May	---	---	---	---	---	Very brief	Occasional	
		June	---	---	---	---	---	Very brief	Occasional	
		July	---	---	---	---	---	Very brief	Occasional	
		August	---	---	---	---	---	Very brief	Occasional	
		September	---	---	---	---	---	Very brief	Occasional	
		October	---	---	---	---	---	Very brief	Occasional	
		November	---	---	---	---	---	---	Rare	
		December	---	---	---	---	---	---	Rare	
Kennebec-----	B	January	3.0-5.0	>6.0	---	---	---	---	Rare	
		February	3.0-5.0	>6.0	---	---	---	---	Rare	
		March	3.0-5.0	>6.0	---	---	---	Very brief	Occasional	
		April	3.0-5.0	>6.0	---	---	---	Very brief	Occasional	
		May	3.0-5.0	>6.0	---	---	---	Very brief	Occasional	
		June	3.0-5.0	>6.0	---	---	---	Very brief	Occasional	
		July	3.0-5.0	>6.0	---	---	---	Very brief	Occasional	
		August	---	---	---	---	---	Very brief	Occasional	
		September	---	---	---	---	---	Very brief	Occasional	
		October	---	---	---	---	---	Very brief	Occasional	
		November	3.0-5.0	>6.0	---	---	---	---	Rare	
		December	3.0-5.0	>6.0	---	---	---	---	Rare	
Ka: Kahola-----	B	January	---	---	---	---	---	---	Rare	
		February	---	---	---	---	---	---	Rare	
		March	---	---	---	---	---	---	Rare	
		April	---	---	---	---	---	---	Rare	
		May	---	---	---	---	---	---	Rare	
		June	---	---	---	---	---	---	Rare	
		July	---	---	---	---	---	---	Rare	
		August	---	---	---	---	---	---	Rare	
		September	---	---	---	---	---	---	Rare	
		October	---	---	---	---	---	---	Rare	
		November	---	---	---	---	---	---	Rare	
		December	---	---	---	---	---	---	Rare	
Ke: Kenesaw-----	B		---	---	---	---	---	---	---	
Kf: Kenesaw-----	B		---	---	---	---	---	---	---	
KN:			---	---	---	---	---	---	---	

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro-logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
Kennebec-----	B	January	3.3-3.7	>6.0	---	---	---	---	Rare
		February	3.3-3.7	>6.0	---	---	---	---	Rare
		March	3.3-3.7	>6.0	---	---	---	Brief	Occasional
		April	3.3-3.7	>6.0	---	---	---	Brief	Occasional
		May	---	---	---	---	---	Brief	Occasional
		June	---	---	---	---	---	Brief	Occasional
		July	---	---	---	---	---	Brief	Occasional
		August	---	---	---	---	---	Brief	Occasional
		September	---	---	---	---	---	Brief	Occasional
		October	---	---	---	---	---	Brief	Occasional
		November	---	---	---	---	---	---	Rare
		December	---	---	---	---	---	---	Rare
M-W: Miscellaneous Water-----	---		---	---	---	---	---	---	
Ma: Mayberry-----	D	February	0.8-1.2	2.8-3.2	---	---	---	---	None
March		0.8-1.2	2.8-3.2	---	---	---	---	None	
April		0.8-1.2	2.8-3.2	---	---	---	---	None	
Mb: Mayberry-----	D	March	0.5-1.5	1.0-3.0	---	---	---	---	None
April		0.5-1.5	1.0-3.0	---	---	---	---	None	
May		0.5-1.5	1.0-3.0	---	---	---	---	None	
Mu: Muir-----	B	April	---	---	---	---	None	Brief	Rare
May		---	---	---	---	---	None	Brief	Rare
June		---	---	---	---	---	None	Brief	Rare
July		---	---	---	---	---	None	Brief	Rare
August		---	---	---	---	---	None	Brief	Rare
September		---	---	---	---	---	None	Brief	Rare
October		---	---	---	---	---	None	Brief	Rare
QUA: Quarries-----		---		---	---	---	---	---	---
Rd: Reading-----		B	January	---	---	---	---	---	---
February	---		---	---	---	---	---	---	Rare
March	---		---	---	---	---	---	---	Rare
April	---		---	---	---	---	---	---	Rare
May	---		---	---	---	---	---	---	Rare
June	---		---	---	---	---	---	---	Rare
July	---		---	---	---	---	---	---	Rare
August	---		---	---	---	---	---	---	Rare
September	---		---	---	---	---	---	---	Rare
October	---		---	---	---	---	---	---	Rare
November	---		---	---	---	---	---	---	Rare
December	---		---	---	---	---	---	---	Rare
Re: Reading-----	B	January	---	---	---	---	---	---	Rare
February		---	---	---	---	---	---	---	Rare
March		---	---	---	---	---	---	---	Rare
April		---	---	---	---	---	---	---	Rare
May		---	---	---	---	---	---	---	Rare
June		---	---	---	---	---	---	---	Rare
July		---	---	---	---	---	---	---	Rare
August		---	---	---	---	---	---	---	Rare
September		---	---	---	---	---	---	---	Rare
October		---	---	---	---	---	---	---	Rare
November		---	---	---	---	---	---	---	Rare
December		---	---	---	---	---	---	---	Rare
Sa: Sarpy-----	A	January	---	---	---	---	---	---	Rare
February		---	---	---	---	---	---	---	Rare
March		---	---	---	---	---	Brief	Occasional	
April		---	---	---	---	---	Brief	Occasional	
May		---	---	---	---	---	Brief	Occasional	
June		---	---	---	---	---	Brief	Occasional	
July		---	---	---	---	---	Brief	Occasional	
August		---	---	---	---	---	Brief	Occasional	
September		---	---	---	---	---	Brief	Occasional	
October		---	---	---	---	---	Brief	Occasional	
November		---	---	---	---	---	---	Rare	
December		---	---	---	---	---	---	Rare	
Sm: Smolan-----	C		---	---	---	---	---	---	

(Depths of layers are in feet. See text for definitions of terms used in this table. Estimates of the frequency of ponding and flooding apply to the whole year rather than to individual months. Absence of an entry indicates that the feature is not a concern or that data were not estimated.)

Map symbol and soil name	Hydro- logic group	Month	Soil Saturation		Ponding			Flooding	
			Upper limit	Lower limit	Surface water depth	Duration	Frequency	Duration	Frequency
Sn: Smolan-----	C		---	---	---	---	---	---	---
So: Smolan, eroded-----	C		---	---	---	---	---	---	---
St: Clime-----	C		---	---	---	---	---	---	---
Su: Sutphen-----	D	April	---	---	---	---	---	Brief	Occasional
		May	---	---	---	---	---	Brief	Occasional
		June	---	---	---	---	---	Brief	Occasional
		July	---	---	---	---	---	Brief	Occasional
		August	---	---	---	---	---	Brief	Occasional
		September	---	---	---	---	---	Brief	Occasional
		October	---	---	---	---	---	Brief	Occasional
Ts: Tully-----	C		---	---	---	---	---	---	---
Tt: Tully, eroded-----	C		---	---	---	---	---	---	---
Tu: Tully-----	C		---	---	---	---	---	---	---
Tv: Tully, eroded-----	C		---	---	---	---	---	---	---
W: Water-----	---		---	---	---	---	---	---	---
Wm: Wymore-----	D	March	1.0-3.0	1.5-3.0	---	---	---	---	None
		April	1.0-3.0	1.5-3.0	---	---	---	---	None
Wn: Wymore-----	D	March	1.0-3.0	1.5-3.0	---	---	---	---	None
		April	1.0-3.0	1.5-3.0	---	---	---	---	None
Wo: Wymore, eroded-----	D	March	1.0-3.0	1.5-3.0	---	---	---	---	None
		April	1.0-3.0	1.5-3.0	---	---	---	---	None
Wr: Wymore-----	D	March	1.0-3.0	1.5-3.0	---	---	---	---	None
		April	1.0-3.0	1.5-3.0	---	---	---	---	None
Ws: Wymore, eroded-----	D	March	1.0-3.0	1.5-3.0	---	---	---	---	None
		April	1.0-3.0	1.5-3.0	---	---	---	---	None

The following table gives estimates of various soil features. The estimates are used in land use planning that involves engineering considerations.

A restrictive layer is a nearly continuous layer that has one or more physical, chemical, or thermal properties that significantly impede the movement of water and air through the soil or that restrict roots or otherwise provide an unfavorable root environment. Examples are bedrock, cemented layers, dense layers, and frozen layers. The table indicates the hardness and thickness of the restrictive layer, both of which significantly affect the ease of excavation. Depth to top is the vertical distance from the soil surface to the upper boundary of the restrictive layer.

Potential for frost action is the likelihood of upward or lateral expansion of the soil caused by the formation of segregated ice lenses (frost heave) and the subsequent collapse of the soil and loss of strength on thawing. Frost action occurs when moisture moves into the freezing zone of the soil. Temperature, texture, density, permeability, content of organic matter, and depth to the water table are the most important factors considered in evaluating the potential for frost action. It is assumed that the soil is not insulated by vegetation or snow and is not artificially drained. Silty and highly structured, clayey soils that have a high water table in winter are the most susceptible to frost action. Well drained, very gravelly, or very sandy soils are the least susceptible. Frost heave and low soil strength during thawing cause damage to pavements and other rigid structures.

Risk of corrosion pertains to potential soil-induced electrochemical or chemical action that corrodes or weakens uncoated steel or concrete. The rate of corrosion of uncoated steel is related to such factors as soil moisture, particle-size distribution, acidity, and electrical conductivity of the soil. The rate of corrosion of concrete is based mainly on the sulfate and sodium content, texture, moisture content, and acidity of the soil. Special site examination and design may be needed if the combination of factors results in a severe hazard of corrosion. The steel or concrete in installations that intersect soil boundaries or soil layers is more susceptible to corrosion than the steel or concrete in installations that are entirely within one kind of soil or within one soil layer.

For uncoated steel, the risk of corrosion, expressed as low, moderate, or high, is based on soil drainage class, total acidity, electrical resistivity near field capacity, and electrical conductivity of the saturation extract.

For concrete, the risk of corrosion also is expressed as low, moderate, or high. It is based on soil texture, acidity, and amount of sulfates in the saturation extract.

Map symbol and soil name	Restrictive layer				Potential for Frost action	Risk of corrosion	
	Kind	Depth to top In	Thickness In	Hardness		Uncoated Steel	Concrete
027CS: Crete-----	---	---	---	---	Moderate	Moderate	Low
027CX: Crete-----	---	---	---	---	Moderate	Moderate	Low
027HN: Hobbs-----	---	---	---	---	Moderate	Low	Low
027KS: Kipson-----	7-20	Bedrock (paralithic)	---	---	Moderate	Low	Low
Sogn-----	4-20	Bedrock (lithic)	---	---	Moderate	Low	Low
061BE: Benfield-----	20-40	Bedrock (paralithic)	---	Moderately cemented	Low	High	Low
Florence-----	40-60	Bedrock (lithic)	---	Indurated	Low	Moderate	Low
061CF: Clime-----	20-40	Bedrock (paralithic)	---	Moderately cemented	Low	High	Low
Sogn-----	4-20	Bedrock (lithic)	---	Strongly cemented	Moderate	Low	Low
061CR: Crete-----	---	---	---	---	Low	Moderate	Low
061CS: Crete-----	---	---	---	---	Low	Moderate	Low
061EU: Eudora-----	---	---	---	---	High	Low	Low
061HE: Haynie-----	---	---	---	---	High	Low	Low
061KA: Kahola-----	---	---	---	---	Moderate	Low	Low
061KB: Kahola-----	---	---	---	---	Moderate	Low	Low
061RE: Reading-----	---	---	---	---	Moderate	Moderate	Low
061TO: Tully-----	---	---	---	---	Low	High	Low
117PA: Pawnee-----	---	---	---	---	High	High	Low
117PB: Pawnee-----	---	---	---	---	High	High	Low
149HS: Haynie-----	---	---	---	---	High	Low	Low
Sarpy-----	---	---	---	---	Low	Low	Low
149PS: Paxico-----	---	---	---	---	High	High	Low
149SF: Sarpy-----	---	---	---	---	Low	Low	Low
197CM: Clime-----	20-40	Bedrock (paralithic)	---	Weakly cemented	Moderate	High	Low
197FL: Florence-----	40-60	Bedrock (lithic)	---	Indurated	Moderate	Moderate	Low
Labette-----	20-40	Bedrock (lithic)	---	Indurated	Moderate	High	Low
197IB: Irwin-----	---	---	---	---	Moderate	High	Low
197ID: Irwin-----	---	---	---	---	Moderate	High	Low
197IV: Ivan-----	---	---	---	---	Moderate	Low	Low
197IX: Ivan-----	---	---	---	---	Moderate	Low	Low
197PN: Pawnee-----	---	---	---	---	High	High	Low
197WE: Wamego-----	20-40	Bedrock (paralithic)	---	Noncemented	Moderate	Moderate	Moderate
201CS: Crete-----	---	---	---	---	Moderate	Moderate	Low
201CX: Crete, eroded---	---	---	---	---	Moderate	Moderate	Low
201KS: Kipson-----	7-20	Bedrock (paralithic)	---	Weakly cemented	Moderate	Low	Low
Sogn-----	4-20	Bedrock (lithic)	---	Indurated	Moderate	Low	Low
201LC: Lancaster-----	20-40	Bedrock (paralithic)	---	Moderately cemented	Moderate	Low	Moderate
Ad: Ivan-----	---	---	---	---	Moderate	Low	Low
AED: Arents, Earthen Dam-----	---	---	---	---	---	---	---
BE: Benfield-----	20-40	Bedrock (paralithic)	---	Weakly cemented	Moderate	High	Low
Bf: Benfield-----	22-39	Bedrock (paralithic)	---	---	Moderate	High	Low
Florence-----	24-39	Bedrock (lithic)	---	Indurated	Moderate	Moderate	Low

Map symbol and soil name	Restrictive layer				Potential for Frost action	Risk of corrosion	
	Kind	Depth to top	Thickness	Hardness		Uncoated Steel	Concrete
Bk:		In	In				
Wymore-----	---	---	---	---	High	High	Moderate
Kennebec-----	---	---	---	---	High	Moderate	Low
BOP:							
Borrow Pits-----	---	---	---	---	---	---	---
Ca:							
Carr-----	---	---	---	---	Low	Low	Low
Sarpy-----	---	---	---	---	Low	Low	Low
Ch:							
Chase-----	---	---	---	---	High	High	Low
Cs:							
Clime-----	20-40	Bedrock (paralithic)	---	Weakly cemented	Moderate	High	Low
Sogn-----	4-20	Bedrock (lithic)	---	Indurated	Moderate	Low	Low
CT:							
Crete-----	---	---	---	---	Moderate	Moderate	Low
Dr:							
Dwight-----	40-60	Bedrock (lithic)	---	---	Moderate	High	Moderate
Irwin-----	40-60	Bedrock (paralithic)	---	---	Moderate	High	Low
Dw:							
Dwight-----	40-60	Bedrock (lithic)	---	---	Moderate	High	Moderate
Irwin-----	40-60	Bedrock (paralithic)	---	---	Moderate	High	Low
Em:							
Elmont-----	40-60	Bedrock (paralithic)	---	---	High	Moderate	Low
En:							
Elmont-----	40-60	Bedrock (paralithic)	---	---	High	Moderate	Low
Clime-----	20-40	Bedrock (paralithic)	---	---	Moderate	High	Low
Eu:							
Eudora-----	---	---	---	---	High	Low	Low
Ga:							
Geary-----	---	---	---	---	High	Low	Low
Ge:							
Geary-----	---	---	---	---	High	Low	Low
Ha:							
Haynie-----	---	---	---	---	High	Low	Low
HO:							
Hobbs-----	---	---	---	---	Moderate	Low	Low
Ic:							
Irwin-----	40-60	Bedrock (paralithic)	---	Weakly cemented	Moderate	High	Low
Id:							
Irwin, eroded---	40-60	Bedrock (paralithic)	---	Weakly cemented	Moderate	High	Low
Ie:							
Ivan-----	---	---	---	---	Moderate	Low	Low
Iv:							
Ivan-----	---	---	---	---	Moderate	Low	Low
Kennebec-----	---	---	---	---	High	Moderate	Low
Ka:							
Kahola-----	---	---	---	---	Moderate	Low	Low
Ke:							
Kenesaw-----	---	---	---	---	Moderate	Moderate	Low
Kf:							
Kenesaw-----	---	---	---	---	Moderate	Moderate	Low
KN:							
Kennebec-----	---	---	---	---	High	Moderate	Low
M-W:							
Miscellaneous	---	---	---	---	---	---	---
Water-----							
Ma:							
Mayberry-----	---	---	---	---	High	High	Low
Mb:							
Mayberry-----	---	---	---	---	High	High	Low
Mu:							
Muir-----	---	---	---	---	Moderate	Low	Moderate
QUA:							
Quarries-----	---	---	---	---	---	---	---
Rd:							
Reading-----	---	---	---	---	High	Moderate	Low
Re:							
Reading-----	---	---	---	---	High	Moderate	Low
Sa:							
Sarpy-----	---	---	---	---	Low	Low	Low
Sm:							
Smolan-----	---	---	---	---	Moderate	Moderate	Low
Sn:							
Smolan-----	---	---	---	---	Moderate	Moderate	Low
So:							
Smolan, eroded--	---	---	---	---	Moderate	Moderate	Low
St:							
Clime-----	20-40	Bedrock (paralithic)	---	Moderately cemented	Low	High	Low

Map symbol and soil name	Restrictive layer				Potential for Frost action	Risk of corrosion	
	Kind	Depth to top	Thickness	Hardness		Uncoated Steel	Concrete
Su:		In	In				
Sutphen-----	---	---	---	---	Low	High	Low
Ts:							
Tully-----	---	---	---	---	Low	High	Low
Tt:							
Tully, eroded---	---	---	---	---	Moderate	High	Low
Tu:							
Tully-----	---	---	---	---	Moderate	High	Low
Tv:							
Tully, eroded---	---	---	---	---	Moderate	High	Low
W:							
Water-----	---	---	---	---	Low	---	---
Wm:							
Wymore-----	---	---	---	---	High	High	Moderate
Wn:							
Wymore-----	---	---	---	---	High	High	Moderate
Wo:							
Wymore, eroded--	---	---	---	---	High	High	Moderate
Wr:							
Wymore-----	---	---	---	---	High	High	Moderate
Ws:							
Wymore, eroded--	---	---	---	---	High	High	Moderate

WATER MANAGEMENT
Riley County, Kansas

The soils of the survey area are rated in the Water Management table according to limitations that affect their suitability for water management. Soils are rated for pond reservoir areas, drainage, irrigation, terraces and diversions, and grassed waterways. Restrictive features that affect each soil for the specified use is also provided in the table.

The ratings in the table are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Moderately limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Limited indicates that the soil has one or more features that are significant limitations for the specified use. The limitations can be overcome, but generally require special design, soil reclamation, or installation procedures that may result in additional expense. Fair performance and moderate to high maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Limitation class terms, such as very limited or limited, etc., limitation ratings, and numerical ratings are shown for each soil feature listed. As many as three soil features may be listed for each soil component if applicable. The overall limitation rating for the soil component is based on the most severe limitation.

Pond reservoir areas hold water behind a dam or embankment. Soils best suited to this use have low seepage potential in the upper 60 inches. The seepage potential is determined by the permeability of the soil and the depth to fractured bedrock or other permeable material. Excessive slope can affect the storage capacity of the reservoir area.

Embankments, dikes, and levees are raised structures of soil material, generally less than 20 feet high, constructed to impound water or to protect land against overflow. In this table, the soils are rated as a source of material for embankment fill. The ratings apply to the soil material below the surface layer to a depth of about 5 feet. It is assumed that soil layers will be uniformly mixed and compacted during construction.

The ratings do not indicate the ability of the natural soil to support an embankment. Soil properties to a depth even greater than the height of the embankment can affect performance and safety of the embankment. Generally, deeper onsite investigation is needed to determine these properties.

Soil material in embankments must be resistant to seepage, piping, and erosion and have favorable compaction characteristics. Unfavorable features include less than 5 feet of suitable material and a high content of stones or boulders, organic matter, or salts or sodium. A high water table affects the amount of usable material. It also affects traffic ability.

Aquifer-fed excavated ponds are pits or dugouts that extend to a ground-water aquifer or to a depth below a permanent water table. Excluded are ponds that are fed only by surface runoff and embankment ponds that impound water 3 feet or more above the original surface. Excavated ponds are affected by depth to a permanent water table, permeability of the aquifer, and quality of the water as inferred from the salinity of the soil. Depth to bedrock and the content of large stones affect the ease of excavation.

Drainage is the removal of excess surface and subsurface water from the soil. How easily and effectively the soil is drained depends on the depth to bedrock, to a cemented pan, or to other layers that affect the rate of water movement; permeability; depth to a high water table or depth of standing water if the soil is subject to ponding; slope; susceptibility to flooding; subsidence of organic layers; and the potential for frost action. Excavating and grading and the stability of ditch banks are affected by depth to bedrock or to a cemented pan, large stones, slope, and the hazard of cutbanks caving. The productivity of the soil after drainage is adversely affected by extreme acidity or by toxic substances in the root zone, such as salts, sodium, and sulfur. Availability of drainage outlets is not considered in the ratings.

Irrigation is the controlled application of water to supplement rainfall and support plant growth. The design and management of an irrigation system are affected by depth to the water table, the need for drainage, flooding, available water capacity, intake rate, permeability, erosion hazard, and slope. The construction of a system is affected by large stones and depth to bedrock or to a cemented pan. The performance of a system is affected by the depth of the root zone, the amount of salts or sodium, and soil reaction.

Terraces and diversions are embankments or a combination of channels and ridges constructed across a slope to control erosion and conserve moisture by intercepting runoff. Slope, wetness, large stones, and depth to bedrock or to a cemented pan affect the construction of terraces and diversions. A restricted rooting depth, a very limited hazard of wind erosion or water erosion, an excessively coarse texture, and restricted permeability adversely affect maintenance.

Grassed waterways are natural or constructed channels, generally broad and shallow, which conduct surface water to outlets at a non-erosive velocity. Large stones, wetness, slope, and depth to bedrock or to a cemented pan affect the construction of grassed waterways. A hazard of wind erosion, low available water capacity, restricted rooting depth, toxic substances such as salts and sodium, and restricted permeability adversely affect the growth and maintenance of the grass after construction.

WATER MANAGEMENT--Continued
Riley County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
027CS: Crete-----	Limitation: deep to water	Limitation: erodes easily percs slowly	Limitation: erodes easily	Limitation: erodes easily percs slowly
027CX: Crete-----	Limitation: deep to water	Limitation: erodes easily percs slowly slope	Limitation: erodes easily	Limitation: erodes easily percs slowly
027HN: Hobbs-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
027KS: Kipson-----	Limitation: deep to water	Limitation: slope thin layer	Limitation: area reclaim large stones slope	Limitation: area reclaim large stones slope
Sogn-----	Limitation: deep to water	Limitation: slope thin layer	Limitation: area reclaim slope depth to rock	Limitation: area reclaim slope depth to rock
061BE: Benfield-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily slope	Limitation: area reclaim erodes easily slope
Florence-----	Limitation: deep to water	Limitation: large stones slope droughty	Limitation: large stones slope	Limitation: large stones slope droughty
061CF: Clime-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily slope	Limitation: area reclaim erodes easily slope
Sogn-----	Limitation: deep to water	Limitation: slope thin layer	Limitation: area reclaim slope depth to rock	Limitation: area reclaim slope depth to rock
061CR: Crete-----	Limitation: deep to water	Limitation: erodes easily percs slowly	Limitation: erodes easily	Limitation: erodes easily percs slowly
061CS: Crete-----	Limitation: deep to water	Limitation: erodes easily percs slowly	Limitation: erodes easily	Limitation: erodes easily percs slowly
061EU: Eudora-----	Limitation: deep to water	Limitation: flooding	Limitation: erodes easily	Limitation: erodes easily
061HE: Haynie-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
061KA: Kahola-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
061KB: Kahola-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
061RE: Reading-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
061TO: Tully-----	Limitation: deep to water	Limitation: erodes easily percs slowly slope	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
117PA: Pawnee-----	Limitation: frost action percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily
117PB: Pawnee-----	Limitation: frost action percs slowly slope	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily
149HS: Haynie-----	Limitation: deep to water	Limitation: erodes easily soil blowing	Limitation: erodes easily soil blowing	Limitation: erodes easily
Sarpy-----	Limitation: deep to water	Limitation: fast intake droughty	Limitation: too sandy soil blowing	Limitation: droughty

WATER MANAGEMENT--Continued
Riley County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
149PS: Paxico-----	Limitation: flooding frost action	Limitation: erodes easily wetness	Limitation: erodes easily wetness	Limitation: erodes easily
149SF: Sarpy-----	Limitation: deep to water	Limitation: fast intake droughty	Limitation: too sandy soil blowing	Limitation: droughty
197CM: Clime-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily	Limitation: area reclaim erodes easily
197FL: Florence-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily depth to rock	Limitation: erodes easily depth to rock
Labette-----	Limitation: deep to water	Limitation: large stones slope droughty	Limitation: large stones slope	Limitation: large stones slope droughty
197IB: Irwin-----	Limitation: deep to water	Limitation: percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
197ID: Irwin-----	Limitation: deep to water	Limitation: percs slowly slope	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
197IV: Ivan-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
197IX: Ivan-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
197PN: Pawnee-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
197WE: Wamego-----	Limitation: deep to water	Limitation: percs slowly slope depth to rock	Limitation: erodes easily percs slowly depth to rock	Limitation: erodes easily percs slowly depth to rock
201CS: Crete-----	Limitation: deep to water	Limitation: erodes easily percs slowly	Limitation: erodes easily	Limitation: erodes easily percs slowly
201CX: Crete, eroded---	Limitation: deep to water	Limitation: erodes easily percs slowly slope	Limitation: erodes easily	Limitation: erodes easily percs slowly
201KS: Kipson-----	Limitation: deep to water	Limitation: large stones slope thin layer	Limitation: area reclaim large stones slope	Limitation: area reclaim large stones slope
Sogn-----	Limitation: deep to water	Limitation: slope thin layer	Limitation: area reclaim slope depth to rock	Limitation: area reclaim slope depth to rock
201LC: Lancaster-----	Limitation: deep to water	Limitation: slope depth to rock	Limitation: depth to rock	Limitation: depth to rock
Ad: Ivan-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
AED: Arents, Earthen Dam-----	---	---	---	---
BE: Benfield-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily	Limitation: area reclaim erodes easily
Bf: Benfield-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily slope	Limitation: area reclaim erodes easily slope

WATER MANAGEMENT--Continued
Riley County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
Florence-----	Limitation: deep to water	Limitation: large stones slope droughty	Limitation: large stones slope	Limitation: large stones slope droughty
Bk: Wymore-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily slope wetness	Limitation: erodes easily slope wetness
Kennebec-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
BOP: Borrow Pits-----	---	---	---	---
Ca: Carr-----	Limitation: deep to water	Limitation: flooding soil blowing	Limitation: soil blowing	Favorable
Sarpy-----	Limitation: deep to water	Limitation: fast intake droughty	Limitation: too sandy soil blowing	Limitation: droughty
Ch: Chase-----	Limitation: frost action percs slowly	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly
Cs: Clime-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily slope	Limitation: area reclaim erodes easily slope
Sogn-----	Limitation: deep to water	Limitation: slope thin layer	Limitation: area reclaim depth to rock	Limitation: area reclaim depth to rock
CT: Crete-----	Limitation: deep to water	Limitation: erodes easily percs slowly slope	Limitation: erodes easily	Limitation: erodes easily percs slowly
Dr: Dwight-----	Limitation: deep to water	Limitation: erodes easily excess sodium percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily excess sodium percs slowly
Irwin-----	Limitation: deep to water	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
Dw: Dwight-----	Limitation: deep to water	Limitation: erodes easily excess sodium percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily excess sodium percs slowly
Irwin-----	Limitation: deep to water	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
Em: Elmont-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily	Limitation: erodes easily
En: Elmont-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
Clime-----	Limitation: deep to water	Limitation: percs slowly slope thin layer	Limitation: area reclaim erodes easily slope	Limitation: area reclaim erodes easily slope
Eu: Eudora-----	Limitation: deep to water	Limitation: flooding	Limitation: erodes easily	Limitation: erodes easily
Ga: Geary-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
Ge: Geary-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily	Limitation: erodes easily
Ha: Haynie-----	Limitation: deep to water	Limitation: erodes easily soil blowing	Limitation: erodes easily soil blowing	Limitation: erodes easily
HO: Hobbs-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
Ic: Irwin-----	Limitation: deep to water	Limitation: erodes easily percs slowly slope	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly

WATER MANAGEMENT--Continued
Riley County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
Id: Irwin, eroded---	Limitation: deep to water	Limitation: erodes easily percs slowly slope	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
Ie: Ivan-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
Iv: Ivan-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
Kennebec-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
Ka: Kahola-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
Ke: Kenesaw-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily	Limitation: erodes easily
Kf: Kenesaw-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily slope	Limitation: erodes easily slope
KN: Kennebec-----	Limitation: deep to water	Limitation: flooding	Favorable	Favorable
M-W: Miscellaneous Water-----	---	---	---	---
Ma: Mayberry-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily percs slowly wetness	Limitation: erodes easily percs slowly wetness
Mb: Mayberry-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness
Mu: Muir-----	Limitation: deep to water	Favorable	Favorable	Favorable
QUA: Quarries-----	---	---	---	---
Rd: Reading-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
Re: Reading-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
Sa: Sarpy-----	Limitation: deep to water	Limitation: fast intake droughty	Limitation: too sandy soil blowing	Limitation: droughty
Sm: Smolan-----	Limitation: deep to water	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
Sn: Smolan-----	Limitation: deep to water	Limitation: erodes easily percs slowly slope	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
So: Smolan, eroded--	Limitation: deep to water	Limitation: erodes easily percs slowly slope	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
St: Clime-----	Limitation: deep to water	---	Limitation: percs slowly slope depth to rock	---
Su: Sutphen-----	Limitation: deep to water	Limitation: flooding percs slowly slow intake	Limitation: percs slowly	Limitation: percs slowly
Ts: Tully-----	Limitation: deep to water	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
Tt: Tully, eroded---	Limitation: deep to water	Limitation: percs slowly	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly

WATER MANAGEMENT--Continued
Riley County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
Tu: Tully-----	Limitation: deep to water	Limitation: percs slowly slope	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
Tv: Tully, eroded---	Limitation: deep to water	Limitation: percs slowly slope	Limitation: erodes easily percs slowly	Limitation: erodes easily percs slowly
W: Water-----	---	---	---	---
Wm: Wymore-----	Limitation: frost action percs slowly	Limitation: percs slowly wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness
Wn: Wymore-----	Limitation: frost action percs slowly	Limitation: percs slowly wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness
Wo: Wymore, eroded--	Limitation: frost action percs slowly	Limitation: percs slowly wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness
Wr: Wymore-----	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness
Ws: Wymore, eroded--	Limitation: frost action percs slowly slope	Limitation: percs slowly slope wetness	Limitation: erodes easily wetness	Limitation: erodes easily wetness

WATER MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
027CS: Crete-----	90	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack	0.76	Very limited Deep to water	1.00
027CX: Crete-----	83	Somewhat limited Seepage	0.57	Not limited		Very limited Deep to water	1.00
027HN: Hobbs-----	90	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.84	Very limited Deep to water	1.00
027KS: Kipson-----	70	Very limited Seepage Depth to bedrock Slope	1.00 0.53 0.01	Very limited Thin layer Piping	1.00 0.32	Very limited Deep to water	1.00
Sogn-----	15	Very limited Seepage Depth to bedrock Slope	1.00 1.00 0.01	Very limited Thin layer Piping	1.00 0.58	Very limited Deep to water	1.00
061BE: Benfield-----	42	Somewhat limited Slope Depth to bedrock	0.08 0.02	Somewhat limited Hard to pack Thin layer	0.60 0.56	Very limited Deep to water	1.00
Florence-----	28	Somewhat limited Seepage Depth to bedrock	0.05 0.01	Somewhat limited Thin layer	0.01	Very limited Deep to water	1.00
061CF: Clime-----	60	Somewhat limited Depth to bedrock Slope	0.11 0.01	Somewhat limited Thin layer Hard to pack	0.86 0.39	Very limited Deep to water	1.00
Sogn-----	20	Very limited Seepage Depth to bedrock	1.00 1.00	Very limited Thin layer	1.00	Very limited Deep to water	1.00
061CR: Crete-----	90	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack	0.75	Very limited Deep to water	1.00
061CS: Crete-----	90	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack	0.76	Very limited Deep to water	1.00
061EU: Eudora-----	85	Very limited Seepage	1.00	Very limited Piping Seepage	1.00 0.07	Very limited Deep to water	1.00
061HE: Haynie-----	55	Somewhat limited Seepage	0.70	Very limited Piping Seepage	1.00 0.04	Very limited Deep to water	1.00
061KA: Kahola-----	75	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.61	Very limited Deep to water	1.00
061KB: Kahola-----	75	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.61	Very limited Deep to water	1.00
061RE: Reading-----	85	Somewhat limited Seepage	0.05	Somewhat limited Piping	0.01	Very limited Deep to water	1.00
061TO: Tully-----	85	Somewhat limited Seepage	0.05	Not limited		Very limited Deep to water	1.00
117PA: Pawnee-----	88	Not limited		Very limited Depth to saturated zone	1.00	Very limited Deep to water	1.00

WATER MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
117PB: Pawnee-----	88	Not limited		Hard to pack	0.62		
				Very limited Depth to saturated zone	1.00	Very limited Deep to water	1.00
				Hard to pack	0.62		
149HS: Haynie-----	60	Somewhat limited Seepage	0.70	Very limited Piping Seepage	1.00 0.03	Very limited Deep to water	1.00
Sarpy-----	25	Very limited Seepage	1.00	Somewhat limited Seepage	0.50	Very limited Deep to water	1.00
149PS: Paxico-----	90	Very limited Seepage	1.00	Very limited Piping Depth to saturated zone Seepage	1.00 0.95 0.22	Very limited Cutbanks cave Deep to water	1.00 0.02
149SF: Sarpy-----	90	Very limited Seepage	1.00	Somewhat limited Seepage	0.50	Very limited Deep to water	1.00
197CM: Clime-----	85	Somewhat limited Depth to bedrock	0.08	Somewhat limited Thin layer Hard to pack	0.81 0.24	Very limited Deep to water	1.00
197FL: Florence-----	40	Somewhat limited Seepage Depth to bedrock	0.05 0.01	Somewhat limited Thin layer	0.01	Very limited Deep to water	1.00
Labette-----	30	Somewhat limited Depth to bedrock	0.69	Somewhat limited Thin layer Hard to pack	0.70 0.28	Very limited Deep to water	1.00
197IB: Irwin-----	80	Not limited		Somewhat limited Hard to pack	0.19	Very limited Deep to water	1.00
197ID: Irwin-----	85	Not limited		Somewhat limited Hard to pack	0.51	Very limited Deep to water	1.00
197IV: Ivan-----	90	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.56	Very limited Deep to water	1.00
197IX: Ivan-----	80	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.05	Very limited Deep to water	1.00
197PN: Pawnee-----	85	Not limited		Very limited Depth to saturated zone	1.00	Very limited Deep to water	1.00
197WE: Wamego-----	90	Somewhat limited Depth to bedrock	0.26	Somewhat limited Thin layer	0.96	Very limited Deep to water	1.00
201CS: Crete-----	95	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack	0.81	Very limited Deep to water	1.00
201CX: Crete, eroded-----	90	Somewhat limited Seepage	0.57	Not limited		Very limited Deep to water	1.00
201KS: Kipson-----	70	Very limited Seepage Depth to bedrock Slope	1.00 0.53 0.08	Very limited Thin layer Piping	1.00 0.23	Very limited Deep to water	1.00

WATER MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer-fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Sogn-----	15	Very limited Seepage Depth to bedrock	1.00 1.00	Very limited Thin layer Piping	1.00 0.50	Very limited Deep to water	1.00
201LC: Lancaster-----	85	Somewhat limited Seepage Depth to bedrock	0.70 0.13	Somewhat limited Thin layer Piping	0.88 0.36	Very limited Deep to water	1.00
Ad: Ivan-----	99	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.18	Very limited Deep to water	1.00
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
BE: Benfield-----	89	Somewhat limited Depth to bedrock	0.08	Somewhat limited Thin layer Hard to pack	0.81 0.12	Very limited Deep to water	1.00
Bf: Benfield-----	45	Somewhat limited Depth to bedrock Slope	0.04 0.01	Somewhat limited Thin layer Hard to pack	0.70 0.12	Very limited Deep to water	1.00
Florence-----	30	Somewhat limited Depth to bedrock Seepage	0.86 0.05	Somewhat limited Thin layer	0.86	Very limited Deep to water	1.00
Bk: Wymore-----	60	Somewhat limited Seepage Slope	0.05 0.02	Very limited Depth to saturated zone Hard to pack	1.00 0.51	Very limited Deep to water	1.00
Kennebec-----	45	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.99	Somewhat limited Deep to water Slow refill Cutbanks cave	0.81 0.30 0.10
BOP: Borrow Pits-----	100	Not rated		Not rated		Not rated	
Ca: Carr-----	45	Very limited Seepage	1.00	Very limited Piping Seepage	1.00 0.08	Very limited Deep to water	1.00
Sarpy-----	40	Very limited Seepage	1.00	Very limited Seepage	1.00	Very limited Deep to water	1.00
Ch: Chase-----	84	Not limited		Somewhat limited Hard to pack Depth to saturated zone	0.82 0.43	Very limited Deep to water	1.00
Cs: Clime-----	50	Somewhat limited Depth to bedrock Slope	0.11 0.01	Somewhat limited Thin layer Hard to pack	0.86 0.43	Very limited Deep to water	1.00
Sogn-----	30	Very limited Seepage Depth to bedrock	1.00 1.00	Very limited Thin layer	1.00	Very limited Deep to water	1.00
CT: Crete-----	83	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack	0.78	Very limited Deep to water	1.00
Dr: Dwight-----	45	Somewhat limited Depth to bedrock	0.10	Somewhat limited Hard to pack Thin layer	0.92 0.11	Very limited Deep to water	1.00

WATER MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer-fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Irwin-----	40	Somewhat limited Depth to bedrock	0.00	Somewhat limited Hard to pack Thin layer	0.97 0.11	Very limited Deep to water	1.00
Dw: Dwight-----	45	Somewhat limited Depth to bedrock	0.10	Somewhat limited Hard to pack Thin layer	0.92 0.11	Very limited Deep to water	1.00
Irwin-----	40	Somewhat limited Depth to bedrock	0.00	Somewhat limited Hard to pack Thin layer	0.98 0.11	Very limited Deep to water	1.00
Em: Elmont-----	74	Somewhat limited Seepage Depth to bedrock	0.05 0.00	Somewhat limited Thin layer Piping	0.11 0.03	Very limited Deep to water	1.00
En: Elmont-----	35	Somewhat limited Seepage Depth to bedrock	0.05 0.00	Somewhat limited Thin layer Piping	0.11 0.03	Very limited Deep to water	1.00
Clime-----	30	Somewhat limited Depth to bedrock	0.11	Somewhat limited Thin layer	0.85	Very limited Deep to water	1.00
Eu: Eudora-----	88	Very limited Seepage	1.00	Very limited Piping Seepage	1.00 0.07	Very limited Deep to water	1.00
Ga: Geary-----	90	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.08	Very limited Deep to water	1.00
Ge: Geary-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.08	Very limited Deep to water	1.00
Ha: Haynie-----	90	Somewhat limited Seepage	0.70	Very limited Piping Seepage	1.00 0.07	Very limited Deep to water	1.00
HO: Hobbs-----	89	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.83	Very limited Deep to water	1.00
Ic: Irwin-----	85	Somewhat limited Depth to bedrock	0.00	Somewhat limited Hard to pack Thin layer	0.95 0.02	Very limited Deep to water	1.00
Id: Irwin, eroded-----	85	Somewhat limited Depth to bedrock	0.00	Somewhat limited Hard to pack Thin layer	0.95 0.02	Very limited Deep to water	1.00
Ie: Ivan-----	88	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.32	Very limited Deep to water	1.00
Iv: Ivan-----	45	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.32	Very limited Deep to water	1.00
Kennebec-----	45	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.99	Somewhat limited Deep to water Slow refill Cutbanks cave	0.81 0.30 0.10
Ka: Kahola-----	85	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.68	Very limited Deep to water	1.00
Ke: Kenesaw-----	90	Somewhat limited Seepage	0.70	Very limited Piping	1.00	Very limited Deep to water	1.00

WATER MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer-fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Kf: Kenesaw-----	85	Somewhat limited Seepage	0.70	Very limited Piping	1.00	Very limited Deep to water	1.00
KN: Kennebec-----	95	Somewhat limited Seepage	0.70	Somewhat limited Piping Depth to saturated zone	0.71 0.09	Somewhat limited Deep to water Slow refill Cutbanks cave	0.54 0.30 0.10
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Mayberry-----	95	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.83	Very limited Deep to water	1.00
Mb: Mayberry-----	95	Not limited		Very limited Depth to saturated zone Hard to pack	1.00 0.82	Very limited Deep to water	1.00
Mu: Muir-----	84	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.58	Very limited Deep to water	1.00
QUA: Quarries-----	100	Not rated		Not rated		Not rated	
Rd: Reading-----	90	Somewhat limited Seepage	0.57	Somewhat limited Piping	0.04	Very limited Deep to water	1.00
Re: Reading-----	90	Somewhat limited Seepage	0.57	Somewhat limited Piping	0.04	Very limited Deep to water	1.00
Sa: Sarpy-----	98	Very limited Seepage	1.00	Somewhat limited Seepage	0.43	Very limited Deep to water	1.00
Sm: Smolan-----	90	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack	0.56	Very limited Deep to water	1.00
Sn: Smolan-----	75	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack	0.56	Very limited Deep to water	1.00
So: Smolan, eroded-----	80	Somewhat limited Seepage	0.05	Somewhat limited Hard to pack	0.71	Very limited Deep to water	1.00
St: Clime-----	75	Somewhat limited Slope Depth to bedrock	0.50 0.06	Somewhat limited Thin layer Hard to pack	0.77 0.43	Very limited Deep to water	1.00
Su: Sutphen-----	100	Not limited		Somewhat limited Hard to pack	0.99	Very limited Deep to water	1.00
Ts: Tully-----	85	Somewhat limited Seepage	0.05	Not limited		Very limited Deep to water	1.00
Tt: Tully, eroded-----	85	Not limited		Somewhat limited Hard to pack	0.50	Very limited Deep to water	1.00
Tu: Tully-----	85	Not limited		Somewhat limited		Very limited	

WATER MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer-fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Tv: Tully, eroded-----	85	Not limited		Hard to pack	0.50	Deep to water	1.00
				Somewhat limited Hard to pack	0.50	Very limited Deep to water	1.00
W: Water-----	100	Not rated		Not rated		Not rated	
Wm: Wymore-----	100	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00	Very limited Deep to water	1.00
					0.51		
Wn: Wymore-----	90	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00	Very limited Deep to water	1.00
					0.51		
Wo: Wymore, eroded-----	90	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00	Very limited Deep to water	1.00
					0.61		
Wr: Wymore-----	90	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00	Very limited Deep to water	1.00
					0.51		
Ws: Wymore, eroded-----	90	Somewhat limited Seepage	0.05	Very limited Depth to saturated zone Hard to pack	1.00	Very limited Deep to water	1.00
					0.63		

SANITARY FACILITIES
Riley County, Kansas

Sanitary Facilities

The following tables show the degree and kind of soil limitations that affect septic tank absorption fields, sewage lagoons, sanitary landfills, and daily cover for landfill. The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect these uses. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Septic tank absorption fields are areas in which effluent from a septic tank is distributed into the soil through subsurface tiles or perforated pipe. Only that part of the soil between depths of 24 and 60 inches is evaluated. The ratings are based on the soil properties that affect absorption of the effluent, construction and maintenance of the system, and public health. Permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, and flooding affect absorption of the effluent. Stones and boulders, ice, and bedrock or a cemented pan interfere with installation. Subsidence interferes with installation and maintenance. Excessive slope may cause lateral seepage and surfacing of the effluent in downslope areas.

Some soils are underlain by loose sand and gravel or fractured bedrock at a depth of less than 4 feet below the distribution lines. In these soils the absorption field may not adequately filter the effluent, particularly when the system is new. As a result, the ground water may become contaminated.

Sewage lagoons are shallow ponds constructed to hold sewage while aerobic bacteria decompose the solid and liquid wastes. Lagoons should have a nearly level floor surrounded by cut slopes or embankments of compacted soil. Nearly impervious soil material for the lagoon floor and sides is required to minimize seepage and contamination of ground water. Considered in the ratings are slope, permeability, depth to a water table, ponding, depth to bedrock or a cemented pan, flooding, large stones, and content of organic matter.

Soil permeability is a critical property affecting the suitability for sewage lagoons. Most porous soils eventually become sealed when they are used as sites for sewage lagoons. Until sealing occurs, however, the hazard of pollution is severe. Soils that have a permeability rate of more than 2 inches per hour are too porous for the proper functioning of sewage lagoons. In these soils, seepage of the effluent can result in contamination of the ground water. Ground-water contamination is also a hazard if fractured bedrock is within a depth of 40 inches, if the water table is high enough to raise the level of sewage in the lagoon, or if floodwater overtops the lagoon.

A high content of organic matter is detrimental to proper functioning of the lagoon because it inhibits aerobic activity. Slope, bedrock, and cemented pans can cause construction problems, and large stones can hinder compaction of the lagoon floor. If the lagoon is to be uniformly deep throughout, the slope must be gentle enough and the soil material must be thick enough over bedrock or a cemented pan to make land smoothing practical.

A trench sanitary landfill is an area where solid waste is placed in successive layers in an excavated trench. The waste is spread, compacted, and covered daily with a thin layer of soil excavated at the site. When the trench is full, a final cover of soil material at least 2 feet thick is placed over the landfill. The ratings in the table are based on the soil properties that affect the risk of pollution, the ease of excavation, trafficability, and revegetation. These properties include permeability, depth to bedrock or a cemented pan, depth to a water table, ponding, slope, flooding, texture, stones and boulders, highly organic layers, soil reaction, and content of salts and sodium. Unless otherwise stated, the ratings apply only to that part of the soil within a depth of about 6 feet. For deeper trenches, onsite investigation may be needed.

Hard, nonrippable bedrock, creviced bedrock, or highly permeable strata in or directly below the proposed trench bottom can affect the ease of excavation and the hazard of ground-water pollution. Slope affects construction of the trenches and the movement of surface water around the landfill. It also affects the construction and performance of roads in areas of the landfill.

Soil texture and consistence affect the ease with which the trench is dug and the ease with which the soil can be used as daily or final cover. They determine the workability of the soil when dry and when wet. Soils that are plastic and sticky when wet are difficult to excavate, grade, or compact and are difficult to place as a uniformly thick cover over a layer of refuse.

The soil material used as the final cover for a trench landfill should be suitable for plants. It should not have excess sodium or salts and should not be too acid. The surface layer generally has the best workability, the highest content of organic matter, and the best potential for plants. Material from the surface layer should be stockpiled for use as the final cover.

SANITARY FACILITIES
Riley County, Kansas

In an area sanitary landfill, solid waste is placed in successive layers on the surface of the soil. The waste is spread, compacted, and covered daily with a thin layer of soil from a source away from the site. A final cover of soil material at least 2 feet thick is placed over the completed landfill. The ratings in the table are based on the soil properties that affect trafficability and the risk of pollution. These properties include flooding, permeability, depth to a water table, ponding, slope, and depth to bedrock or a cemented pan.

Flooding is a serious problem because it can result in pollution in areas downstream from the landfill. If permeability is too rapid or if fractured bedrock, a fractured cemented pan, or the water table is close to the surface, the leachate can contaminate the water supply. Slope is a consideration because of the extra grading required to maintain roads in the steeper areas of the landfill. Also, leachate may flow along the surface of the soils in the steeper areas and cause difficult seepage problems.

Daily cover for landfill is the soil material that is used to cover compacted solid waste in an area sanitary landfill. The soil material is obtained offsite, transported to the landfill, and spread over the waste. The ratings in the table also apply to the final cover for a landfill. They are based on the soil properties that affect workability, the ease of digging, and the ease of moving and spreading the material over the refuse daily during wet and dry periods. These properties include soil texture, depth to a water table, ponding, rock fragments, slope, depth to bedrock or a cemented pan, reaction, and content of salts, sodium, or lime.

Loamy or silty soils that are free of large stones and excess gravel are the best cover for a landfill. Clayey soils may be sticky and difficult to spread; sandy soils are subject to wind erosion.

Slope affects the ease of excavation and of moving the cover material. Also, it can influence runoff, erosion, and reclamation of the borrow area.

After soil material has been removed, the soil material remaining in the borrow area must be thick enough over bedrock, a cemented pan, or the water table to permit revegetation. The soil material used as the final cover for a landfill should be suitable for plants. It should not have excess sodium, salts, or lime and should not be too acid.

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
027CS: Crete-----	90	Very limited Restricted permeability	1.00	Somewhat limited Slope	0.00
027CX: Crete-----	83	Very limited Restricted permeability	1.00	Somewhat limited Slope	0.91
027HN: Hobbs-----	90	Very limited Flooding Restricted permeability	1.00 0.50	Seepage	0.32
027KS: Kipson-----	70	Very limited Depth to bedrock	1.00	Very limited Depth to soft bedrock	1.00
		Slope	0.84	Slope	1.00
				Seepage	0.50
Sogn-----	15	Very limited Depth to bedrock	1.00	Very limited Depth to hard bedrock	1.00
		Slope	0.84	Slope	1.00
061BE: Benfield-----	42	Very limited Restricted permeability	1.00	Very limited Depth to soft bedrock	1.00
		Depth to bedrock	1.00	Slope	1.00
		Slope	1.00		
Florence-----	28	Very limited Restricted permeability	1.00	Very limited Slope	1.00
		Depth to bedrock	0.47	Depth to hard bedrock	0.05
		Slope	0.16		
061CF: Clime-----	60	Very limited Restricted permeability	1.00	Very limited Depth to soft bedrock	1.00
		Depth to bedrock	1.00	Slope	1.00
		Slope	0.84		
Sogn-----	20	Very limited Depth to bedrock	1.00	Very limited Depth to hard bedrock	1.00
				Slope	0.67
061CR: Crete-----	90	Very limited Restricted permeability	1.00	Not limited	
061CS: Crete-----	90	Very limited Restricted permeability	1.00	Somewhat limited Slope	0.09
061EU: Eudora-----	85	Very limited Flooding	1.00	Very limited Flooding Seepage	1.00 1.00
061HE: Haynie-----	55	Very limited Flooding Restricted permeability	1.00 0.50	Very limited Flooding Seepage	1.00 0.50
061KA: Kahola-----	75	Very limited Flooding Restricted permeability	1.00 0.50	Very limited Flooding Seepage	1.00 0.50
061KB: Kahola-----	75	Very limited Flooding Restricted permeability	1.00 0.50	Very limited Flooding Seepage	1.00 0.50
061RE: Reading-----	85	Very limited Restricted permeability	1.00	Somewhat limited Flooding	0.40
061TO: Tully-----	85	Very limited		Somewhat limited	

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
117PA: Pawnee-----	88	Restricted permeability	1.00	Slope	0.91
		Very limited Restricted permeability	1.00	Somewhat limited Depth to saturated zone	0.25
		Depth to saturated zone	1.00	Slope	0.09
117PB: Pawnee-----	88	Very limited Restricted permeability	1.00	Somewhat limited Slope	0.91
		Depth to saturated zone	1.00	Depth to saturated zone	0.25
149HS: Haynie-----	60	Very limited Flooding	1.00	Very limited Flooding	1.00
		Restricted permeability	0.50	Seepage	0.50
Sarpy-----	25	Very limited Flooding	1.00	Very limited Flooding	1.00
		Filtering capacity	1.00	Seepage	1.00
149PS: Paxico-----	90			Slope	0.00
		Very limited Flooding	1.00	Very limited Flooding	1.00
		Depth to saturated zone	1.00	Seepage	1.00
149SF: Sarpy-----	90	Restricted permeability	0.50	Depth to saturated zone	1.00
		Very limited Flooding	1.00	Very limited Flooding	1.00
197CM: Clime-----	85	Filtering capacity	1.00	Seepage	1.00
		Very limited Restricted permeability	1.00	Very limited Depth to soft bedrock	1.00
197FL: Florence-----	40	Depth to bedrock	1.00	Slope	0.67
		Very limited Restricted permeability	1.00	Very limited Slope	1.00
		Depth to bedrock	0.47	Seepage	0.50
Labette-----	30	Slope	0.04	Depth to hard bedrock	0.05
		Very limited Restricted permeability	1.00	Very limited Depth to hard bedrock	1.00
197IB: Irwin-----	80	Depth to bedrock	1.00	Slope	0.33
		Very limited Restricted permeability	1.00	Somewhat limited Slope	0.00
197ID: Irwin-----	85	Very limited Restricted permeability	1.00	Somewhat limited Slope	0.67
197IV: Ivan-----	90	Very limited Flooding	1.00	Very limited Flooding	1.00
		Restricted permeability	0.50	Seepage	0.50
197IX: Ivan-----	80	Very limited Flooding	1.00	Very limited Flooding	1.00
		Restricted permeability	0.50	Seepage	0.50
197PN: Pawnee-----	85	Very limited Restricted permeability	1.00	Somewhat limited Slope	0.67
		Depth to saturated zone	1.00		
197WE: Wamego-----	90	Very limited Restricted permeability	1.00	Very limited Depth to soft bedrock	1.00

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
201CS: Crete-----	95	Depth to bedrock	1.00	Slope	0.67
		Very limited Restricted permeability	1.00	Somewhat limited Slope	0.00
201CX: Crete, eroded-----	90	Very limited Restricted permeability	1.00	Somewhat limited Slope	0.67
201KS: Kipson-----	70	Depth to bedrock	1.00	Seepage	0.32
		Slope	1.00	Very limited Depth to soft bedrock	1.00
Sogn-----	15	Seepage	0.50	Slope	1.00
		Very limited Depth to bedrock	1.00	Seepage	0.50
201LC: Lancaster-----	85	Depth to bedrock	1.00	Very limited Depth to hard bedrock	1.00
		Restricted permeability	0.50	Slope	1.00
Ad: Ivan-----	99	Slope	0.16	Seepage	0.50
		Very limited Depth to bedrock	1.00	Very limited Depth to soft bedrock	1.00
AED: Arents, Earthen Dam-----	100	Seepage	0.50	Slope	0.00
		Very limited Restricted permeability	0.50	Not rated	Not rated
BE: Benfield-----	89	Not rated	Not rated	Very limited Depth to soft bedrock	1.00
		Very limited Restricted permeability	1.00	Slope	0.67
Bf: Benfield-----	45	Depth to bedrock	1.00	Very limited Depth to soft bedrock	1.00
		Restricted permeability	1.00	Slope	1.00
Florence-----	30	Slope	0.84	Very limited Depth to hard bedrock	1.00
		Very limited Depth to bedrock	1.00	Slope	1.00
Bk: Wymore-----	60	Restricted permeability	1.00	Very limited Slope	1.00
		Slope	0.16	Depth to saturated zone	0.25
Kennebec-----	45	Depth to saturated zone	1.00	Very limited Flooding	1.00
		Slope	0.96	Depth to saturated zone	0.71
BOP: Borrow Pits-----	100	Flooding	1.00	Seepage	0.50
		Depth to saturated zone	1.00	Not rated	Not rated
Ca: Carr-----	45	Restricted permeability	0.50	Very limited Flooding	1.00
		Very limited Flooding	1.00	Seepage	1.00
Sarpy-----	40	Depth to saturated zone	1.00	Very limited Flooding	1.00
		Restricted permeability	1.00	Seepage	1.00
Ch: Chase-----	84	Very limited		Very limited	

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Cs: Clime-----	50	Restricted permeability	1.00	Depth to saturated zone	1.00
		Depth to saturated zone	1.00	Flooding	0.40
		Flooding	0.40		
Sogn-----	30	Very limited		Very limited	
		Restricted permeability	1.00	Depth to soft bedrock	1.00
		Depth to bedrock	1.00	Slope	0.84
CT: Crete-----	83	Very limited		Very limited	
		Restricted permeability	1.00	Depth to hard bedrock	1.00
		Flooding	0.40	Slope	1.00
Dr: Dwight-----	45	Very limited		Somewhat limited	
		Restricted permeability	1.00	Slope	0.67
		Depth to bedrock	0.78		
Irwin-----	40	Very limited		Somewhat limited	
		Restricted permeability	1.00	Depth to hard bedrock	0.42
		Depth to bedrock	0.78	Slope	0.00
Dw: Dwight-----	45	Very limited		Somewhat limited	
		Restricted permeability	1.00	Depth to soft bedrock	0.42
		Depth to bedrock	0.78	Slope	0.09
Irwin-----	40	Very limited		Somewhat limited	
		Restricted permeability	1.00	Depth to hard bedrock	0.42
		Depth to bedrock	0.78	Slope	0.00
Em: Elmont-----	74	Very limited		Somewhat limited	
		Restricted permeability	1.00	Depth to soft bedrock	0.42
		Depth to bedrock	0.78	Slope	0.09
En: Elmont-----	35	Very limited		Somewhat limited	
		Restricted permeability	1.00	Slope	0.91
		Depth to bedrock	0.78	Seepage	0.50
Clime-----	30	Very limited		Depth to soft bedrock	0.42
		Restricted permeability	1.00	Very limited	
		Depth to bedrock	1.00	Slope	1.00
Eu: Eudora-----	88	Very limited		Depth to soft bedrock	1.00
		Flooding	1.00	Slope	1.00
		Seepage	0.50		
Ga: Geary-----	90	Somewhat limited		Very limited	
		Restricted permeability	0.50	Flooding	1.00
		Flooding	1.00	Seepage	1.00
Ge: Geary-----	100	Somewhat limited		Slope	0.09
		Restricted permeability	0.50	Somewhat limited	
		Flooding	1.00	Slope	0.91
Ha: Haynie-----	90	Very limited		Seepage	0.50
		Flooding	1.00	Very limited	
		Restricted permeability	1.00	Flooding	1.00
HO: Hobbs-----	89	Very limited		Seepage	0.50
		Flooding	1.00	Very limited	
		Restricted permeability	0.50	Flooding	1.00

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Ic: Irwin-----	85	Very limited Restricted permeability Depth to bedrock	1.00 0.52	Somewhat limited Slope Depth to soft bedrock	0.91 0.08
Id: Irwin, eroded-----	85	Very limited Restricted permeability Depth to bedrock	1.00 0.52	Somewhat limited Slope Depth to soft bedrock	0.91 0.08
Ie: Ivan-----	88	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage Slope	0.50 0.00
Iv: Ivan-----	45	Very limited Flooding Restricted permeability	1.00 0.50	Very limited Flooding Seepage	1.00 0.50
Kennebec-----	45	Very limited Flooding Depth to saturated zone Restricted permeability	1.00 1.00 0.50	Very limited Flooding Depth to saturated zone Seepage	1.00 0.71 0.50
Ka: Kahola-----	85	Somewhat limited Restricted permeability Flooding	0.50 0.40	Somewhat limited Seepage Flooding	0.50 0.40
Ke: Kenesaw-----	90	Somewhat limited Restricted permeability	0.50	Somewhat limited Seepage Slope	0.50 0.33
Kf: Kenesaw-----	85	Somewhat limited Restricted permeability Slope	0.50 0.00	Very limited Slope Seepage	1.00 0.50
KN: Kennebec-----	95	Very limited Flooding Depth to saturated zone Restricted permeability	1.00 1.00 0.50	Very limited Flooding Depth to saturated zone Seepage	1.00 1.00 0.50
M-W: Miscellaneous Water-	100	Not rated		Not rated	
Ma: Mayberry-----	95	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Somewhat limited Slope	0.33
Mb: Mayberry-----	95	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Somewhat limited Slope	0.33
Mu: Muir-----	84	Somewhat limited Restricted permeability Flooding	0.50 0.40	Somewhat limited Seepage Flooding	0.50 0.40
QUA: Quarries-----	100	Not rated		Not rated	
Rd: Reading-----	90	Somewhat limited Restricted permeability Flooding	0.68 0.40	Somewhat limited Flooding Seepage	0.40 0.32
Re: Reading-----	90	Somewhat limited		Somewhat limited	

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
Sa: Sarpy-----	98	Restricted permeability	0.68	Flooding	0.40
		Flooding	0.40	Seepage	0.32
				Slope	0.00
Sm: Smolan-----	90	Very limited		Very limited	
		Flooding	1.00	Flooding	1.00
		Filtering capacity	1.00	Seepage	1.00
Sn: Smolan-----	75			Slope	0.00
		Very limited		Somewhat limited	
		Restricted permeability	1.00	Slope	0.09
So: Smolan, eroded-----	80	Very limited		Somewhat limited	
		Restricted permeability	1.00	Slope	0.91
St: Clime-----	75	Very limited		Very limited	
		Restricted permeability	1.00	Depth to soft bedrock	1.00
		Depth to bedrock	1.00	Slope	1.00
Su: Sutphen-----	100	Very limited		Very limited	
		Flooding	1.00	Flooding	1.00
		Restricted permeability	1.00		
Ts: Tully-----	85	Very limited		Somewhat limited	
		Restricted permeability	1.00	Slope	0.09
Tt: Tully, eroded-----	85	Very limited		Somewhat limited	
		Restricted permeability	1.00	Slope	0.09
Tu: Tully-----	85	Very limited		Somewhat limited	
		Restricted permeability	1.00	Slope	0.91
Tv: Tully, eroded-----	85	Very limited		Somewhat limited	
		Restricted permeability	1.00	Slope	0.91
W: Water-----	100	Not rated		Not rated	
Wm: Wymore-----	100	Very limited		Somewhat limited	
		Restricted permeability	1.00	Depth to saturated zone	0.25
		Depth to saturated zone	1.00		
Wn: Wymore-----	90	Very limited		Somewhat limited	
		Restricted permeability	1.00	Depth to saturated zone	0.25
		Depth to saturated zone	1.00	Slope	0.09
Wo: Wymore, eroded-----	90	Very limited		Somewhat limited	
		Restricted permeability	1.00	Depth to saturated zone	0.25
		Depth to saturated zone	1.00	Slope	0.09
Wr: Wymore-----	90	Very limited		Somewhat limited	
		Restricted permeability	1.00	Slope	0.91
		Depth to saturated zone	1.00	Depth to saturated zone	0.25
Ws: Wymore, eroded-----	90	Very limited		Somewhat limited	
		Restricted permeability	1.00	Slope	0.91

SANITARY FACILITIES--Continued
 Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Septic tank absorption fields		Sewage lagoons	
		Rating class and limiting features	Value	Rating class and limiting features	Value
		Depth to saturated zone	1.00	Depth to saturated zone	0.25

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
027CS: Crete-----	90	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
027CX: Crete-----	83	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
027HN: Hobbs-----	90	Very limited Flooding	1.00	Very limited Flooding	1.00	Not limited	
027KS: Kipson-----	70	Very limited Depth to bedrock Seepage Slope Too clayey	1.00 1.00 0.84 0.50	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Carbonate content Slope Too clayey	1.00 1.00 0.84 0.50
Sogn-----	15	Very limited Depth to bedrock Seepage Slope Too clayey	1.00 1.00 0.84 0.50	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Hard to compact Slope Too clayey	1.00 1.00 0.84 0.50
061BE: Benfield-----	42	Very limited Depth to bedrock Too clayey Slope Seepage	1.00 1.00 1.00 1.00	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to bedrock Too clayey Hard to compact Slope	1.00 1.00 1.00 1.00
Florence-----	28	Very limited Depth to bedrock Too clayey Seepage Content of large stones Slope	1.00 1.00 1.00 1.00 0.21 0.16	Somewhat limited Slope Depth to bedrock	0.16 0.05	Very limited Too clayey Gravel content Content of large stones Slope Depth to bedrock	1.00 0.47 0.21 0.16 0.05
061CF: Clime-----	60	Very limited Depth to bedrock Too clayey Seepage Slope	1.00 1.00 1.00 0.84	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Too clayey Hard to compact Slope	1.00 1.00 1.00 0.84
Sogn-----	20	Very limited Depth to bedrock Seepage Too clayey	1.00 1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey	1.00 0.50
061CR: Crete-----	90	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
061CS: Crete-----	90	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
061EU: Eudora-----	85	Very limited Flooding Seepage	1.00 1.00	Very limited Flooding Seepage	1.00 1.00	Somewhat limited Seepage	0.50
061HE: Haynie-----	55	Very limited Flooding	1.00	Very limited Flooding	1.00	Not limited	
061KA: Kahola-----	75	Very limited Flooding	1.00	Very limited Flooding	1.00	Not limited	
061KB: Kahola-----	75	Very limited Flooding	1.00	Very limited Flooding	1.00	Not limited	
061RE: Reading-----	85	Somewhat limited Too clayey Flooding	0.50 0.40	Somewhat limited Flooding	0.40	Somewhat limited Too clayey	0.50
061TO: Tully-----	85	Very limited Too clayey	1.00	Not limited		Very limited Too clayey Hard to compact	1.00 1.00
117PA: Pawnee-----	88	Very limited Depth to saturated zone Too clayey	1.00 0.50	Somewhat limited Depth to saturated zone	0.75	Very limited Hard to compact Depth to saturated zone Too clayey	1.00 0.86 0.50
117PB: Pawnee-----	88	Very limited		Somewhat limited		Very limited	

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
149HS: Haynie-----	60	Depth to saturated zone	1.00	Depth to saturated zone	0.75	Hard to compact	1.00
		Too clayey	0.50			Depth to saturated zone	0.86
Sarpy-----	25	Very limited Flooding	1.00	Very limited Flooding	1.00	Not limited	
		Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Too Sandy	1.00
149PS: Paxico-----	90	Seepage Too Sandy	1.00	Seepage	1.00	Seepage	1.00
		Very limited Flooding	1.00	Very limited Flooding	1.00	Somewhat limited Depth to saturated zone	0.68
149SF: Sarpy-----	90	Depth to saturated zone	1.00	Depth to saturated zone	1.00		
		Seepage	1.00				
197CM: Clime-----	85	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00
		Too clayey	1.00			Too clayey	1.00
197FL: Florence-----	40	Seepage	1.00			Hard to compact	1.00
		Slope	0.04	Somewhat limited Depth to bedrock Slope	0.05 0.04	Very limited Too clayey	1.00
Labette-----	30	Hard to compact	0.83			Gravel content	0.83
		Depth to bedrock	1.00	Very limited Depth to bedrock	1.00	Depth to bedrock	1.00
197IB: Irwin-----	80	Too clayey	1.00			Too clayey	1.00
		Seepage	1.00			Hard to compact	1.00
197ID: Irwin-----	85	Seepage	1.00			Gravel content	0.83
		Slope	0.04	Not limited		Depth to bedrock	0.05
197IV: Ivan-----	90	Slope	0.04			Slope	0.04
		Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00
197IX: Ivan-----	80	Too clayey	1.00			Too clayey	1.00
		Seepage	1.00			Hard to compact	1.00
197PN: Pawnee-----	85	Slope	0.04			Gravel content	0.04
		Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
197WE: Wamego-----	90	Hard to compact	0.04			Hard to compact	1.00
		Depth to bedrock	1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00
201CS: Crete-----	95	Too clayey	0.50			Too clayey	0.50
		Very limited Too clayey	1.00	Not limited		Very limited Too clayey	1.00
201CX: Crete, eroded-----	90	Very limited Too clayey	1.00			Hard to compact	1.00
		Not limited		Not limited		Very limited Hard to compact	1.00
201KS: Kipson-----	70	Not limited				Very limited Hard to compact	1.00
		Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock	1.00
Sogn-----	15	Slope	1.00			Slope	1.00
		Seepage	1.00			Slope	1.00
		Too clayey	0.50			Carbonate content	1.00
		Seepage	1.00			Too clayey	0.50
		Slope	0.16			Depth to bedrock	1.00
						Slope	0.16

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
201LC: Lancaster-----	85	Very limited Depth to bedrock Seepage Too clayey	1.00 1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey	1.00 0.50
Ad: Ivan-----	99	Very limited Flooding Too clayey	1.00 0.50	Very limited Flooding	1.00	Somewhat limited Too clayey	0.50
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
BE: Benfield-----	89	Very limited Depth to bedrock Too clayey Seepage	1.00 1.00 1.00	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Too clayey Hard to compact	1.00 1.00 1.00
Bf: Benfield-----	45	Very limited Depth to bedrock Too clayey Seepage Slope	1.00 1.00 1.00 0.84	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Too clayey Hard to compact Slope	1.00 1.00 1.00 0.84
Florence-----	30	Very limited Depth to bedrock Too clayey Seepage Slope	1.00 1.00 1.00 0.16	Very limited Depth to bedrock Slope	1.00 0.16	Very limited Depth to bedrock Too clayey Hard to compact Gravel content Slope	1.00 1.00 1.00 0.91 0.16
Bk: Wymore-----	60	Very limited Depth to saturated zone Slope Too clayey	1.00 0.96 0.50	Somewhat limited Slope Depth to saturated zone	0.96 0.75	Very limited Hard to compact Slope Depth to saturated zone Too clayey	1.00 0.96 0.86 0.50
Kennebec-----	45	Very limited Flooding Depth to saturated zone Too clayey	1.00 1.00 0.50	Very limited Flooding Depth to saturated zone	1.00 1.00	Somewhat limited Too clayey	0.50
BOP: Borrow Pits-----	100	Not rated		Not rated		Not rated	
Ca: Carr-----	45	Very limited Flooding Seepage	1.00 1.00	Very limited Flooding Seepage	1.00 1.00	Somewhat limited Seepage	0.50
Sarpy-----	40	Very limited Flooding Seepage Too Sandy	1.00 1.00 1.00	Very limited Flooding Seepage	1.00 1.00	Very limited Too Sandy Seepage	1.00 1.00
Ch: Chase-----	84	Very limited Too clayey Depth to saturated zone Flooding	1.00 0.44 0.40	Somewhat limited Flooding	0.40	Very limited Too clayey Hard to compact Depth to saturated zone	1.00 1.00 0.09
Cs: Clime-----	50	Very limited Depth to bedrock Too clayey Seepage Slope	1.00 1.00 1.00 0.84	Very limited Depth to bedrock Slope	1.00 0.84	Very limited Depth to bedrock Too clayey Hard to compact Slope	1.00 1.00 1.00 0.84
Sogn-----	30	Very limited Depth to bedrock Seepage Too clayey	1.00 1.00 0.50	Very limited Depth to bedrock	1.00	Very limited Depth to bedrock Hard to compact Too clayey	1.00 1.00 0.50
CT: Crete-----	83	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
Dr: Dwight-----	45	Very limited Depth to bedrock Too clayey Seepage	1.00 1.00 1.00	Somewhat limited Depth to bedrock	0.42	Very limited Too clayey Hard to compact Depth to bedrock	1.00 1.00 0.42
Irwin-----	40	Very limited Depth to bedrock Too clayey	1.00 1.00	Somewhat limited Depth to bedrock	0.42	Very limited Too clayey Hard to compact	1.00 1.00

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Dw: Dwight-----	45	Seepage Very limited Depth to bedrock Too clayey Seepage	1.00 1.00 1.00 1.00 1.00	Somewhat limited Depth to bedrock	0.42	Depth to bedrock Very limited Too clayey Hard to compact Depth to bedrock	0.42 1.00 1.00 0.42
Irwin-----	40	Very limited Depth to bedrock Too clayey Seepage	1.00 1.00 1.00 1.00	Somewhat limited Depth to bedrock	0.42	Very limited Too clayey Hard to compact Depth to bedrock	1.00 1.00 1.00 0.42
Em: Elmont-----	74	Very limited Depth to bedrock Seepage Too clayey	1.00 1.00 1.00 0.50	Somewhat limited Depth to bedrock	0.42	Somewhat limited Too clayey Depth to bedrock	0.50 0.42
En: Elmont-----	35	Very limited Depth to bedrock Seepage Too clayey Slope	1.00 1.00 1.00 0.50 0.04	Somewhat limited Depth to bedrock Slope	0.42 0.04	Somewhat limited Too clayey Depth to bedrock Slope	0.50 0.42 0.04
Clime-----	30	Very limited Depth to bedrock Seepage Too clayey Slope	1.00 1.00 1.00 0.50 0.16	Very limited Depth to bedrock Slope	1.00 0.16	Very limited Depth to bedrock Too clayey Slope	1.00 0.50 0.16
Eu: Eudora-----	88	Very limited Flooding Seepage	1.00 1.00	Very limited Flooding Seepage	1.00 1.00	Somewhat limited Seepage	0.50
Ga: Geary-----	90	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
Ge: Geary-----	100	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
Ha: Haynie-----	90	Very limited Flooding Too clayey	1.00 0.50	Very limited Flooding	1.00	Somewhat limited Too clayey	0.50
HO: Hobbs-----	89	Very limited Flooding	1.00	Very limited Flooding	1.00	Not limited	
Ic: Irwin-----	85	Very limited Depth to bedrock Too clayey Seepage	1.00 1.00 1.00 1.00	Somewhat limited Depth to bedrock	0.08	Very limited Too clayey Hard to compact Depth to bedrock	1.00 1.00 0.08
Id: Irwin, eroded-----	85	Very limited Depth to bedrock Too clayey Seepage	1.00 1.00 1.00 1.00	Somewhat limited Depth to bedrock	0.08	Very limited Too clayey Hard to compact Depth to bedrock	1.00 1.00 0.08
Ie: Ivan-----	88	Somewhat limited Too clayey	0.50	Not limited		Somewhat limited Too clayey	0.50
Iv: Ivan-----	45	Very limited Flooding Too clayey	1.00 0.50	Very limited Flooding	1.00	Somewhat limited Too clayey	0.50
Kennebec-----	45	Very limited Flooding Depth to saturated zone Too clayey	1.00 1.00 1.00 0.50	Very limited Flooding Depth to saturated zone	1.00 1.00	Somewhat limited Too clayey	0.50
Ka: Kahola-----	85	Somewhat limited Too clayey Flooding	0.50 0.40	Somewhat limited Flooding	0.40	Somewhat limited Too clayey	0.50
Ke: Kenesaw-----	90	Not limited		Not limited		Not limited	
Kf: Kenesaw-----	85	Somewhat limited Slope	0.00	Somewhat limited Slope	0.00	Somewhat limited Slope	0.00
KN: Kennebec-----	95	Very limited Flooding Depth to saturated zone	1.00 1.00	Very limited Flooding Depth to saturated zone	1.00 1.00	Not limited	
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ma: Mayberry-----	95	Very limited Depth to saturated zone Too clayey	1.00 1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone Too clayey Hard to compact	1.00 1.00 1.00
Mb: Mayberry-----	95	Very limited Depth to saturated zone Too clayey	1.00 1.00	Very limited Depth to saturated zone	1.00	Very limited Too clayey Hard to compact Depth to saturated zone	1.00 1.00 1.00
Mu: Muir-----	84	Somewhat limited Flooding	0.40	Somewhat limited Flooding	0.40	Not limited	
QUA: Quarries-----	100	Not rated		Not rated		Not rated	
Rd: Reading-----	90	Somewhat limited Too clayey Flooding	0.50 0.40	Somewhat limited Flooding	0.40	Somewhat limited Too clayey	0.50
Re: Reading-----	90	Somewhat limited Too clayey Flooding	0.50 0.40	Somewhat limited Flooding	0.40	Somewhat limited Too clayey	0.50
Sa: Sarpy-----	98	Very limited Flooding Seepage Too Sandy	1.00 1.00 1.00	Very limited Flooding Seepage	1.00 1.00	Very limited Too Sandy Seepage	1.00 1.00
Sm: Smolan-----	90	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
Sn: Smolan-----	75	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
So: Smolan, eroded-----	80	Somewhat limited Too clayey	0.50	Not limited		Very limited Hard to compact Too clayey	1.00 0.50
St: Clime-----	75	Very limited Slope Depth to bedrock Too clayey Seepage	1.00 1.00 1.00 1.00	Very limited Slope Depth to bedrock	1.00 1.00	Very limited Depth to bedrock Slope Too clayey	1.00 1.00 1.00
Su: Sutphen-----	100	Very limited Flooding Too clayey	1.00 0.50	Very limited Flooding	1.00	Very limited Hard to compact Too clayey	1.00 0.50
Ts: Tully-----	85	Very limited Too clayey	1.00	Not limited		Very limited Too clayey Hard to compact	1.00 1.00
Tt: Tully, eroded-----	85	Very limited Too clayey	1.00	Not limited		Very limited Too clayey Hard to compact	1.00 1.00
Tu: Tully-----	85	Very limited Too clayey	1.00	Not limited		Very limited Too clayey Hard to compact	1.00 1.00
Tv: Tully, eroded-----	85	Very limited Too clayey	1.00	Not limited		Very limited Too clayey Hard to compact	1.00 1.00
W: Water-----	100	Not rated		Not rated		Not rated	
Wm: Wymore-----	100	Very limited Depth to saturated zone Too clayey	1.00 0.50	Somewhat limited Depth to saturated zone	0.75	Very limited Hard to compact Depth to saturated zone Too clayey	1.00 0.86 0.50
Wn: Wymore-----	90	Very limited		Somewhat limited		Very limited	

SANITARY FACILITIES--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Trench sanitary landfill		Area sanitary landfill		Daily cover for landfill	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Wo: Wymore, eroded-----	90	Depth to saturated zone	1.00	Depth to saturated zone	0.75	Hard to compact	1.00
		Too clayey	0.50			Depth to saturated zone	0.86
Wr: Wymore-----	90	Very limited	1.00	Somewhat limited	0.75	Very limited	1.00
		Depth to saturated zone				0.50	
Ws: Wymore, eroded-----	90	Very limited	1.00	Somewhat limited	0.75	Very limited	1.00
		Depth to saturated zone				0.50	
		Too clayey		Depth to saturated zone		Too clayey	0.50
		Very limited	1.00	Somewhat limited	0.75	Very limited	1.00
		Depth to saturated zone	0.50	Depth to saturated zone		Hard to compact	0.86
		Too clayey		Depth to saturated zone		Too clayey	0.50
		Very limited	1.00	Somewhat limited	0.75	Very limited	1.00
		Depth to saturated zone	0.50	Depth to saturated zone		Hard to compact	0.86
		Too clayey		Depth to saturated zone		Too clayey	0.50

AGRICULTURAL WASTE MANAGEMENT
Riley County, Kansas

The nature of the soil is also important in the application of organic wastes and wastewater to land as fertilizers and irrigation; it is also important when the soil is used as a medium for treatment and disposal of these wastes. Favorable soil properties are required to prevent environmental damage.

The use of organic wastes and wastewater as production resources will result in energy conservation, prevent the waste of these important resources, and prevent problems associated with their disposal. Where disposal is the goal, and a maximum amount is disposed in a minimum area to hold costs to a minimum, risk of environmental damage is the principal constraint. Where the reuse goal is pursued, and a minimum amount is applied to a maximum area to obtain the greatest benefit, environmental damage is unlikely.

Interpretations developed for waste management may include ratings for (1) manure and food processing wastes; (2) municipal sewage sludge; (3) irrigation use of wastewater; or (4) treatment of wastewater by the slow rate process, overland flow process, or rapid infiltration process. If available, these should be located in this subsection.

Soil properties are important considerations in areas where soils are used as sites for the treatment and disposal of organic waste and wastewater. Selection of soils with properties that favor waste management can help to prevent environmental damage.

The Ag-Waste tables show the degree and kind of soil limitations affecting the treatment of agricultural waste, including municipal and food-processing wastewater and effluent from lagoons or storage ponds. Municipal wastewater is the waste stream from a municipality. It contains domestic waste and may contain industrial waste. It may have received primary or secondary treatment. It is rarely untreated sewage. Food-processing wastewater results from the preparation of fruits, vegetables, milk, cheese, and meats for public consumption. In places it is high in content of sodium and chloride. In the context of these tables, the effluent in lagoons and storage ponds is from facilities used to treat or store food-processing wastewater or domestic or animal waste. Domestic and food-processing wastewater is very dilute, and the effluent from the facilities that treat or store it commonly is very low in content of carbonaceous and nitrogenous material; the content of nitrogen commonly ranges from 10 to 30 milligrams per liter. The wastewater from animal waste treatment lagoons or storage ponds, however, has much higher concentrations of these materials, mainly because the manure has not been diluted as much as the domestic waste. The content of nitrogen in this wastewater generally ranges from 50 to 2,000 milligrams per liter. When wastewater is applied, checks should be made to ensure that nitrogen, phosphorus, heavy metals, and salts are not added in excessive amounts.

The ratings in the tables are for waste management systems that not only dispose of and treat organic waste or wastewater but also are beneficial to crops (application of manure and food-processing waste, application of sewage sludge, and disposal of wastewater by irrigation) and for waste management systems that are designed only for the purpose of wastewater disposal and treatment (overland flow of wastewater, rapid infiltration of wastewater, and slow rate treatment of wastewater).

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect agricultural waste management. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are generally favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Somewhat limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the tables indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.00 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Application of manure and food-processing waste not only disposes of waste material but also can improve crop production by increasing the supply of nutrients in the soils where the material is applied. Manure is the excrement of livestock and poultry, and food-processing waste is damaged fruit and vegetables and the peelings, stems, leaves, pits, and soil particles removed in food preparation. The manure and food-processing waste are either solid, slurry, or liquid. Their nitrogen content varies. A high content of nitrogen limits the application rate. Toxic or otherwise dangerous wastes, such as those mixed with the lye used in food processing, are not considered in the ratings.

The ratings are based on the soil properties that affect absorption, plant growth, microbial activity, erodibility, the rate at which the waste is applied, and the method by which the waste is applied. The properties that affect absorption include permeability, depth to a water table, ponding, the sodium adsorption ratio, depth to bedrock or a cemented pan, and available water capacity. The properties that affect plant growth and microbial activity include reaction, the sodium adsorption ratio, salinity, and bulk density. The wind erodibility group, the soil erodibility factor K, and slope are considered in estimating the likelihood that wind erosion or water erosion will transport the waste material from the application site. Stones, cobbles, a water table, ponding, and flooding can hinder the application of waste. Permanently frozen soils are unsuitable for waste treatment.

Application of sewage sludge not only disposes of waste material but also can improve crop production by increasing the supply of nutrients in the soils where the material is applied. In the context of this table, sewage sludge is the residual product of the treatment of municipal sewage. The solid component consists mainly of cell mass, primarily bacteria cells that developed during secondary treatment and have incorporated soluble organics into their own bodies. The sludge has small amounts of sand, silt, and other solid debris. The content of nitrogen varies. Some sludge has constituents that are toxic to plants or hazardous to the food chain, such as heavy metals and exotic organic compounds, and should be analyzed chemically prior to use.

AGRICULTURAL WASTE MANAGEMENT
Riley County, Kansas

The content of water in the sludge ranges from about 98 percent to less than 40 percent. The sludge is considered liquid if it is more than about 90 percent water, slurry if it is about 50 to 90 percent water, and solid if it is less than about 50 percent water.

The ratings in the table are based on the soil properties that affect absorption, plant growth, microbial activity, erodibility, the rate at which the sludge is applied, and the method by which the sludge is applied. The properties that affect absorption, plant growth, and microbial activity include permeability, depth to a water table, ponding, the sodium adsorption ratio, depth to bedrock or a cemented pan, available water capacity, reaction, salinity, and bulk density. The wind erodibility group, the soil erodibility factor K, and slope are considered in estimating the likelihood that wind erosion or water erosion will transport the waste material from the application site. Stones, cobbles, a water table, ponding, and flooding can hinder the application of sludge. Permanently frozen soils are unsuitable for waste treatment.

Disposal of wastewater by irrigation not only disposes of municipal wastewater and wastewater from food-processing plants, lagoons, and storage ponds but also can improve crop production by increasing the amount of water available to crops. The ratings in the table are based on the soil properties that affect the design, construction, management, and performance of the irrigation system. The properties that affect design and management include the sodium adsorption ratio, depth to a water table, ponding, available water capacity, permeability, slope, and flooding. The properties that affect construction include stones, cobbles, depth to bedrock or a cemented pan, depth to a water table, and ponding.

The properties that affect performance include depth to bedrock or a cemented pan, bulk density, the sodium adsorption ratio, salinity, reaction, and the cation-exchange capacity, which is used to estimate the capacity of a soil to adsorb heavy metals. Permanently frozen soils are not suitable for disposal of wastewater by irrigation.

See the National Soil Handbook, September 1992, Part 620, for criteria used in rating soils for sanitary facilities and waste management.

AGRICULTURAL WASTE MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food-processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
027CS: Crete-----	90	Very limited Restricted permeability Too acid	1.00 0.11	Very limited Restricted permeability Too acid	1.00 0.42	Very limited Restricted permeability Too acid	1.00 0.42
027CX: Crete-----	83	Very limited Restricted permeability Too acid	1.00 0.11	Very limited Restricted permeability Too acid	1.00 0.42	Very limited Restricted permeability Too steep for surface application Too acid Too steep for sprinkler application	1.00 0.66 0.42 0.00
027HN: Hobbs-----	90	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
027KS: Kipson-----	70	Very limited Depth to bedrock Droughty Slope Runoff limitation	1.00 0.97 0.84 0.40	Very limited Depth to bedrock Droughty Slope	1.00 0.97 0.84	Very limited Depth to bedrock Too steep for surface application Droughty Too steep for sprinkler application	1.00 1.00 0.97 0.89
Sogn-----	15	Very limited Depth to bedrock Droughty Slope Runoff limitation	1.00 1.00 0.84 0.40	Very limited Droughty Depth to bedrock Slope	1.00 1.00 0.84	Very limited Droughty Depth to bedrock Too steep for surface application Too steep for sprinkler application	1.00 1.00 1.00 0.89
061BE: Benfield-----	42	Very limited Restricted permeability Slope Droughty Depth to bedrock	1.00 1.00 0.01 0.01	Very limited Restricted permeability Slope Droughty Depth to bedrock	1.00 1.00 0.01 0.01	Very limited Restricted permeability Too steep for surface application Too steep for sprinkler application Droughty Depth to bedrock	1.00 1.00 1.00 0.01 0.01
Florence-----	28	Somewhat limited Droughty Restricted permeability Slope	0.37 0.30 0.16	Somewhat limited Droughty Restricted permeability Slope	0.37 0.22 0.16	Very limited Too steep for surface application Too steep for sprinkler application Droughty Restricted permeability	1.00 0.39 0.37 0.22
061CF: Clime-----	60	Very limited Restricted permeability Slope Depth to bedrock Droughty	1.00 0.84 0.46 0.11	Very limited Restricted permeability Slope Depth to bedrock Droughty	1.00 0.84 0.46 0.11	Very limited Restricted permeability Too steep for surface application Too steep for sprinkler application Depth to bedrock Droughty	1.00 1.00 0.89 0.46 0.11
Sogn-----	20	Very limited Depth to bedrock Droughty Runoff limitation	1.00 1.00 0.40	Very limited Droughty Depth to bedrock	1.00 1.00	Very limited Droughty Depth to bedrock Too steep for surface application	1.00 1.00 0.31

AGRICULTURAL WASTE MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food-processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
061CR: Crete-----	90	Very limited Restricted permeability Too acid	1.00 0.11	Very limited Restricted permeability Too acid	1.00 0.42	Very limited Restricted permeability Too acid	1.00 0.42
061CS: Crete-----	90	Very limited Restricted permeability Too acid	1.00 0.11	Very limited Restricted permeability Too acid	1.00 0.42	Very limited Restricted permeability Too acid Too steep for surface application	1.00 0.42 0.00
061EU: Eudora-----	85	Somewhat limited Flooding Filtering capacity	0.60 0.00	Very limited Flooding Filtering capacity	1.00 0.00	Somewhat limited Flooding Filtering capacity	0.60 0.00
061HE: Haynie-----	55	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
061KA: Kahola-----	75	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
061KB: Kahola-----	75	Somewhat limited Flooding	0.60	Very limited Flooding	1.00	Somewhat limited Flooding	0.60
061RE: Reading-----	85	Somewhat limited Restricted permeability Too acid	0.30 0.03	Somewhat limited Flooding Restricted permeability Too acid	0.40 0.22 0.14	Somewhat limited Restricted permeability Too acid	0.22 0.14
061TO: Tully-----	85	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability Too steep for surface application Too steep for sprinkler application	1.00 0.66 0.00
117PA: Pawnee-----	88	Very limited Restricted permeability Depth to saturated zone Runoff limitation	1.00 1.00 0.40	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Restricted permeability Depth to saturated zone Too steep for surface application	1.00 1.00 0.00
117PB: Pawnee-----	88	Very limited Restricted permeability Depth to saturated zone Runoff limitation	1.00 1.00 0.40	Very limited Restricted permeability Depth to saturated zone	1.00 1.00	Very limited Restricted permeability Depth to saturated zone Too steep for surface application Too steep for sprinkler application	1.00 1.00 0.66 0.00
149HS: Haynie-----	60	Somewhat limited Flooding	0.60	Very limited Flooding	1.00	Somewhat limited Flooding	0.60
Sarpy-----	25	Very limited Filtering capacity Droughty	1.00 0.65	Very limited Flooding Filtering capacity Droughty	1.00 1.00 0.65	Very limited Filtering capacity Droughty	1.00 0.65
		Flooding Leaching limitation	0.60 0.45		0.65	Flooding	0.60
149PS: Paxico-----	90	Very limited		Very limited		Very limited	

AGRICULTURAL WASTE MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food-processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
149SF: Sarpy-----	90	Flooding	1.00	Flooding	1.00	Flooding	1.00
		Depth to saturated zone	0.95	Depth to saturated zone	0.95	Depth to saturated zone	0.95
		Filtering capacity	0.00	Filtering capacity	0.00	Filtering capacity	0.00
		Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
197CM: Clime-----	85	Filtering capacity	1.00	Filtering capacity	1.00	Filtering capacity	1.00
		Droughty	0.65	Droughty	0.65	Droughty	0.65
		Leaching limitation	0.45				
		Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00
197FL: Florence-----	40	Droughty	0.32	Droughty	0.32	Droughty	0.32
		Depth to bedrock	0.29	Depth to bedrock	0.29	Too steep for surface application	0.31
						Depth to bedrock	0.29
		Somewhat limited Restricted permeability	0.30	Somewhat limited Restricted permeability	0.22	Very limited Too steep for surface application	1.00
Labette-----	30	Droughty	0.07	Droughty	0.07	Restricted permeability	0.22
		Slope	0.04	Slope	0.04	Too steep for sprinkler application	0.22
		Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Droughty	0.07
		Depth to bedrock	0.10	Depth to bedrock	0.10	Very limited Restricted permeability	1.00
197IB: Irwin-----	80	Too acid	0.03	Too acid	0.14	Too acid	0.14
				Depth to bedrock	0.10	Depth to bedrock	0.10
						Too steep for surface application	0.08
		Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00
197ID: Irwin-----	85	Runoff limitation	0.40				
		Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00
		Runoff limitation	0.40	Sodium content	0.08	Too steep for surface application	0.31
						Sodium content	0.08
197IV: Ivan-----	90	Sodium content	0.08				
		Somewhat limited Flooding	0.60	Very limited Flooding	1.00	Somewhat limited Flooding	0.60
197IX: Ivan-----	80	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
197PN: Pawnee-----	85	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Restricted permeability	1.00	Restricted permeability	1.00	Restricted permeability	1.00
		Runoff limitation	0.40			Too steep for surface application	0.31
197WE: Wamego-----	90	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00
		Depth to bedrock	0.84	Depth to bedrock	0.84	Depth to bedrock	0.84
		Droughty	0.41	Droughty	0.41	Droughty	0.41
		Too acid	0.03	Too acid	0.14	Too steep for surface application	0.31

AGRICULTURAL WASTE MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food-processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
201CS: Crete-----	95	Very limited Restricted permeability Too acid	1.00 0.11	Very limited Restricted permeability Too acid	1.00 0.42	Too acid	0.14
201CX: Crete, eroded-----	90	Somewhat limited Restricted permeability Too acid	0.89 0.11	Somewhat limited Restricted permeability Too acid	0.78 0.42	Somewhat limited Restricted permeability Too acid Too steep for surface application	1.00 0.42 0.31
201KS: Kipson-----	70	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to bedrock Slope	1.00 1.00	Very limited Depth to bedrock Too steep for surface application	1.00 1.00
Sogn-----	15	Droughty	0.96	Droughty	0.96	Too steep for sprinkler application	1.00
		Runoff limitation	0.40			Droughty	0.96
201LC: Lancaster-----	85	Very limited Depth to bedrock Droughty	1.00 0.99	Very limited Depth to bedrock Droughty	1.00 0.99	Very limited Depth to bedrock Too steep for surface application	1.00 1.00
		Runoff limitation Slope	0.40 0.16	Slope	0.16	Droughty Too steep for sprinkler application	0.99 0.39
Ad: Ivan-----	99	Somewhat limited Depth to bedrock Droughty	0.54 0.11	Somewhat limited Depth to bedrock Too acid	0.54 0.14	Somewhat limited Depth to bedrock Too steep for surface application	0.54 0.31
		Too acid	0.03	Droughty	0.11	Too acid Droughty	0.14 0.11
AED: Arents, Earthen Dam-	100	Very limited Flooding	1.00	Very limited Flooding	1.00	Very limited Flooding	1.00
BE: Benfield-----	89	Not rated		Not rated		Not rated	
Bf: Benfield-----	45	Very limited Restricted permeability Depth to bedrock	1.00 0.29	Very limited Restricted permeability Depth to bedrock	1.00 0.29	Very limited Restricted permeability Too steep for surface application	1.00 0.31
		Droughty	0.00	Droughty	0.00	Depth to bedrock Droughty	0.29 0.00
Florence-----	30	Very limited Restricted permeability Slope	1.00 0.84	Very limited Restricted permeability Slope	1.00 0.84	Very limited Restricted permeability Too steep for surface application	1.00 1.00
		Depth to bedrock	0.10	Depth to bedrock	0.10	Too steep for sprinkler application Depth to bedrock	0.89 0.10
Florence-----	30	Very limited Droughty Depth to bedrock	1.00 0.46	Very limited Droughty Depth to bedrock	1.00 0.46	Very limited Droughty Too steep for surface application	1.00 1.00
		Restricted permeability	0.30	Restricted permeability	0.22	Depth to bedrock	0.46

AGRICULTURAL WASTE MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food-processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Bk: Wymore-----	60	Slope	0.16	Slope	0.16	Too steep for sprinkler application	0.39
						Restricted permeability	0.22
		Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Too steep for surface application	1.00
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Restricted permeability	1.00
		Slope	0.96	Slope	0.96	Depth to saturated zone	1.00
Kennebec-----	45	Runoff limitation	0.40	Too acid	0.14	Too steep for sprinkler application	0.97
		Too acid	0.03			Too acid	0.14
		Somewhat limited Flooding	0.60	Very limited Flooding	1.00	Somewhat limited Flooding	0.60
BOP: Borrow Pits-----	100	Not rated		Not rated		Not rated	
Ca: Carr-----	45	Somewhat limited Flooding	0.60	Very limited Flooding	1.00	Somewhat limited Flooding	0.60
Sarpy-----	40	Filtering capacity	0.00	Filtering capacity	0.00	Filtering capacity	0.00
		Very limited Filtering capacity	1.00	Very limited Flooding	1.00	Very limited Filtering capacity	1.00
		Flooding	0.60	Filtering capacity	1.00	Flooding	0.60
Ch: Chase-----	84	Droughty Leaching limitation	0.52 0.45	Droughty	0.52	Droughty	0.52
		Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00
Cs: Clime-----	50	Depth to saturated zone	0.43	Depth to saturated zone	0.43	Depth to saturated zone	0.43
		Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00
		Slope	0.84	Slope	0.84	Too steep for surface application	1.00
Sogn-----	30	Depth to bedrock	0.46	Depth to bedrock	0.46	Too steep for sprinkler application	0.89
		Droughty	0.08	Droughty	0.08	Depth to bedrock	0.46
		Very limited Depth to bedrock	1.00	Very limited Droughty	1.00	Droughty	0.08
CT: Crete-----	83	Droughty	1.00	Depth to bedrock	1.00	Depth to bedrock	1.00
		Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Too steep for surface application	0.91
		Too acid	0.11	Too acid	0.42	Too steep for sprinkler application	0.02
Dr: Dwight-----	45	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00

AGRICULTURAL WASTE MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food-processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Irwin-----	40	Runoff limitation	0.40	Droughty	0.02	Droughty	0.02
		Droughty	0.02				
		Salinity	0.00				
		Very limited Restricted permeability	1.00				
		Runoff limitation	0.40			Very limited Restricted permeability Too steep for surface application	0.00
Dw: Dwight-----	45	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00
		Runoff limitation	0.40	Droughty	0.02	Droughty	0.02
		Droughty	0.02				
		Salinity	0.00				
Irwin-----	40	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00
		Runoff limitation	0.40			Too steep for surface application	0.00
Em: Elmont-----	74	Somewhat limited Restricted permeability	0.30	Somewhat limited Restricted permeability	0.22	Somewhat limited Too steep for surface application	0.66
		Too acid	0.02	Too acid	0.07	Restricted permeability	0.22
						Too acid	0.07
						Too steep for sprinkler application	0.00
En: Elmont-----	35	Somewhat limited Restricted permeability	0.30	Somewhat limited Restricted permeability	0.22	Very limited Too steep for surface application	1.00
		Slope	0.04	Too acid	0.07	Restricted permeability	0.22
		Too acid	0.02	Slope	0.04	Too steep for sprinkler application	0.22
						Too acid	0.07
Clime-----	30	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00
		Depth to bedrock	0.42	Depth to bedrock	0.42	Too steep for surface application	1.00
		Slope	0.16	Slope	0.16	Depth to bedrock	0.42
		Droughty	0.00	Droughty	0.00	Too steep for sprinkler application	0.39
						Droughty	0.00
Eu: Eudora-----	88	Somewhat limited Flooding	0.60	Very limited Flooding	1.00	Somewhat limited Flooding	0.60
		Filtering capacity	0.00	Filtering capacity	0.00	Filtering capacity	0.00
Ga: Geary-----	90	Somewhat limited Too acid	0.03	Somewhat limited Too acid	0.14	Somewhat limited Too acid	0.14
						Too steep for surface application	0.00
Ge: Geary-----	100	Somewhat limited Too acid	0.03	Somewhat limited Too acid	0.14	Somewhat limited Too steep for surface application	0.66
						Too acid	0.14
						Too steep for sprinkler application	0.00
Ha: Haynie-----	90	Somewhat limited Flooding	0.60	Very limited Flooding	1.00	Somewhat limited Flooding	0.60

AGRICULTURAL WASTE MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food-processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
HO: Hobbs-----	89	Restricted permeability	0.30	Restricted permeability	0.22	Restricted permeability	0.22
		Somewhat limited Flooding	0.60	Very limited Flooding	1.00	Somewhat limited Flooding	0.60
Ic: Irwin-----	85	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00
		Runoff limitation	0.40			Too steep for surface application	0.66
						Too steep for sprinkler application	0.00
Id: Irwin, eroded-----	85	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00
		Runoff limitation	0.40			Too steep for surface application	0.66
						Too steep for sprinkler application	0.00
Ie: Ivan-----	88	Not limited		Not limited		Not limited	
Iv: Ivan-----	45	Somewhat limited Flooding	0.60	Very limited Flooding	1.00	Somewhat limited Flooding	0.60
		Somewhat limited Flooding	0.60	Very limited Flooding	1.00	Somewhat limited Flooding	0.60
Ka: Kahola-----	85	Not limited		Somewhat limited Flooding	0.40	Not limited	
Ke: Kenesaw-----	90	Not limited		Not limited		Somewhat limited Too steep for surface application	0.08
Kf: Kenesaw-----	85	Somewhat limited Slope	0.00	Somewhat limited Slope	0.00	Very limited Too steep for surface application	1.00
						Too steep for sprinkler application	0.10
KN: Kennebec-----	95	Somewhat limited Flooding	0.60	Very limited Flooding	1.00	Somewhat limited Flooding	0.60
		Depth to saturated zone	0.09	Depth to saturated zone	0.09	Depth to saturated zone	0.09
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
Ma: Mayberry-----	95	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Restricted permeability	1.00	Restricted permeability	1.00	Restricted permeability	1.00
		Runoff limitation	0.40	Too acid	0.14	Too acid	0.14
		Too acid	0.03			Too steep for surface application	0.08
Mb: Mayberry-----	95	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00	Very limited Depth to saturated zone	1.00
		Restricted permeability	1.00	Restricted permeability	1.00	Restricted permeability	1.00
		Runoff limitation	0.40	Too acid	0.14	Too acid	0.14
		Too acid	0.03			Too steep for surface application	0.08

AGRICULTURAL WASTE MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food-processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Mu: Muir-----	84	Not limited		Somewhat limited Flooding	0.40	Not limited	
QUA: Quarries-----	100	Not rated		Not rated		Not rated	
Rd: Reading-----	90	Somewhat limited Too acid	0.03	Somewhat limited Flooding Too acid	0.40 0.14	Somewhat limited Too acid	0.14
Re: Reading-----	90	Somewhat limited Too acid	0.03	Somewhat limited Flooding Too acid	0.40 0.14	Somewhat limited Too acid	0.14
Sa: Sarpy-----	98	Very limited Filtering capacity Droughty	1.00 0.65	Very limited Flooding Filtering capacity Droughty	1.00 1.00 0.65	Very limited Filtering capacity Droughty Flooding	1.00 0.65 0.60
Sm: Smolan-----	90	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability Too steep for surface application	1.00 0.00
Sn: Smolan-----	75	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability Too steep for surface application Too steep for sprinkler application	1.00 0.66 0.00
So: Smolan, eroded-----	80	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability Too steep for surface application Too steep for sprinkler application	1.00 0.66 0.00
St: Clime-----	75	Very limited Slope	1.00	Very limited Slope	1.00	Very limited Too steep for surface application	1.00
		Restricted permeability	1.00	Restricted permeability	1.00	Too steep for sprinkler application	1.00
		Depth to bedrock	0.20	Depth to bedrock	0.20	Restricted permeability	1.00
		Droughty	0.10	Droughty	0.10	Depth to bedrock Droughty	0.20 0.10
Su: Sutphen-----	100	Very limited Restricted permeability Flooding Runoff limitation	1.00 0.60 0.40	Very limited Restricted permeability Flooding	1.00 1.00	Very limited Restricted permeability Flooding	1.00 0.60
Ts: Tully-----	85	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability Too steep for surface application	1.00 0.00

AGRICULTURAL WASTE MANAGEMENT--Continued
Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food-processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Tt: Tully, eroded-----	85	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability Too steep for surface application	1.00 0.00
Tu: Tully-----	85	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability Too steep for surface application Too steep for sprinkler application	1.00 0.66 0.00
Tv: Tully, eroded-----	85	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability Too steep for surface application Too steep for sprinkler application	1.00 0.66 0.00
W: Water-----	100	Not rated		Not rated		Not rated	
Wm: Wymore-----	100	Very limited Restricted permeability Depth to saturated zone Runoff limitation Too acid	1.00 1.00 0.40 0.03	Very limited Restricted permeability Depth to saturated zone Too acid	1.00 1.00 0.14	Very limited Restricted permeability Depth to saturated zone Too acid	1.00 1.00 0.14
Wn: Wymore-----	90	Very limited Restricted permeability Depth to saturated zone Runoff limitation Too acid	1.00 1.00 0.40 0.03	Very limited Restricted permeability Depth to saturated zone Too acid	1.00 1.00 0.14	Very limited Restricted permeability Depth to saturated zone Too acid Too steep for surface application	1.00 1.00 0.14 0.00
Wo: Wymore, eroded-----	90	Very limited Restricted permeability Depth to saturated zone Runoff limitation Too acid	1.00 1.00 0.40 0.03	Very limited Restricted permeability Depth to saturated zone Too acid	1.00 1.00 0.14	Very limited Restricted permeability Depth to saturated zone Too acid Too steep for surface application	1.00 1.00 0.14 0.00
Wr: Wymore-----	90	Very limited Restricted permeability Depth to saturated zone Runoff limitation Too acid	1.00 1.00 0.40 0.03	Very limited Restricted permeability Depth to saturated zone Too acid	1.00 1.00 0.14	Very limited Restricted permeability Depth to saturated zone Too steep for surface application Too acid Too steep for sprinkler application	1.00 1.00 0.66 0.14 0.00
Ws: Wymore, eroded-----	90	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00	Very limited Restricted permeability	1.00

AGRICULTURAL WASTE MANAGEMENT--Continued
 Riley County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.00 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Application of manure and food-processing waste		Application of sewage sludge		Disposal of wastewater by irrigation	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
		Depth to saturated zone	1.00	Depth to saturated zone	1.00	Depth to saturated zone	1.00
		Runoff limitation	0.40	Too acid	0.14	Too steep for surface application	0.66
		Too acid	0.03			Too acid	0.14
						Too steep for sprinkler application	0.00

WIN-PST SPISP II
SOIL SENSITIVITY TO PESTICIDE LOSS RATING REPORT

Soils Data Table: SOIL_KS Sort Order: MUSYM

Riley County, Kansas: KS161

MUSYM/SEQ#	COMPONENT/TEXTURE/MU%	HYD	KFACT	SURFACE DEPTH	% OM	SPISP II Ratings		
						Leaching (SLP)	Solution Runoff (SSRP)	Adsorbed Runoff (SARP)
027CS 1	CRETE SIL 100%	C	0.37	6"	3.0%	L	H	H
027CX 1	CRETE SICL 100%	C	0.37	6"	3.0%	L	H	H
027HN 1	HOBBS SIL 90%	B	0.32	7"	3.0%	I	I	I
027KS 1	KIPSON SICL 79%	D	0.32	8"	2.0%	V	H	H (s)
027KS 2	SOGN SICL 20%	D	0.32	12"	0.8%	V	H	H (s)
061BE 1	BENFIELD SICL 60%	C	0.37	5"	4.0%	L	H	H (s)
061BE 2	FLORENCE GR-SIL 40%	C	0.24	5"	6.0%	L	H	H
061CF 1	CLIME SICL 60%	C	0.32	12"	3.0%	L	H	H (s)
061CF 2	SOGN SICL 20%	D	0.32	9"	2.0%	V	H	H (s)
061CR 1	CRETE SICL 90%	C	0.37	6"	3.0%	L	H	H
061CS 1	CRETE SICL 90%	C	0.37	6"	3.0%	L	H	H
061EU 1	EUDORA SIL 85%	B	0.32	7"	2.0%	I	I	I
061HE 1	HAYNIE SIL 57%	B	0.32	10"	2.0%	I	I	I
061KA 1	KAHOLA SIL 75%	B	0.32	24"	3.0%	L	I	I
061KB 1	KAHOLA SIL 75%	B	0.32	24"	3.0%	L	I	I
061RE 1	READING SICL 80%	B	0.32	8"	3.0%	I	I	I
061TO 1	TULLY SICL 80%	C	0.37	12"	4.5%	L	H	H
117PA 1	PAWNEE CL 85%	D	0.37	13"	3.0%	H (w)	H	H
117PB 1	PAWNEE CL 90%	D	0.37	13"	3.0%	H (w)	H	H
149HS 1	HAYNIE VFSL 70%	B	0.37	9"	1.3%	I	I	I
149HS 2	SARPY FS 30%	A	0.15	6"	0.6%	H	L	L
149PS 1	PAXICO SIL 100%	B	0.37	42"	2.0%	H (w)	I	I
149SF 1	SARPY S 100%	A	0.15	6"	0.6%	H	L	L
197CM 1	CLIME SICL 85%	C	0.32	5"	3.0%	L	H	H
197FL 1	FLORENCE GR-SIL 40%	C	0.24	14"	6.0%	L	H	H
197FL 2	LABETTE SIL 30%	C	0.32	7"	3.0%	L	H	H
197IB 1	IRWIN SICL 80%	D	0.32	12"	3.0%	V	H	H
197ID 1	IRWIN SICL 85%	D	0.37	6"	3.0%	V	H	H

WIN-PST SPISP II
SOIL SENSITIVITY TO PESTICIDE LOSS RATING REPORT

Soils Data Table: SOIL_KS Sort Order: MUSYM

Riley County, Kansas: KS161

197IV 1	IVAN SIL 90%	B	0.32	36"	3.0% L	I	I
197IX 1	IVAN SICL 80%	B	0.32	40"	3.0% L	I	I
197PN 1	PAWNEE CL 85%	D	0.37	14"	3.0% H (w)	H	H
197WE 1	WAMEGO SICL 90%	C	0.32	9"	3.0% L	H	H
201CS 1	CRETE SICL 100%	C	0.37	9"	3.0% L	H	H
201CX 1	CRETE SICL 90%	C	0.37	5"	3.0% L	H	H
201KS 1	KIPSON SICL 85%	D	0.32	12"	2.0% V	H	H (s)
201LC 1	LANCASTER L 100%	B	0.28	9"	2.5% I	I	I
Ad 1	ALLUVIAL LAND SIL 100%	B	0.32	7"	3.0% I	I	I
AED 1	ARENTS, EARTHEN DAM 100%		0.00	0"	0.0% ?	?	?
BE 1	BENFIELD SICL 100%	C	0.37	10"	2.5% L	H	H
Bf 1	BENFIELD SICL 65%	C	0.37	6"	2.5% L	H	H (s)
Bf 2	FLORENCE GR-SIL 35%	C	0.24	5"	3.0% L	H	H
Bk 1	BREAKS SICL 60%	D	0.37	13"	3.0% H (w)	H	H (s)
Bk 2	ALLUVIAL LAND SIL 40%	B	0.32	18"	5.5% L	I	I
BOP 1	BORROW PITS 100%		0.00	0"	0.0% ?	?	?
Ca 1	CARR FSL 60%	B	0.24	17"	0.5% H	I	I
Ca 2	SARPY LFS 40%	A	0.17	5"	0.5% H	L	L
Ch 1	CHASE SICL 100%	C	0.37	13"	3.0% H (w)	H	H
Cs 1	CLIME SICL 65%	C	0.32	12"	3.0% L	H	H (s)
Cs 2	SOGN SICL 35%	D	0.32	9"	2.0% V	H	H
CT 1	CRETE SICL 100%	C	0.37	8"	3.0% L	H	H
Dr 1	DWIGHT SIL 55%	D	0.43	4"	3.0% V	H	H
Dr 2	IRWIN SICL 45%	D	0.37	11"	3.0% V	H	H
Dw 1	DWIGHT SIL 55%	D	0.43	4"	3.0% V	H	H
Dw 2	IRWIN SICL 45%	D	0.37	11"	3.0% V	H	H
Em 1	ELMONT SIL 100%	B	0.32	10"	3.0% I	I	I
En 1	ELMONT SIL 65%	B	0.32	10"	3.0% I	I	I
En 2	CLIME SICL 35%	C	0.32	12"	3.0% L	H	H
Eu 1	EUDORA SIL 90%	B	0.32	12"	1.5% I	I	I

WIN-PST SPISP II
SOIL SENSITIVITY TO PESTICIDE LOSS RATING REPORT

Soils Data Table: SOIL_KS Sort Order: MUSYM

Riley County, Kansas: KS161

Ga 1	GEARY SIL 100%	B	0.32	8"	2.5% I	I	I
Ge 1	GEARY SIL 100%	B	0.32	8"	2.5% I	I	I
Ha 1	HAYNIE VFSL 100%	B	0.37	10"	2.0% I	I	I
HO 1	HOBBS SIL 85%	B	0.32	7"	3.0% I	I	I
Ic 1	IRWIN SICL 100%	D	0.37	11"	3.0% V	H	H
Id 1	IRWIN SICL 100%	D	0.37	11"	3.0% V	H	H
Ie 1	IVAN SICL 100%	B	0.32	7"	3.0% I	I	I
Iv 1	IVAN SIL 50%	B	0.32	7"	3.0% I	I	I
Iv 2	KENNEBEC SIL 50%	B	0.32	18"	5.5% L	I	I
Ka 1	KAHOLA SIL 100%	B	0.32	13"	3.0% I	I	I
Ke 1	KENESAW SIL 100%	B	0.32	12"	2.0% I	I	I
Kf 1	KENESAW SIL 100%	B	0.32	12"	2.0% I	I	I
KN 1	KENNEBEC SIL 97%	B	0.28	48"	4.0% L	I	I
M-W 1	MISCELLANEOUS WATER 100%		0.00	0"	0.0% ?	?	?
Ma 1	MAYBERRY CL 85%	D	0.37	10"	2.0% H (w)	H	H
Mb 1	MAYBERRY CL 85%	D	0.37	10"	2.0% H (w)	H	H
Mu 1	MUIR SIL 80%	B	0.32	4"	3.0% I	I	I
QUA 1	QUARRIES 100%		0.00	0"	0.0% ?	?	?
Rd 1	READING SIL 100%	B	0.32	11"	3.0% I	I	I
Re 1	READING SIL 100%	B	0.32	11"	3.0% I	I	I
Sa 1	SARPY LFS 100%	A	0.17	5"	0.5% H	L	L
Sm 1	SMOLAN SIL 100%	C	0.37	8"	3.0% L	H	H
Sn 1	SMOLAN SIL 100%	C	0.37	8"	3.0% L	H	H
So 1	SMOLAN SICL 100%	C	0.37	7"	3.0% L	H	H
St 1	STONY STEEP LAND ST-SICL 100%	C	0.28	2"	3.0% L	H	H (s)
Su 1	SUTPHEN SIC 100%	D	0.28	8"	3.0% V	H	H
Ts 1	TULLY SICL 80%	C	0.37	7"	4.5% L	H	H
Tt 1	TULLY SICL 100%	C	0.37	7"	2.5% L	H	H
Tu 1	TULLY SICL 99%	C	0.37	10"	3.0% L	H	H

WIN-PST SPISP II
SOIL SENSITIVITY TO PESTICIDE LOSS RATING REPORT

Soils Data Table: SOIL_KS Sort Order: MUSYM

Riley County, Kansas: KS161

Tv 1	TULLY SICL 100%	C	0.37	7"	3.0% L	H	H
W 1	WATER 100%		0.00	0"	0.0% ?	?	?
Wm 1	WYMORE SICL 100%	D	0.37	13"	3.0% H (w)	H	H
Wn 1	WYMORE SICL 100%	D	0.37	13"	3.0% H (w)	H	H
Wo 1	WYMORE SICL 100%	D	0.37	7"	3.0% H (w)	H	H
Wr 1	WYMORE SICL 100%	D	0.37	13"	3.0% H (w)	H	H
Ws 1	WYMORE SICL 100%	D	0.37	7"	3.0% H (w)	H	H

(.\REPORTS\SOILS.TXT generated on 12/12/01 at 12:11:15)

H -- High
I -- Intermediate
L -- Low
V -- Very Low

Conditions that affect ratings:

- m -- There are macropores in the surface horizon deeper than 24"
- w -- The high water table comes within 24" of the surface during the growing season
- s -- The field slope is greater than 15%

SPISP II S-Ratings:

- SLP -- Soil Leaching Potential
- SSRP -- Soil Solution Runoff Potential
- SARP -- Soil Adsorbed Runoff Potential

In this section, hydric soils are defined and described and the hydric soils in the survey area are listed. The three essential characteristics of wetlands are hydrophytic vegetation, hydric soils, and wetland hydrology (Cowardin and others, 1979; U.S. Army Corps of Engineers, 1987; National Research Council, 1995; Tiner, 1985). Criteria for each of the characteristics must be met for areas to be identified as wetlands. Undrained hydric soils that have natural vegetation should support a dominant population of ecological wetland plant species. Hydric soils that have been converted to other uses should be capable of being restored to wetlands.

Hydric soils are defined by the National Technical Committee for Hydric Soils (NTCHS) as soils that formed under conditions of saturation, flooding, or ponding long enough during the growing season to develop anaerobic conditions in the upper part (Federal Register, 1994). These soils are either saturated or inundated long enough during the growing season to support the growth and reproduction of hydrophytic vegetation.

The NTCHS definition identifies general soil properties that are associated with wetness. In order to determine whether a specific soil is a hydric soil or nonhydric soil, however, more specific information, such as information about the depth and duration of the water table, is needed. Thus, criteria that identify those estimated soil properties unique to hydric soils have been established (Federal Register, 1995). These criteria are used to identify a phase of a soil series that normally is associated with wetlands. The criteria used are selected estimated soil properties that are described in "Soil Taxonomy" (USDA, 1999) and "Keys to Soil Taxonomy" (USDA, 1998) and in the "Soil Survey Manual" (USDA, 1993).

If soils are wet enough for a long enough period to be considered hydric, they should exhibit certain properties that can be easily observed in the field. These visible properties are indicators of hydric soils. The indicators used to make onsite determinations of hydric soils in this survey area are specified in "Field Indicators of Hydric Soils in the United States" (Hurt and others, 1996).

Hydric soils are identified by examining and describing the soil to a depth of about 20 inches. This depth may be greater if determination of an appropriate indicator so requires. It is always recommended that soils be excavated and described to the depth necessary for an understanding of the redoximorphic processes. Then, using the completed soil descriptions, soil scientists can compare the soil features required by each indicator and specify which indicators have been matched with the conditions observed in the soil. The soil can be identified as a hydric soil if at least one of the approved indicators is present.

Map units in the Hydric Soil Interpretations table meet the definition of hydric soils and, in addition, have at least one of the hydric soil indicators. This list can help in planning land uses; however, onsite investigation is recommended to determine the hydric soils on a specific site (National Research Council, 1995; Hurt and others, 1996).

Map units that are made up of hydric soils may have small areas, or inclusions, of nonhydric soils in the higher positions on the landform, and map units made up of nonhydric soils may have inclusions of hydric soils in the lower positions on the landform.

These map units, in general, do not meet the definition of hydric soils because they do not have one of the hydric soil indicators. A portion of these map units, however, may include hydric soils. Onsite investigation is recommended to determine whether hydric soils occur and the location of the included hydric soils.

HYDRIC SOIL INTERPRETATIONS
 HYDRIC SOILS LIST
 Riley County, Kansas

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria				
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria	
027CS: CRETE SILT LOAM, 1 TO 3 PERCENT SLOPES	CRETE	No	hillslope	---	---	---	---	
	BENFIELD	No	hillslope	---	---	---	---	
	GEARY	No	hillslope	---	---	---	---	
	HOBBS	No	flood plain	---	---	---	---	
	HOLDER	No	hillslope	---	---	---	---	
	LANCASTER	No	hillslope	---	---	---	---	
027CX: CRETE SILTY CLAY LOAM, 3 TO 8 PERCENT SLOPES, ERODED	CRETE	No	hillside	---	---	---	---	
	GEARY	No	hillslope	---	---	---	---	
	HOLDER	No	hillslope	---	---	---	---	
	BENFIELD	No	hillslope	---	---	---	---	
	HOBBS	No	flood plain	---	---	---	---	
	LANCASTER	No	hillslope	---	---	---	---	
027HN: HOBBS SILT LOAM, CHANNELED	HOBBS	No	flood plain	---	---	---	---	
	CRETE	No	hillslope	---	---	---	---	
	GEARY	No	hillslope	---	---	---	---	
	MUIR	No	flood plain	---	---	---	---	
	UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES	
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO	
027KS: KIPSON-SOBN SILTY CLAY LOAMS, 5 TO 20 PERCENT SLOPES	KIPSON	No	hillslope	---	---	---	---	
	SOBN	No	hillslope	---	---	---	---	
	BENFIELD	No	hillslope	---	---	---	---	
	TULLY	No	hillslope	---	---	---	---	
	GEARY	No	hillslope	---	---	---	---	
	CRETE	No	hillslope	---	---	---	---	
	ROCK OUTCROP	---	---	---	---	---	---	
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO	
	061BE: BENFIELD-FLORENCE COMPLEX, 5 TO 30 PERCENT SLOPES	BENFIELD	No	hillslope	---	---	---	---
		FLORENCE	No	hillslope	---	---	---	---
CLIME		No	hillslope	---	---	---	---	
KONZA		No	ridge	---	---	---	---	
LABETTE		No	hillslope	---	---	---	---	
IRWIN		No	hillslope	---	---	---	---	
TULLY		No	hillslope	---	---	---	---	
IVAN		No	flood plain	---	---	---	---	
KAHOLA		No	flood plain	---	---	---	---	
KONZA		No	ridge	---	---	---	---	
UNNAMED HYDRIC SOIL (saturation)		Yes	flood plain, marsh	2B3	YES	NO	NO	
061CF: CLIME-SOBN SILTY CLAY LOAMS, 5 TO 20 PERCENT SLOPES	CLIME	No	hillslope	---	---	---	---	
	SOBN	No	hillslope	---	---	---	---	
	TULLY	No	hillslope	---	---	---	---	
	IRWIN	No	hillslope	---	---	---	---	
	TUTTLE	No	hillslope	---	---	---	---	
	IVAN	No	flood plain	---	---	---	---	
061CR: CRETE SILTY CLAY LOAM, 0 TO 1 PERCENT SLOPES	KAHOLA	No	flood plain	---	---	---	---	
	KONZA	No	ridge	---	---	---	---	
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO	
	CRETE	No	ridge	---	---	---	---	
	HASTINGS	No	divide	---	---	---	---	
	HOLDER	No	hillslope	---	---	---	---	
061CS: CRETE SILTY CLAY LOAM, 1 TO 4 PERCENT SLOPES	CRETE	No	hillslope	---	---	---	---	
	HASTINGS	No	divide	---	---	---	---	
	HOLDER	No	hillslope	---	---	---	---	
	CLIME	No	hillslope	---	---	---	---	

HYDRIC SOIL INTERPRETATIONS
 HYDRIC SOILS LIST
 Riley County, Kansas

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
061EU: EUDORA SILT LOAM, OCCASIONALLY FLOODED	EUDORA	No	flood plain	---	---	---	---
	MCCOOK	No	stream terrace	---	---	---	---
	SARPY	No	flood plain	---	---	---	---
	UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO
061HE: HAYNIE SILT LOAM, FREQUENTLY FLOODED	HAYNIE	No	flood plain	---	---	---	---
	UNNAMED STRATIFIED SOILS (fine- silty)	No	flood plain	---	---	---	---
	UNNAMED STRATIFIED SOILS (fine)	No	flood plain	---	---	---	---
	UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO
	UNNAMED STRATIFIED SOILS (sandy)	No	flood plain	---	---	---	---
061KA: KAHOLA SILT LOAM, CHANNELED	KAHOLA	No	flood plain	---	---	---	---
	TULLY	No	hillslope	---	---	---	---
	IVAN	No	flood plain	---	---	---	---
	UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES
061KB: KAHOLA SILT LOAM, OCCASIONALLY FLOODED	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO
	KAHOLA	No	flood plain	---	---	---	---
	IVAN	No	flood plain	---	---	---	---
	TULLY	No	hillslope	---	---	---	---
	READING	No	flood plain	---	---	---	---
061RE: READING SILTY CLAY LOAM, 0 TO 2 PERCENT SLOPES	UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO
	KAHOLA	No	flood plain	---	---	---	---
061TO: TULLY SILTY CLAY LOAM, 3 TO 8 PERCENT SLOPES	READING	No	flood plain	---	---	---	---
	TULLY	No	hillslope	---	---	---	---
117PA: PAWNEE CLAY LOAM, 1 TO 4 PERCENT SLOPES	KAHOLA	No	flood plain	---	---	---	---
	READING	No	flood plain	---	---	---	---
	BENFIELD	No	hillslope	---	---	---	---
	CLIME	No	hillslope	---	---	---	---
	FLORENCE	No	hillslope	---	---	---	---
	IVAN	No	flood plain	---	---	---	---
	PAWNEE	No	hillslope	---	---	---	---
	KIPSON	No	hillslope	---	---	---	---
	MORRILL	No	hillslope	---	---	---	---
	SHELBY	No	hillslope	---	---	---	---
117PB: PAWNEE CLAY LOAM, 4 TO 8 PERCENT SLOPES	WYMORE	No	hillslope	---	---	---	---
	PAWNEE	No	hillslope	---	---	---	---
	KIPSON	No	hillslope	---	---	---	---
	MORRILL	No	hillslope	---	---	---	---
	SHELBY	No	hillslope	---	---	---	---
WYMORE	No	hillslope	---	---	---	---	

HYDRIC SOIL INTERPRETATIONS
 HYDRIC SOILS LIST
 Riley County, Kansas

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
149HS: HAYNIE-SARPY COMPLEX, OCCASIONALLY FLOODED	HAYNIE	No	flood-plain step	---	---	---	---
	SARPY	No	flood plain	---	---	---	---
	EUDORA	No	flood plain	---	---	---	---
	KIMO	No	flood plain	---	---	---	---
	UNNAMED HYDRIC SOIL	Yes	depression, flood plain	2B3	YES	NO	NO
149PS: PAXICO SILT LOAM, FREQUENTLY FLOODED	PAXICO	Yes	flood plain	4	NO	YES	NO
	HAYNIE	No	flood-plain step	---	---	---	---
	SARPY	No	flood plain	---	---	---	---
149SF: SARPY SAND, FREQUENTLY FLOODED	SARPY	Yes	flood plain	4	NO	YES	NO
	EUDORA	No	flood plain	---	---	---	---
	HAYNIE	No	flood-plain step	---	---	---	---
	KIMO	No	flood-plain step	---	---	---	---
197CM: CLIME SILTY CLAY LOAM, 3 TO 7 PERCENT SLOPES	CLIME	No	hillslope	---	---	---	---
	MARTIN	No	hillslope	---	---	---	---
	SOGN	No	hillslope	---	---	---	---
	WAMEGO	No	hillslope	---	---	---	---
197FL: FLORENCE-LABETTE COMPLEX, 3 TO 15 PERCENT SLOPES	FLORENCE	No	hillslope	---	---	---	---
	LABETTE	No	ridge	---	---	---	---
	CLIME	No	hillslope	---	---	---	---
	MARTIN	No	hillslope	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
	SOGN	No	hillslope	---	---	---	---
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO
197IB: IRWIN SILTY CLAY LOAM, 1 TO 3 PERCENT SLOPES	IRWIN	No	hillslope	---	---	---	---
	DWIGHT	No	hillslope	---	---	---	---
	LADYSMITH	No	divide	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
197ID: IRWIN SILTY CLAY LOAM, 3 TO 7 PERCENT SLOPES	KONZA	No	ridge	---	---	---	---
	CLIME	No	hillslope	---	---	---	---
	FLORENCE	No	hillslope	---	---	---	---
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO
	IRWIN	No	hillslope	---	---	---	---
	CHASE	No	stream terrace	---	---	---	---
197IV: IVAN SILT LOAM, OCCASIONALLY FLOODED	READING	No	stream terrace	---	---	---	---
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO
	IVAN	No	flood plain	---	---	---	---
	MARTIN	No	hillslope	---	---	---	---
197IX: IVAN SILTY CLAY LOAM, CHANNELED	READING	No	stream terrace	---	---	---	---
	UNNAMED HYDRIC SOIL	Yes	flood plain, marsh	2B3	YES	NO	NO
	IVAN	No	flood plain	---	---	---	---
	MARTIN	No	hillslope	---	---	---	---
197PN: PAWNEE CLAY LOAM, 3 TO 7 PERCENT SLOPES	MORRILL	No	hillslope	---	---	---	---
	OSKA	No	hillslope	---	---	---	---
	WAMEGO	No	hillslope	---	---	---	---
197WE: WAMEGO SILTY CLAY LOAM, 3 TO 7 PERCENT SLOPES	OLMITZ	No	fan terrace	---	---	---	---
	PAWNEE	No	hillslope	---	---	---	---
201CS: CRETE SILTY CLAY LOAM, 1 TO 3 PERCENT SLOPES	CRETE	No	hillslope	---	---	---	---
	HOBBS	No	flood plain	---	---	---	---

HYDRIC SOIL INTERPRETATIONS
HYDRIC SOILS LIST
Riley County, Kansas

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
201CX: CRETE SILTY CLAY LOAM, 3 TO 7 PERCENT SLOPES, ERODED	CRETE	No	hillslope	---	---	---	---
	HOBBS LONGFORD	No No	flood plain hillslope	---	---	---	---
201KS: KIPSON-SOQN COMPLEX, 5 TO 30 PERCENT SLOPES	KIPSON	No	hillslope	---	---	---	---
	SOQN	No	hillslope	---	---	---	---
	CRETE	No	hillslope	---	---	---	---
	TULLY	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---
	UNNAMED HYDRIC SOIL	Yes	drainageway, marsh	2B3	YES	NO	NO
201LC: LANCASTER LOAM, 3 TO 7 PERCENT SLOPES	UNNAMED HYDRIC SOILS	Yes	hillslope, marsh	2B3	YES	NO	NO
	LANCASTER	No	hillslope	---	---	---	---
	CRETE	No	hillslope	---	---	---	---
	WELLS	No	hillslope	---	---	---	---
	LONGFORD	No	hillslope	---	---	---	---
	EDALGO	No	hillslope	---	---	---	---
	HEDVILLE	No	hillslope	---	---	---	---
	Ad: IVAN SILT LOAM, CHANNELED	IVAN	No	flood plain	---	---	---
UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES	
AED: ARENTS, EARTHEN DAM	ARENTS, EARTHEN DAM	Unranked	---	---	---	---	---
BE: BENFIELD SILTY CLAY LOAM, 3 TO 7 PERCENT SLOPES	BENFIELD	No	hillslope	---	---	---	---
	CRETE	No	hillslope	---	---	---	---
	KIPSON	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---
Bf: BENFIELD-FLORENCE COMPLEX, 5 TO 20 PERCENT SLOPES	BENFIELD	No	hillslope	---	---	---	---
	FLORENCE	No	hillslope	---	---	---	---
	CLIME	No	hillslope	---	---	---	---
	SOQN	No	hillslope	---	---	---	---
	DWIGHT	No	depression, ridge	---	---	---	---
	IRWIN	No	ridge	---	---	---	---
	TULLY	No	hillslope	---	---	---	---
Bk: WYMORE-KENNEBEC COMPLEX, 0 TO 17 PERCENT SLOPES	WYMORE	No	hillslope	---	---	---	---
	KENNEBEC	No	flood plain	---	---	---	---
	IVAN	No	flood plain	---	---	---	---
	UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO
BOP: BORROW PITS	BORROW PITS	Unranked	---	---	---	---	---
Ca: CARR-SARPY COMPLEX, OCCASIONALLY FLOODED	CARR	No	flood plain	---	---	---	---
	SARPY	No	flood plain	---	---	---	---
	HAYNIE	No	flood plain	---	---	---	---
	UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO

HYDRIC SOIL INTERPRETATIONS
 HYDRIC SOILS LIST
 Riley County, Kansas

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
Ch: CHASE SILTY CLAY LOAM, RARELY FLOODED	CHASE	No	terrace	---	---	---	---
	READING	No	terrace	---	---	---	---
	SUTPHEN	No	flood plain	---	---	---	---
	UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES
Cs: CLIME-SOIGN COMPLEX, 5 TO 20 PERCENT SLOPES	CLIME	No	hillslope	---	---	---	---
	SOIGN	No	hillslope	---	---	---	---
	Unnamed soil	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
	UNNAMED HYDRIC SOIL	Yes	drainageway, marsh	2B3	YES	NO	NO
CT: CRETE SILTY CLAY LOAM, 3 TO 7 PERCENT SLOPES	UNNAMED HYDRIC SOILS	Yes	hillslope, marsh	2B3	YES	NO	NO
	CRETE	No	hillslope	---	---	---	---
	GEARY	No	hillslope	---	---	---	---
	HOLDER	No	hillslope	---	---	---	---
	BENFIELD	No	hillslope	---	---	---	---
	HOBBS	No	flood plain	---	---	---	---
Dr: DWIGHT-IRWIN COMPLEX, 1 TO 4 PERCENT SLOPES	LANCASTER	No	hillslope	---	---	---	---
	DWIGHT	No	depression, ridge	---	---	---	---
	IRWIN	No	ridge	---	---	---	---
	CLIME	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---
Dw: DWIGHT-IRWIN COMPLEX, 1 TO 4 PERCENT SLOPES, ERODED	WYMORE	No	hillslope	---	---	---	---
	DWIGHT	No	depression, divide	---	---	---	---
	IRWIN	No	divide	---	---	---	---
	CLIME	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---
Em: ELMONT SILT LOAM, 3 TO 8 PERCENT SLOPES	WYMORE	No	hillslope	---	---	---	---
	ELMONT	No	hillside	---	---	---	---
	UNNAMED SOIL (moderately deep)	No	hillside	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---
En: ELMONT-CLIME COMPLEX, 5 TO 15 PERCENT SLOPES	ELMONT	No	hillside	---	---	---	---
	CLIME	No	hillside	---	---	---	---
	UNNAMED SOIL (moderately deep)	No	hillslope	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
	SOIGN	No	hillslope	---	---	---	---
Eu: EUDORA SILT LOAM, RARELY FLOODED	EUDORA	No	flood plain	---	---	---	---
	HAYNIE	No	flood plain	---	---	---	---
	MUIR	No	flood plain	---	---	---	---
	UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO
Ga: GEARY SILT LOAM, 1 TO 4 PERCENT SLOPES	GEARY	No	hillside	---	---	---	---
	SMOLAN	No	hillside	---	---	---	---
Ge: GEARY SILT LOAM, 4 TO 8 PERCENT SLOPES	GEARY	No	hillside	---	---	---	---
	KENESAW	No	hillside	---	---	---	---
	SMOLAN	No	hillside	---	---	---	---

HYDRIC SOIL INTERPRETATIONS
 HYDRIC SOILS LIST
 Riley County, Kansas

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
Ha: HAYNIE VERY FINE SANDY LOAM, OCCASIONALLY FLOODED	HAYNIE	No	flood plain	---	---	---	---
	CARR	No	flood plain	---	---	---	---
	EUDORA UNNAMED HYDRIC SOIL (ponding)	No Yes	flood plain depression, flood plain	---	---	---	---
HO: HOBBS SILT LOAM, OCCASIONALLY FLOODED	UNNAMED	Yes	3	NO	NO	YES	
	HOBBS	No	flood plain	---	---	---	---
	SUTPHEN	No	flood plain	---	---	---	---
	CRETE	No	hillslope	---	---	---	---
	GEARY	No	hillslope	---	---	---	---
Ic: IRWIN SILTY CLAY LOAM, 4 TO 8 PERCENT SLOPES	UNNAMED	Yes	3	NO	NO	YES	
	UNNAMED HYDRIC SOIL (ponding)	Yes	2B3	YES	NO	NO	
	UNNAMED HYDRIC SOIL (saturation)	Yes	2B3	YES	NO	NO	
Id: IRWIN SILTY CLAY LOAM, 4 TO 8 PERCENT SLOPES, ERODED	IRWIN	No	hillslope	---	---	---	---
	CLIME	No	hillslope	---	---	---	---
	ROCK OUTCROP WYMORE	---	---	---	---	---	---
Ie: IVAN SILTY CLAY LOAM, 1 TO 3 PERCENT SLOPES	IRWIN	No	hillslope	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
	CLIME	No	hillslope	---	---	---	---
Iv: IVAN AND KENNEBEC SILT LOAMS, OCCASIONALLY FLOODED	ROCK OUTCROP WYMORE	---	---	---	---	---	---
	IVAN	No	flood plain	---	---	---	---
	READING	No	terrace	---	---	---	---
	UNNAMED	Yes	3	NO	NO	YES	
	UNNAMED HYDRIC SOIL (ponding)	Yes	2B3	YES	NO	NO	
Ka: KAHOLA SILT LOAM, RARELY FLOODED	UNNAMED HYDRIC SOIL (saturation)	Yes	2B3	YES	NO	NO	
	IVAN	No	flood plain	---	---	---	---
	KENNEBEC	No	flood plain	---	---	---	---
	MUIR	No	flood plain	---	---	---	---
	READING	No	terrace	---	---	---	---
Ke: KENESAW SILT LOAM, 2 TO 6 PERCENT SLOPES	UNNAMED	Yes	3	NO	NO	YES	
	UNNAMED HYDRIC SOIL (ponding)	Yes	2B3	YES	NO	NO	
	UNNAMED HYDRIC SOIL (saturation)	Yes	2B3	YES	NO	NO	
	KAHOLA	No	flood plain	---	---	---	---
	EUDORA	No	flood plain	---	---	---	---
Kf: KENESAW SILT LOAM, 6 TO 10 PERCENT SLOPES	HAYNIE	No	flood plain	---	---	---	---
	UNNAMED	Yes	3	NO	NO	YES	
	UNNAMED HYDRIC SOIL (ponding)	Yes	2B3	YES	NO	NO	
KN: KENNEBEC SILT LOAM, OCCASIONALLY FLOODED	UNNAMED HYDRIC SOIL (saturation)	Yes	2B3	YES	NO	NO	
	UNNAMED HYDRIC SOIL	Yes	2B3	YES	NO	NO	
	HYDRIC SOIL	Yes	2B3	YES	NO	NO	

HYDRIC SOIL INTERPRETATIONS
 HYDRIC SOILS LIST
 Riley County, Kansas

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
M-W: MISCELLANEOUS WATER	MISCELLANEOUS WATER	Unranked	---	---	---	---	---
Ma: MAYBERRY CLAY LOAM, 2 TO 6 PERCENT SLOPES	MAYBERRY	No	hillslope	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
Mb: MAYBERRY CLAY LOAM, 2 TO 6 PERCENT SLOPES, ERODED	MAYBERRY	No	---	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
Mu: MUIR SILT LOAM, RARELY FLOODED	MUIR	No	flood plain	---	---	---	---
	EUDORA	No	flood plain	---	---	---	---
	READING	No	terrace	---	---	---	---
	SUTPHEN	No	flood plain	---	---	---	---
QUA: QUARRIES	UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES
	QUARRIES	No	---	---	---	---	---
Rd: READING SILT LOAM, 0 TO 1 PERCENT SLOPES, RARELY FLOODED	READING	No	terrace	---	---	---	---
	CHASE	No	terrace	---	---	---	---
	MUIR	No	flood plain	---	---	---	---
Re: READING SILT LOAM, 1 TO 3 PERCENT SLOPES, RARELY FLOODED	READING	No	alluvial fan	---	---	---	---
	TULLY	No	hillslope	---	---	---	---
Sa: SARPY LOAMY FINE SAND, 0 TO 4 PERCENT SLOPES, OCCASIONALLY FLOODED	SARPY	No	flood plain	---	---	---	---
	UNNAMED HYDRIC SOIL (ponding)	Yes	depression, flood plain	3	NO	NO	YES
	UNNAMED HYDRIC SOIL (saturation)	Yes	flood plain, marsh	2B3	YES	NO	NO
Sm: SMOLAN SILT LOAM, 1 TO 4 PERCENT SLOPES	SMOLAN	No	hillslope	---	---	---	---
	GEARY	No	hillslope	---	---	---	---
Sn: SMOLAN SILT LOAM, 4 TO 8 PERCENT SLOPES	WYMORE	No	hillslope	---	---	---	---
	SMOLAN	No	hillslope	---	---	---	---
So: SMOLAN SILTY CLAY LOAM, 4 TO 8 PERCENT SLOPES, ERODED	GEARY	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---
	SMOLAN	No	hillslope	---	---	---	---
St: CLIME SILTY CLAY LOAM, 20 TO 40 PERCENT SLOPES, STONY	GEARY	No	hillslope	---	---	---	---
	CLIME	No	hillslope	---	---	---	---
	TUTTLE	No	hillslope	---	---	---	---
	TULLY	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---
	IVAN	No	flood plain	---	---	---	---
	KAHOLA	No	flood plain	---	---	---	---
Su: SUTPHEN SILTY CLAY, OCCASIONALLY FLOODED	SOGN	No	hillslope	---	---	---	---
	SUTPHEN	No	flood plain	---	---	---	---
	UNNAMED HYDRIC SOIL	Yes	depression, flood plain	2B3	YES	NO	NO
Ts: TULLY SILTY CLAY LOAM, 1 TO 4 PERCENT SLOPES	UNNAMED HYDRIC SOILS	Yes	ephemeral oxbow lake	3	NO	NO	YES
	TULLY	No	hillslope	---	---	---	---
	KAHOLA	No	flood plain	---	---	---	---
	READING	No	flood plain	---	---	---	---
	CLIME	No	hillslope	---	---	---	---
FLORENCE	No	hillslope	---	---	---	---	

HYDRIC SOIL INTERPRETATIONS
 HYDRIC SOILS LIST
 Riley County, Kansas

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria
Tt: TULLY SILTY CLAY LOAM, 1 TO 4 PERCENT SLOPES, ERODED	TULLY	No	hillslope	---	---	---	---
	IRWIN	No	ridge	---	---	---	---
	READING	No	terrace	---	---	---	---
Tu: TULLY SILTY CLAY LOAM, 4 TO 8 PERCENT SLOPES	WYMORE	No	hillslope	---	---	---	---
	TULLY	No	hillslope	---	---	---	---
	IRWIN	No	ridge	---	---	---	---
Tv: TULLY SILTY CLAY LOAM, 4 TO 8 PERCENT SLOPES, ERODED	WYMORE	No	hillslope	---	---	---	---
	UNNAMED	Yes	hillslope,	2B3	YES	NO	NO
	HYDRIC SOIL		marsh				
W: WATER	TULLY	No	hillslope	---	---	---	---
	CLIME	No	hillslope	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
Wm: WYMORE SILTY CLAY LOAM, 0 TO 1 PERCENT SLOPES	ROCK OUTCROP	---	---	---	---	---	---
	WATER	Yes	---	4,3	NO	YES	YES
	WYMORE	No	hillslope	---	---	---	---
Wn: WYMORE SILTY CLAY LOAM, 1 TO 4 PERCENT SLOPES	WYMORE	No	hillslope	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---
Wo: WYMORE SILTY CLAY LOAM, 1 TO 4 PERCENT SLOPES, ERODED	WYMORE	No	hillslope	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---
Wr: WYMORE SILTY CLAY LOAM, 4 TO 8 PERCENT SLOPES	WYMORE	No	hillslope	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---
Ws: WYMORE SILTY CLAY LOAM, 4 TO 8 PERCENT SLOPES, ERODED	WYMORE	No	hillslope	---	---	---	---
	IRWIN	No	hillslope	---	---	---	---
	ROCK OUTCROP	---	---	---	---	---	---

HYDRIC SOIL INTERPRETATIONS
 HYDRIC SOILS LIST
 Riley County, Kansas

All mapunits are displayed regardless of hydric status and are listed in alpha-numeric order by mapunit symbol. The "Hydric Soils Criteria" columns indicate the conditions that caused the mapunit component to be classified as "Hydric" or "Non-Hydric". These criteria are defined in "Hydric Soils of the United States" (USDA Miscellaneous Publication No. 1491, June, 1991). See the "Criteria for Hydric Soils" endnote to determine the meaning of these columns. Spot symbols are footnoted at the end of the table.

Map symbol and map unit name	Component	Hydric	Local landform	Hydric soils criteria			
				Hydric criteria code	Meets saturation criteria	Meets flooding criteria	Meets ponding criteria

FOOTNOTE: There may be small areas of included soils or miscellaneous areas that are significant to use and management of the soil; yet are too small to delineate on the soil map at the map's original scale. These may be designated as spot symbols and are defined in the published Soil Survey Report or the USDA-NRCS Technical Guide, Part II.

Areas mapped as water or any map unit that contains one of the following conventional symbols is considered a hydric soil map unit: marshes or swamps; wet spots; depressions; streams, lakes and ponds.

1. All Histosols except Folists, or
2. Soils in Aquic suborders, great groups, or subgroups, Albolls suborder, Aquisalids, Pachic subgroups, or Cumulic subgroups that are:
 - a. Somewhat poorly drained with a water table equal to 0.0 foot (ft) from the surface during the growing season, or
 - b. poorly drained or very poorly drained and have either:
 - (1) water table equal to 0.0 ft during the growing season if textures are coarse sand, sand, or fine sand in all layers within 20 inches (in), or for other soils
 - (2) water table at less than or equal to 0.5 ft from the surface during the growing season if permeability is equal to or greater than 6.0 in/hour (h) in all layers within 20 in, or
 - (3) water table at less than or equal to 1.0 ft from the surface during the growing season if permeability is less than 6.0 in/h in any layer within 20 in, or
3. Soils that are frequently ponded for long duration or very long duration during the growing season, or
4. Soils that are frequently flooded for long duration or very long duration during the growing season.