

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Limitations affecting construction of haul roads and log landings		Suitability for log landings		Soil rutting hazard	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Bp: Bestpitch-----	75	Severe Flooding Strength Wetness	1.00 1.00 1.00	Poorly suited Flooding Strength Wetness	1.00 1.00 1.00	Severe Wetness Strength	1.00 1.00
Ca: Carmichael-----	35	Moderate Strength	0.50	Poorly suited Wetness Strength	1.00 0.50	Severe Strength	1.00
Carmichael-----	30	Moderate Strength	0.50	Poorly suited Wetness Strength	1.00 0.50	Severe Strength	1.00
Co: Corsica-----	50	Moderate Strength	0.50	Poorly suited Wetness Strength	1.00 0.50	Severe Strength	1.00
Corsica-----	20	Moderate Strength	0.50	Poorly suited Wetness Strength	1.00 0.50	Severe Strength	1.00
DhC: Downer-----	35	Slight		Moderately suited Slope	0.50	Moderate Strength	0.50
Hammonton-----	35	Slight		Moderately suited Slope	0.50	Moderate Strength	0.50
DoB: Downer-----	60	Slight		Well suited		Moderate Strength	0.50
DOE: Downer-----	50	Moderate Slope Sandiness	0.50 0.50	Poorly suited Slope	1.00	Moderate Strength	0.50
DUD: Downer-----	40	Slight		Poorly suited Slope	1.00	Moderate Strength	0.50
Unicorn-----	40	Moderate Strength	0.50	Poorly suited Slope Strength	1.00 0.50	Severe Strength	1.00

Table FOR-1.--Forestland Management--Continued

Map symbol and soil name	Pct. of map unit	Limitations affecting construction of haul roads and log landings		Suitability for log landings		Soil rutting hazard	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Fg: Fallsington-----	35	Moderate Strength	0.50	Poorly suited Wetness Strength	1.00 0.50	Severe Strength	1.00
Fallsington-----	20	Moderate Strength	0.50	Poorly suited Wetness Strength	1.00 0.50	Severe Strength	1.00
FmA: Fort Mott-----	60	Slight		Well suited		Moderate Strength	0.50
FmB: Fort Mott-----	60	Slight		Well suited		Moderate Strength	0.50
GfB: Galestown-----	40	Moderate Sandiness	0.50	Moderately suited Sandiness	0.50	Moderate Strength	0.50
Fort Mott-----	30	Slight		Well suited		Moderate Strength	0.50
GfC: Galestown-----	40	Moderate Sandiness	0.50	Moderately suited Sandiness Slope	0.50 0.50	Moderate Strength	0.50
Fort Mott-----	30	Slight		Moderately suited Slope	0.50	Moderate Strength	0.50
GrA: Greenwich-----	60	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
HnA: Hammonton-----	55	Slight		Well suited		Moderate Strength	0.50
HnB: Hammonton-----	65	Slight		Well suited		Moderate Strength	0.50
Ho: Honga-----	100	Severe Flooding Strength Wetness	1.00 1.00 1.00	Poorly suited Flooding Strength Wetness	1.00 1.00 1.00	Severe Wetness Strength	1.00 1.00
Hr: Hurlock-----	35	Slight		Poorly suited Wetness	1.00	Moderate Strength	0.50
Hurlock-----	30	Slight		Poorly suited Wetness	1.00	Moderate Strength	0.50

Table FOR-1.--Forestland Management--Continued

Map symbol and soil name	Pct. of map unit	Limitations affecting construction of haul roads and log landings		Suitability for log landings		Soil rutting hazard	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
IgA: Ingleside-----	65	Slight		Well suited		Moderate Strength	0.50
IgB: Ingleside-----	60	Slight		Well suited		Moderate Strength	0.50
IgC: Ingleside-----	55	Slight		Moderately suited Slope	0.50	Moderate Strength	0.50
Kn: Kentuck-----	50	Moderate Strength	0.50	Poorly suited Wetness Strength	1.00 0.50	Severe Strength	1.00
Lo: Longmarsh-----	65	Severe Flooding Strength	1.00 0.50	Poorly suited Flooding Wetness Strength	1.00 1.00 0.50	Severe Strength	1.00
LZ: Longmarsh-----	30	Severe Flooding Strength	1.00 0.50	Poorly suited Flooding Wetness Strength	1.00 1.00 0.50	Severe Strength	1.00
Zekiah-----	30	Severe Flooding Strength	1.00 0.50	Poorly suited Flooding Wetness Strength	1.00 1.00 0.50	Severe Strength	1.00
M-W: Water-----	100	Not rated		Not rated		Not rated	
MkA: Matapeake-----	80	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
MkB: Matapeake-----	70	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
MkC: Matapeake-----	70	Moderate Strength	0.50	Moderately suited Strength Slope	0.50 0.50	Severe Strength	1.00
MtA: Mattapex-----	45	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
Butlertown-----	30	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00

Table FOR-1.--Forestland Management--Continued

Map symbol and soil name	Pct. of map unit	Limitations affecting construction of haul roads and log landings		Suitability for log landings		Soil rutting hazard	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
MtB: Mattapex-----	45	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
Butlertown-----	30	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
MtC: Mattapex-----	70	Moderate Strength	0.50	Moderately suited Strength Slope	0.50 0.50	Severe Strength	1.00
NsA: Nassawango-----	65	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
NsB: Nassawango-----	70	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
Ot: Othello-----	35	Moderate Strength	0.50	Poorly suited Wetness Strength	1.00 0.50	Severe Strength	1.00
Othello-----	25	Moderate Strength	0.50	Poorly suited Wetness Strength	1.00 0.50	Severe Strength	1.00
PiA: Pineyneck-----	50	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
PiB: Pineyneck-----	50	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
PiC: Pineyneck-----	50	Moderate Strength	0.50	Moderately suited Strength Slope	0.50 0.50	Severe Strength	1.00
Pk: Puckum-----	65	Severe Flooding Strength Wetness	1.00 1.00 1.00	Poorly suited Flooding Strength Wetness	1.00 1.00 1.00	Severe Wetness Strength	1.00 1.00 1.00
UbB: Udorthents-----	85	Not rated		Not rated		Not rated	
UdB: Udorthents-----	45	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00

Table FOR-1.--Forestland Management--Continued

Map symbol and soil name	Pct. of map unit	Limitations affecting construction of haul roads and log landings		Suitability for log landings		Soil rutting hazard	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
U1B: Udorthents, Landfill	80	Not rated		Not rated		Not rated	
UoA: Unicorn-----	65	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
UoB: Unicorn-----	55	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
Ur: Urban Land-----	80	Not rated		Not rated		Not rated	
UsA: Unicorn-----	45	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
Sassafras-----	25	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
UsB: Unicorn-----	35	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
Sassafras-----	30	Moderate Strength	0.50	Moderately suited Strength	0.50	Severe Strength	1.00
UsC: Unicorn-----	40	Moderate Strength	0.50	Moderately suited Strength Slope	0.50 0.50	Severe Strength	1.00
Sassafras-----	25	Moderate Strength	0.50	Moderately suited Strength Slope	0.50 0.50	Severe Strength	1.00
W: Water-----	100	Not rated		Not rated		Not rated	
Wh: Whitemarsh-----	30	Moderate Strength	0.50	Poorly suited Wetness Strength	1.00 0.50	Severe Strength	1.00

