

WATER MANAGEMENT
Comanche County, Kansas

The soils of the survey area are rated in the Water Management table according to limitations that affect their suitability for water management. Soils are rated for pond reservoir areas, drainage, irrigation, terraces and diversions, and grassed waterways. Restrictive features that affect each soil for the specified use is also provided in the table.

The ratings in the table are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. Not limited indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. Slightly limited indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. Moderately limited indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. Limited indicates that the soil has one or more features that are significant limitations for the specified use. The limitations can be overcome, but generally require special design, soil reclamation, or installation procedures that may result in additional expense. Fair performance and moderate to high maintenance can be expected. Very limited indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Limitation class terms, such as very limited or limited, etc., limitation ratings, and numerical ratings are shown for each soil feature listed. As many as three soil features may be listed for each soil component if applicable. The overall limitation rating for the soil component is based on the most severe limitation.

Pond reservoir areas hold water behind a dam or embankment. Soils best suited to this use have low seepage potential in the upper 60 inches. The seepage potential is determined by the permeability of the soil and the depth to fractured bedrock or other permeable material. Excessive slope can affect the storage capacity of the reservoir area.

Embankments, dikes, and levees are raised structures of soil material, generally less than 20 feet high, constructed to impound water or to protect land against overflow. In this table, the soils are rated as a source of material for embankment fill. The ratings apply to the soil material below the surface layer to a depth of about 5 feet. It is assumed that soil layers will be uniformly mixed and compacted during construction.

The ratings do not indicate the ability of the natural soil to support an embankment. Soil properties to a depth even greater than the height of the embankment can affect performance and safety of the embankment. Generally, deeper onsite investigation is needed to determine these properties.

Soil material in embankments must be resistant to seepage, piping, and erosion and have favorable compaction characteristics. Unfavorable features include less than 5 feet of suitable material and a high content of stones or boulders, organic matter, or salts or sodium. A high water table affects the amount of usable material. It also affects traffic ability.

Aquifer-fed excavated ponds are pits or dugouts that extend to a ground-water aquifer or to a depth below a permanent water table. Excluded are ponds that are fed only by surface runoff and embankment ponds that impound water 3 feet or more above the original surface. Excavated ponds are affected by depth to a permanent water table, permeability of the aquifer, and quality of the water as inferred from the salinity of the soil. Depth to bedrock and the content of large stones affect the ease of excavation.

Drainage is the removal of excess surface and subsurface water from the soil. How easily and effectively the soil is drained depends on the depth to bedrock, to a cemented pan, or to other layers that affect the rate of water movement; permeability; depth to a high water table or depth of standing water if the soil is subject to ponding; slope; susceptibility to flooding; subsidence of organic layers; and the potential for frost action. Excavating and grading and the stability of ditch banks are affected by depth to bedrock or to a cemented pan, large stones, slope, and the hazard of cutbanks caving. The productivity of the soil after drainage is adversely affected by extreme acidity or by toxic substances in the root zone, such as salts, sodium, and sulfur. Availability of drainage outlets is not considered in the ratings.

Irrigation is the controlled application of water to supplement rainfall and support plant growth. The design and management of an irrigation system are affected by depth to the water table, the need for drainage, flooding, available water capacity, intake rate, permeability, erosion hazard, and slope. The construction of a system is affected by large stones and depth to bedrock or to a cemented pan. The performance of a system is affected by the depth of the root zone, the amount of salts or sodium, and soil reaction.

Terraces and diversions are embankments or a combination of channels and ridges constructed across a slope to control erosion and conserve moisture by intercepting runoff. Slope, wetness, large stones, and depth to bedrock or to a cemented pan affect the construction of terraces and diversions. A restricted rooting depth, a very limited hazard of wind erosion or water erosion, an excessively coarse texture, and restricted permeability adversely affect maintenance.

Grassed waterways are natural or constructed channels, generally broad and shallow, which conduct surface water to outlets at a non-erosive velocity. Large stones, wetness, slope, and depth to bedrock or to a cemented pan affect the construction of grassed waterways. A hazard of wind erosion, low available water capacity, restricted rooting depth, toxic substances such as salts and sodium, and restricted permeability adversely affect the growth and maintenance of the grass after construction.

WATER MANAGEMENT--Continued
Comanche County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
007BB: Blanket-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
007BC: Blanket-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
007GB: Grant-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
007PA: Pond Creek-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
007PD: Pond Creek-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
025CS: Carey-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
025CY: Carey-----	Limitation: deep to water	Limitation: slope	Limitation: erodes easily	Limitation: erodes easily
025MS: Missler-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
025RF: Roxbury-----	Limitation: deep to water	Limitation: flooding	Limitation: erodes easily	Limitation: erodes easily
025SH: Shellabarger----	Limitation: deep to water	Limitation: slope	Limitation: too sandy	Favorable
097HB: Harney-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
097LH: Lancaster-----	Limitation: deep to water	Limitation: slope thin layer	Limitation: area reclaim slope	Limitation: area reclaim slope
Hedville-----	Limitation: deep to water	Limitation: slope thin layer soil blowing	Limitation: area reclaim slope depth to rock	Limitation: area reclaim slope depth to rock
Ab: Abilene-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
Ac: Abilene-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
AED: Arents, Earthen Dam-----	---	---	---	---
An: Albion-----	Limitation: deep to water	Limitation: soil blowing droughty	Limitation: too sandy soil blowing	Limitation: droughty
As: Albion-----	Limitation: deep to water	Limitation: slope soil blowing droughty	Limitation: slope too sandy soil blowing	Limitation: slope droughty
Shellabarger----	Limitation: deep to water	Limitation: slope soil blowing	Limitation: slope soil blowing	Limitation: slope
Bt: Buttermilk-----	Limitation: deep to water	Limitation: excess salt	Limitation: erodes easily	Limitation: erodes easily excess salt
Ca: Canadian-----	Limitation: deep to water	Limitation: soil blowing droughty	Limitation: soil blowing	Limitation: droughty
Cc: Carey-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
Cd: Carey-----	Limitation: deep to water	Limitation: erodes easily slope	Limitation: erodes easily	Limitation: erodes easily
Ch: Case-----	Limitation: deep to water	Favorable	Favorable	Favorable
Ck: Case-----	Limitation: deep to water	Limitation: slope	Favorable	Favorable

WATER MANAGEMENT--Continued
Comanche County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
Cm: Case-----	Limitation: deep to water	Limitation: slope	Limitation: slope	Limitation: slope
Co: Clairemont-----	Limitation: deep to water	Limitation: erodes easily flooding	Limitation: erodes easily	Limitation: erodes easily
Cp: Clairemont-----	Limitation: deep to water	Limitation: erodes easily flooding	Limitation: erodes easily	Limitation: erodes easily
Cr: Clark-----	Limitation: deep to water	Favorable	Favorable	Favorable
Cs: Clark-----	Limitation: deep to water	Favorable	Favorable	Favorable
Ct: Clark-----	Limitation: deep to water	Limitation: slope	Favorable	Favorable
Cw: Clark-----	Limitation: deep to water	Limitation: slope	Limitation: slope	Limitation: slope
Kingsdown-----	Limitation: deep to water	Limitation: soil blowing	Limitation: soil blowing	Favorable
Dc: Dale-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
Ed: Elandco-----	Limitation: deep to water	Limitation: erodes easily flooding	Limitation: erodes easily	Limitation: erodes easily
Ef: Elandco-----	Limitation: deep to water	Limitation: erodes easily flooding	Limitation: erodes easily	Limitation: erodes easily
Fe: Farnum-----	Limitation: deep to water	Favorable	Favorable	Favorable
Ff: Farnum-----	Limitation: deep to water	Favorable	Favorable	Favorable
He: Hedville-----	Limitation: deep to water	Limitation: slope soil blowing depth to rock	Limitation: slope soil blowing depth to rock	Limitation: slope depth to rock
Rock Outcrop----	---	---	---	---
Hr: Holdrege-----	Limitation: deep to water	Favorable	Limitation: erodes easily	Limitation: erodes easily
Kc: Kanza-----	Limitation: flooding cutbanks cave	Limitation: fast intake wetness droughty	Limitation: too sandy wetness soil blowing	Limitation: wetness droughty
Kf: Kaski-----	Limitation: deep to water	Favorable	Favorable	Favorable
Kn: Kingsdown-----	Limitation: deep to water	Limitation: soil blowing	Limitation: soil blowing	Favorable
Ko: Kingsdown-----	Limitation: deep to water	Limitation: slope soil blowing	Limitation: soil blowing	Favorable
Kr: Krier-----	Limitation: excess salt flooding cutbanks cave	Limitation: flooding wetness droughty	Limitation: too sandy wetness	Limitation: excess sodium excess salt wetness
Ld: Lancaster-----	Limitation: deep to water	Limitation: slope soil blowing depth to rock	Limitation: soil blowing depth to rock	Limitation: depth to rock
Hedville-----	Limitation: deep to water	Limitation: slope soil blowing depth to rock	Limitation: slope soil blowing depth to rock	Limitation: slope depth to rock
Le: Lesho-----	Limitation: flooding cutbanks cave	Limitation: flooding wetness	Limitation: too sandy wetness	Favorable

WATER MANAGEMENT--Continued
Comanche County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
Ln: Lincoln-----	Limitation: deep to water	Limitation: fast intake soil blowing droughty	Limitation: too sandy soil blowing	Limitation: droughty
Lo: Lincoln-----	Limitation: deep to water	Limitation: flooding soil blowing droughty	Limitation: too sandy soil blowing	Limitation: droughty
Lr: Lincoln-----	Limitation: deep to water	Limitation: fast intake soil blowing droughty	Limitation: too sandy soil blowing	Limitation: droughty
Krier-----	Limitation: excess salt flooding cutbanks cave	Limitation: flooding wetness droughty	Limitation: too sandy wetness	Limitation: excess sodium excess salt wetness
M-W:	---	---	---	---
Oa: Obaro-----	Limitation: deep to water	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock
Ob: Obaro-----	Limitation: deep to water	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock
Rock Outcrop----	---	---	---	---
Oc: Ost-----	Limitation: deep to water	Limitation: slope	Favorable	Favorable
Ph: Port-----	Limitation: deep to water	Limitation: erodes easily flooding	Limitation: erodes easily	Limitation: erodes easily
Po: Pratt-----	Limitation: deep to water	Limitation: fast intake slope droughty	Limitation: too sandy soil blowing	Limitation: droughty
Pr: Pratt-----	Limitation: deep to water	Limitation: fast intake slope droughty	Limitation: too sandy soil blowing	Limitation: droughty
Pt: Pratt-----	Limitation: deep to water	Limitation: fast intake slope droughty	Limitation: slope too sandy soil blowing	Limitation: slope droughty
Tivoli-----	Limitation: deep to water	Limitation: fast intake slope droughty	Limitation: slope too sandy soil blowing	Limitation: slope droughty
Qr: Quinlan-----	Limitation: deep to water	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock
Woodward-----	Limitation: deep to water	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock
Qt: Quinlan-----	Limitation: deep to water	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock
Woodward-----	Limitation: deep to water	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock	Limitation: erodes easily slope depth to rock
Sb: St. Paul-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
Sc: St. Paul-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
Sg: Shellabarger----	Limitation: deep to water	Limitation: soil blowing	Limitation: soil blowing	Favorable

WATER MANAGEMENT--Continued
Comanche County, Kansas

(The information in this report indicates the dominant soil condition but does not eliminate the need for onsite investigation)

Map symbol and soil name	Features affecting--			
	Drainage	Irrigation	Terraces and diversions	Grassed waterways
Sh: Shellabarger----	Limitation: deep to water	Limitation: soil blowing	Limitation: soil blowing	Favorable
Sm: Shellabarger----	Limitation: deep to water	Limitation: slope soil blowing	Limitation: soil blowing	Favorable
Tv: Tivoli-----	Limitation: deep to water	Limitation: fast intake slope droughty	Limitation: slope too sandy soil blowing	Limitation: slope droughty
W: Water-----	---	---	---	---
Wd: Waldeck-----	Limitation: flooding	Limitation: flooding wetness soil blowing	Limitation: wetness soil blowing	Favorable
We: Westview-----	Limitation: deep to water	Limitation: erodes easily	Limitation: erodes easily	Limitation: erodes easily
Wf: Wellsford-----	Limitation: deep to water	Limitation: percs slowly slope slow intake	Limitation: percs slowly slope depth to rock	Limitation: percs slowly slope depth to rock
Wo: Woodward-----	Limitation: deep to water	Limitation: erodes easily depth to rock	Limitation: erodes easily depth to rock	Limitation: erodes easily depth to rock
Ws: Woodward-----	Limitation: deep to water	Limitation: erodes easily slope depth to rock	Limitation: erodes easily depth to rock	Limitation: erodes easily depth to rock
Quinlan-----	Limitation: deep to water	Limitation: erodes easily slope depth to rock	Limitation: erodes easily depth to rock	Limitation: erodes easily depth to rock
Ye: Yahola-----	Limitation: deep to water	Limitation: flooding soil blowing	Limitation: soil blowing	Favorable
Ze: Zenda-----	Limitation: flooding	Limitation: flooding wetness	Limitation: wetness	Favorable

WATER MANAGEMENT--Continued
Comanche County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
007BB: Blanket-----	100	Somewhat limited Seepage	0.70	Not limited		Very limited Deep to water	1.00
007BC: Blanket-----	100	Somewhat limited Seepage	0.70	Not limited		Very limited Deep to water	1.00
007GB: Grant-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.96	Very limited Deep to water	1.00
007PA: Pond Creek-----	100	Somewhat limited Seepage	0.05	Somewhat limited Piping	0.70	Very limited Deep to water	1.00
007PD: Pond Creek-----	100	Somewhat limited Seepage	0.05	Somewhat limited Piping	0.70	Very limited Deep to water	1.00
025CS: Carey-----	100	Somewhat limited Seepage Depth to bedrock	0.70 0.00	Somewhat limited Piping Thin layer	0.97 0.02	Very limited Deep to water	1.00
025CY: Carey-----	100	Somewhat limited Seepage Depth to bedrock	0.70 0.00	Somewhat limited Piping Thin layer	0.97 0.02	Very limited Deep to water	1.00
025MS: Missler-----	100	Somewhat limited Seepage	0.05	Not limited		Very limited Deep to water	1.00
025RF: Roxbury-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.60	Very limited Deep to water	1.00
025SH: Shellabarger-----	100	Somewhat limited Seepage	0.70	Somewhat limited Seepage	0.09	Very limited Deep to water	1.00
097HB: Harney-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.04	Very limited Deep to water	1.00
097LH: Lancaster-----	65	Somewhat limited Seepage Depth to bedrock	0.70 0.34	Very limited Piping Thin layer	1.00 0.99	Very limited Deep to water	1.00
Hedville-----	35	Very limited Seepage Depth to bedrock Slope	1.00 1.00 0.00	Very limited Thin layer Seepage	1.00 0.08	Very limited Deep to water	1.00
Ab: Abilene-----	100	Somewhat limited Seepage	0.05	Not limited		Very limited Deep to water	1.00
Ac: Abilene-----	100	Somewhat limited Seepage	0.05	Not limited		Very limited Deep to water	1.00
AED: Arents, Earthen Dam-	100	Not rated		Not rated		Not rated	
An: Albion-----	100	Very limited Seepage	1.00	Somewhat limited Seepage	0.98	Very limited Deep to water	1.00
As: Albion-----	65	Very limited Seepage	1.00	Somewhat limited Seepage	0.98	Very limited Deep to water	1.00
Shellabarger-----	35	Somewhat limited Seepage	0.70	Somewhat limited Seepage	0.09	Very limited Deep to water	1.00

WATER MANAGEMENT--Continued
Comanche County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer-fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Bt: Buttermilk-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping Salinity	0.44 0.12	Very limited Deep to water	1.00
Ca: Canadian-----	100	Very limited Seepage	1.00	Very limited Piping Seepage	1.00 0.07	Very limited Deep to water	1.00
Cc: Carey-----	100	Somewhat limited Seepage Depth to bedrock	0.70 0.00	Somewhat limited Piping Thin layer	0.95 0.02	Very limited Deep to water	1.00
Cd: Carey-----	100	Somewhat limited Seepage Depth to bedrock	0.70 0.00	Somewhat limited Piping Thin layer	0.95 0.02	Very limited Deep to water	1.00
Ch: Case-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.12	Very limited Deep to water	1.00
Ck: Case-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.12	Very limited Deep to water	1.00
Cm: Case-----	100	Somewhat limited Seepage Slope	0.70 0.00	Somewhat limited Piping	0.12	Very limited Deep to water	1.00
Co: Clairemont-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.93	Very limited Deep to water	1.00
Cp: Clairemont-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.93	Very limited Deep to water	1.00
Cr: Clark-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.12	Very limited Deep to water	1.00
Cs: Clark-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.12	Very limited Deep to water	1.00
Ct: Clark-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.12	Very limited Deep to water	1.00
Cw: Clark-----	55	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.12	Very limited Deep to water	1.00
Kingsdown-----	45	Very limited Seepage	1.00	Somewhat limited Seepage	0.09	Very limited Deep to water	1.00
Dc: Dale-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.82	Very limited Deep to water	1.00
Ed: Elandco-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.76	Very limited Deep to water	1.00
Ef: Elandco-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.76	Very limited Deep to water	1.00
Fe: Farnum-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.25	Very limited Deep to water	1.00
Ff: Farnum-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.25	Very limited Deep to water	1.00

WATER MANAGEMENT--Continued
Comanche County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer- fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
He: Hedville-----	70	Very limited Seepage Depth to bedrock Slope	1.00 1.00 0.10	Very limited Thin layer Seepage	1.00 0.08	Very limited Deep to water	1.00
Rock Outcrop-----	30	Not rated		Not rated		Not rated	
Hr: Holdrege-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.58	Very limited Deep to water	1.00
Kc: Kanza-----	100	Very limited Seepage	1.00	Very limited Depth to saturated zone Seepage	1.00 0.96	Very limited Cutbanks cave	1.00
Kf: Kaski-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.82	Very limited Deep to water	1.00
Kn: Kingsdown-----	100	Very limited Seepage	1.00	Somewhat limited Seepage	0.09	Very limited Deep to water	1.00
Ko: Kingsdown-----	100	Very limited Seepage	1.00	Somewhat limited Seepage	0.09	Very limited Deep to water	1.00
Kr: Krier-----	100	Very limited Seepage	1.00	Very limited Seepage Depth to saturated zone Salinity	1.00 1.00 0.12	Very limited Cutbanks cave Salty water Deep to water	1.00 0.50 0.00
Ld: Lancaster-----	65	Somewhat limited Seepage Depth to bedrock	0.70 0.09	Somewhat limited Piping Thin layer Seepage	1.00 0.83 0.09	Very limited Deep to water	1.00
Hedville-----	35	Very limited Seepage Depth to bedrock	1.00 1.00	Very limited Thin layer Seepage	1.00 0.08	Very limited Deep to water	1.00
Le: Lesho-----	100	Very limited Seepage	1.00	Somewhat limited Seepage Depth to saturated zone	1.00 0.43	Very limited Cutbanks cave Deep to water	1.00 0.25
Ln: Lincoln-----	100	Very limited Seepage	1.00	Somewhat limited Seepage	0.89	Very limited Deep to water	1.00
Lo: Lincoln-----	100	Very limited Seepage	1.00	Somewhat limited Seepage	0.89	Very limited Deep to water	1.00
Lr: Lincoln-----	55	Very limited Seepage	1.00	Somewhat limited Seepage	0.56	Very limited Deep to water	1.00
Krier-----	45	Very limited Seepage	1.00	Very limited Seepage Depth to saturated zone Salinity	1.00 1.00 0.12	Very limited Cutbanks cave Salty water Deep to water	1.00 0.01 0.00
Oa: Obaro-----	100	Somewhat limited Seepage Depth to bedrock	0.70 0.04	Somewhat limited Piping Thin layer	0.76 0.70	Very limited Deep to water	1.00
Ob: Obaro-----	75	Somewhat limited		Somewhat limited		Very limited	

WATER MANAGEMENT--Continued
Comanche County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer-fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Rock Outcrop-----	25	Seepage Depth to bedrock Slope Not rated	0.70 0.04 0.02	Piping Thin layer Not rated	0.76 0.70	Deep to water Not rated	1.00
Oc: Ost-----	100	Somewhat limited Seepage	0.05	Very limited Piping	1.00	Very limited Deep to water	1.00
Ph: Port-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.68	Very limited Deep to water	1.00
Po: Pratt-----	100	Very limited Seepage	1.00	Somewhat limited Seepage	0.57	Very limited Deep to water	1.00
Pr: Pratt-----	100	Very limited Seepage	1.00	Somewhat limited Seepage	0.57	Very limited Deep to water	1.00
Pt: Pratt-----	75	Very limited Seepage	1.00	Somewhat limited Seepage	0.57	Very limited Deep to water	1.00
Tivoli-----	25	Very limited Seepage Slope	1.00 0.12	Somewhat limited Seepage	0.99	Very limited Deep to water	1.00
Or: Quinlan-----	55	Very limited Seepage Depth to bedrock Slope	1.00 0.69 0.00	Very limited Thin layer Piping	1.00 1.00	Very limited Deep to water	1.00
Woodward-----	45	Somewhat limited Seepage Depth to bedrock Slope	0.70 0.11 0.00	Very limited Piping Thin layer	1.00 0.86	Very limited Deep to water	1.00
Qt: Quinlan-----	55	Very limited Seepage Depth to bedrock Slope	1.00 0.69 0.21	Very limited Thin layer Piping	1.00 1.00	Very limited Deep to water	1.00
Woodward-----	45	Somewhat limited Seepage Depth to bedrock Slope	0.70 0.11 0.08	Very limited Piping Thin layer	1.00 0.86	Very limited Deep to water	1.00
Sb: St. Paul-----	100	Somewhat limited Seepage	0.57	Somewhat limited Piping	0.55	Very limited Deep to water	1.00
Sc: St. Paul-----	100	Somewhat limited Seepage	0.57	Somewhat limited Piping	0.55	Very limited Deep to water	1.00
Sg: Shellabarger-----	100	Somewhat limited Seepage	0.70	Somewhat limited Seepage	0.09	Very limited Deep to water	1.00
Sh: Shellabarger-----	100	Somewhat limited Seepage	0.70	Somewhat limited Seepage	0.09	Very limited Deep to water	1.00
Sm: Shellabarger-----	100	Somewhat limited Seepage	0.70	Somewhat limited Seepage	0.09	Very limited Deep to water	1.00
Tv: Tivoli-----	100	Very limited Seepage Slope	1.00 0.12	Somewhat limited Seepage	0.99	Very limited Deep to water	1.00

WATER MANAGEMENT--Continued
Comanche County, Kansas

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct of map unit	Pond Reservoir Area		Embankments, Dikes, and Levees		Excavated Ponds (Aquifer-fed)	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
W: Water-----	100	Not rated		Not rated		Not rated	
Wd: Waldeck-----	100	Very limited Seepage	1.00	Very limited Seepage Depth to saturated zone	1.00 0.43	Very limited Cutbanks cave Deep to water	1.00 0.25
We: Westview-----	100	Somewhat limited Seepage	0.70	Somewhat limited Piping	0.48	Very limited Deep to water	1.00
Wf: Wellsford-----	100	Very limited Seepage Depth to bedrock Slope	1.00 0.58 0.04	Very limited Thin layer Hard to pack	1.00 0.50	Very limited Deep to water	1.00
Wo: Woodward-----	100	Somewhat limited Seepage Depth to bedrock	0.70 0.11	Very limited Piping Thin layer	1.00 0.85	Very limited Deep to water	1.00
Ws: Woodward-----	65	Somewhat limited Seepage Depth to bedrock	0.70 0.11	Very limited Piping Thin layer	1.00 0.86	Very limited Deep to water	1.00
Quinlan-----	35	Very limited Seepage Depth to bedrock	1.00 0.69	Very limited Thin layer Piping	1.00 1.00	Very limited Deep to water	1.00
Ye: Yahola-----	100	Very limited Seepage	1.00	Very limited Piping Seepage	1.00 0.07	Very limited Deep to water	1.00
Ze: Zenda-----	100	Somewhat limited Seepage	0.70	Somewhat limited Depth to saturated zone Piping	0.43 0.14	Somewhat limited Slow refill Deep to water Cutbanks cave	0.30 0.25 0.10