

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD**

**IRRIGATION WATER CONVEYANCE
GALVANIZED STEEL DITCH AND CANAL LINING
(Ft.)**

CODE 428C

DEFINITION

A fixed lining of impervious material installed in an existing or newly constructed irrigation field ditch or irrigation canal or lateral.

PURPOSE

To prevent waterlogging of land, to maintain water quality, to prevent erosion, and to reduce water losses.

CONDITIONS WHERE PRACTICE APPLIES

This standard applies to linings made of galvanized steel installed in a preformed ditch or canal section.

Linings to which this standard apply are restricted to ditches having characteristics as follows:

Bottom width	Not to exceed 30 inches
Velocity	Not to exceed 15 ft/s

This standard applies to both the ditch and the steel lining. Ditches and canals to be lined shall serve as integral parts of an irrigation water distribution or conveyance system designed to facilitate the conservation use of soil and water resources on a farm or group of farms.

CRITERIA

General Criteria Applicable to All Purposes

This practice shall conform to all federal, state, and local laws, rules, and regulations. Laws, rules, and regulations of particular concern include those involving water rights, land use, pollution control, property easements, wetlands, preservation of cultural resources, and

endangered species.

The water supply, water quality, and rate of irrigation delivery for the area served by the pipeline shall be sufficient to make irrigation practical for the crops to be grown and the irrigation water application methods to be used.

Lined ditches and canals shall either be located where they will not be susceptible to damage from side drainage flooding or be protected from such damage.

Steel linings shall not be installed in areas high in salt or other chemical concentrations injurious to galvanized steel unless the liners are protected with coatings or anodic protection specifically designed to protect the liner from these chemicals.

Capacity. A lined ditch or canal shall have enough capacity to meet its requirement as part of the planned irrigation water distribution or conveyance system without danger of overtopping. Design capacity shall be based upon the following, whichever is greater:

1. The capacity shall be adequate to deliver the volume of water required to meet the peak consumptive use of the crops.
2. The capacity shall be large enough to provide an adequate irrigation stream for all methods of irrigation planned.

For design purposes, the carrying capacity of steel-lined ditches and canals shall be considered to be equal to the capacity as computed by Manning's Formula, using a coefficient of roughness n of not less than 0.013.

Velocity. A design velocity in excess of 1.7 times the critical velocity shall be restricted to straight reaches that discharge into a section or structure designed to reduce the velocity to less than the critical velocity. The maximum velocity in these straight reaches shall be 15 ft/s.

Freeboard. The required freeboard varies with the size of the ditch or canal, the velocity of the water, the horizontal and vertical alignment, the amount of storm or waste water that may be intercepted, and the change in the water surface elevation that may occur when any control structure is operating. The minimum freeboard for any lined ditch or canal shall be 3 inches.

If the velocity is within ± 30 percent of critical, the freeboard shall be at least 6 inches. The minimum freeboard requirement is based on the assumption that the finished channel bottom elevations will vary no more than 0.1 foot from the design elevations. Construction deviations greater than 0.2 foot shall not be permitted. If a construction deviation greater than 0.1 foot is permitted, the minimum freeboard shall be increased an additional 3 inches.

Additional freeboard shall be provided as required by slope, velocity, depth of flow, alignment, obstructions, curves, and other site conditions.

Water surface elevations. All lined ditches and canals shall be designed so that the water surface elevations at field takeout points are high enough to provide the required flow onto the field surface. If ditch checks or other control structures are to provide the necessary head, the backwater effect must be considered in computing freeboard requirements. The required elevation of the water surface above the field surface varies according to the type of takeout or device used and the amount of water to be delivered. A minimum head of 4 inches shall be provided.

Ditch or canal pad or foundation. Ditch and canal banks shall be built up with earth to a height sufficient to support the full height of the lining and to provide an anchorage for the top

edge of the lining. In cut sections, other than in rock, a berm shall be constructed not less than 2 inches above the top of the lining.

Berms and ditch banks shall be wide enough to prevent excessive deposition in cut sections and to ensure support of the lining in fill sections. The minimum width shall be 1 foot. If the bank or berm is to be used as a roadway, the minimum top width shall be adequate for the purpose.

Outside bank slopes and slopes above the berm elevation in cut sections must be flat enough to ensure stability.

Related structures. Plans for ditch or canal lining installations shall provide for adequate inlets, outlets, turnouts, checks, crossings, and other related structures needed for successful conservation irrigation.

Structures shall be constructed or installed in such a way that the capacity or the freeboard of the ditch is not reduced and the effectiveness of the lining is not impaired.

All structures shall meet Natural Resources Conservation Service (NRCS) standards and specifications for the type of structure used.

Bulkheads, formed to fit the lining and of sufficient size to extend at least 12 inches into the earthen ditch pad for the entire width of the ditch lining, shall be installed at the beginning and end of the lining section and at intervening points, as needed, to provide adequate anchorage.

Materials. Galvanized lining material shall meet the requirements detailed in the specifications under "Materials."

PLANS AND SPECIFICATIONS

Plans and specifications for installing galvanized steel irrigation ditches and canal linings shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purposes.