

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD**

CLEARING AND SNAGGING

(Ft.)

CODE 326

DEFINITION

Removing snags, drifts, or other obstructions from a channel or drainage way.

PURPOSE

Reducing significant human and/or natural environmental risks by improving physical characteristics of a channel to:

- Restore flow capacity;
- Prevent bank erosion by eddies;
- Reduce the formation of bars; and/or
- Minimize blockages by debris and ice.

CONDITIONS WHERE PRACTICE APPLIES

Any channel or urban floodway where the removal of trees, brush, and other obstructions is needed to accomplish one or more of the listed purposes.

CRITERIA

Clearing and snagging shall not be completed on any channel where significant channel erosion will occur, major impairment to the landscape resource quality is likely, or significant impairment to habitat for fish and wildlife will occur, unless needed restoration actions are included with the application of this practice.

Utilities and Permits. The landowner shall be responsible for locating all buried utilities in the project area, including drainage tile and other structural measures.

The landowner shall obtain all necessary permissions from regulatory agencies, including the Illinois Department of Agriculture, US Army Corps of Engineers, US Environmental Protection Agency, Illinois Environmental Protection Agency and Illinois Department of Natural Resources – Office of Water Resources, or document that no permits are required.

Capacity. The capacity of the channel, both before and after improvement, shall be determined using Manning's Formula with applicable values of the retardance factor "n" from Supplement B to the National Engineering Handbook, Section 5 – Hydraulics, or similar source. The value of "n" used to determine channel capacity after improvement shall reflect the degree of natural changes and maintenance expected to occur in future years.

Location. The area to be cleared and snagged shall include the perimeter of the channel, the flow area of the urban floodway, or both. Trees on the bank that are leaning over or other objects that may fall into the channel shall also be included. If root balls are still attached to the streambank, cut off the log 6 to 12 inches above the ground and leave the stump and root mass for bank stability.

Stability. Clearing and snagging shall only be specified for other areas such as: berms, areas used for temporary disposal sites or travelways, or for other planned conservation uses where needed to implement this practice.

Clearing and snagging shall not impair channel stability. The criteria for determining channel stability shall comply with Conservation Practice Standard (582), Open Channel. The

NRCS, Illinois

April 2008

effect on downstream and upstream reaches due to the removal of obstructions shall be analyzed using appropriate stream and channel geomorphologic procedures.

If clearing and snagging will result in streambank erosion, criteria within Conservation Practice Standard (580), Streambank and Shoreline Protection will be used in conjunction with this standard.

Vegetation. All areas denuded and disturbed during snag removal shall be restored by planting native vegetation where practical. Disturbance of wetlands, riparian areas, and fish and wildlife habitat sites shall be minimized or avoided where possible. Cleared material shall be removed from the floodplain or deposited in approved areas that will not significantly affect the flow capacity of the stream.

CONSIDERATIONS

Ground-disturbing activities associated with this practice, including but not limited to areas of equipment/vehicle traffic in the channel and floodway and areas of vegetation removal, have the potential to adversely affect cultural resources.

Insure that threatened and endangered species and their habitat shall not be permanently adversely impacted by the use of this practice.

Effects on water quantity and quality should be considered.

Removal of deadfalls, stumps, and trees from streambanks and channels may increase discharge, velocity and channel capacity that could reduce flood damage from out of bank flow.

Improved flow conditions may lower the hydraulic gradient and drain flood plains more quickly. Rapid drawdown may cause sloughing of saturated, unstable streambanks.

Decreased groundwater recharge in water-losing streams may result from reduced residence time of water in the channel.

Temporary losses of aquatic or wetland habitat may occur with the removal of vegetation.

During implementation of the practice, there may be increased turbidity due to an increased sediment load. Water quality may be further degraded by chemical substances (i.e. organic nitrogen or phosphorus) attached to the sediment particles.

During construction, a heavy organic load may be produced resulting in a decreased availability of dissolved oxygen. Long-term effects may cause a decrease in yields of sediment and sediment-attached substances.

Increased surface water temperatures, at low flow, may occur from removal of shade-producing canopy until regrowth occurs. Accelerated flows may reduce the period of time water is exposed for "sun warming," thus reducing water temperature.

In streams carrying dissolved substances, a reduction in ground water recharge may contribute to improved aquifer quality.

The number of pools and riffles forming the channel bottom may be reduced and fish habitat could be adversely affected.

Measures and construction methods that enhance fish and wildlife values should be incorporated as needed and practical. Special attention should be given to landscape aesthetics, to protecting and maintaining key shade, food, and den trees, and to stabilization of disturbed areas.

Consider removal methods and the disposal location of cleared material that will not be used for bioengineering (removal from site, placement in or out of the floodplain, not placed in wetland areas, etc.), and implement according to permit conditions.

PLANS AND SPECIFICATIONS

Plans and specifications for clearing and snagging shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purpose(s).

Construction operations shall be carried out in a manner and sequence so that impacts on the environment will be minimized and held within acceptable limits.

All operations shall be carried out in a safe and skillful manner. Safety and health regulations shall be observed and appropriate safety measures used.

OPERATION AND MAINTENANCE

A maintenance program shall be established by the landowner/user to maintain channel capacity and vegetative cover. Items to consider are:

- Where applicable, control grazing in the construction area during vegetative establishment and when soil conditions are wet.
- Fertilize as needed to maintain a vigorous vegetative cover.
- Promptly repair eroded areas.
- Remove major silt and sediment accumulations in the channel cross-

section as soon as practical, when the effects are causing significant bank erosion problems.

- Re-establish vegetation cover immediately where scour erosion has removed established seeding.
- Keep inlets to side drainage structures and channels open and armor if necessary.
- Periodically inspect the area for signs of significant streambank undermining or instability.

REFERENCES

McConnel, C. 1983. Stream Obstruction Removal Guidelines. American Fisheries Society. Bethesda, MD.

NRCS National Engineering Handbook, Section 5, Hydraulics

NATURAL RESOURCES CONSERVATION SERVICE
ILLINOIS CONSTRUCTION SPECIFICATION
CLEARING AND SNAGGING

Scope

The work shall consist of removing trees, stumps, debris and other obstructions from the channel as required by the construction plans.

Location

The location of the clearing and snagging activity shall be as shown on the construction plans or as staked in the field.

Material to be Cleared

Down trees, logs, drifts, boulders, debris and other obstructions lying wholly or partly in the channel shall be removed. Piling, piers, headwalls, and sediment bars that obstruct the free flow of water shall be removed if so designated in the drawings.

Clearing and Snagging Methods

All trees, stumps, and brush to be removed within the perimeter of the channel shall be cut as close to the ground as the cutting tools permit. If trees on the bank that are leaning over are to be cleared, the tree is to be cut 6 to 12 inches from the ground, leaving the stump and root mass for bank stability. If other areas are to be cleared, the trees, brush, and other woody vegetation shall be cut within the maximum distance above the ground level specified.

Trees shall be felled in such a manner as to avoid damage to other trees, property, and objects outside the limits of clearing.

Selective snagging, where possible, shall be performed primarily with hand-operated equipment, water-based equipment, or small equipment used in a manner that will minimize soil, water, and other resource disturbances.

If herbicide treatment is planned, the stumps and brush in the specified area shall be treated at the time of clearing according to the recommendations of the manufacturer of the herbicide specified or being used.

The use of explosives in all clearing and snagging operations shall be in strict compliance with applicable state statutes and regulations.

Measures and construction methods that enhance fish and wildlife values shall be incorporated as needed and practical. Special attention shall be given to visual resources, protecting and maintaining key shade, food, and den trees and to stabilization of disturbed areas.

Disposal of Cleared Material

If channels are located in cultivated areas or in areas of high value land, trees, logs, and all combustible material resulting from the clearing and snagging operations shall be burned, buried, or piled in designated disposal areas as specified. All burning shall be performed outside the channel and shall conform to regulations of the Illinois Environmental Protection Agency. In other areas, such as woodland or rangeland, where burning is prohibited, material shall be disposed of in such a manner that it does not float away or reenter the channel.

Residue from burning and noncombustible material shall be buried outside the channel or placed in designated disposal areas. All buried material shall have an adequate earth cover to permit proper land use.

Vegetation

A protective cover of vegetation shall be established on all areas denuded and disturbed during snag removal when specified in the design plans. Refer to Construction Specification 342, Critical Area Seeding, for detailed seeding requirements.

Utilities

The landowner shall be responsible for locating all buried utilities in the project area, including drainage tile and other structural measures.