

NATURAL RESOURCES CONSERVATION SERVICE

CONSERVATION PRACTICE STANDARD

STRUCTURE FOR WATER CONTROL

(No.)

Code 587

DEFINITION

A structure in a water management system that conveys water, controls the direction or rate of flow, maintains a desired water surface elevation, or measures water.

PURPOSES

The practice may be applied as a management component of a water management system to control the stage, discharge, distribution, delivery, or direction of water flow.

CONDITIONS WHERE PRACTICE APPLIES

This practice applies wherever a permanent structure is needed as an integral part of a water control system to serve one or more of the following functions:

- To convey water from one elevation to a lower elevation within, to, or from a water conveyance system such as a ditch, channel, canal, or pipeline designed to operate under open channel conditions. Typical structures: drops, chutes, turnouts, surface water inlets, head gates, pump boxes, and stilling basins.
- To control the elevation of water in drainage or irrigation ditches. Typical structures: checks, flashboard risers, check dams.
- To control the division or measurement of irrigation water. Typical structures: division boxes and water measurement devices.
- To keep trash, debris, or weed seeds from entering pipelines. Typical structure: debris screen.
- To control the direction of channel flow resulting from tides, high water or backflow from flooding. Typical structures: tide and water management gates.
- To control water table level, remove surface or subsurface water from adjoining land, flood land for frost protection or manage water levels for wildlife or recreation. Typical structures: water level control structures, flashboard risers, pipe drop inlets, and box inlets.
- To convey water over, under, or along a ditch, canal, road, railroad, or other barriers. Typical structures: bridges, culverts, flumes, inverted siphons, and long span pipes.
- To modify water flow to provide habitat for fish, wildlife, and other aquatic animals. Typical structures: chutes, cold water release structures, and flashboard risers.
- To provide silt management in ditches or canals. Typical structure: sluice.
- To supplement a resource management system on land where organic waste or commercial fertilizer is applied.

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resources Conservation Service.

- To create, restore, or enhance wetland hydrology.

CRITERIA

General Criteria Applicable To All Purposes

All work shall be planned, designed, and constructed to comply with all Federal, State, and Local laws and regulations.

Structures shall complement an approved plan if soil, climate and site specific conditions permit. A protective cover of vegetation shall be established on all disturbed earth surfaces. If soil or climatic conditions preclude the use of vegetation and protection is needed, non-vegetative means, such as mulches or gravels shall be used unless temporary vegetation can be established.

The structure shall be fenced, if necessary, to protect vegetation. Vegetation shall be established in compliance with Natural Resources Conservation Service (NRCS) Field Office Technical Guide (FOTG) Standard (342) Critical Area Planting or NRCS FOTG Standard (580) Streambank and Shoreline Protection.

The water level upstream of water control structures shall not be raised on adjacent landowners without their written permission.

CONSIDERATIONS

When planning, designing, and installing this practice, the following items should be considered:

Effects on the water budget, especially on volumes and rates of runoff, infiltration, evaporation, transpiration, deep percolation, and ground water recharge.

Potential for a change in the rate of plant growth and transpiration because of changes in the volume of soil water.

Effects on downstream flows or aquifers that would affect other water uses or users.

Effects on the field water table to ensure that it will provide a suitable rooting depth for the anticipated crop.

Potential use for irrigation management to conserve water.

Effect of construction on aquatic life. Effects on stream system channel morphology and stability as it relates to erosion and the movement of sediment, solutes, and sediment-attached substances carried by runoff.

Effects on the movement of dissolved substances below the root zone and to ground water.

Effects of field water table on salt content in the root zone.

Short term and construction related effects of this practice on the quality of downstream water.

Effects of water level control on the temperatures of downstream waters and their effects on aquatic and wildlife communities.

Effects on wetlands or water related wildlife habitats.

Effects on the turbidity of downstream water resources.

Design alternatives presented to the client should address economics, ecological concerns, and acceptable level of risk for design criteria as it relates to hazards to life or property.

Provisions must be made for necessary maintenance. Care should be used to protect the surrounding visual resources. If watercourse fisheries are important, special precautions or design features may be needed to facilitate continuation of fish migrations.

PLANS AND SPECIFICATIONS

The plan should specify the location, grades, quantities, dimensions, materials, and hydraulic and structural requirements for the individual structure.

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resources Conservation Service.

Plans and specifications shall be prepared in accordance with the criteria of this standard and shall describe the requirements for applying the practice to achieve its intended purpose.

OPERATION AND MAINTENANCE

An operation and management plan shall be established by the landowner/user to maintain vegetative cover and the structure for water control. Items shall be site specific and include but are not limited to:

Structures will be checked and necessary maintenance, including removal of debris, undesirable trees or brush shall be performed after major storm events or at least annually.

Water level management and timing shall be adequately described wherever applicable.

Do not graze protected areas around the structure without a grazing plan.

Fertilize to maintain a vigorous vegetative cover. Caution should be used in applying fertilizer to prevent degradation of water quality.

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resources Conservation Service.