

**NATURAL RESOURCES CONSERVATION SERVICE  
CONSERVATION PRACTICE STANDARD**

**IRRIGATION REGULATING RESERVOIR**

(No.)

**CODE 552**

**DEFINITION**

A small storage reservoir constructed to regulate an irrigation water supply.

**PURPOSE**

Collect and store water for a relatively short period of time to:

- Improve irrigation water management by regulating fluctuating flows in streams, canals, or from pumping plants.
- Provide storage for tailwater recovery and reuse.
- Improve offsite water quality.

**CONDITIONS WHERE PRACTICE APPLIES**

This standard applies to reservoirs created by impoundment structures and excavated pits for short-term storage of diverted surface water, water from pumped or flowing wells, or water from an irrigation delivery system. This standard applies to structures designed primarily for flow control or those designed to store water for only a few hours or a few days.

This standard applies to sites meeting the following applicable conditions:

1. The existing available irrigation stream is of such size that regulation is necessary to accomplish the intended purposes. For example, low yield irrigation wells where collection facilities are needed for efficient irrigation application.
2. Water must be stored to be used between times of rotation delivery.
3. An adequate and dependable volume of good quality water is or can be made

available by storage.

4. Topographic, geologic and soil conditions are suitable for practical construction of a regulating reservoir having adequate storage capacity, and any pervious soils in the reservoir area can be sealed to insure seepage losses are not excessive.
5. If surface runoff enters the reservoir, the contributing drainage area is or can be protected against erosion so that normal sedimentation does not materially shorten planned reservoir life.

This standard pertains to the planning and functional design of irrigation regulating reservoirs. It does not include detailed design criteria or construction specifications for individual regulating reservoirs or components of the regulating facility.

This standard also applies to regulating reservoirs constructed of concrete, steel, and other suitable materials used to collect water from two or more irrigation wells for use in irrigation systems.

**CRITERIA**

***General Criteria Applicable To All Purposes***

Criteria for design of components not addressed in NRCS practice standards shall be consistent with sound engineering principles.

All planned work shall comply with all federal, State, and local laws and regulations. Laws and regulations of particular concern include those involving water rights, land use, pollution control, property easements, wetlands, preservation of cultural resources, and endangered species.

Colorado statutes govern the use of surface and underground water. It is the responsibility of the landowner to comply with the applicable laws and regulations concerning applications, permits, and water rights for the installation and operation of irrigation regulating reservoirs.

Reservoirs excavated for the acquisition of groundwater shall meet the requirements of the State of Colorado - State Board of Examiners of Water Well Construction and Pump Installation Contractors.

**State of Colorado Jurisdictional Dams.**

Jurisdictional dams having a height greater than 10 feet to the spillway crest, or stores more than 100 acre-feet of water, or covers more than 20 acres at the high waterline shall be approved by the State Engineer of Colorado.

**State of Colorado Non-Jurisdictional Dams.**

Non-Jurisdictional Dams are smaller than jurisdictional dam and a Notice of Intent to Construct a Non-Jurisdictional Dam must be filed 10 days prior to construction. Approval from the Colorado Division Engineer is required for construction.

Irrigation regulating reservoirs created by earthen pits or embankments shall be designed and constructed according to NRCS Conservation Practice Standard and Specification for Pond (378).

Regulating reservoirs constructed of materials other than earth shall be designed according to sound engineering principles for the material being used.

Pumping plants installed to serve irrigation regulating reservoirs shall be designed and constructed according to NRCS Conservation Practice Standard for Pumping Plant (533).

Where additional storage is required to provide for sediment deposition, storage facilities shall be sized accordingly. Allowable retention times shall be site specific to the particular soil type(s).

***Additional Criteria Applicable To Regulating Fluctuating Flows In Streams, Canals, Or From Pumping Plants***

**Capacity.** Irrigation regulating reservoirs shall have a usable capacity sufficient to permit the existing irrigation stream to be regulated so that irrigation water can be applied with a reasonably high efficiency. In computing capacity requirements consideration shall be given to diverted inflow, surface runoff, precipitation, evaporation, and seepage, as applicable. Excessive seepage losses shall be prevented by the use of an adapted method of sealing or lining. Additional capacity shall be provided, as necessary, for sediment storage.

Capacity requirements for regulating reservoirs used as part of a system for collecting water from two or more wells shall be based on the discharge capacities of the contributing wells and on the operation frequency of the irrigation system.

**Inlet protection.** Reservoir embankment or excavated side slopes at inlets shall be protected from erosion by use of pipe inlets or other suitable structures. Inlet structure capacity shall be adequate to accommodate the design inflow rate.

**Overflow protection.** An overflow protection structure having a capacity equal to or greater than the inlet stream shall be provided for an enclosed embankment. This structure may be designed and installed in combination with the outlet works.

**Outlet works.** Outlet works shall be provided for the controlled release of irrigation water. The outlet works may consist of a gated conduit through or over the embankment for gravity flow to the irrigated area or to a pumping plant. They may also consist of a pumping plant designed to lift water directly from the reservoir basin.

The capacity of the outlet works shall be adequate to provide the outflow rate needed to meet peak period irrigation system demands.

***Additional Criteria Applicable To Storage For Tailwater Recovery And Reuse***

Irrigation regulating reservoirs used in irrigation tailwater recovery and reuse systems are often referred to as tailwater pits or sumps.

**Capacity.** Capacity requirements for irrigation regulating reservoirs for tailwater recovery shall be based on irrigation system runoff volume and rate, as well as, required level of water control at the point tailwater is returned to the irrigation system. Excessive seepage losses shall be prevented by the use of an adapted method of sealing or lining.

For systems where tailwater is discharged into an irrigation pit or regulating reservoir or into a pipeline having facilities for regulating fluctuating flows (e.g. a float valve), small pits or sumps with frequently cycling pumping plants may be used. For systems unable to regulate flows, tailwater sumps or pits shall be made large enough to provide the regulation needed to permit efficient use of the water.

When energy sources for tailwater pump back systems are subject to interruption, safe emergency bypass areas cannot be provided, or tailwater discharges violate local or state regulations, tailwater storage requirements shall, as a minimum, include a volume adequate to store the complete runoff from a single irrigation set.

**Inlet protection.** Sumps and pits shall be equipped with inlets designed to protect side slopes and collection facilities from erosion. A dike, ditch, or water control structure shall be provided, if required by state law, to limit the entrance of rainfall runoff into the designed inlet. Sediment traps shall be installed as needed.

#### ***Additional Criteria Applicable To Improving Water Quality***

**Capacity.** Where additional storage and/or flow regulation is required to provide adequate retention time for breakdown of chemicals in runoff waters, storage facilities shall be sized accordingly. Allowable retention times shall be site specific to the particular chemical of concern.

Seepage from irrigation regulating reservoirs shall be controlled to the extent practical when the facility is expected to receive chemical-laden waters. Control may be in the form of natural soil liners, soil additives, commercial liners, or other approved methods.

**Inlet protection.** Reservoir embankment or excavated side slopes at inlets shall be protected from erosion by use of pipe inlets or other suitable structures. Inlet structure capacity shall be adequate to accommodate the design inflow rate.

#### **CONSIDERATIONS**

When planning this practice the following items should be considered, as applicable:

Effects of erosion and the movement of sediment, pathogens, and the soluble and sediment-attached substances carried by runoff.

Short-term and construction-related effects on quality of downstream watercourses.

Potential of uncovering or redistributing toxic material.

Effects on:

- The water budget, especially on volume and rate of runoff, infiltration, evaporation, transpiration, deep percolation, and ground water recharge.
- Downstream flows or aquifers that would affect other water uses or users.
- The movement of dissolved substances to ground water.
- Wetlands or water-related wildlife habitats.
- Cultural resources.

#### **PLANS AND SPECIFICATIONS**

Plans and specifications for irrigation regulating reservoirs shall be in keeping with this standard and shall describe the requirements for properly installing the practice to achieve its intended purpose.

#### **OPERATION AND MAINTENANCE**

An Operation and Maintenance plan specific to facilities installed shall be prepared for use by the landowner or operator. The plan should provide specific instructions for operating and maintaining facilities to ensure they function properly. The plan shall include provisions to address the following, as a minimum:

- Periodic cleaning and re-grading of collection facilities to maintain proper flow lines and functionality.
- Periodic checks and removal of debris as necessary from inlet and outlet structures to assure proper operation.
- Periodic removal of sediment from traps and/or storage facilities to maintain design capacity and efficiency.
- Inspection or testing of all pipelines and pumping plant components and appurtenances, as applicable.
- Routine maintenance of all mechanical components in accordance with manufacturer recommendations.
- Periodic inspection and maintenance of embankments including control of erosion and undesirable vegetation.
- Periodic water quality analysis as necessary to evaluate nutrients, pesticides, and pathogens.

## **REFERENCES**

State of Colorado - Rules and Regulations for Dam Safety and Dam Construction, 2 CCR 402-1, can be located at the following web address: <http://water.state.co.us/>

State of Colorado - Rules and Regulations for Water Well Construction, Pump Installation, and Monitoring and Observation Hole/Well Construction (Water Well Construction Rules) 2 CCR 402-2 can be located at the following web address: <http://water.state.co.us/boe/>

USDA NRCS, National Engineering Field Handbook for Conservation Practices, Chapters 3, 11, and 15.

USDA NRCS, National NRCS Technical Releases:

TR-12 Procedure for Determining Sediment Storage Requirements for Reservoirs

TR-60 Earth Dams and Reservoirs

USDA NRCS, National Engineering Handbook Series.

**NRCS, CO**

**May 2003**