

**NATURAL RESOURCES CONSERVATION SERVICE**  
**CONSERVATION PRACTICE STANDARD**  
**SEASONAL TUNNEL SYSTEM FOR CROPS**  
**(Ft<sup>2</sup>)**

**CODE 798**

**DEFINITION**

A seasonal polyethylene covered structure with no electrical, ventilation, and heating system that is used to cover crops to extend the growing season in an environmentally safe manner.

**PURPOSES**

- Extend the crop growing season
- Improve plant quality
- Improve soil quality
- Improve water quality from reduced nutrient and pesticide transport

**CONDITIONS WHERE PRACTICE APPLIES**

This practice applies to existing cultivated cropland where extension of growing season is needed due to climate conditions and crops can be grown in the natural soil profile. Permanently raised beds may be installed to improve soil condition, fertility, and agri-ability access, but does not apply to crops not grown in the natural soil profile (i.e. tables/benches, portable pots, etc.).

The practice does not include greenhouses or low tunnel systems that may cover single crop rows.

**CRITERIA**

**General Criteria Applicable to All Purposes**

Plan supportive conservation practices to address all environmental concerns associated with the use of tunnel systems.

The seasonal tunnel structure must be planned, designed, and constructed in accordance with manufacturer's recommendation. The tunnel frame must be constructed of metal, wood, or durable plastic; and be at least 6 feet in height.

Seasonal tunnel structures shall be selected and applied to obtain 100 percent coverage over the crop area. The material shall be of a significant thickness to withstand the temperature modification for the period required. As a minimum, a 6-mil greenhouse-grade, UV resistant polyethylene cover will be used.

The seasonal tunnel system along with necessary appurtenances shall be designed to provide a service life of not less than 4 years.

In climate conditions where snow loads may damage the structure, the tunnel cover shall be removed at the end of the growing season.

Runoff shall be directed away from the tunnel structure to avoid ponding. Runoff may be captured and used for irrigation purposes. Runoff may empty into surface or underground outlets, or onto the ground surface. Surface and underground outlets shall be sized to ensure adequate capacity. Provide for clean-out as appropriate. When runoff from tunnel covers empties onto the ground surface, a stable outlet shall be provided.

Surface or ground outlets such as rock pads, rock filled trenches with subsurface drains, concrete and other erosion-resistant pads, or preformed channels may be used.

Seeding and vegetation shall be established on all disturbed earth surfaces.

**Additional Criteria to Reduce Nutrient and Pesticide Transport**

The irrigation water applied under the covered area shall not exceed the available water capacity of the soil to avoid runoff and leaching below the root zone.

**Additional Criteria to Improve Soil Quality**

January 2010

The area inside the seasonal structure shall have a positive Soil Conditioning Index and soil loss with tolerable limits using currently approved agency wind and water erosion technology.

### CONSIDERATIONS

Locate the tunnel cover convenient for ingress/egress of plant materials.

Remove or manipulate side covers to control internal temperatures.

Rotate the location of the tunnel to allow rain, wind, sun, and cold temperatures to cleanse the soil from the disease build up. Rotation allows growing cover crops on the site during the uncovered period.

Plan the appropriate measures to address:

- Crop rotation
- irrigation water management
- nutrient management
- pest management
- runoff from the structure

Have a reliable source of good quality water near or in the tunnel.

### PLANS AND SPECIFICATIONS

Plans and specifications shall be prepared in accordance with the criteria of this standard.

As a minimum, the plans and specifications shall provide the following:

- Layout and location of the tunnel cover; erosion control, runoff, and vegetative cover practices.
- Materials list and structural details of the cover including all necessary appurtenances as appropriate for the complete system.
- Procedure and timing for installing the tunnel cover (construction sequence), erosion control, runoff, and vegetative practices.
- Procedure and timing to remove structure.
- Site preparation.

### OPERATION AND MAINTENANCE

An operation and maintenance (O&M) plan must be prepared and reviewed with the landowner or operator responsible for the application of the practice. The O&M plan shall provide specific instruction for proper operation and maintenance of each component of this practice and shall detail the level of repairs needed to maintain the effectiveness and useful life of the practice.

Covered area will be periodically inspected, and shall be reinstalled or repaired as needed to accomplish the intended purpose.

Removal of cover materials shall be consistent with the intended purpose and site conditions.

Operation of equipment near and on the site shall not compromise the intended purpose of the cover.

### REFERENCES

Community Garden Guide Season Extension - High Tunnel, NRCS

<http://plant-materials.nrcs.usda.gov/mipmc>

Community Garden Guide Season Extension – Hoophouses, NRCS.

<http://plant-materials.nrcs.usda.gov/mipmc/communitygardens.html>

University of Minnesota,

<http://hightunnels.cfans.umn.edu/resources.htm>

Part I: Introduction to High Tunnels". Spaw, M. and William, K.

<http://www.hightunnels.org/foreducators.htm>

High Tunnel Production Manual". Penn State University College of Agriculture, Department of Horticulture. White, L. and Orzolek, M. 2003

[http://www.nasga.org/publications/pubs\\_hightunnel.htm](http://www.nasga.org/publications/pubs_hightunnel.htm)

"High Tunnels". Ted Blomgren of Cornell Cooperative Extension and Tracy Frisch of the Regional Farm and Food Project.

<http://www.uvm.edu/sustainableagriculture/hightunnels.htm>