

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
AaB: Bullock-----	60	Poor Sodium content Low content of organic matter Droughty Depth to bedrock Water erosion	0.00 0.12 0.15 0.58 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.22 0.87	Fair Sodium content Salinity Depth to bedrock	0.22 0.50 0.58
Parchin-----	30	Poor Sodium content Low content of organic matter Droughty Depth to bedrock Too acid Water erosion	0.00 0.12 0.30 0.58 0.97 0.99	Poor Depth to bedrock Shrink-swell	0.00 0.96	Poor Hard to reclaim Sodium content Depth to bedrock Salinity	0.00 0.00 0.58 0.88
AbC: Bullock-----	55	Poor Sodium content Low content of organic matter Droughty Depth to bedrock Water erosion	0.00 0.12 0.15 0.58 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.22 0.87	Fair Sodium content Salinity Depth to bedrock	0.22 0.50 0.58
Slickspots, Dry----	30	Not rated		Not rated		Not rated	
Ac: Bullock-----	50	Poor Sodium content Low content of organic matter Droughty Depth to bedrock Water erosion	0.00 0.12 0.15 0.58 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.22 0.87	Fair Sodium content Salinity Depth to bedrock	0.22 0.50 0.58
Trembles-----	20	Fair Low content of organic matter	0.88	Good		Good	

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Slickspots, Dry-----	15	Not rated		Not rated		Not rated	
AdD: Amor-----	60	Fair Depth to bedrock 0.58 Low content of organic matter 0.88 Droughty 0.93 Carbonate content 0.97		Poor Depth to bedrock 0.00 Low strength 0.78 Shrink-swell 0.87		Fair Slope 0.37 Depth to bedrock 0.58 Carbonate content 0.97	
Cabba-----	25	Poor Droughty 0.00 Depth to bedrock 0.00 Low content of organic matter 0.50 Water erosion 0.90		Poor Depth to bedrock 0.00 Low strength 0.78		Poor Depth to bedrock 0.00 Slope 0.37	
Ar: Arnegard-----	90	Fair Low content of organic matter 0.50		Good		Good	
Ba: Badland-----	80	Not rated		Not rated		Not rated	
Bb: Banks-----	95	Poor Wind erosion 0.00 Too sandy 0.02 Low content of organic matter 0.12 Droughty 0.71		Good		Fair Too sandy 0.02	
BCA: Belfield-----	55	Fair Low content of organic matter 0.12 Sodium content 0.22 Too clayey 0.32 Salinity 0.88 Water erosion 0.90		Poor Low strength 0.00 Shrink-swell 0.12		Poor Salinity 0.00 Sodium content 0.02 Too Clayey 0.19	

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Grail-----	35	Poor Too clayey Low content of organic matter Water erosion	0.00 0.12 0.90	Poor Low strength Shrink-swell	0.00 0.56	Poor Too Clayey	0.00
BdB: Belfield-----	55	Fair Low content of organic matter Sodium content Too clayey Salinity Water erosion	0.12 0.22 0.32 0.88 0.90	Poor Low strength Shrink-swell	0.00 0.12	Poor Salinity Sodium content Too Clayey	0.00 0.02 0.19
Marmarth-----	30	Fair Droughty Low content of organic matter Depth to bedrock	0.47 0.50 0.58	Poor Depth to bedrock Shrink-swell	0.00 0.99	Fair Depth to bedrock	0.58
BeC: Belfield-----	55	Fair Low content of organic matter Sodium content Too clayey Salinity Water erosion	0.12 0.22 0.32 0.88 0.90	Poor Low strength Shrink-swell	0.00 0.12	Poor Salinity Sodium content Too Clayey	0.00 0.02 0.19
Morton-----	30	Fair Low content of organic matter Depth to bedrock Water erosion Droughty	0.50 0.58 0.90 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.87	Fair Depth to bedrock	0.58

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
BfA: Belfield-----	65	Fair Low content of organic matter Sodium content Too clayey Salinity Water erosion	0.12 0.22 0.32 0.88 0.90	Poor Low strength Shrink-swell	0.00 0.12	Poor Salinity Sodium content Too Clayey	0.00 0.02 0.19
Rhoades-----	20	Poor Sodium content Low content of organic matter Salinity Droughty Too clayey	0.00 0.50 0.50 0.57 0.88	Poor Low strength Depth to bedrock Shrink-swell	0.00 0.00 0.12	Poor Salinity Too Clayey	0.00 0.57
BhE: Blackhall-----	40	Poor Droughty Depth to bedrock Low content of organic matter Sodium content	0.00 0.00 0.12 0.78	Poor Depth to bedrock Slope	0.00 0.00	Poor Slope Depth to bedrock Sodium content	0.00 0.00 0.78
Cabbart-----	40	Poor Droughty Depth to bedrock Low content of organic matter Carbonate content	0.00 0.00 0.88 0.97	Poor Depth to bedrock Slope Low strength	0.00 0.00 0.00	Poor Slope Depth to bedrock Carbonate content	0.00 0.00 0.97
CaE: Cabba-----	55	Poor Droughty Depth to bedrock Low content of organic matter Water erosion	0.00 0.00 0.50 0.90	Poor Depth to bedrock Slope Low strength	0.00 0.00 0.78	Poor Slope Depth to bedrock	0.00 0.00

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Lantry-----	30	Fair Carbonate content Depth to bedrock Droughty Low content of organic matter Water erosion	0.46 0.58 0.79 0.88 0.90	Poor Depth to bedrock Low strength Slope	0.00 0.22 0.50	Poor Slope Carbonate content Depth to bedrock	0.00 0.46 0.58
CbD: Cabba-----	65	Poor Droughty Depth to bedrock Low content of organic matter Water erosion	0.00 0.00 0.50 0.90	Poor Depth to bedrock Slope Low strength	0.00 0.50 0.78	Poor Slope Depth to bedrock	0.00 0.00
Trembles-----	30	Fair Low content of organic matter	0.88	Good		Good	
CcD: Cabba-----	50	Poor Droughty Depth to bedrock Low content of organic matter Water erosion	0.00 0.00 0.88 0.90	Poor Depth to bedrock Shrink-swell	0.00 0.96	Poor Depth to bedrock Slope Rock fragments Salinity	0.00 0.04 0.28 0.88
Wayden-----	40	Poor Droughty Depth to bedrock Too clayey Low content of organic matter Cobble content	0.00 0.00 0.12 0.88 0.96	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.85	Poor Depth to bedrock Rock fragments Too Clayey Slope	0.00 0.00 0.09 0.96
CdE: Cohagen-----	50	Poor Wind erosion Droughty Depth to bedrock Low content of organic matter Too sandy	0.00 0.00 0.00 0.88 0.92	Poor Depth to bedrock Slope	0.00 0.08	Poor Slope Depth to bedrock Too sandy	0.00 0.00 0.92

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Vebar-----	40	Fair Droughty Depth to bedrock	0.53 0.58	Poor Depth to bedrock Slope	0.00 0.50	Poor Slope Depth to bedrock	0.00 0.58
DaB: Daglum-----	60	Poor Sodium content Too clayey Low content of organic matter Salinity	0.00 0.00 0.50 0.50	Poor Low strength Shrink-swell	0.00 0.12	Poor Salinity Sodium content Too Clayey	0.00 0.00 0.00
Felor-----	35	Fair Low content of organic matter Water erosion	0.12 0.99	Poor Low strength Shrink-swell	0.00 0.38	Good	
Db: Dimmick-----	50	Poor Too clayey	0.00	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.12	Poor Too Clayey Depth to saturated zone	0.00 0.00
Heil-----	40	Poor Too clayey Low content of organic matter Salinity Water erosion	0.00 0.50 0.88 0.99	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.12	Poor Too Clayey Depth to saturated zone Salinity	0.00 0.00 0.00
FaA: Farnuf-----	90	Fair Low content of organic matter	0.12	Poor Low strength Shrink-swell	0.00 0.87	Good	
FaB: Farnuf-----	90	Fair Low content of organic matter	0.12	Poor Low strength Shrink-swell	0.00 0.87	Good	

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
FbA: Farnuf-----	65	Fair Low content of organic matter	0.12	Poor Low strength Shrink-swell	0.00 0.87	Good	
Daglum-----	25	Poor Sodium content Too clayey Low content of organic matter Salinity	0.00 0.00 0.50 0.50	Poor Low strength Shrink-swell	0.00 0.12	Poor Salinity Sodium content Too Clayey	0.00 0.00 0.00
FcB: Felor-----	60	Fair Low content of organic matter Water erosion	0.12 0.99	Poor Low strength Shrink-swell	0.00 0.38	Good	
Yegen-----	30	Fair Low content of organic matter	0.12	Fair Depth to bedrock	0.58	Good	
FcC: Felor-----	55	Fair Low content of organic matter Water erosion	0.12 0.99	Poor Low strength Shrink-swell	0.00 0.38	Good	
Yegen-----	35	Fair Low content of organic matter	0.12	Fair Depth to bedrock	0.58	Good	
Fd: Dogiecreek-----	75	Poor Salinity Too alkaline Low content of organic matter Carbonate content	0.00 0.00 0.50 0.92	Fair Depth to saturated zone	0.14	Poor Salinity Depth to saturated zone	0.00 0.14

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ga: Grail-----	90	Poor Too clayey Low content of organic matter Water erosion	0.00 0.12 0.90	Poor Low strength Shrink-swell	0.00 0.56	Poor Too Clayey	0.00
LaA: Lawther-----	90	Poor Too clayey Salinity Low content of organic matter	0.00 0.88 0.88	Poor Low strength Shrink-swell	0.00 0.12	Poor Too Clayey	0.00
LaB: Lawther-----	90	Poor Too clayey Salinity Low content of organic matter	0.00 0.88 0.88	Poor Low strength Shrink-swell	0.00 0.12	Poor Too Clayey	0.00
LaC: Lawther-----	85	Poor Too clayey Salinity Low content of organic matter	0.00 0.88 0.88	Poor Low strength Shrink-swell	0.00 0.12	Poor Too Clayey	0.00
LbB: Lefor-----	90	Fair Depth to bedrock Droughty Low content of organic matter Too acid	0.58 0.78 0.88 0.97	Poor Depth to bedrock Shrink-swell	0.00 0.90	Fair Depth to bedrock	0.58
MaB: Manning-----	90	Fair Low content of organic matter Droughty	0.50 0.99	Good		Poor Hard to reclaim	0.00

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
MbB: Marmarth-----	85	Fair Droughty Low content of organic matter Depth to bedrock	0.47 0.50 0.58	Poor Depth to bedrock Shrink-swell	0.00 0.99	Fair Depth to bedrock	0.58
McA: Morton-----	85	Fair Low content of organic matter Depth to bedrock Water erosion Droughty	0.50 0.58 0.90 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.87	Fair Depth to bedrock	0.58
McB: Morton-----	85	Fair Low content of organic matter Depth to bedrock Water erosion Droughty	0.50 0.58 0.90 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.87	Fair Depth to bedrock	0.58
McC: Morton-----	85	Fair Low content of organic matter Depth to bedrock Water erosion Droughty	0.50 0.58 0.90 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.87	Fair Depth to bedrock	0.58
MdC: Morton-----	55	Fair Low content of organic matter Depth to bedrock Water erosion Droughty	0.50 0.58 0.90 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.87	Fair Depth to bedrock	0.58

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Lantry-----	25	Fair Carbonate content Depth to bedrock Droughty Low content of organic matter Water erosion	0.46 0.58 0.79 0.88 0.90	Poor Depth to bedrock Low strength	0.00 0.22	Fair Carbonate content Depth to bedrock	0.46 0.58
MdD: Morton-----	40	Fair Low content of organic matter Depth to bedrock Water erosion Droughty	0.50 0.58 0.90 0.98	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.87	Fair Depth to bedrock	0.58
Lantry-----	35	Fair Carbonate content Depth to bedrock Droughty Low content of organic matter Water erosion	0.46 0.58 0.79 0.88 0.90	Poor Depth to bedrock Low strength	0.00 0.22	Fair Slope Carbonate content Depth to bedrock	0.37 0.46 0.58
MeD: Morton-----	65	Fair Low content of organic matter Depth to bedrock Water erosion Droughty	0.50 0.58 0.90 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.87	Fair Depth to bedrock	0.58
Rhoades-----	20	Poor Sodium content Low content of organic matter Salinity Droughty Too clayey	0.00 0.50 0.50 0.57 0.88	Poor Low strength Depth to bedrock Shrink-swell	0.00 0.00 0.12	Poor Salinity Too Clayey Slope	0.00 0.57 0.63
Pa: Parshall-----	85	Fair Low content of organic matter	0.50	Good		Good	

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Pb: Orthents, Hummocky--	45	Poor Too sandy Wind erosion Low content of organic matter Droughty	0.00 0.00 0.12 0.71	Good		Poor Too sandy	0.00
Hanly-----	40	Poor Wind erosion Too sandy Low content of organic matter	0.00 0.00 0.12	Good		Poor Too sandy	0.00
RaA: Reeder-----	90	Fair Depth to bedrock Droughty	0.58 0.87	Poor Depth to bedrock Shrink-swell	0.00 0.87	Fair Depth to bedrock	0.58
RaC: Reeder-----	85	Fair Depth to bedrock Droughty	0.58 0.87	Poor Depth to bedrock Shrink-swell	0.00 0.87	Fair Depth to bedrock	0.58
RbB: Reeder-----	60	Fair Depth to bedrock Droughty	0.58 0.87	Poor Depth to bedrock Shrink-swell	0.00 0.87	Fair Depth to bedrock	0.58
Amor-----	25	Fair Depth to bedrock Low content of organic matter Droughty Carbonate content	0.58 0.88 0.93 0.97	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.78 0.87	Fair Depth to bedrock Carbonate content	0.58 0.97
RcC: Reeder-----	55	Fair Depth to bedrock Droughty	0.58 0.87	Poor Depth to bedrock Shrink-swell	0.00 0.87	Fair Depth to bedrock	0.58

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Lantry-----	30	Fair Carbonate content Depth to bedrock Droughty Low content of organic matter Water erosion	0.46 0.58 0.79 0.88 0.90	Poor Depth to bedrock Low strength	0.00 0.22	Fair Carbonate content Depth to bedrock	0.46 0.58
RdB: Reeder-----	60	Fair Depth to bedrock Droughty	0.58 0.87	Poor Depth to bedrock Shrink-swell	0.00 0.87	Fair Depth to bedrock	0.58
Rhoades-----	30	Poor Sodium content Low content of organic matter Salinity Droughty Too clayey	0.00 0.50 0.50 0.57 0.88	Poor Low strength Depth to bedrock Shrink-swell	0.00 0.00 0.12	Poor Salinity Too Clayey	0.00 0.57
ReB: Regent-----	65	Poor Too clayey Depth to bedrock Low content of organic matter Water erosion Droughty	0.00 0.58 0.88 0.90 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.21	Poor Too Clayey Depth to bedrock	0.00 0.58
Daglun-----	25	Poor Sodium content Too clayey Low content of organic matter Salinity	0.00 0.00 0.50 0.50	Poor Low strength Shrink-swell	0.00 0.12	Poor Salinity Sodium content Too Clayey	0.00 0.00 0.00

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
RfB: Regent-----	65	Poor Too clayey Depth to bedrock Low content of organic matter Water erosion Droughty	0.00 0.58 0.88 0.90 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.21	Poor Too Clayey Depth to bedrock	0.00 0.58
Savage-----	25	Poor Too clayey Low content of organic matter Water erosion	0.00 0.88 0.90	Poor Low strength Shrink-swell	0.00 0.12	Poor Too Clayey	0.00
RhD: Regent-----	60	Poor Too clayey Depth to bedrock Low content of organic matter Water erosion Droughty	0.00 0.58 0.88 0.90 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.21	Poor Too Clayey Depth to bedrock	0.00 0.58
Wayden-----	35	Poor Droughty Depth to bedrock Too clayey Low content of organic matter Water erosion	0.00 0.00 0.00 0.88 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.85	Poor Depth to bedrock Too Clayey Slope	0.00 0.00 0.63
RkD: Rhoades-----	50	Poor Sodium content Low content of organic matter Salinity Droughty Too clayey	0.00 0.50 0.50 0.57 0.88	Poor Low strength Depth to bedrock Shrink-swell	0.00 0.00 0.12	Poor Salinity Too Clayey	0.00 0.57

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Cabba-----	25	Poor Droughty Depth to bedrock Low content of organic matter Water erosion	0.00 0.00 0.50 0.90	Poor Depth to bedrock Low strength Slope	0.00 0.78 0.92	Poor Depth to bedrock Slope	0.00 0.00
RmC: Rhoades-----	40	Poor Sodium content Low content of organic matter Salinity Droughty Too clayey	0.00 0.50 0.50 0.57 0.88	Poor Low strength Depth to bedrock Shrink-swell	0.00 0.00 0.12	Poor Salinity Too Clayey	0.00 0.57
Daglum-----	30	Poor Sodium content Too clayey Low content of organic matter Salinity	0.00 0.00 0.50 0.50	Poor Low strength Shrink-swell	0.00 0.12	Poor Salinity Sodium content Too Clayey	0.00 0.00 0.00
Slickspots, Dry-----	15	Not rated		Not rated		Not rated	
RnD: Rhoades-----	50	Poor Sodium content Low content of organic matter Salinity Droughty Too clayey	0.00 0.50 0.50 0.57 0.88	Poor Low strength Depth to bedrock Shrink-swell	0.00 0.00 0.12	Poor Salinity Too Clayey	0.00 0.57
Rock Outcrop, Sandstone-----	35	Not rated		Not rated		Not rated	
RoE: Rock Outcrop, Sandstone-----	50	Not rated		Not rated		Not rated	

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Cabba-----	40	Poor Droughty Depth to bedrock Low content of organic matter Water erosion	0.00 0.00 0.50 0.90	Poor Depth to bedrock Low strength Slope	0.00 0.78 0.92	Poor Depth to bedrock Slope	0.00 0.00
SaA: Savage-----	85	Poor Too clayey Low content of organic matter Water erosion	0.00 0.88 0.90	Poor Low strength Shrink-swell	0.00 0.12	Poor Too Clayey	0.00
SbA: Savage-----	65	Poor Too clayey Low content of organic matter Water erosion	0.00 0.88 0.90	Poor Low strength Shrink-swell	0.00 0.12	Poor Too Clayey	0.00
Daglum-----	25	Poor Sodium content Too clayey Low content of organic matter Salinity	0.00 0.00 0.50 0.50	Poor Low strength Shrink-swell	0.00 0.12	Poor Salinity Sodium content Too Clayey	0.00 0.00 0.00
Sc: Shambo-----	90	Fair Low content of organic matter	0.12	Fair Shrink-swell	0.99	Good	
Sd: Shambo-----	85	Good		Good		Good	
SeA: Stady-----	90	Fair Low content of organic matter Droughty	0.12 0.95	Good		Fair Rock fragments Hard to reclaim	0.03 0.98

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Sh: Lohler-----	65	Poor Too clayey Low content of organic matter Water erosion	0.00 0.50 0.99	Poor Low strength Shrink-swell	0.00 0.12	Poor Too Clayey Salinity	0.00 0.88
Trembles-----	25	Fair Low content of organic matter	0.88	Good		Good	
Ta: Trembles-----	95	Fair Low content of organic matter	0.88	Good		Good	
Tb: Trembles-----	90	Fair Low content of organic matter	0.88	Good		Good	
TcD: Twilight-----	40	Fair Droughty Depth to bedrock	0.04 0.58	Poor Depth to bedrock	0.00	Fair Slope Depth to bedrock	0.37 0.58
Marmarth-----	25	Fair Droughty Low content of organic matter Depth to bedrock	0.47 0.50 0.58	Poor Depth to bedrock Shrink-swell	0.00 0.99	Fair Depth to bedrock	0.58
Parchin-----	25	Poor Sodium content Droughty Low content of organic matter Depth to bedrock Too acid Water erosion	0.00 0.06 0.12 0.58 0.97 0.99	Poor Depth to bedrock Low strength	0.00 0.78	Poor Hard to reclaim Sodium content Depth to bedrock Salinity	0.00 0.22 0.58 0.88

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
VaC: Vebar-----	65	Fair Low content of organic matter Droughty Depth to bedrock	0.50 0.53 0.58	Poor Depth to bedrock	0.00	Fair Depth to bedrock	0.58
Cohagen-----	30	Poor Wind erosion Droughty Depth to bedrock Low content of organic matter Too sandy	0.00 0.00 0.00 0.88 0.92	Poor Depth to bedrock	0.00	Poor Depth to bedrock Too sandy	0.00 0.92
VaD: Vebar-----	55	Fair Low content of organic matter Droughty Depth to bedrock	0.50 0.53 0.58	Poor Depth to bedrock	0.00	Fair Slope Depth to bedrock	0.37 0.58
Cohagen-----	35	Poor Wind erosion Droughty Depth to bedrock Too sandy Low content of organic matter	0.00 0.00 0.00 0.22 0.88	Poor Depth to bedrock Slope	0.00 0.50	Poor Slope Depth to bedrock Too sandy	0.00 0.00 0.22
VbB: Vebar-----	65	Fair Low content of organic matter Droughty Depth to bedrock	0.50 0.53 0.58	Poor Depth to bedrock	0.00	Fair Depth to bedrock	0.58
Tally-----	25	Fair Low content of organic matter	0.88	Good		Good	

Section II
Soil and Site Information

Construction Materials Table 2
Perkins County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
w: Water (less Than 40 Acres)-----	100	Not rated		Not rated		Not rated	
WaD: Wabek-----	85	Poor Droughty Low content of organic matter	0.00 0.50	Fair Slope	0.50	Poor Slope Rock fragments Hard to reclaim	0.00 0.00 0.00
WbA: Wabek-----	90	Poor Droughty Low content of organic matter	0.00 0.50	Good		Poor Rock fragments Hard to reclaim	0.00 0.00
WcA: Watrous-----	85	Poor Droughty Low content of organic matter Depth to bedrock	0.00 0.00 0.58	Not Rated Depth to bedrock	0.00	Fair Depth to bedrock	0.58
YaB: Yegen-----	90	Fair Low content of organic matter	0.12	Fair Depth to bedrock	0.58	Good	
YaC: Yegen-----	90	Fair Low content of organic matter	0.12	Fair Depth to bedrock	0.58	Good	
Za: Zeona-----	90	Poor Wind erosion Low content of organic matter Too sandy Droughty	0.00 0.12 0.36 0.76	Good		Fair Too sandy	0.36

