

# IRRIGATION REGULATING RESERVOIR

(No.)  
Code 552

Natural Resources Conservation Service  
Conservation Practice Standard

## I. Definition

A small storage reservoir constructed to regulate an irrigation water supply.

## II. Purpose

Collect and store water for a relatively short period of time to:

- Provide storage for tailwater recovery and reuse.
- Improve offsite water quality.

## III. Conditions Where Practice Applies

This standard applies to reservoirs created by impoundment structures and excavated pits for short-term storage of water from an irrigation delivery system. This standard applies to structures designed primarily for flow control or those designed to store water for only a few hours or a few days.

This standard applies to sites meeting the following applicable conditions:

1. Water must be stored to be used between times of rotation delivery.
2. An adequate and dependable volume of good quality water is or can be made available by storage.
3. Topographic, geologic and soil conditions are suitable for practical construction of a regulating reservoir having adequate storage capacity, and any pervious soils in the reservoir area can be sealed to insure seepage losses are not excessive.
4. If surface runoff enters the reservoir, the contributing drainage area is or can be protected against erosion so that normal sedimentation does not materially shorten planned reservoir life.

This standard pertains to the planning and functional design of irrigation regulating reservoirs. It does not include detailed design criteria or construction

specifications for individual regulating reservoirs or components of the regulating facility.

## IV. Federal, Tribal, State, and Local Laws

Irrigation regulating reservoirs shall comply with all federal, tribal, state and local laws, rules or regulations. The operator is responsible for securing required permits. This standard does not contain the text of federal, tribal, state or local laws governing irrigation regulating reservoirs.

## V. Criteria

### A. General Criteria Applicable to All Purposes

Criteria for design of components not addressed in NRCS practice standards shall be consistent with sound engineering principles.

Irrigation regulating reservoirs created by earthen pits or embankments shall be designed and constructed according to NRCS Conservation Practice Standard for Pond - 378.

Pumping plants installed to serve irrigation regulating reservoirs shall be designed and constructed according to NRCS Conservation Practice Standard for Pumping Plant - 533.

Where additional storage is required to provide for sediment deposition, storage facilities shall be sized accordingly. Allowable retention times shall be site specific to the particular soil type(s).

### B. Additional Criteria Applicable to Storage For Tailwater Recovery and Reuse

Irrigation regulating reservoirs used in irrigation tailwater recovery and reuse systems are often referred to as tailwater pits or sumps.

**Capacity.** Capacity requirements for irrigation regulating reservoirs for tailwater recovery shall be based on irrigation system runoff volume and rate, as well as, required level of water control at the point tailwater is returned to the irrigation

system. Excessive seepage losses shall be prevented by sealing or lining the reservoir.

For systems where tailwater is discharged into an irrigation pit or regulating reservoir or into a pipeline having facilities for regulating fluctuating flows (e.g. a float valve), small pits or sumps with frequently cycling pumping plants may be used. For systems unable to regulate flows, tailwater sumps or pits shall be made large enough to provide the regulation needed to permit efficient use of the water.

When energy sources for tailwater pump back systems are subject to interruption, safe emergency bypass areas cannot be provided, or tailwater discharges violate local or state regulations, tailwater storage requirements shall, as a minimum, include a volume adequate to store the complete runoff from a single irrigation set.

**Inlet protection.** Sumps and pits shall be equipped with inlets designed to protect side slopes and collection facilities from erosion. A dike, ditch, or water control structure shall be provided, if needed, to limit the entrance of rainfall runoff into the designed inlet. Sediment traps shall be installed as needed.

### C. Additional Criteria Applicable to Improving Water Quality

**Capacity.** Where additional storage and/or flow regulation is required to provide adequate retention time for breakdown of chemicals in runoff waters, storage facilities shall be sized accordingly. Allowable retention times shall be site specific to the particular chemical of concern.

Seepage from irrigation regulating reservoirs shall be minimized to the extent practical when the facility is expected to receive chemical-laden waters. Control may be in the form of natural soil liners, soil additives, commercial liners, or other approved methods.

**Inlet protection.** Reservoir embankment or excavated side slopes at inlets shall be protected from erosion by use of pipe inlets or other suitable structures. Inlet structure capacity shall be adequate to accommodate the design inflow rate.

## VI. Considerations

Additional recommendations relating to design that may enhance the use of, or avoid problems with, this practice but are not required to ensure its basic conservation functions are as follows.

- A. Effects of erosion and the movement of sediment, pathogens, and the soluble and sediment-attached substances carried by runoff.
- B. Short-term and construction-related effects on quality of downstream watercourses.
- C. Potential of uncovering or redistributing toxic material.
- D. Effects on:
  - The water budget, especially on volume and rate of runoff, infiltration, evaporation, transpiration, deep percolation, and ground water recharge.
  - Downstream flows or aquifers that would affect other water uses or users.
  - The movement of dissolved substances to ground water.
  - Wetlands or water-related wildlife habitats.
  - Cultural resources.

## VII. Plans and Specifications

Plans and specifications for irrigation regulating reservoirs shall be in keeping with this standard and shall describe the requirements for properly installing the practice to achieve its intended purpose.

## VIII. Operation and Maintenance

An operation and maintenance plan specific to facilities installed shall be prepared for use by the landowner or operator. The plan should provide specific instructions for operating and maintaining facilities to ensure they function properly. The plan shall include provisions to address the following, as a minimum:

- Periodic cleaning and re-grading of collection facilities to maintain proper flow lines and functionality.
- Periodic checks and removal of debris as necessary from inlet and outlet structures to assure proper operation.

- Periodic removal of sediment from traps and/or storage facilities to maintain design capacity.
- Inspection or testing of all pipelines and pumping plant components and appurtenances.
- Routine maintenance of all mechanical components.
- Periodic inspection and maintenance of embankments including control of erosion and undesirable vegetation.
- Periodic water quality analysis as necessary to evaluate nutrients, pesticides, and pathogens.

## **IX References**

USDA, NRCS, Wisconsin Field Office Technical Guide, Section IV, Conservation Practice Standards and Specifications.