

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD
CONNECTICUT**

POND SEALING OR LINING - FLEXIBLE MEMBRANE

(No.)

CODE 521A

DEFINITION

A manufactured hydraulic barrier consisting of a functionally continuous layer of synthetic or partially synthetic, flexible material.

PURPOSE

To restrict, impede, and control seepage of contaminants from water and waste impoundment structures for water conservation and environmental protection.

CONDITION WHERE PRACTICE APPLIES

On ponds and water storage structures that require treatment to control seepage rates within acceptable limits.

On earthen waste storage structures, waste treatment lagoons and other structures that require treatment to control seepage of contaminants from the storage structure.

CRITERIA

Laws and Regulations. All federal, state, and local laws, rules, and regulations, including local inland wetland agency regulations, governing the construction and use of this practice as well as setbacks from wells, surface water and property boundaries shall be followed. Planned work shall comply with all federal, state, and local laws and permit conditions and requirements.

The landowner shall obtain all necessary permits prior to construction or any land clearing activities.

Design. Structures to be lined shall have been constructed to meet all applicable NRCS standards. All inlets, outlets, ramps, and other appurtenances may be installed before, during, or

after the liner placement, but shall be done in a manner that does not damage or impair the proper operation or integrity of the liner.

Design and installation of the flexible membrane shall be in accordance with manufacturer recommendations. All flexible membrane installations shall be certified by the installer as meeting the material and installation requirements of the plans and specifications.

Manufacturer recommendations shall be followed with regard to protection from weather and exposure.

Minimum Criteria for Membranes

Type	Limiting Parameter	
	Wastewater	Clear Water
HDPE	40 mil	30 mil
LLDPE	40 mil	20 mil
PVC	30 mil	20 mil
GCL	0.75 lb./sq ft (bentonite)	
EPDM	45 mil	
PP (Reinforced)	36 mil	24 mil
(Un-reinforced)	40 mil	20 mil
RPE	NR	24 mil

1 mil = 1/1000 of an inch

HDPE – High Density Polyethylene Geomembrane

LLDPE – Linear Low Density Polyethylene Geomembrane

PVC – Polyvinyl Chloride Geomembrane

GCL – Geosynthetic Clay Liner

EPDM – Synthetic Rubber Geomembrane

PP – Polypropylene Geomembrane

RPE – Reinforced Polyethylene Geomembrane

NR – Not Recommended

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resources Conservation Service Connecticut State Office (<http://www.ct.nrcs.usda.gov>), or download it from the Connecticut electronic Field Office Technical Guide (eFOTG) <http://www.nrcs.usda.gov/technical/efotg/>

**NRCS, CT
October, 2008**

Cover Soil. PVC and GCL liners shall be covered with a minimum of 12 inches of soil. Cover soil may be used on other liners but is not required.

Cover soil shall be used as cover for liners when required for the proper performance, protection and durability of the installation. Cover soils shall not contain sharp, angular stones or any objects that could damage the liner. Maximum allowable particle size of soil cover material shall be 3/8-inch for geomembrane liners and 1/2-inch for geosynthetic clay liners, unless the liner is cushioned by an 8-ounce or greater needle punched, non-woven geotextile padding material. Cover materials shall be stable against slippage down the slope under all operational and exposure conditions.

Subgrade Preparation. Subgrade preparation shall conform to manufacturer recommendations. Subgrade materials shall not contain sharp, angular stones or any objects that could damage the liner or adversely affect its function.

Padding. A cushion or padding shall be placed beneath the liner if the subgrade particles contain sharp angular stones that could damage the liner or particles greater than 3/8-inch for geomembrane liners and 1/2-inch for geosynthetic clay liners. The padding or cushion may be an 8-ounce or greater non-woven geotextile or a soil meeting the particle size and shape requirements of the subgrade.

Anchorage. Liners shall be anchored to prevent uplift due to wind or slippage down the side slope.

Safety. Design shall include appropriate safety features to minimize the hazards of the structure. Warning signs, fences, ladders, ropes, bars, rails, and other devices shall be provided, as appropriate, to ensure the safety of humans and livestock.

CONSIDERATIONS

Venting of wastewater pond liners not covered with soil is recommended unless other site conditions exist to allow dissipation of gas pressure from beneath the liner. One such condition is the presence of granular foundation soils (SW, GW or GP). A minimum vent spacing of 50 feet is recommended.

If high water tables could adversely affect the proper functioning of the structure, interceptor or relief-type drainage systems should be considered to control uplift pressures.

PLANS AND SPECIFICATIONS

Plans and specifications shall be prepared for specific field sites in accordance with this standard and shall describe the requirements for applying the practice to achieve its intended uses.

As a minimum, the plans and specifications shall provide the following:

1. Layout of the containment structure, collection points, waste transfer locations or pipelines, and topography of the site
2. Required liner properties, cushion materials, and pipeline materials
3. Subgrade details, including tolerances on smoothness of the finished grade
4. Details of liner installation, seaming requirements, and requirements for attachments and appurtenances
5. Quality control testing
6. Fence and signage requirements, if required.

Specifications for applying this practice shall be prepared for each area and recorded using approved specification sheets, job sheets, and narrative statements in the conservation plan, or other acceptable documentation.

To the extent practical, specifications shall conform to NRCS National Engineering Handbook Parts 642 and 643 (Section 20).

AS-BUILT DRAWINGS

As-built drawings shall be prepared showing all pertinent elements and elevations as actually installed. As-built data and drawings will be provided to the owner/operator, regulatory state agency and participating partners upon construction completion.

OPERATION AND MAINTENANCE

A plan for operation and maintenance (O&M) of the liner and structure shall be prepared. The plan shall be consistent with the purposes of the type of liner chosen, intended life, safety

requirements and design criteria. The plan shall contain requirements including but not limited to:

1. Design capacity and liquid level of the structure.
2. A description of the normal operation, safety concerns and maintenance requirements.
3. Repair procedures.
4. Periodic inspection of the following:
 - Visible portions of the liner for tears punctures, or other damage;

- Liner interface with inlets, outlets, ramps, or other appurtenances for damage;
- Liquid level in the structure;
- Ballooning of the liner indicating presence of gas beneath the liner.

REFERENCES

Quality Assurance and Quality Control for Waste Containment Facilities, EPA/1600/R-93/182, September 1993.