

**NATURAL RESOURCES CONSERVATION SERVICE  
PACIFIC ISLANDS AREA**

**CONSERVATION PRACTICE STANDARD**

**MULCHING**

(Ac.)

**CODE 484**

**DEFINITION**

Applying plant residues or other suitable materials produced off site, to the land surface.

**PURPOSE**

- Conserve soil moisture
- Reduce energy use associated with irrigation
- Moderate soil temperature
- Provide erosion control
- Suppress weed growth
- Facilitate the establishment of vegetative cover
- Improve soil quality
- Reduce airborne particulates

**CONDITIONS WHERE PRACTICE APPLIES**

This practice applies to all lands where mulches are needed. This practice may be used alone or in combination with other practices.

**CRITERIA**

**General Criteria Applicable to All Purposes**

The selection of mulching materials will depend primarily on site conditions and the material's availability. Mulch materials shall consist of natural and/or artificial materials that are environmentally safe such as plant residue, wood bark or chips, gravel, plastic, fabric, rice hulls, or other equivalent materials of sufficient dimension (depth or thickness) and durability to achieve the intended purpose for the required time period.

Prior to mulching, the soil surface shall be prepared in order to achieve the desired purpose.

The mulch material shall be evenly applied and, if

necessary, anchored to the soil. Tackifiers, emulsions, pinning, netting, crimping or other acceptable methods of anchoring will be used if needed to hold the mulch in place for specified periods.

As a minimum, manufactured mulches shall be applied according to the manufacturer's specifications.

Mulching operations shall comply with federal, state, and/or local laws and regulations during the installation, operation, and maintenance of this practice.

Mulch material shall be relatively free of disease, pesticides, chemicals, noxious weed seeds, and other pests and pathogens.

Consult the Pacific Islands Area [Agronomy Technical Note 8](#) for more information concerning mulch selection and mulching calculations.

**Additional Criteria to Conserve Soil Moisture and/or Reduce Energy Use Associated with Irrigation**

Mulch materials applied to the soil surface shall provide at least 60 percent surface cover to reduce potential evaporation. The material shall be of a significant thickness to persist for the period required for the conservation of water and/or energy.

**Additional Criteria to Moderate Soil Temperature**

Mulch materials shall be selected and applied to obtain 100 percent coverage over the area treated. The material shall be of a significant thickness to persist for the period required for the temperature modification.

**Additional Criteria to Provide Erosion Control**

When mulching with cereal grain straw or grass hay, apply at a rate to achieve a minimum 70

percent ground cover. Mulch rate shall be determined using current erosion prediction technology to reach the soil erosion objective.

When mulching with wood products such as wood chips, bark, or shavings or other wood materials, apply a minimum 2-inch thickness.

When mulching with gravel or other inorganic material apply a minimum 2 inch thickness and shall consist of pieces 0.75 to 2 inches in diameter.

#### **Additional Criteria to Suppress Weed Growth**

The thickness of mulch will be determined by the size of the plant being mulched. Mulches shall be kept clear of the stems of plants where disease is likely to occur. Mulches applied around growing plants or prior to weed seedling development shall have 100 percent ground cover. Thickness of the mulch shall be adequate to prevent emergence of targeted weeds. Plastic mulches may be used.

#### **Additional Criteria to Establish Vegetative Cover**

Mulch shall be applied at a rate that achieves a minimum of 70 percent ground cover to provide protection from erosion and runoff and yet allow adequate light and air penetration to the seedbed to ensure proper germination and emergence.

#### **Additional Criteria to Improve Soil Quality**

Apply mulch materials with a carbon to nitrogen ratio (C:N) less than 30 to 1 so that soil nitrogen is not immobilized by soil biota. Do not apply mulch with C:N less than 20:1 to an area of designed flow in watercourses.

Use the Soil Conditioning Index to assess soil quality impacts and to determine the type and rate of the mulching material.

#### **Additional Criteria to Reduce Airborne Particulate Matter from Wind Erosion**

Mulch rate shall be determined using current wind erosion prediction technology to reach the soil erosion (movement of particulates offsite) objective.

### **CONSIDERATIONS**

Evaluate the effects of mulching on evaporation, infiltration, and runoff. Mulch material may affect microbial activity in the soil surface, increase infiltration, and decrease runoff, erosion, and evaporation. The temperature of the surface runoff may also be lowered.

Mulch material used to conserve soil moisture should be applied prior to moisture loss. Prior to mulching, ensure soil under shallow rooted crops is moist, as these crops require a constant supply of moisture.

Mulch materials with a high water holding capacity and/or high impermeability to water droplets may adversely affect the water needs of plants.

Fine textured mulches (e.g. rice hulls) which allow less oxygen penetration than coarser materials should be no thicker than 2 inches.

Organic materials with C:N ratios of less than 20:1 will release nitrate-nitrogen which could cause water quality impairments.

Mulching may also provide habitat for beneficial insect and provide pest suppression.

Clear and infra-red transmissible (IRT) plastics have the greatest warming potential. They are transparent to incoming radiation and trap the longer wavelengths radiating from the soil. Black mulches are limited to warming soils by conduction only and are less effective.

Clear mulches allow profuse weed growth and may negate the benefits of soil warming. Black mulches provide effective weed control. Wavelength selective (IRT) plastic provides the soil warming characteristics of clear mulch with the weed control ability of black mulch.

Low permeability mulches (e.g. Plastic) may increase concentrated flow and erosion on un-mulched areas.

Consider potential toxic allelopathic effects that mulch material may have on other organisms. Animal and plant pest species may be incompatible with the site.

Consider the potential for increased pathogenic activity within the applied mulch material.

Keep mulch 3 to 6 inches away from plant stems and crowns to prevent disease and pest problems. Additional weed control may be needed around the plant base area.

Deep mulch provides nesting habitat for ground-burrowing rodents that can chew extensively on tree trunks and/or tree roots.

Some mulch material may adversely affect aquatic environments through changes in water chemistry or as waterborne debris. Consider placing mulch in locations that minimizes these risks.

Consider potential effects of soil physical and chemical properties. Refer to soil survey data as a preliminary planning tool for assessment of areas. Consult the Web Soil Survey at: <http://websoilsurvey.nrcs.usda.gov/app/> to obtain Soil Properties and Qualities information.

### PLANS AND SPECIFICATIONS

Specifications shall be prepared for each site and purpose and recorded using the Pacific Islands Area jobsheet for this practice, technical notes, and other acceptable documentation.

Documentation shall include:

- Purpose of the mulch
- Type of mulch material used
- The percent cover and/or thickness of mulch material
- Timing of application
- Site preparation
- Listing of netting, tackifiers, or method of anchoring, and
- Operation and maintenance.

### OPERATION AND MAINTENANCE

Mulched areas will be periodically inspected, and mulch shall be reinstalled or repaired as needed to accomplish the intended purpose.

Evaluate the effectiveness of the mulch (application, amount of cover provided, durability, etc.) and adjust the management or type of mulch to better meet the intended purpose(s).

Removal or incorporation of mulch materials shall be consistent with the intended purpose and site conditions.

Operation of equipment near and on the site shall not compromise the intended purpose of the mulch.

Prevent or repair any fire damage to the mulch material.

Properly collect and dispose of artificial mulch material after intended use.

Monitor and control undesirable weeds in mulched areas.

The Pacific Islands Area jobsheet for this practice shall be used to record the operation and

maintenance of the practice on the treatment unit, and reviewed with the client.

### REFERENCES

Agriculture and Agri-Food Canada. 2000. Plastic mulches for commercial vegetable production. Canada-Saskatchewan Irrigation Diversification Centre. Outlook, Saskatchewan.

Renard, K.G., G.R. Foster, G.A. Weesies, D.K. McCool, and D.C. Yoder, Coordinators. 1997. Predicting soil erosion by water: A guide to conservation planning with the Revised Universal Soil Loss Equation (RUSLE). U.S. Department of Agriculture, Agriculture Handbook No. 703.

Shaffer, M.J., and W.E. Larson (ed.). 1987. NTRM, a soil-crop simulation model for nitrogen, tillage and crop residue management. USDA Conserv. Res. Rep. 34-1. USDA-ARS.

Toy, T.J., and G.R. Foster. (Ed.) 1998. Guidelines for the use of the Revised Universal Soil Loss Equation (RUSLE) Version 1.06 on mined lands, construction sites, and reclaimed lands. USDI, OSMR.

USDA, NRCS. 2011. National Agronomy Manual. 190-V, 4<sup>th</sup> Ed. Washington, D.C.

USDA Natural Resources Conservation Service, Pacific Islands Area, April 2012. PI Agronomy Technical Note No. 8 – [Mulching Principles and Calculations](#).