

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
1	ADDERTON LOAM, 2 TO 6 PERCENT SLOPES								
		ADDERTON	85	> 72	None	Not limited	Very limited	Moderate	Low
10	BRONELL GRAVELLY SANDY LOAM, 2 TO 15 PERCENT SLOPES								
		BRONELL	85	> 72	None	Somewhat limited	Very limited	Moderately rapid	Low
100	SEDILLO COBBLY SANDY LOAM, 4 TO 25 PERCENT SLOPES								
		SEDILLO	85	> 72	None	Very limited	Very limited	Moderate	Medium
101	SEDILLO VERY GRAVELLY LOAM, 1 TO 5 PERCENT SLOPES								
		SEDILLO	90	> 72	None	Somewhat limited	Very limited	Moderate	Low
102	SEITZ GRAVELLY FINE SANDY LOAM, 20 TO 40 PERCENT SLOPES								
		SEITZ	90	> 72	None	Very limited	Very limited	Slow	Very high
103	SEITZ-BUSHVALLEY COMPLEX, 15 TO 50 PERCENT SLOPES								
		SEITZ	65	> 72	None	Very limited	Very limited	Slow	Very high
		BUSHVALLEY	20	> 72	None	Very limited	Very limited	Slow	Very high
104	SHANTA LOAM, 0 TO 3 PERCENT SLOPES								
		SHANTA	85	> 72	Rare	Very limited	Very limited	Moderate	Low
105	SHANTA LOAM, DRY, 0 TO 3 PERCENT SLOPES								
		SHANTA, DRY	85	> 72	Rare	Very limited	Somewhat limited	Moderate	Low
106	SHANTA-NEDERLAND ASSOCIATION								
		SHANTA	70	> 72	Rare	Very limited	Somewhat limited	Moderate	Low
		NEDERLAND ASSOCIATION	15	> 72	None	Very limited	Very limited	Moderate	High
107	SHINGLE VERY COBBLY SANDY LOAM, 10 TO 40 PERCENT SLOPES								
		SHINGLE	85	> 72	None	Very limited	Very limited	Slow	Very high
108	SHINGLE LOAM, 3 TO 20 PERCENT SLOPES								
		SHINGLE	90	> 72	None	Very limited	Very limited	Slow	Very high
109	SHRINE LOAM, 2 TO 8 PERCENT SLOPES								
		SHRINE	95	> 72	None	Somewhat limited	Somewhat limited	Moderate	Medium
11	BRONELL-KERHAYDEN COMPLEX, 10 TO 40 PERCENT SLOPES								
		BRONELL	50	> 72	None	Very limited	Very limited	Moderate	High
		KERHAYDEN	40	> 72	None	Very limited	Very limited	Moderate	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
110	SWISSVALE-RENTSAC COMPLEX, 20 TO 55 PERCENT SLOPES								
		SWISSVALE	45	> 72	None	Very limited	Very limited	Slow	Very high
		RENTSAC	35	> 72	None	Very limited	Very limited	Slow	Very high
111	TEASPOON VERY GRAVELLY SANDY LOAM, 15 TO 45 PERCENT SLOPES								
		TEASPOON	80	> 72	None	Very limited	Very limited	Slow	Very high
112	TECOLOTE VERY GRAVELLY SANDY LOAM, 15 TO 40 PERCENT SLOPES								
		TECOLOTE	85	> 72	None	Very limited	Very limited	Moderate	High
113	TECOLOTE VERY COBBLY SANDY LOAM, 5 TO 20 PERCENT SLOPES								
		TECOLOTE	90	> 72	None	Somewhat limited	Very limited	Moderate	Medium
114	TELLURA GRAVELLY CLAY LOAM, 4 TO 25 PERCENT SLOPES								
		TELLURA	90	> 72	None	Very limited	Very limited	Slow	Very high
115	TOLEX VERY GRAVELLY SANDY LOAM, 15 TO 40 PERCENT SLOPES								
		TOLEX	85	> 72	None	Very limited	Very limited	Slow	Very high
116	TOLEX-LARKSON COMPLEX, WARM, 25 TO 50 PERCENT SLOPES								
		TOLEX, WARM	45	> 72	None	Very limited	Very limited	Slow	Very high
		LARKSON, WARM	40	> 72	None	Very limited	Very limited	Slow	Very high
117	TRAVESSILLA CHANNERY LOAM, 5 TO 20 PERCENT SLOPES								
		TRAVESSILLA	85	> 72	None	Very limited	Very limited	Slow	Very high
118	TRAVESSILLA-ROCK OUTCROP COMPLEX, 5 TO 50 PERCENT SLOPES								
		TRAVESSILLA	55	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
119	TROUTDALE-ROBERT, WARM, COMPLEX, 2 TO 15 PERCENT SLOPES								
		TROUTDALE	65	> 72	None	Somewhat limited	Very limited	Moderate	Medium
		ROBERT, WARM	20	> 72	None	Very limited	Very limited	Slow	Very high
12	BRONELL VARIANT-WESIX-ROCK OUTCROP COMPLEX, 30 TO 60 PERCENT SLOPES								
		BRONELL VARIANT	60	> 72	None	Very limited	Very limited	Moderate	High
		WESIX	20	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	15	> 72	None	Very limited	Very limited	Very slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
120	USTIC TORRIORTHENTS, BOULDERY-ROCK OUTCROP COMPLEX, 35 TO 90 PERCENT SLOPES								
		USTIC TORRIORTHENTS	55	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
121	USTIC TORRIORTHENTS-SEDILLO COMPLEX, 15 TO 40 PERCENT SLOPES								
		USTIC TORRIORTHENTS	70	> 72	None	Very limited	Very limited	Moderately slow	Very high
		SEDILLO	20	> 72	None	Very limited	Very limited	Moderate	High
122	WAGES LOAM, 2 TO 9 PERCENT SLOPES								
		WAGES	90	> 72	None	Not limited	Somewhat limited	Moderate	Medium
123	WAHATOYA-TOLEX COMPLEX, 25 TO 55 PERCENT SLOPES								
		WAHATOYA	50	> 72	None	Very limited	Very limited	Slow	High
		TOLEX	30	> 72	None	Very limited	Very limited	Slow	Very high
124	WANN-SHANTA, DRY, ASSOCIATION								
		WANN	55	24-72	Occasional	Very limited	Very limited	Moderately rapid	Very low
		SHANTA ASSOCIATION, DRY	35	> 72	Rare	Very limited	Somewhat limited	Moderate	Low
125	WESIX VERY CHANNERY LOAM, 5 TO 40 PERCENT SLOPES								
		WESIX	90	> 72	None	Very limited	Very limited	Slow	Very high
126	WETMORE-BUNDO, DRY-ROCK OUTCROP COMPLEX, 35 TO 75 PERCENT SLOPES								
		WETMORE	40	> 72	None	Very limited	Very limited	Slow	Very high
		BUNDO, DRY	30	> 72	None	Very limited	Very limited	Moderate	Medium
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
127	WETMORE-ROCK OUTCROP COMPLEX, 40 TO 80 PERCENT SLOPES								
		WETMORE	50	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	35	> 72	None	Very limited	Very limited	Very slow	Very high
128	WILEY LOAM, COOL, 2 TO 6 PERCENT SLOPES								
		WILEY, COOL	90	> 72	None	Not limited	Somewhat limited	Moderate	Low
129	WILEY SILT LOAM, 1 TO 6 PERCENT SLOPES								
		WILEY	95	> 72	None	Not limited	Somewhat limited	Moderate	Low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
13	BUNDO VERY COBBLY SANDY LOAM, 30 TO 60 PERCENT SLOPES								
	BUNDO		75	> 72	None	Very limited	Very limited	Moderate	Medium
130	YOUGA SANDY LOAM, 3 TO 10 PERCENT SLOPES								
	YOUGA		90	> 72	None	Not limited	Very limited	Moderately slow	High
14	BUSHVALLEY COBBLY LOAM, 5 TO 40 PERCENT SLOPES								
	BUSHVALLEY		80	> 72	None	Very limited	Very limited	Slow	Very high
15	BUSHVALLEY-WHITEMAN COBBLY LOAMS, 15 TO 50 PERCENT SLOPES								
	BUSHVALLEY		65	> 72	None	Very limited	Very limited	Slow	Very high
	WHITEMAN		20	> 72	None	Very limited	Very limited	Slow	Very high
16	CASCAJO VERY GRAVELLY SANDY LOAM, 10 TO 40 PERCENT SLOPES								
	CASCAJO		80	> 72	None	Very limited	Very limited	Moderately rapid	Medium
17	CASCAJO VARIANT GRAVELLY SANDY LOAM, 5 TO 12 PERCENT SLOPES								
	CASCAJO VARIANT		100	> 72	None	Somewhat limited	Very limited	Moderately rapid	Low
18	CASVARE-TEASPOON COMPLEX, 20 TO 50 PERCENT SLOPES								
	CASVARE		45	> 72	None	Very limited	Very limited	Slow	High
	TEASPOON		35	> 72	None	Very limited	Very limited	Slow	Very high
19	CATHEDRAL-ROCK OUTCROP COMPLEX, 45 TO 80 PERCENT SLOPES								
	CATHEDRAL		75	> 72	None	Very limited	Very limited	Slow	Very high
	ROCK OUTCROP		15	> 72	None	Very limited	Very limited	Very slow	Very high
2	AMALIA VERY GRAVELLY LOAM, 25 TO 50 PERCENT SLOPES								
	AMALIA		75	> 72	None	Very limited	Very limited	Moderately slow	Very high
20	CERRILLOS GRAVELLY SANDY LOAM, 3 TO 8 PERCENT SLOPES								
	CERRILLOS		95	> 72	None	Not limited	Very limited	Moderate	Medium
21	CHITTUM SANDY LOAM, DRY, 5 TO 20 PERCENT SLOPES								
	CHITTUM, DRY		85	> 72	None	Very limited	Very limited	Slow	Very high
22	COALDALE VERY GRAVELLY SANDY LOAM, 20 TO 45 PERCENT SLOPES								
	COALDALE		90	> 72	None	Very limited	Very limited	Slow	Very high
23	COCHETOPA CLAY LOAM, 2 TO 6 PERCENT SLOPES								
	COCHETOPA		95	> 72	None	Not limited	Somewhat limited	Moderately slow	Medium

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
24	CORPENING GRAVELLY LOAM, 5 TO 25 PERCENT SLOPES								
		CORPENING	80	> 72	None	Very limited	Very limited	Slow	Very high
25	CRYOBOROLLS, 15 TO 35 PERCENT SLOPES								
		CRYOBOROLLS	90	> 72	None	Very limited	Very limited	Moderate	Medium
26	CUMULIC CRYAQUOLLS, 2 TO 5 PERCENT SLOPES								
		CUMULIC CRYAQUOLLS	95	9-72	Occasional	Very limited	Very limited	Moderately slow	Medium
27	CURECANTI GRAVELLY SANDY LOAM, 4 TO 10 PERCENT SLOPES								
		CURECANTI	100	> 72	None	Somewhat limited	Very limited	Moderate	Medium
28	CURECANTI VERY COBBLY SANDY LOAM, 15 TO 45 PERCENT SLOPES								
		CURECANTI	90	> 72	None	Very limited	Very limited	Moderate	High
29	CURECANTI VARIANT EXTREMELY COBBLY LOAM, 8 TO 20 PERCENT SLOPES, VERY STONY								
		CURECANTI VARIANT	90	> 72	None	Somewhat limited	Very limited	Slow	Very high
3	AQUIC USTIFLUVENTS								
		AQUIC USTIFLUVENTS	80	30-72	Occasional	Very limited	Very limited	Moderately rapid	Very low
30	DUMPS AND PITS								
		DUMPS AND PITS	90	> 72	None	Very limited	Very limited	Moderate	High
31	ESS VERY GRAVELLY SANDY CLAY LOAM, 20 TO 45 PERCENT SLOPES								
		ESS	85	> 72	None	Very limited	Very limited	Moderately slow	Very high
32	ESS VERY GRAVELLY LOAM, 30 TO 50 PERCENT SLOPES								
		ESS	85	> 72	None	Very limited	Very limited	Moderately slow	Very high
33	ESS-BUSHVALLEY COMPLEX, 10 TO 45 PERCENT SLOPES								
		ESS	55	> 72	None	Very limited	Very limited	Moderately slow	Very high
		BUSHVALLEY	35	> 72	None	Very limited	Very limited	Slow	Very high
34	FORT COLLINS LOAM, 1 TO 4 PERCENT SLOPES								
		FORT COLLINS	100	> 72	None	Not limited	Somewhat limited	Moderate	Low
35	FORT COLLINS LOAM, COOL, 0 TO 2 PERCENT SLOPES								
		FORT COLLINS, COOL	95	> 72	None	Not limited	Somewhat limited	Moderate	Low
36	FORT COLLINS LOAM, COOL, 2 TO 5 PERCENT SLOPES								
		FORT COLLINS, COOL	100	> 72	None	Not limited	Somewhat limited	Moderate	Low
37	FORT COLLINS VARIANT LOAM, 3 TO 8 PERCENT SLOPES								
		FORT COLLINS VARIANT	95	> 72	None	Not limited	Somewhat limited	Moderately slow	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
38	GRANILE VERY GRAVELLY SANDY LOAM, 4 TO 25 PERCENT SLOPES								
	GRANILE		85	> 72	None	Very limited	Very limited	Moderate	Medium
39	GRANILE VERY GRAVELLY SANDY LOAM, 25 TO 45 PERCENT SLOPES								
	GRANILE		85	> 72	None	Very limited	Very limited	Moderate	High
4	AQUOLLS, 0 TO 5 PERCENT SLOPES								
	AQUOLLS		100	12-72	Frequent	Very limited	Very limited	Moderately rapid	Very low
40	GRANILE-GUFFEY VERY GRAVELLY SANDY LOAMS, 25 TO 50 PERCENT SLOPES								
	GRANILE		50	> 72	None	Very limited	Very limited	Moderate	High
	GUFFY		35	> 72	None	Very limited	Very limited	Moderate	Medium
41	HAPLOBOROLLS, VERY STONY-ROCK OUTCROP COMPLEX, 40 TO 90 PERCENT SLOPES								
	HAPLOBOROLLS		60	> 72	None	Very limited	Very limited	Moderate	High
	ROCK OUTCROP		25	> 72	None	Very limited	Very limited	Very slow	Very high
42	HEATH COBBLY LOAM, 5 TO 30 PERCENT SLOPES								
	HEATH		85	> 72	None	Very limited	Very limited	Very slow	Very high
43	HERAKLE-ROCK OUTCROP COMPLEX, 15 TO 45 PERCENT SLOPES								
	HERAKLE		65	> 72	None	Very limited	Very limited	Slow	Very high
	ROCK OUTCROP		20	> 72	None	Very limited	Very limited	Very slow	Very high
44	HODDEN GRAVELLY LOAM, 3 TO 8 PERCENT SLOPES								
	HODDEN		95	> 72	None	Not limited	Very limited	Moderate	Medium
45	HOODLE LOAM, 5 TO 20 PERCENT SLOPES								
	HOODLE		85	> 72	None	Somewhat limited	Very limited	Moderately slow	High
46	JODERO SANDY LOAM, 2 TO 5 PERCENT SLOPES								
	JODERO		90	> 72	None	Not limited	Very limited	Moderate	Low
47	JODERO VARIANT CLAY LOAM, 1 TO 3 PERCENT SLOPES								
	JODERO VARIANT		95	> 72	Rare	Very limited	Somewhat limited	Moderately slow	Medium
48	KIM LOAM, 0 TO 3 PERCENT SLOPES								
	KIM		95	> 72	None	Not limited	Somewhat limited	Moderate	Low
49	KIM LOAM, 3 TO 8 PERCENT SLOPES								
	KIM		90	> 72	None	Not limited	Somewhat limited	Moderate	Medium

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
5	ARENTS, 10 TO 45 PERCENT SLOPES								
		ARENTS	100	> 72	None	Very limited	Very limited	Moderate	High
50	KIM LOAM, COOL, 3 TO 8 PERCENT SLOPES								
		KIM, COOL	95	> 72	None	Not limited	Somewhat limited	Moderate	Medium
51	KIM LOAM, MODERATELY WET, 0 TO 3 PERCENT SLOPES								
		KIM, MODERATELY WET	95	48-72	None	Somewhat limited	Somewhat limited	Moderate	Low
52	KIM-CASCAJO COMPLEX, 2 TO 15 PERCENT SLOPES								
		KIM	50	> 72	None	Not limited	Somewhat limited	Moderate	Medium
		CASCAJO	35	> 72	None	Very limited	Very limited	Moderately rapid	Low
53	KIM-SHINGLE COMPLEX, 3 TO 20 PERCENT SLOPES								
		KIM	60	> 72	None	Somewhat limited	Very limited	Moderate	Medium
		SHINGLE	35	> 72	None	Very limited	Very limited	Slow	Very high
54	LAKEHELEN-ROCK OUTCROP COMPLEX, 45 TO 80 PERCENT SLOPES								
		LAKEHELEN	45	> 72	None	Very limited	Very limited	Slow	High
		ROCK OUTCROP	35	> 72	None	Very limited	Very limited	Very slow	Very high
55	LARAND VERY GRAVELLY FINE SANDY LOAM, 10 TO 40 PERCENT SLOPES								
		LARAND	75	> 72	None	Very limited	Very limited	Moderate	High
56	LARKSON STONY LOAM, 5 TO 20 PERCENT SLOPES								
		LARKSON	90	> 72	None	Very limited	Very limited	Slow	Very high
57	LIBEG EXTREMELY COBBLY SANDY LOAM, 10 TO 20 PERCENT SLOPES								
		LIBEG	95	> 72	None	Very limited	Very limited	Moderate	Medium
58	LIMON SILTY CLAY LOAM, SALINE								
		LIMON, SALINE	95	> 72	Rare	Very limited	Somewhat limited	Slow	High
59	LIMON SILTY CLAY LOAM, MODERATELY WET, 0 TO 2 PERCENT SLOPES								
		LIMON, MODERATELY WET	100	36-39	None	Very limited	Very limited	Slow	High
6	BLOOM LOAM, 0 TO 2 PERCENT SLOPES								
		BLOOM	100	21-72	Occasional	Very limited	Very limited	Moderate	Low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
60	LIMON SILTY CLAY LOAM, MODERATELY WET, RARELY FLOODED, 0 TO 1 PERCENT SLOPES								
		LIMON, MODERATELY WET	95	36-39	Rare	Very limited	Very limited	Slow	High
61	LIMON-GAYNOR SILTY CLAY LOAMS, 0 TO 3 PERCENT SLOPES								
		LIMON	70	> 72	None	Very limited	Somewhat limited	Slow	High
		GAYNOR	30	> 72	None	Very limited	Very limited	Slow	High
62	LIMON-GAYNOR SILTY CLAY LOAMS, 3 TO 12 PERCENT SLOPES								
		LIMON	55	> 72	None	Very limited	Very limited	Slow	Very high
		GAYNOR	35	> 72	None	Very limited	Very limited	Slow	Very high
63	LIMON-GAYNOR SILTY CLAY LOAMS, MODERATELY WET, 0 TO 3 PERCENT SLOPES								
		LIMON, MODERATELY WET	65	36-39	None	Very limited	Very limited	Slow	High
		GAYNOR, MODERATELY WET	35	33-36	None	Very limited	Very limited	Slow	High
64	LOUVIERS-TRAVESSILLA COMPLEX, 20 TO 50 PERCENT SLOPES								
		LOUVIERS	40	> 72	None	Very limited	Very limited	Slow	Very high
		TRAVESSILLA	35	> 72	None	Very limited	Very limited	Slow	Very high
65	MANVEL SILT LOAM, 0 TO 3 PERCENT SLOPES								
		MANVEL	95	> 72	None	Not limited	Not limited	Moderately slow	Medium
66	MANVEL SILT LOAM, 3 TO 8 PERCENT SLOPES								
		MANVEL	90	> 72	None	Not limited	Somewhat limited	Moderately slow	High
67	MANVEL SILTY CLAY LOAM, SALINE								
		MANVEL, SALINE	95	> 72	None	Not limited	Not limited	Moderately slow	Medium
68	MANZANOLA LOAM, 1 TO 5 PERCENT SLOPES								
		MANZANOLA	90	> 72	None	Somewhat limited	Somewhat limited	Slow	High
69	MARTINSDALE SANDY LOAM, 3 TO 12 PERCENT SLOPES								
		MARTINSDALE	90	> 72	None	Not limited	Very limited	Moderately slow	High
7	BOYLE VERY GRAVELLY SANDY LOAM, 10 TO 40 PERCENT SLOPES								
		BOYLE	85	> 72	None	Very limited	Very limited	Moderate	High
70	MARTINSDALE VARIANT SANDY LOAM, 2 TO 5 PERCENT SLOPES								
		MARTINSDALE VARIANT	100	> 72	None	Not limited	Very limited	Moderately slow	Low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
71	MIDWAY CLAY LOAM, 3 TO 15 PERCENT SLOPES								
		MIDWAY	85	> 72	None	Very limited	Very limited	Slow	Very high
72	MIDWAY-CASCAJO COMPLEX, 10 TO 40 PERCENT SLOPES								
		MIDWAY	60	> 72	None	Very limited	Very limited	Slow	Very high
		CASCAJO	20	> 72	None	Very limited	Very limited	Moderately rapid	Medium
73	MORSET LOAM, 2 TO 8 PERCENT SLOPES								
		MORSET	90	> 72	None	Not limited	Very limited	Moderately slow	High
74	MUSSEL-BRONELL COMPLEX, 2 TO 15 PERCENT SLOPES								
		MUSSEL	60	> 72	None	Not limited	Very limited	Moderate	Low
		BRONELL	40	> 72	None	Somewhat limited	Very limited	Moderately rapid	Low
75	NEVILLE FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES								
		NEVILLE	95	> 72	None	Not limited	Somewhat limited	Moderate	Medium
76	NUNN STONY LOAM, 3 TO 8 PERCENT SLOPES								
		NUNN	95	> 72	None	Not limited	Somewhat limited	Slow	Very high
77	NUNN LOAM, 2 TO 5 PERCENT SLOPES								
		NUNN	95	> 72	None	Not limited	Somewhat limited	Slow	High
78	NUNN CLAY LOAM, 0 TO 2 PERCENT SLOPES								
		NUNN	85	> 72	None	Somewhat limited	Somewhat limited	Slow	High
79	NUNN CLAY LOAM, 2 TO 8 PERCENT SLOPES								
		NUNN	90	> 72	None	Not limited	Somewhat limited	Slow	Very high
8	BOYLE-MARTINSDALE COMPLEX, 3 TO 20 PERCENT SLOPES								
		BOYLE	45	> 72	None	Very limited	Very limited	Moderate	Medium
		MARTINSDALE	40	> 72	None	Not limited	Very limited	Moderately slow	High
80	OTERO LOAMY FINE SAND, 3 TO 8 PERCENT SLOPES								
		OTERO	95	> 72	None	Not limited	Very limited	Moderately rapid	Low
81	OTERO FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES								
		OTERO	95	> 72	None	Not limited	Very limited	Moderately rapid	Low
82	PENDANT EXTREMELY GRAVELLY LOAM, 10 TO 40 PERCENT SLOPES, VERY STONY								
		PENDANT	85	> 72	None	Very limited	Very limited	Slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
83	PENROSE-MINNEQUA COMPLEX, 2 TO 25 PERCENT SLOPES								
		PENROSE	45	> 72	None	Very limited	Very limited	Slow	Very high
		MINNEQUA	40	> 72	None	Somewhat limited	Very limited	Moderate	Medium
84	PENROSE-ROCK OUTCROP COMPLEX, 25 TO 40 PERCENT SLOPES								
		PENROSE	60	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
85	QUERIDA GRAVELLY SANDY LOAM, 2 TO 8 PERCENT SLOPES								
		QUERIDA	90	> 72	None	Not limited	Very limited	Moderately rapid	Low
86	RALEIGH-ROCK OUTCROP COMPLEX, 15 TO 40 PERCENT SLOPES								
		RALEIGH	70	> 72	None	Very limited	Very limited	Moderate	High
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
87	REDCAMERON-ROCK OUTCROP-TEASPOON COMPLEX, 20 TO 70 PERCENT SLOPES								
		REDCAMERON	30	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
		TEASPOON	20	> 72	None	Very limited	Very limited	Slow	Very high
88	RENTSAC VERY CHANNERY LOAM, 20 TO 55 PERCENT SLOPES								
		RENTSAC	80	> 72	None	Very limited	Very limited	Slow	Very high
89	RENTSAC VARIANT CHANNERY LOAM, 5 TO 25 PERCENT SLOPES								
		RENTSAC VARIANT	90	> 72	None	Very limited	Very limited	Slow	Very high
9	BOYLE-ROCK OUTCROP COMPLEX, 40 TO 60 PERCENT SLOPES								
		BOYLE, WARM	60	> 72	None	Very limited	Very limited	Moderate	High
		ROCK OUTCROP	25	> 72	None	Very limited	Very limited	Very slow	Very high
90	RESORT VERY GRAVELLY SANDY LOAM, 20 to 45 PERCENT SLOPES								
		RESORT	90	> 72	None	Very limited	Very limited	Moderate	High
91	RESORT-ROCK OUTCROP COMPLEX, 30 TO 60 PERCENT SLOPES								
		RESORT	60	> 72	None	Very limited	Very limited	Moderate	High
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
92	RIVERWASH								
		RIVERWASH	90	12-72	Frequent	Very limited	Very limited	Rapid	Negligible

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
93	RIZOZO-NEVILLE COMPLEX, 3 TO 30 PERCENT SLOPES								
		RIZOZO	50	> 72	None	Very limited	Very limited	Slow	Very high
		NEVILLE	40	> 72	None	Not limited	Very limited	Moderate	Medium
94	RIZOZO-ROCK OUTCROP COMPLEX, 15 TO 45 PERCENT SLOPES								
		RIZOZO	70	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
95	ROCK OUTCROP								
		ROCK OUTCROP	95	> 72	None	Very limited	Very limited	Very slow	Very high
96	ROGERT VERY GRAVELLY SANDY LOAM, WARM, 10 TO 40 PERCENT SOUTH SLOPES								
		ROGERT	85	> 72	None	Very limited	Very limited	Slow	Very high
97	ROGERT VERY GRAVELLY SANDY LOAM, WARM, 15 TO 40 PERCENT SLOPES								
		ROGERT, WARM	80	> 72	None	Very limited	Very limited	Slow	Very high
98	ROYGORGE VERY GRAVELLY SANDY CLAY LOAM, 25 TO 50 PERCENT SLOPES								
		ROYGORGE	85	> 72	None	Very limited	Very limited	Slow	Very high
99	SAWFORK VERY COBBLY LOAM, 8 TO 40 PERCENT SLOPES								
		SAWFORK	90	> 72	None	Very limited	Very limited	Moderately slow	Very high