

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
1	ALAMOSA LOAM, 0 TO 6 PERCENT SLOPES								
		ALAMOSA	100	15-72	Frequent	Very limited	Very limited	Moderately slow	Medium
10	CONDIE COARSE SANDY LOAM, 2 TO 15 PERCENT SLOPES								
		CONDIE	100	> 72	None	Somewhat limited	Very limited	Very slow	Very high
11	CONDIE COARSE SANDY LOAM, 15 TO 40 PERCENT SLOPES								
		CONDIE	100	> 72	None	Very limited	Very limited	Moderate	High
12	FORTWINGATE-ROCK OUTCROP COMPLEX, 15 TO 60 PERCENT SLOPES								
		FORTWINGATE	40	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
13	GARBER VERY GRAVELLY COARSE SANDY LOAM, 2 TO 15 PERCENT SLOPES								
		GARBER	100	> 72	None	Somewhat limited	Very limited	Moderate	Low
14	GARBER VERY GRAVELLY COARSE SANDY LOAM, 15 TO 40 PERCENT SLOPES								
		GARBER	100	> 72	None	Very limited	Very limited	Moderate	Medium
15	GUFFEY VERY GRAVELLY SANDY LOAM, 5 TO 40 PERCENT SLOPES								
		GUFFEY	100	> 72	None	Very limited	Very limited	Very slow	Very high
16	GUFFEY VERY GRAVELLY SANDY LOAM, 40 TO 60 PERCENT SLOPES								
		GUFFEY	100	> 72	None	Very limited	Very limited	Very slow	Very high
17	HERBMAN VERY GRAVELLY SANDY LOAM, 15 TO 40 PERCENT SLOPES								
		HERBMAN	100	> 72	None	Very limited	Very limited	Moderate	High
18	HERBMAN-ROCK OUTCROP COMPLEX, 15 TO 40 PERCENT SLOPES								
		HERBMAN	60	> 72	None	Very limited	Very limited	Moderate	High
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
19	IVYWILD GRAVELLY SANDY LOAM, 5 TO 40 PERCENT SLOPES								
		IVYWILD	100	> 72	None	Very limited	Very limited	Very slow	High
2	AQUOLLS, 1 TO 10 PERCENT SLOPES								
		AQUOLLS	100	12-72	Frequent	Very limited	Very limited	Moderately rapid	Low
20	IVYWILD GRAVELLY SANDY LOAM, 40 TO 70 PERCENT SLOPES								
		IVYWILD	100	> 72	None	Very limited	Very limited	Very slow	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
21	IVYWILD-CATAMOUNT GRAVELLY SANDY LOAMS, 5 TO 70 PERCENT SLOPES,								
		IVYWILD	50	> 72	None	Very limited	Very limited	Moderate	High
		CATAMOUNT	35	> 72	None	Very limited	Very limited	Moderate	High
22	KASSLER VERY GRAVELLY COARSE SANDY LOAM, 5 TO 35 PERCENT SLOPES								
		KASSLER	100	> 72	None	Very limited	Very limited	Moderately rapid	Medium
23	KUTCH CLAY LOAM, 10 TO 40 PERCENT SLOPES								
		KUTCH	100	> 72	None	Very limited	Very limited	Very slow	Very high
24	LEGAULT VERY GRAVELLY COARSE SANDY LOAM, 5 TO 40 PERCENT SLOPES								
		LEGAULT	100	> 72	None	Very limited	Very limited	Very slow	Very high
25	LEGAULT VERY GRAVELLY COARSE SANDY LOAM, 40 TO 65 PERCENT SLOPES								
		LEGAULT	100	> 72	None	Very limited	Very limited	Moderately rapid	Medium
26	LEGAULT-ROCK OUTCROP COMPLEX, 15 TO 65 PERCENT SLOPES								
		LEGAULT	50	> 72	None	Very limited	Very limited	Very slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
27	PALBOONE-SECURITY COMPLEX, 15 TO 40 PERCENT SLOPES								
		PALBOONE	50	> 72	None	Very limited	Very limited	Moderately rapid	Medium
		SECURITY	30	> 72	None	Very limited	Very limited	Very slow	High
28	PALBOONE-SECURITY COMPLEX, 40 TO 70 PERCENT SLOPES								
		PALBOONE	50	> 72	None	Very limited	Very limited	Moderately rapid	Medium
		SECURITY	30	> 72	None	Very limited	Very limited	Very slow	High
29	PENDANT COBBLY LOAM, 15 TO 40 PERCENT SLOPES								
		PENDANT	100	> 72	None	Very limited	Very limited	Very slow	Very high
3	BOYETT-FRENCHCREEK COMPLEX, 2 TO 15 PERCENT SLOPES								
		BOYETT	50	> 72	None	Somewhat limited	Very limited	Moderately rapid	Low
		FRENCHCREEK	35	> 72	None	Somewhat limited	Very limited	Moderately rapid	Low
30	PENDANT COBBLY LOAM, 40 TO 70 PERCENT SLOPES								
		PENDANT	100	> 72	None	Very limited	Very limited	Very slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
31	PENDANT-ROCK OUTCROP COMPLEX, 15 TO 70 PERCENT SLOPES								
		PENDANT	60	> 72	None	Very limited	Very limited	Very slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
32	PERRY PARK COARSE SANDY LOAM, 1 TO 15 PERCENT SLOPES								
		PERRY PARK	100	> 72	None	Somewhat limited	Very limited	Moderate	Medium
33	ROCK OUTCROP-CATAMOUNT COMPLEX, 15 TO 70 PERCENT SLOPES								
		ROCK OUTCROP	45	> 72	None	Very limited	Very limited	Very slow	Very high
		CATAMOUNT	40	> 72	None	Very limited	Very limited	Very slow	Very high
34	ROCK OUTCROP-SECURITY-CATHEDRAL COMPLEX, 15 TO 65 PERCENT SLOPES								
		ROCK OUTCROP	40	> 72	None	Very limited	Very limited	Very slow	Very high
		SECURITY	30	> 72	None	Very limited	Very limited	Very slow	High
		CATHEDRAL	25	> 72	None	Very limited	Very limited	Very slow	Very high
35	ROCK OUTCROP-SPHINX COMPLEX, 15 TO 80 PERCENT SLOPES								
		ROCK OUTCROP	45	> 72	None	Very limited	Very limited	Very slow	Very high
		SPHINX	40	> 72	None	Very limited	Very limited	Very slow	Very high
36	ROCK OUTCROP-SPHINX, WARM COMPLEX, 15 TO 80 PERCENT SLOPES								
		ROCK OUTCROP	45	> 72	None	Very limited	Very limited	Very slow	Very high
		SPHINX	40	> 72	None	Very limited	Very limited	Very slow	Very high
37	SACHETT-ROCK OUTCROP COMPLEX, 5 TO 70 PERCENT SLOPES								
		SACHETT	70	> 72	None	Very limited	Very limited	Very slow	Very high
		ROCK OUTCROP	25	> 72	None	Very limited	Very limited	Very slow	Very high
38	SECURITY VERY GRAVELLY COARSE SANDY LOAM, 5 TO 40 PERCENT SLOPES								
		SECURITY	100	> 72	None	Very limited	Very limited	Very slow	High
39	SECURITY VERY GRAVELLY COARSE SANDY LOAM, 40 TO 65 PERCENT SLOPES								
		SECURITY	100	> 72	None	Very limited	Very limited	Very slow	High
4	BOYETT-FRENCHCREEK COMPLEX, 15 TO 40 PERCENT SLOPES								
		BOYETT	50	> 72	None	Very limited	Very limited	Very slow	Medium
		FRENCHCREEK	30	> 72	None	Very limited	Very limited	Moderately rapid	Low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
40	SECURITY-CATHEDRAL COMPLEX, 40 TO 65 PERCENT SLOPES, VERY STONY								
		SECURITY	55	> 72	None	Very limited	Very limited	Very slow	High
		CATHEDRAL	30	> 72	None	Very limited	Very limited	Very slow	Very high
41	SECURITY-CATHEDRAL-ROCK OUTCROP COMPLEX, 15 TO 65 PERCENT SLOPES VERY STONY								
		SECURITY	40	> 72	None	Very limited	Very limited	Very slow	High
		CATHEDRAL	30	> 72	None	Very limited	Very limited	Very slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
42	SPHINX GRAVELLY COARSE SANDY LOAM, 15 TO 40 PERCENT SLOPES								
		SPHINX	100	> 72	None	Very limited	Very limited	Very slow	Very high
43	SPHINX GRAVELLY COARSE SANDY LOAM, 40 TO 70 PERCENT SLOPES								
		SPHINX	100	> 72	None	Very limited	Very limited	Very slow	Very high
44	SPHINX GRAVELLY COARSE SANDY LOAM, WARM, 15 TO 40 PERCENT SLOPES								
		SPHINX	100	> 72	None	Very limited	Very limited	Very slow	Very high
45	SPHINX GRAVELLY COARSE SANDY LOAM, WARM, 40 TO 70 PERCENT SLOPES								
		SPHINX	100	> 72	None	Very limited	Very limited	Very slow	Very high
46	SPHINX-ROCK OUTCROP COMPLEX, 15 TO 80 PERCENT SLOPES								
		SPHINX	60	> 72	None	Very limited	Very limited	Very slow	Very high
		ROCK OUTCROP	25	> 72	None	Very limited	Very limited	Very slow	Very high
47	SPHINX, WARM-ROCK OUTCROP COMPLEX, 15 TO 80 PERCENT SLOPES								
		SPHINX	60	> 72	None	Very limited	Very limited	Very slow	Very high
		ROCK OUTCROP	25	> 72	None	Very limited	Very limited	Very slow	Very high
48	TECOLOTE VERY GRAVELLY SANDY LOAM, 15 TO 40 PERCENT SLOPES, VERY STONY								
		TECOLOTE	100	> 72	None	Very limited	Very limited	Very slow	Medium
49	TECOLOTE VERY GRAVELLY SANDY LOAM, 40 TO 70 PERCENT SLOPES, VERY STONY								
		TECOLOTE	100	> 72	None	Very limited	Very limited	Very slow	Medium
5	CATAMOUNT GRAVELLY SANDY LOAM, 5 TO 40 PERCENT SLOPES								
		CATAMOUNT	100	> 72	None	Very limited	Very limited	Rapid	Low
50	TOMAH SANDY LOAM, 2 TO 15 PERCENT SLOPES								
		TOMAH	100	> 72	None	Somewhat limited	Very limited	Moderate	Medium

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
51	TRIPIT LOAM, 5 TO 15 PERCENT SLOPES								
		TRIPIT	100	> 72	None	Somewhat limited	Very limited	Very slow	High
6	CATAMOUNT GRAVELLY SANDY LOAM, 40 TO 70 PERCENT SLOPES								
		CATAMOUNT	100	> 72	None	Very limited	Very limited	Very slow	Very high
7	CATAMOUNT-ROCK OUTCROP COMPLEX, 15 TO 70 PERCENT SLOPES								
		CATAMOUNT	60	> 72	None	Very limited	Very limited	Very slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
8	CATHEDRAL GRAVELLY SANDY LOAM, 40 TO 65 PERCENT SLOPES, EXTREMELY STONY								
		CATHEDRAL	100	> 72	None	Very limited	Very limited	Slow	Very high
9	CIRQUE LAND, 15 TO 75 PERCENT SLOPES								
		CIRQUE LAND	100	> 72	None	Very limited	Very limited	Very rapid	Low