

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
1	ABOR CLAY LOAM, 5 TO 30 PERCENT SLOPES								
		ABOR	85	> 72	None	Very limited	Very limited	Very slow	Very high
10	BLAZON, MOIST-RENTSAC COMPLEX, 8 TO 65 PERCENT SLOPES								
		BLAZON, MOIST	50	> 72	None	Very limited	Very limited	Very slow	Very high
		RENTSAC	35	> 72	None	Very limited	Very limited	Very slow	Very high
100	WORK LOAM, 1 TO 3 PERCENT SLOPES								
		WORK	85	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	Medium
101	WORK LOAM, 3 TO 8 PERCENT SLOPES								
		WORK	85	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	High
102	WORK LOAM, 8 TO 15 PERCENT SLOPES								
		WORK	85	> 72	None	Somewhat limited	Very limited	Moderately slow	High
103	WORK LOAM, 15 TO 25 PERCENT SLOPES								
		WORK	85	> 72	None	Very limited	Very limited	Moderately slow	Very high
104	YAMAC LOAM, 2 TO 15 PERCENT SLOPES								
		YAMAC	85	> 72	None	Somewhat limited	Very limited	Moderate	Medium
105	ZOLTAY CLAY LOAM, 1 TO 3 PERCENT SLOPES								
		ZOLTAY	85	> 72	None	Somewhat limited	Somewhat limited	Slow	High
106	ZOLTAY CLAY LOAM, 3 TO 8 PERCENT SLOPES								
		ZOLTAY	85	> 72	None	Somewhat limited	Somewhat limited	Slow	Very high
107	ZOLTAY CLAY LOAM, 8 TO 15 PERCENT SLOPES								
		ZOLTAY	85	> 72	None	Somewhat limited	Very limited	Slow	Very high
108	ZOLTAY CLAY LOAM, 15 TO 25 PERCENT SLOPES								
		ZOLTAY	85	> 72	None	Very limited	Very limited	Slow	Very high
11	BOROLIC CALCIORTHIDS-GUBEN COMPLEX, 6 TO 50 PERCENT SLOPES								
		BOROLIC CALCIORTHID	60	> 72	None	Very limited	Very limited	Moderately slow	Very high
		GUBEN	30	> 72	None	Somewhat limited	Very limited	Moderate	Medium
12	BUCKLON-INCHAU LOAMS, 25 TO 50 PERCENT SLOPES								
		BUCKLON	55	> 72	None	Very limited	Very limited	Slow	Very high
		INCHAU	35	> 72	None	Very limited	Very limited	Slow	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
13	BULKLEY CHANNERY SILTY CLAY LOAM, 5 TO 30 PERCENT SLOPES								
		BULKLEY	85	> 72	None	Very limited	Very limited	Slow	Very high
14	BULKLEY-ABOR CLAY LOAMS, 5 TO 30 PERCENT SLOPES								
		BULKLEY	60	> 72	None	Very limited	Very limited	Slow	Very high
		ABOR	30	> 72	None	Very limited	Very limited	Very slow	Very high
15	CASTNER CHANNERY LOAM, 5 TO 50 PERCENT SLOPES								
		CASTNER	85	> 72	None	Very limited	Very limited	Very slow	Very high
16	CHIPETA SILTY CLAY LOAM, 3 TO 25 PERCENT SLOPES								
		CHIPETA	85	> 72	None	Very limited	Very limited	Very slow	Very high
17	CHIPETA SILTY CLAY LOAM, 3 TO 25 PERCENT SLOPES, ERODED								
		CHIPETA	85	> 72	None	Very limited	Very limited	Very slow	Very high
18	CHIPETA-KILLPACK SILTY CLAY LOAMS, 3 TO 15 PERCENT SLOPES								
		CHIPETA	60	> 72	None	Very limited	Very limited	Very slow	Very high
		KILLPACK	30	> 72	None	Somewhat limited	Very limited	Very slow	Very high
19	CHIPETA-WALKNOLLS COMPLEX, 5 TO 15 PERCENT SLOPES								
		CHIPETA	40	> 72	None	Very limited	Very limited	Very slow	Very high
		WALKNOLLS	35	> 72	None	Very limited	Very limited	Slow	Very high
2	ABSAROCKE-DELSON CHANNERY LOAMS, 8 TO 65 PERCENT SLOPES								
		ABSAROCKE	55	> 72	None	Very limited	Very limited	Very slow	Very high
		DELSON	35	> 72	None	Very limited	Very limited	Slow	Very high
20	CLAYBURN LOAM, 3 TO 15 PERCENT SLOPES								
		CLAYBURN	85	> 72	None	Somewhat limited	Very limited	Moderate	Medium
21	CLIFFDOWN-CLIFFDOWN VARIANT COMPLEX, 5 TO 65 PERCENT SLOPES								
		CLIFFDOWN	55	> 72	None	Not limited	Very limited	Moderate	Medium
		CLIFFDOWN VARIANT	35	> 72	None	Very limited	Very limited	Moderately slow	Very high
22	CLIFTERSON CHANNERY LOAM, 1 TO 15 PERCENT SLOPES								
		CLIFTERSON	85	> 72	None	Somewhat limited	Very limited	Moderately rapid	Low
23	COCHETOPA LOAM, 9 TO 50 PERCENT SLOPES								
		COCHETOPA	85	> 72	None	Very limited	Very limited	Slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
24	COCHETOPA-JERRY COMPLEX, 12 TO 25 PERCENT SLOPES								
		COCHETOPA	50	> 72	None	Very limited	Very limited	Slow	Very high
		JERRY	40	> 72	None	Very limited	Very limited	Moderate	Medium
25	COLOROW SANDY LOAM								
		COLOROW	85	60-72	Rare	Very limited	Very limited	Moderately rapid	Very low
26	COWDREY-TAMPICO LOAMS, 15 TO 50 PERCENT SLOPES								
		COWDREY	60	> 72	None	Very limited	Very limited	Slow	Very high
		TAMPICO	30	> 72	None	Very limited	Very limited	Moderate	High
27	CURECANTI VERY COBBLY LOAM, 1 TO 8 PERCENT SLOPES								
		CURECANTI	85	> 72	None	Very limited	Very limited	Moderate	Medium
28	DELSON-PERMA COMPLEX, 3 TO 65 PERCENT SLOPES								
		DELSON	60	> 72	None	Somewhat limited	Very limited	Slow	Very high
		PERMA	35	> 72	None	Very limited	Very limited	Moderate	High
29	DOLLARD SILTY CLAY LOAM, 3 TO 8 PERCENT SLOPES								
		DOLLARD	85	> 72	None	Somewhat limited	Very limited	Very slow	Very high
3	ABSHER LOAM, 0 TO 3 PERCENT SLOPES								
		ABSHER	85	> 72	None	Very limited	Somewhat limited	Very slow	Very high
30	DOLLARD SILTY CLAY LOAM, 8 TO 15 PERCENT SLOPES								
		DOLLARD	85	> 72	None	Somewhat limited	Very limited	Very slow	Very high
31	DOLLARD SILTY CLAY LOAM, 15 TO 40 PERCENT SLOPES								
		DOLLARD	90	> 72	None	Very limited	Very limited	Very slow	Very high
32	FLUVAQUENTS, FREQUENTLY FLOODED *								
		FLUVAQUENTS, FRQNTLY FLOODED	85	27-72	Occasional	Very limited	Very limited	Moderate	Low
33	FORELLE LOAM, 3 TO 8 PERCENT SLOPES								
		FORELLE	85	> 72	None	Not limited	Somewhat limited	Moderate	Medium
34	FORELLE LOAM, 8 TO 15 PERCENT SLOPES								
		FORELLE	85	> 72	None	Somewhat limited	Very limited	Moderate	Medium

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
35	GAYNOR-MIDWAY SILTY CLAY LOAMS, DRY, 2 TO 25 PERCENT SLOPES								
		GAYNOR	50	> 72	None	Very limited	Very limited	Slow	Very high
		MIDWAY	35	> 72	None	Very limited	Very limited	Slow	Very high
36	GLEN DIVE FINE SANDY LOAM								
		GLEN DIVE	85	> 72	Rare	Very limited	Very limited	Moderate	Low
37	GLEN TON SANDY LOAM, 1 TO 6 PERCENT SLOPE								
		GLEN TON	85	> 72	Occasional	Very limited	Very limited	Moderately rapid	Very low
38	GUBEN LOAM, 0 TO 3 PERCENT SLOPES								
		GUBEN	90	> 72	None	Somewhat limited	Very limited	Moderate	Low
39	GUBEN LOAM, 3 TO 8 PERCENT SLOPES								
		GUBEN	90	> 72	None	Somewhat limited	Very limited	Moderate	Medium
4	ABSHER LOAM, 3 TO 8 PERCENT SLOPES								
		ABSHER	85	> 72	None	Very limited	Somewhat limited	Very slow	Very high
40	HAGGA LOAM								
		HAGGA	85	18-72	Rare	Very limited	Very limited	Moderately slow	Medium
41	HAVRE LOAM, 0 TO 4 PERCENT SLOPES								
		HAVRE	85	> 72	Rare	Very limited	Somewhat limited	Moderate	Low
42	IRIGUL CHANNERY LOAM, 5 TO 50 PERCENT SLOPES								
		IRIGUL	85	> 72	None	Very limited	Very limited	Very slow	Very high
43	IRIGUL-PARACHUTE COMPLEX, 5 TO 30 PERCENT SLOPES								
		IRIGUL	60	> 72	None	Very limited	Very limited	Very slow	Very high
		PARACHUTE	30	> 72	None	Very limited	Very limited	Slow	High
44	JERRY LOAM, 12 TO 45 PERCENT SLOPES								
		JERRY	85	> 72	None	Very limited	Very limited	Moderate	High
45	JERRY-THORNBURGH-RHONE COMPLEX, 8 TO 65 PERCENT SLOPES								
		JERRY	35	> 72	None	Very limited	Very limited	Moderate	High
		THORNBURGH	30	> 72	None	Very limited	Very limited	Moderate	High
		RHONE	20	> 72	None	Very limited	Very limited	Slow	High
46	KINNEAR FINE SANDY LOAM, 1 TO 5 PERCENT SLOPES								
		KINNEAR	85	> 72	None	Not limited	Somewhat limited	Moderate	Low

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
47	KOBAR SILTY CLAY LOAM, 0 TO 3 PERCENT SLOPES								
		KOBAR	85	> 72	None	Somewhat limited	Somewhat limited	Slow	High
48	KOBAR SILTY CLAY LOAM, 3 TO 8 PERCENT SLOPES								
		KOBAR	85	> 72	None	Somewhat limited	Somewhat limited	Slow	Very high
49	KOBAR SILTY CLAY LOAM, 8 TO 15 PERCENT SLOPES								
		KOBAR	85	> 72	None	Somewhat limited	Very limited	Slow	Very high
5	BADLAND								
		BADLAND	95	> 72	None	Very limited	Very limited	Very slow	Very high
50	LAMPHER-TAMPICO-KAMACK LOAMS, 5 TO 60 PERCENT SLOPES								
		LAMPHER	35	> 72	None	Very limited	Very limited	Moderate	High
		TAMPICO	25	> 72	None	Very limited	Very limited	Moderate	High
		KAMACK	25	> 72	None	Very limited	Very limited	Very slow	High
51	MERGEL-REDTHAYNE-DOLLARD COMPLEX, 8 TO 65 PERCENT SLOPES								
		MERGEL	35	> 72	None	Very limited	Very limited	Moderate	High
		REDTHAYNE	30	> 72	None	Very limited	Very limited	Moderate	High
		DOLLARD	20	> 72	None	Very limited	Very limited	Very slow	Very high
52	MIRACLE FINE SANDY LOAM, 3 TO 25 PERCENT SLOPES								
		MIRACLE	85	> 72	None	Very limited	Very limited	Slow	High
53	MOYERSON STONY CLAY LOAM, 15 TO 65 PERCENT SLOPES								
		MOYERSON	90	> 72	None	Very limited	Very limited	Very slow	Very high
54	NAGITSY-IRIGUL CHANNERY LOAMS, 5 TO 50 PERCENT SLOPES								
		NAGITSY	50	> 72	None	Very limited	Very limited	Very slow	High
		IRIGUL	35	> 72	None	Very limited	Very limited	Very slow	Very high
55	NIHILL CHANNERY SANDY LOAM, 5 TO 50 PERCENT SLOPES								
		NIHILL	90	> 72	None	Very limited	Very limited	Moderately rapid	Medium
56	NORTHWATER LOAM, 5 TO 50 PERCENT SLOPES								
		NORTHWATER	85	> 72	None	Very limited	Very limited	Slow	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
57	OWEN CREEK-JERRY-BURNETTE LOAMS, 5 TO 35 PERCENT SLOPES								
		OWEN CREEK	40	> 72	None	Very limited	Very limited	Very slow	Very high
		JERRY	30	> 72	None	Very limited	Very limited	Moderate	High
		BURNETTE	20	> 72	None	Very limited	Very limited	Slow	Very high
58	PARACHUTE LOAM, 25 TO 75 PERCENT SLOPES								
		PARACHUTE	85	> 72	None	Very limited	Very limited	Slow	High
59	PARACHUTE-RHONE LOAMS, 5 TO 30 PERCENT SLOPES								
		PARACHUTE	55	> 72	None	Very limited	Very limited	Slow	High
		RHONE	35	> 72	None	Very limited	Very limited	Slow	Medium
6	BARCUS CHANNERY LOAMY SAND, 2 TO 8 PERCENT SLOPES								
		BARCUS	85	> 72	Rare	Very limited	Very limited	Rapid	Very low
60	PATENT LOAM, 0 TO 3 PERCENT SLOPES								
		PATENT	85	> 72	None	Not limited	Somewhat limited	Moderate	Low
61	PATENT LOAM, 3 TO 8 PERCENT SLOPES								
		PATENT	85	> 72	None	Not limited	Somewhat limited	Moderate	Medium
62	PATENT LOAM, 8 TO 15 PERCENT SLOPES								
		PATENT	85	> 72	None	Somewhat limited	Very limited	Moderate	Medium
63	PATENT LOAM, 15 TO 25 PERCENT SLOPES								
		PATENT	85	> 72	None	Very limited	Very limited	Moderate	High
64	PICEANCE FINE SANDY LOAM, 5 TO 15 PERCENT SLOPES								
		PICEANCE	85	> 72	None	Very limited	Very limited	Moderate	Medium
65	PINELLI CLAY LOAM, 3 TO 12 PERCENT SLOPES								
		PINELLI	85	> 72	None	Very limited	Very limited	Moderately slow	High
66	POTTS-BEGAY FINE SANDY LOAMS, 2 TO 7 PERCENT SLOPES								
		POTTS	60	> 72	None	Not limited	Somewhat limited	Moderate	Medium
		BEGAY	20	> 72	None	Not limited	Very limited	Moderately rapid	Low
67	RABBITEY FLAGGY LOAM, 10 TO 65 PERCENT SLOPES								
		RABBITEY	80	> 72	None	Very limited	Very limited	Slow	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
68	RABBITEY-WORK LOAMS, 10 TO 25 PERCENT SLOPES								
		RABBITEY	45	> 72	None	Very limited	Very limited	Slow	Medium
		WORK	35	> 72	None	Very limited	Very limited	Moderately slow	High
69	RAZORBA CHANNERY SANDY LOAM, 30 TO 75 PERCENT SLOPES								
		RAZORBA	80	> 72	None	Very limited	Very limited	Moderately rapid	Medium
7	BILLINGS SILTY CLAY LOAM, 0 TO 5 PERCENT SLOPES								
		BILLINGS	85	> 72	None	Not limited	Somewhat limited	Slow	High
70	REDCREEK-RENTSAC COMPLEX, 5 TO 30 PERCENT SLOPES								
		REDCREEK	60	> 72	None	Very limited	Very limited	Slow	Very high
		RENTSAC	30	> 72	None	Very limited	Very limited	Very slow	Very high
71	REDROB LOAM								
		REDROB	85	33-72	Rare	Very limited	Very limited	Moderate	Low
72	REDROB VARIANT LOAM								
		REDROB VARIANT	85	36-72	Rare	Very limited	Very limited	Moderate	Low
73	RENTSAC CHANNERY LOAM, 5 TO 50 PERCENT SLOPES								
		RENTSAC	80	> 72	None	Very limited	Very limited	Very slow	Very high
74	RENTSAC-MOYERSON-ROCK OUTCROP COMPLEX, 5 TO 65 PERCENT SLOPES								
		RENTSAC	40	> 72	None	Very limited	Very limited	Very slow	Very high
		MOYERSON	25	> 72	None	Very limited	Very limited	Very slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
75	RENTSAC-PICEANCE COMPLEX, 2 TO 30 PERCENT SLOPES								
		RENTSAC	60	> 72	None	Very limited	Very limited	Very slow	Very high
		PICEANCE	30	> 72	None	Very limited	Very limited	Moderate	Medium
76	RHONE LOAM, 30 TO 75 PERCENT SLOPES								
		RHONE	85	> 72	None	Very limited	Very limited	Slow	High
77	RHONE-NORTHWATER-LAMPHIER LOAMS, 3 TO 50 PERCENT SLOPES								
		RHONE	40	> 72	None	Very limited	Very limited	Slow	High
		NORTHWATER	30	> 72	None	Very limited	Very limited	Slow	High
		LAMPHIER	20	> 72	None	Very limited	Very limited	Moderate	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
78	ROCK OUTCROP								
		ROCK OUTCROP	90	> 72	None	Very limited	Very limited	Very slow	Very high
79	SHAWA LOAM, 1 TO 3 PERCENT SLOPES								
		SHAWA	85	> 72	None	Not limited	Somewhat limited	Moderate	Low
8	BILLINGS-TORRIFLUENTS COMPLEX, GULLIED, 0 TO 5 PERCENT SLOPES								
		BILLINGS, GULLIED	55	> 72	None	Not limited	Somewhat limited	Slow	Very high
		TORRIFLUENTS, GULLIED	35	> 72	Occasional	Very limited	Very limited	Moderately rapid	Very low
80	SHAWA LOAM, 3 TO 8 PERCENT SLOPES								
		SHAWA	85	> 72	None	Not limited	Somewhat limited	Moderate	Medium
81	SHAWA LOAM, WET, 0 TO 5 PERCENT SLOPES								
		SHAWA, WET	85	48-72	Rare	Very limited	Somewhat limited	Moderate	Low
82	SILAS LOAM, 0 TO 8 PERCENT SLOPES								
		SILAS	85	60-72	None	Somewhat limited	Somewhat limited	Moderate	Low
83	SILAS LOAM, 8 TO 12 PERCENT SLOPES								
		SILAS	85	60-72	None	Somewhat limited	Very limited	Moderate	Medium
84	SILAS VARIANT LOAM								
		SILAS VARIANT	85	57-72	Rare	Very limited	Somewhat limited	Moderately slow	Low
85	SINKSON GRAVELLY SANDY LOAM, 1 TO 8 PERCENT SLOPES								
		SINKSON	85	> 72	None	Not limited	Somewhat limited	Moderate	Medium
86	SINKSON GRAVELLY SANDY LOAM, 8 TO 15 PERCENT								
		SINKSON	85	> 72	None	Somewhat limited	Very limited	Moderate	Medium
87	STARMAN-VANDAMORE COMPLEX, 5 TO 40 PERCENT SLOPES								
		STARMAN	50	> 72	None	Very limited	Very limited	Slow	Very high
		VANDAMORE	40	> 72	None	Very limited	Very limited	Slow	High
88	TAMPICO-MIRACLE COMPLEX, 8 TO 50 PERCENT SLOPES								
		TAMPICO	60	> 72	None	Very limited	Very limited	Moderate	High
		MIRACLE	30	> 72	None	Very limited	Very limited	Slow	High
89	TISWORTH FINE SANDY LOAM, 0 TO 5 PERCENT SLOPES								
		TISWORTH	85	> 72	None	Not limited	Somewhat limited	Slow	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
9	BLAKABIN-RHONE-WAYBE COMPLEX, 5 TO 50 PERCENT SLOPES								
		BLAKABIN	45	> 72	None	Very limited	Very limited	Slow	Very high
		RHONE	25	> 72	None	Very limited	Very limited	Slow	High
		WAYBE	20	> 72	None	Very limited	Very limited	Very slow	Very high
90	TORRIFLUENTS, GULLIED*								
		TORRIFLUENTS, GULLIED*	90	> 72	Occasional	Very limited	Very limited	Moderately rapid	Very low
91	TORRIORTHENTS-ROCK OUTCROP COMPLEX, 15 TO 90 PERCENT SLOPES								
		TORRIORTHENTS	50	> 72	None	Very limited	Very limited	Slow	High
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
92	TREMBLES LOAM, WET								
		TREMBLES, WET	85	> 72	Occasional	Very limited	Very limited	Moderately rapid	Very low
93	TURLEY FINE SANDY LOAM, 0 TO 3 PERCENT SLOPES								
		TURLEY	85	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	Medium
94	TURLEY FINE SANDY LOAM, 3 TO 8 PERCENT SLOPES								
		TURLEY	85	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	High
95	UFFENS LOAM, 0 TO 5 PERCENT SLOPES								
		UFFENS	85	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	Medium
96	VEATCH CHANNERY LOAM, 12 TO 50 PERCENT SLOPES								
		VEATCH	85	> 72	None	Very limited	Very limited	Slow	High
97	WALKNOLLS CHANNERY SANDY LOAM, 5 TO 50 PERCENT SLOPES								
		WALKNOLLS	90	> 72	None	Very limited	Very limited	Slow	Very high
98	WAYBE-VANDAMORE VARIANT-ROCK OUTCROP COMPLEX, 5 TO 30								
		WAYBE	45	> 72	None	Very limited	Very limited	Very slow	Very high
		VANDAMORE VARIANT	25	> 72	None	Somewhat limited	Very limited	Moderate	Medium
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
99	WINNEMUCCA-CLAYBURN LOAMS, 8 TO 25 PERCENT SLOPES								
		WINNEMUCCA	60	> 72	None	Very limited	Very limited	Slow	Very high
		CLAYBURN	25	> 72	None	Somewhat limited	Very limited	Moderate	Medium