

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
101B	TUPUYCI-IVES COMPLEX, 1 TO 3 PERCENT SLOPES								
		TUPUYCI	60	> 72	None	Very limited	Very limited	Moderately rapid	Very low
		IVES	20	> 72	None	Very limited	Very limited	Moderately rapid	Very low
103B	BATTLEROCK SILTY CLAY LOAM, SLIGHTLY SALINE-SODIC, 0 TO 3 PERCENT SLOPES								
		BATTLEROCK	70	> 72	None	Very limited	Very limited	Moderately slow	Medium
103S	BATTLEROCK LOAM, SALINE-SODIC, 0 TO 3 PERCENT SLOPES								
		BATTLEROCK, SODIC	70	> 72	None	Very limited	Very limited	Moderately rapid	Very low
105B	IVES SANDY LOAM, 1 TO 3 PERCENT SLOPES								
		IVES	85	> 72	None	Very limited	Very limited	Moderately rapid	Very low
107B	COWBOY CLAY, 1 TO 3 PERCENT SLOPES								
		COWBOY	85	> 72	None	Very limited	Somewhat limited	Slow	High
110B	RAVOLA SILT LOAM, 1 TO 3 PERCENT SLOPES								
		RAVOLA	85	> 72	None	Very limited	Somewhat limited	Moderately slow	Medium
122C	YOGOVUCI-TAQOCI COMPLEX, 2 TO 6 PERCENT SLOPES								
		YOGOVUCI	40	> 72	None	Somewhat limited	Very limited	Moderately slow	Medium
		TAQOCI	40	> 72	None	Not limited	Very limited	Moderate	Low
124C	HOPE SILTY CLAY LOAM, 1 TO 6 PERCENT SLOPES								
		HOPE	75	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	Medium
125B	CHIMROCK LOAM, SODIC, 1 TO 3 PERCENT SLOPES								
		CHIMROCK, SODIC	65	> 72	None	Somewhat limited	Somewhat limited	Slow	Medium
126B	CHIMROCK LOAM, 1 TO 3 PERCENT SLOPES								
		CHIMROCK	75	> 72	None	Not limited	Very limited	Moderate	Low
128B	DECOROCK-SALAMANDER ASSOCIATION, 1 TO 25 PERCENT SLOPES								
		DECOROCK	60	> 72	None	Very limited	Very limited	Very slow	Very high
		SALAMANDER	30	> 72	None	Not limited	Very limited	Moderate	Low
150D	PERSAYO-YOGOVUCI ASSOCIATION, 1 TO 12 PERCENT SLOPES								
		PERSAYO	50	> 72	None	Somewhat limited	Very limited	Very slow	Very high
		YOGOVUCI	35	> 72	None	Not limited	Very limited	Moderately slow	Medium

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
169B	COWBOY-KAVA COMPLEX, 1 TO 3 PERCENT SLOPES								
		COWBOY	50	> 72	None	Somewhat limited	Somewhat limited	Very slow	High
		KAVA	30	> 72	None	Very limited	Very limited	Very slow	Very high
170C	COWBOY-KAVA COMPLEX, 3 TO 12 PERCENT SLOPES								
		COWBOY	50	> 72	None	Somewhat limited	Somewhat limited	Very slow	Very high
		KAVA	30	> 72	None	Very limited	Very limited	Very slow	Very high
180E	DECOROCK-SALAMANDER-BADLANDS ASSOCIATION, 3 TO 60 PERCENT SLOPES								
		DECOROCK	60	> 72	None	Very limited	Very limited	Very slow	Very high
		SALAMANDER	20	> 72	None	Not limited	Very limited	Moderate	Low
		BADLANDS	10	> 72	Not Rated	Very limited	Very limited	Very slow	Very high
203B	REDLANDS FINE SANDY LOAM, 1 TO 3 PERCENT SLOPES								
		REDLANDS	85	> 72	None	Not limited	Very limited	Moderately rapid	Very low
203C	REDLANDS FINE SANDY LOAM, 3 TO 6 PERCENT SLOPES								
		REDLANDS	85	> 72	None	Not limited	Very limited	Moderately rapid	Very low
205B	MACK FINE SANDY LOAM, 1 TO 3 PERCENT SLOPES								
		MACK	80	> 72	None	Not limited	Very limited	Moderate	Low
205C	MACK FINE SANDY LOAM, 3 TO 6 PERCENT SLOPES								
		MACK	80	> 72	None	Not limited	Very limited	Moderate	Low
208B	MARIANO FINE SANDY LOAM, 1 TO 3 PERCENT SLOPES								
		MARIANO	75	> 72	None	Not limited	Very limited	Moderately rapid	Very low
208C	MARIANO FINE SANDY LOAM, 3 TO 6 PERCENT SLOPES								
		MARIANO	75	> 72	None	Not limited	Very limited	Moderately rapid	Very low
208CS	MARIANO FINE SANDY LOAM, 3 TO 6 PERCENT SLOPES, STONY								
		MARIANO	80	> 72	None	Not limited	Very limited	Moderately rapid	Very low
215B	BLUECHIEF FINE SANDY LOAM, 1 TO 3 PERCENT SLOPES								
		BLUECHIEF	80	> 72	None	Very limited	Very limited	Very slow	High
215C	BLUECHIEF FINE SANDY LOAM, 3 TO 6 PERCENT SLOPES								
		BLUECHIEF	80	> 72	None	Very limited	Very limited	Very slow	High

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
217D	BLUECHIEF-ROCK OUTCROP COMPLEX, 1 TO 12 PERCENT SLOPES								
		BLUECHIEF	75	> 72	None	Very limited	Very limited	Very slow	High
		ROCK OUTCROP	15	> 72	None	Very limited	Very limited	Very slow	Very high
250C	PERSAYO LOAM, 3 TO 12 PERCENT SLOPES								
		PERSAYO	75	> 72	None	Very limited	Very limited	Very slow	Very high
250E	PERSAYO GRAVELLY LOAM, 12 TO 45 PERCENT SLOPES								
		PERSAYO	85	> 72	None	Very limited	Very limited	Very slow	Very high
256C	GREYCAP-NOMAD COMPLEX, 1 TO 6 PERCENT SLOPES								
		GREYCAP	40	> 72	None	Not limited	Somewhat limited	Very slow	Very high
		NOMAD	40	> 72	None	Very limited	Very limited	Very slow	High
260C	GYPSEY LOAM, 3 TO 6 PERCENT SLOPES								
		GYPSEY	80	> 72	None	Somewhat limited	Very limited	Very slow	High
260D	GYPSEY LOAM, 6 TO 12 PERCENT SLOPES, ROLLING HILLS								
		GYPSEY	75	> 72	None	Somewhat limited	Very limited	Very slow	High
265C	PERSAYO-FARB COMPLEX, 3 TO 15 PERCENT SLOPES								
		Persayo	50	> 72	None	Somewhat limited	Very limited	Very slow	Not Rated
		Farb	25	> 72	None	Somewhat limited	Very limited	Moderately rapid	Not Rated
271C	OAGAMATI SILTY CLAY LOAM, 1 TO 6 PERCENT SLOPES								
		OAGAMATI	70	> 72	None	Very limited	Very limited	Very slow	High
275C	UZONA LOAM, 1 TO 6 PERCENT SLOPES								
		UZONA	75	> 72	None	Very limited	Somewhat limited	Slow	Medium
280D	JUANALO GRAVELY FINE SANDY LOAM, 1 TO 6 PERCENT SLOPES								
		JUANALO	75	> 72	None	Very limited	Very limited	Slow	Very high
		JUANALO	75	> 72	None	Very limited	Very limited	Slow	Very high
285C	NATAANI-YOGOUCI COMPLEX, 3 TO 9 PERCENT SLOPES								
		NATAANI	60	> 72	None	Somewhat limited	Very limited	Very slow	High
		YOGOUCI	20	> 72	None	Somewhat limited	Very limited	Moderate	Medium
401C	AWITAVA FINE SANDY LOAM, 3 TO 9 PERCENT SLOPES								
		AWITAVA	85	> 72	None	Not limited	Very limited	Very slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
460C	ROCK OUTCROP-TRAVESSILLA COMPLEX								
		Rock Outcrop	60	> 72	None	Very limited	Very limited	Very slow	Very high
		Travessilla	20	> 72	None	Very limited	Very limited	Very slow	High
470C	TRAVESSILLA-ROCK OUTCROP COMPLEX								
		Travessilla	60	> 72	None	Very limited	Very limited	Very slow	High
		Rock Outcrop	20	> 72	None	Very limited	Very limited	NA	Very high
510C	WETHERILL-KUCU COMPLEX, 3 TO 6 PERCENT SLOPES								
		Wetherill	60	> 72	None	Not limited	Somewhat limited	Moderate	Low
		Kucu	25	> 72	None	Not limited	Very limited	Very slow	High
510D	DOLCAN-KUCU ASSOCIATION, 3 to 25 PERCENT SLOPES								
		Dolcan	50	> 72	None	Very limited	Very limited	Very slow	Very high
		Kucu	30	> 72	None	Not limited	Very limited	Very slow	High
BP	BARROW PITS								
		PITS	95	> 72	None	Not limited	Somewhat limited	NA	Not Rated
C10	BARX VERY FINE SANDY LOAM, 1 TO 4 PERCENT SLOPES								
		BARX	90	> 72	None	Not limited	Somewhat limited	Moderate	Low
C105	RIZNO-GAPMESA COMPLEX, 3 TO 9 PERCENT SLOPES								
		RIZNO	45	> 72	None	Very limited	Very limited	Slow	Very high
		GAPMESA	35	> 72	None	Very limited	Very limited	Slow	High
C107	RIZNO-RUINPOINT-ROCK OUTCROP COMPLEX, 1 TO 15 PERCENT SLOPES								
		RIZNO	35	> 72	None	Very limited	Very limited	Slow	Very high
		RUINPOINT	25	> 72	None	Somewhat limited	Somewhat limited	Moderate	Medium
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
C108	ROCK OUTCROP								
		ROCK OUTCROP	95	> 72	None	Very limited	Very limited	Very slow	Very high
C109	ROMBERG-CROSSCAN COMPLEX, 6 TO 25 PERCENT SLOPES								
		ROMBERG	45	> 72	None	Very limited	Very limited	Moderately slow	High
		CROSSCAN	40	> 72	None	Very limited	Very limited	Slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
C11	BARX-GAPMESA COMPLEX, 2 TO 6 PERCENT SLOPES								
		BARX	60	> 72	None	Not limited	Somewhat limited	Moderate	Low
		GAPMESA	30	> 72	None	Very limited	Very limited	Slow	Medium
C110	ROMBERG-CROSSCAN-ROCK OUTCROP COMPLEX, 25 TO 80 PERCENT SLOPES								
		ROMBERG	35	> 72	None	Very limited	Very limited	Moderately slow	Very high
		CROSSCAN	30	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
C111	ROUBIDEAU LOAM, 1 TO 6 PERCENT SLOPES								
		ROUBIDEAU	80	> 72	None	Very limited	Very limited	Slow	Medium
C115	SHARPS, DRY-GAPMESA COMPLEX, 6 TO 12 PERCENT SLOPES								
		SHARPS, DRY	45	> 72	None	Somewhat limited	Very limited	Slow	High
		GAPMESA	40	> 72	None	Very limited	Very limited	Slow	High
C119	SHEEK-ARCHULETA COMPLEX, 6 TO 25 PERCENT SLOPES								
		SHEEK	50	> 72	None	Very limited	Very limited	Moderately slow	High
		ARCHULETA	35	> 72	None	Very limited	Very limited	Slow	Very high
C12	BATTLEROCK CLAY LOAM, 0 TO 6 PERCENT SLOPES								
		BATTLEROCK	85	> 72	None	Very limited	Somewhat limited	Moderately slow	Medium
C120	SHEEK-ARCHULETA-ROCK OUTCROP COMPLEX, 25 TO 80 PERCENT SLOPES								
		SHEEK	35	> 72	None	Very limited	Very limited	Moderately slow	Very high
		ARCHULETA	30	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
C121	SHEEK-ARCHULETA-ROCK OUTCROP COMPLEX, 25 TO 80 PERCENT SLOPES, NORTH ASPECT								
		SHEEK	40	> 72	None	Very limited	Very limited	Moderately slow	Very high
		ARCHULETA	25	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
C122	SHEPPARD FINE SAND, 1 TO 6 PERCENT SLOPES								
		SHEPPARD	90	> 72	None	Not limited	Very limited	Rapid	Negligible
		SHEPPARD	90	> 72	None	Not limited	Very limited	Rapid	Negligible

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
C123	SIDESHOW SILTY CLAY LOAM, 0 TO 3 PERCENT SLOPES								
		SIDESHOW	90	> 72	None	Very limited	Somewhat limited	Slow	High
C124	SIDESHOW SILTY CLAY LOAM, 3 TO 6 PERCENT SLOPES								
		SIDESHOW	90	> 72	None	Very limited	Somewhat limited	Slow	Very high
C128	STEPHOUSE-ROCK OUTCROP COMPLEX, 3 TO 10 PERCENT SLOPES								
		STEPHOUSE	55	> 72	None	Not limited	Very limited	Very slow	Very high
		ROCK OUTCROP	25	> 72	None	Very limited	Very limited	Very slow	Very high
C129	TORRIORTHENTS, 12 TO 65 PERCENT SLOPES								
		TORRIORTHENTS	90	> 72	None	Very limited	Very limited	Moderately slow	Very high
C130	TORRIORTHENTS-BADLAND COMPLEX, 25 TO 100 PERCENT SLOPES								
		TORRIORTHENTS	50	> 72	None	Very limited	Very limited	Slow	Very high
		BADLAND	40	> 72	None	Very limited	Very limited	Very slow	Very high
C131	TRAGMON-SHEEK COMPLEX, 12 TO 25 PERCENT SLOPES								
		TRAGMON	50	> 72	None	Very limited	Very limited	Moderate	Medium
		SHEEK	35	> 72	None	Very limited	Very limited	Moderately slow	High
C133	TYPIC TORRIORTHENTS-ROCK OUTCROP COMPLEX, 12 TO 80 PERCENT SLOPES								
		TYPIC TORRIORTHENTS	60	> 72	None	Very limited	Very limited	Moderately slow	Very high
		ROCK OUTCROP	25	> 72	None	Very limited	Very limited	Very slow	Very high
C135	USTIC TORRIFLUENTS, 0 TO 3 PERCENT SLOPES								
		USTIC TORRIFLUENTS	80	> 72	None	Very limited	Very limited	Moderately rapid	Very low
C136	USTIC TORRIORTHENTS-GULLIED LAND COMPLEX, 1 TO 60 PERCENT SLOPES								
		USTIC TORRIORTHENTS	45	> 72	None	Very limited	Very limited	Moderate	Medium
		GULLIED LAND	40	> 72	None	Very limited	Very limited	Slow	Very high
C138	UZACOL-ZWICKER-CLAYSPRINGS COMPLEX, 3 TO 12 PERCENT SLOPES								
		UZACOL	35	> 72	None	Very limited	Somewhat limited	Slow	Very high
		ZWICKER	30	> 72	None	Very limited	Very limited	Slow	Very high
		CLAYSPRINGS	20	> 72	None	Very limited	Very limited	Very slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
C140	WAUQUIE VERY STONY LOAM, 6 TO 25 PERCENT SLOPES								
		WAUQUIE	85	> 72	None	Very limited	Very limited	Moderate	Medium
C141	WAUQUIE-DOLCAN COMPLEX, 6 TO 25 PERCENT SLOPES								
		WAUQUIE	45	> 72	None	Very limited	Very limited	Moderate	Medium
		DOLCAN	40	> 72	None	Very limited	Very limited	Very slow	Very high
C142	WAUQUIE-DOLCAN-ROCK OUTCROP COMPLEX, 25 TO 80 PERCENT SLOPES								
		WAUQUIE	40	> 72	None	Very limited	Very limited	Moderate	High
		DOLCAN	30	> 72	None	Very limited	Very limited	Very slow	Very high
		ROCK OUTCROP	15	> 72	None	Very limited	Very limited	Very slow	Very high
C143	WETHERILL SILT LOAM, 1 TO 3 PERCENT SLOPES								
		WETHERILL	90	> 72	None	Not limited	Somewhat limited	Moderate	Low
		WETHERILL	90	> 72	None	Not limited	Somewhat limited	Moderate	Low
C144	WETHERILL SILT LOAM, 3 TO 6 PERCENT SLOPES								
		WETHERILL	85	> 72	None	Not limited	Somewhat limited	Moderate	Medium
		WETHERILL	85	> 72	None	Not limited	Somewhat limited	Moderate	Medium
C145	WETHERILL SILT LOAM, 6 TO 12 PERCENT SLOPES								
		WETHERILL	80	> 72	None	Somewhat limited	Very limited	Moderate	Low
		WETHERILL	80	> 72	None	Somewhat limited	Very limited	Moderate	Low
C147	YARTS FINE SANDY LOAM, 1 TO 6 PERCENT SLOPES								
		YARTS	85	> 72	None	Not limited	Very limited	Moderately rapid	Very low
C150	ZIGZAG-SIDESHOW COMPLEX, 25 TO 65 PERCENT SLOPES								
		ZIGZAG	60	> 72	None	Very limited	Very limited	Slow	Very high
		SIDESHOW	30	> 72	None	Very limited	Very limited	Slow	Very high
C151	ZYME GRAVELLY CLAY LOAM, 3 TO 12 PERCENT SLOPES								
		ZYME	85	> 72	None	Very limited	Very limited	Slow	Very high
C152	ZYME VERY CHANNERY CLAY LOAM, 12 TO 65 PERCENT SLOPES								
		ZYME	80	> 72	None	Very limited	Very limited	Slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
C20	CAHONA-PULPIT COMPLEX, 3 TO 9 PERCENT SLOPES								
		CAHONA	50	> 72	None	Not limited	Somewhat limited	Moderately slow	High
		PULPIT	35	> 72	None	Very limited	Very limited	Slow	High
C22	CLAYSPRINGS VERY STONY CLAY LOAM, 12 TO 65 PERCENT SLOPES								
		CLAYSPRINGS	80	> 72	None	Very limited	Very limited	Very slow	Very high
C31	FARB-ROCK OUTCROP COMPLEX, 3 TO 12 PERCENT SLOPES								
		FARB	55	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high
C38	FLUVENTS-FLUVAQUENTS COMPLEX, 0 TO 3 PERCENT SLOPES								
		FLUVENTS	55	> 72	Occasional	Very limited	Very limited	Rapid	Negligible
		FLUVAQUENTS	30	> 72	Frequent	Very limited	Very limited	Moderately rapid	Very low
C4	ARABRAB-LONGBURN COMPLEX, 3 TO 15 PERCENT SLOPES								
		ARABRAB	45	> 72	None	Somewhat limited	Very limited	Slow	Very high
		LONGBURN	40	> 72	None	Very limited	Very limited	Slow	Very high
C42	GLADEL-PULPIT COMPLEX, 3 TO 9 PERCENT SLOPES								
		GLADEL	45	> 72	None	Very limited	Very limited	Slow	Very high
		PULPIT	35	> 72	None	Very limited	Very limited	Slow	High
C65	LILLINGS SILT LOAM, SODIC, 1 TO 3 PERCENT SLOPES								
		LILLINGS	90	> 72	None	Very limited	Somewhat limited	Moderate	Low
C66	LILLINGS SILTY CLAY LOAM, 1 TO 3 PERCENT SLOPES								
		LILLINGS	90	> 72	None	Very limited	Somewhat limited	Moderately slow	Medium
C67	LILLINGS SILTY CLAY LOAM, 3 TO 6 PERCENT SLOPES								
		LILLINGS	90	> 72	None	Very limited	Somewhat limited	Moderately slow	High
C68	LONGBURN-ROCK OUTCROP COMPLEX, 10 TO 45 PERCENT SLOPES								
		LONGBURN	65	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	20	> 72	None	Very limited	Very limited	Very slow	Very high
C69	LONGBURN-ROCK OUTCROP COMPLEX, 45 TO 80 PERCENT SLOPES								
		LONGBURN	50	> 72	None	Very limited	Very limited	Slow	Very high
		ROCK OUTCROP	30	> 72	None	Very limited	Very limited	Very slow	Very high

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
C70	MACK FINE SANDY LOAM, 0 TO 6 PERCENT SLOPES								
		MACK	85	> 72	None	Not limited	Somewhat limited	Moderate	Low
C71	MIKETT CLAY LOAM, SALINE-SODIC, 0 TO 3 PERCENT SLOPES								
		MIKETT	85	> 72	None	Somewhat limited	Very limited	Moderately slow	Medium
C73	MIKIM CLAY LOAM, 1 TO 3 PERCENT SLOPES								
		MIKIM	90	> 72	None	Not limited	Somewhat limited	Moderately slow	Medium
C75	MIKIM LOAM, 3 TO 6 PERCENT SLOPES								
		MIKIM	90	> 72	None	Not limited	Somewhat limited	Moderately slow	High
C76	MOREFIELD LOAM, 1 TO 3 PERCENT SLOPES								
		MOREFIELD	90	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	Medium
C77	MOREFIELD LOAM, 3 TO 6 PERCENT SLOPES								
		MOREFIELD	90	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	High
C88	POGO LOAM, 0 TO 2 PERCENT SLOPES								
		POGO	90	> 72	Frequent	Very limited	Very limited	Moderately slow	Medium
C92	PRATER-DOLCAN COMPLEX, 25 TO 60 PERCENT SLOPES								
		PRATER	60	> 72	None	Very limited	Very limited	Slow	Very high
		DOLCAN	15	> 72	None	Very limited	Very limited	Very slow	Very high
C94	PULPIT SILT LOAM, 3 TO 6 PERCENT SLOPES								
		PULPIT	80	> 72	None	Very limited	Very limited	Slow	High
C97	RAMPER CLAY LOAM, 0 TO 3 PERCENT SLOPES								
		RAMPER	90	> 72	None	Very limited	Somewhat limited	Moderately slow	Medium
C98	RAMPER LOAM, 0 TO 3 PERCENT SLOPES								
		RAMPER	90	> 72	None	Very limited	Somewhat limited	Moderately slow	Medium
C99	RAVOLA CLAY LOAM, 0 TO 3 PERCENT SLOPES								
		RAVOLA	85	> 72	None	Very limited	Somewhat limited	Moderately slow	Medium
S102	BLACKSTON-CAMAC-ROCK OUTCROP COMPLEX, 0 TO 60 PERCENT SLOPES								
		BLACKSTON	55	> 72	None	Not limited	Very limited	Moderate	Not Rated
		CAMAC	20	> 72	None	Very limited	Very limited	Moderately slow	Not Rated
		ROCK OUTCROP	15	> 72	None	Very limited	Very limited	NA	Not Rated

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
S107	TOCITO-GULLIED LAND COMPLEX, 1 TO 3 PERCENT SLOPES								
		TOCITO	55	> 72	Rare	Very limited	Somewhat limited	Moderately slow	Not Rated
		GULLIED LAND	30	> 72	None	Very limited	Very limited	Moderate	Not Rated
S117	BADLAND-ROCK OUTCROP COMPLEX								
		BADLAND	75	> 72	None	Very limited	Very limited	NA	Not Rated
		ROCK OUTCROP	15	> 72	None	Very limited	Very limited	NA	Not Rated
S137	PERSAYO-CAIRN-PATEL COMPLEX, 1 TO 25 PERCENT SLOPES								
		PERSAYO	35	> 72	None	Very limited	Very limited	Slow	Not Rated
		CAIRN	30	> 72	None	Not limited	Very limited	Moderate	Not Rated
		PATEL	25	> 72	None	Very limited	Very limited	Slow	Not Rated
S142	BEBEEVAR-WALREES COMPLEX, 0 TO 2 PERCENT SLOPES								
		BEBEEVAR	60	51-72	Occasional	Very limited	Very limited	Moderately rapid	Not Rated
		WALREES	25	33-72	Frequent	Very limited	Very limited	Moderately slow	Not Rated
S165	JEDDITO-ESCAVADA ASSOCIATION, 0 TO 3 PERCENT SLOPES								
		JEDDITO	70	> 72	Rare	Very limited	Very limited	Moderate	Not Rated
		ESCAVADA	15	66-72	None	Very limited	Very limited	Moderate	Not Rated
S167	HOSKAY-PATEL-BADLAND COMPLEX, 1 TO 25 PERCENT SLOPES								
		HOSKAY	40	> 72	None	Very limited	Somewhat limited	Slow	Not Rated
		PATEL	30	> 72	None	Very limited	Very limited	Slow	Not Rated
		BADLAND	15	> 72	None	Very limited	Very limited	NA	Not Rated
S190	JEDDITO LOAMY FINE SAND, 0 TO 2 PERCENT SLOPES								
		JEDDITO	85	> 72	Rare	Very limited	Very limited	Moderately slow	Not Rated
S230	RAVOLA VERY FINE SANDY LOAM, 1 TO 3 PERCENT SLOPES								
		RAVOLA	80	> 72	None	Very limited	Very limited	Moderate	Not Rated
S250	LITTLEHAT-PERSAYO-NATAANI COMPLEX, 1 TO 15 PERCENT SLOPES								
		LITTLEHAT	35	> 72	None	Somewhat limited	Very limited	Moderate	Not Rated
		PERSAYO	30	> 72	None	Very limited	Very limited	Slow	Not Rated
		NATAANI	20	> 72	None	Somewhat limited	Very limited	Moderate	Not Rated

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
S255	BENALLY FINE SANDY LOAM, 1 TO 5 PERCENT SLOPES								
		BENALLY	80	> 72	None	Somewhat limited	Somewhat limited	Slow	Not Rated
S260	LITTLEHAT-PERSAYO-BADLAND COMPLEX, 3 TO 45 PERCENT SLOPES								
		LITTLEHAT	35	> 72	None	Very limited	Very limited	Moderate	Not Rated
		PERSAYO	35	> 72	None	Very limited	Very limited	Slow	Not Rated
		BADLAND	15	> 72	None	Very limited	Very limited	NA	Not Rated
S265	CAMAC-KIMBETO-BADLAND ASSOCIATION, 0 TO 50 PERCENT SLOPES								
		CAMAC	35	> 72	None	Very limited	Very limited	Moderately slow	Not Rated
		KIMBETO	35	> 72	None	Not limited	Somewhat limited	Moderate	Not Rated
		BADLAND	15	> 72	None	Very limited	Very limited	NA	Not Rated
S285	WATER-RIVERWASH COMPLEX								
		WATER	70	> 72	Not Rated	Not limited	Not limited	NA	Not Rated
		RIVERWASH	20	12-72	Frequent	Very limited	Very limited	Rapid	Not Rated
S300	FARVIEW-ROCK OUTCROP COMPLEX, 1 TO 10 PERCENT SLOPES								
		FARVIEW	50	> 72	None	Very limited	Very limited	Moderately rapid	Not Rated
		ROCK OUTCROP	35	> 72	None	Very limited	Very limited	NA	Not Rated
S303	SNAPILL VERY FINE SANDY LOAM, 1 TO 6 PERCENT SLOPES								
		SNAPILL	85	> 72	None	Not limited	Somewhat limited	Moderate	Not Rated
S304	FARVIEW-BECLABITO-ROCK OUTCROP COMPLEX, 1 TO 10 PERCENT SLOPES								
		FARVIEW	60	> 72	None	Very limited	Very limited	Moderately rapid	Not Rated
		BECLABITO	20	> 72	None	Somewhat limited	Somewhat limited	Moderately slow	Not Rated
		ROCK OUTCROP	10	> 72	None	Very limited	Very limited	NA	Not Rated
S305	STRYCH-EAGLEYE-ROCK OUTCROP COMPLEX, 15 TO 70 PERCENT SLOPES								
		STRYCH	50	> 72	None	Very limited	Very limited	Moderately rapid	Not Rated
		EAGLEYE	25	> 72	None	Very limited	Very limited	Slow	Not Rated
		ROCK OUTCROP	15	> 72	None	Very limited	Very limited	NA	Not Rated

Map Unit Symbol	Map Unit Name	Component Name	Percent of Map Unit	Depth to Seasonal High Water Table (inches)	Seasonal Flooding Frequency	Limitations for Buildings without Basements	Limitations for Sewage Lagoons	Permeability Class	Runoff Class
S400	WETHERILL-ATLATL ASSOCIATION, 1 TO 15 PERCENT SLOPES								
		WETHERILL	50	> 72	None	Somewhat limited	Very limited	Moderate	Not Rated
		ATLATL	35	> 72	None	Very limited	Very limited	Moderate	Not Rated
S401	VESSILLA-ROCK OUTCROP COMPLEX, 5 TO 25 PERCENT SLOPES								
		VESSILLA	65	> 72	None	Very limited	Very limited	Moderately rapid	Not Rated
		ROCK OUTCROP	25	> 72	None	Very limited	Very limited	NA	Not Rated
S503	CLAYSPRINGS-BADLAND COMPLEX, 35 TO 60 PERCENT SLOPES								
		CLAYSPRINGS	60	> 72	None	Very limited	Very limited	Very slow	Not Rated
		BADLAND	30	> 72	None	Very limited	Very limited	NA	Not Rated
S504	TOHONA-KIMNOLI-CLAYSPRINGS COMPLEX, 2 TO 45 PERCENT SLOPES								
		TOHONA	50	> 72	None	Very limited	Very limited	Slow	Not Rated
		KIMNOLI	20	> 72	None	Very limited	Very limited	Moderate	Not Rated
		CLAYSPRINGS	15	> 72	None	Very limited	Very limited	Very slow	Not Rated
W	WATER								
		WATER	100	> 72	None	Not limited	Not limited	NA	Not Rated