

# Sealing a Pond with Additives

Alabama Job Sheet No. AL 521B/C

## Definition

Ponds with excessive seepage can sometimes be sealed utilizing either bentonite or soil dispersants. Bentonite is a natural clay material that can absorb water and expand to several times its normal volume. Soil dispersants are either polyphosphates or soda ash, which can be used to chemically alter the soil structure of certain types of soil to reduce permeability. Additives in a finely ground form can be mixed and compacted with the soil in the earthen surface of a farm pond or waste impoundment to impede or prevent excessive seepage. Bentonite treatment works best on coarse-grained soils or very silty, fine-grained soils. Soil dispersants work best on clay soils that have high calcium content.

## General Information

The area to be treated with additives must be properly prepared. The soil should be free of all vegetation, trash, roots, frozen soil, snow, ice, stones over 2 in., and other objectionable material. The additive must be evenly applied over the surface to be treated. Application is best with either a drop type spreader or by hand. Spreaders that throw the additive into the air should not be used. When placed by hand, bags of additive should be placed in a grid pattern according to the application rate, broken open, and the contents evenly hand raked over the grid area. *(Mask and goggles should be worn when handling additives to protect from dust.)*

The rate of application of additive and the resultant liner thickness to treat farm ponds should be based on laboratory tests or on acceptable procedures according to the soil type being treated and the planned depth of water. NRCS personnel can help determine these values.

Since waste impoundments have a potential to pollute groundwater, the rate of application of additive and the resultant liner thickness must be based on laboratory tests only.



Liners with additives may have to be constructed in several 4 to 6 inch layers to achieve the designed thickness. Water may need to be added and thoroughly mixed to drier soils prior to the introduction of the additive in order to approach the proper water content for compaction. The additive in each layer should then be thoroughly mixed with the soil using rototillage or other approved methods. Each layer should be compacted at the proper water content, with the specified equipment, and properly bonded to other layers using appropriate construction techniques.

The minimum thickness of a finished additive treated liner is 6 inches. Water deeper than 6 feet will require a thicker liner.

Experience has proven that additive treated soil liners can be constructed only when soil moisture content and weather conditions are suitable. Construction should be started only when weather forecasts indicate sufficient continuous dry days to complete the job. Additive should be spread, incorporated, and compacted on the same day to eliminate problems due to unsuitable weather.

## Operation and Maintenance

The additive treated liner should be protected from drying and cracking, surface erosion, animals, and equipment. A protective soil layer of at least 6 inches should be placed over the liner for general protection. Any damage to the liner should be immediately repaired.

## References

- NRCS AL Conservation Practice Standards
- Code 378 - Pond
- Code 521B - Pond Sealing or Lining (Soil Dispersant Treatment)
- Code 521C - Pond Sealing or Lining (Bentonite)
- Code 313 - Waste Storage Facility
- Code 359 - Waste Treatment Lagoon

The United States Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, gender, religion, age, disability, political beliefs, sexual orientation, and marital or family status. (Not all prohibited bases apply to all programs.) Persons with disabilities who require alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact the USDA's TARGET Center at (202) 720-2600 (voice and TDD).

To file a complaint of discrimination, write the USDA, Director, Office of Civil Rights, Room 326W, Whitten Building, 14th and Independence Avenue, SW, Washington, D.C. 20250-9410 or call (202) 720-5964 (voice or TDD). USDA is an equal opportunity provider and employer.

# Pond Sealing or Lining – With Additives Worksheet

Land User: \_\_\_\_\_ County: \_\_\_\_\_ Date: \_\_\_\_\_

Farm No.: \_\_\_\_\_ Tract No. : \_\_\_\_\_ Assisted by: \_\_\_\_\_

## Pond liner material and rate:

✓	Liner Material	Rate
	Soil Dispersant/Soil Mixture	(lbs/ft <sup>2</sup> per lift)
	Sodium Bentonite/Soil Mixture	(lbs/ft <sup>2</sup> per lift)

Number of lifts required in liner: \_\_\_\_\_

Thickness of each lift: \_\_\_\_\_ in.

Depth of protective soil cover if required: \_\_\_\_\_ in.

Provisions for protection from damage during pond drainage or pump out (if needed):

Specific water content and compaction requirements shall be: