NATURAL RESOURCES CONSERVATION SERVICE

CONSERVATION PRACTICE STANDARD

IRRIGATION SYSTEM, SURFACE AND SUBSURFACE

(Ac.)

CODE 443

DEFINITION

A system in which all necessary earthwork, multi-outlet pipelines, and water-control structures have been installed for distribution of water by surface means, such as furrows, borders, and contour levees, or by subsurface means through water table control.

PURPOSE

This practice may be applied as part of a resource management system to achieve one or more of the following purposes:

- Efficiently convey and distribute irrigation water to the surface point of application without causing excessive water loss, erosion, or water quality impairment.
- Efficiently convey and distribute irrigation water to the subsurface point of application without causing excessive water loss or water quality impairment.
- Apply chemicals and/or nutrients as part of a surface irrigation system in a manner which protects water quality.
- Reduce Energy Use.

CONDITIONS WHERE PRACTICE APPLIES

Areas must be suitable for irrigation and water supplies must be adequate in quantity and quality to make irrigation practical for planned crops to be grown and application methods to be used.

This standard does not apply to detailed design criteria and construction specifications for individual water control or conveyance structures, or appurtenances.

Site conditions for a subsurface irrigation system shall be such that a water-table can be created and maintained to supply water to the crop root zone.

Subsurface irrigation under this standard applies to irrigation through water table control by adding water at water control structures and using perforated pipe, tubing (usually 3 inches or greater diameter), or operation of ditch structures to raise the water table.

This standard does not apply to irrigation systems employing subsurface line-source emitters on buried drip tapes or tubing which is addressed with NRCS Conservation Practice Standard, Irrigation System, Microirrigation (441).

CRITERIA

The owner is responsible for securing necessary permits and water rights, complying with all laws and regulations, and meeting legal requirements applicable to the installation, operation, and maintenance of this practice and associated structures.

General Criteria Applicable to All Purposes

Design and implementation of subsidiary components and/or structures shall meet all applicable Natural Resource Conservation Service (NRCS) conservation practice standards. The criteria for the design of any components not specifically addressed in Arizona conservation practice standards or construction and materials specifications shall be consistent with sound engineering principles and/or manufacturer recommendations.

Conservation irrigation methods. All irrigation systems must be designed as an integral part of an overall plan of conservation land use and treatment for the farm which is based on capabilities of the land*, the*

landowner/operator goals and needs of the irrigated area.

All farm irrigation system designs shall be based on the use of sound irrigation water application methods which are suited to site conditions (combination of soil*s, topography, water supply,* and slope) and crops to be grown. Adapted methods are those methods which will provide efficient use of water without destructive soil erosion or water quality degradation. *Design and implementation of this practice shall follow the detailed design criteria found in National Engineering Handbook, Part 652 – Irrigation Guide. Site specific design criteria (CU, soils, etc.) may be available from local irrigation guides and shall be followed, where available.*

***Materials*.** *Pipeline materials, appurtenances and subsidiary practices shall meet the minimum requirements as outlined in applicable Arizona Construction and Material Specifications and Conservation Practice Standards.*

Capacity. The irrigation system *and its components* shall have adequate capacity to meet the intended purpose(s).

If more than one irrigation method will be used on the same field, the system capacity shall be adequate for the method requiring the highest water delivery rate. *If crops with different peak use requirements are to be grown, the system capacity must be based on the crop or combinations of crops having the highest use rate.*

All structures and water delivery components *(above ground, multi-outlet pipes, furrows, borders, contour levees, or contour ditches and)* shall be designed for maximum flow conditions expected and shall have adequate capacity and/or freeboard.

Water control. Farm irrigation systems shall include necessary structures required for water control such as: measuring devices, division boxes, checks, turnouts, pipelines, lined ditches, valves, pumps, and gates to control and regulate water for efficient application *distribution and drainage without damaging the crop*.

Additional Criteria Applicable to Surface Irrigation Systems

Design of physical components shall be in accordance with NRCS Conservation Practice Standards, Irrigation Pipeline (430), Irrigation Canal or Lateral (320), Irrigation Field Ditch (388), Structure for Water Control (587), Pumping Plant (533), and other pertinent conservation practice standards.

Capacity. *The system shall have either (1) a design capacity adequate to meet water demands of all crops to be irrigated in the design area or (2) enough capacity to meet the requirements of water application during critical crop growth periods when less than full irrigation is planned.*

In computing capacity requirements, allowance must be made for reasonable water losses during application and any leaching requirements.

Design application rate. The design rate of application shall be within a range established by the minimum practical application rate for climatic conditions, *the peak consumptive* use *of the selected crop,* and the maximum rate consistent with the soil water intake rate and conservation practices used on the land.

Irrigation system shall have a minimum Distribution Uniformity (DU) of 75-percent.

Water surface elevation. All systems for irrigation by surface methods shall be designed with water surface elevation at field takeout points adequate to provide required flow onto the field surface. A head of at least 4 inches shall be provided.

Location of delivery ditches or aboveground, multi-outlet distribution pipelines. Delivery ditches or pipelines used for surface irrigation shall be located so *that* irrigation water can be applied uniformly over the entire field without causing erosion. Ditch or pipeline spacing shall be such that irrigation run lengths are not longer than *the* maximums specified in *National Engineering Handbook (NEH), Part 652 – Irrigation Guide*, local irrigation guides or those determined acceptable based on field slopes. If more than one crop is to be grown or more than one method of irrigation used, the ditch or distribution pipeline spacing shall not exceed

the allowable run length determined for the limiting crop or method.

Irrigation Water Management. An Irrigation Water Management Plan meeting requirements of NRCS Conservation Practice Standard, Irrigation Water Management (449) shall be developed for use with this practice.

Aboveground, multi-outlet distribution pipeline.

Working pressure. The maximum working pressure for all aboveground, multi-outlet distribution pipe except for poly irrigation tubing shall be 10 pounds per square inch or 23 feet of head. Appropriate head control appurtenances shall be installed to reduce maximum working pressure to acceptable levels.

For poly irrigation tubing, manufacturer's recommendations for maximum allowable working pressure shall be followed. If the manufacturer's recommendations are not available, the hoop stress formula in NRCS National Engineering Handbook (NEH) Part 636, Chapter 52, shall be used to determine maximum working pressure, using a Factor of Safety of 1.5.

Friction losses. For design purposes, friction head losses shall be no less than those computed by the Hazen-Williams equation, using roughness coefficients of C=130 for aluminum pipe and C=150 for plastic or poly irrigation tubing.

Flow velocity. Velocity in the pipeline when operating at system capacity shall not exceed 7 feet per second unless appropriate surge protection is provided.

Capacity. The design capacity of the pipeline shall be sufficient to deliver an adequate irrigation stream to the design area for the planned irrigation method.

Outlet gates. Individual outlet gates shall have capacity at design working pressure to deliver required flow to a point at least 4 inches above the field surface.

Head requirement. The working head shall not be less than 0.5 foot above outlet gates, unless a detailed design or manufacturer's literature indicates a lower head is adequate to deliver required water to the field. *The pipe shall be installed on a uniform grade when the working head is less than 1.0 foot above the outlet gates.*

Where either design working head exceeds 5 feet or stream flows are erosive, an effective method of energy dissipation shall be installed at each gate, or permanent vegetation shall be established and maintained along the pipeline to provide erosion control.

Flushing. A suitable outlet shall be installed at the end of the pipeline for flushing the line free of sediment or other foreign material.

Materials. Pipe shall be aluminum *meeting ASTM B 313, or ASTM B 210* or plastic material certified for above ground use. All fittings and couplers shall equal or exceed the pressure rating of the pipe with which they will be used. They shall be made of material which is recommended by the manufacturer for use with the pipe

Pipe and appurtenances shall be furnished with a coupling system which is compatible with the selected pipe material. . *Aluminum pipelines shall be coupled with a suitable insulating material.*

Rubber gaskets shall be according to the manufacturer's standard design dimensions and tolerances for the pipe material selected. They shall be of such size and shape that, after assembly, adequate compressive force is provided against the spigot and socket to affect a positive seal. The gasket shall be a continuous elastomeric ring and shall be the sole element depended upon to make the joint flexible and watertight.

Minimum wall thickness for aluminum gated pipe shall be 0.050 inches for 6 through 10 inches in diameter, and 0.058 inches for 12 inch diameter pipe.

If dissimilar metals are used, the fittings or orifice plates shall be protected against galvanic corrosion.

Corrosion protection shall be provided for aluminum pipe when:

- Conveying water with a copper content exceeding 0.02 parts per million. . *(Copper content in excess of 0.02 ppm produces nodular pitting and rapid deterioration of*

material when water is allowed to become stagnant).

- In contact with soil having a resistivity of less than 500 ohm-centimeters.
- In contact with soil having a pH less than 4 or greater than 9.

Minimum wall thickness of PVC gated pipe including consideration of any standard manufacturing tolerances shall be not be less than 0.09 inch. The pressure rating of the pipe shall be 22 pounds per square inch or greater, prior to gate installation.

Minimum wall thickness of poly irrigation tubing shall be 6 mil (0.006 inch).

Materials made of, or which have been exposed to hazardous or potentially harmful materials, such as asbestos, shall not be used.

Related structures. An open ditch supply shall include a permanent water control structure as the inlet to multi-outlet pipe. *If required, screens or other devices shall be installed to remove debris upstream of the gated pipe inlet.*

When the water supply for poly irrigation tubing is greater than 0.5 foot above the ground, a PVC or aluminum fitting shall be used to convey water between the supply outlet and the poly irrigation tubing at ground level.

Erosion control. The design of farm irrigation systems shall provide for the conveyance and distribution of irrigation water without causing damaging soil erosion. All unlined ditches shall have non-erosive gradients. If water is conveyed on slopes steep enough to cause excessive flow velocities, the irrigation system design shall provide for the installation of structural erosion control measures such as pipe drops, chutes, buried pipelines, and erosion-resistant ditch linings. Polyacrylamide may be applied for erosion control according to NRCS Conservation Practice Standard, Anionic Polyacrylamide (PAM) Application (450) in lieu of, or in combination with structural measures.

Seepage control. *For surface irrigation systems, ditches shall not traverse highly permeable soils without adequate measures for seepage control.* If site conditions require conveyance of water across excessively permeable soils, the irrigation system design shall provide for pipelines, flumes, or lined ditches, as needed, to prevent excessive seepage losses.

Designs shall provide means for minimizing seepage losses, unless specifically planned for subsurface application.

Tailwater and excess runoff removal. Irrigation system designs shall include facilities of adequate capacity for safe removal of *excess* irrigation tailwater and storm water runoff. If erosion is a hazard, collection facilities (ditches) constructed for this purpose shall be on non-erosive gradients or stabilized by lining or structural measures. If field elevations do not permit non-erosive disposal of tailwater or excess water by gravity flow, the design shall provide for installation of pumping plants and other needed appurtenant structures. Ditches shall be protected from bank erosion.

If excess water will be reused for irrigation, the system shall include a tailwater reuse system that conforms to NRCS Conservation Practice Standard, Irrigation System, Tailwater Recovery (447).

Additional Criteria Applicable to Subsurface Irrigation Systems

Subsurface irrigation systems shall be designed to maintain the water table at predetermined design elevations below the ground surface at all points in the application area.

Feeder ditches or conduits for subsurface irrigation shall be spaced so the variation in depth from the land surface to the water table provides adequate irrigation of the most limiting crop to be grown.

Design of physical components shall be in accordance with NRCS Conservation Practice Standards, Subsurface Drain (606), Structure for Water Control (587), Pumping Plant (533), and other pertinent conservation practice standards.

Soils. Site conditions shall be such that water can move laterally from open ditches or irrigation tiles to form and maintain a water table at the design depth as specified in the irrigation water management plan. Subsurface irrigation shall not be employed unless the

irrigated area has a slowly permeable water restrictive layer.

Soil survey information for the irrigated area can be used in preliminary planning. Final design shall be based on on-site lateral hydraulic conductivity measurements or average lateral hydraulic conductivity determined from laboratory tests of each soil layer.

Lateral Spacing. Laterals shall be equally spaced in each subunit. Maximum spacing of irrigation tiles or open ditches shall be no more that one-half the lateral or ditch spacing specified in local drainage guides or no more that one-half the lateral or ditch spacing computed using procedures found in NRCS Part 650, Chapter 14, or NRCS NEH Part 624.

Water Control. Within each managed subunit, the water level control structure shall be of sufficient size to allow adequate flow to meet water requirements of that subunit. The control structures should be set on elevation intervals not to exceed 1 foot.

Water level control structures must be covered or otherwise protected to prevent accidental entry by animals, livestock, machinery or humans.

Irrigation Water Management. An Irrigation Water Management Plan meeting requirements of NRCS Conservation Practice Standard, Irrigation Water Management (449) shall be developed for use with this practice.

Additional Criteria Applicable to Application of Chemicals and/or Nutrients with a Surface Irrigation System

The installation and operation of an irrigation system for the purpose of chemical and/or nutrient application shall comply with all applicable federal, state and local laws, rules and regulations. This includes backflow and anti-siphon prevention measures to protect surface and ground water sources. Additionally, surface waters shall be protected from direct application and runoff.

Design of physical components shall be in accordance with NRCS Conservation Practice Standards Irrigation Pipeline (430), Waste Transfer (634), Structure for Water Control (587), Pumping Plant (533), and other pertinent conservation practice standards.

Capacity. The system shall have a design capacity adequate to supply the specified amount of chemical and/or nutrients to the design area in the specified operating period.

Nutrient and Pest Management. Chemicals, fertilizers, waste water, and liquid manure shall be applied in accordance with appropriate NRCS Conservation Practice Standards, Nutrient Management (590), Pest Management (595), and Waste Utilization (633).

Investigations, Surveys and Design

Criteria. *Documentation requirements will be as outlined below, in addition to the documentation requirements for the practice components used in the system.*

Make a preliminary site assessment or reconnaissance to determine if the practice is feasible, considering the field or system layout, soils, crops, topography, water supply, and may include:

- *Pits, trenches, borings, review of existing data or other suitable means of soil investigation to determine soil conditions, including type, texture (silty sand, lean clay, etc.), intake rate, available water holding capacity (AWC), characteristics (physical and chemical properties), depths, water table, inhibiting layers, etc. Classification shall be by the Unified Soil Classification System (SM, CL, etc.).*
- *Water source (i.e., available flow rate, volume, seasonal variation, dependability, etc.) and water quality test results (if applicable).*
- *Crop type (basis for CU determination), rotation, tillage practices, etc.*
- *Verify appropriate state or local laws for permitting and approval requirements and notify landowner of his/her responsibilities.*
- *Verification or certification of used materials (if any).*

To adequately plan and layout this practice, a topographic survey is required, that adequately details:

- *Site topography, as needed to show the irrigation system position and component layout, irrigation methods, physical features of the site (field boundaries and slope), including existing*

features/practices, ground elevations (slopes), location of any utilities or markers, etc.
- *If applicable, a permanent benchmark(s) may be set and described. Preferably, the elevations and coordinates should be based on a local (assumed) or coordinate system (State or grid) and clearly stated on the plan. Datum (Elevations) should be associated either with the Northing and Easting coordinates or with the Longitude and Latitude.*

The design of a practice is the application of Field Office Technical Guide practice standards, and using experience and judgment in the development of a solution to the problem or the objective. All computations and decisions made during the design of a practice are to be checked by another qualified individual and appropriate notations made. Design computations, calculations or analysis shall meet the following criteria:

- *Determine the irrigated acres for each field and system requirements as related to meeting the needs of the intended use (peak consumptive use, AWC, soil type and texture, impervious layers or water table, irrigation system efficiency or application rates, quantity and timing of irrigation water availability, deficit irrigation, etc). Calculate the design application depth (gross, net and duration).*
- *Perform a hydraulic analysis of the system using approved irrigation software (Surface, FIRI or approved equal) simulating the proposed irrigation system. Analysis should include pipe hydraulics (friction loss), gate discharge, deep percolation, runoff, etc. Include support documentation for input parameters and values used.*
- *Fittings and appurtenance (type, size, pressure settings, capacity, head loss, location) shall be designed in accordance with applicable conservation practice standards or from published manufacturer literature.*
- *Include estimates of earthwork, pipe, fittings and appurtenances, concrete, vegetative components, etc.*
- *Subsidiary and applicable components shall be designed in accordance with applicable conservation practice standards (i.e., pipelines shall meet the requirements of Conservation Practice 430 – Irrigation Pipeline, etc.);*

***Installation and Basis of Acceptance**. For construction that does not meet State, OSHA, or Tribal criteria or requirements where deficient construction materials were used, NRCS may consider a waiver request for approval of construction after it has received a signed and sealed construction and/or material exemption from a licensed engineer. Required exemption shall be for installation of materials that do not meet minimum quality criteria as found in applicable Standards, Specifications, ASTM's, AWWA standards, etc.*

Contractors performing work under this practice shall abide by all Federal, State or Tribal laws or criteria, and must be licensed by the state DWR or board of technical registration where the work is being implemented.

Additional Criteria Applicable to Reduce Energy Use

Provide analysis to demonstrate reduction of energy use from practice implementation.

Reduction of energy use is calculated as average annual or seasonal energy reduction compared to previous operating conditions.

CONSIDERATIONS

When planning this practice the following items should be considered:

- Effects of soluble salts, nutrients, and /or pesticides on surface and ground water quality.
- Effects of saturated water levels on such soil nutrient processes as plant nitrogen use or denitrification, and root development.
- Effects on the soil biota which will alter nutrient cycling carbon utilization. Water logged and tillage dominated soils become bacteria driven systems which denitrify and ineffectively utilize carbon.
- Effects on aquatic and wildlife communities, wetlands or water-related wildlife habitats, including effects upon pollinator foraging and nesting habitats.

- When planning and designing surface and subsurface irrigation systems: soil texture, intake, slope, and depth are important soil properties which influence installation, performance and soil limitations related to intake rate, seepage, corrosivity, and soil compaction. Designers should refer to soil survey information for the irrigated area during preliminary planning and conduct on-site soil investigations prior to final design.

When designing a surface irrigation system the following should be considered:

- To improve surface irrigation efficiency surface tillage should be reduced when possible. The destruction of soil structure caused by physical and chemical disturbance can severely impede some soils ability to take in water.
- Impact of salt leaching requirements on system management, capacity, and drainage requirements.
- Effects of erosion and/or movement of sediment and sediment-attached substances carried by runoff including salinity, nutrients, pesticides, seeds and vegetative portions of invasive plants.
- Effect of elevated irrigation tailwater temperatures on downstream receiving waters.
- Irrigation system capacity should be determined based on appropriate design application efficiency. Design application efficiency should be no greater than 90 percent for properly designed level surface irrigation systems and a maximum of 80 percent for graded systems. Guidance for selecting design application efficiencies is provided in NRCS NEH Part 623, and NRCS NEH Part 652.
- Design, evaluation, and simulation models WINSRFR and SURFACE can be very useful tools in finalizing surface system designs.

When designing a subsurface irrigation system the following should be considered:

- Potential benefits of water level control on downstream water quality.
- Potential effects of practice management on lateral seepage.
- Orienting lateral lines along the contours to maximize the area influenced by each water level control structure.
- Soil layers in the water transmission zone (root zone) should have a higher lateral saturated hydraulic conductivity than the vertical saturated hydraulic conductivity of the water restrictive layer. However, if lateral hydraulic conductivity of any single soil layer in the root zone exceeds 10 times that of other layers, lateral seepage may make it difficult to raise the water table to the design depth.
- Irrigation system capacity should be determined based on an appropriate design application efficiency. Design application efficiency should be no greater than 90 percent for soils with minimal lateral losses and a maximum of 75 percent for all other soils.
- Be aware that additional pumping capacity may be needed to raise the water table during drought periods.
- Design procedures and guidance for subsurface irrigation system planning and design are provided in NRCS NEH Part 624, Chapter 10.

When planning a surface irrigation system employing an above ground, multi-outlet, distribution pipeline the following should be considered:

- Provisions should be made for thrust control at locations subject to pipe movement.
- Good grade control along the pipeline and along the rows is needed to assure uniform water distribution.
- Consider the water source and potential trash types and amounts when designing or selecting inlet screen types and sizes.
- Plan for disposal of used poly irrigation tubing and encourage recycling.
- Anchor poly irrigation tubing when winds may cause it to move.

- PVC Gated pipe with wall thickness less than 0.12 inch will be more flexible making soil support and uniform pipe grade more important if an irrigation stream contains sand. Sand will tend to settle and accumulate in any gated pipe lows.

***Flow Measurement**. A water measurement device or structure (ramp flume, cipolletti weir, etc.) may be installed to manage water applications and for on-going evaluation of system performance. Manufacturer's recommendations or sound engineering principles must be followed regarding size, placement, orientation, etc.*

PLANS AND SPECIFICATIONS

Construction plans shall include all components needed for the safe operation of the proposed improvements such as railing, fencing, or warning signs as appropriate. The plans shall address operations near existing utilities, trench excavations and any other items related to construction of the structure that may pose a safety risk to those involved.

*Development of p*lans and specifications for surface and subsurface irrigation systems *will be guided by the National Engineering Handbook, Part 650, the Engineering Field Handbook, and shall be in accordance with the National Engineering Manual, Parts 541 and 542, and* shall be in keeping with this standard, *prepared for each specific site* and shall *adequately* describe the requirements for applying *or installing* this practice to achieve its intended purpose. *As a minimum, the plans and specifications shall include:*

- *Project location map, including section, township and range, North arrow, cooperator/owner acknowledgement and certification signature blocks, engineering job class (cover sheet);*
- *References that the owner/cooperator are responsible for all permits, rights-of-way, easements and the contact, coordination and location determination of any existing utilities or clearances (buried utility disclaimer);*
- *If applicable, a map showing the location of the practice(s) or system in reference to a known or established benchmark or reference point with the location, description and elevation clearly shown. Topographical features and/or controls shall be shown, showing tie in with existing or other planned practices;*
- *Field surveys and notes, soil investigations or geologic soil boring locations and soil classifications, earthwork or material estimates/quantities (if applicable);*
- *System overview and layout (i.e., location and orientation of practice in relation to existing or planned facilities; identify the water source (reservoir, well, pump, etc.); stationing and alignment for all underground and above ground conveyance pipelines; pipe type, diameter, and rating; gate openings (size/type) and spacing; field or irrigated boundaries; field slopes; mainline and lateral line locations; vegetative requirements; construction/installation criteria, including State and Federal [OSHA] safety requirements, etc.);*
- *Profile views or cross sections (pipeline, ditches) of the proposed system and components;*
- *Appurtenance and/or fittings (i.e., valves, air vents, regulators, pressure relief, pressure regulators, etc.), as required, for proper system functionality.*
- *Construction notes, details or specifications to clarify a component and furnish directions or site specific requirement, i.e. quantities of materials.*
- *Use Arizona Construction and Material Specifications for each item of work and material, as applicable and available. Additional specifications may need to be written to provide full material and installation instructions.*

All designs completed by non-NRCS personal shall meet minimum State licensing board requirements and NRCS requirements and criteria as outlined in the General Manual, the National Engineering Manual (including Arizona Supplements), and the National Engineering Handbook.

OPERATION AND MAINTENANCE

An operation and maintenance plan specific to the *site and* facilities installed shall be prepared*, and reviewed,* for use by the landowner or operator responsible for operation and maintenance. The plan *shall document needed actions, including reference to periodic inspections and the prompt repair or replacement of damaged components, and*

should provide specific instructions for operating and maintaining facilities to ensure they function properly *and adequately throughout their expected life*.

O&M requirements shall be determined as part of the design. Any requirements should be documented as brief statements in the plans, the specifications, or the conservation plan narrative, or as a separate O&M plan. The plan shall include provisions to address the following:

- Periodic cleaning and regrading of tailwater collection facilities to maintain proper drainage, capacity, and functionality *and maintain design border/furrow spacing*.
- Periodic checks and removal of debris *or blockage* as necessary from trash racks*, ditch and pipe inlets, outlets,* and structures to assure proper operation.
- Periodic removal and planned placement of sediment from traps and/or storage facilities to maintain design capacity and efficiency.
- Inspection and testing of all pipeline and pumping plant components and appurtenances, *as applicable, including the prompt repair of all leaks or worn parts in delivery facilities*.
- Routine maintenance of all *screens, filters, valves, timers*, mechanical *and/or electrical* components in accordance with the manufacturer's recommendations.
- Periodic land smoothing or grading of surface irrigated fields required to maintain the design grade in the direction of flow.
- *Only operate the system when needed to furnish water for plant growth (peak consumptive use), salt management, or to store moisture within the soil profile. Monitor crops regularly, noting areas of moisture stress and repair or adjust system operations, as needed.*
- *Operate the system at the pressure, discharge rate, duration, speed, and frequency as designed, or adjust flows to provide uniform distribution throughout the border or furrow. Water should reach the end of the border/furrow so as to minimize runoff, yet maintain as uniform application throughout the system length.*
- *Allow the pipe and lateral lines to fill gradually when being put into use after shut down or draining. Filling at the specified rate requirements and opening/closing valves to prevent excessive water hammer.*
- *Adjust irrigation schedule(s) and set time(s), as necessary, for the soils, crops, topography, moisture monitoring method, allowable soil moisture depletion and irrigation induced erosion.*
- *Verify that runoff water is promptly removed by a drainage or tail water recovery system.*
- *During non-seasonal use, drain and place all removable appurtenances in an area where they will not be damaged.*
- *Remove all rodents or burrowing animals that have or may potentially damage any part of the delivery or application facilities. Immediately repair any damage caused by their activity.*
- *Immediately repair any damage resulting from vandalism, vehicles, or livestock.*
- *Install and maintain fences to prevent livestock access where excessive trampling of banks or ditch may occur, and do not allow livestock near equipment during operation.*
- *Maintain vigorous growth of vegetative coverings, this may include re-seeding, fertilization, and application or herbicides. Periodic mowing may also be needed to control excessive growth.*

Additionally for a subsurface irrigation, the plan shall include, as a minimum:

- Water control structure elevation settings by date required to maintain water table at design depth.
- Critical dates and water table target elevations during planned crop growing season.
- Inclusion of specification and locations of all required groundwater observation wells.

REFERENCES

USDA-NRCS, National Engineering Handbook, Part 623, Irrigation.

USDA-NRCS, National Engineering Handbook, Part 624, Drainage.

USDA-NRCS, National Engineering Handbook, Part 636, Chapter 52, Structural Design of Flexible Conduits.

USDA-NRCS, National Engineering Handbook, Part 650, Engineering Field Handbook, Chapter 14, Water Management (Drainage).

USDA-NRCS, National Engineering Handbook, Part 652, National Irrigation Guide.