

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD**

CROSS WIND RIDGES

(Ac.)

CODE 588

DEFINITION

Ridges formed by tillage, planting or other operations and aligned perpendicular to prevailing wind direction during critical wind erosion periods.

PURPOSE

This practice supports one or more of the following purposes:

- Reduce soil erosion from wind – Resource concern (SOIL EROSION - Sheet, rill, & wind erosion).
- Protect growing crops from damage by windblown soil particles – Resource concern (DEGRADED PLANT CONDITION – Undesirable plant productivity and health).
- Reduce soil particulate emissions affecting air quality – Resource concern (AIR QUALITY IMPACTS - Emissions of Particulate Matter - PM - and PM Precursors).

CONDITIONS WHERE PRACTICE APPLIES

This practice applies to cropland with soils that are stable enough to sustain effective ridges and cloddiness, such as loamy and clayey soil materials.

It is not well adapted on soils with lower aggregate stability such as sandy soil materials and certain organic soils.

CRITERIA

General Criteria Applicable to All Purposes

The ridge orientation, height, spacing, and time period that ridges are present shall be determined using the currently approved wind erosion prediction technology and shall account for other practices in the conservation management system.

Orientation of ridges during critical erosion periods shall not exceed 45 degrees from perpendicular to erosive wind direction.

Spacing between ridges shall be no more than 4 times the designed height of the created ridges.

Additional Criteria to Protect Growing Crops from Damage by Windblown Soil Particles.

Wind erosion shall not exceed the crop tolerance of sensitive crops to damage by windblown soil particles, as specified in the National Agronomy Manual (Table 502-1) and the planned conservation and production objectives.

CONSIDERATIONS

To be most effective, cross wind ridges should be oriented perpendicular to the direction of erosive winds.

Transport of windblown sediment and sediment-borne contaminants offsite can be reduced by this practice when used in a resource management system.

Adjacent fields, roads or field corners may need treatment to stop saltation of soil particles onto fields protected by cross wind ridges.

To be effective on coarse textured soils such as very fine sandy loams, fine sandy loams, sandy loams, and sand soils cross wind ridges should be established when soil is moist. Ridges on these soils will deteriorate quickly and shorten the protection period.

Cross wind ridges may be created at right angles to the predominant erosive wind direction on bare unprotected fields as a form of emergency tillage to reduce wind erosion. However, cross wind ridges generally have a temporary impact on reducing wind erosion and may not last throughout the critical wind erosion period.

Cross wind ridges are most effective when used in combination with other practices in a conservation management system to reduce wind erosion.

PLANS AND SPECIFICATIONS

Prepare Plans and Specifications for the establishment and operation of this practice for each field or treatment unit according to the planning criteria and operation and maintenance requirements of this conservation practice standard.

Specifications shall describe the requirements for applying this practice to achieve the intended purpose.

Record practice specifications in the Colorado 588 – Cross Wind Ridges, Implementation Requirements document.

OPERATION AND MAINTENANCE

Ridges shall be established or re-established by equipment such as chisel plows, drills with hoe openers, or other implements that form effective ridges.

After establishment, ridges shall be maintained through those periods when wind erosion is expected to occur, or until growing crops provide enough cover to protect the soil from wind erosion.

If ridges become ineffective they shall be re-established unless doing so would damage a growing crop.

REFERENCES

Skidmore, E.L. and N.P. Woodruff. 1968. Wind erosion forces in the United States and their use in predicting soil loss. USDA, Agriculture Handbook 346.

USDA, ARS. 2013. Wind Erosion Prediction System, ver 1.3.9. Manhattan, KS.
<http://ars.usda.gov/services/software/download.htm?softwareid=416>

USDA, ARS, NRCS. 2014. Wind Erosion Prediction System. Manhattan, KS.
<http://weru.ksu.edu/nrcs/wepsnrcs.html>

USDA, NRCS. 2011. National Agronomy Manual. 190-V. 4th ed., Part 502, Wind erosion. Table 502-1, Crop tolerance to blowing soil. pp 502-2. Washington, DC.
<http://directives.sc.egov.usda.gov/OpenNonWebContent.aspx?content=29608.wba>