POTENTIALLY HIGHLY ERODIBLE LAND		New Castle County, Delaware				
Map Unit Symbol	Map Unit Name	R	T	K	LS	EI*
AdB2	Aldino silt loam, 3 to 8 % slopes, mod. Eroded	190	3	0.43	0.29	7.8977
BuB2	Butlertown silt loam, 2 to 5% slopes, mod. Eroded	190	3	0.43	0.35	9.5317
ChB2	Chester loam, 3 to 8% slopes, mod. Eroded	190	4	0.32	0.72	10.9440
CsB2	Collington fsl, 2 to 5% slopes, mod. Eroded	190	4	0.28	0.35	4.6550
DeB2	Delanco sil, 3 to 8% slopes, mod. Eroded	190	4	0.37	0.72	12.6540
EaB2	Elioak sil, 3 to 8 % slopes, mod. Eroded	190	4	0.32	0.72	10.9440
EmB	Elkton sil, 2 to 5% slopes	190	3	0.43	0.35	9.5317
EnB2	Elsinboro sil, 3 to 8% slopes, mod. Eroded	190	4	0.37	0.72	12.6540
GmB2	Glenelg and Manor l, 3 to 8 % slopes, mod eroded	190	3	0.32	0.72	14.5920
GnB2	Glenville sil, 3 to 8% slopes,mod. Eroded	190	3	0.32	0.72	14.5920
HbA	Hatboro silt loam, local alluvium, 0 to 3 % slopes	190	4	0.49	0.15	3.4913
HbC	Hatboro silt loam, local alluvium, 3 to 12 % slopes	190	4	0.49	0.29	6.7498
KeB2	Keyport sil, 2-5%, Mod. Eroded	190	3	0.43	0.35	9.5317
KrB	Kinkora silt loam, 3 to 8% slopes	190	4	0.43	0.72	14.7060
MeB2	Matapeake sil, 2-5%, mod. Eroded	190	4	0.37	0.35	6.1513
MeC2	Matapeake sil, 5-10%, mod. Eroded	190	4	0.37	0.45	7.9088
MkB2	Matapeake sil, silty substratum, 2-5%, mod. Eroded	190	4	0.37	0.35	6.1513
MtB2	Mattapex sil, 2-5%, mod. Eroded	190	4	0.37	0.35	6.1513
MtC2	Mattapex sil, 5-10%, mod. Eroded	190	4	0.37	0.45	7.9088
NmB2	Neshaminy and Montalto silt loams, 3 to 8% slopes, mod. Er.	190	4	0.32	0.72	10.9440
RuC2	Rumford ls, 5-10 %, mod. Eroded	190	4	0.17	1.15	9.2863
SaB2	Sassafras sl, 2-5%, mod. Eroded	190	4	0.28	0.35	4.6550
SaC2	Sassafras sl, 5-10%, mod. Eroded	190	4	0.28	0.59	7.8470
TaB2	Talleyville silt loam, 2 to 5% slopes, mod. Eroded	190	4	0.32	0.72	10.9440
TaC2	Talleyville silt loam, 5 to 10% slopes, mod. Eroded	190	4	0.32	0.48	7.2960
WcA	Watchung and Calvert silt loams, 0 to 3 % slopes	190	3	0.43	0.15	4.0850
WcB	Watchung and Calvert silt loams, 3 to 8 % slopes	190	3	0.43	0.29	7.8977
WoB2	Woodstown sl, 2-5%, mod. Eroded	190	4	0.28	0.35	4.6550
WsB2	Woodstown l, 2-5%, mod. Eroded	190	4	0.28	0.35	4.6550

The Highly Erodible and Potentially Highly Erodible Soil Map Unit List is the list that was in effect as of January 1, 1990 and will be used to calculate the erodibility index (EI). If the LS factor for a field is greater than the LS factor listed for a specific soil, the EI will be greater than 8, and the soil will be considered highly erodible. * (EI)=(R x K x LS)/(T)

HIGHLY ERODIBLE LAND		New Castle County, Delaware				
Map Unit Symbol	Map Unit Name	R	T	K	LS	EI*
BuC2	Butlertown silt loam, 5 to 10 % slopes, mod. Eroded	190	3	0.43	1.15	31.3183
ChC2	Chester loam, 8 to 15% slopes, mod. Eroded	190	4	0.32	1.33	20.2160
ChC3	Chester loam, 8-15%, sev. eroded	190	3	0.43	1.33	36.2203
ChD2	Chester loam, 15-25%, mod. Eroded	190	4	0.32	3.70	56.2400
ChD3	Chester loam, 15 to 25% slopes, sev. Eroded	190	3	0.43	3.70	100.7633
CsC3	Collington fsl, 5 to 10% slopes, sev. Eroded	190	3	0.32	1.15	23.3067
CsD3	Collington fsl, 10 to 25% slopes, sev. Eroded	190	3	0.32	2.21	44.7893
EkC3	Elioak sicl, 8 to 15% slopes, sev. Eroded	190	3	0.37	1.33	31.1663
EkD3	Elioak sicl, 15 to 25% slopes, sev. Eroded	190	3	0.37	3.70	86.7033
EnC2	Elsinboro sil, 8 to 15% slopes, mod. Eroded	190	4	0.37	1.33	23.3748
GmC2	Glenelg and Manor l, 8 to 15 % slopes, mod eroded	190	3	0.32	1.33	26.9547
GmC3	Glenelg and Manor l, 8 to 15 % slopes, sev. eroded	190	2	0.43	1.33	54.3305
GmD2	Glenelg and Manor l, 15 to 25 % slopes, mod. Eroded	190	3	0.32	3.70	74.9867
GmD3	Glenelg and Manor l, 15 to 25 % slopes, sev. Eroded	190	2	0.43	3.70	151.1450
GmE	Glenelg and Manor l, 25 to 40 % slopes	190	3	0.32	---	
KeC2	Keyport sil, 5-10%, mod. Eroded	190	3	0.43	1.15	31.3183
KpC3	Keyport sicl, 5-10%, sev. eroded	190	2	0.32	1.15	34.9600
MeC3	Matapeake sil, 5-10%, sev. Eroded	190	3	0.43	1.15	31.3183
MeD2	Matapeake sil, 10-15%, mod. Eroded	190	4	0.37	2.21	38.8408
MeD3	Matapeake sil, 10-15%, sev. Eroded	190	3	0.43	2.21	60.1857
MkC2	Matapeake sil, silty substratum, 5-10%, mod. Eroded	190	4	0.37	1.15	20.2113
MtC3	Mattapex sil, 5-10%, sev. Eroded	190	3	0.43	1.15	31.3183
NmC2	Neshaminy and Montalto silt loams, 8 to 15% slopes, mod. Er.	190	4	0.32	1.33	20.2160
NnC3	Neshaminy and Montalto sicl's, 8 to 15% slopes, sev. er.	190	3	0.32	1.33	26.9547
NnD3	Neshaminy and Montalto sicl's, 15 to 25% slopes, sev. er.	190	3	0.32	3.70	74.9867
NsE	Neshaminy and Talleyville very stony sil's, 3 to 35% slopes	190	4	0.32	---	
SaC3	Sassafras sl, 5 to 10% slopes, sev. eroded	190	3	0.37	1.15	26.9483
SaD2	Sassafras sl, 10-15%, mod. Eroded	190	4	0.28	2.21	29.3930
SaD3	Sassafras sl, 10-15%, sev. Eroded	190	3	0.37	2.21	51.7877
SmE	Sassafras and Matapeake soils, 15-30%	190	4	0.28	---	

The Highly Erodible and Potentially Highly Erodible Soil Map Unit List is the list that was in effect as of January 1, 1990 and will be used to calculate the erodibility index (EI). If the LS factor for a field is greater than the LS factor listed for a specific soil, the EI will be greater than 8, and the soil will be considered highly erodible. * (EI)=(R x K x LS)/(T)