

NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD

UNDERGROUND OUTLET

(Feet)

CODE 620



DEFINITION

A conduit or system of conduits installed beneath the surface of the ground to convey surface water to a suitable outlet.

PURPOSE

To carry water to a suitable outlet from terraces, water and sediment control basins, diversions, waterways, surface drains, other similar practices or flow concentrations without causing damage by erosion or flooding.

CONDITIONS WHERE PRACTICE APPLIES

This practice applies where:

- Disposal of surface water is necessary.
- An outlet is needed for a terrace, diversion, water and sediment control basin, or similar practice but a surface outlet is impractical because of stability problems, topography, climatic conditions, land use or equipment traffic.
- The site is suitable for an underground outlet.

CRITERIA

Planned work shall be in conformance with all Federal, state, and local rules and regulations.

Impact to cultural resources, wetlands and Federal and state protected species shall be evaluated and avoided or minimized to the extent practicable during planning, design and implementation of this conservation practice in accordance with established National and Florida policy, General Manual (GM) Title 420-Part 401; Title 450-Part 401, Title 190-Parts 410.22 and 410.26, National Planning Procedures Handbook (NPPH) Florida Supplements to Parts 600.1 and 600.6, National Cultural Resources Procedures Handbook (NCRPH), National Food Security Act Manual (NFSAM), and the National Environmental Compliance Handbook (NECH).

Capacity. The design capacity of the underground outlet is based on requirements of the structure or practice it serves. The underground outlet can be designed to function as the only outlet for a structure or it can be designed to function with other type of outlets. The capacity of the underground outlet for natural or constructed basins shall be adequate for the intended purpose without causing inundation damage to crops, excessive damage to crops, vegetation, or improvements.

Underground outlets may be designed for either pressure or gravity flow. If a pressure system is designed, all pipe and joints must be adequate to withstand the design pressure, including surges and vacuum. To fully utilize conduit capacity, design the inlet to provide maximum flow in the conduit. To prevent pressure flow or overloading of the conduit a flow restricting device such as an orifice or weir can be used to limit flow into the conduit.

If there are multiple structures flowing into an underground outlet, design the system so that upstream structures do not discharge into downstream structures unless the downstream

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resources Conservation Service.

structure is designed to accommodate the extra flow.

Pressure-relief wells may be used to allow excess flow to escape the conduit and flow over the surface. Only use pressure relief wells where there is a stable outlet for the flow from the relief well. Cover pressure relief wells with a grate or other appropriate covering to prevent the entry of small animals and debris.

Inlet. An inlet can be a collection box, a perforated riser, or other appropriate device. For perforated risers, use durable, structurally sound material that is resistant to damage by rodents or other animals. Use fire resistant materials for the inlet if fire is an expected hazard.

Inlets must have an appropriate trash guard to ensure that trash or other debris entering the inlet passes through the conduit without plugging.

Design collection boxes large enough to allow maintenance and cleaning operations. Use blind inlets where the installation of an open or above ground structure is impractical. Design the blind inlet with a graded granular filter around the conduit. Design the filter based on the particle size of the surrounding soil and the desired flow rate. Refer to National Engineering Handbook (NEH) Part 650, Engineering Field Handbook, Chapter 14 for the design of blind inlets.

Conduit. Underground outlets shall be conduits of tubing, tile or pipe. The minimum allowable conduit diameter is 4 inches. Design hydraulically smooth joints using materials and methods recommended by the manufacturer of the conduit.

The maximum design velocity must not exceed the safe velocity for the conduit materials and installation according to the conduit manufacturer's recommendation. Refer to Florida conservation practice standard Subsurface Drain, Code 606 for safe velocity design criteria.

Thrust blocking or anchoring shall be provided where needed to prevent undesired movement of the conduit. Placement and bedding requirements for the conduit are required to ensure integrity of the installation.

If junction boxes and other structures are needed, design them to allow cleaning and other maintenance activities. Maintain a downward

grade towards the outlet in all sections of the underground outlet.

Materials. Plastic, concrete, aluminum, and steel shall meet the requirements specified in the applicable ASTM standard. All materials specified in Florida NRCS conservation practice standard Subsurface Drain, Code 606 can be used for underground outlets. Materials must meet applicable site specific design requirements for leakage, external loading, internal pressure, and vacuum.

Underground outlet conduits can be perforated or nonperforated, depending on the design requirements. Use a filter fabric wrap (sock) or appropriately designed granular filter if migration of soil particles around conduit is anticipated. Design the filter based on the particle size of the surrounding soil to prevent rapid clogging of the filter. Refer to Florida NRCS conservation practice standard Subsurface Drain, Code 606 for design criteria of filter media. Protect all exposed plastic materials from degradation due to exposure to sunlight.

Outlet. The outlet must be stable for anticipated design flow conditions from the underground outlet. Design the underground outlet for water surface conditions at the outlet expected during the design flow conditions.

The outlet must consist of a minimum length of 10 feet continuous section of closed conduit or a headwall at the outlet. If a closed conduit is used, the material must be durable and strong enough to withstand all anticipated loads. Do not design outlets to be placed in areas of active erosion. Use fire resistant materials if fire is an expected hazard. All outlets must have animal guards to prevent the entry of rodents or other animals. Design animal guards to allow passage of debris while blocking the entry of animals that cannot easily escape from the conduit.

A vertical outlet may be used to discharge water to the ground surface where topography does not allow adequate conduit cover using a horizontal outlet, or where it is practical to discharge over a vegetated filter strip.

The vertical outlet (relief well) shall be adequately perforated and placed in an envelope of coarsely graded aggregate to allow the system to drain during periods when not in use.

Stabilization. Re-shape and re-grade all disturbed areas so that they blend with the surrounding land features and conditions. Re-vegetate or otherwise protect from erosion, disturbed areas that will not be farmed, as soon as possible after construction in accordance with Florida conservation practice standard Critical Area Planting, Code 342.

CONSIDERATIONS

Pressure relief wells, if not properly covered, can present a safe hazard for people or animals stepping into the well. In addition, pressure relief wells can be easily damaged by field equipment. To prevent accidents mark the location of pressure relief wells with a high visibility marker.

The rapid removal of water through an underground outlet will affect the water budget where it is installed. It can reduce infiltration. It can increase or decrease peak flows to receiving waters and reduce long term flows into the same waters. Consider these long term environmental, social, and economic effects when making design decisions for the underground outlet and the structure or practice it serves.

If perforated pipe is used for the subsurface conduit, locate the practice so that it has a minimal effect to the hydrology of wetlands.

To prevent sediment from collecting in the conduit, underground outlets should be designed with a minimum velocity of 1.4 ft/s.

Where perforated risers are used, often the risers are perforated below the surface of the ground to facilitate drainage. In this situation, if soil entry into the riser perforations is a problem, use an appropriately designed gravel or geotextile filter around the buried portion of the riser.

Seasonal water sources can be very important for migratory waterfowl and other wildlife. The use of a water control structure, on the inlet of an underground outlet during non-cropping times of the year, can allow water to pond in the structure to provide water for wildlife.

Underground outlets can provide a direct conduit to receiving waters for contaminated runoff from crop land. Underground outlets and the accompanying structure or practice should be installed as part of a conservation system that addresses issues such as nutrient and pest

management, residue management and filter areas.

The construction of an underground outlet in a riparian corridor can have an adverse effect on the visual resources of the corridor. Consider the visual quality of the riparian area when designing the underground outlet.

If an installation in a crop field is too shallow, tillage equipment can damage an underground outlet. Consider the type and depth of tillage that will likely occur when designing the depth of an underground outlet. A minimum of 2 feet of cover is recommended over all conduits.

PLANS AND SPECIFICATIONS

Plans and specifications for underground outlets shall be in keeping with this standard and shall describe the requirements for installing the practice according to this standard. As a minimum, the plans and specifications shall include, but not limited to, the following:

- A plan view of the layout of the underground outlet.
- Typical cross sections or bedding requirements for the underground outlet.
- Profile of the underground outlet.
- Details of the inlet and outlet.
- Seeding requirements if needed.
- Construction specifications that describe in writing site specific installation requirements of the underground outlet.

OPERATION AND MAINTENANCE

An operation and maintenance plan shall be developed for this practice and include, but not limited to, the following items:

- Periodic inspections, especially immediately following significant runoff events. Promptly repair or replace of damaged components.
- Keep inlets, trash guards, collection boxes, and structures clean and free of materials that can reduce flow.
- Repair or replacement of inlets damaged by farm equipment.
- Repair of leaks and broken or crushed lines to insure proper functioning of the conduit.
- Periodic checking of the outlet and animal guards to ensure proper functioning.

- Repair of eroded areas at the pipe outlet.
- Maintenance of adequate backfill over the conduit.
- To maintain the permeability of surface materials on blind inlets, periodic scouring or removal and replacement of the surface soil layer may be necessary.

REFERENCES

Florida NRCS Conservation Practice Standards
Critical Area Planting, Code 342
Subsurface Drain, Code 606

General Manual

Title 420-Part 401

Title 450-Part 401

Title 190-Parts 410.22 and 410.26

National Cultural Resources Handbook

National Engineering Handbook, Part 650

Engineering Field Handbook, Chapter 14

National Environmental Compliance Handbook

National Food Security Act Manual

National Planning Procedures Handbook

Florida Supplements to Parts 600.1 and
600.6