U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE 01/13/2006

EROSION FACTORS

Mapunit	Comp %	Cap Clc	R Fact	Slope L-RV-H %	Slope length (ft)	Hyd Grp	T	WEI	Horz Desig	Depth (in)	Texture RV	Total Sand RV	Total Silt RV	Total Clay RV	USLE Kf Factor	OM RV %
IA015-Boone County, Iowa																
6																
Okoboji	95	3	175	0.0-0.5-1.0	200	b/d	5	86	H1	0-16	SICL	7.4	54.1	38.5	.32	10.50
									H2	16-36	SICL	7.4	54.1	38.5	.32	8.50
									H3	36-60	SR- L SICL	20.1	54.9	25.0	.28	2.00
27C																
Terril	95	3	175	5.0-7.0-9.0	151	b	5	48	H1	0-28	L	41.1	36.9	22.0	.24	3.50
									H2	28-61	L	37.4	35.6	27.0	.28	2.50
28B																
Dickman	100	3	175	1.0-3.0-5.0	200	a	3	86	H1	0-16	FSL	67.6	20.4	12.0	.20	2.00
									H2	16-50	SL	68.3	19.7	12.0	.20	1.50
									H3	50-60	SR- S SI	96.0	1.5	2.5	.15	0.25
28C																
Dickman	100	4	175	5.0-7.0-9.0	151	a	3	86	H1	0-16	FSL	67.6	20.4	12.0	.20	2.00
									H2	16-50	SL	68.3	19.7	12.0	.20	1.50
									H3	50-60	SR- S SI	96.0	1.5	2.5	.15	0.25
55																
Nicollet	95	1	175	1.0-2.0-3.0	200	b	5	48	H1	0-17	L	38.1	36.4	25.5	.24	5.50
									H2	17-37	CL	33.6	36.9	29.5	.32	0.75
									H3	37-60	L	37.4	35.6	27.0	.32	0.25
62C2																
Storden	100	3	175	5.0-7.0-9.0	151	b	5	86	H1	0-6	L	39.8	37.7	22.5	.28	2.20
									H2	6-60	L	39.1	36.9	24.0	.37	0.25
62D2																
Storden	100	3	175	9.0-12.0-14.0	151	b	5	86	H1	0-6	L	39.8	37.7	22.5	.28	2.20
									H2	6-60	L	39.1	36.9	24.0	.37	0.25
62E2																
Storden	100	4	175	14.0-16.0-18.0	125	b	5	86	H1	0-6	L	39.8	37.7	22.5	.28	2.20
									H2	6-60	L	39.1	36.9	24.0	.37	0.25
62F																
Storden	100	6	175	18.0-22.0-25.0	125	b	5	86	H1	0-6	L	39.8	37.7	22.5	.28	3.00
									H2	6-60	L	39.1	36.9	24.0	.37	0.25
73D																
Salida	95	4	175	5.0-10.0-14.0	151	a	5	0	H1	0-8	GR-SL	66.6	23.4	10.0	.20	2.00
									H2	8-13	GR-LS	79.2	15.8	5.0	.17	0.25
									H3	13-60	GR-LS	81.1	16.4	2.5	.17	0.25

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE 01/13/2006

EROSION FACTORS

Mapunit	Comp %	Cap Clc	R Fact	Slope L-RV-H %	Slope length (ft)	Hyd Grp	T	WEI	Horz Desig	Depth (in)	Texture RV	Total Sand RV	Total Silt RV	Total Clay RV	USLE Kf Factor	OM RV %
73F																
Salida	90	7	175	14.0-20.0-25.0	125	a	5	0	H1	0-8	GR-SL	66.6	23.4	10.0	.20	2.00
									H2	8-13	GR-LS	79.2	15.8	5.0	.17	0.25
									H3	13-60	GR-LS	81.1	16.4	2.5	.17	0.25
90																
Okoboji	95	3	175	0.0-0.5-1.0	200	b/d	5	48	H1	0-9	MK-SIL	24.0	51.0	25.0	.32	13.50
									H2	9-27	SICL	7.4	54.1	38.5	.32	8.50
									H3	27-42	SICL	7.1	52.9	40.0	.32	3.50
									H4	42-60	SR- L SICL	38.5	36.5	25.0	.28	2.00
95																
Harps	95	2	175	0.0-1.0-2.0	200	b/d	5	86	H1	0-22	L	38.0	36.0	26.0	.24	5.00
									H2	22-54	L	38.5	36.5	25.0	.32	2.50
									H3	54-61	L	38.5	36.5	25.0	.32	0.50
107																
Webster	95	2	175	0.0-1.0-2.0	200	b/d	5	38	H1	0-22	SICL	20.0	49.0	31.0	.28	6.50
									H2	22-33	SICL	17.8	52.2	30.0	.32	3.00
									H3	33-60	L	39.2	37.3	23.5	.32	1.50
135																
Coland	95	2	175	0.0-1.0-2.0	200	b/d	5	48	H1	0-9	CL	35.4	33.6	31.0	.24	6.00
									H2	9-41	CL	35.4	33.6	31.0	.24	4.00
									H3	41-60	CL	38.8	33.2	28.0	.28	1.00
138B																
Clarion	100	2	175	2.0-4.0-5.0	200	b	5	48	H1	0-18	L	41.6	37.4	21.0	.24	3.50
									H2	18-40	L	37.4	35.6	27.0	.37	0.75
									H3	40-60	L	43.3	39.7	17.0	.37	0.25
138C																
Clarion	100	3	175	5.0-7.0-9.0	151	b	5	48	H1	0-18	L	41.6	37.4	21.0	.24	3.50
									H2	18-40	L	37.4	35.6	27.0	.37	0.75
									H3	40-60	L	43.3	39.7	17.0	.37	0.25
138C2																
Clarion	95	3	175	5.0-7.0-9.0	151	b	5	48	H1	0-7	L	41.6	37.4	21.0	.28	2.70
									H2	7-18	L	41.6	37.4	21.0	.32	1.50
									H3	18-40	L	37.4	35.6	27.0	.37	0.75
									H4	40-60	L	43.3	39.7	17.0	.37	0.25
138D2																
Clarion	95	3	175	9.0-12.0-14.0	151	b	5	48	H1	0-7	L	41.6	37.4	21.0	.28	2.70
									H2	7-18	L	41.6	37.4	21.0	.32	1.50
									H3	18-40	L	37.4	35.6	27.0	.37	0.75
									H4	40-60	L	43.3	39.7	17.0	.37	0.25

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE 01/13/2006

EROSION FACTORS

Mapunit	Comp %	Cap Clc	R Fact	Slope L-RV-H %	Slope length (ft)	Hyd Grp	T	WEI	Horz Desig	Depth (in)	Texture RV	Total Sand RV	Total Silt RV	Total Clay RV	USLE Kf Factor	OM RV %
167																
Ames	100	3	175	0.0-0.5-1.0	200	c/d	5	48	H1	0-17	SIL	27.0	54.0	19.0	.37	3.00
									H2	17-53	CL	29.7	31.8	38.5	.37	0.50
									H3	53-60	L	37.2	36.3	26.5	.37	0.25
168B																
Hayden	100	2	175	2.0-4.0-5.0	200	b	5	56	H1	0-10	L	43.0	39.5	17.5	.32	2.50
									H2	10-42	L	37.9	35.6	26.5	.37	0.75
									H3	42-60	L	41.6	37.4	21.0	.28	0.25
168C																
Hayden	100	3	175	5.0-7.0-9.0	151	b	5	56	H1	0-10	L	43.0	39.5	17.5	.32	2.50
									H2	10-42	L	37.9	35.6	26.5	.37	0.75
									H3	42-60	L	41.6	37.4	21.0	.28	0.25
168C2																
Hayden	100	3	175	5.0-7.0-9.0	151	b	5	56	H1	0-10	L	43.0	39.5	17.5	.32	2.00
									H2	10-42	L	37.9	35.6	26.5	.37	0.75
									H3	42-60	L	41.6	37.4	21.0	.28	0.25
168D2																
Hayden	95	3	175	9.0-12.0-14.0	151	b	5	56	H1	0-10	L	43.0	39.5	17.5	.32	2.00
									H2	10-42	L	37.9	35.6	26.5	.37	0.75
									H3	42-60	L	41.6	37.4	21.0	.28	0.25
Storden	5	3	175	9.0-12.0-14.0	151	b	5	86	H1	0-6	L	39.8	37.7	22.5	.28	2.20
									H2	6-60	L	39.1	36.9	24.0	.37	0.25
168E																
Hayden	95	4	175	14.0-16.0-18.0	125	b	5	56	H1	0-10	L	43.0	39.5	17.5	.32	2.50
									H2	10-42	L	37.9	35.6	26.5	.37	0.75
									H3	42-60	L	41.6	37.4	21.0	.28	0.25
203																
Cylinder	95	2	175	0.0-1.0-2.0	200	b	4	48	H1	0-24	L	38.8	36.7	24.5	.24	4.50
									H2	24-35	L	38.0	36.0	26.0	.32	2.50
									H3	35-60	COS	89.2	3.8	7.0	.15	0.25
221																
Palms	100	3	175	0.0-0.5-1.0	200	a/d	5	134	H1	0-36	MUCK	19.0	53.0	28.0	.28	35.00
									H2	36-63	SIL	26.3	52.7	21.0	.37	7.50
224																
Linder	95	2	175	0.0-1.0-2.0	200	b	4	86	H1	0-19	SL	65.1	18.9	16.0	.20	4.00
									H2	19-31	SL	66.8	19.2	14.0	.24	0.25
									H3	31-60	GR-S	93.6	1.4	5.0	.20	0.25

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE 01/13/2006

EROSION FACTORS

Mapunit	Comp %	Cap Clc	R Fact	Slope L-RV-H %	Slope length (ft)	Hyd Grp	T	WEI	Horz Desig	Depth (in)	Texture RV	Total Sand RV	Total Silt RV	Total Clay RV	USLE Kf Factor	OM RV %
236B																
Lester	100	2	175	2.0-4.0-5.0	200	b	5	48	H1	0-10	L	41.6	37.4	21.0	.28	3.00
									H2	10-32	CL	33.6	36.9	29.5	.28	0.75
									H3	32-48	L	38.5	36.5	25.0	.37	0.25
236C2																
Lester	100	3	175	5.0-7.0-9.0	151	b	5	48	H1	0-10	L	41.6	37.4	21.0	.28	2.50
									H2	10-32	CL	33.6	36.9	29.5	.28	0.75
									H3	32-48	L	38.5	36.5	25.0	.37	0.25
259																
Biscay	95	2	175	0.0-1.0-2.0	200	b/d	4	48	H1	0-17	CL	36.5	35.5	28.0	.28	6.00
									H2	17-36	CL	36.5	35.5	28.0	.28	0.75
									H3	36-60	SR- GR-COS LS	80.4	16.1	3.5	.10	0.25
307																
Dundas	95	2	175	0.0-1.0-2.0	200	b/d	5	48	H1	0-10	SIL	27.1	54.4	18.5	.28	4.00
									H2	10-35	CL	34.7	37.8	27.5	.28	0.50
									H3	35-60	L	39.8	37.7	22.5	.28	0.25
308																
Wadena	95	2	175	0.0-1.0-2.0	200	b	4	48	H1	0-21	L	39.8	37.7	22.5	.24	4.00
									H2	21-38	SL	62.0	19.0	19.0	.32	0.75
									H3	38-60	SR- GR-COS S	94.4	2.6	3.0	.32	0.25
308B																
Wadena	95	2	175	2.0-4.0-5.0	200	b	4	48	H1	0-21	L	39.8	37.7	22.5	.24	3.50
									H2	21-38	SL	62.0	19.0	19.0	.32	0.75
									H3	38-60	SR- GR-COS S	94.4	2.6	3.0	.32	0.25
325																
Le Sueur	95	1	175	0.0-1.0-2.0	200	b	5	48	H1	0-8	L	39.2	37.3	23.5	.24	3.50
									H2	8-40	CL	33.6	36.9	29.5	.32	1.25
									H3	40-60	L	38.5	36.5	25.0	.32	0.25
335																
Harcot	100	2	175	0.0-1.0-2.0	200	b/d	4	86	H1	0-20	L	38.1	36.4	25.5	.24	5.00
									H2	20-33	GR-SCL	58.2	17.8	24.0	.28	1.50
									H3	33-60	GR-S	93.6	1.4	5.0	.15	0.50
354																
Palms	100	5	175	0.0-0.5-1.0	200	a/d	5	134	H1	0-14	MPT	19.0	53.0	28.0	.28	35.00
									H2	14-36	MUCK	19.0	53.0	28.0	.28	35.00
									H3	36-60	SIL	26.3	52.7	21.0	.37	7.50

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE 01/13/2006

EROSION FACTORS

Mapunit	Comp %	Cap Clc	R Fact	Slope L-RV-H %	Slope length (ft)	Hyd Grp	T	WEI	Horz Desig	Depth (in)	Texture RV	Total Sand RV	Total Silt RV	Total Clay RV	USLE Kf Factor	OM RV %
355																
Luther	95	1	175	0.0-1.0-2.0	200	b	5	48	H1	0-4	L	41.1	36.9	22.0	.28	3.00
									H2	4-15	L	41.6	37.4	21.0	.32	0.75
									H3	15-36	CL	34.7	32.8	32.5	.32	0.25
									H4	36-60	L	37.9	35.6	26.5	.32	0.25
356G																
Hayden	40	7	175	25.0-38.0-50.0	102	b	5	56	H1	0-10	L	43.0	39.5	17.5	.32	2.70
									H2	10-42	L	37.9	35.6	26.5	.37	0.75
									H3	42-60	L	41.6	37.4	21.0	.28	0.25
Storden	40	7	175	25.0-38.0-50.0	102	b	5	86	H1	0-6	L	39.8	37.7	22.5	.28	2.70
									H2	6-60	L	39.1	36.9	24.0	.37	0.25
383																
Marna	95	2	175	0.0-1.0-2.0	200	c/d	5	86	H1	0-22	SICL	17.3	47.7	35.0	.28	6.50
									H2	22-46	SIC	5.5	47.0	47.5	.32	0.75
									H3	46-60	CL	33.6	36.9	29.5	.37	0.25
385B																
Guckeen	95	2	175	1.0-3.0-4.0	200	c	5	86	H1	0-18	CL	30.2	32.3	37.5	.28	5.00
									H2	18-36	SICL	6.8	54.2	39.0	.28	0.75
									H3	36-60	CL	34.8	33.2	32.0	.37	0.25
444C																
Jacwin	95	3	175	3.0-6.0-9.0	151	b	4	48	H1	0-13	L	38.8	36.7	24.5	.28	5.00
									H2	13-29	SCL	56.3	17.7	26.0	.28	1.50
									H3	29-33	C	18.2	29.3	52.5	.28	0.50
									H4	33-60	WB	--	--	--	--	---
485																
Spillville	95	2	175	0.0-1.0-2.0	200	b	5	48	H1	0-52	L	41.1	36.9	22.0	.24	4.50
									H2	52-60	L	42.7	38.3	19.0	.28	2.50
485B																
Spillville	95	2	175	2.0-4.0-5.0	200	b	5	48	H1	0-52	L	41.1	36.9	22.0	.24	4.00
									H2	52-60	L	42.7	38.3	19.0	.28	2.50
507																
Canisteo	95	2	175	0.0-1.0-2.0	200	b/d	5	86	H1	0-18	SICL	20.0	49.0	31.0	.24	6.50
									H2	18-38	CL	37.1	35.4	27.5	.32	0.75
									H3	38-60	L	37.4	35.6	27.0	.32	0.25
511																
Blue Earth	95	3	175	0.0-0.5-1.0	200	b/d	5	48	H1	0-22	MK-L	32.2	42.8	25.0	.28	20.00
									H2	22-40	L	32.2	42.8	25.0	.28	17.50
									H3	40-65	SICL	7.4	64.6	28.0	.28	0.25

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE 01/13/2006

EROSION FACTORS

Mapunit	Comp %	Cap Clc	R Fact	Slope L-RV-H %	Slope length (ft)	Hyd Grp	T	WEI	Horz Desig	Depth (in)	Texture RV	Total Sand RV	Total Silt RV	Total Clay RV	USLE Kf Factor	OM RV %
536																
Hanlon	95	2	175	0.0-1.0-2.0	200	b	5	86	H1	0-8	FSL	65.4	19.6	15.0	.20	2.50
									H2	8-43	FSL	65.4	19.6	15.0	.20	1.50
									H3	43-60	FSL	65.2	27.3	7.5	.20	1.50
									H4	60-64	FSL	63.5	26.5	10.0	.24	0.50
559																
Talcot	95	2	175	0.0-1.0-2.0	200	b/d	4	86	H1	0-23	CL	34.7	32.8	32.5	.28	6.00
									H2	23-38	CL	34.7	32.8	32.5	.28	4.00
									H3	38-60	SR- GR-COS LS	80.4	16.1	3.5	.15	0.75
566B																
Moingona	100	2	175	1.0-3.0-5.0	200	b	5	56	H1	0-12	L	42.7	38.3	19.0	.24	3.50
									H2	12-40	CL	37.0	35.0	28.0	.28	0.75
									H3	40-60	L	37.1	40.4	22.5	.28	0.25
566C																
Moingona	100	3	175	5.0-7.0-9.0	151	b	5	56	H1	0-12	L	42.7	38.3	19.0	.24	3.50
									H2	12-40	CL	37.0	35.0	28.0	.28	0.75
									H3	40-60	L	37.1	40.4	22.5	.28	0.25
566D																
Moingona	100	3	175	9.0-12.0-14.0	151	b	5	56	H1	0-12	L	42.7	38.3	19.0	.24	3.50
									H2	12-40	CL	37.0	35.0	28.0	.28	0.75
									H3	40-60	L	37.1	40.4	22.5	.28	0.25
585B																
Coland	50	2	175	2.0-4.0-5.0	200	b/d	5	48	H1	0-9	CL	35.4	33.6	31.0	.24	5.50
									H2	9-41	CL	35.4	33.6	31.0	.24	4.00
									H3	41-60	L	42.7	38.3	19.0	.28	1.00
Spillville	40	2	175	2.0-4.0-5.0	200	b	5	48	H1	0-52	L	41.1	36.9	22.0	.24	5.00
									H2	52-60	L	42.7	38.3	19.0	.28	2.50
636																
Buckney	95	3	175	1.0-2.0-3.0	200	b	4	86	H1	0-17	FSL	66.9	20.1	13.0	.20	2.00
									H2	17-60	FSL	63.5	26.5	10.0	.20	0.50
639D																
Storden	60	4	175	9.0-12.0-14.0	151	b	5	86	H1	0-6	L	39.8	37.7	22.5	.28	2.50
									H2	6-60	L	39.1	36.9	24.0	.37	0.25
Salida	30	4	175	9.0-12.0-14.0	151	a	5	0	H1	0-8	GR-SL	66.6	23.4	10.0	.20	2.50
									H2	8-13	GR-LS	79.2	15.8	5.0	.17	0.25
									H3	13-60	GR-LS	81.1	16.4	2.5	.17	0.25

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE 01/13/2006

EROSION FACTORS

Mapunit	Comp %	Cap Clc	R Fact	Slope L-RV-H %	Slope length (ft)	Hyd Grp	T	WEI	Horz Desig	Depth (in)	Texture RV	Total Sand RV	Total Silt RV	Total Clay RV	USLE Kf Factor	OM RV %
639E																
Storden	60	6	175	14.0-20.0-25.0	125	b	5	86	H1	0-6	L	39.8	37.7	22.5	.28	2.50
									H2	6-60	L	39.1	36.9	24.0	.37	0.25
Salida	30	7	175	14.0-20.0-25.0	125	a	5	0	H1	0-8	GR-SL	66.6	23.4	10.0	.20	2.50
									H2	8-13	GR-LS	79.2	15.8	5.0	.17	0.25
									H3	13-60	GR-LS	81.1	16.4	2.5	.17	0.25
655																
Crippin	95	1	175	1.0-2.0-3.0	200	b	5	86	H1	0-18	L	38.8	36.7	24.5	.24	5.50
									H2	18-30	L	37.4	35.6	27.0	.28	3.50
									H3	30-60	L	38.5	36.5	25.0	.37	1.50
733																
Calco	100	2	175	0.0-1.0-2.0	200	b/d	5	86	H1	0-12	SICL	6.9	62.6	30.5	.28	6.00
									H2	12-33	CL	26.3	41.2	32.5	.28	4.00
									H3	33-60	CL	27.1	44.9	28.0	.32	2.00
778																
Sattre	95	2	175	0.0-1.0-2.0	200	b	4	48	H1	0-15	L	41.6	37.4	21.0	.24	3.50
									H2	15-35	L	39.5	37.5	23.0	.28	0.75
									H3	35-60	S	93.6	1.4	5.0	.20	0.25
778B																
Sattre	100	2	175	2.0-4.0-5.0	200	b	4	48	H1	0-15	L	41.6	37.4	21.0	.24	3.00
									H2	15-35	L	39.5	37.5	23.0	.28	0.75
									H3	35-60	S	93.6	1.4	5.0	.20	0.25
778C																
Sattre	100	3	175	5.0-7.0-9.0	151	b	4	48	H1	0-15	L	41.6	37.4	21.0	.24	3.00
									H2	15-35	L	39.5	37.5	23.0	.28	0.75
									H3	35-60	S	93.6	1.4	5.0	.20	0.25
823																
Ridgeport	100	3	175	0.0-1.0-2.0	200	b	4	86	H1	0-14	SL	66.8	19.2	14.0	.20	2.50
									H2	14-32	SL	66.8	19.2	14.0	.24	0.50
									H3	32-60	S	93.6	1.4	5.0	.15	0.25
823B																
Ridgeport	100	3	175	2.0-4.0-5.0	200	b	4	86	H1	0-14	SL	66.8	19.2	14.0	.20	2.00
									H2	14-32	SL	66.8	19.2	14.0	.24	0.50
									H3	32-60	S	93.6	1.4	5.0	.15	0.25
823C2																
Ridgeport	100	3	175	5.0-7.0-9.0	151	b	4	86	H1	0-14	SL	66.8	19.2	14.0	.24	1.50
									H2	14-32	SL	66.8	19.2	14.0	.28	0.25
									H3	32-60	S	93.6	1.4	5.0	.15	0.25

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE 01/13/2006

EROSION FACTORS

Mapunit	Comp %	Cap Clc	R Fact	Slope L-RV-H %	Slope length (ft)	Hyd Grp	T	WEI	Horz Desig	Depth (in)	Texture RV	Total Sand RV	Total Silt RV	Total Clay RV	USLE Kf Factor	OM RV %
828B																
Zenor	95	3	175	2.0-4.0-5.0	200	b	4	86	H1	0-12	SL	67.9	19.6	12.5	.20	2.00
									H2	12-33	L	43.8	40.2	16.0	.20	0.50
									H3	33-60	LS	79.2	15.8	5.0	.15	0.50
828C																
Zenor	95	3	175	5.0-7.0-9.0	151	b	4	86	H1	0-12	SL	67.9	19.6	12.5	.20	1.50
									H2	12-33	L	43.8	40.2	16.0	.20	0.50
									H3	33-60	LS	79.2	15.8	5.0	.15	0.50
828C2																
Zenor	95	3	175	5.0-7.0-9.0	151	b	4	86	H1	0-12	SL	67.9	19.6	12.5	.20	1.50
									H2	12-33	L	43.8	40.2	16.0	.20	0.50
									H3	33-60	LS	79.2	15.8	5.0	.15	0.50
829D2																
Zenor	50	4	175	9.0-12.0-14.0	151	b	4	86	H1	0-12	SL	67.9	19.6	12.5	.20	1.80
									H2	12-33	L	43.8	40.2	16.0	.20	0.50
									H3	33-60	LS	79.2	15.8	5.0	.15	0.50
Storden	30	3	175	9.0-12.0-14.0	151	b	5	86	H1	0-6	L	39.8	37.7	22.5	.28	1.80
									H2	6-60	L	39.1	36.9	24.0	.37	0.25
829E2																
Zenor	50	6	175	14.0-20.0-25.0	125	b	4	86	H1	0-12	SL	67.9	19.6	12.5	.20	1.80
									H2	12-33	L	43.8	40.2	16.0	.20	0.50
									H3	33-60	LS	79.2	15.8	5.0	.15	0.50
Storden	30	6	175	14.0-20.0-25.0	125	b	5	86	H1	0-6	L	39.8	37.7	22.5	.28	1.80
									H2	6-60	L	39.1	36.9	24.0	.37	0.25
1135																
Coland	90	5	175	0.0-1.0-2.0	200	b/d	5	48	H1	0-9	CL	35.4	33.6	31.0	.24	5.50
									H2	9-41	CL	35.4	33.6	31.0	.24	4.00
									H3	41-60	CL	38.8	33.2	28.0	.28	1.00
1636																
Buckney	90	5	175	0.0-1.0-2.0	200	b	4	86	H1	0-17	FSL	66.9	20.1	13.0	.20	2.00
									H2	17-60	FSL	63.5	26.5	10.0	.20	0.50
2485B																
Spillville	50	2	175	2.0-4.0-5.0	200	b	5	48	H1	0-52	L	41.1	36.9	22.0	.24	3.00
									H2	52-60	L	42.7	38.3	19.0	.28	2.50
Buckney	30	6	175	0.0-1.0-2.0	200	b	4	86	H1	0-17	FSL	66.9	20.1	13.0	.20	3.00
									H2	17-60	FSL	63.5	26.5	10.0	.20	0.50

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE 01/13/2006

EROSION FACTORS

Mapunit	Comp %	Cap Clc	R Fact	Slope L-RV-H %	Slope length (ft)	Hyd Grp	T	WEI	Horz Desig	Depth (in)	Texture RV	Total Sand RV	Total Silt RV	Total Clay RV	USLE Kf Factor	OM RV %
4055																
Nicollet	50	1	175	1.0-2.0-3.0	200	b	5	48	H1	0-17	L	38.1	36.4	25.5	.24	6.00
									H2	17-37	CL	33.6	36.9	29.5	.32	0.75
									H3	37-60	L	37.4	35.6	27.0	.32	0.25
4138B																
Clarion	50	2	175	2.0-4.0-5.0	200	b	5	48	H1	0-18	L	41.6	37.4	21.0	.24	4.00
									H2	18-40	L	37.4	35.6	27.0	.37	0.75
									H3	40-60	L	43.3	39.7	17.0	.37	0.25
4138C																
Clarion	50	3	175	5.0-7.0-9.0	151	b	5	48	H1	0-18	L	41.6	37.4	21.0	.24	4.00
									H2	18-40	L	37.4	35.6	27.0	.37	0.75
									H3	40-60	L	43.3	39.7	17.0	.37	0.25
Storden	20	3	175	5.0-7.0-9.0	151	b	5	86	H1	0-6	L	39.8	37.7	22.5	.28	2.20
									H2	6-60	L	39.1	36.9	24.0	.37	0.25
4507																
Canisteo	50	2	175	0.0-1.0-2.0	200	b/d	5	86	H1	0-18	SICL	20.0	49.0	31.0	.24	6.00
									H2	18-36	CL	37.1	34.4	28.5	.32	0.75
									H3	36-60	L	37.4	35.6	27.0	.32	0.25
5040																
Orthents	100		175	?-?-?	---	--	--	--	H1	0-80	VAR	--	--	--	--	---