

**NATURAL RESOURCES CONSERVATION SERVICE**  
**CONSERVATION PRACTICE STANDARD**  
**CHANNEL BED STABILIZATION**

(Ft.)

**CODE 584**

**DEFINITION**

Measure(s) used to stabilize the bed or bottom of a channel.

**PURPOSE**

This practice may be applied as part of a conservation management system to support one or more of the following:

- Maintain or alter channel bed elevation or gradient
- Modify sediment transport or deposition
- Manage surface water and groundwater levels in floodplains, riparian areas, and wetlands.

**CONDITIONS WHERE PRACTICE APPLIES**

This practice applies to the beds of existing or newly constructed alluvial or threshold channels that are undergoing damaging aggradation or degradation and that cannot be feasibly controlled by clearing or snagging, by the establishment of vegetative protection, by the installation of bank protection, or by the installation of upstream water control measures.

**CRITERIA**

Measures shall be designed and installed according to a site-specific plan.

Measures to be applied shall be compatible with improvements planned or being carried out by others.

Sufficient depth shall be maintained to provide adequate outlets for subsurface drains, tributary streams or ditches, or other channels.

The effect of channel work on existing structures such as culverts, bridges, buried cables,

pipelines, and irrigation flumes, shall be evaluated to determine impact on their intended functions.

Measures shall be designed for flow duration, depth of inundation, buoyancy, uplift, scour, angle of attack, and stream velocity and be sustainable for higher flow conditions, based on acceptable risk.

Measures shall be compatible with the bank or shoreline materials, water chemistry, channel hydraulics, and slope characteristics, both above and below the water line.

Measures shall be designed for anticipated ice action, debris impact, and fluctuating water levels.

Spoil material from clearing, grubbing, and channel excavation shall be disposed of in a manner that will not interfere with the function of the channel and in accordance with all local, State, Tribal, and Federal laws and regulations.

All disturbed areas around measures shall be protected from erosion. Vegetation shall be selected that is best suited for the anticipated site conditions.

Measures shall be designed to avoid adverse effects on endangered, threatened, proposed, and candidate species and their habitats.

Measures shall be designed to avoid adverse effects on archaeological, historic, structural, and traditional cultural properties.

Measures will not impede the upstream or downstream passage of aquatic organisms.

Channel clearing to remove stumps, fallen trees, debris, and sediment bars shall only be done when they are causing or could cause detrimental bank erosion or structural failure. Habitat-forming elements that provide cover,

food, pools, and water turbulence shall be retained or replaced to the extent possible.

Measures shall be designed to maintain the appropriate sediment transport regime in order to avoid detrimental erosion or sedimentation upstream and downstream.

Measures shall not impair the floodway or floodplain functions.

Measures shall not result in adverse effects on the function of the stream or the stream corridor. These adverse effects include destruction of instream habitat, sediment transport imbalances, passage barriers, or unexpected changes in channel plan, pattern, or profile.

When water surface elevations are a concern, the effects of protective measures shall not cause detrimental changes in water surface elevations.

The quantity and character of the sediments entering the reach of channel under consideration shall be analyzed on the basis of both present conditions and projected conditions caused by changes in land use or land treatment and upstream improvements or structural measures.

## CONSIDERATIONS

Consider area-wide planning for proper design, function, and management of protective measures, where the design reach involves multiple stakeholders.

Assess channel stabilization needs in sufficient detail to identify the causes contributing to the instability (e.g. watershed alterations resulting in significant modifications of discharge or sediment production). Due to the complexity of such an assessment, use of an interdisciplinary team should be considered.

When designing protective measures, consider the changes that may occur in the watershed hydrology and sedimentation over the design life of the measure.

Consider using woody material removed during construction in the overall practice design.

Consider maintaining or improving the habitat value for fish and wildlife, which includes lowering or moderating water temperature, and improving water quality.

Consider opportunities to improve habitat for threatened, endangered, and other species of concern, where applicable.

Consider maximizing adjacent wetland functions and values with the project design and minimizing adverse effects to existing wetland functions and values.

Consider protecting side channel inlets and outlets from erosion or sedimentation.

Consider the type of human use and social and safety aspects when designing the protective measures. Use construction materials, grading practices, vegetation, and other site development elements that enhance aesthetics, recreational use, and maintain or complement existing landscape uses such as pedestrian paths, climate controls, and buffers. Avoid excessive disturbance and compaction of the site during installation.

Measures should be designed to minimize safety hazards to boaters, swimmers, or people using the channel.

## PLANS AND SPECIFICATIONS

Plans and specifications for this practice shall be prepared for specific channel reaches and field sites and shall describe the requirements for applying the practice to achieve its intended purpose(s).

Construction operations shall be carried out in a manner and sequence so that impacts on the environment will be minimized and held within acceptable limits.

As a minimum, include, as applicable, the following items in the plans and specifications:

- plan view of the layout of the channel and work planned
- typical cross section of the channel work area
- Profile of the channel work area
- description of works of improvement and extent of removal
- location of disposal areas or location of areas off limits for disposal of debris
- location and description of trees or woody vegetation to be left undisturbed

- method of debris disposal
- manner and sequence of construction operations so that impacts on the environment will be minimized
- erosion control measures, as applicable
- vegetative requirements for areas denuded and disturbed, as applicable

All operations shall be carried out in a safe and skillful manner. Safety and health regulations shall be observed and appropriate safety measures used.

The following list of Construction Specifications is intended as a guide to selecting the appropriate specifications for each specific project. The list includes most, but may not contain all, of the specifications needed for a specific project:

IA-1	Site Preparation
IA-5	Pollution Control
IA-6	Seeding and Mulching for Protective Cover
IA-21	Excavation
IA-32	Concrete for Minor Structures
IA-45	Plastic (PVC, PE) Pipe
IA-51	Corrugated Metal Pipe
IA-52	Steel Pipe Conduits

IA-61	Loose Rock Riprap
IA-92	Fences
IA-95	Geotextile

### **OPERATION AND MAINTENANCE**

An Operation and Maintenance plan will be prepared. The plan shall provide specific instructions for operating and maintaining the system to insure that it functions properly. . Specified actions shall include normal repetitive activities in the application and use of the practice (operation), and repair and upkeep of the practice (maintenance). It shall also provide for periodic inspections and prompt repair or replacement of damaged components.

### **REFERENCES**

- NRCS National Engineering Handbook (NEH)  
Part 650, Chapter 6, Structures.
- NRCS National Engineering Handbook (NEH)  
Part 650, Chapter 14, Water Management (Drainage).
- NRCS National Engineering Handbook (NEH)  
Part 650, Chapter 16, Streambank and Shoreline Protection.