

**NATURAL RESOURCES CONSERVATION SERVICE**  
**CONSERVATION PRACTICE STANDARD**  
**HIGH TUNNEL SYSTEM**  
(ft<sup>2</sup>)

**CODE 325**

**DEFINITION**

An enclosed polyethylene, polycarbonate, plastic, or fabric covered structure that is used to cover and protect crops from sun, wind, excessive rainfall, or cold, to extend the growing season in an environmentally safe manner.

**PURPOSES**

- Improve plant health and vigor

**CONDITIONS WHERE PRACTICE APPLIES**

This practice applies to cropland where extension of growing season is needed due to climate conditions and crops can be grown in the natural soil profile. Permanently raised beds may be installed to improve soil condition, fertility, and access, but does not apply to crops **not** grown in the natural soil profile (i.e. tables/benches, portable pots, hydroponically etc.).

The practice does not include greenhouses or low tunnel systems that may cover single crop rows. The practice cannot be used to provide shelter or housing for any livestock, or to store supplies or equipment.

**CRITERIA**

**General Criteria Applicable to All Purposes**

Plan supportive conservation practices to address all environmental concerns associated with the use of tunnel systems.

Locate structures to avoid buried utilities.

Locate the structure near a viable water source for irrigation.

Seasonal tunnel structures shall be selected and applied over the crop area.

The high tunnel structure must be planned, designed, and constructed from a manufactured kit in accordance with manufacturers' recommendations. The high tunnel frame must be constructed of metal, wood, or durable plastic; and be at least 6 feet in height at the peak of the structure. If required for enclosure, end wall covering may be greenhouse-grade plastic, polycarbonate, wood, or other. Use structures with the entry/exit point sized to facilitate movement of equipment and supplies needed for the production of planned crops.

Significant modifications to the high tunnel structure design must be verified and approved by the manufacturer prior to construction to ensure that any warranties remain in effect.

Select the high tunnel covering material of a significant thickness to withstand the temperature change for the period required and shall have a 4-year-minimum lifespan. For polyethylene covers, use a minimum 6-mil greenhouse grade, UV-resistant material.

For organic producers, it will be the responsibility of the producer to make sure that all permissible activities, design, material used, and material specifications are consistent with the USDA Agricultural Marketing Service National Organic Program, National Standards on Organic Agricultural Production and Handling.

The tunnel cover shall be removed or rolled up at the end of the growing season unless the structure is designed to withstand expected snow loads.

Select the tunnel cover and structure designed by the manufacturer to withstand expected wind loads or manage the tunnel system in a manner that limits wind damage.

Where the intensity or duration of sunlight can shorten the growing season, the appropriate thickness of shade cloth may be used in place of, or in addition to impervious plastic covers. When shade cloth is used alone, end walls are not required.

Runoff shall be directed away from the tunnel structure to avoid ponding. Runoff may be captured and used for irrigation purposes. The minimum design capacity for runoff structures shall be a 10-year storm frequency, 5-minute rainfall precipitation event. Runoff may empty into surface or underground outlets, or onto the ground surface when properly protected by an erosion resistant soil cover. Surface and underground outlets shall be sized to ensure adequate capacity. Provide for clean-out as appropriate. When runoff from tunnel covers empties onto the ground surface, a detention basin, storage reservoir, or stable outlet shall be provided.

Surface or ground outlets such as rock pads, rock-filled trenches with subsurface drains, concrete and other erosion-resistant pads, or preformed channels may be used.

Seeding and vegetation shall be established on all disturbed earth surfaces using Critical Area Planting (CPS 342).

## **CONSIDERATIONS**

Runoff may be captured and used for irrigation purposes, if allowed by State law, though runoff should not be relied on as the only source of irrigation water. Use the criteria for CPS Code 558, Roof Runoff Structure, to design any structure needed to meet the runoff criteria above. Runoff may empty into surface or underground outlets, or onto the ground surface when properly protected. Size surface and underground outlets according to the criteria for CPS Code 620, Underground Outlet, to ensure adequate capacity. Provide for cleanout as appropriate. Surface or ground outlets such as rock pads, rock-filled trenches with subsurface drains, concrete and other erosion-resistant pads, or preformed channels may be used.

Consider managing the high tunnel system to maintain or improve soil health by following a soil management system that creates a favorable habitat for soil microbes by:

- minimizing soil disturbance, physical, chemical and biological
- using plant diversity in the rotation to increase diversity below ground
- keeping a living root growing year round as much as possible
- keeping the soil covered with residue and growing plants year round

Locate the high tunnel conveniently for ingress/egress of plant materials, equipment, and other operation and maintenance activities.

**NRCS, Illinois**

**September 2016**

Remove or manipulate side covers to control internal temperatures and humidity. Installation of vents, fans, or heaters should be considered and should be included in the manufacturer's design and recommendations. If providing protection from the sun extends the growing season, consider a high tunnel structure that includes shade cloth.

If available, consider installing a supplemental manufacturer's kit to provide additional structural support.

Consider setting end posts in concrete, the use of heavier 12 to 14 gauge steel, and a double layer of plastic to increase integrity of the structure.

Consider a minimum clearance of 10 to 20 feet between adjacent tunnel installations for snow removal and cover installation.

Consider potential shading of high tunnel structures by other structures or trees and locate at a distance of two times the height of the tree or structure.

Control weeds with soil fabrics, covers, or mulches.

Consider additional conservation practices where appropriate to include:

- crop rotation
- irrigation water management
- salinity management
- nutrient management
- integrated pest management
- critical area planting
- mulching
- roof runoff structure
- diversion
- underground outlets
- heavy use protection
- cover crop

## **PLANS AND SPECIFICATIONS**

Prepare plans and specifications in accordance with the criteria of this standard.

As a minimum, the plans and specifications include the following:

- Identify purpose.
- Document the planned growing season.
- Layout and location of the high tunnel.
- Site preparations and the required supporting practices for erosion control, runoff, and vegetative cover according to the requirements of the corresponding conservation practice standard.
- The planned width and length of the seasonal high tunnel. A statement that the seasonal high tunnel will be built per the manufacturer's directions.
- Procedure and timing to remove or roll up the high tunnel cover prior to inclement weather conditions.
- Procedure and timing to add or replace shade cloth for protection from the sun for the high tunnel cover.

## **OPERATION AND MAINTENANCE**

Managing a tunnel requires intensive and vigilant attention by the producer.

Prepare an operation and maintenance (O&M) plan and review with the landowner and/or operator responsible for the practice. Provide specific instruction for proper operation and maintenance of each component of this practice and detail the level of repairs needed to maintain the effectiveness and useful life of the practice.

Periodically inspect the high tunnel and repair, reinstall, or replace, as needed to accomplish the intended purpose.

Manage the structure in a manner that limits wind and/or snow damage. Close sides and ends before storm events. In areas that receive snow and ice, the structure should be closed prior to winter weather.

Remove snow and ice from the structure cover and sides promptly to prevent structure failure.

When the structure is at serious risk of collapse due to weather conditions, consider slashing the plastic cover to relieve pressure and save the framework.

Perform soil tests regularly to monitor nutrients and to monitor salt build-up. The soils under the immobile high tunnels may require periodic “flushing” to remove salt build-up. This is accomplished by removing the cover for a season to allow natural precipitation to infiltrate, or by artificially flooding the ground under cover.

If needed, seed all disturbed earth surfaces outside of the high tunnel and maintain the vegetation throughout the structure’s life.

Removal of cover materials shall be consistent with the intended purpose and site conditions.

Plan for proper disposal of the cover at the end of its useful life.

Operation of equipment near and on the site shall not compromise the intended purpose of the high tunnel structure or its cover.

## **REFERENCES**

Community Garden Guide Season Extension - High Tunnel, NRCS. Rose Lake Plant Materials Center, East Lansing, Michigan.

“High Tunnel Production Manual”. Penn State University College of Agriculture, Department of Horticulture. White, L. and Orzolek, M. 2003.

"High Tunnels: Using Low-Cost Technology to Increase Yields, Improve Quality and Extend the Season". Ted Blomgren, Cornell Cooperative Extension, and Tracy Frisch, Regional Farm and Food Project. Published by the University of Vermont Center for Sustainable Agriculture. 2007.

“Minnesota high tunnel production manual for commercial growers”. Edited by: Terrance T. Nennich, Sr., University of Minnesota Extension and Suzanne Wold-Burkness, University of Minnesota. 2013.

“Growing Under Cover: A Guide to Polyunnel Options for Kansas Growers”; Kansas Rural Center; Kim Scherman, 2014.