

## NONTECHNICAL SOIL DESCRIPTIONS

These descriptions describe soil properties or management considerations specific to a soil map unit and components of map units. These reports are generated from the National Soil Information System soil database for distribution to land users.

---

**Aa--Alluvial Land**

Alluvial Land component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .37. This soil is moderately well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is frequently flooded and is not ponded. The top of the seasonal high water table is at 36 inches. There are no saline horizons. It is in nonirrigated land capability class 7s. This component is not a hydric soil.

**Ad--Alluvial Land, Wet**

Alluvial Land component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .37. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is frequently flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 7s. This component is a hydric soil.

**Be--Beaches**

Beaches component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .05. This soil is poorly drained. The slowest permeability within 60 inches is rapid. Available water capacity is moderate and shrink swell potential is low. This soil is frequently flooded and is not ponded. The top of the seasonal high water table is at 36 inches. The soil has a moderately saline horizon. It is in nonirrigated land capability class 8w. This component is a hydric soil.

**BlA--Beltsville Silt Loam, 0 To 2 Percent Slopes**

Beltsville component makes up 95 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

**BlB2--Beltsville Silt Loam, 2 To 5 Percent Slopes, Moderately Eroded**

Beltsville component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**BlB3--Beltsville Silt Loam, 2 To 5 Percent Slopes, Severely Eroded**

Beltsville component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**BlC2--Beltsville Silt Loam, 5 To 10 Percent Slopes Moderately Eroded**

Beltsville component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**BlC3--Beltsville Silt Loam, 5 To 10 Percent Slopes, Severely Eroded**

Beltsville component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

**Bm--Bibb Silt Loam**

Bibb component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is poorly drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is frequently flooded and is not ponded. The top of the seasonal high water table is at 12 inches. There are no saline horizons. It is in nonirrigated land capability class 5w. This component is a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

**BrB2--Bourne Fine Sandy Loam, 2 To 5 Percent Slopes, Moderately Eroded**

Bourne component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .28. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**BrC3--Bourne Fine Sandy Loam, 5 To 10 Percent Slopes, Severely Eroded**

Bourne component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 24 inches. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**CaB2--Caroline Silt Loam, 2 To 5 Percent Slopes, Moderately Eroded**

Caroline component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is very slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**CaC2--Caroline Silt Loam, 5 To 10 Percent Slopes Moderately Eroded**

Caroline component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is very slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**CaC3--Caroline Silt Loam, 5 To 10 Percent Slopes, Severely Eroded**

Caroline component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is very slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**CaD2--Caroline Silt Loam, 10 To 15 Percent Slopes, Moderately Eroded**

Caroline component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is very slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

**CaD3--Caroline Silt Loam, 10 To 15 Percent Slopes, Severely Eroded**

Caroline component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is very slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

**ChA--Chillum Loam, 0 To 2 Percent Slopes**

Chillum component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 1. This component is not a hydric soil.

**ChB2--Chillum Loam, 2 To 6 Percent Slopes Moderately Eroded**

Chillum component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**ChC2--Chillum Loam, 6 To 12 Percent Slopes, Moderately Eroded**

Chillum component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

**ChC3--Chillum Loam, 6 To 12 Percent Slopes, Severely Eroded**

Chillum component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

**CrB2--Croom Gravelly Sandy Loam, 2 To 5 Percent Slopes, Moderately Eroded**

Croom component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**CrC2--Croom Gravelly Sandy Loam, 5 To 10 Percent Slopes, Moderately Eroded**

Croom component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**CrD2--Croom Gravelly Sandy Loam, 10 To 15 Percent Slopes, Moderately Eroded**

Croom component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**CrD3--Croom Gravelly Sandy Loam, 10 To 15 Percent Slopes, Severely Eroded**

Croom component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

**Cu--Cut And Fill Land**

Cut And Fill Land component makes up 100 percent of the map unit. The assigned Kw erodibility factor is . Available water capacity is very low and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 8s. This component is not a hydric soil.

**Ek--Elkton Silt Loam**

Elkton component makes up 50 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is poorly drained. The slowest permeability within 60 inches is very slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

Elkton component makes up 50 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is poorly drained. The slowest permeability within 60 inches is very slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is a hydric soil.

**EvB--Evesboro Loamy Sand, 0 To 8 Percent Slopes**

Evesboro component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .17. This soil is excessively drained. The slowest permeability within 60 inches is rapid. Available water capacity is high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 7s. This component is not a hydric soil.

**EvC--Evesboro Loamy Sand, 8 To 15 Percent Slopes**

Evesboro component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .17. This soil is excessively drained. The slowest permeability within 60 inches is rapid. Available water capacity is high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 7s. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

**EwC2--Evesboro-Westphalia Complex, 6 To 12 Percent Slopes, Moderately Eroded**

Evesboro component makes up 60 percent of the map unit. The assigned Kw erodibility factor is .17. This soil is excessively drained. The slowest permeability within 60 inches is rapid. Available water capacity is high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 7s. This component is not a hydric soil.

Westphalia component makes up 40 percent of the map unit. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**EwD2--Evesboro-Westphalia Complex, 12 To 20 Percent Slopes, Moderately Eroded**

Evesboro component makes up 60 percent of the map unit. The assigned Kw erodibility factor is .17. This soil is excessively drained. The slowest permeability within 60 inches is rapid. Available water capacity is high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 7s. This component is not a hydric soil.

Westphalia component makes up 40 percent of the map unit. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

**EwE2--Evesboro-Westphalia Complex 20 To 45 Percent Slopes, Moderately Eroded**

Evesboro component makes up 60 percent of the map unit. The assigned Kw erodibility factor is .17. This soil is excessively drained. The slowest permeability within 60 inches is rapid. Available water capacity is high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 7s. This component is not a hydric soil.

Westphalia component makes up 40 percent of the map unit. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 7e. This component is not a hydric soil.

**FaB--Faceville Silt Loam, 0 To 5 Percent Slopes**

Faceville component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**Fs--Fallsington Sandy Loam**

Fallsington component makes up 50 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .24. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

Fallsington component makes up 50 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .24. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is a hydric soil.

**Gp--Gravel Pits**

Gravel Pits component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .02. The slowest permeability within 60 inches is rapid. Available water capacity is low and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 8s. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

- KeC2--Kempsville Fine Sandy Loam, 5 To 10 Percent Slopes, Moderately Eroded  
Kempsville component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.
- KeC3--Kempsville Fine Sandy Loam, 5 To 10 Percent Slopes, Severely Eroded  
Kempsville component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.
- KeD2--Kempsville Fine Sandy Loam, 10 To 15 Percent Slopes, Moderately Eroded  
Kempsville component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.
- KeD3--Kempsville Fine Sandy Loam, 10 To 15 Percent Slopes, Severely Eroded  
Kempsville component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.
- KpA--Keyport Fine Sandy Loam, 0 To 2 Percent Slopes  
Keyport component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .37. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.
- KpB2--Keyport Fine Sandy Loam, 2 To 5 Percent Slopes, Moderately Eroded  
Keyport component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .37. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.
- KrA--Keyport Silt Loam, 0 To 2 Percent Slopes  
Keyport component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.
- KrB2--Keyport Silt Loam, 2 To 5 Percent Slopes Moderately Eroded  
Keyport component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.
- KrC2--Keyport Silt Loam, 5 To 10 Percent Slopes, Moderately Eroded  
Keyport component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is moderate. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 33 inches. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

**Kz--Klej Loamy Sand, 0 To 5 Percent Slopes**

Klej component makes up 95 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .17. This soil is somewhat poorly drained. The slowest permeability within 60 inches is very slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 18 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is not a hydric soil.

**Le--Leonardtwn Silt Loam**

Leonardtwn component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is poorly drained. The slowest permeability within 60 inches is slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 4w. This component is a hydric soil.

**MaB2--Marr Fine Sandy Loam, 2 To 6 Percent Slopes, Moderately Eroded**

Marr component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .32. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**MaC2--Marr Fine Sandy Loam, 6 To 12 Percent Slopes, Moderately Eroded**

Marr component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .32. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**MaC3--Marr Fine Sandy Loam, 6 To 12 Percent Slopes, Severely Eroded**

Marr component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .32. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

**MmA--Matapeake Fine Sandy Loam, 0 To 2 Percent Slopes**

Matapeake component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .37. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 1. This component is not a hydric soil.

**MmB2--Matapeake Fine Sandy Loam, 2 To 5 Percent Slopes Moderately Eroded**

Matapeake component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .37. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**MnA--Matapeake Silt Loam, 0 To 2 Percent Slopes**

Matapeake component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 1. This component is not a hydric soil.

**MnB2--Matapeake Silt Loam, 2 To 5 Percent Slopes, Moderately Eroded**

Matapeake component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**MnC3--Matapeake Silt Loam, 5 To 10 Percent Slopes, Severely Eroded**

Matapeake component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

**MtA--Mattapex Fine Sandy Loam, 0 To 2 Percent Slopes**

Mattapex component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .37. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 27 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

**MtB2--Mattapex Fine Sandy Loam, 2 To 5 Percent Slopes, Moderately Eroded**

Mattapex component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .37. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 27 inches. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**MuA--Mattapex Silt Loam, 0 To 2 Percent Slopes**

Mattapex component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 27 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

**MuB2--Mattapex Silt Loam, 2 To 5 Percent Slopes, Moderately Eroded**

Mattapex component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 27 inches. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**MuC2--Mattapex Silt Loam, 5 To 10 Percent Slopes, Moderately Eroded**

Mattapex component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 27 inches. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**On--Othello Fine Sandy Loam**

Othello component makes up 100 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .37. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is a hydric soil.

**Ot--Othello Silt Loam**

Othello component makes up 100 percent of the map unit. Prime farmland if drained. The assigned Kw erodibility factor is .37. This soil is poorly drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 6 inches. There are no saline horizons. It is in nonirrigated land capability class 3w. This component is a hydric soil.

**RuB--Rumford Loamy Sand, 0 To 5 Percent Slopes**

Rumford component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .17. This soil is well drained. The slowest permeability within 60 inches is moderately rapid. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2s. This component is not a hydric soil.

**RuC2--Rumford Loamy Sand, 5 To 10 Percent Slopes, Moderately Eroded**

Rumford component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .17. This soil is well drained. The slowest permeability within 60 inches is moderately rapid. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

**SaA--Sassafras Sandy Loam, 0 To 2 Percent Slopes**

Sassafras component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 1. This component is not a hydric soil.

**SaB2--Sassafras Sandy Loam, 2 To 5 Percent Slopes, Moderately Eroded**

Sassafras component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**SaC2--Sassafras Sandy Loam, 5 To 10 Percent Slopes, Moderately Eroded**

Sassafras component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**SaC3--Sassafras Sandy Loam, 5 To 10 Percent Slopes, Severely Eroded**

Sassafras component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

**SaD2--Sassafras Sandy Loam, 10 To 15 Percent Slopes Moderately Eroded**

Sassafras component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

**SaD3--Sassafras Sandy Loam, 10 To 15 Percent Slopes, Severely Eroded**

Sassafras component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 6e. This component is not a hydric soil.

**SfA--Sassafras Loam, 0 To 2 Percent Slopes**

Sassafras component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 1. This component is not a hydric soil.

**SfB2--Sassafras Loam, 2 To 5 Percent Slopes, Moderately Eroded**

Sassafras component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .28. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**SmC2--Sassafras-Chillum Complex, 6 To 12 Percent Slopes, Moderately Eroded**

Sassafras component makes up 65 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .20. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

Chillum component makes up 35 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

## NONTECHNICAL SOIL DESCRIPTIONS--Continued

---

**SmC3--Sassafras-Chillum Complex, 6 To 12 Percent Slopes, Severely Eroded**

Sassafras component makes up 65 percent of the map unit. The assigned Kw erodibility factor is .20. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

Chillum component makes up 35 percent of the map unit. The assigned Kw erodibility factor is .43. This soil is well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**Tm--Tidal Marsh**

Tidal Marsh component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .37. This soil is very poorly drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is frequently flooded and is not ponded. The top of the seasonal high water table is at 0 inches. The soil has a slightly saline horizon. It is in nonirrigated land capability class 7w. This component is a hydric soil.

**WeB2--Westphalia Fine Sandy Loam, 2 To 6 Percent Slopes, Moderately Eroded**

Westphalia component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 2e. This component is not a hydric soil.

**WeC2--Westphalia Fine Sandy Loam, 6 To 12 Percent Slopes, Moderately Eroded**

Westphalia component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

**WeC3--Westphalia Fine Sandy Loam, 6 To 12 Percent Slopes, Severely Eroded**

Westphalia component makes up 100 percent of the map unit. The assigned Kw erodibility factor is .49. This soil is well drained. The slowest permeability within 60 inches is moderate. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The water table is deeper than 6 feet. There are no saline horizons. It is in nonirrigated land capability class 4e. This component is not a hydric soil.

**WsA--Woodstown Sandy Loam, 0 To 2 Percent Slopes**

Woodstown component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .24. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 30 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

**WsB--Woodstown Sandy Loam, 2 To 5 Percent Slopes**

Woodstown component makes up 100 percent of the map unit. All areas are prime farmland. The assigned Kw erodibility factor is .24. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 30 inches. There are no saline horizons. It is in nonirrigated land capability class 2w. This component is not a hydric soil.

**WsC2--Woodstown Sandy Loam, 5 To 10 Percent Slopes, Moderately Eroded**

Woodstown component makes up 100 percent of the map unit. Farmland of statewide importance. The assigned Kw erodibility factor is .24. This soil is moderately well drained. The slowest permeability within 60 inches is moderately slow. Available water capacity is very high and shrink swell potential is low. This soil is not flooded and is not ponded. The top of the seasonal high water table is at 30 inches. There are no saline horizons. It is in nonirrigated land capability class 3e. This component is not a hydric soil.

