

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD**

**RESIDUE AND TILLAGE MANAGEMENT
NO TILL/STRIP TILL/DIRECT SEED**

(Ac.)

CODE 329

DEFINITION

Managing the amount, orientation and distribution of crop and other plant residue on the soil surface year round while limiting soil-disturbing activities to only those necessary to place nutrients, condition residue and plant crops.

PURPOSE

- Reduce sheet and rill erosion.
- Reduce wind erosion.
- Improve soil organic matter content.
- Reduce CO₂ losses from the soil.
- Reduce soil particulate emissions
- Increase plant-available moisture
- Provide food and escape cover for wildlife

CONDITIONS WHERE PRACTICE APPLIES

This practice applies to all cropland and other land where crops are planted.

This practice includes planting methods commonly referred to as no-till, strip till, direct seed, zero till, slot till or zone till. Approved implements are: no-till and strip-till planters; certain drills and air seeders; strip-type fertilizer and manure injectors and applicators; in-row chisels; and similar implements that only disturb strips and slots. All other are considered

to be full-width or capable of full disturbance and therefore not compatible.

CRITERIA

General Criteria Applicable to All Purposes

Do not burn residue.

Distribute all residues uniformly over the entire field.

Do not perform full-width tillage, regardless of the depth of the tillage operation.

In determining the Soil Tillage Intensity Rating (STIR) value, include all field operations that are performed during the crop interval between harvest of the previous crop and harvest or termination of the current crop (includes fallow periods). The STIR value must not exceed 30.

Additional Criteria to Reduce Sheet and Rill Erosion

Using the current approved water erosion prediction technology, determine the amount of randomly disturbed surface residue needed, and the amount of surface soil disturbance allowed to reduce erosion to the planned soil loss objective. In the calculations, account for the effects

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resources Conservation Service. Contact Alice Begin at 207-990-568 or email alice.begin@me.usda.gov

**NRCS, ME
January 2007**

of other practices in the management system.

Additional Criteria to Reduce Wind Erosion

Using the current approved wind erosion prediction technology, determine the amount and orientation of standing and surface residue needed, and the amount of surface soil disturbance allowed to reduce erosion to the planned soil loss objective. In the calculations, account for the effects of other practices in the management system.

Additional Criteria to Improve Soil Condition

An evaluation of the cropping system using the current approved soil conditioning index procedure must result in a positive trend.

Additional Criteria to Reduce CO₂ Loss from the Soil

In determining the Soil Tillage Intensity Rating (STIR) value, include all field operations that are performed during the crop interval between harvest of the previous crop and harvest or termination of the current crop. The STIR value must not exceed 20.

An evaluation of the cropping system, using the current approved soil conditioning index procedure must result in a positive trend.

Additional Criteria to Reduce Soil Particulate Emissions

Determine the amount and orientation of residue needed and the amount of surface soil disturbance allowed to reduce wind erosion to the tolerable soil loss value (T) using the current approved wind erosion prediction technology. In the calculations,

account for the effects of other practices in the conservation management system.

Additional Criteria to Increase Plant – available Moisture

Reducing Evaporation from the Soil Surface. The annual Soil Tillage Intensity Rating (STIR) value for all soil-disturbing activities in the cropping system must be no more than 20.

Crop stubble height during the time evaporation losses can be expected to occur shall be:

- At least 10 inches for crops with a row spacing of less than 15 inches.
- At least 15 inches for crops with a row spacing of 15 inches or greater.

These stubble heights shall be present on at least 60% of the field.

Trapping Snow. Crop stubble height during the time significant snowfall is expected to occur shall be:

- At least 10 inches for crops with a row spacing of less than 15 inches.
- At least 15 inches for crops with a row spacing of 15 inches or greater.

These heights shall be present over at least 50% of the field.

Perform fall field operations that disturb residue as close to perpendicular as possible to the direction of prevailing winds during the time that significant snowfall is expected to occur.

Additional Criteria to Provide Food and Cover for Wildlife

Determine the time that residue is present, the amount and orientation of residue and the height of stubble needed to provide

adequate food and cover for the target species using an approved habitat evaluation procedure.

CONSIDERATIONS

General. Removing of crop residue, such as by bailing or grazing, can have a negative impact on resources. These activities should not be performed without full evaluation of impacts on soil, water, animal, plant and air resources.

Production of adequate amounts of crop residues necessary to achieve the purposes of this practice can be enhanced by selection of high residue producing crops and crop varieties in the rotation, use of cover crops, and adjustment of plant populations and row spacing.

Using no till/strip till/direct seed for all crops in the rotation or cropping system can enhance the positive effects of this practice by:

- Increasing the rate of soil organic matter accumulation
- Sequestering more carbon in the soil
- Further reducing the amount of particulate matter generated by field operations
- Forming root channels and other near-surface voids that increase infiltration

A field border planted to permanent vegetation can:

- Allow unobstructed turning for equipment
- Eliminate unproductive end rows
- Provide food and escape cover for wildlife
- Provide travel lanes for farming operations

Increasing Soil Organic Matter Level and Reducing CO₂ Loss – CO₂ loss is

directly related to the volume of soil disturbed, the intensity of the disturbance and the soil moisture content and soil temperature at the time the disturbance occurs. The following guidelines can make this practice more effective:

- Shallow soil disturbance (1-3 inches) releases less CO₂ than deeper operations.
- When deep soil disturbance is performed, such as by subsoiling or fertilizer injection, make sure the vertical slot created by these implements is closed at the surface.
- Planting with a single disk opener no-till drill will release less CO₂ than planting with a wide-point hoe/chisel opener air seeder drill.
- Soil disturbance that occurs when soil temperature are below 50 degree F will release less CO₂ than operations done when the soil is warmer.

Reducing Soil Particulate Emissions –

Slower operating speeds generally produce fewer particulate emissions.

Dry soils will produce more particulates than moist soils.

Reducing the wind erosion rate below the tolerable soil loss will help reduce particulate emissions. This can be done by:

- Increasing the level of crop residue cover
- Reducing the number of soil-disturbing operations
- Installing other practices to reduce wind erosion, such as Herbicides Wind Barriers (Code 603) or Cross Wind Trap Strips (Code 589C).

Managing Soil Moisture and Protecting Crops from Freeze Damage

– The type, timing and depth of soil-disturbing activities all influence moisture loss. Shall operations (1-2 inches) or operations that do not invert the soil will reduce moisture loss compared to deeper operations or those that invert and mix the soil.

Soil-disturbing operations performed when the soil surface is moist will result in greater moisture loss than operations done when the top two or three inches of soil have dried.

Leaving stubble taller than the minimum required will increase the relative humidity close to the soil surface, which reduces in rate of evaporative loss from the soil.

Leaving stubble taller than the 10-inch minimum will trap more snow and provide better protection to plants from freezing or desiccation.

Variable-height stubble patterns may be created to further increase snow storage.

Performing all field operations on the contour will slow overland flow and allow more opportunity for infiltration.

Wildlife Food and Cover – Leaving rows of unharvested crop standing at intervals across the field adjacent to permanent cover will enhance the value of residues for wildlife food and cover. Leaving unharvested crop rows for two growing seasons will further enhance the value of these areas for wildlife.

Leave crop residues undisturbed after harvest (do not shred or roll) to maximize their cover and food source benefits.

Avoid disturbing standing stubble or heavy residue during the nesting season for ground nesting species.

NRCS, ME

January 2007

PLANS AND SPECIFICATIONS

Prepare specifications for establishment and operation of this practice for each field or treatment until according to the Criteria and Considerations described in this standard. Specifications shall be recorded using approved specification sheets, job sheets, narrative statements in the conservation plan, or other acceptable documentation.

OPERATION AND MAINTENANCE

No operation and maintenance requirements, national in scope, have been identified for this practice.

REFERENCES

Bolton, Ryan, 2003. Impact of the surface residue layer on decomposition, soil water properties and nitrogen dynamics. M.S. thesis. Univ. of Saskatchewan, Saskatoon, Saskatchewan, CA.

Reicosky, D.C., M.J. Lindstrom, T.E. Schumacher, D.E. Lobb and D.D. Malo. 2005. Tillage –induced CO₂ loss across an eroded landscape. Soil Tillage Res. 81:183-194.

Reicosky, D.C. 2004. Tillage-included soil properties and chamber mixing effects on gas exchange. Proc. 16th Triennial Conf. Int. Soil Till. Org. (ISTRO)

Renard, K.G., G.R. Foster, G.A. Weesies, D.K. Mcool, and D.C. Yoder, coordinators. 1997. Predicting soil erosion by water. A guide to conservation planning with the Revised Universal Soil Loss Equation (RUSLE). U.S. Department of Agriculture, Agriculture Handbook No. 703.

Shaffer M.J. and W.E. Larson (ed). 1987. Tillage and surface-residue sensitive potential evaporation submodel. In NTRM, a soil-crop simulation model for

nitrogen, tillage and crop residue management. USDA Conserv. Res. Rep. 34-1. USDA-ARS.

Skidmore, E.L. and N.P. Woodruff, 1968. Wind erosion forces in the United States and their use in predicting soil loss. U.S. Department of Agriculture. Agriculture Handbook No. 346.

U.S.D.A. Natural Resources Conservation Service. 2002. National Agronomy Manual. 190-V. 3rd ed.