

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD**

**RESIDUE AND TILLAGE MANAGEMENT
RIDGE TILL**

(Ac.)

CODE 346

DEFINITION

Managing the amount, orientation, and distribution of crop and other plant residues on the soil surface year-round, while growing crops on pre-formed ridges alternated with furrows protected by crop residue.

Maintain ridge height throughout the harvest and winter seasons by controlling equipment or livestock traffic.

After planting, maintain residues in the furrows until the ridges are rebuilt by cultivation. Rebuild ridges to their original height and shape during the last row cultivation.

PURPOSE

- Reduce sheet and rill erosion
- Reduce wind erosion
- Maintain or improve soil condition
- Reduce soil particulate emissions
- Manage snow to increase plant-available moisture
- Modify cool wet site conditions
- Provide food and escape cover for wildlife

Stable Outlets. A stable outlet must exist where ridges direct runoff to areas of concentrated flow.

Maximum Row Grade. Row grades shall not exceed 9%.

If irrigation is used with this practice, row grades shall not exceed 7%. Where residue cover is less than 30%, row grade shall not exceed 7%.

CONDITIONS WHERE PRACTICE APPLIES

This practice applies to all cropland and other land where crops are planted.

This practice includes tillage and planting methods commonly referred to as ridge till or ridge planting. It does not include no-till planting on ridges, or bedding or listing operations that bury crop residues.

Additional Criteria to Reduce Sheet and Rill Erosion.

Move soil and residue removed from the top of the ridge into the furrow between the ridges.

After planting, maintain the top of the ridge at least 3 inches higher than the furrow between the ridges.

CRITERIA

General Criteria Applicable to All Purposes

Following crop harvest, leave residue on the surface until planting with no additional disturbance except for normal weathering.

Shape the ridge top to direct runoff to the protected furrow area.

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact the Natural Resources Conservation Service. Contact Alice Begin at 207-990-568 or email alice.begin@me.usda.gov

**NRCS, ME
January 2007**

Additional Criteria to Reduce Wind Erosion

Use wind erosion calculations to account for the effects of ridge height, spacing and orientation to the direction of erosive winds.

Additional Criteria to Maintain or Improve Soil Condition

An evaluation of the cropping system using the current approved soil conditioning index procedure must result in a positive trend.

Rebuild ridges using cultivation tools that maintain residues in the surface layer.

Additional Criteria to Reduce Soil Particulate Emissions

Use the current approved wind erosion prediction technology to determine the amount and orientation of residue needed and the amount of surface soil disturbance allowed to reduce wind erosion to the tolerable soil loss value (T). In the calculations, account for the effects of other practices in the conservation management system.

Additional Criteria to Manage Snow to Increase Plant-Available Moisture

During the time that significant snowfall is expected to occur, maintain minimum distance between the bottom of the furrow and the top of the stubble as follows:

- At least 10 inches for crops with a row spacing of less than 15 inches;
- At least 15 inches for crops with a row spacing of 15 inches or greater.

If this minimum distance cannot be achieved, orient ridges so as not to exceed 45 degrees from perpendicular to the prevailing wind direction during periods of expected snowfall.

Additional Criteria to Modify Cool Wet Site Conditions

Ridge height prior to planting shall be at least 6 inches.

Additional Criteria to Provide Food and Escape Cover for Wildlife

Determine the amount of residue and height of stubble needed to provide cover during winter months, using an approved wildlife management plan. Stubble shall remain standing over winter.

CONSIDERATIONS

General. Removal of residue, such as by baling or grazing, can have negative impacts on resources. These activities should not be performed without full evaluation of impacts on soil, water, animal, plants and air resources.

Ridge till may be practiced continuously throughout some crop sequences, or may be managed as part of a residue management system that includes other tillage and planting methods such as mulch till or no till. In mixed systems, ridges must be periodically re-established. Selection of acceptable tillage methods for specific site conditions may be aided by an approved Soil Tillage Suitability Rating.

Production of adequate amounts of crop residues necessary for the proper functioning of this practice can be enhanced by selection of high-residue producing crops and crop varieties in the rotation, use of cover crops, and adjustment of plant population and/or row spacing.

Since row cultivation is typically used for weed control and to reform ridges, this practice has the potential to reduce herbicide requirements.

A field border planted to permanent vegetation can assist in unobstructed turning, elimination of end rows and providing travel lanes for farming operations.

Leaving unharvested crop rows at intervals across the field can enhance the value of residue cover and food for wildlife.

Maintaining or Improving Soil Condition and Reducing CO₂ Loss from the Soil - - Continuous ridge planting will allow organic material to accumulate in the surface horizon.

Reconstruction of ridges in the same row area year after year will maximize organic matter buildup and biological activity in the row.

CO₂ loss is directly related to the volume of soil disturbed, the intensity of the disturbance and the soil moisture content and soil temperature at the time the disturbance occurs.

- Shallow soil disturbance (1-3 inches) releases less CO₂ than deeper operations.
- When deep soil disturbance is performed, such as by subsoiling or fertilizer injection, make sure the vertical tillage slot created by these implements is closed at the surface.
- Planting with a single disk opener no-till drill will release less CO₂ than planting with a wide-point hoe/chisel opener air seeder drill.
- Soil disturbance that occurs when soil temperatures are below 50 degrees F will release less CO₂ than operations done when the soil is warmer.

Soil compaction may be reduced by controlled traffic, in which wheel traffic from all operations is limited to the area between designated rows or traffic areas.

Providing Food and Escape Cover for Wildlife – Avoid disturbing standing stubble or heavy residue during the nesting season for ground-nesting species.

Foregoing fall shredding or tillage operations will maximize the amount of wildlife food and cover during critical winter months.

Leaving rows of unharvested crop standing at intervals across the field or adjacent to permanent cover will enhance the value of residues for wildlife food and cover. Leaving unharvested crop rows for two growing seasons will further enhance the value of these areas for wildlife.

PLANS AND SPECIFICATIONS

Prepare specifications for establishment and operation of this practice for each field or

treatment unit according to the Criteria and Considerations described in this standard. Record specifications using approved specification sheets, job sheets, narrative statements in the conservation plan or other acceptable documentation.

OPERATION AND MAINTENANCE

No operation and maintenance requirements, national in scope, have been identified for this practice.

REFERENCES

Bolton, Ryan, 2003. Impact of the surface residue layer on decomposition, soil water properties and nitrogen dynamics. M.S. thesis. Univ. of Saskatchewan, Saskatoon, Saskatchewan, CA.

Renard, K.G., G.R. Foster, G.A. Weesies, D.K. McCool, and D.C. Yoder, coordinators. 1997. Predicting soil erosion by water. A guide to conservation planning with the Revised Universal Soil Loss Equation (RUSLE). U.S. Department of Agriculture, Agriculture Handbook No. 703.

Shaffer, M.J. and W.E. Larson (ed.) 1987. Tillage and surface-residue sensitive potential evaporation submodel. In NTRM, a soil-crop simulation model for nitrogen, tillage and crop residue management. USDA Conserv. Res. Rep. 34-1. USDA-ARS.

Skidmore, E.L. and N.P. Woodruff. 1968. Wind erosion forces in the United States and their use in predicting soil loss. U.S. Department of Agriculture. Agriculture Handbook No. 346.

U.S.D.A. Natural Resources Conservation Service. 2002. National Agronomy Manual. 190-V. 3rd ed.