

Scenario Worksheet

Practice and Scenario Description:

Information Type	Data
Region	Appalachian
State	North Carolina
Discipline Group	Environmental Engineering
Practice Code/Name	317 - Composting Facility
Scenario ID	1
Scenario Name	Composter, with concrete floor and wood walls
Scenario Description	The composting facility, with concrete under bins only, is installed to address water quality concerns and disease vectors resulting from improper waste disposal by providing a dedicated facility for storage and treatment, and by creating a compost product that can be used in multiple ways including land application for enrichment of crop ground. All animal mortality composting shall be done using Practice Standard 316 - Animal Mortality Facility. Potential Associated Practices: Pond Sealing or Lining, Bentonite Sealant (521C), Pond Sealing or Lining, Compacted Clay Treatment (521D), Pond Sealing or Lining, Flexible Membrane (521A), Pond Sealing or Lining, Soil Dispersant (521B), Fence (382), Critical Area Planting (342), Nutrient Management (590), Access Road (560), Structure for water control (587), Diversion (362), Pipeline (516), Subsurface Drain (606), Heavy Use Area Protection (561), Roofs and Covers (367), Roof Runoff
Before Practice Situation	Manure and other agricultural by-products are not being utilized or controlled in an environmentally safe manner. The wastes are either accumulating at the source, or other location, or are being transported but not properly utilized or disposed of. This situation poses an environmental threat of excessive nutrients, organics, and pathogens being transported into surface and groundwaters, in addition to the use of excessive amounts of fertilizers.
After Practice Situation	Manure, litter and other agricultural by-products are being controlled, by the collection at the source, and stored properly, at an environmentally suitable location, until such time that they are disposed of or utilized in a proper manner, typically in accordance with a nutrient management plan. The typical composter is designed to handle organic material from a 4 house poultry operation containing 20,000 4 lbs birds in each house. The typical composter is 40' x 56' with 5' high bins, 4-primary bins and 1 secondary bin with Storage Area. Strip top 1' of soil and roll compact same back into sub-floor. The bins are constructed on a 5" concrete slab used to store and stabilize manure, litter and other agricultural by-products from a four house complex on any farm.
Scenario Feature Measure	Square Foot Floor Area
Scenario Unit	Square Foot
Scenario Typical Size	2240

Cost Summary:

Cost Category	Scenario Cost	Scenario Cost/Unit
Materials	\$4,879.88	\$2.18
Equipment/Installation	\$7,705.75	\$3.44
Labor	\$1,680.30	\$0.75
Mobilization	\$92.60	\$0.04
Acquisition of Technical Knowledge	\$0.00	\$0.00
Foregone Income	\$0.00	\$0.00
Total	\$14,358.53	\$6.41

Cost Details:

Cost Category	Component ID	Component Name	Component Description	Unit	Price (\$/unit)	Quantity	Cost
Materials	1609	Lumber, planks, posts and timbers, treated	Treated dimension lumber with nominal thickness greater than 2". Includes lumber and fasteners. Does not include labor.	Board Foot	\$1.17	1800	\$2,106.00
Materials	1044	Dimension Lumber, Treated	Treated dimension lumber with nominal thickness equal or less than 2". Includes lumber and fasteners	Board Foot	\$0.71	2960	\$2,101.60
Materials	46	Aggregate, Gravel, Graded	Gravel, includes materials, equipment and labor to transport and place. Includes washed and unwashed gravel.	Cubic yard	\$24.01	28	\$672.28
Equipment/Installation	1220	Excavation, common earth, small equipment, 50 ft	Bulk excavation of common earth with dozer <100 HP with average push distance of 50 feet. Includes equipment and labor.	Cubic Yard	\$2.28	83	\$189.24
Equipment/Installation	37	Concrete, CIP, slab on grade, reinforced	Steel reinforced concrete formed and cast-in-place as a slab on grade by chute placement. Typical strength is 3000 to 4000 psi. Includes materials, labor and equipment to transport, place and finish.	Cubic yard	\$207.24	35	\$7,253.40
Equipment/Installation	49	Earthfill, Roller Compacted	Earthfill, roller or machine compacted, includes equipment and labor	Cubic yard	\$3.17	83	\$263.11
Labor	231	General Labor	Labor performed using basic tools such as power tool, shovels, and other tools that do not require extensive training. Ex. pipe layer, herder, concrete placement, materials spreader, flagger, etc.	Hour	\$18.67	90	\$1,680.30
Mobilization	1139	Mobilization, medium equipment	Equipment with 70-150 HP or typical weights between 14,000 and 30,000 pounds.	Each	\$92.60	1	\$92.60

Scenario Worksheet

Practice and Scenario Description:

Information Type	Data
Region	Appalachian
State	North Carolina
Discipline Group	Environmental Engineering
Practice Code/Name	317 - Composting Facility
Scenario ID	2
Scenario Name	Composter, with concrete floor and concrete walls
Scenario Description	<p>The composting facility, with concrete under bins only, is installed to address water quality concerns and disease vectors resulting from improper waste disposal by providing a dedicated facility for storage and treatment, and by creating a compost product that can be used in multiple ways including land application for enrichment of crop ground. All animal mortality composting shall be done using Practice Standard 316 - Animal Mortality Facility.</p> <p>Potential Associated Practices: Pond Sealing or Lining, Bentonite Sealant (521C), Pond Sealing or Lining, Compacted Clay Treatment (521D), Pond Sealing or Lining, Flexible Membrane (521A), Pond Sealing or Lining, Soil Dispersant (521B), Fence (382), Critical Area Planting (342), Nutrient Management (590), Access Road (560), Structure for water control (587), Diversion (362), Pipeline (516), Subsurface Drain (606), Heavy Use Area Protection (561), Roofs and Covers (367), Roof Runoff</p>
Before Practice Situation	Manure and other agricultural by-products are not being utilized or controlled in an environmentally safe manner. The wastes are either accumulating at the source, or other location, or are being transported but not properly utilized or disposed of. This situation poses an environmental threat of excessive nutrients, organics, and pathogens being transported into surface and groundwaters, in addition to the use of excessive amounts of fertilizers.
After Practice Situation	Manure, litter and other agricultural by-products are being controlled, by the collection at the source, and stored properly, at an environmentally suitable location, until such time that they are disposed of or utilized in a proper manner, typically in accordance with a nutrient management plan. The typical composter is designed to handle organic material from a 4 house poultry operation containing 20,000 4 lbs birds in each house. The typical composter is 40' x 56' with 5' high bins, 4-primary bins and 1 secondary bin with Storage Area. Strip top 1' of soil and roll compact same back into sub-floor. The bins are constructed on a 5" concrete-slab used to store and stabilize manure, litter and other agricultural by-products from a four house complex on any farm.
Scenario Feature Measure	Square Foot Floor Area
Scenario Unit	Square Foot
Scenario Typical Size	2240

Cost Summary:

Cost Category	Scenario Cost	Scenario Cost/Unit
Materials	\$672.28	\$0.30
Equipment/Installation	\$25,806.25	\$11.52
Labor	\$0.00	\$0.00
Mobilization	\$92.60	\$0.04
Acquisition of Technical Knowledge	\$0.00	\$0.00
Foregone Income	\$0.00	\$0.00
Total	\$26,571.13	\$11.86

Cost Details:

Cost Category	Component ID	Component Name	Component Description	Unit	Price (\$/unit)	Quantity	Cost
Materials	46	Aggregate, Gravel, Graded	Gravel, includes materials, equipment and labor to transport and place. Includes washed and unwashed gravel.	Cubic yard	\$24.01	28	\$672.28
Equipment/Installation	1220	Excavation, common earth, small equipment, 50 ft	Bulk excavation of common earth with dozer <100 HP with average push distance of 50 feet. Includes equipment and labor.	Cubic Yard	\$2.28	83	\$189.24
Equipment/Installation	38	Concrete, CIP, formed reinforced	Steel reinforced concrete formed and cast-in-placed in formed structures such as walls or suspended slabs by chute placement. Typical strength is 3000 to 4000 psi. Includes materials, labor and equipment to transport, place and finish.	Cubic yard	\$329.10	55	\$18,100.50
Equipment/Installation	37	Concrete, CIP, slab on grade, reinforced	Steel reinforced concrete formed and cast-in-placed as a slab on grade by chute placement. Typical strength is 3000 to 4000 psi. Includes materials, labor and equipment to transport, place and finish.	Cubic yard	\$207.24	35	\$7,253.40
Equipment/Installation	49	Earthfill, Roller Compacted	Earthfill, roller or machine compacted, includes equipment and labor	Cubic yard	\$3.17	83	\$263.11
Labor	231	General Labor	Labor performed using basic tools such as power tool, shovels, and other tools that do not require extensive training. Ex. pipe layer, herder, concrete placement, materials spreader, flagger, etc.	Hour	\$18.67	0	\$0.00
Mobilization	1139	Mobilization, medium equipment	Equipment with 70-150 HP or typical weights between 14,000 and 30,000 pounds.	Each	\$92.60	1	\$92.60

Scenario Worksheet

Practice and Scenario Description:

Information Type	Data
Region	Appalachian
State	North Carolina
Discipline Group	Environmental Engineering
Practice Code/Name	317 - Composting Facility
Scenario ID	3
Scenario Name	Composter, windrow, all weather surface
Scenario Description	The composting facility is installed to address water quality concerns and disease vectors resulting from improper waste disposal by providing a dedicated facility for storage and treatment, and by creating a compost product that can be used in multiple ways including land application for enrichment of crop ground. This scenario is applicable when geological, soil, climate conditions or state and local regulations prohibit the use of an earthen surface. All animal mortality composting shall be done using Practice Standard 316 - Animal Mortality Facility. Potential Associated Practices: Pond Sealing or Lining, Bentonite Sealant (521C), Pond Sealing or Lining, Compacted Clay Treatment (521D), Pond Sealing or Lining.
Before Practice Situation	Manure and other agricultural by-products are not being utilized or controlled in an environmentally safe manner. The wastes are either accumulating at the source, or other location, or are being transported but not properly utilized or disposed of. This situation poses an environmental threat of excessive nutrients, organics, and pathogens being transported into surface and groundwaters, in addition to the use of excessive amounts of fertilizers.
After Practice Situation	Manure and other agricultural by-products are being controlled, by the collection at the source, and stored properly, at an environmentally suitable location, until such time that they are disposed of or utilized in a proper manner, typically in accordance with a nutrient management plan. This is incorporated as part of the overall waste management system meeting the National Engineering Handbook (NEH), Part 651, Agricultural Waste Management Field Handbook (AWMFH) that has been developed to also account for end use of the product from the composting facility. This scenario consists of installing a gravel pad over impervious soil to act as a working area to compost organic material in a static pile, windrow, that has sufficient carbon based bulking material to allow natural aeration. Piles typically turned at least once to go into another heat cycle prior to final disposal, typically land application. Typical pad 90' x 363' (3/4 acre) on an improved gravel surface. Sub base material sufficiently compacted or improved. Include sufficient area for processing equipment access. Single piles or windrows to minimize runoff. Site to be located out of drainage areas, off-site water diverted and any runoff to spread
Scenario Feature Measure	Square Foot Floor Area
Scenario Unit	Square Foot
Scenario Typical Size	32670

Cost Summary:

Cost Category	Scenario Cost	Scenario Cost/Unit
Materials	\$14,526.05	\$0.44
Equipment/Installation	\$15,560.60	\$0.48
Labor	\$0.00	\$0.00
Mobilization	\$173.20	\$0.01
Acquisition of Technical Knowledge	\$0.00	\$0.00
Foregone Income	\$0.00	\$0.00
Total	\$30,259.85	\$0.93

Cost Details:

Cost Category	Component ID	Component Name	Component Description	Unit	Price (\$/unit)	Quantity	Cost
Materials	46	Aggregate, Gravel, Graded	Gravel, includes materials, equipment and labor to transport and place. Includes washed and unwashed gravel.	Cubic yard	\$24.01	605	\$14,526.05
Equipment/Installation	1223	Excavation, common earth, large equipment, 150 ft	Bulk excavation of common earth including sand and gravel with dozer >100 HP with average push distance of 150 feet. Includes equipment and labor.	Cubic Yard	\$3.36	1210	\$4,065.60
Equipment/Installation	42	Geotextile, woven	Woven Geotextile Fabric. Includes materials, equipment and labor	Square Yard	\$2.11	3630	\$7,659.30
Equipment/Installation	49	Earthfill, Roller Compacted	Earthfill, roller or machine compacted, includes equipment and labor	Cubic yard	\$3.17	1210	\$3,835.70
Mobilization	1140	Mobilization, large equipment	Equipment >150HP or typical weights greater than 30,000 pounds or loads requiring over width or over length permits.	Each	\$173.20	1	\$173.20

Scenario Worksheet

Practice and Scenario Description:

Information Type	Data
Region	Appalachian
State	North Carolina
Discipline Group	Environmental Engineering
Practice Code/Name	317 - Composting Facility
Scenario ID	4
Scenario Name	Composter, with compacted earth floor, windrow
Scenario Description	The composting facility is installed to address water quality concerns and disease vectors resulting from improper waste disposal by providing a dedicated facility for storage and treatment, and by creating a compost product that can be used in multiple ways including land application for enrichment of crop ground. This scenario is applicable when geological, soil, and climate conditions are appropriate for earth floors and are allowed by state and local regulations. All animal mortality composting shall be done using Practice Standard 316 - Animal Mortality Facility. Potential Associated Practices: Pond Sealing or Lining, Bentonite Sealant (521C), Pond Sealing or Lining, Compacted Clay Treatment (521D), Pond Sealing or Lining.
Before Practice Situation	Manure and other agricultural by-products are not being utilized or controlled in an environmentally safe manner. The wastes are either accumulating at the source, or other location, or are being transported but not properly utilized or disposed of. This situation poses an environmental threat of excessive nutrients, organics, and pathogens being transported into surface and groundwaters, in addition to the use of excessive amounts of fertilizers.
After Practice Situation	Manure and other agricultural by-products are being controlled, by the collection at the source, and stored temporarily, at an environmentally suitable location, until such time that they are disposed of or utilized in a proper manner, typically in accordance with a nutrient management plan. This scenario consists of removing and compacting back into place the top 1' of soil to create a compacted, impervious earthen floor to act as a working area to compost organic material in a static pile, windrow, that has sufficient carbon based bulking material to allow natural aeration. Piles typically turned at least once to go into another heat cycle prior to final deposal, typically land application. Typical pad 90' x 363' (3/4 acre) on an improved compacted earthen surface. Include sufficient area for processing equipment access. Single piles or windrows to minimize runoff. Site to be located out of drainage areas, off-site water diverted and any runoff to spread out into a grassed area or vegetated treatment area as per regulations. Site preparation includes topsoil removal, compaction of subsoil, and reinstalling topsoil, compacted.
Scenario Feature Measure	Square Foot Floor Area
Scenario Unit	Square Foot
Scenario Typical Size	32670

Cost Summary:

Cost Category	Scenario Cost	Scenario Cost/Unit
Materials	\$0.00	\$0.00
Equipment/Installation	\$7,901.30	\$0.24
Labor	\$0.00	\$0.00
Mobilization	\$173.20	\$0.01
Acquisition of Technical Knowledge	\$0.00	\$0.00
Foregone Income	\$0.00	\$0.00
Total	\$8,074.50	\$0.25

Cost Details:

Cost Category	Component ID	Component Name	Component Description	Unit	Price (\$/unit)	Quantity	Cost
Equipment/Installation	1223	Excavation, common earth, large equipment, 150 ft	Bulk excavation of common earth including sand and gravel with dozer >100 HP with average push distance of 150 feet. Includes equipment and labor.	Cubic Yard	\$3.36	1210	\$4,065.60
Equipment/Installation	49	Earthfill, Roller Compacted	Earthfill, roller or machine compacted, includes equipment and labor	Cubic yard	\$3.17	1210	\$3,835.70
Mobilization	1140	Mobilization, large equipment	Equipment >150HP or typical weights greater than 30,000 pounds or loads requiring over width or over length permits.	Each	\$173.20	1	\$173.20