

Practice: 367 - Roofs and Covers

Scenario: #1 - Post Frame Roof, less than 30ft wide

Scenario Description: A timber framed building with a timber or steel "sheet" roof and supporting foundation. Manure is stored as a liquid in basins, tanks, and as a solid on concrete and earthen surfaces. Excess precipitation can cause premature filling of storages or cause nutrients to leach from solid manure piles leading to uncontrolled runoff as well as odor issues. Associated practices include Waste Storage Facility (313), Animal Mortality Facility (316), Composting Facility (317), Agrichemical Handling Facility (309), Roof Runoff Structure (558), and Waste Treatment (629).

Before Situation: Applicable where the exclusion of precipitation from an animal waste storage and/or treatment facility will improve of an existing or planned system. Manure is stored as a liquid in basins, tanks, and as a solid on concrete and earthen surfaces. Excess precipitation can cause premature filling of storages or cause nutrients to leach from solid manure piles leading to uncontrolled runoff as well as odor issues.

After Situation: A timber framed building with a timber or steel "sheet" roof and supporting foundation. Engineered and installed in accordance with appropriate building codes and permits. Typical size is 1,000 square feet and is over an approved animal waste management facility as a component of a CNMP. It is designed to prevent precipitation to allow proper management of animal waste streams (manure or compost streams), thus mitigating the negative factors from the "before practice implementation".

Scenario Feature Measure: Footprint of building

Scenario Unit: Square Foot

Scenario Typical Size: 1000

Total Scenario Cost: \$9,261.59

Scenario Cost/Unit: \$9.26

Cost Details

| Component Name | Id | Description | Unit | Cost | Qty | Total |
|----------------|----|-------------|------|------|-----|-------|
|----------------|----|-------------|------|------|-----|-------|

Mobilization

| | | | | | | |
|------------------------------------|------|--|------|----------|---|----------|
| Mobilization, medium equipment | 1139 | Equipment with 70-150 HP or typical weights between 14,000 and 30,000 pounds. | Each | \$253.88 | 1 | \$253.88 |
| Mobilization, very small equipment | 1137 | Equipment that is small enough to be transported by a pick-up truck with typical weights less than 3,500 pounds. Can be multiple pieces of equipment if all hauled simultaneously. | Each | \$70.11 | 2 | \$140.21 |

Materials

| | | | | | | |
|--|------|---|-------------|--------|------|------------|
| Roof, Post Frame Building , less than 30' wide | 1672 | Post Frame Building, no sides, - less than 30' width. Building sites with expected snow loads up to 30 lbs per square foot and wind exposure in semi protected areas (wooded or terrain with numerous closely spaced obstructions). Includes materials, shipping, equipment, and installation. Does not include foundation preparation. | Square Foot | \$8.87 | 1000 | \$8,867.50 |
|--|------|---|-------------|--------|------|------------|

Practice: 367 - Roofs and Covers

Scenario: #2 - Post Frame Roof, 30-60ft wide

Scenario Description: A timber framed building with a timber or steel "sheet" roof and supporting foundation. Manure is stored as a liquid in basins, tanks, and as a solid on concrete and earthen surfaces. Excess precipitation can cause premature filling of storages or cause nutrients to leach from solid manure piles leading to uncontrolled runoff as well as odor issues. Associated practices include Waste Storage Facility (313), Animal Mortality Facility (316), Composting Facility (317), Agrichemical Handling Facility (309), Roof Runoff Structure (558), and Waste Treatment (629).

Before Situation: Applicable where the exclusion of precipitation from an animal waste storage and/or treatment facility will improve of an existing or planned system. Manure is stored as a liquid in basins, tanks, and as a solid on concrete and earthen surfaces. Excess precipitation can cause premature filling of storages or cause nutrients to leach from solid manure piles leading to uncontrolled runoff as well as odor issues.

After Situation: A timber framed building with a timber or steel "sheet" roof and supporting foundation. Engineered and installed in accordance with appropriate building codes and permits. Typical size is 4,000 square feet and is over an approved animal waste management facility as a component of a CNMP. It is designed to prevent precipitation to allow proper management of animal waste streams (manure or compost streams), thus mitigating the negative factors from the "before practice implementation".

Scenario Feature Measure: Footprint of building

Scenario Unit: Square Foot

Scenario Typical Size: 4000

Total Scenario Cost: \$34,234.09

Scenario Cost/Unit: \$8.56

Cost Details

| Component Name | Id | Description | Unit | Cost | Qty | Total |
|----------------|----|-------------|------|------|-----|-------|
|----------------|----|-------------|------|------|-----|-------|

Mobilization

| | | | | | | |
|------------------------------------|------|--|------|----------|---|----------|
| Mobilization, medium equipment | 1139 | Equipment with 70-150 HP or typical weights between 14,000 and 30,000 pounds. | Each | \$253.88 | 1 | \$253.88 |
| Mobilization, very small equipment | 1137 | Equipment that is small enough to be transported by a pick-up truck with typical weights less than 3,500 pounds. Can be multiple pieces of equipment if all hauled simultaneously. | Each | \$70.11 | 2 | \$140.21 |

Materials

| | | | | | | |
|--|------|--|-------------|--------|------|-------------|
| Roof, Post Frame Building, 30' to 60' wide | 1676 | Post Frame Building, no sides, - 30' to 60' width. Building sites with expected snow loads up to 30 lbs per square foot and wind exposure in semi protected areas (wooded or terrain with numerous closely spaced obstructions). Includes materials, shipping, equipment, and installation. Does not include foundation preparation. | Square Foot | \$8.46 | 4000 | \$33,840.00 |
|--|------|--|-------------|--------|------|-------------|

Practice: 367 - Roofs and Covers

Scenario: #5 - Steel Frame and Roof

Scenario Description: A steel framed building with steel "sheet" roof and supporting foundation. Manure is stored as a liquid in basins, tanks, and as a solid on concrete and earthen surfaces. Excess precipitation can cause premature filling of storages or cause nutrients to leach from solid manure piles leading to uncontrolled runoff as well as odor issues. Associated practices includes Waste Storage Facility (313), Animal Mortality Facility (316), Composting Facility (317), Roof Runoff Structure (558), and Waste Treatment (629).

Before Situation: Applicable where the exclusion of precipitation from an animal waste storage and/or treatment facility will improve of an existing or planned system. Manure is stored as a liquid in basins, tanks, and as a solid on concrete and earthen surfaces. Excess precipitation can cause premature filling of storages or cause nutrients to leach from solid manure piles leading to uncontrolled runoff as well as odor issues.

After Situation: A steel framed building with steel "sheet" roof and supporting foundation. Engineered and installed in accordance with appropriate building codes and permits. Typical size is 10,000 square feet and is over an approved animal waste management facility as a component of a CNMP. It is designed to prevent precipitation to allow proper management of animal waste streams (manure or compost streams), thus mitigating the negative factors from the "before practice implementation".

Scenario Feature Measure: Footprint of building

Scenario Unit: Square Foot

Scenario Typical Size: 10000

Total Scenario Cost: \$65,617.42

Scenario Cost/Unit: \$6.56

Cost Details

| Component Name | Id | Description | Unit | Cost | Qty | Total |
|----------------|----|-------------|------|------|-----|-------|
|----------------|----|-------------|------|------|-----|-------|

Mobilization

| | | | | | | |
|------------------------------------|------|--|------|----------|---|----------|
| Mobilization, medium equipment | 1139 | Equipment with 70-150 HP or typical weights between 14,000 and 30,000 pounds. | Each | \$253.88 | 2 | \$507.76 |
| Mobilization, very small equipment | 1137 | Equipment that is small enough to be transported by a pick-up truck with typical weights less than 3,500 pounds. Can be multiple pieces of equipment if all hauled simultaneously. | Each | \$70.11 | 2 | \$140.21 |

Materials

| | | | | | | |
|---|------|---|-------------|--------|-------|-------------|
| Roof, Steel Frame Monoslope Building, greater than 60' wide | 1677 | Steel Frame Monoslope Building, greater than 60' width, includes materials, equipment, and installation. Does not include foundation preparation. | Square Foot | \$6.50 | 10000 | \$64,969.45 |
|---|------|---|-------------|--------|-------|-------------|