



Animal Enhancement Activity – ANM18 – Retrofit Watering Facility for Wildlife Escape

State Criteria

One structure (ramp) is required for every 30 linear feet of tank/trough edge. A tank with 59.9 feet or less of tank perimeter requires one ramp. Tanks with 60 feet of perimeter up to 89.9 feet require two ramps, and so forth. For square or rectangle tanks, simply add the outside dimensions. For round tanks, X feet of diameter multiplied by 3.14 provides the circumference. (Example: a 10 foot diameter tank has a circumference of 31.4 feet.)

Ramps must extend to the bottom of the watering facility. A ramp is not required on the outside of the tank to meet the requirements of this enhancement.

DOCUMENTATION REQUIREMENTS:

Complete the Table below:

1 Tract	2 Field(s)	3 Planned Number of watering facility retrofits	4 Applied Number of watering facility retrofits
<i>Ex. 100</i>	<i>R1</i>	<i>1</i>	<i>1</i>

EX= EXAMPLE, COLUMNS 1-3 NRCS COMPLETES, COLUMN 4 PRODUCER COMPLETES

I certify that the retrofitted watering facility information meets these specifications including the following documentation as applicable:

1. Indicate number of watering facilities retrofitted according to the criteria (complete table above).
2. Map showing the location of the retrofitted watering facilities.
3. Attach a photograph for each modified watering facility.

Certified by: _____ **Date:** _____