

**NATURAL RESOURCES CONSERVATION SERVICE
 CONSERVATION PRACTICE STANDARD
 POND SEALING OR LINING**

Flexible Membrane

(No.)

CODE 521A

DEFINITION

A manufactured hydraulic barrier consisting of a functionally continuous layer of synthetic or partially synthetic, flexible material.

PURPOSE

To restrict, impede, and control seepage of contaminants from water and waste impoundment structures for water conservation and environmental protection.

CONDITION WHERE PRACTICE APPLIES

On ponds and water storage structures that require treatment to control seepage rates within acceptable limits.

On earthen waste storage lagoons and other waste impoundment structures that require treatment to control seepage of contaminants from the storage structure.

CRITERIA

Design. Structures to be lined shall have been constructed to meet all applicable NRCS standards. All inlets, outlets, ramps, and other appurtenances may be installed before, during, or after the liner placement, but shall be done in a manner that does not damage or impair the proper operation of the liner.

Design and installation of the flexible membrane shall be in accordance with manufacturer recommendations. All flexible membrane installations shall be certified by the installer as meeting the material and installation requirements of the plans and specifications.

Manufacturer recommendations shall be followed with regard to protection from weather and exposure.

Minimum Criteria for Membranes

Type	Limiting Parameter	
	Wastewater	Clear Water
HDPE	40 mil	30 mil
LLDPE	40 mil	20 mil
PVC	30 mil	20 mil
GCL	0.75 lb./sq ft (bentonite)	
EPDM	45 mil	
PP (Reinforced)	36 mil	24 mil
(Un-reinforced)	40 mil	20 mil
RPE	NR	24 mil

1 mil = 1/1000 of an inch

- HDPE – High Density Polyethylene Geomembrane
- LLDPE – Linear Low Density Polyethylene Geomembrane
- PVC – Polyvinyl Chloride Geomembrane
- GCL – Geosynthetic Clay Liner
- EPDM – Synthetic Rubber Geomembrane
- PP – Polypropylene Geomembrane
- RPE – Reinforced Polyethylene Geomembrane
- NR – Not Recommended

Cover Soil. PVC and GCL liners shall be covered with a minimum of 12 inches of soil. Cover soil may be used on other liners but is not required.

Cover soil shall be used as cover for liners when required for the proper performance, protection, and durability of the installation. Cover soils shall not contain sharp, angular stones or any objects that could damage the liner. Maximum allowable particle size of soil cover material shall

Conservation practice standards are reviewed periodically, and updated if needed. To obtain the current version of this standard, contact your Natural Resources Conservation Service [State Office](#), or visit the [Field Office Technical Guide](#).

POND SEALING OR LINING - FLEXIBLE MEMBRANE (521A)-2

be 3/8-in for geomembrane liners and 1/2-inch for geosynthetic clay liners, unless the liner is cushioned by an 8-ounce or greater needle punched, non-woven geotextile padding material. Cover materials shall be stable against slippage down the slope under all operational and exposure conditions.

Subgrade Preparation. Subgrade preparation shall conform to manufacturer recommendations. Subgrade materials shall not contain sharp, angular stones or any objects that could damage the liner or adversely affect its function.

Padding. A cushion or padding shall be placed beneath the liner. The padding or cushion shall be an 8-ounce or greater non-woven geotextile.

Anchorage. Liners shall be anchored to prevent uplift due to wind or slippage down the side slope. Anchor trench shall be at least 2 feet wide and 2 feet deep with liner extending across bottom of trench.

Safety. Design shall include appropriate safety features to minimize the hazards of the structure. Warning signs, ladders, ropes, bars, rails, and other devices shall be provided, as appropriate, to ensure the safety of humans and livestock. Ponds shall be fenced to protect the liner from damage and for the safety of humans, livestock, wildlife, and pets.

Vents. If the pond liner is not covered with soil or the pond is located in a location that has historically been used to collect waste, vents shall be installed unless other site conditions exist to allow dissipation of gas pressure from beneath the liner. One such condition is the presence of granular foundation soils (SE, GW, or GP). The maximum vent spacing is 50 feet.

If high water tables could adversely affect the proper functioning of the structure, interceptor or relief-type drainage systems shall be provided to control uplift pressures.

PLANS AND SPECIFICATIONS

Plans and specifications shall be prepared for specific field sites in accordance with this standard and shall describe the requirements for applying the practice to achieve its intended uses.

**NE-T.G. Notice 623
Section IV
NRCS-February 2011**

As a minimum, the plans and specifications shall provide the following:

- 1) Layout of the containment structure, collection points, waste transfer locations or pipelines, and topography of the site
- 2) Required liner properties, cushion materials, and pipeline materials
- 3) Subgrade details, including tolerances on smoothness of the finished grade
- 4) Details of liner installation, seaming requirements, and requirements for attachments and appurtenances
- 5) Quality control testing
- 6) Fence and signage requirements, if required.

OPERATION AND MAINTENANCE

A plan for operation and maintenance (O&M) of the liner and structure shall be prepared. The plan shall be consistent with the purposes of the type of liner chosen, intended life, safety requirements, and design criteria. The plan shall contain requirements including but not limited to:

- 1) Design capacity and liquid level of the structure.
- 2) A description of the normal operation, safety concerns, and maintenance requirements.
- 3) Repair procedures.
- 4) Periodic inspection of the following:
 - Visible portions of the liner for tears punctures, or other damage;
 - Liner interface with inlets, outlets, ramps, or other appurtenances for damage;
 - Liquid level in the structure;
 - Ballooning of the liner indicating presence of gas beneath the liner.

REFERENCES

Quality Assurance and Quality Control for Waste Containment Facilities, EPA/1600/R-93/182, September 1993.