HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

January 2002

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
1C	ALS	50	0.20	220	5	8.8	1	7	0.20	1	15	8.0	400	600	500	2.41	5	0.7	3
1C	ICENE	35	0.20	86	5	3.4	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
2C	ALS	50	0.20	220	5	8.8	1	7	0.20	2	15	8.5	400	600	500	2.52	5	0.7	3
2C	MESMAN	35	0.20	86	5	3.4	3	7	0.37	0	2	1.0	400	900	650	0.64	5	0.3	3
3A	ALVODEST	55	0.20	86	5	3.4	3	7	0.43	0	1	0.5	400	900	650	0.40	5	0.2	3
3A	PLAYAS	30	0.20	56	5	2.2	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
4B	ANAWALT	85	0.20	48	1	9.6	1	20	0.28	2	8	5.0	400	900	650	1.99	1	11.1	1
5C	ANAWALT	50	0.20	48	1	9.6	1	20	0.28	2	15	8.5	400	600	500	2.52	1	14.1	1
5C	ORENEVA	35	0.20	0	2	0.0	3	20	0.10	2	15	8.5	400	600	500	2.52	2	2.5	3
6C	ANAWALT	50	0.20	48	1	9.6	1	20	0.28	2	15	8.5	400	600	500	2.52	1	14.1	1
6C	PEARLWISE	35	0.20	48	2	4.8	3	20	0.28	2	15	8.5	400	600	500	2.52	2	7.0	3
7E	ARGIXEROLLS	60	0.20	56	2	5.6	3	46	0.32	15	30	22.5	250	500	375	4.20	2	30.9	1
7E	BADLAND	25	0.20	0	5	0.0	3	46	0.00	15	30	22.5	250	500	375	4.20	5	0.0	3
8A	BICONDOA	85	0.20	38	5	1.5	3	7	0.28	0	2	1.0	400	900	650	0.64	5	0.3	3
9C	BLIZZARD	85	0.20	0	1	0.0	3	36	0.15	0	15	7.5	400	600	500	2.31	1	12.5	1
10C	BOOTH	85	0.20	38	2	3.8	3	46	0.20	2	15	8.5	400	600	500	2.52	2	11.6	1
11C	BOOTH	85	0.20	86	2	8.6	1	46	0.20	2	15	8.5	400	600	500	2.52	2	11.6	1
12C	BOOTH	85	0.20	0	2	0.0	3	46	0.15	2	15	8.5	400	600	500	2.52	2	8.7	1
12E	BOOTH	85	0.20	0	2	0.0	3	46	0.15	15	30	22.5	250	500	375	4.20	2	14.5	1
13C	BOOTH	50	0.20	0	2	0.0	3	46	0.15	2	15	8.5	400	600	500	2.52	2	8.7	1
13C	BOOTH	35	0.20	0	2	0.0	3	46	0.15	2	15	8.5	400	600	500	2.52	2	8.7	1
13E	BOOTH	50	0.20	0	2	0.0	3	46	0.15	15	30	22.5	250	500	375	4.20	2	14.5	1
13E	BOOTH	35	0.20	0	2	0.0	3	46	0.15	15	30	22.5	250	500	375	4.20	2	14.5	1
14F	BOOTH	45	0.20	0	2	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	2	20.4	1
14F	BOOTH	40	0.20	0	2	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	2	20.4	1
15F	BOOTH	45	0.20	0	2	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	2	20.4	1
15F	BOOTH	40	0.20	0	2	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	2	20.4	1
16C	BOOTH	50	0.20	0	2	0.0	3	46	0.15	2	15	8.5	400	600	500	2.52	2	8.7	1
16C	BOOTH	35	0.20	86	2	8.6	1	46	0.20	2	15	8.5	400	600	500	2.52	2	11.6	1
17E	BOOTH	55	0.20	0	2	0.0	3	46	0.15	5	30	17.5	250	500	375	3.56	2	12.3	1
17E	NUSS	30	0.20	38	1	7.6	3	46	0.17	5	30	17.5	250	500	375	3.56	1	27.9	1
18F	BOOTH	55	0.20	0	2	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	2	20.4	1

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
18F	NUSS	30	0.20	38	1	7.6	3	46	0.17	30	50	40.0	250	500	375	5.92	1	46.3	1
19F	BOOTH	55	0.20	0	2	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	2	20.4	1
19F	NUSS	30	0.20	38	1	7.6	3	46	0.17	30	50	40.0	250	500	375	5.92	1	46.3	1
20C	BOOTH	45	0.20	0	2	0.0	3	46	0.15	2	15	8.5	400	600	500	2.52	2	8.7	1
20C	ROCK OUTCROP	40	0.20	0	5	0.0	3	46	0.00	2	15	8.5	400	600	500	2.52	5	0.0	3
21F	BOOTH	50	0.20	0	2	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	2	20.4	1
21F	ROCK OUTCROP	35	0.20	0	5	0.0	3	46	0.00	30	50	40.0	250	500	375	5.92	5	0.0	3
22F	BOOTH	45	0.20	0	2	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	2	20.4	1
22F	ROCK OUTCROP	40	0.20	0	5	0.0	3	46	0.00	30	50	40.0	250	500	375	5.92	5	0.0	3
23C	BOOTH	40	0.20	0	2	0.0	3	46	0.15	0	15	7.5	400	600	500	2.31	2	8.0	3
23C	NUSS	30	0.20	38	1	7.6	3	46	0.17	0	15	7.5	400	600	500	2.31	1	18.1	1
23C	ROYST	20	0.20	0	2	0.0	3	46	0.17	0	15	7.5	400	600	500	2.31	2	9.0	1
24E	BOOTH	40	0.20	0	2	0.0	3	46	0.15	15	40	27.5	250	500	375	4.77	2	16.4	1
24E	NUSS	30	0.20	38	1	7.6	3	46	0.17	15	40	27.5	250	500	375	4.77	1	37.3	1
24E	ROYST	20	0.20	0	2	0.0	3	46	0.17	15	40	27.5	250	500	375	4.77	2	18.6	1
24G	BOOTH	40	0.20	0	2	0.0	3	46	0.15	40	60	50.0	250	500	375	6.62	2	22.8	1
24G	NUSS	30	0.20	38	1	7.6	3	46	0.17	40	60	50.0	250	500	375	6.62	1	51.8	1
24G	ROYST	20	0.20	0	2	0.0	3	46	0.17	40	60	50.0	250	500	375	6.62	2	25.9	1
25F	BOOTH	35	0.20	0	2	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	2	20.4	1
25F	BOOTH	30	0.20	0	2	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	2	20.4	1
25F	ROCK OUTCROP	25	0.20	0	5	0.0	3	46	0.00	30	50	40.0	250	500	375	5.92	5	0.0	3
26A	BORAVALL	85	0.20	48	5	1.9	3	7	0.43	0	1	0.5	400	900	650	0.40	5	0.2	3
27A	BOULDER LAKE	85	0.20	86	5	3.4	3	26	0.20	0	2	1.0	400	900	650	0.64	5	0.7	3
28C	BRACE	55	0.20	48	2	4.8	3	7	0.28	2	15	8.5	400	600	500	2.52	2	2.5	3
28C	COGLIN	30	0.20	0	5	0.0	3	7	0.05	2	15	8.5	400	600	500	2.52	5	0.2	3
29C	BRACE	55	0.20	48	2	4.8	3	7	0.28	2	15	8.5	400	600	500	2.52	2	2.5	3
29C	RAZ	30	0.20	0	1	0.0	3	7	0.15	2	15	8.5	400	600	500	2.52	1	2.6	3
30B	BUFFARAN	85	0.20	38	1	7.6	3	7	0.28	0	5	2.5	400	900	650	1.22	1	2.4	3
31E	BULLUMP	85	0.20	0	5	0.0	3	46	0.17	5	30	17.5	250	500	375	3.56	5	5.6	3
32E	BULLUMP	85	0.20	38	5	1.5	3	46	0.24	10	40	25.0	250	500	375	4.49	5	9.9	1
33G	BULLUMP	85	0.20	38	5	1.5	3	46	0.24	30	70	50.0	250	500	375	6.62	5	14.6	1
34G	BULLUMP	35	0.20	0	5	0.0	3	46	0.10	30	70	50.0	250	500	375	6.62	5	6.1	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
34G	NUSS	30	0.20	38	1	7.6	3	46	0.17	30	70	50.0	250	500	375	6.62	1	51.8	1
34G	ROCK OUTCROP	20	0.20	0	5	0.0	3	46	0.00	30	70	50.0	250	500	375	6.62	5	0.0	3
35F	BULLUMP	40	0.20	0	5	0.0	3	46	0.10	30	50	40.0	250	500	375	5.92	5	5.4	3
35F	NUSS	25	0.20	38	1	7.6	3	46	0.17	30	50	40.0	250	500	375	5.92	1	46.3	1
35F	ROCK OUTCROP	20	0.20	0	5	0.0	3	46	0.00	30	50	40.0	250	500	375	5.92	5	0.0	3
36G	BULLUMP	40	0.20	0	5	0.0	3	46	0.10	30	50	40.0	250	500	375	5.92	5	5.4	3
36G	ROCK OUTCROP	25	0.20	0	5	0.0	3	46	0.00	50	70	60.0	250	500	375	7.15	5	0.0	3
36G	NUSS	20	0.20	38	1	7.6	3	46	0.17	20	50	35.0	250	500	375	5.50	1	43.0	1
37E	BULLUMP	65	0.20	0	5	0.0	3	46	0.17	5	30	17.5	250	500	375	3.56	5	5.6	3
37E	SHERVAL	20	0.20	0	5	0.0	3	46	0.17	5	20	12.5	400	600	500	3.28	5	5.1	3
38F	BULLUMP	50	0.20	0	5	0.0	3	46	0.10	30	50	40.0	250	500	375	5.92	5	5.4	3
38F	LORELLA	35	0.20	0	1	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	1	40.9	1
39G	BULLUMP	50	0.20	0	5	0.0	3	46	0.10	30	70	50.0	250	500	375	6.62	5	6.1	3
39G	BULLUMP	20	0.20	0	5	0.0	3	46	0.10	30	70	50.0	250	500	375	6.62	5	6.1	3
39G	RUBBLE LAND	20	0.20	0	5	0.0	3	46	0.00	30	70	50.0	250	500	375	6.62	5	0.0	3
40B	CALIMUS	85	0.20	48	5	1.9	3	26	0.37	0	5	2.5	400	900	650	1.22	5	2.4	3
41C	CARRYBACK	85	0.20	0	2	0.0	3	36	0.10	2	15	8.5	400	600	500	2.52	2	4.5	3
42B	CARRYBACK	60	0.20	0	2	0.0	3	36	0.10	0	5	2.5	400	900	650	1.22	2	2.2	3
42B	CARRYBACK	25	0.20	0	2	0.0	3	36	0.10	0	5	2.5	400	900	650	1.22	2	2.2	3
43C	CARRYBACK	50	0.20	0	2	0.0	3	36	0.10	5	15	10.0	400	600	500	2.82	2	5.1	3
43C	ROCK OUTCROP	35	0.20	0	5	0.0	3	36	0.00	5	15	10.0	400	600	500	2.82	5	0.0	3
44C	CHEWAUCAN	85	0.20	0	3	0.0	3	31	0.10	2	15	8.5	400	600	500	2.52	3	2.6	3
45E	CHOCKTOOT	85	0.20	0	5	0.0	3	70	0.10	15	40	27.5	250	500	375	4.77	5	6.7	3
45G	CHOCKTOOT	85	0.20	0	5	0.0	3	70	0.10	40	60	50.0	250	500	375	6.62	5	9.3	1
46E	CHOCKTOOT	50	0.20	0	5	0.0	3	70	0.10	15	40	27.5	250	500	375	4.77	5	6.7	3
46E	KITTLESON	35	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
47C	CORRAL	85	0.20	86	1	17.2	1	13	0.24	2	15	8.5	400	600	500	2.52	1	7.9	3
48C	CORRAL	85	0.20	86	1	17.2	1	13	0.24	2	15	8.5	400	600	500	2.52	1	7.9	3
49C	COZTUR	85	0.20	56	1	11.2	1	20	0.20	2	15	8.5	400	600	500	2.52	1	10.1	1
50A	CRESSLER	85	0.20	38	4	1.9	3	68	0.24	0	2	1.0	400	900	650	0.64	4	2.6	3
51A	CRUMP	85	0.20	56	5	2.2	3	7	0.02	0	1	0.5	400	900	650	0.40	5	0.01	3
52A	CRUMP	85	0.20	38	5	1.5	3	7	0.10	0	1	0.5	400	900	650	0.40	5	0.1	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
53A	CRUMP	55	0.20	38	5	1.5	3	7	0.10	0	1	0.5	400	900	650	0.40	5	0.1	3
53A	BORAVALL	35	0.20	48	5	1.9	3	7	0.43	0	1	0.5	400	900	650	0.40	5	0.2	3
54A	CRUMP	45	0.20	38	5	1.5	3	7	0.10	0	1	0.5	400	900	650	0.40	5	0.1	3
54A	OZAMIS	40	0.20	38	5	1.5	3	7	0.32	0	1	0.5	400	900	650	0.40	5	0.2	3
55A	CRUMP	50	0.20	56	5	2.2	3	7	0.02	0	1	0.5	400	900	650	0.40	5	0.01	3
55A	PIT	35	0.20	86	5	3.4	3	7	0.28	0	1	0.5	400	900	650	0.40	5	0.2	3
56A	CRUMP	50	0.20	56	5	2.2	3	7	0.02	0	1	0.5	400	900	650	0.40	5	0.01	3
56A	REESE	35	0.20	86	5	3.4	3	7	0.24	0	1	0.5	400	900	650	0.40	5	0.1	3
57A	DEGARMO	50	0.20	48	3	3.2	3	31	0.37	0	2	1.0	400	900	650	0.64	3	2.5	3
57A	WELCH	35	0.20	0	5	0.0	3	31	0.32	0	2	1.0	400	900	650	0.64	5	1.3	3
58C	DEPPY	45	0.20	0	1	0.0	3	7	0.15	5	15	10.0	400	600	500	2.82	1	3.0	3
58C	TUMTUM	40	0.20	38	1	7.6	3	7	0.24	5	15	10.0	400	600	500	2.82	1	4.7	3
59F	DEPPY	60	0.20	0	1	0.0	3	7	0.10	30	50	40.0	250	500	375	5.92	1	4.1	3
59F	RUBBLE LAND	25	0.20	0	5	0.0	3	7	0.00	30	50	40.0	250	500	375	5.92	5	0.0	3
60G	DERAPTER	60	0.20	0	3	0.0	3	36	0.10	30	70	50.0	250	500	375	6.62	3	7.9	3
60G	ROCK OUTCROP	30	0.20	0	5	0.0	3	36	0.00	30	70	50.0	250	500	375	6.62	5	0.0	3
61C	DESEED	90	0.20	48	2	4.8	3	20	0.37	2	15	8.5	400	600	500	2.52	2	9.3	1
62C	DESEED	50	0.20	48	2	4.8	3	20	0.37	2	15	8.5	400	600	500	2.52	2	9.3	1
62C	FREZNIK	35	0.20	0	2	0.0	3	20	0.15	2	15	8.5	400	600	500	2.52	2	3.8	3
63F	DESEED	50	0.20	0	2	0.0	3	20	0.15	2	30	16.0	250	500	375	3.36	2	5.0	3
63F	DESEED	35	0.20	0	2	0.0	3	20	0.15	30	50	40.0	250	500	375	5.92	2	8.9	1
64B	DETER	85	0.20	48	5	1.9	3	46	0.24	0	5	2.5	400	900	650	1.22	5	2.7	3
64C	DETER	85	0.20	48	5	1.9	3	46	0.24	5	15	10.0	400	600	500	2.82	5	6.2	3
65B	DETER	85	0.20	48	5	1.9	3	26	0.24	0	5	2.5	400	900	650	1.22	5	1.5	3
65C	DETER	85	0.20	48	5	1.9	3	26	0.24	5	15	10.0	400	600	500	2.82	5	3.5	3
66C	DEVADA	50	0.20	0	1	0.0	3	20	0.17	2	15	8.5	400	600	500	2.52	1	8.6	1
66C	DESEED	35	0.20	48	2	4.8	3	20	0.37	2	15	8.5	400	600	500	2.52	2	9.3	1
67C	DEVOY	50	0.20	38	2	3.8	3	36	0.20	2	15	8.5	400	600	500	2.52	2	9.1	1
67C	BLIZZARD	35	0.20	0	1	0.0	3	36	0.15	2	15	8.5	400	600	500	2.52	1	13.6	1
68C	DIAZ	85	0.20	0	2	0.0	3	7	0.15	2	15	8.5	400	600	500	2.52	2	1.3	3
69B	DONICA	85	0.20	48	5	1.9	3	46	0.20	0	5	2.5	400	900	650	1.22	5	2.3	3
69C	DONICA	85	0.20	48	5	1.9	3	46	0.20	5	15	10.0	400	600	500	2.82	5	5.2	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
70C	DRAKESFLAT	85	0.20	48	2	4.8	3	20	0.28	2	15	8.5	400	600	500	2.52	2	7.0	3
70E	DRAKESFLAT	85	0.20	48	2	4.8	3	20	0.28	15	30	22.5	250	500	375	4.20	2	11.8	1
71C	DRAKESFLAT	45	0.20	48	2	4.8	3	20	0.28	2	15	8.5	400	600	500	2.52	2	7.0	3
71C	COGLIN	40	0.20	0	5	0.0	3	20	0.05	2	15	8.5	400	600	500	2.52	5	0.5	3
72F	DRAKESPEAK	85	0.20	56	5	2.2	3	70	0.15	20	50	35.0	250	500	375	5.50	5	11.6	1
73B	DREWS	85	0.20	56	5	2.2	3	46	0.28	0	5	2.5	400	900	650	1.22	5	3.2	3
73C	DREWS	85	0.20	56	5	2.2	3	46	0.28	5	15	10.0	400	600	500	2.82	5	7.3	3
73E	DREWS	85	0.20	56	5	2.2	3	46	0.28	15	30	22.5	250	500	375	4.20	5	10.8	1
74C	DREWS	85	0.20	48	5	1.9	3	46	0.20	5	15	10.0	400	600	500	2.82	5	5.2	3
75B	DREWS	50	0.20	56	5	2.2	3	46	0.28	0	5	2.5	400	900	650	1.22	5	3.2	3
75B	OXWALL	35	0.20	38	1	7.6	3	46	0.20	0	5	2.5	400	900	650	1.22	1	11.3	1
76B	DREWSGAP	85	0.20	56	2	5.6	3	46	0.28	0	5	2.5	400	900	650	1.22	2	7.9	3
76C	DREWSGAP	85	0.20	56	2	5.6	3	46	0.28	5	15	10.0	400	600	500	2.82	2	18.1	1
77E	EGLIRIM	85	0.20	0	5	0.0	3	26	0.15	2	30	16.0	250	500	375	3.36	5	2.6	3
78F	EGLIRIM	45	0.20	0	5	0.0	3	26	0.15	30	50	40.0	250	500	375	5.92	5	4.6	3
78F	EGLIRIM	40	0.20	0	5	0.0	3	26	0.15	30	50	40.0	250	500	375	5.92	5	4.6	3
79C	ERAKATAK	85	0.20	38	2	3.8	3	36	0.20	2	15	8.5	400	600	500	2.52	2	9.1	1
80E	ERAKATAK	50	0.20	38	2	3.8	3	36	0.20	15	30	22.5	250	500	375	4.20	2	15.1	1
80E	CARRYBACK	35	0.20	0	2	0.0	3	36	0.10	15	30	22.5	250	500	375	4.20	2	7.6	3
81E	FELCHER	85	0.20	0	2	0.0	3	20	0.10	5	30	17.5	250	500	375	3.56	2	3.6	3
82F	FELCHER	85	0.20	0	2	0.0	3	20	0.10	30	50	40.0	250	500	375	5.92	2	5.9	3
83G	FELCHER	60	0.20	0	2	0.0	3	20	0.10	30	70	50.0	250	500	375	6.62	2	6.6	3
83G	ROCK OUTCROP	25	0.20	0	5	0.0	3	20	0.00	30	70	50.0	250	500	375	6.62	5	0.0	3
84F	FELCHER	45	0.20	0	2	0.0	3	20	0.10	30	50	40.0	250	500	375	5.92	2	5.9	3
84F	WESTBUTTE	40	0.20	0	2	0.0	3	20	0.10	30	50	40.0	250	500	375	5.92	2	5.9	3
85C	FERTALINE	85	0.20	38	2	3.8	3	20	0.24	2	15	8.5	400	600	500	2.52	2	6.0	3
86C	FERTALINE	45	0.20	38	2	3.8	3	20	0.24	2	15	8.5	400	600	500	2.52	2	6.0	3
86C	COGLIN	40	0.20	0	5	0.0	3	20	0.05	2	15	8.5	400	600	500	2.52	5	0.5	3
87B	FITZWATER	85	0.20	48	5	1.9	3	36	0.24	0	5	2.5	400	900	650	1.22	5	2.1	3
88E	FITZWATER	85	0.20	0	5	0.0	3	36	0.10	2	30	16.0	250	500	375	3.36	5	2.4	3
89F	FITZWATER	85	0.20	0	5	0.0	3	36	0.10	30	50	40.0	250	500	375	5.92	5	4.3	3
90F	FITZWATER	50	0.20	0	5	0.0	3	36	0.10	30	50	40.0	250	500	375	5.92	5	4.3	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
90F	FITZWATER	35	0.20	0	5	0.0	3	36	0.10	30	50	40.0	250	500	375	5.92	5	4.3	3
91F	FITZWATER	60	0.20	0	5	0.0	3	36	0.10	30	50	40.0	250	500	375	5.92	5	4.3	3
91F	WESTBUTTE	25	0.20	0	2	0.0	3	36	0.10	30	50	40.0	250	500	375	5.92	2	10.7	1
92C	FLOKE	50	0.20	0	1	0.0	3	20	0.10	2	15	8.5	400	600	500	2.52	1	5.0	3
92C	FLOKE	35	0.20	0	1	0.0	3	20	0.05	2	15	8.5	400	600	500	2.52	1	2.5	3
93C	FLOKE	45	0.20	0	1	0.0	3	20	0.10	2	15	8.5	400	600	500	2.52	1	5.0	3
93C	RATTO	40	0.20	0	1	0.0	3	20	0.15	2	15	8.5	400	600	500	2.52	1	7.6	3
94A	FLUVAQUENTS	90	0.20	0	5	0.0	3	41	0.00	0	2	1.0	400	900	650	0.64	5	0.0	3
95B	FORDNEY	85	0.20	86	5	3.4	3	26	0.10	0	5	2.5	400	900	650	1.22	5	0.6	3
95C	FORDNEY	85	0.20	86	5	3.4	3	26	0.10	5	15	10.0	400	600	500	2.82	5	1.5	3
96C	FREZNIK	85	0.20	0	2	0.0	3	20	0.15	2	15	8.5	400	600	500	2.52	2	3.8	3
97A	GOOSE LAKE	85	0.20	48	2	4.8	3	36	0.43	0	1	0.5	400	900	650	0.40	2	3.1	3
98A	GOOSE LAKE	85	0.20	48	2	4.8	3	36	0.43	0	1	0.5	400	900	650	0.40	2	3.1	3
99A	GOOSE LAKE	85	0.20	38	2	3.8	3	36	0.43	0	1	0.5	400	900	650	0.40	2	3.1	3
100C	HAGER	45	0.20	38	2	3.8	3	7	0.20	2	15	8.5	400	600	500	2.52	2	1.8	3
100C	HAGER	40	0.20	0	2	0.0	3	7	0.05	2	15	8.5	400	600	500	2.52	2	0.4	3
101C	HALLIHAN	85	0.20	86	5	3.4	3	70	0.17	0	15	7.5	400	600	500	2.31	5	5.5	3
102E	HALLIHAN	85	0.20	86	5	3.4	3	70	0.17	15	40	27.5	250	500	375	4.77	5	11.3	1
102G	HALLIHAN	85	0.20	86	5	3.4	3	70	0.17	40	60	50.0	250	500	375	6.62	5	15.8	1
103E	HAMMERSLEY	50	0.20	48	3	3.2	3	70	0.28	15	40	27.5	250	500	375	4.77	3	31.2	1
103E	KITTLESON	35	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
103G	HAMMERSLEY	50	0.20	48	3	3.2	3	70	0.28	40	70	55.0	250	500	375	6.91	3	45.1	1
103G	KITTLESON	35	0.20	86	3	5.7	3	70	0.20	40	70	55.0	250	500	375	6.91	3	32.2	1
104E	HARCANY	85	0.20	38	5	1.5	3	36	0.10	15	30	22.5	250	500	375	4.20	5	3.0	3
105E	HARCANY	50	0.20	38	5	1.5	3	36	0.10	5	30	17.5	250	500	375	3.56	5	2.6	3
105E	HARCANY	35	0.20	38	5	1.5	3	36	0.10	5	30	17.5	250	500	375	3.56	5	2.6	3
106F	HARCANY	50	0.20	38	5	1.5	3	36	0.10	30	50	40.0	250	500	375	5.92	5	4.3	3
106F	HARCANY	35	0.20	38	5	1.5	3	36	0.10	30	50	40.0	250	500	375	5.92	5	4.3	3
107E	HARCANY	50	0.20	38	5	1.5	3	54	0.10	5	30	17.5	250	500	375	3.56	5	3.9	3
107E	HARCANY	35	0.20	38	5	1.5	3	54	0.10	5	30	17.5	250	500	375	3.56	5	3.9	3
108G	HARCANY	35	0.20	38	5	1.5	3	36	0.10	30	70	50.0	250	500	375	6.62	5	4.8	3
108G	HARCANY	30	0.20	38	5	1.5	3	36	0.10	30	70	50.0	250	500	375	6.62	5	4.8	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
108G	ROCK OUTCROP	20	0.20	0	5	0.0	3	36	0.00	30	70	50.0	250	500	375	6.62	5	0.0	3
109B	HARRIMAN	85	0.20	56	5	2.2	3	26	0.24	0	5	2.5	400	900	650	1.22	5	1.5	3
109C	HARRIMAN	85	0.20	56	5	2.2	3	26	0.24	5	15	10.0	400	600	500	2.82	5	3.5	3
110C	HART	85	0.20	38	2	3.8	3	36	0.10	2	15	8.5	400	600	500	2.52	2	4.5	3
111C	HART	45	0.20	38	2	3.8	3	36	0.10	2	15	8.5	400	600	500	2.52	2	4.5	3
111C	HART	40	0.20	0	2	0.0	3	36	0.05	2	15	8.5	400	600	500	2.52	2	2.3	3
112C	HELPHENSTEIN	40	0.20	86	5	3.4	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
112C	TURPIN	30	0.20	56	5	2.2	3	7	0.32	0	5	2.5	400	900	650	1.22	5	0.5	3
112C	KEWAKE	20	0.20	220	5	8.8	1	7	0.15	2	15	8.5	400	600	500	2.52	5	0.5	3
113A	ICENE	35	0.20	86	5	3.4	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
113A	LOFFTUS	30	0.20	56	2	5.6	3	7	0.55	0	1	0.5	400	900	650	0.40	2	0.8	3
113A	PIT	25	0.20	48	5	1.9	3	7	0.43	0	1	0.5	400	900	650	0.40	5	0.2	3
114B	ICENE	35	0.20	86	5	3.4	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
114B	MESMAN	25	0.20	86	5	3.4	3	7	0.37	0	5	2.5	400	900	650	1.22	5	0.6	3
114B	REESE	25	0.20	86	5	3.4	3	7	0.49	0	1	0.5	400	900	650	0.40	5	0.3	3
115A	ICENE	55	0.20	86	5	3.4	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
115A	PLAYAS	30	0.20	56	5	2.2	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
116G	ITCA	90	0.20	0	1	0.0	3	46	0.15	30	70	50.0	250	500	375	6.62	1	45.7	1
117F	ITCA	45	0.20	0	1	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	1	40.9	1
117F	BULLUMP	40	0.20	0	5	0.0	3	46	0.10	30	50	40.0	250	500	375	5.92	5	5.4	3
118B	JESSE CAMP	85	0.20	48	4	2.4	3	7	0.43	2	5	3.5	400	900	650	1.55	4	1.2	3
119C	KEWAKE	55	0.20	220	5	8.8	1	7	0.15	1	15	8.0	400	600	500	2.41	5	0.5	3
119C	HELPHENSTEIN	30	0.20	86	5	3.4	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
120C	KEWAKE	55	0.20	220	5	8.8	1	7	0.15	1	15	8.0	400	600	500	2.41	5	0.5	3
120C	ICENE	30	0.20	86	5	3.4	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
121C	KEWAKE	35	0.20	220	5	8.8	1	7	0.15	1	15	8.0	400	600	500	2.41	5	0.5	3
121C	OZAMIS	30	0.20	86	5	3.4	3	7	0.20	0	1	0.5	400	900	650	0.40	5	0.1	3
121C	REESE	20	0.20	86	5	3.4	3	7	0.49	0	1	0.5	400	900	650	0.40	5	0.3	3
122E	KITTLESON	85	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
123E	KITTLESON	50	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
123E	HALLIHAN	35	0.20	86	5	3.4	3	70	0.17	15	40	27.5	250	500	375	4.77	5	11.3	1
124A	LAKEVIEW	85	0.20	48	5	1.9	3	46	0.24	0	2	1.0	400	900	650	0.64	5	1.4	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
125A	LAKEVIEW	85	0.20	38	5	1.5	3	46	0.28	0	2	1.0	400	900	650	0.64	5	1.7	3
126A	LAKEVIEW	85	0.20	38	5	1.5	3	46	0.28	0	2	1.0	400	900	650	0.64	5	1.7	3
127A	LAKEVIEW	85	0.20	38	5	1.5	3	7	0.28	0	2	1.0	400	900	650	0.64	5	0.3	3
128A	LAKEVIEW	50	0.20	38	5	1.5	3	46	0.28	0	2	1.0	400	900	650	0.64	5	1.7	3
128A	STOCKDRIVE	35	0.20	86	3	5.7	3	46	0.37	0	1	0.5	400	900	650	0.40	3	2.3	3
129E	LAMBRING	45	0.20	0	3	0.0	3	36	0.15	5	30	17.5	250	500	375	3.56	3	6.4	3
129E	LAMBRING	25	0.20	0	3	0.0	3	36	0.15	5	30	17.5	250	500	375	3.56	3	6.4	3
129E	ROCK OUTCROP	15	0.20	0	5	0.0	3	36	0.00	5	30	17.5	250	500	375	3.56	5	0.0	3
130G	LAMBRING	45	0.20	0	3	0.0	3	36	0.15	30	70	50.0	250	500	375	6.62	3	11.9	1
130G	LAMBRING	25	0.20	0	3	0.0	3	36	0.15	30	70	50.0	250	500	375	6.62	3	11.9	1
130G	ROCK OUTCROP	15	0.20	0	5	0.0	3	36	0.00	30	70	50.0	250	500	375	6.62	5	0.0	3
131A	LANGSLET	85	0.20	48	5	1.9	3	7	0.32	0	2	1.0	400	900	650	0.64	5	0.3	3
132C	LASERE	85	0.20	56	2	5.6	3	46	0.24	2	15	8.5	400	600	500	2.52	2	13.9	1
133E	LASERE	85	0.20	38	2	3.8	3	46	0.17	5	30	17.5	250	500	375	3.56	2	13.9	1
134F	LASERE	85	0.20	38	2	3.8	3	46	0.17	30	50	40.0	250	500	375	5.92	2	23.2	1
135C	LASERE	50	0.20	56	2	5.6	3	46	0.24	2	15	8.5	400	600	500	2.52	2	13.9	1
135C	LASERE	35	0.20	56	2	5.6	3	46	0.24	2	15	8.5	400	600	500	2.52	2	13.9	1
136E	LASERE	50	0.20	38	2	3.8	3	46	0.17	5	30	17.5	250	500	375	3.56	2	13.9	1
136E	LORELLA	35	0.20	0	1	0.0	3	46	0.15	5	30	17.5	250	500	375	3.56	1	24.6	1
137G	LASERE	35	0.20	38	2	3.8	3	46	0.17	30	50	40.0	250	500	375	5.92	2	23.2	1
137G	LORELLA	30	0.20	0	1	0.0	3	46	0.15	30	70	50.0	250	500	375	6.62	1	45.7	1
137G	BULLUMP	20	0.20	0	5	0.0	3	46	0.10	30	70	50.0	250	500	375	6.62	5	6.1	3
138C	LOBERT	85	0.20	48	5	1.9	3	54	0.24	2	15	8.5	400	600	500	2.52	5	6.5	3
139B	LOCANE	85	0.20	38	1	7.6	3	20	0.20	2	8	5.0	400	900	650	1.99	1	7.9	3
140C	LOCANE	45	0.20	38	1	7.6	3	20	0.20	2	15	8.5	400	600	500	2.52	1	10.1	1
140C	ANAWALT	40	0.20	48	1	9.6	1	20	0.28	2	15	8.5	400	600	500	2.52	1	14.1	1
140E	LOCANE	50	0.20	38	1	7.6	3	20	0.20	15	30	22.5	250	500	375	4.20	1	16.8	1
140E	ANAWALT	40	0.20	48	1	9.6	1	20	0.28	15	30	22.5	250	500	375	4.20	1	23.5	1
141A	LOFFTUS	45	0.20	56	2	5.6	3	7	0.55	0	1	0.5	400	900	650	0.40	2	0.8	3
141A	MESMAN	40	0.20	86	5	3.4	3	7	0.37	0	2	1.0	400	900	650	0.64	5	0.3	3
142A	LOFFTUS	45	0.20	56	2	5.6	3	7	0.55	0	1	0.5	400	900	650	0.40	2	0.8	3
142A	REESE	40	0.20	86	5	3.4	3	7	0.49	0	1	0.5	400	900	650	0.40	5	0.3	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
143F	LONGJOHN	85	0.20	86	5	3.4	3	70	0.17	15	50	32.5	250	500	375	5.27	5	12.5	1
144E	LORELLA	85	0.20	0	1	0.0	3	46	0.15	2	30	16.0	250	500	375	3.36	1	23.2	1
145C	LORELLA	85	0.20	86	1	17.2	1	26	0.20	2	15	8.5	400	600	500	2.52	1	13.1	1
146G	LORELLA	55	0.20	0	1	0.0	3	46	0.15	30	70	50.0	250	500	375	6.62	1	45.7	1
146G	ITCA	30	0.20	0	1	0.0	3	46	0.15	30	70	50.0	250	500	375	6.62	1	45.7	1
147F	LORELLA	50	0.20	0	1	0.0	3	46	0.15	30	50	40.0	250	500	375	5.92	1	40.9	1
147F	LASERE	35	0.20	38	2	3.8	3	46	0.17	30	50	40.0	250	500	375	5.92	2	23.2	1
148F	LORELLA	50	0.20	0	1	0.0	3	26	0.15	30	50	40.0	250	500	375	5.92	1	23.1	1
148F	ROCK OUTCROP	35	0.20	0	5	0.0	3	26	0.00	30	50	40.0	250	500	375	5.92	5	0.0	3
149G	LORELLA	50	0.20	0	1	0.0	3	36	0.15	30	70	50.0	250	500	375	6.62	1	35.8	1
149G	RUBBLE LAND	35	0.20	0	5	0.0	3	36	0.00	30	70	50.0	250	500	375	6.62	5	0.0	3
150A	MACYFLET	50	0.20	38	4	1.9	3	26	0.43	0	2	1.0	400	900	650	0.64	4	1.8	3
150A	BOULDER LAKE	35	0.20	86	5	3.4	3	26	0.20	0	2	1.0	400	900	650	0.64	5	0.7	3
151C	MADELINE	50	0.20	56	1	11.2	1	36	0.20	5	15	10.0	400	600	500	2.82	1	20.3	1
151C	NINEMILE	35	0.20	0	1	0.0	3	36	0.15	5	15	10.0	400	600	500	2.82	1	15.2	1
151E	MADELINE	50	0.20	56	1	11.2	1	36	0.20	15	30	22.5	250	500	375	4.20	1	30.3	1
151E	NINEMILE	35	0.20	0	1	0.0	3	36	0.15	15	30	22.5	250	500	375	4.20	1	22.7	1
152A	MALIN	85	0.20	86	5	3.4	3	31	0.37	0	1	0.5	400	900	650	0.40	5	0.9	3
153A	MCCONNEL	85	0.20	56	5	2.2	3	7	0.10	0	2	1.0	400	900	650	0.64	5	0.1	3
153C	MCCONNEL	85	0.20	56	5	2.2	3	7	0.10	2	15	8.5	400	600	500	2.52	5	0.4	3
154C	MCCONNEL	85	0.20	0	5	0.0	3	7	0.05	5	15	10.0	400	600	500	2.82	5	0.2	3
155C	MCCONNEL	90	0.20	56	5	2.2	3	7	0.10	2	15	8.5	400	600	500	2.52	5	0.4	3
156B	MCCONNEL	85	0.20	86	5	3.4	3	7	0.17	0	5	2.5	400	900	650	1.22	5	0.3	3
157C	MCCONNEL	55	0.20	86	5	3.4	3	7	0.17	1	15	8.0	400	600	500	2.41	5	0.6	3
157C	ICENE	30	0.20	86	5	3.4	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
158F	MCCONNEL	45	0.20	56	5	2.2	3	7	0.10	30	50	40.0	250	500	375	5.92	5	0.8	3
158F	MCCONNEL	40	0.20	56	5	2.2	3	7	0.10	30	50	40.0	250	500	375	5.92	5	0.8	3
159C	MCNYE	65	0.20	48	3	3.2	3	7	0.20	2	15	8.5	400	600	500	2.52	3	1.2	3
159C	WILDHILL	20	0.20	38	2	3.8	3	7	0.17	2	15	8.5	400	600	500	2.52	2	1.5	3
160F	MCNYE	60	0.20	48	3	3.2	3	7	0.20	30	50	40.0	250	500	375	5.92	3	2.8	3
160F	WILDHILL	25	0.20	38	2	3.8	3	7	0.17	30	50	40.0	250	500	375	5.92	2	3.5	3
161C	MERLIN	85	0.20	0	1	0.0	3	54	0.10	0	15	7.5	400	600	500	2.31	1	12.5	1

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
162B	MESMAN	85	0.20	86	5	3.4	3	7	0.37	0	5	2.5	400	900	650	1.22	5	0.6	3
163B	MESMAN	85	0.20	86	5	3.4	3	7	0.37	0	5	2.5	400	900	650	1.22	5	0.6	3
163C	MESMAN	85	0.20	86	5	3.4	3	7	0.37	5	15	10.0	400	600	500	2.82	5	1.5	3
164C	MESMAN	50	0.20	86	5	3.4	3	7	0.37	0	2	1.0	400	900	650	0.64	5	0.3	3
164C	ALS	35	0.20	220	5	8.8	1	7	0.20	2	15	8.5	400	600	500	2.52	5	0.7	3
165C	MOUND	85	0.20	38	3	2.5	3	65	0.17	0	15	7.5	400	600	500	2.31	3	8.5	1
166G	MOUND	85	0.20	38	3	2.5	3	65	0.17	40	60	50.0	250	500	375	6.62	3	24.4	1
167E	MOUND	85	0.20	38	3	2.5	3	65	0.17	2	30	16.0	250	500	375	3.36	3	12.4	1
168F	MOUND	85	0.20	0	3	0.0	3	65	0.10	30	50	40.0	250	500	375	5.92	3	12.8	1
169E	MOUND	50	0.20	38	3	2.5	3	70	0.17	15	40	27.5	250	500	375	4.77	3	18.9	1
169E	POLANDER	35	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
169G	MOUND	50	0.20	38	3	2.5	3	70	0.17	40	70	55.0	250	500	375	6.91	3	27.4	1
169G	POLANDER	40	0.20	86	3	5.7	3	70	0.20	40	70	55.0	250	500	375	6.91	3	32.2	1
170E	MOUND	50	0.20	38	3	2.5	3	70	0.17	15	40	27.5	250	500	375	4.77	3	18.9	1
170E	POLANDER	35	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
170G	MOUND	50	0.20	38	3	2.5	3	70	0.17	40	70	55.0	250	500	375	6.91	3	27.4	1
170G	POLANDER	40	0.20	86	3	5.7	3	70	0.20	40	70	55.0	250	500	375	6.91	3	32.2	1
171E	MOUND	35	0.20	38	3	2.5	3	65	0.17	15	40	27.5	250	500	375	4.77	3	17.6	1
171E	ROYST	30	0.20	0	2	0.0	3	65	0.17	15	40	27.5	250	500	375	4.77	2	26.3	1
171E	NUSS	20	0.20	38	1	7.6	3	65	0.17	15	40	27.5	250	500	375	4.77	1	52.7	1
171G	MOUND	35	0.20	38	3	2.5	3	65	0.17	40	60	50.0	250	500	375	6.62	3	24.4	1
171G	ROYST	30	0.20	0	2	0.0	3	65	0.17	40	60	50.0	250	500	375	6.62	2	36.6	1
171G	NUSS	20	0.20	38	1	7.6	3	65	0.17	40	60	50.0	250	500	375	6.62	1	73.2	1
172A	MUDPOT	85	0.20	86	5	3.4	3	7	0.20	0	2	1.0	400	900	650	0.64	5	0.2	3
173A	MUDPOT	50	0.20	86	5	3.4	3	7	0.20	0	2	1.0	400	900	650	0.64	5	0.2	3
173A	SWALESILVER	35	0.20	86	5	3.4	3	7	0.37	0	2	1.0	400	900	650	0.64	5	0.3	3
174C	NEWLANDS	50	0.20	56	3	3.7	3	36	0.37	5	15	10.0	400	600	500	2.82	3	12.5	1
174C	HART	35	0.20	38	2	3.8	3	36	0.10	5	15	10.0	400	600	500	2.82	2	5.1	3
175E	NEWLANDS	35	0.20	56	3	3.7	3	36	0.37	15	30	22.5	250	500	375	4.20	3	18.7	1
175E	HART	30	0.20	38	2	3.8	3	36	0.10	15	30	22.5	250	500	375	4.20	2	7.6	3
175E	MASCAMP	20	0.20	0	1	0.0	3	36	0.15	15	30	22.5	250	500	375	4.20	1	22.7	1
176F	NEWLANDS	35	0.20	56	3	3.7	3	36	0.37	30	50	40.0	250	500	375	5.92	3	26.3	1

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
176F	HART	30	0.20	38	2	3.8	3	36	0.10	30	50	40.0	250	500	375	5.92	2	10.7	1
176F	MASCAMP	20	0.20	0	1	0.0	3	36	0.15	30	50	40.0	250	500	375	5.92	1	32.0	1
177C	NEWLANDS	50	0.20	56	3	3.7	3	36	0.37	5	15	10.0	400	600	500	2.82	3	12.5	1
177C	NINEMILE	35	0.20	0	1	0.0	3	36	0.15	5	15	10.0	400	600	500	2.82	1	15.2	1
178C	NINEMILE	85	0.20	0	1	0.0	3	36	0.15	2	15	8.5	400	600	500	2.52	1	13.6	1
179C	NINEMILE	85	0.20	0	1	0.0	3	36	0.15	2	15	8.5	400	600	500	2.52	1	13.6	1
180C	NINEMILE	85	0.20	0	1	0.0	3	36	0.10	2	15	8.5	400	600	500	2.52	1	9.1	1
180E	NINEMILE	85	0.20	0	1	0.0	3	36	0.10	15	30	22.5	250	500	375	4.20	1	15.1	1
181C	NINEMILE	60	0.20	0	1	0.0	3	36	0.15	2	15	8.5	400	600	500	2.52	1	13.6	1
181C	WESTBUTTE	30	0.20	0	2	0.0	3	36	0.10	2	15	8.5	400	600	500	2.52	2	4.5	3
182A	NORAD	85	0.20	48	5	1.9	3	7	0.28	0	2	1.0	400	900	650	0.64	5	0.3	3
183B	NUSS	85	0.20	38	1	7.6	3	46	0.17	0	5	2.5	400	900	650	1.22	1	9.6	1
184C	OBSERVATION	50	0.20	38	2	3.8	3	46	0.24	0	15	7.5	400	600	500	2.31	2	12.7	1
184C	BOOTH	35	0.20	86	2	8.6	1	46	0.20	0	15	7.5	400	600	500	2.31	2	10.6	1
185C	OLD CAMP	85	0.20	0	1	0.0	3	7	0.15	2	15	8.5	400	600	500	2.52	1	2.6	3
186F	OLD CAMP	85	0.20	0	1	0.0	3	7	0.15	30	50	40.0	250	500	375	5.92	1	6.2	3
187C	ORENEVA	85	0.20	0	2	0.0	3	20	0.10	2	15	8.5	400	600	500	2.52	2	2.5	3
187E	ORENEVA	85	0.20	0	2	0.0	3	20	0.10	15	30	22.5	250	500	375	4.20	2	4.2	3
188B	OROVADA	50	0.20	56	3	3.7	3	7	0.43	0	5	2.5	400	900	650	1.22	3	1.2	3
188B	MESMAN	35	0.20	86	5	3.4	3	7	0.37	0	5	2.5	400	900	650	1.22	5	0.6	3
189B	OXWALL	85	0.20	38	1	7.6	3	46	0.20	0	5	2.5	400	900	650	1.22	1	11.3	1
190B	OXWALL	50	0.20	38	1	7.6	3	46	0.20	0	5	2.5	400	900	650	1.22	1	11.3	1
190B	SALISBURY	35	0.20	48	2	4.8	3	46	0.37	0	5	2.5	400	900	650	1.22	2	10.4	1
191A	OZAMIS	85	0.20	48	5	1.9	3	20	0.24	0	1	0.5	400	900	650	0.40	5	0.4	3
192A	OZAMIS	85	0.20	38	5	1.5	3	20	0.32	0	1	0.5	400	900	650	0.40	5	0.5	3
193A	OZAMIS	85	0.20	86	5	3.4	3	7	0.20	0	1	0.5	400	900	650	0.40	5	0.1	3
194A	OZAMIS	35	0.20	86	5	3.4	3	7	0.20	0	1	0.5	400	900	650	0.40	5	0.1	3
194A	CRUMP	30	0.20	56	5	2.2	3	7	0.02	0	1	0.5	400	900	650	0.40	5	0.01	3
194A	REESE	25	0.20	86	5	3.4	3	7	0.32	0	1	0.5	400	900	650	0.40	5	0.2	3
195A	OZAMIS	50	0.20	48	5	1.9	3	7	0.24	0	1	0.5	400	900	650	0.40	5	0.1	3
195A	REESE	35	0.20	86	5	3.4	3	7	0.49	0	1	0.5	400	900	650	0.40	5	0.3	3
196C	PAIT	85	0.20	56	5	2.2	3	7	0.24	5	15	10.0	400	600	500	2.82	5	0.9	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
197E	PAIT	85	0.20	38	5	1.5	3	7	0.17	5	30	17.5	250	500	375	3.56	5	0.8	3
198C	PAIT	50	0.20	38	5	1.5	3	7	0.17	1	15	8.0	400	600	500	2.41	5	0.6	3
198C	ICENE	35	0.20	86	5	3.4	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
199E	PEARLWISE	85	0.20	48	2	4.8	3	31	0.28	2	30	16.0	250	500	375	3.36	2	14.6	1
200E	PERNOG	55	0.20	56	1	11.2	1	46	0.15	15	30	22.5	250	500	375	4.20	1	29.0	1
200E	ITCA	30	0.20	0	1	0.0	3	46	0.15	5	15	10.0	400	600	500	2.82	1	19.4	1
201A	PIT	85	0.20	86	5	3.4	3	26	0.28	0	1	0.5	400	900	650	0.40	5	0.6	3
202A	PIT	85	0.20	38	5	1.5	3	7	0.28	0	1	0.5	400	900	650	0.40	5	0.2	3
203A	PIT	85	0.20	38	5	1.5	3	7	0.20	0	1	0.5	400	900	650	0.40	5	0.1	3
204A	PIT	45	0.20	38	5	1.5	3	7	0.20	0	1	0.5	400	900	650	0.40	5	0.1	3
204A	OZAMIS	40	0.20	38	5	1.5	3	7	0.32	0	1	0.5	400	900	650	0.40	5	0.2	3
205A	PLAYAS	90	0.20	56	5	2.2	3	13	0.37	0	1	0.5	400	900	650	0.40	5	0.4	3
205B	PLAYAS	85	0.20	56	5	2.2	3	7	0.00	2	5	3.5	400	900	650	1.55	5	0.0	3
206A	PLAYAS	55	0.20	56	5	2.2	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
206A	HELPHENSTEIN	30	0.20	86	5	3.4	3	7	0.37	0	2	1.0	400	900	650	0.64	5	0.3	3
207C	POLANDER	85	0.20	86	3	5.7	3	70	0.20	0	15	7.5	400	600	500	2.31	3	10.8	1
208E	POLANDER	85	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
209E	POLANDER	85	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
210E	POLANDER	35	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
210E	TWELVEMILE	25	0.20	56	5	2.2	3	70	0.10	15	40	27.5	250	500	375	4.77	5	6.7	3
210E	MOUND	25	0.20	38	3	2.5	3	70	0.17	15	40	27.5	250	500	375	4.77	3	18.9	1
211E	POLANDER	35	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
211E	TWELVEMILE	25	0.20	56	5	2.2	3	70	0.10	15	40	27.5	250	500	375	4.77	5	6.7	3
211E	MOUND	25	0.20	38	3	2.5	3	70	0.17	15	40	27.5	250	500	375	4.77	3	18.9	1
212C	POLANDER	45	0.20	86	3	5.7	3	70	0.20	0	15	7.5	400	600	500	2.31	3	10.8	1
212C	XEROLLS	45	0.20	0	3	0.0	3	70	0.10	0	15	7.5	400	600	500	2.31	3	5.4	3
213E	POLANDER	45	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
213E	XEROLLS	45	0.20	0	3	0.0	3	70	0.10	15	40	27.5	250	500	375	4.77	3	11.1	1
214E	POLANDER	45	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
214E	XEROLLS	45	0.20	0	3	0.0	3	70	0.10	15	40	27.5	250	500	375	4.77	3	11.1	1
215C	RATTO	85	0.20	0	1	0.0	3	20	0.15	2	15	8.5	400	600	500	2.52	1	7.6	3
216C	RATTO	85	0.20	56	1	11.2	1	7	0.20	2	15	8.5	400	600	500	2.52	1	3.5	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
217C	RATTO	55	0.20	0	1	0.0	3	20	0.15	2	15	8.5	400	600	500	2.52	1	7.6	3
217C	COGLIN	30	0.20	0	5	0.0	3	20	0.05	2	15	8.5	400	600	500	2.52	5	0.5	3
218C	RATTO	50	0.20	56	1	11.2	1	7	0.20	2	15	8.5	400	600	500	2.52	1	3.5	3
218C	COGLIN	35	0.20	0	5	0.0	3	7	0.05	2	15	8.5	400	600	500	2.52	5	0.2	3
219D	RAZ	50	0.20	0	1	0.0	3	20	0.15	2	20	11.0	400	600	500	3.01	1	9.0	1
219D	BRACE	35	0.20	48	2	4.8	3	20	0.28	2	20	11.0	400	600	500	3.01	2	8.4	1
220C	RAZ	55	0.20	134	1	26.8	1	20	0.17	2	15	8.5	400	600	500	2.52	1	8.6	1
220C	BRACE	35	0.20	134	2	13.4	1	20	0.17	2	15	8.5	400	600	500	2.52	2	4.3	3
221F	REDCANYON	50	0.20	0	2	0.0	3	31	0.05	30	50	40.0	250	500	375	5.92	2	4.6	3
221F	ROCK OUTCROP	35	0.20	0	5	0.0	3	31	0.00	30	50	40.0	250	500	375	5.92	5	0.0	3
222F	REDCANYON	50	0.20	0	2	0.0	3	31	0.05	30	50	40.0	250	500	375	5.92	2	4.6	3
222F	ROCK OUTCROP	35	0.20	0	5	0.0	3	31	0.00	30	50	40.0	250	500	375	5.92	5	0.0	3
223A	REESE	85	0.20	86	5	3.4	3	7	0.49	0	1	0.5	400	900	650	0.40	5	0.3	3
224A	REESE	85	0.20	86	5	3.4	3	7	0.32	0	1	0.5	400	900	650	0.40	5	0.2	3
225A	REESE	85	0.20	86	5	3.4	3	7	0.32	0	1	0.5	400	900	650	0.40	5	0.2	3
226A	REESE	45	0.20	86	5	3.4	3	7	0.24	0	1	0.5	400	900	650	0.40	5	0.1	3
226A	OZAMIS	40	0.20	86	5	3.4	3	7	0.20	0	1	0.5	400	900	650	0.40	5	0.1	3
227A	REESE	50	0.20	86	5	3.4	3	7	0.49	0	1	0.5	400	900	650	0.40	5	0.3	3
227A	PLAYAS	35	0.20	56	5	2.2	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
228F	RIDDLERANCH	85	0.20	0	2	0.0	3	20	0.17	30	50	40.0	250	500	375	5.92	2	10.1	1
229G	RIDDLERANCH	35	0.20	0	2	0.0	3	20	0.17	30	70	50.0	250	500	375	6.62	2	11.3	1
229G	RIDDLERANCH	30	0.20	0	2	0.0	3	20	0.17	30	70	50.0	250	500	375	6.62	2	11.3	1
229G	ROCK OUTCROP	20	0.20	0	5	0.0	3	20	0.00	30	70	50.0	250	500	375	6.62	5	0.0	3
230A	RIVERWASH	85	0.20	0	5	0.0	3	7	0.00	0	2	1.0	400	900	650	0.64	5	0.0	3
231G	ROCK OUTCROP	50	0.20	0	5	0.0	3	20	0.00	30	70	50.0	250	500	375	6.62	5	0.0	3
231G	FELCHER	35	0.20	0	2	0.0	3	20	0.10	30	70	50.0	250	500	375	6.62	2	6.6	3
232G	ROCK OUTCROP	45	0.20	0	5	0.0	3	31	0.00	50	75	62.5	250	500	375	7.26	5	0.0	3
232G	RUBBLE LAND	40	0.20	0	5	0.0	3	31	0.00	50	75	62.5	250	500	375	7.26	5	0.0	3
233G	ROCK OUTCROP	50	0.20	0	5	0.0	3	63	0.00	10	80	45.0	250	500	375	6.29	5	0.0	3
233G	XEROLLS	40	0.20	0	3	0.0	3	63	0.10	10	80	45.0	250	500	375	6.29	3	13.2	1
234F	ROCK OUTCROP	55	0.20	0	5	0.0	3	26	0.00	20	50	35.0	250	500	375	5.50	5	0.0	3
234F	XEROLLS	30	0.20	0	3	0.0	3	26	0.10	20	35	27.5	250	500	375	4.77	3	4.1	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
235E	ROGGER	85	0.20	56	3	3.7	3	70	0.17	15	40	27.5	250	500	375	4.77	3	18.9	1
235G	ROGGER	85	0.20	56	3	3.7	3	70	0.17	40	60	50.0	250	500	375	6.62	3	26.3	1
236G	ROGGER	55	0.20	56	3	3.7	3	46	0.17	40	60	50.0	250	500	375	6.62	3	17.3	1
236G	BULLUMP	30	0.20	0	5	0.0	3	46	0.10	40	60	50.0	250	500	375	6.62	5	6.1	3
237E	ROGGER	60	0.20	56	3	3.7	3	70	0.17	15	40	27.5	250	500	375	4.77	3	18.9	1
237E	POLANDER	30	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
238E	ROYST	50	0.20	0	2	0.0	3	50	0.17	2	30	16.0	250	500	375	3.36	2	14.3	1
238E	NUSS	35	0.20	38	1	7.6	3	50	0.17	2	30	16.0	250	500	375	3.36	1	28.5	1
239F	ROYST	35	0.20	0	2	0.0	3	50	0.17	30	50	40.0	250	500	375	5.92	2	25.2	1
239F	NUSS	30	0.20	38	1	7.6	3	50	0.17	30	50	40.0	250	500	375	5.92	1	50.3	1
239F	ROCK OUTCROP	20	0.20	0	5	0.0	3	50	0.00	30	50	40.0	250	500	375	5.92	5	0.0	3
240F	ROYST	35	0.20	0	2	0.0	3	50	0.17	30	50	40.0	250	500	375	5.92	2	25.2	1
240F	NUSS	30	0.20	38	1	7.6	3	50	0.17	30	50	40.0	250	500	375	5.92	1	50.3	1
240F	ROCK OUTCROP	20	0.20	0	5	0.0	3	50	0.00	30	50	40.0	250	500	375	5.92	5	0.0	3
241G	RUBBLE LAND	45	0.20	0	5	0.0	3	46	0.00	30	70	50.0	250	500	375	6.62	5	0.0	3
241G	FITZWATER	25	0.20	0	5	0.0	3	46	0.10	30	70	50.0	250	500	375	6.62	5	6.1	3
241G	FITZWATER	20	0.20	0	5	0.0	3	46	0.10	30	70	50.0	250	500	375	6.62	5	6.1	3
242C	RUTAB	85	0.20	56	5	2.2	3	20	0.15	2	15	8.5	400	600	500	2.52	5	1.5	3
243B	SALISBURY	85	0.20	48	2	4.8	3	46	0.37	0	5	2.5	400	900	650	1.22	2	10.4	1
243C	SALISBURY	85	0.20	48	2	4.8	3	46	0.37	5	15	10.0	400	600	500	2.82	2	24.0	1
244D	SHERVAL	85	0.20	0	5	0.0	3	70	0.17	5	20	12.5	400	600	500	3.28	5	7.8	3
245C	SIMON	50	0.20	56	5	2.2	3	20	0.43	2	15	8.5	400	600	500	2.52	5	4.3	3
245C	ANAWALT	35	0.20	48	1	9.6	1	20	0.28	2	15	8.5	400	600	500	2.52	1	14.1	1
246A	SPANGENBURG	45	0.20	86	5	3.4	3	7	0.43	0	2	1.0	400	900	650	0.64	5	0.4	3
246A	SPANGENBURG	40	0.20	86	5	3.4	3	7	0.43	0	2	1.0	400	900	650	0.64	5	0.4	3
247A	SPANGENBURG	35	0.20	86	5	3.4	3	7	0.43	0	2	1.0	400	900	650	0.64	5	0.4	3
247A	SPANGENBURG	30	0.20	86	5	3.4	3	7	0.43	0	2	1.0	400	900	650	0.64	5	0.4	3
247A	BERDUGO	20	0.20	86	5	3.4	3	7	0.32	0	2	1.0	400	900	650	0.64	5	0.3	3
248A	SPANGENBURG	50	0.20	86	5	3.4	3	7	0.43	0	1	0.5	400	900	650	0.40	5	0.2	3
248A	SWALESILVER	35	0.20	86	5	3.4	3	7	0.37	0	1	0.5	400	900	650	0.40	5	0.2	3
249A	STOCKDRIVE	85	0.20	86	3	5.7	3	46	0.37	0	1	0.5	400	900	650	0.40	3	2.3	3
250A	SWALESILVER	85	0.20	86	5	3.4	3	7	0.37	0	2	1.0	400	900	650	0.64	5	0.3	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
251A	TANDY	85	0.20	134	5	5.4	3	36	0.20	0	1	0.5	400	900	650	0.40	5	0.6	3
252A	THUNDEREGG	85	0.20	86	3	5.7	3	46	0.37	0	1	0.5	400	900	650	0.40	3	2.3	3
253A	TULANA	85	0.20	56	5	2.2	3	20	0.32	0	1	0.5	400	900	650	0.40	5	0.5	3
254A	TURPIN	55	0.20	56	5	2.2	3	7	0.32	0	5	2.5	400	900	650	1.22	5	0.5	3
254A	OZAMIS	30	0.20	86	5	3.4	3	7	0.20	0	1	0.5	400	900	650	0.40	5	0.1	3
255A	TURPIN	45	0.20	56	5	2.2	3	7	0.32	1	8	4.5	400	900	650	1.84	5	0.8	3
255A	REESE	30	0.20	86	5	3.4	3	7	0.49	0	1	0.5	400	900	650	0.40	5	0.3	3
255A	REESE	15	0.20	86	5	3.4	3	7	0.32	0	1	0.5	400	900	650	0.40	5	0.2	3
256C	TWELVEMILE	85	0.20	56	5	2.2	3	70	0.10	0	15	7.5	400	600	500	2.31	5	3.2	3
257E	TWELVEMILE	85	0.20	56	5	2.2	3	70	0.10	15	40	27.5	250	500	375	4.77	5	6.7	3
257G	TWELVEMILE	85	0.20	56	5	2.2	3	70	0.10	40	60	50.0	250	500	375	6.62	5	9.3	1
258E	TWELVEMILE	85	0.20	56	5	2.2	3	70	0.10	15	40	27.5	250	500	375	4.77	5	6.7	3
258G	TWELVEMILE	85	0.20	56	5	2.2	3	70	0.10	40	60	50.0	250	500	375	6.62	5	9.3	1
259E	VITALE	65	0.20	48	2	4.8	3	46	0.24	5	15	10.0	400	600	500	2.82	2	15.5	1
259E	BULLUMP	20	0.20	0	5	0.0	3	46	0.10	15	30	22.5	250	500	375	4.20	5	3.9	3
260A	WELCH	85	0.20	0	5	0.0	3	31	0.32	0	1	0.5	400	900	650	0.40	5	0.8	3
261A	WELCH	60	0.20	0	5	0.0	3	36	0.32	0	2	1.0	400	900	650	0.64	5	1.5	3
261A	DEGARMO	30	0.20	48	3	3.2	3	36	0.37	0	2	1.0	400	900	650	0.64	3	2.9	3
262E	WESTBUTTE	85	0.20	0	2	0.0	3	36	0.10	5	30	17.5	250	500	375	3.56	2	6.4	3
263F	WESTBUTTE	50	0.20	0	2	0.0	3	36	0.10	30	50	40.0	250	500	375	5.92	2	10.7	1
263F	NINEMILE	40	0.20	0	1	0.0	3	36	0.15	30	50	40.0	250	500	375	5.92	1	32.0	1
264G	WESTBUTTE	65	0.20	0	2	0.0	3	36	0.10	30	70	50.0	250	500	375	6.62	2	11.9	1
264G	ROCK OUTCROP	20	0.20	0	5	0.0	3	36	0.00	30	70	50.0	250	500	375	6.62	5	0.0	3
265C	WESTSIDE	50	0.20	38	3	2.5	3	13	0.17	2	15	8.5	400	600	500	2.52	3	1.9	3
265C	WESTSIDE	50	0.20	38	3	2.5	3	13	0.17	2	15	8.5	400	600	500	2.52	3	1.9	3
266E	WILDHILL	85	0.20	38	2	3.8	3	7	0.17	2	30	16.0	250	500	375	3.36	2	2.0	3
267F	WILDHILL	85	0.20	38	2	3.8	3	7	0.17	30	50	40.0	250	500	375	5.92	2	3.5	3
268C	WINTERIM	85	0.20	0	3	0.0	3	70	0.20	0	15	7.5	400	600	500	2.31	3	10.8	1
269E	WINTERIM	85	0.20	0	3	0.0	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
269G	WINTERIM	85	0.20	0	3	0.0	3	70	0.20	40	60	50.0	250	500	375	6.62	3	30.9	1
270E	WINTERIM	85	0.20	0	3	0.0	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
270G	WINTERIM	85	0.20	0	3	0.0	3	70	0.20	40	60	50.0	250	500	375	6.62	3	30.9	1

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.

HIGHLY ERODIBLE LAND LIST - LAKE COUNTY, OREGON, SOUTHERN PART

January 2002

HEL Class:
1 = Highly Erodible
3 = Non Highly Erodible

MAP UNIT SYMBOL	COMPONENT NAME	COMP. PCT.	WIND C FACTOR	WEI (I)	T	WIND EI (IC/T)	WIND HEL CLASS	USLE R FACTOR	Kw	SLOPE LOW (%)	SLOPE HIGH (%)	SLOPE AVG. (%)	SLOPE LENGTH MIN (FT.)	SLOPE LENGTH MAX (FT.)	SLOPE LENGTH AVG. (FT.)	AVG. LS	T	WATER EI (RKLS/T)	WATER HEL CLASS
271E	WINTERIM	85	0.20	0	3	0.0	3	63	0.20	2	30	16.0	250	500	375	3.36	3	14.1	1
272C	WINTERIM	60	0.20	0	3	0.0	3	60	0.20	0	15	7.5	400	600	500	2.31	3	9.2	1
272C	BOOTH	30	0.20	0	2	0.0	3	60	0.15	0	15	7.5	400	600	500	2.31	2	10.4	1
273E	WINTERIM	50	0.20	0	3	0.0	3	60	0.20	15	40	27.5	250	500	375	4.77	3	19.1	1
273E	BOOTH	35	0.20	0	2	0.0	3	60	0.15	15	40	27.5	250	500	375	4.77	2	21.5	1
274F	WINTERIM	55	0.20	0	3	0.0	3	63	0.20	30	50	40.0	250	500	375	5.92	3	24.9	1
274F	WINTERIM	30	0.20	0	3	0.0	3	63	0.20	30	50	40.0	250	500	375	5.92	3	24.9	1
275E	WOODCHOPPER	60	0.20	38	5	1.5	3	70	0.20	15	40	27.5	250	500	375	4.77	5	13.4	1
275E	POLANDER	30	0.20	86	3	5.7	3	70	0.20	15	40	27.5	250	500	375	4.77	3	22.3	1
276C	WOODCHOPPER	60	0.20	38	5	1.5	3	70	0.20	0	15	7.5	400	600	500	2.31	5	6.5	3
276C	ROGGER	30	0.20	56	3	3.7	3	70	0.17	0	15	7.5	400	600	500	2.31	3	9.2	1
277E	WOODCHOPPER	60	0.20	38	5	1.5	3	70	0.20	15	40	27.5	250	500	375	4.77	5	13.4	1
277E	ROGGER	30	0.20	56	3	3.7	3	70	0.17	15	40	27.5	250	500	375	4.77	3	18.9	1
278G	XEROLLS	60	0.20	0	3	0.0	3	70	0.10	40	60	50.0	250	500	375	6.62	3	15.4	1
278G	ROCK OUTCROP	30	0.20	0	5	0.0	3	70	0.00	40	60	50.0	250	500	375	6.62	5	0.0	3
279G	XEROLLS	60	0.20	0	3	0.0	3	70	0.10	40	60	50.0	250	500	375	6.62	3	15.4	1
279G	ROCK OUTCROP	30	0.20	0	5	0.0	3	70	0.00	40	60	50.0	250	500	375	6.62	5	0.0	3
280G	XEROLLS	45	0.20	0	3	0.0	3	20	0.10	30	75	52.5	250	500	375	6.77	3	4.5	3
280G	ROCK OUTCROP	40	0.20	0	5	0.0	3	20	0.00	30	75	52.5	250	500	375	6.77	5	0.0	3
281G	XEROLLS	45	0.20	0	3	0.0	3	70	0.10	30	80	55.0	250	500	375	6.91	3	16.1	1
281G	ROCK OUTCROP	20	0.20	0	5	0.0	3	70	0.00	30	80	55.0	250	500	375	6.91	5	0.0	3
281G	POLANDER	20	0.20	86	3	5.7	3	70	0.20	30	60	45.0	250	500	375	6.29	3	29.4	1
282B	ZORRAVISTA	85	0.20	250	5	10.0	1	7	0.17	0	5	2.5	400	900	650	1.22	5	0.3	3
283B	ZORRAVISTA	50	0.20	250	5	10.0	1	7	0.17	2	8	5.0	400	900	650	1.99	5	0.5	3
283B	HINTON	35	0.20	86	5	3.4	3	7	0.15	0	5	2.5	400	900	650	1.22	5	0.3	3

This Highly Erodible Land list is a revision of a list prepared in May 1989, before the final correlation was completed. The I, Kw, and T factors are from the NASIS soil database as of January 2002.