

**330 - Contour Farming Implementation Requirements**

**Producer:**  
**Farm Name:**  
**Planner:**

**Project or Contract:**  
**Tract Number(s):**  
**Field Number(s):**

**Practice Location Map**

*(Refer to Conservation Plan Map for a detailed aerial view of where practice is to be installed on farm/site, showing all major components, stationing, relative location to any landmarks, and survey benchmarks)*



**Index**

- Cover Sheet/  
Drawings
- Specifications
- Operation &  
Maintenance

Utility Safety /  
One-Call System  
Information

**On the attached conservation plan map, delineate the contour baseline(s), correction areas, and stable outlets for concentrated flow.**

**Description of work:**

**NRCS Review Only**

<b>Designed By:</b>	<b>Date:</b>
<b>Checked By:</b>	<b>Date:</b>
<b>Approved By:</b>	<b>Date:</b>

## 330 - Contour Farming Implementation Requirements

### The Practice Purpose(s):

Reduce sheet and rill erosion.

Reduce transport of sediment, other solids and the contaminants attached to them.

Increase water infiltration

Site Planning Conditions for the Dominant Critical Soil Map Unit/Component			
Planning Map Unit/Component	Planning Slope %	Planning Length of Slope (ft)	Percent Absolute Contour Row Grade Planned

Minimum and Maximum Contour Row Grades	
<p><b>Minimum Contour Row Grade (Percent)</b></p> <p>The crop rows shall have sufficient grade to ensure that runoff water does not pond and cause unacceptable crop damage.</p>	<p><b>Maximum Contour Row Grade (Percent)</b></p> <p>The maximum row grade shall not exceed: (a) one-half of the up-and-down hill slope percent used for conservation planning, or (b) 10 percent, whichever is less. Up to a 25-percent deviation from the design row grade is permitted within 150 feet of a stable outlet.</p>

Minimum Tillage Ridge Heights and In-Row Plant Spacing		
Row spacing greater than 10 inches	Row spacing 10 inches or less	No Tillage Planting
<p>The minimum ridge height shall be 2 inches during the period of the rotation that is most vulnerable to sheet and rill erosion</p>	<p>The minimum ridge height shall be one inch for close-grown crops, such as small grains. Plant height shall be at least 6 inches high and the spacing between plants within the row shall not be greater than 2 inches during the time most vulnerable to sheet and rill erosion.</p>	<p>No minimum ridge height</p>

**Corrections Areas:** Where field operations begin to converge between two non-parallel contour baselines, establish a correction area that either is permanently in sod, established to an annual close-grown crop.

## 330 - Contour Farming Implementation Requirements

### OPERATION AND MAINTENANCE

Perform all tillage and planting operations parallel to contour baselines or terraces, diversions, or contour buffer strip boundaries where these practices are used, provided the applicable row grade criteria are met.

Where terraces, diversions, or contour buffer strips are not present, maintain contour markers on grades that, when followed during establishment of each crop, will maintain crop rows at designed grades. Contour markers may be field boundaries, a crop row left untilled near or on an original contour baseline or other readily identifiable, continuous, lasting marker. All tillage and planting operations shall be parallel to the established marker. If a marker is lost, re-establish a contour baseline within the applicable criteria set forth by this standard prior to seedbed preparation for the next crop.

Farming operations should begin on the contour baselines and precede both up and down the slope in a parallel pattern until patterns meet. Where field operations begin to converge between two non-parallel contour baselines, establish a correction area that either is permanently in sod, established to an annual close-grown crop.

Where contour row curvature becomes too sharp to keep machinery aligned with rows during field operations, establish sod turn strips on sharp ridge points or other odd areas as needed.

#### **Client's Acknowledgement (To be completed after practice I&E and design have been approved.)**

By signing below, I acknowledge that I:

- have reviewed this Jobsheet and have an understanding of its contents and requirements;
- will make no changes to this Jobsheet, without prior concurrence of NRCS;
- will install, operate, and maintain this practice in accordance with this Jobsheet; and
- will obtain all necessary permits and/or rights, comply with all ordinances and laws, and notify all utilities pertaining to the installation, operation, and maintenance of the practice.

---

Print Name

---

Signature

---

Date

